Learning latent causal graphs via mixture oracles

Abstract

We study the problem of reconstructing a causal graphical model from data in the presence of latent variables. The main problem of interest is recovering the causal structure over the latent variables while allowing for general, potentially nonlinear dependence between the variables. In many practical problems, the dependence between raw observations (e.g. pixels in an image) is much less relevant than the dependence between certain high-level, latent features (e.g. concepts or objects), and this is the setting of interest. We provide conditions under which both the latent representations and the underlying latent causal model are identifiable by a reduction to a mixture oracle. The proof is constructive, and leads to several algorithms for explicitly reconstructing the full graphical model. We discuss efficient algorithms and provide experiments illustrating the algorithms in practice.

1 Introduction

Understanding causal relationships between objects and/or concepts is a core component of human reasoning, and by extension, a core component of artificial intelligence [33, 40]. Causal relationships are robust to perturbations, encode invariances in a system, and enable agents to reason effectively about the effects of their actions in an environment. Broadly speaking, the problem of inferring causal relationships can be broken down into two main steps [48]: 1) The extraction of high-level causal features from raw data, and 2) The inference of causal relationships between these high-level features. From here, one may consider estimating the magnitude of causal effects, the effect of interventions, reasoning about counterfactuals, etc.

Causal graphical models [40, 41] provide a natural framework for these problems, and have long been used to model causal systems' hidden variables [20–22, 45]. For example, graphical models give convenient semantics for modeling latent and selection variables [17, 56], and can be used for structure learning in the presence of latent variables [3, 27, 52]. It is well-known that in general, without additional assumptions, a causal graphical model given by a directed acyclic graph (DAG) is not identifiable in the presence of latent variables [e.g., 40, 55]. This is a generic property of nonparametric structural models: Without assumptions, identifiability is impossible, however, given enough structure, identifiability can be rescued. Examples of this phenomenon include linearity [3, 5, 14, 23, 58], independence [1, 9, 58], rank [14, 23], sparsity [5], and graphical constraints [3, 4]. In all of these approaches, some type of parametric structure (e.g. linear or logistic) is imposed on the model.

In this paper, we consider a general setting for this problem with *discrete* latent variables, while allowing otherwise arbitrary (possibly nonlinear) dependencies from the latent to the observed variables. The latent causal graph between the latent vaiables is also allowed to be arbitrary: No assumptions are placed on the structure of this DAG. We do not assume that the number of hidden variables, their state spaces, or their relationships are known; in fact, we provide explicit conditions under which all of this can be recovered uniquely. To accomplish this, we highlight a crucial reduction between the problem of learning a DAG model over these variables—given access only

to the observed data—and discrete deconvolution problems, i.e. learning the parameters of a finite mixture model. This observation leads to new identifiability conditions and algorithms for learning causal models with latent structure.

Overview Our starting point is a simple reduction of the graphical model recovery problem to three modular subproblems:

1. The bipartite graph Γ between hidden and observed nodes,

2. The latent distribution $\mathbb{P}(H)$ over the hidden variables H, and

3. A directed acyclic graph (DAG) Λ over the latent distribution.

From here, the crucial observation is to reduce the recovery problems for Γ and $\mathbb{P}(H)$ to the problem of learning a finite mixture over the observed data. The latter is a well-studied problem with many practical algorithms and theoretical guarantees. We do not require parametric assumptions on this mixture, which allows for very general dependencies between the observed and hidden variables. From this mixture model, we extract what is needed to learn the full graph structure.

This perspective leads to a systematic, modular approach for learning the latent causal graph via mixture oracles (see Section 2 for definitions). Ultimately, the application of these ideas requires a practical implementation of this mixture oracle, which is discussed in Section 6.

Contributions More precisely, we make the following contributions:

1. (Section 3) We provide general conditions under which the latent causal model G is identifiable (Theorem 3.2). Surprisingly, these conditions mostly amount to nondegeneracy conditions on the joint distribution. As we show, without these assumptions identifiability breaks down and as a result reconstruction becomes impossible.

2. (Section 4) We carefully analyze the problem of reconstructing Γ under progressively weaker assumptions: First, we derive a brute-force algorithm that identifies Γ in a general setting (Theorem 4.2), and then under a linear independence condition we derive a polynomial-time algorithm based on tensor decomposition and Jennrich's algorithm (Theorem 4.8).

3. (Section 5) Building on top of the previous step, where we learn the bipartite graph and sizes of the domains of latent variables, we develop an efficient algorithm for learning the latent distribution $\mathbb{P}(H)$ from observed data (Theorem 5.4).

4. (Section 6-7) We implement these algorithms as part of an end-to-end pipeline for learning the full causal graph and illustrate its performance on simulated data.

A prevailing theme throughout is the fact that the hidden variables leave a recognizable "signature" in the observed data through the marginal mixture models induced over subsets of observed variables. By cleverly exploiting these signatures, the number of hidden variables, their states, and their relationships can be recovered exactly.

Previous work Graphical models with latent variables have been extensively studied in the literature; as such we focus only on the most closely related work on causal graphical models here. Most of the prior work in this area has focused on linear models [3, 23, 52, 58] or known structure [19, 31, 49]. When the structure is not known *a priori*, we find ourselves in the realm of *structure learning*, which is our focus. Less is known regarding structure learning for nonlinear models with latent variables, although there has been recent progress based on nonlinear ICA [29, 38]. For example, Yang et al. [59] proposed CausalVAE, which assumes a linear structural equation model and knowledge of the concept labels for the latent variables, in order to leverage the iVAE model from [29]. By contrast, our results make no linearity assumptions and do not require these additional labels. It is also worth noting recent progress on learning discrete Boltzmann machines [10, 11], which can be interpreted as an Ising model with a bipartite structure and a single hidden layer—in particular, there is no hidden causal structure. Nevertheless, this line of work shows that learning Boltzmann machines is computationally hard in a precise sense.

Along these lines, a prevailing theme in the causal inference literature has been negative results asserting that in the presence of latent variables, causal inference is impossible [25, 47]. Our results do not contradict this important line of work, and instead adopts a more optimistic tone: We show that

(a) A single hidden state.   (b) Two independent hidden states.   (c) Three dependent hidden states.

Figure 1: Illustration of the basic model. Note that there are no edges between observed variables or edges oriented from observed to hidden. (a) A latent variable model with a single hidden state; i.e. a mixture model. (b)-(c) Two examples of latent variable models with more complicated hidden structure.

under reasonable assumptions—essentially that the latent variables are discrete and well-separated—identifiability and exact recovery of latent causal relationships is indeed possible. This optimistic approach is implicit in recent progress on visual relationship detection [39], causal feature learning [13, 36], and interaction modeling [30, 34]. In this spirit, our work provides theoretical grounding for some of these ideas.

Mixture models and clustering While our theoretical results in Sections 3-5 assume access to a mixture oracle (see Definition 2.4), in Section 6 we discuss how this oracle can be implemented in practice. To provide context for these results, we briefly mention related work on learning mixture models from data. Mixture models can be learned under a variety of parametric and nonparametric assumptions. Although much is known about parametric models [e.g. 35], of more interest to us are nonparametric models in which the mixture components are allowed to be flexible, such as mixtures of product distributions [24, 26], grouped observations [46, 57] and general nonparametric mixtures [6, 50]. In each of these cases, a mixture oracle can be implemented without parametric assumptions. In practice, we use clustering algorithms such as K-means or hierarchical clustering to implement this oracle. We note also that the specific problem of consistently estimating the order of a mixture model, which will be of particular importance in the sequel, has been the subject of intense scrutiny in the statistics literature [e.g. 15, 18, 32, 37].

Broader impacts and societal impact Latent variable models have numerous practical applications. Many of these applications positively address important social problems, however, these models can certainly be applied nefariously. For example, if the latent variables represent private, protected information, our results imply that this hidden private data can be leaked into publicly released data, which is obviously undesirable. Understanding how to infer unprotected data while safeguarding protected data is an important problem, and our results shed light on when this is and isn't possible.

2 Background

Let $G = (V, E)$ be a DAG with $V = (X, H)$, where $X \in \mathbb{R}^n$ denotes the observed part and $H \in \Omega := \Omega_1 \times \cdots \times \Omega_m$ denotes the hidden, or latent, part. Throughout this paper, we assume that each Ω_i is a discrete space with $|\Omega_i| \geq 2$. We assume further that there are no edges between observed variables and no edges from observed to hidden variables, and that the distribution of V satisfies the Markov property with respect to G (see the supplement for definitions). Under these assumptions, G decomposes as the union of two subgraphs $G = \Gamma \cup \Lambda$, where Γ is a directed, bipartite graph of edges pointing from H to X, and Λ is a DAG over the latent variables H. Similar assumptions have appeared in previous work [3, 58], and although nontrivial, they encapsulate our keen interest in reconstructing the structure amongst the latent variables, and captures relevant applications where the relationships between raw observations is less relevant than so-called "causal features" [12, 13]. See Figure 1 for examples.

Throughout this paper, we use standard notation such as $\mathrm{pa}(j)$ for parents, $\mathrm{ch}(j)$ for children, and $\mathrm{ne}(j)$ for neighbors. Given a subset $V' \subset V$, $\mathrm{pa}(V') := \cup_{j \in V'} \mathrm{pa}(j)$ and given a subgraph $G' \subset G$,

126 $\text{pa}_{G'}(V') := \text{pa}(V') \cap G'$, with similar notation for children and neighbors. We let $A \in \{0,1\}^{|X| \times |H|}$
127 denote the adjacency matrix of Γ and denote its columns by $a_j \in \{0,1\}^{|X|}$.

2.1 Assumptions

129 It is well-known that without additional assumptions, the latent variables H cannot be identified from
130 X, let alone the DAG Λ. For example, we can always replace a pair of distinct hidden variables
131 H_i and H_j with a single hidden variable H_0 that takes values in $\Omega_i \times \Omega_j$. Similarly, a single latent
132 variable can be split into two or more latent variables. In order to avoid this type of degeneracy, we
133 make the following assumptions:

134 **Assumption 2.1** (No twins)**.** *For any hidden variables $H_i \neq H_j$ we have $\text{ne}_\Gamma(H_i) \neq \text{ne}_\Gamma(H_j)$.*

135 **Assumption 2.2** (Minimality)**.** *There is no DAG G' such that:*

136   *1. $\mathbb{P}(V)$ is Markov with respect to G';*

137   *2. G is obtained from G' by merging a pair of hidden variables;*

138   *3. G' satisfies Assumption 2.1.*

139 These assumptions are necessary for the recovery of Λ in the sense that, without these assumptions,
140 latent variables can be created or destroyed without changing the observed distribution $\mathbb{P}(X)$. Finally,
141 we make a mild assumption on the probabilities, in order to avoid degenerate cases where certain
142 configurations of the latent variables have zero probability:

143 **Assumption 2.3** (Nondegeneracy)**.** *The distribution over $V = (X, H)$ satisfies:*

144   *(a) $\mathbb{P}(H = h) > 0$ for all $h \in \Omega_1 \times \ldots \times \Omega_k$.*

145   *(b) For all $S \subset X$ and $a \neq b$, $\mathbb{P}(S | \text{pa}(S) = a) \neq \mathbb{P}(S | \text{pa}(S) = b)$, where a and b are distinct*
146   *configurations of $\text{pa}(S)$.*

147 Without this nondegeneracy condition, H cannot be identified; see the supplement for details.

2.2 Mixture oracles

149 Let $S \subset X$ be a subset of the observed variables. We can always write the marginal distribution $\mathbb{P}(S)$
150 as

$$\mathbb{P}(S) = \sum_{h \in \Omega} \mathbb{P}(H = h)\mathbb{P}(S \,|\, H = h). \tag{1}$$

151 When $S = X$, this can be interpreted as a mixture model with $K := |\Omega|$ components. When $S \subsetneq X$,
152 however, multiple components can "collapse" onto the same component, resulting in a mixture with
153 fewer than K components. Let $k(S)$ denote this number, so that we may define a discrete random
154 variable Z with $k(S)$ states such that for all $j \in [k(S)]$, we have

$$\mathbb{P}(S) = \sum_{j=1}^{k(S)} \underbrace{\mathbb{P}(Z = j)}_{:=\pi(S,j)} \underbrace{\mathbb{P}(S \,|\, Z = j)}_{:=C(S,j)} = \sum_{j=1}^{k(S)} \pi(S,j) C(S,j). \tag{2}$$

155 Then $\pi(S, j)$ is the weight of the jth mixture component over S, and $C(S, j)$ is the corresponding
156 jth component. It turns out that these probabilities precisely encode the conditional independence
157 structure of H. To make this formal, we define the following oracle:

158 **Definition 2.4.** *A mixture oracle is an oracle that takes $S \subset X$ as input and returns the number of*
159 *components $k(S)$ as well as the weights $\pi(S, j)$ and components $C(S, j)$ for each $j \in [k(S)]$. This*
160 *oracle will be denoted by* MixOracle(S).

161 Although our theoretical results are couched in the language of this oracle, we provide practical
162 implementation details in Section 6 and experiments to validate our approach in Section 7.

163 A sufficient condition for the existence of a mixture oracle is that the mixture model over X is
164 identifiable. This is because identifiability implies that the number of components K, the weights

$\mathbb{P}(Z = j)$, and the mixture components $\mathbb{P}(X \mid Z = j)$ are determined by $\mathbb{P}(X)$. The marginal weights $\pi(S, j)$ and components $C(S, j)$ can then be recovered by simply projecting the full mixture over X onto S.

Remark 2.5. *In fact, we do not need the full power of* MixOracle. *For our algorithms it is sufficient to have access to $k(S)$ for a sufficiently large family of $S \subset X$, the list of weights $\pi(X, j)$, and a map that relates components in the full mixture over X to the components in the marginal mixtures over each variable X_i (see Section 5 for details).*

Before concluding this section, we note an important consequence of Assumption 2.3 that will be used in the sequel:

Observation 2.6. *Under Assumption 2.3, for any $S \subseteq X$*

$$k(S) = \prod_{H_i \in \mathrm{pa}(S)} \dim(H_i) =: \dim(\mathrm{pa}(S)).$$

Proof. By the Markov property, S is independent of $H \setminus \mathrm{pa}(S)$. There are $\dim(\mathrm{pa}(S))$ possible assignments to the hidden variables in $\mathrm{pa}(S)$ and by Assumption 2.3, distinct assignments to the hidden variables induce distinct components in the marginal distribution $P(S)$. Hence, by definition, $k(S) = \dim(\mathrm{pa}(S))$. $\qquad\square$

3 Recovery of the latent causal graph

We first consider the oracle setting in which we have access to $\mathsf{MixOracle}(S)$.

Observe that the problem of learning G can be reduced to learning $(\Gamma, \mathbb{P}(H))$: Since we can decompose G into a bipartite subgraph Γ and a latent subgraph Λ, it suffices to learn these two components separately. We then further reduce the problem of learning Λ to learning the latent distribution $\mathbb{P}(H)$. First, we will show how to reconstruct Γ from $\mathsf{MixOracle}(S)$. Then, we will show how to learn the latent distribution $\mathbb{P}(H)$ from $\mathsf{MixOracle}(S)$.

Thus, the problem of learning G is reduced to the mixture oracle:

$$G \to (\Gamma, \mathbb{P}(H)) \to \mathsf{MixOracle}(S).$$

In the sequel, we focus our attention on recovering $(\Gamma, \mathbb{P}(H))$. In order to recover $\mathbb{P}(H)$, we will require the following assumption:

Assumption 3.1 (Subset condition). *We say that the bipartite graph Γ satisfies the subset condition (SSC) if for any pair of distinct hidden rariables H_i, H_j the set $\mathrm{ne}_\Gamma(H_i)$ is not a subset of $\mathrm{ne}_\Gamma(H_j)$.*

This assumption is weaker than the common "anchor words" assumption from the topic modeling literature. The latter assumption says that every topic has a word that is unique to this topic, and it is commonly assumed for efficient recovery of latent structure [7, 8].

Under this assumption, we have the following key result:

Theorem 3.2. *Under Assumptions 2.1, 2.2, 2.3, and 3.1, $(\Gamma, \mathbb{P}(H))$ can be reconstructed from $\mathbb{P}(X)$ and $\mathsf{MixOracle}(S)$. Furthermore, if additionally the columns of the bipartite adjacency matrix A are linearly independent, there is an efficient algorithm for this reconstruction.*

The proof is constructive and leads to an efficient algorithm as alluded to in the previous theorem. An overview of the main ideas behind the proof of this result are presented in Sections 4 and 5; the complete proof of this theorem can be found in the supplement.

Theorem 3.2 guarantees recovery of the latent distribution $\mathbb{P}(H)$. Once we know $\mathbb{P}(H)$, identifying Λ from $\mathbb{P}(H)$ is a well-studied problem with many solutions [40, 55]. For simplicity, it suffices to assume that $\mathbb{P}(H)$ is faithful to Λ, which implies that Λ can be learned up to Markov equivalence. This assumption is *not* necessary, and any number of alternative identifiability assumptions on $\mathbb{P}(H)$ can be plugged in place of faithfulness, for example triangle faithfulness [54], independent noise [43, 51], post-nonlinearity [60], equality of variances [42], etc. More details on learning Λ from $\mathbb{P}(H)$ can be found in Section 6.

4 Learning the bipartite graph

In this section we outline the main ideas behind the recovery of Γ in Theorem 3.2. We begin by establishing conditions that ensure Γ is identifiable, and then proceed to consider efficient algorithms for its recovery.

4.1 Identifiability result

We study a slightly more general setup in which the identifiability of Γ depends on how much information we request from the MixOracle. Clearly, we want to rely on MixOracle as little as possible. As the proofs in the supplement indicate, the only information required for this step are the number of components. Neither the weights nor the components are needed.

Definition 4.1. *We say that Γ is t-recoverable if Γ can be uniquely recovered from X and the sequence $(\mathsf{MixOracle}(S) \mid |S| \leq t)$.*

Theorem 4.2. *Let Γ be the causal bipartite graph between X and H.*

    (a) Assume that $\mathrm{ne}_\Gamma(H_i) \neq \mathrm{ne}_\Gamma(H_j)$ for any $i \neq j$. Then Γ and $\dim(H_i)$ are n-recoverable.

    (b) Let $t \geq 3$. Assume that for every $S \subseteq H$ with $|S| \geq 2$ we have

$$\dim \mathrm{span}\{a_j \mid j \in S\} \geq \frac{2}{t}|S| + 1,$$

    then Γ and $\dim(H_i)$ are t-recoverable.

Note that Assumption 3.1 implies the assumption in Theorem 4.2(a). Finally, as in Section 2, we argue that in the absence of additional assumptions, this assumption is in fact necessary:

Observation 4.3. *If there is a pair of distinct variables $H_i, H_j \in H$ such that $\mathrm{ne}_\Gamma(H_1) = \mathrm{ne}_\Gamma(H_2)$, then Γ is not n-recoverable.*

4.2 Ideas behind the recovery

In Corollary 4.4 below, we recast Observation 2.6 as an additive identity. This transforms the problem of learning Γ into an instance of more general problem that is discussed in the appendix. The results of this section apply to this more general version.

Corollary 4.4. *Assume that Assumptions 2.3 hold. For $H_i \in H$ define $w(H_i) = \log(\dim(H_i))$. Then for every set $S \subseteq X$*

$$\log(k(S)) = \sum_{H_i \in \mathrm{pa}(S)} w(H_i). \tag{3}$$

In order to argue about the causal structure of the hidden variables we first need to identify the variables themselves. By Assumption 2.1, every hidden variable leaves a "signature" among the observed variables, which is the set $\mathrm{ne}_\Gamma(H_i)$ of observed variables it affects. In particular, note that $H_i \in \bigcap_{X_s \in \mathrm{ne}_\Gamma(H_i)} \mathrm{pa}(X_s)$ and if there is no H_j with $\mathrm{ne}_\Gamma(H_i) \subset \mathrm{ne}_\Gamma(H_j)$ then H_i is the unique element of the intersection. The lemma above allows us to extract information about the union of parent sets, and we wish to turn it into the information about intersections. This motivates the following definitions.

Definition 4.5. *Let Γ and w be as above. Define*

$$\mathrm{sne}_\Gamma(S) = \bigcap_{x \in S} \mathrm{ne}_\Gamma(x) \quad and \quad \mathrm{Wsne}_\Gamma(S) = \sum_{v \in \mathrm{sne}_\Gamma(S)} w(v) \tag{4}$$

Lemma 4.6. *For a set $S \subseteq X$ we have*

$$\mathrm{Wsne}_\Gamma(S) = \sum_{U \subseteq S, U \neq \emptyset} (-1)^{|U|+1} W_\Gamma(U), \quad where \quad W_\Gamma(S) = \sum_{v \in \mathrm{ne}_\Gamma(S)} w(v). \tag{5}$$

The proof of this lemma is a simple application of the Inclusion-Exclusion principle.

Remark 4.7. *The RHS of Eq. (5) only depends on W evaluated on subsets of S. Thus, in particular, if $|S| \leq t$ to compute $\mathrm{Wsne}(S)$ it is enough to know MixOracle on all sets of size $\leq t$.*

Finally, the values of the function Wsne_Γ can be organized into a tensor, and from here the problem of learning Γ can be cast as decomposition problem for this tensor. These proof details are spelled out in the supplement; in the next section we illustrate this procedure for the special case of 3-recovery.

4.3 Efficient 3-recovery

Under a simple additional assumption Γ can be recovered efficiently. We are primarily interested in the case $t = 3$. The main idea is to note that a rank-three tensor involving the columns of A can be written in terms of Wsne_Γ. We can then apply Jennrich's algorithm [28] to decompose the tensor and recover these columns, which yield Γ. To see this, let $I = (i_1, i_2, i_3) \subseteq X$ be a triple of indices, and note that

$$\sum_{j \in H} w(j)(a_j)_{i_1}(a_j)_{i_2}(a_j)_{i_3} = \Big(\sum_{j \in H} w(j) a_j \otimes a_j \otimes a_j \Big)_{(i_1, i_2, i_3)} = \mathrm{Wsne}_\Gamma(I). \tag{6}$$

Theorem 4.8. *Assume that the columns of A are linearly independent. Then Γ and $\dim(H_i)$, for all i, are 3-recoverable in $O(n^3)$ space and $O(n^4)$ time.*

Proof. It takes $O(n^3)$ space and $O(n^3)$ time to compute M_3 and then Jennrich's algorithm can decompose the tensor in $O(n^3)$ space and $O(n^4)$ time. $\qquad\square$

5   Learning the latent distribution

In this section we outline the main ideas behind the recovery of $\mathbb{P}(H)$ in Theorem 3.2.

Remark 5.1. *Since the variables H are not observed, $\mathsf{MixOracle}(S)$ only tells us the set*

$$\{(i, \pi(S, i), C(S, i)) \mid i \in [k(S)]\}.$$

But the correspondence $\Omega \ni h \leftrightarrow j \in [K := |\Omega|]$ between a possible tuple h of values of hidden variables and the corresponding mixture component is unknown.

Since the values of H are not observed, we may learn this correspondence only up to a relabelings of Ω_i. By definition, the input distribution has $K := |\Omega|$ mixture components over X and $k_i := k(X_i)$ mixture components over X_i. Fix any enumeration of these components by $[K]$ and $[k_i]$, respectively. To recover the correspondence $\Omega \ni h \leftrightarrow j \in [K]$, we will need access to the map

$$L : [K] \to [k_1] \times \cdots \times [k_n], \tag{7}$$

defined so that $[L(j)]_i$ equals to the index of the mixture component $C(X, j)$ (marginalized over X_i) in the marginal distribution over X_i. Crucially, this discussion establishes that L can be computed from a combination of $\mathsf{MixOracle}(X)$ and $\mathsf{MixOracle}(X_i)$ for each i.

The map L encodes partial information about the causal structure in G. Indeed, if $h_1, h_2 \in \Omega$ are a pair of states of hidden variables H that coincide on $\mathrm{pa}(X_i)$ for some $X_i \in X$, then by the Markov property the components that correspond to h_1 and h_2 should have the same marginal distribution over X_i.

Example 5.2. *Consider the DAG on Figure 2. We do not make any assumptions about the causal structure between hidden variables. This DAG has 3 hidden variables, and we assume that each of them takes values in set $\{0, 1\}$. Then by assumptions 2.3 every observed variable is a mixture of 4 components, while the distribution on X is a mixture of 8 components. Note that the anchor word assumption is violated here, while (SSC) assumption is satisfied. The map $L : [8] \to [4] \times [4] \times [4]$ for an example as in Fig. 2 has form*

$i:$	1	2	3	4	5	6	7	8
$L(i):$	$(2,4,3),$	$(4,3,4),$	$(4,4,2),$	$(3,2,4),$	$(2,3,1),$	$(1,1,3),$	$(3,1,2),$	$(1,2,1)$

Our goal is to find the correspondence between $h \in \Omega = \{0, 1\}^3$ and $i \in [8]$. (The projection on the third variable is not shown on Figure 2, so the third coordinate of L cannot be deduced from the plot.)

A bipartite graph Γ

Figure 2: Example of a latent DAG and corresponding mixture distribution

We now show that there is an algorithm that exactly recovers $\mathbb{P}(H)$ from the bipartite graph Γ, the map $L : [K] \to [k_1] \times \cdots \times [k_n]$, and the mixture weights (probabilities) $\{\pi(X, i) \mid i \in [K]\} = \{\mathbb{P}(Z = i) \mid i \in [K]\}$. Each of these inputs can be computed from MixOracle.

Definition 5.3. *Let J be an order-m tensor whose i-th mode is indexed by values of H_i, such that $J(h_1, h_2, \ldots, h_m) = \mathbb{P}(H = h)$. That is, J is the joint probability table of H.*

Theorem 5.4. *Suppose Assumptions 2.3 and 3.1 hold. Then the correspondence $\Omega \ni h \leftrightarrow C(X, i)$ and the tensor $J(h_1, h_2, \ldots, h_m) = \mathbb{P}(H = (h_1, h_2, \ldots, h_m))$ can be efficiently reconstructed from L, Γ and $\{\pi(X, i)\}_{i \in [K]}$.*

Observation 5.5. *If Assumption 3.1 is violated, then J cannot be reconstructed uniquely. Moreover, in this case G cannot be uniquely identified.*

6 Implementation details

The results in Section 3 assume access to the mixture oracle $\mathsf{MixOracle}(S)$. Of course, in practice, learning mixture models is a nontrivial problem. Fortunately, many algorithms exist for approximating this oracle: In our implementation, we used K-means. A naïve application of clustering algorithms, however, ignores the significant structure *between* different subsets of observed variables. Thus, we also enforce internal consistency amongst these computations, which makes estimation much more robust in practice. In the remainder of this section, we describe the details of these computations.

Estimating the number of marginal components   In order to estimate the number of components in a marginal distribution for a subset S of observed variables with $|S| \leq 3$, we use K-means combined with agglomerative clustering to merge nearby cluster centers, and then select the number of components that has the highest silhouette score. Done independently, this step ignores the structure of the global mixture, and is not robust. In order to make learning more robust we observe that the assumptions on the distribution imply the following properties:

- *Divisibility condition:* The number of components we expect to observe over a set S of observed variables is divisible by a number of components we observe on the subset $S' \subset S$ of observed variables (see Obs. 2.6).

- *Structure of means:* Observe that the projections of the means of mixture clusters in the marginal distribution over S are the same as the means of mixture components over variables S' for every $S' \subseteq S$. Hence, if we learn the mixture models over S and S' with the correct numbers of components $k(S)$ and $k(S')$, we expect the projections to be close.

Example 6.1. *Suppose we are confident that the number of components in the mixture over X_1 is in the set $\{6, 7, 8\}$, over X_2 is in $\{4, 5, 6\}$ and the number of components in the mixture over $\{X_1, X_2\}$ is in the set $\{20, 21, 22, 23, 24, 25, 26\}$. Using divisibility condition between X_1 and $\{X_1, X_2\}$ we may shrink the set of candidates to $\{21, 24\}$. Next using the divisibility condition for X_2 and $\{X_1, X_2\}$ we may determine that the number of components should be 24.*

Figure 3: Average Structural Hamming distance for recovery of G, where $m = |H|$ and $n = |X|$.

With these observations in mind, we use a weighted voting procedure, where every set S votes for the number of components in every superset and every subset based on divisibility or means alignment. We then predict the true number of components by picking the candidate with the most votes.

Constructing L   In order to estimate L from samples we learn the mixture over the entire set of variables (using K-means and the number of components predicted on the previous step) and over each variable separately (again, using previous step). After this we project the mean of each component to a space over which X_i is defined and pick the closest mean in L_2 distance (see Figure 2).

Reconstructing the latent graphical model   Once we obtain the joint probability table of H, the final piece is to learn the latent DAG Λ on H. This is a standard problem of learning the causal structure among m discrete variables given samples from their joint distribution. For this a multitude of approaches have been proposed in the literature, for instance the PC algorithm [53] or the GES algorithm [16]. In our experiments, we use the Fast Greedy Equivalence Search [44] with the discrete BIC score, without assuming faithfulness. The final graph G is therefore obtained from Γ and Λ.

7   Experiments

We implemented these algorithms in an end-to-end pipeline that inputs observed data and outputs an estimate of the causal graph G and an estimate for the joint probability table $\mathbb{P}(H)$. To test this pipeline, we ran experiments on synthetic data. Full details about these experiments, including a detailed description of the entire pipeline, can be found in Appendix E in the supplement.

Data generation   We start with a causal DAG G generated from the Erdös-Rényi model, for different settings of m, n and $|\Omega_i|$. We then generate samples from the probability distribution that corresponds to G. We take each mixture component to be a Gaussian distribution with random mean and covariance (we do not force mixture components to be well-separated, aside from constraining the covariances to be small). Additionally, we do not impose restrictions on the weights of the components, which may be very small. As a result, it is common to have highly unbalanced clusters (e.g. we may have less than 30 points in one component and over 1000 in another). Figure 3 reports the results of 600 simulations; 300 each for $N = 10000$ samples and $N = 15000$ samples.

Results   To compare how well our model recovers the underlying DAG, we compute the Structural Hamming Distance (SHD) between our estimated DAG and the true DAG. Since GES returns a CPDAG instead of a DAG, we also report the number of correct but unoriented edges in the estimated DAG. The average SHD across different problems sizes ranged from zero to 1.33. The highest SHD for any single run was 6. For context, the simulated DAGs had between 3 and 25 edges. Note that any errors are entirely due to estimation error in the K-means implementation of MixOracle, which we expect can be improved significantly. These results indicate that the proposed pipeline is surprisingly effective at recovering the causal graph.

References

[1] E. S. Allman, C. Matias, and J. A. Rhodes. Identifiability of parameters in latent structure models with many observed variables. *Annals of Statistics*, pages 3099–3132, 2009.

[2] A. Anandkumar, D. Hsu, F. Huang, and S. Kakade. Learning mixtures of tree graphical models. volume 2, pages 1052–1060, 2012. cited By 15.

[3] A. Anandkumar, D. Hsu, A. Javanmard, and S. Kakade. Learning linear Bayesian networks with latent variables. In *Proceedings of The 30th International Conference on Machine Learning*, pages 249–257, 2013.

[4] A. Anandkumar, R. Valluvan, et al. Learning loopy graphical models with latent variables: Efficient methods and guarantees. *Annals of Statistics*, 41(2):401–435, 2013.

[5] T. W. Anderson. Estimating linear statistical relationships. *The Annals of Statistics*, pages 1–45, 1984.

[6] B. Aragam, C. Dan, E. P. Xing, and P. Ravikumar. Identifiability of nonparametric mixture models and bayes optimal clustering. *Ann. Statist.*, 48(4):2277–2302, 2020. ISSN 0090-5364. doi: 10.1214/19-AOS1887. arXiv:1802.04397.

[7] S. Arora, R. Ge, and A. Moitra. Learning topic models–going beyond svd. In *2012 IEEE 53rd annual symposium on foundations of computer science*, pages 1–10. IEEE, 2012.

[8] S. Arora, R. Ge, Y. Halpern, D. Mimno, A. Moitra, D. Sontag, Y. Wu, and M. Zhu. A practical algorithm for topic modeling with provable guarantees. In *International Conference on Machine Learning*, pages 280–288. PMLR, 2013.

[9] S. Bonhomme, K. Jochmans, and J.-M. Robin. Estimating multivariate latent-structure models. *Annals of Statistics*, 44(2):540–563, 2016.

[10] G. Bresler and R.-D. Buhai. Learning restricted boltzmann machines with sparse latent variables. *Advances in Neural Information Processing Systems*, 33, 2020.

[11] G. Bresler, F. Koehler, and A. Moitra. Learning restricted boltzmann machines via influence maximization. In *Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing*, pages 828–839, 2019.

[12] K. Chalupka, P. Perona, and F. Eberhardt. Visual causal feature learning. *arXiv preprint arXiv:1412.2309*, 2014.

[13] K. Chalupka, F. Eberhardt, and P. Perona. Causal feature learning: an overview. *Behaviormetrika*, 44(1):137–164, 2017.

[14] V. Chandrasekaran, P. A. Parrilo, A. S. Willsky, et al. Latent variable graphical model selection via convex optimization. *The Annals of Statistics*, 40(4):1935–1967, 2012.

[15] J. Chen and A. Khalili. Order selection in finite mixture models with a nonsmooth penalty. *Journal of the American Statistical Association*, 104(485):187–196, 2009.

[16] D. M. Chickering. Optimal structure identification with greedy search. *Journal of machine learning research*, 3(Nov):507–554, 2002.

[17] D. Colombo, M. H. Maathuis, M. Kalisch, and T. S. Richardson. Learning high-dimensional directed acyclic graphs with latent and selection variables. *Annals of Statistics*, 40(1):294–321, 2012.

[18] D. Dacunha-Castelle, E. Gassiat, et al. The estimation of the order of a mixture model. *Bernoulli*, 3(3):279–299, 1997.

[19] M. Ding, C. Daskalakis, and S. Feizi. Gans with conditional independence graphs: On subadditivity of probability divergences. In *International Conference on Artificial Intelligence and Statistics*, pages 3709–3717. PMLR, 2021.

[20] R. J. Evans and T. S. Richardson. Markovian acyclic directed mixed graphs for discrete data. *The Annals of Statistics*, pages 1452–1482, 2014.

[21] R. J. Evans, T. S. Richardson, et al. Smooth, identifiable supermodels of discrete dag models with latent variables. *Bernoulli*, 25(2):848–876, 2019.

[22] R. J. Evans et al. Margins of discrete bayesian networks. *The Annals of Statistics*, 46(6A): 2623–2656, 2018.

[23] B. Frot, P. Nandy, and M. H. Maathuis. Robust causal structure learning with some hidden variables. *arXiv preprint arXiv:1708.01151*, 2017.

[24] S. L. Gordon and L. J. Schulman. Hadamard extensions and the identification of mixtures of product distributions. *arXiv preprint arXiv:2101.11688*, 2021.

[25] J. Grimmer, D. Knox, and B. M. Stewart. Na\" ive regression requires weaker assumptions than factor models to adjust for multiple cause confounding. *arXiv preprint arXiv:2007.12702*, 2020.

[26] P. Hall and X.-H. Zhou. Nonparametric estimation of component distributions in a multivariate mixture. *Annals of Statistics*, pages 201–224, 2003.

[27] P. O. Hoyer, S. Shimizu, and A. J. Kerminen. Estimation of linear, non-gaussian causal models in the presence of confounding latent variables. *arXiv preprint cs/0603038*, 2006.

[28] R. I. Jennrich. An asymptotic χ_2 test for the equality of two correlation matrices. *Journal of the American Statistical Association*, 65(330):904–912, 1970.

[29] I. Khemakhem, D. Kingma, R. Monti, and A. Hyvarinen. Variational autoencoders and nonlinear ica: A unifying framework. In *International Conference on Artificial Intelligence and Statistics*, pages 2207–2217. PMLR, 2020.

[30] T. Kipf, E. Fetaya, K.-C. Wang, M. Welling, and R. Zemel. Neural relational inference for interacting systems. In *International Conference on Machine Learning*, pages 2688–2697. PMLR, 2018.

[31] M. Kocaoglu, C. Snyder, A. G. Dimakis, and S. Vishwanath. Causalgan: Learning causal implicit generative models with adversarial training. *arXiv preprint arXiv:1709.02023*, 2017.

[32] V. I. Koltchinskii. Empirical geometry of multivariate data: a deconvolution approach. *Annals of statistics*, pages 591–629, 2000.

[33] P. Larrañaga and S. Moral. Probabilistic graphical models in artificial intelligence. *Applied soft computing*, 11(2):1511–1528, 2011.

[34] Y. Li, A. Torralba, A. Anandkumar, D. Fox, and A. Garg. Causal discovery in physical systems from videos. *arXiv preprint arXiv:2007.00631*, 2020.

[35] B. G. Lindsay. Mixture models: theory, geometry and applications. In *NSF-CBMS regional conference series in probability and statistics*, pages i–163. JSTOR, 1995.

[36] D. Lopez-Paz, R. Nishihara, S. Chintala, B. Scholkopf, and L. Bottou. Discovering causal signals in images. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 6979–6987, 2017.

[37] T. Manole and A. Khalili. Estimating the number of components in finite mixture models via the group-sort-fuse procedure. *arXiv preprint arXiv:2005.11641*, 2020.

[38] R. P. Monti, K. Zhang, and A. Hyvärinen. Causal discovery with general non-linear relationships using non-linear ica. In *Uncertainty in Artificial Intelligence*, pages 186–195. PMLR, 2020.

[39] A. Newell and J. Deng. Pixels to graphs by associative embedding. *arXiv preprint arXiv:1706.07365*, 2017.

[40] J. Pearl. *Probabilistic reasoning in intelligent systems: Networks of plausible inference*. Morgan Kaufmann, 1988.

[41] J. Pearl. *Causality*. Cambridge university press, 2009.

[42] J. Peters and P. Bühlmann. Identifiability of Gaussian structural equation models with equal error variances. *Biometrika*, 101(1):219–228, 2013.

[43] J. Peters, J. M. Mooij, D. Janzing, and B. Schölkopf. Causal discovery with continuous additive noise models. *Journal of Machine Learning Research*, 15(1):2009–2053, 2014.

[44] J. Ramsey, M. Glymour, R. Sanchez-Romero, and C. Glymour. A million variables and more: the fast greedy equivalence search algorithm for learning high-dimensional graphical causal models, with an application to functional magnetic resonance images. *International journal of data science and analytics*, 3(2):121–129, 2017.

[45] T. S. Richardson, R. J. Evans, J. M. Robins, and I. Shpitser. Nested markov properties for acyclic directed mixed graphs. *arXiv preprint arXiv:1701.06686*, 2017.

[46] A. Ritchie, R. A. Vandermeulen, and C. Scott. Consistent estimation of identifiable nonparametric mixture models from grouped observations. *arXiv preprint arXiv:2006.07459*, 2020.

[47] J. M. Robins, R. Scheines, P. Spirtes, and L. Wasserman. Uniform consistency in causal inference. *Biometrika*, 90(3):491–515, 2003.

[48] B. Schölkopf, F. Locatello, S. Bauer, N. R. Ke, N. Kalchbrenner, A. Goyal, and Y. Bengio. Toward causal representation learning. *Proceedings of the IEEE*, 109(5):612–634, 2021.

[49] X. Shen, F. Liu, H. Dong, Q. Lian, Z. Chen, and T. Zhang. Disentangled generative causal representation learning. *arXiv preprint arXiv:2010.02637*, 2020.

[50] T. Shi, M. Belkin, and B. Yu. Data spectroscopy: Eigenspaces of convolution operators and clustering. *Annals of Statistics*, pages 3960–3984, 2009.

[51] S. Shimizu, P. O. Hoyer, A. Hyvärinen, and A. Kerminen. A linear non-Gaussian acyclic model for causal discovery. *Journal of Machine Learning Research*, 7:2003–2030, 2006.

[52] R. Silva, R. Scheine, C. Glymour, and P. Spirtes. Learning the structure of linear latent variable models. *Journal of Machine Learning Research*, 7(Feb):191–246, 2006.

[53] P. Spirtes and C. Glymour. An algorithm for fast recovery of sparse causal graphs. *Social Science Computer Review*, 9(1):62–72, 1991.

[54] P. Spirtes and J. Zhang. A uniformly consistent estimator of causal effects under the k-triangle-faithfulness assumption. *Statistical Science*, pages 662–678, 2014.

[55] P. Spirtes, C. Glymour, and R. Scheines. *Causation, prediction, and search*, volume 81. The MIT Press, 2000.

[56] P. L. Spirtes, C. Meek, and T. S. Richardson. Causal inference in the presence of latent variables and selection bias. *arXiv preprint arXiv:1302.4983*, 2013.

[57] R. A. Vandermeulen and C. D. Scott. An operator theoretic approach to nonparametric mixture models, 2016.

[58] F. Xie, R. Cai, B. Huang, C. Glymour, Z. Hao, and K. Zhang. Generalized independent noise condition for estimating latent variable causal graphs. *Advances in Neural Information Processing Systems*, 33, 2020.

[59] M. Yang, F. Liu, Z. Chen, X. Shen, J. Hao, and J. Wang. Causalvae: Disentangled representation learning via neural structural causal models. *arXiv preprint arXiv:2004.08697*, 2020.

[60] K. Zhang and A. Hyvärinen. On the identifiability of the post-nonlinear causal model. In *Proceedings of the twenty-fifth conference on uncertainty in artificial intelligence*, pages 647–655. AUAI Press, 2009.