SCALING LAWS IN MEAN-FIELD GAMES

ABSTRACT

In this work, we attempt to bridge the two largely independently evolving fields of
finite-agent and infinite-agent games, by studying the scaling laws in mean-field
games. The key is to obtain the optimal policies of a set of finite-agent games with
different numbers of agents (population size) and then investigate how the policies
evolve with the population size. However, either deriving the closed-form solution
for each game is theoretically intractable, training a distinct policy for each game
is computationally intensive, or directly applying the policy trained in a game to
other games is sub-optimal. We address these challenges through the **P**opulation-
size-**A**ware **P**olicy **O**ptimization (PAPO). Our contributions are three-fold. First,
to efficiently generate efficient policies for games with different population sizes,
we propose PAPO, which unifies two natural options (augmentation and hyper-
network) and achieves significantly better performance. PAPO consists of three
components: i) the population-size encoding which transforms the original value
of population size to an equivalent encoding to avoid training collapse, ii) a hyper-
network to generate a distinct policy for each game conditioned on the population
size, and iii) the population size as an additional input to the generated policy.
Next, we construct a multi-task-based training procedure to efficiently train the
neural networks of PAPO by sampling data from multiple games with different
population sizes. Finally, extensive experiments on multiple environments show
the significant superiority of PAPO over baselines, and extensive analysis of the
scaling laws of the generated policies further deepens our understanding of the
two fields of finite-agent and infinite-agent games. To our best knowledge, this
work presents the first attempt to bridge the two research fields.

1 INTRODUCTION

Games involving a finite number of agents have been ex-
tensively investigated, ranging from board games such as
Go (Silver et al., 2016; 2018), Poker (Brown & Sandholm,
2018; 2019; Moravčík et al., 2017), and Chess (Campbell
et al., 2002) to real-time strategy games such as StarCraft
II (Vinyals et al., 2019) and Dota 2 (Berner et al., 2019).
However, existing works are typically limited to a handful
of agents, which hinders them from broader applications.
To break the curse of many agents (Wang et al., 2020),
mean-field game (MFG) (Huang et al., 2006; Lasry & Li-
ons, 2007) was introduced to study the games that involve
an infinite number of agents. Recently, benefiting from
reinforcement learning (RL) (Sutton & Barto, 2018) and
deep RL (Lillicrap et al., 2016; Mnih et al., 2015), MFG
provides a versatile framework to model games with large
population of agents (Cui & Koeppl, 2022; Fu et al., 2019;
Guo et al., 2019; Laurière et al., 2022; Perolat et al., 2021;
Perrin et al., 2022; 2020; Yang et al., 2018b).

Figure 1: Experiments on Taxi Match-
ing environment show the failure of
two naive methods and the success of
our PAPO. ↓ means the lower the better
performance. See Sec. 5.1 for details.

Despite the successes of finite-agent games and infinite-agent games, the two fields are largely evolv-
ing independently. Several fundamental questions motivate us to bridge the two fields. First, how the
finite-agent games and optimal policies of agents evolve with the population size? As the population

size increases, the finite-agent games[1] approximate, though never equal to, their infinite-agent counterparts (Cui & Koeppl, 2021; Mguni et al., 2018). Therefore, the solutions returned by methods in finite-agent games should be consistent with that returned by methods in infinite-agent games. As we can never generate finite-agent games with infinite number of agents, we need to investigate the evolution of the finite-agent games and the optimal policies of agents, i.e., scaling laws, to check the consistency of the methods. However, theoretically investigating the scaling laws is infeasible, as obtaining the closed-form solutions of a set of finite-agent games is typically intractable. Hence, another natural question is: how to efficiently generate efficient policies for a set of finite-agent games with different population sizes? Most methods in finite-agent games can only return the solution of the game with a given number of agents (Bai & Jin, 2020; Jia et al., 2019; Littman et al., 2001). Unfortunately, the number of agents varies dramatically and rapidly in many real-world scenarios. For example, the number of taxis could be several hundred in rush hour while it could be a handful at midnight (Alonso-Mora et al., 2017). Fig. 1 demonstrates the failure of two naive options: i) directly transfer the policy trained in a given game to other games (PPO-Naive), and ii) train a policy by using the data sampled from multiple games (PPO). Furthermore, computing the optimal policies of agents in games with different population sizes is computationally intensive.

In this work, we propose a novel approach to efficiently generate efficient policies for games with different population sizes, and then investigate the scaling laws of the generated policies. Our main contributions are three-fold. First, we propose PAPO, which unifies two natural methods: augmentation and hypernetwork, and thus, achieves better performance. Specifically, PAPO consists of three components: i) the population-size encoding which transforms the original value of population size to an equivalent encoding to avoid training collapse, ii) a hypernetwork to generate a distinct policy for each game conditioned on the population size, and iii) the population size as an additional input to the generated policy. Next, to efficiently train the neural networks of PAPO, we construct a multi-task-based training procedure where the networks are trained by using the data sampled from games with different population sizes. Finally, extensive experiments on multiple widely used game environments demonstrate the superiority of PAPO over several naive and strong baselines. Furthermore, with a proper similarity measure (centered kernel alignment (Kornblith et al., 2019)), we conduct an extensive analysis to show the scaling laws of the policies generated by PAPO, which deepens our understanding of the two fields of finite-agent and infinite-agent games. By establishing the state-of-the-art for bridging the two research fields, we believe that this work contributes to accelerating the research in both fields from a new and unified perspective.

2 RELATED WORKS

Learning in Markov Games (MGs). Among finite-agent games, Markov game (Littman, 1994; Shapley, 1953) is a widely used framework for characterizing games with sequential decision making, e.g., in multi-agent reinforcement learning. There is a long line of work in developing efficient algorithms for finding Nash equilibria of MGs under various assumptions such as full environmental knowledge (Hansen et al., 2013; Hu & Wellman, 2003; Littman et al., 2001; Wei et al., 2020), access to simulators (Jia et al., 2019; Sidford et al., 2020; Wei et al., 2017; 2021), and special structures like zero-sum games (Bai & Jin, 2020; Bai et al., 2020; Chen et al., 2021; Huang et al., 2021a; Jin et al., 2021; Xie et al., 2020; Zhang et al., 2020) and potential games (Ding et al., 2022; Fox et al., 2021; Leonardos et al., 2022), or built on techniques for learning single-agent Markov decision process (Bai et al., 2021; Liu et al., 2021). Our work adds to the vast body of existing works on learning in MGs. Instead of concentrating on the policy learning in a given MG, we aim to investigate how the finite-agent games and optimal policies of agents evolve with the population size, i.e., scaling laws (Kaplan et al., 2020; Kello et al., 2010; Lobacheva et al., 2020), and propose novel methods to efficiently generate policies that work well across games with different population sizes, given that the agents are homogeneous which is a common phenomenon in many real-world scenarios such as crowd modeling (Yang et al., 2020b), Ad auction (Gummadi et al., 2012), fleet management (Lin et al., 2018), and sharing economy (Hamari et al., 2016).

Learning in Mean-Field Games (MFGs). In contrast to finite-agent MGs, MFGs consider the case with an infinite number of agents. Since introduced in (Huang et al., 2006) and (Lasry & Lions, 2007), MFG has gained intensive research attention due to its power in modeling games involving a

---

[1]In this paper, we consider the finite-agent games where the agents are homogeneous.

large population of agents (Achdou & Laurière, 2020; Gomes et al., 2014; Lauriere, 2021; Ruthotto et al., 2020). Recently, the capability of MFG is further revealed by benefiting from RL (Fu et al., 2019; Guo et al., 2019; Perolat et al., 2021; Perrin et al., 2020) and deep RL (Laurière et al., 2022; Perrin et al., 2022; Subramanian & Mahajan, 2019; Yang et al., 2018a;b). Despite the progress, the evolution of finite-agent games to infinite-agent MFGs is poorly understood and unexplored. However, directly studying the evolution of finite-agent games and optimal policies of agents with the population size is infeasible as it is hard to obtain the closed-form solutions to the games. Our work makes the first attempt to bridge the two research fields of finite-agent games and infinite-agent games by establishing a novel tool which we call PAPO.

Hypernetwork. A Hypernetwork (Ha et al., 2016) is a neural network designed to produce the parameters of another network. It has gained popularity recently in a variety of fields such as computer vision (Brock et al., 2018; Jia et al., 2016; Littwin & Wolf, 2019; Potapov et al., 2018) and RL (Huang et al., 2021b; Rashid et al., 2018). In (Sarafian et al., 2021), Hypernetwork was used to map the state or task context to the Q network or policy network parameters. Differently, in addition to generating a distinct efficient policy for each population size by using Hypernetwork, we also investigate the scaling laws of the generated policies, which has not been done in the literature.

3 Preliminaries

In this section, we present the game models (finite-agent Markov game and infinite-agent mean-field game) and problem statement of this work.

Finite-agent Markov Game. A Markov Game (MG) with $N < \infty$ homogeneous agents is denoted as $G(N) = (\mathcal{N}, \mathcal{S}, \mathcal{A}, p, r, \mathcal{T})$. $\mathcal{N} = \{1, \cdots, N\}$ is the set of agents. $\mathcal{S}$ and $\mathcal{A}$ are respectively the shared state and action spaces. At each time step $t \in \mathcal{T} = \{0, 1, \cdots, T\}$, an agent i in state s_t^i takes an action a_t^i. Let $z_{\boldsymbol{s}_t}^N$ denote the empirical distribution of the agent states $\boldsymbol{s}_t = (s_t^1, \cdots, s_t^N)$ with $z_{\boldsymbol{s}_t}^N(s) = \frac{1}{N} \sum_{i=1}^N \mathbf{1}\{s_t^i = s\}$, for all $s \in \mathcal{S}$. Then, $z_{\boldsymbol{s}_t}^N \in \Delta(\mathcal{S})$, the probability distribution over $\mathcal{S}$. For agent i, given the state s_t^i, action a_t^i, and state distribution $z_{\boldsymbol{s}_t}^N$, its dynamical behavior is described by the state transition function $p : \mathcal{S} \times \mathcal{A} \times \Delta(\mathcal{A}) \to \Delta(\mathcal{S})$ and it receives a reward of $r(s_t^i, a_t^i, z_{\boldsymbol{s}_t}^N)$. Let $\pi^i : \mathcal{S} \to \Delta(\mathcal{A})$ denote the policy[2] of agent i. Accordingly, $\boldsymbol{\pi} = (\pi^i)_{i \in \mathcal{N}}$ is the joint policy of all agents and $\boldsymbol{\pi}^{-i} = (\pi^j)_{j \in \mathcal{N}, j \neq i}$ is the joint policy of all agents except i. Given the initial joint state $\boldsymbol{s}$ and joint policy $\boldsymbol{\pi}$, the value function for agent $1 \leq i \leq N$ is given by

$$V^i(s^i, \pi^i, \boldsymbol{\pi}^{-i}) = \mathbb{E}\left[\sum_{t=0}^T r(s_t^i, a_t^i, z_{\boldsymbol{s}_t}^N)\Big| s_0^i = s^i, s_{t+1}^i \sim p, a_t^i \sim \pi^i\right]. \tag{1}$$

A joint policy $\boldsymbol{\pi}^* = (\pi^{i,*})_{i \in \mathcal{N}}$ is called a Nash policy if an agent has no incentive to unilaterally deviate from others: for any $i \in \mathcal{N}$, $V^i(s^i, \boldsymbol{\pi}^*) \geq \max_{\pi^i} V^i(s^i, \pi^i, \boldsymbol{\pi}^{-i,*})$. Given a joint policy $\boldsymbol{\pi}$, the NASHCONV$(\boldsymbol{\pi}) = \sum_{i=1}^N \max_{\hat{\pi}^i} V^i(s^i, \hat{\pi}^i, \boldsymbol{\pi}^{-i}) - V^i(s^i, \boldsymbol{\pi})$ measures the "distance" of $\boldsymbol{\pi}$ to the Nash policy. That is, $\boldsymbol{\pi}$ is a Nash policy if NASHCONV$(\boldsymbol{\pi}) = 0$.

Mean-Field Game. A Mean-Field Game (MFG) consists of the same elements as the finite-agent MG except that $N = \infty$, which is denoted as $G(\infty) = (\mathcal{S}, \mathcal{A}, p, r, \mathcal{T})$. In this case, instead of modeling N separate agents, it models a single representative agent and collapses all other (infinite number of) agents into the mean-field, denoted by $\mu_t \in \Delta(\mathcal{S})$. As the agents are homogeneous, the index i is suppressed. Consider a policy π as before. Given some fixed mean-field $(\mu_t)_{t \in \mathcal{T}}$ of the population and initial state $s \sim \mu_0$ of the representative agent, the value function for the agent is

$$V(s, \pi, (\mu_t)_{t \in \mathcal{T}}) = \mathbb{E}\left[\sum_{t=0}^T r(s_t, a_t, \mu_t)\Big| s_0 = s, s_{t+1} \sim p, a_t \sim \pi\right]. \tag{2}$$

π^* is called a Nash policy if the representative agent has no incentive to unilaterally deviate from the population (Perolat et al., 2021; Perrin et al., 2020): $V(s, \pi^*, (\mu_t^*)_{t \in \mathcal{T}}) \geq \max_{\hat{\pi}} V(s, \hat{\pi}, (\mu_t^*)_{t \in \mathcal{T}})$, where $(\mu_t^*)_{t \in \mathcal{T}}$ is the mean-field of the population following π^*. Given a policy π, the NashConv is defined as NASHCONV$(\pi) = \max_{\hat{\pi}} V(s, \hat{\pi}, (\mu_t)_{t \in \mathcal{T}}) - V(s, \pi, (\mu_t)_{t \in \mathcal{T}})$ with $(\mu_t)_{t \in \mathcal{T}}$ being the mean-field of the population following π. Then, π is a Nash policy if NASHCONV$(\pi) = 0$.

---

[2]In experiments, we follow (Laurière et al., 2022) to make the policy be dependent on time by concatenating the state with time. Here, with a slight abuse of notation, we keep using $\mathcal{S}$ and omit the time for simplicity.

Figure 2: The neural network architecture of PAPO.

Problem Statement. Though numerous advancements have been achieved for the finite-agent MGs and infinite-agent MFGs, the two fields are largely evolving independently (we provide more detailed discussion on the connection between MGs and MFGs in Appendix A.2). Bridging the two fields can contribute to accelerating the research in both fields. There are two closely coupled questions: how the finite-agent MGs and optimal policies of agents evolve with the population size, i.e., scaling laws, and how to efficiently generate efficient policies for finite-agent MGs with different population sizes. Formally, let $G = \{G(\underline{N}), \cdots, G(N), \cdots, G(\bar{N})\}$ denote a set of MGs, where $\underline{N}$ and $\bar{N}$ denote the minimum and maximum number of agents. Let π_N^* denote the Nash policy of a game $G(N)$. Let $\rho(N) = \rho(\pi_N^*, \pi_{N+1}^*)$ denote some similarity measure between the Nash policy of $G(N)$ and that of $G(N+1)$. Then, one question is how $\rho(N)$ changes with N. However, directly investigating the evolution of $\rho(N)$ is infeasible, as we need to obtain the Nash policy π_N^* for each game $G(N) \in G$. In addition, directly applying the Nash policy π_N^* to a game $G(N') \in G$ with $N' \neq N$ could result in worse (or arbitrarily worse) performance, i.e., large (or arbitrarily large) NASHCONV(π_N^*) for $G(N')$, as shown in Fig. 1. Thus, another question is how to efficiently generate a policy π_N that works well for each game $G(N) \in G$, i.e., small NASHCONV(π_N), though it may not be the Nash policy $\pi_N \neq \pi_N^*$. Unfortunately, most existing methods can only return the Nash policy for the game with a given N, which hinders them from many real-world applications where the number of agents varies dramatically and rapidly, e.g., the number of taxis could be several hundred in rush hour while it could be a handful at midnight (Alonso-Mora et al., 2017). Furthermore, learning the Nash policies of all the games in G is computationally intensive. Therefore, our objective is to develop novel methods that can efficiently generate efficient policies[3] for the games in G and enable us to investigate the scaling laws.

4 POPULATION-SIZE-AWARE POLICY OPTIMIZATION

We start by introducing the basic structure of the policy network of a representative agent. Let $\pi_{\boldsymbol{\theta}}$ denote the agent's policy parameterized by $\boldsymbol{\theta} \in \Theta$. Note that $\boldsymbol{\theta}$ can be any type of parameterization such as direct policy parameterizations (Leonardos et al., 2022) and neural networks (Agarwal et al., 2021). In this work, we use a neural network with three layers to represent the policy, i.e., $\boldsymbol{\theta} = (\boldsymbol{\theta_1}, \boldsymbol{\theta_2}, \boldsymbol{\theta_3})$ with $\boldsymbol{\theta}_l = (\boldsymbol{w}_l, \boldsymbol{b}_l, \boldsymbol{g}_l)$ denoting the vectors of weights ($\boldsymbol{w}_l$), biases ($\boldsymbol{b}_l$), and scaling factors ($\boldsymbol{g}_l$) of the layer $1 \leq l \leq 3$. In practice, $\boldsymbol{\theta}$ is typically trained by using RL algorithms (see Sec. 4.3 for practical implementation). However, as mentioned in the problem statement, either training a distinct policy for each game is computationally intractable or naively applying a policy trained under a given N to other games is sub-optimal (as shown in Fig. 1). To address these challenges, we propose a new policy optimization approach, the **P**opulation-size-**A**ware **P**olicy **O**ptimization (PAPO), which is shown in Fig. 2.

4.1 POPULATION-SIZE ENCODING

As PAPO is population-size dependent, one may choose to directly take N as the input (we call it the raw encoding (RE, for short)). However, this option cannot work in practice. In many real-world

---

[3]We call a policy an "efficient policy" if it has a small NashConv in the corresponding game.

applications, the population size can be large and vary dramatically and rapidly, e.g., the total number of taxis in Manhattan is around 13,000 and in one day it can fluctuate from a handful at midnight to several hundred in rush hour (Alonso-Mora et al., 2017). When directly taking population sizes as inputs, bigger N's will have a higher contribution to the network's output error and dominant the update of the network. This can degrade the performance or severely, collapse the training (as observed in experiments where the training of PAPO with RE is collapsed).

To address the aforementioned issue, we propose the population-size encoding to pre-process N. We use binary encoding (BE, for short) to equivalently transform the original decimal representation of N into a binary vector with size $k > 0$. Formally, given N, we obtain a vector $e(N) = [e_1, \cdots, e_k]$ such that $N = \sum_{j=1}^{k} 2^{k-j} e_j$ where $e_j \in \{0, 1\}$. After that, the encoding is further mapped to the embedding (through an embedding layer parameterized with η) which will be fed to the policy network and hypernetwork as shown in Fig. 2. With a slight abuse of notation, throughout this work, we simply use N to represent the embedding of $e(N)$ if it is clear from the context.

4.2 POPULATION-SIZE-AWARE ARCHITECTURE

The critical insight of our approach is to leverage the population-size information to generate efficient policies for the games in G. In view of the fact that none of the existing works has addressed a similar problem as ours, we first propose two natural methods: augmentation and hypernetwork.

Augmentation. That is, we concatenate N with s_t and then pass the resulting input to the policy. A similar idea has been adopted in the literature to address the problem of policy generalization. For example, in (Perrin et al., 2022), the state is concatenated with the initial mean-field to endow the policy with the capability of generalizing across the mean-field space. In our context, by augmenting the state with N, the policy can work well across games with different N's.

Hypernetwork. That is, we generate a distinct policy for each game by mapping N to the policy network parameters through a hypernetwork (Ha et al., 2016; Sarafian et al., 2021). This choice is completely different from the augmentation as the game-level information (population size in our context) is fully disentangled from the policy input. More specifically, let h_β denote a hypernetwork parameterized with β. h_β takes N as input and outputs a set of parameters (weights, biases, and scaling factors) which will be reshaped to form the structure of the policy network. Formally, we have $\theta = h_\beta(N)$. In the hypernetwork, three independent heads are used to generate the parameters of the three layers of the policy network (more details of the network architecture such as the number of neurons of each layer can be found in Appendix B.1).

Although the above two methods can obtain efficient policies for the games in G, there is no affirmative answer to the question of which one is better as they achieve the goal from different angles: augmentation uses a fixed set of policy network parameters and takes elements from the cartesian product of two domains (S and $\{2, 3, \cdots\}$) as inputs while the hypernetwork generates a distinct set of policy network parameters for each game. In this work, instead of trying to answer this question, we propose a unified framework, PAPO, which encompasses the two options as two special cases. Specifically, as shown in Fig. 2, PAPO uses a hypernetwork to generate the parameters of the policy network conditioned on N and also takes N as an additional input to the generated policy.

Intuitively, PAPO preserves the merits of the two special cases and possibly achieves better performance. On one hand, it induces a hierarchical information structure. To a certain extent, it decouples the game-level information from the policy by introducing a hypernetwork to encode the varying elements across different games. In the context of our work, the only difference between the games in G is the population size while other game elements such as the state and action spaces are identical. Thus, PAPO can generate a distinct policy (or in other words, a specialized policy) for each game conditioned on the population size. On the other hand, once the policy is generated, PAPO becomes the augmentation, which, as mentioned before, can work well in the corresponding game.

Furthermore, we can investigate the scaling laws of the generated policies by looking into the similarity between them. Formally, let $\pi_{\theta=h_\beta(N)}$ and $\pi_{\theta=h_\beta(N+1)}$ be two policies generated by PAPO for the two games with N and $N + 1$ agents, respectively. Then, the similarity measure, denoted as $\rho(N) = \rho\left(\pi_{\theta=h_\beta(N)}, \pi_{\theta=h_\beta(N+1)}\right)$, as a function of N, characterizes the evolution of the policies with the population size. In practice, one can choose any type of $\rho(N)$. In experiments, we will identify a proper similarity measure that can be used to achieve this goal.

4.3 PRACTICAL IMPLEMENTATION

Notice that PAPO is a general approach. In this section, we specify the practical implementations of the modules in PAPO and construct a training procedure to efficiently train the neural networks.

Algorithmic Framework. We implement PAPO following the framework of PPO (Schulman et al., 2017) as it is one of the most popular algorithms for solving decision-making problems. That is, in addition to the policy network $\boldsymbol{\theta}$ (i.e., actor), a value network ϕ (i.e., critic) is used to estimate the value of a state and also generated by a hypernetwork. Then, the networks (hypernetworks and embedding layers) are trained with the following loss function (see Appendix B.2 for details):

$$L_t(\boldsymbol{\beta}^{\mathrm{A}}, \boldsymbol{\beta}^{\mathrm{C}}) = \mathbb{E}\Big[L_t^1(\boldsymbol{\theta} = h_{\boldsymbol{\beta}^{\mathrm{A}}}(N)) - c_1 L_t^2(\phi = h_{\boldsymbol{\beta}^{\mathrm{C}}}(N)) + c_2 \mathcal{H}(\pi_{\boldsymbol{\theta} = h_{\boldsymbol{\beta}^{\mathrm{A}}}(N)})\Big]. \qquad (3)$$

As the agents learn their policies independently, the policy learning in this work falls in the category of using independent RL to find Nash equilibrium (Ozdaglar et al., 2021). Recent works (Ding et al., 2022; Fox et al., 2021; Leonardos et al., 2022) have shown that independent policy gradient can converge to the Nash equilibrium under some conditions, which, to some extent, provides support to our work. More discussion can be found in Appendix A.1.

Training Procedure. To make PAPO capable of generating efficient policies for the games in the set G, a trivial idea is to train the networks sequentially over G, i.e., train the networks until they converge in one game and then proceed to the next. Unfortunately, such a method is computationally intensive and could suffer catastrophic forgetting, i.e., the networks focus on the learning in the current game. A more reasonable approach is to train the networks by using the data sampled from all the games (a way similar to multi-task learning (Zhang & Yang, 2021)). Inspired by this idea, we construct a multi-task-based training process to efficiently train the networks. At the beginning of an episode, a game $G(N)$ is uniformly sampled from G. Then, PAPO takes N as input and generates a policy which is used by the agents to interact with the environment. Finally, the experience tuples are used to to train the networks. More details can be found in Appendix B.3.

5 EXPERIMENTS

We first discuss the environments, baselines, metric used to assess the quality of learning, similarity measure used to investigate the scaling laws, and then present the results and ablation studies.

Environments. We consider the following environments which have been widely used in previous works: Exploration (Laurière et al., 2022), Taxi Matching (Nguyen et al., 2018), and Crowd in Circle (Perrin et al., 2020). Details of these environments can be found in Appendix C.1.

Baselines. (1) PPO: the standard deep RL method. (2) AugPPO: augments the input of PPO with the population size. (3) HyperPPO: without the additional input to the generated policy. (4) PPO-Large: the number of neurons of each layer is increased such that the total number of learnable parameters is similar to PAPO. (5) AugPPO-Large: similar to PPO-Large. The last two baselines are necessary to show that performance gain is not due to the additional number of learnable parameters, but due to the architecture of PAPO. In addition, all the baselines are trained with the same training procedure as PAPO, which ensures a fair comparison between them and PAPO. More details on baselines and hyperparameters are given in Appendix C.2 and Appendix C.3, respectively.

Approximate NashConv. Computing the exact NashConv is typically intractable in complex games as it requires obtaining the exact best response (BR) policy of the representative agent. Instead, we obtain an approximate BR by training it for a large enough number of episodes ($1e^6$) and thus, obtain an approximate NashConv, which is the common choice in the literature (Laurière et al., 2022; Perrin et al., 2020). More details are given in Appendix C.4. Furthermore, in Appendix D.1, we show the BR training curves to demonstrate that the BR has approximately converged, ensuring that the approximate NashConv is a reasonable metric to assess the quality of learning.

Similarity Measure. Intuitively, two policies are similar means that their output features (representations) of the corresponding layers (not their parameter vectors) are similar, given the same input data. Particularly, the outputs of the final layer are closely related to an agent's decision-making (behavior). Therefore, if the outputs of the final layers of the two policies are similar, then the behaviors induced by the two policies are similar. Inspired by this intuition, we propose to use the centered

Figure 3: Experimental results. **(A)** Approximate NashConv versus population size. **(B)** CKA value versus population size. **(C)** UMAP embeddings of some human-understandable game states: agent on the upper-right/bottom-left of the map and agent on the center of the circle.

kernel alignment (CKA) (Kornblith et al., 2019) to measure the similarity between two policies as it is the widely used index to measure the similarity between two output features of two neural network layers. More details can be found in Appendix C.5.

5.1 RESULTS

In Fig. 1, we show the results obtained in a small-scale setting ($2 \leq N \leq 50$) in Taxi Matching environment to illustrate our motivation. There are two most straightforward options to obtain policies for different games: i) directly apply the policy trained in a given game ($N = 20$, marked by star) to other games, i.e., PPO-Naive, and ii) train a single policy by using the training procedure in Sec. 4.3 and then apply it to the evaluated games, i.e., PPO. At first glance, it might be natural to expect PPO to work well across different games when it is trained by using the data sampled from

different games. However, as shown in the results, though it outperforms PPO-Naive, it still has a large approximate NashConv when evaluating in different games. In striking contrast, PAPO works well across different games. In addition, by comparison between PPO-Naive and PAPO, we can see that, given the same training budget, PAPO still preserves a similar performance in the game ($N = 20$) where PPO-Naive was trained.

In Fig. 3, we show the results obtained in a larger-scale setting ($2 \leq N \leq 200$) in different environments. From Panel A, we can draw the following conclusions. (1) PAPO significantly outperforms other naive and strong baselines in terms of approximate NashConv across different games, which demonstrates that PAPO has achieved one of our goals – efficiently generating efficient policies for a series of finite-agent games. (2) As two special cases of our PAPO, both AugPPO and HyperPPO can work well across different games. However, they are competitive, which verifies that there is no affirmative answer to the question of which one is better (Sec. 4.2). (3) Given the same training budget, simply increasing the number of learnable parameters of the policy (PPO-Large and AugPPO-Large) or only relying on the hypernetwork to generate the policies (HyperPPO), though could outperform the standard policy structure (PPO), is still struggling to achieve better performance. This shows the superiority of PAPO as a unified framework which inherits the merits of the two special cases (AugPPO/AugPPO-Large and HyperPPO) and thus, achieves a better performance.

In Panel B, we show how the policies generated by PAPO change with the population size. From the results we can see that the similarity between two policies increases with the increasing population size. In other words, with the increase in population size, the policies in the games with different population sizes tend to be similar to each other, which shows a convergent evolution of the policies in terms of population size. Though it is impractical to experimentally set $N = \infty$, from the results we hypothesize that the similarity measure increases to 1 when $N \rightarrow \infty$ (the finite-agent game would become an infinite-agent MFG when $N = \infty$). To quantitatively describe the scaling laws, we show the curves fitting the similarity, which is obtained by employing the tools for curve fitting in Numpy (Harris et al., 2020). We consider a function with the form of $\rho(N) = 1 - \frac{a}{N^b} \leq 1$, which maps N to the similarity measure. The fitted curves again verify the aforementioned conclusions. Furthermore, we compute the p-value of each parameter of the function (a and b), which shows that the curves fit well ($p < 0.05$) the original CKA values. Notice that there could be different forms of $\rho(N)$. For example, a more general case is $\rho(N) = 1 - \frac{a}{cN^b+d} \leq 1$. However, by computing the p-values, we found that some parameters (c and d) are less significant and hence, can be removed from $\rho(N)$. We give a more detailed analysis in Appendix. D.2.

In addition, we observed that the variance of the similarity of the input layer is small while that of the output layer is large (especially when N is small). This coincides with the well-known conclusion in deep learning (Alzubaidi et al., 2021; LeCun et al., 2015): the first layer of a neural network extracts the lowest-level features while the last layer extracts the highest-level features. In our context, the only difference between two games is the number of agents while the underlying environmental setup (e.g., grid size) is the same. Hence, the low-level features extracted by the first layers of the policies are similar. In contrast, as the output layers capture the features of agents' decision makings which are largely impacted by the presence of other agents (more precisely, the number of agents), the extracted high-level features could be very different in different games (especially for small N's).

To gain more intuition on how the generated policies are different from each other, in Panel C, we perform an analysis of the policies' output representations similar to (Jaderberg et al., 2019). We manually construct some high-level game states such as "agent on the upper-right/bottom-left of the map" and "agent on the center of the circle" and obtain the output representations of the policy of each game $G(N)$ by using UMAP (McInnes et al., 2018). We colored the representations of some policies: $N \in \{5, 10, 15, 20\}$ and $N \in \{185, 190, 195, 200\}$ to represent small-scale and large-scale settings, respectively. From the results, we can see that when N is large, the policies of different games tend to encode the same game states in similar ways (i.e., the UMAP embeddings of the same game state of different policies tend to be centered), which is aligned with the findings revealed by the CKA values. We give more analysis in Appendix D.3.

5.2 ABLATIONS

To gain a deeper understanding of the proposed approach and further support the results obtained in the previous section, we provide more discussion in this section and Appendix D.

Effect of Population-size Encoding. In Fig. 4, we show the training curves of PAPO when using RE (i.e., directly using N as the input). It is observed that using RE can result in training collapse. In Taxi Matching environment, though PAPO with RE still gets positive reward, it is lower than PAPO with BE. The results demonstrate the importance of the population-size encoding for training the neural networks of PAPO. More detailed analysis can be found in Appedix D.4.

Figure 4: Collapsed training of PAPO when using RE.

Generalization to Unseen Games. In Fig. 5, we show the performance of applying PAPO and other baselines to unseen games. We found that, though the population-size aware methods (PAPO, HyperPPO, AugPPO, and AugPPO-Large) could perform better than the population-size unaware methods (PPO and PPO-Large) in some of the unseen games, their performance fluctuates and could be much worse. Therefore, an important future direction is to improve the generalizability of PAPO (as well as other population-size-aware methods), where more advanced techniques such as adversarial training (Ganin et al., 2016) are needed.

Figure 5: Performance of PAPO and baselines on unseen games.

6 CONCLUSIONS AND FUTURE WORKS

In this work, we make the first attempt to bridge the two fields of finite-agent and infinite-agent games with three main contributions: i) a novel policy optimization approach, PAPO, to efficiently generate efficient policies for a set of games with different population sizes, ii) a multi-task-based training procedure to efficiently train the neural networks of PAPO, and iii) extensive experiments to demonstrate the significant superiority of our approach over several naive and strong baselines, and extensive analysis of the scaling laws of the policies to further deepen our understanding of the two research fields of finite-agent and infinite-agent games.

There are several future directions. (1) Beyond the single type of agents, in real-world scenarios, the agents can be divided into multiple types (Ganapathi Subramanian et al., 2020; Yang et al., 2020a), e.g., in Taxi Matching environment, different vehicles have different capacities (Alonso-Mora et al., 2017). Investigating the scaling laws of each type require new methods and training regimes. (2) Beyond the population size (Gatchel, 2021), in future works, other game elements such as state and action spaces or even the rules of the games can be different between games. PAPO demonstrates the possibility to learn a universal policy for completely different games. (3) Beyond the target set of games, generalization to unseen games requires more advanced techniques such as adversarial training (Ganin et al., 2016). (4) Our approach may have implications for Meta-RL (Fakoor et al., 2019; Finn et al., 2017; Rakelly et al., 2019; Sohn et al., 2019) as well.

REFERENCES

Yves Achdou and Mathieu Laurière. Mean field games and applications: Numerical aspects. *Mean Field Games*, pp. 249–307, 2020.

Alekh Agarwal, Sham M Kakade, Jason D Lee, and Gaurav Mahajan. On the theory of policy gradient methods: Optimality, approximation, and distribution shift. *Journal of Machine Learning Research*, 22(98):1–76, 2021.

Zafarali Ahmed, Nicolas Le Roux, Mohammad Norouzi, and Dale Schuurmans. Understanding the impact of entropy on policy optimization. In *ICML*, pp. 151–160, 2019.

Javier Alonso-Mora, Samitha Samaranayake, Alex Wallar, Emilio Frazzoli, and Daniela Rus. On-demand high-capacity ride-sharing via dynamic trip-vehicle assignment. *PNAS*, 114(3):462–467, 2017.

Laith Alzubaidi, Jinglan Zhang, Amjad J Humaidi, Ayad Al-Dujaili, Ye Duan, Omran Al-Shamma, J Santamaría, Mohammed A Fadhel, Muthana Al-Amidie, and Laith Farhan. Review of deep learning: Concepts, CNN architectures, challenges, applications, future directions. *Journal of Big Data*, 8(1):1–74, 2021.

Yu Bai and Chi Jin. Provable self-play algorithms for competitive reinforcement learning. In *ICML*, pp. 551–560, 2020.

Yu Bai, Chi Jin, and Tiancheng Yu. Near-optimal reinforcement learning with self-play. *NeurIPS*, pp. 2159–2170, 2020.

Yu Bai, Chi Jin, Huan Wang, and Caiming Xiong. Sample-efficient learning of Stackelberg equilibria in general-sum games. *NeurIPS*, pp. 25799–25811, 2021.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Dębiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

Andrew Brock, Theo Lim, JM Ritchie, and Nick Weston. SMASH: One-shot model architecture search through hypernetworks. In *ICLR*, 2018.

Noam Brown and Tuomas Sandholm. Superhuman AI for heads-up no-limit poker: Libratus beats top professionals. *Science*, 359(6374):418–424, 2018.

Noam Brown and Tuomas Sandholm. Superhuman AI for multiplayer poker. *Science*, 365(6456): 885–890, 2019.

Murray Campbell, A Joseph Hoane Jr, and Feng-hsiung Hsu. Deep blue. *Artificial Intelligence*, 134 (1-2):57–83, 2002.

Zixiang Chen, Dongruo Zhou, and Quanquan Gu. Almost optimal algorithms for two-player Markov games with linear function approximation. *arXiv preprint arXiv:2102.07404*, 2021.

Kai Cui and Heinz Koeppl. Approximately solving mean field games via entropy-regularized deep reinforcement learning. In *AISTATS*, pp. 1909–1917, 2021.

Kai Cui and Heinz Koeppl. Learning graphon mean field games and approximate Nash equilibria. In *ICLR*, 2022.

Dongsheng Ding, Chen-Yu Wei, Kaiqing Zhang, and Mihailo R Jovanović. Independent policy gradient for large-scale Markov potential games: Sharper rates, function approximation, and game-agnostic convergence. *arXiv preprint arXiv:2202.04129*, 2022.

Rasool Fakoor, Pratik Chaudhari, Stefano Soatto, and Alexander J Smola. Meta-Q-learning. In *ICLR*, 2019.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *ICML*, pp. 1126–1135, 2017.

Roy Fox, Stephen McAleer, Will Overman, and Ioannis Panageas. Independent natural policy gradient always converges in Markov potential games. *arXiv preprint arXiv:2110.10614*, 2021.

Zuyue Fu, Zhuoran Yang, Yongxin Chen, and Zhaoran Wang. Actor-critic provably finds Nash equilibria of linear-quadratic mean-field games. In *ICLR*, 2019.

Sriram Ganapathi Subramanian, Pascal Poupart, Matthew E Taylor, and Nidhi Hegde. Multi type mean field reinforcement learning. In *AAMAS*, pp. 411–419, 2020.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *Journal of Machine Learning Research*, 17(1):2096–2030, 2016.

Madelyn Gatchel. Variable-player learning for simulation-based games. Master's thesis, Davidson College, 2021.

Diogo A Gomes et al. Mean field games models—a brief survey. *Dynamic Games and Applications*, 4(2):110–154, 2014.

Ramakrishna Gummadi, Peter Key, and Alexandre Proutiere. Repeated auctions under budget constraints: Optimal bidding strategies and equilibria. In *the Eighth Ad Auction Workshop*, volume 4, 2012.

Xin Guo, Anran Hu, Renyuan Xu, and Junzi Zhang. Learning mean-field games. *NeurIPS*, pp. 4966–4976, 2019.

David Ha, Andrew Dai, and Quoc V Le. Hypernetworks. *arXiv preprint arXiv:1609.09106*, 2016.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *ICML*, pp. 1861–1870, 2018.

Juho Hamari, Mimmi Sjöklint, and Antti Ukkonen. The sharing economy: Why people participate in collaborative consumption. *Journal of the Association for Information Science and Technology*, 67(9):2047–2059, 2016.

Thomas Dueholm Hansen, Peter Bro Miltersen, and Uri Zwick. Strategy iteration is strongly polynomial for 2-player turn-based stochastic games with a constant discount factor. *Journal of the ACM*, 60(1):1–16, 2013.

Charles R Harris, K Jarrod Millman, Stéfan J Van Der Walt, Ralf Gommers, Pauli Virtanen, David Cournapeau, Eric Wieser, Julian Taylor, Sebastian Berg, Nathaniel J Smith, et al. Array programming with NumPy. *Nature*, 585(7825):357–362, 2020.

Junling Hu and Michael P Wellman. Nash Q-learning for general-sum stochastic games. *Journal of Machine Learning Research*, 4(Nov):1039–1069, 2003.

Baihe Huang, Jason D Lee, Zhaoran Wang, and Zhuoran Yang. Towards general function approximation in zero-sum Markov games. *arXiv preprint arXiv:2107.14702*, 2021a.

Minyi Huang, Roland P Malhamé, and Peter E Caines. Large population stochastic dynamic games: closed-loop McKean-Vlasov systems and the Nash certainty equivalence principle. *Communications in Information & Systems*, 6(3):221–252, 2006.

Yizhou Huang, Kevin Xie, Homanga Bharadhwaj, and Florian Shkurti. Continual model-based reinforcement learning with hypernetworks. In *ICRA*, pp. 799–805, 2021b.

Max Jaderberg, Wojciech M. Czarnecki, Iain Dunning, Luke Marris, Guy Lever, Antonio Garcia Castañeda, Charles Beattie, Neil C. Rabinowitz, Ari S. Morcos, Avraham Ruderman, Nicolas Sonnerat, Tim Green, Louise Deason, Joel Z. Leibo, David Silver, Demis Hassabis, Koray Kavukcuoglu, and Thore Graepel. Human-level performance in 3D multiplayer games with population-based reinforcement learning. *Science*, 364(6443):859–865, 2019.

Xu Jia, Bert De Brabandere, Tinne Tuytelaars, and Luc V Gool. Dynamic filter networks. *NeurIPS*, pp. 667–675, 2016.

Zeyu Jia, Lin F Yang, and Mengdi Wang. Feature-based Q-learning for two-player stochastic games. *arXiv preprint arXiv:1906.00423*, 2019.

Chi Jin, Qinghua Liu, and Tiancheng Yu. The power of exploiter: Provable multi-agent RL in large state spaces. *arXiv preprint arXiv:2106.03352*, 2021.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

Christopher T Kello, Gordon DA Brown, Ramon Ferrer-i Cancho, John G Holden, Klaus Linkenkaer-Hansen, Theo Rhodes, and Guy C Van Orden. Scaling laws in cognitive sciences. *Trends in Cognitive Sciences*, 14(5):223–232, 2010.

Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *ICML*, pp. 3519–3529, 2019.

Jean-Michel Lasry and Pierre-Louis Lions. Mean field games. *Japanese Journal of Mathematics*, 2 (1):229–260, 2007.

Mathieu Lauriere. Numerical methods for mean field games and mean field type control. *Mean Field Games*, 78:221, 2021.

Mathieu Laurière, Sarah Perrin, Sertan Girgin, Paul Muller, Ayush Jain, Theophile Cabannes, Georgios Piliouras, Julien Pérolat, Romuald Élie, Olivier Pietquin, et al. Scalable deep reinforcement learning algorithms for mean field games. In *ICML*, pp. 12078–12095, 2022.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436–444, 2015.

Stefanos Leonardos, Will Overman, Ioannis Panageas, and Georgios Piliouras. Global convergence of multi-agent policy gradient in Markov potential games. In *ICLR*, 2022.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *ICLR*, 2016.

Kaixiang Lin, Renyu Zhao, Zhe Xu, and Jiayu Zhou. Efficient large-scale fleet management via multi-agent deep reinforcement learning. In *KDD*, pp. 1774–1783, 2018.

Michael L Littman. Markov games as a framework for multi-agent reinforcement learning. In *ICML*, pp. 157–163, 1994.

Michael L Littman et al. Friend-or-foe Q-learning in general-sum games. In *ICML*, pp. 322–328, 2001.

Gidi Littwin and Lior Wolf. Deep meta functionals for shape representation. In *ICCV*, pp. 1824–1833, 2019.

Qinghua Liu, Tiancheng Yu, Yu Bai, and Chi Jin. A sharp analysis of model-based reinforcement learning with self-play. In *ICML*, pp. 7001–7010, 2021.

Ekaterina Lobacheva, Nadezhda Chirkova, Maxim Kodryan, and Dmitry P Vetrov. On power laws in deep ensembles. *NeurIPS*, pp. 2375–2385, 2020.

Leland McInnes, John Healy, and James Melville. Umap: Uniform manifold approximation and projection for dimension reduction. *arXiv preprint arXiv:1802.03426*, 2018.

David Mguni, Joel Jennings, and Enrique Munoz de Cote. Decentralised learning in systems with many, many strategic agents. In *AAAI*, pp. 4686–4693, 2018.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Matej Moravčík, Martin Schmid, Neil Burch, Viliam Lisỳ, Dustin Morrill, Nolan Bard, Trevor Davis, Kevin Waugh, Michael Johanson, and Michael Bowling. Deepstack: Expert-level artificial intelligence in heads-up no-limit poker. *Science*, 356(6337):508–513, 2017.

Duc Thien Nguyen, Akshat Kumar, and Hoong Chuin Lau. Credit assignment for collective multi-agent RL with global rewards. *NeurIPS*, pp. 8102–8113, 2018.

Asuman Ozdaglar, Muhammed O Sayin, and Kaiqing Zhang. Independent learning in stochastic games. *arXiv preprint arXiv:2111.11743*, 2021.

Julien Perolat, Sarah Perrin, Romuald Elie, Mathieu Laurière, Georgios Piliouras, Matthieu Geist, Karl Tuyls, and Olivier Pietquin. Scaling up mean field games with online mirror descent. *arXiv preprint arXiv:2103.00623*, 2021.

Sarah Perrin, Julien Pérolat, Mathieu Laurière, Matthieu Geist, Romuald Elie, and Olivier Pietquin. Fictitious play for mean field games: Continuous time analysis and applications. *arXiv preprint arXiv:2007.03458*, 2020.

Sarah Perrin, Mathieu Laurière, Julien Pérolat, Romuald Élie, Matthieu Geist, and Olivier Pietquin. Generalization in mean field games by learning master policies. In *AAAI*, pp. 7143–7150, 2022.

Alexey Potapov, Oleg Shcherbakov, Innokentii Zhdanov, Sergey Rodionov, and Nikolai Skorobogatko. Hypernets and their application to learning spatial transformations. In *ICANN*, pp. 476–486, 2018.

Kate Rakelly, Aurick Zhou, Chelsea Finn, Sergey Levine, and Deirdre Quillen. Efficient off-policy meta-reinforcement learning via probabilistic context variables. In *ICML*, pp. 5331–5340, 2019.

Tabish Rashid, Mikayel Samvelyan, Christian Schroeder, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. QMIX: Monotonic value function factorisation for deep multi-agent reinforcement learning. In *ICML*, pp. 4295–4304, 2018.

Lars Ruthotto, Stanley J Osher, Wuchen Li, Levon Nurbekyan, and Samy Wu Fung. A machine learning framework for solving high-dimensional mean field game and mean field control problems. *PNAS*, 117(17):9183–9193, 2020.

Naci Saldi, Tamer Basar, and Maxim Raginsky. Markov–Nash equilibria in mean-field games with discounted cost. *SIAM Journal on Control and Optimization*, 56(6):4256–4287, 2018.

Elad Sarafian, Shai Keynan, and Sarit Kraus. Recomposing the reinforcement learning building blocks with hypernetworks. In *ICML*, pp. 9301–9312, 2021.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Lloyd S Shapley. Stochastic games. *PNAS*, 39(10):1095–1100, 1953.

Aaron Sidford, Mengdi Wang, Lin Yang, and Yinyu Ye. Solving discounted stochastic two-player games with near-optimal time and sample complexity. In *AISTATS*, pp. 2992–3002, 2020.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of Go with deep neural networks and tree search. *Nature*, 529(7587):484–489, 2016.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. A general reinforcement learning algorithm that masters chess, shogi, and Go through self-play. *Science*, 362(6419):1140–1144, 2018.

Sungryull Sohn, Hyunjae Woo, Jongwook Choi, and Honglak Lee. Meta reinforcement learning with autonomous inference of subtask dependencies. In *ICLR*, 2019.

Jayakumar Subramanian and Aditya Mahajan. Reinforcement learning in stationary mean-field games. In *AAMAS*, pp. 251–259, 2019.

Richard S Sutton and Andrew G Barto. *Reinforcement Learning: An Introduction*. MIT press, 2018.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in StarCraft II using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

Lingxiao Wang, Zhuoran Yang, and Zhaoran Wang. Breaking the curse of many agents: Provable mean embedding Q-iteration for mean-field reinforcement learning. In *ICML*, pp. 10092–10103, 2020.

Chen-Yu Wei, Yi-Te Hong, and Chi-Jen Lu. Online reinforcement learning in stochastic games. *NeurIPS*, pp. 4987–4997, 2017.

Chen-Yu Wei, Chung-Wei Lee, Mengxiao Zhang, and Haipeng Luo. Linear last-iterate convergence in constrained saddle-point optimization. *arXiv preprint arXiv:2006.09517*, 2020.

Chen-Yu Wei, Chung-Wei Lee, Mengxiao Zhang, and Haipeng Luo. Last-iterate convergence of decentralized optimistic gradient descent/ascent in infinite-horizon competitive Markov games. In *COLT*, pp. 4259–4299, 2021.

Qiaomin Xie, Yudong Chen, Zhaoran Wang, and Zhuoran Yang. Learning zero-sum simultaneous-move Markov games using function approximation and correlated equilibrium. In *COLT*, pp. 3674–3682, 2020.

Fan Yang, Alina Vereshchaka, Changyou Chen, and Wen Dong. Bayesian multi-type mean field multi-agent imitation learning. In *NeurIPS*, pp. 2469–2478, 2020a.

Jiachen Yang, Xiaojing Ye, Rakshit Trivedi, Huan Xu, and Hongyuan Zha. Deep mean field games for learning optimal behavior policy of large populations. In *ICLR*, 2018a.

Jiachen Yang, Xiaojing Ye, Rakshit Trivedi, Huan Xu, and Hongyuan Zha. Learning deep mean field games for modeling large population behavior. In *ICLR*, 2018b.

Shanwen Yang, Tianrui Li, Xun Gong, Bo Peng, and Jie Hu. A review on crowd simulation and modeling. *Graphical Models*, 111:101081, 2020b.

Kaiqing Zhang, Sham Kakade, Tamer Basar, and Lin Yang. Model-based multi-agent RL in zero-sum Markov games with near-optimal sample complexity. *NeurIPS*, pp. 1166–1178, 2020.

Yu Zhang and Qiang Yang. A survey on multi-task learning. *IEEE Transactions on Knowledge and Data Engineering*, 2021.

A LEARNING IN MARKOV GAMES

In this section, we provide more discussion on learning in Markov games. First, we present some discussion and analysis on independent learning for finding Nash equilibria of Markov games. Then, we provide more discussion on the connection between MGs and MFGs presented in this work to further facilitate the understanding of our proposal.

A.1 CONVERGENCE ANALYSIS OF INDEPENDENT POLICY GRADIENT

In a given game, as all the agents learn their policies independently, the policy learning in this work falls in the category of using independent RL to find Nash equilibrium (Ozdaglar et al., 2021). Recent works (Ding et al., 2022; Fox et al., 2021; Leonardos et al., 2022) have shown that independent policy gradient can always converge to the Nash equilibrium under some conditions. In this section, we provide more analysis on the convergence of independent policy gradient in MGs, which, to some extent, provides support to our approach.

A.1.1 MARKOV POTENTIAL GAMES

A Markov game $G(N)$ is called a Markov potential game (MPG) if there exists a state-dependent potential function $\Phi_s : \Pi \to \mathbb{R}$ such that

$$\Phi_s(\pi^i, \boldsymbol{\pi}^{-i}) - \Phi_s(\hat{\pi}^i, \boldsymbol{\pi}^{-i}) = V^i(s, \pi^i, \boldsymbol{\pi}^{-i}) - V^i(s, \hat{\pi}^i, \boldsymbol{\pi}^{-i}), \tag{4}$$

for all agents $i \in \mathcal{N}$, states $s \in \mathcal{S}$ and policies $\pi^i, \hat{\pi}^i \in \Pi^i$, $\boldsymbol{\pi}^{-i} \in \Pi^{-i}$. Π^i is the policy space of agent i and $\Pi = \times_{i \in \mathcal{N}} \Pi^i$ ($\Pi^{-i} = \times_{j \in \mathcal{N}, j \neq i} \Pi^j$) is the space of joint policy of all agents (except i).

As one of the most important and widely studied classes of games, MPGs have gain much research attention recently due to their power in modeling mixed cooperative/competitive environments and the convergence guarantee of independent policy gradient in these games (Ding et al., 2022; Fox et al., 2021; Leonardos et al., 2022).

A.1.2 INDEPENDENT POLICY GRADIENT

Assume that all agents update their policies according to the gradient ascent (GA) on their policies independently, i.e., only local information such as each agent's own rewards, actions and observations is used during the learning process. The GA is given by

$$\pi^{i,k+1} := \pi^{i,k} + \delta \nabla_{\pi^i} V^i(\pi^{i,k}), \quad \forall i \in \mathcal{N}, \tag{5}$$

where k indicates the k-th iteration of the policy. Note that the policy $\pi^{i,k+1}$ after k-th update is always bounded on its policy space $\pi^{i,k+1} \in \Pi^i$, i.e., $\pi^{i,k+1}(\cdot|s) \in \Delta(\mathcal{A})$ for all $s \in \mathcal{S}$. If not so, a projection operation can be applied to ensure this condition. We omit such an operation for simplicity. Furthermore, we assume that all agents $i \in \mathcal{N}$ use the direct policy parameterization with α-greedy exploration as follows:

$$\pi^i(a|s) = (1-\alpha)x_{i,s,a} + \frac{\alpha}{|\mathcal{A}|}, \tag{6}$$

where $x_{i,s,a} \geq 0$ for all states $s \in \mathcal{S}$, actions $a \in \mathcal{A}$ and $\sum_{a \in \mathcal{A}} \pi^i(a|s) = 1$ for all $s \in \mathcal{S}$. Essentially, $\pi^i(s) = (\pi^i(a|s))_{a \in \mathcal{A}}$ is a mixed strategy in state s. α is the exploration parameter.

In practice, the exact gradient $\nabla_{\pi^i} V^i(\pi^{i,k})$ is typically unavailable, agents use stochastic gradient ascent (SGA) to update their policies. Specifically, the exact gradient $\nabla_{\pi^i} V^i(\pi^{i,k})$ is replaced by an estimator, denoted as $\hat{\nabla}^k_{\pi^i}$, which is typically derived from a batch of observations collected through interactions with the game environment by employing the policy $\pi^{i,k}$ at k-th iteration. The commonly used (REINFORCE) gradient estimator is as follows:

$$\hat{\nabla}^k_{\pi^i} = R^i \sum_{t=0}^{T} \nabla \log \pi^{i,k}(a_t|s_t), \tag{7}$$

where $R^i = \sum_{t=0}^{T} r_t$ is the sum of rewards of agent i along the trajectory collected by using the policy $\pi^{i,k}$ at k-th iteration. Now the SGA is given by

$$\pi^{i,k+1} := \pi^{i,k} + \delta \hat{\nabla}^k_{\pi^i}, \quad \forall i \in \mathcal{N}. \tag{8}$$

A.1.3 CONVERGENCE ANALYSIS

In this section, we briefly analyze of the convergence of independent policy gradient in MGs. First, we establish the connection between MGs and MPGs. Then, the convergence follows the results of the convergence of independent policy gradient in MPGs (Leonardos et al., 2022).

Proposition A.1.1. *The finite-agent MG $G(N)$ is an MPG.*

Proof. The key to derive the conclusion is to find a potential function Φ_s, $s \in \mathcal{S}$, such that the condition in Eq. 4 is satisfied. Suppose that in every state $s \in \mathcal{S}$, $G(N)$ is a normal-form potential game with potential function ϕ_s, and each agent i's instantaneous reward is decomposed as

$$r^i(s, \boldsymbol{a}) = \phi_s(\boldsymbol{a}) + u_s^i(\boldsymbol{a}^{-i}), \tag{9}$$

where $u_s^i(\boldsymbol{a}^{-i})$ is a dummy term which only depends on the joint-action of all agents except i. Then, if the following condition holds, the MG $G(N)$ is an MPG:

$$\nabla_{\pi^i(s)} \mathbb{E}_{\tau \sim \boldsymbol{\pi}} \left[\sum_{t=0}^{T} u_{s_t}^i(\boldsymbol{a}_t^{-i}) \Big| s_0 = s' \sim p \right] = c_s \mathbf{1}, \tag{10}$$

for all state $s, s' \in \mathcal{S}$, where $c_s \in \mathbb{R}$ and $\mathbf{1} \in \mathbb{R}^{|\mathcal{A}|}$, $\pi^i(s)$ corresponds to the action distribution of agent i at state s (i.e., the mixed strategy in s), τ is the trajectory when all agents follow the policy $\boldsymbol{\pi}$. For the general case of reward decomposition in Eq. 9, the derivation can be found in (Leonardos et al., 2022), Proposition 3.2.

In the context of our work, as the agents are homogeneous, the instantaneous reward $r^i(s, \boldsymbol{a}) = r(s, a, z_{\boldsymbol{s}_t}^N)$ can be considered as a potential function at each state $s \in \mathcal{S}$, i.e., $\phi_s(\boldsymbol{a}) = r(s, a, z_{\boldsymbol{s}_t}^N)$, while the dummy term is $u_s^i(\boldsymbol{a}^{-i}) \equiv 0$ which trivially satisfies the condition in Eq. 10. Therefore,

$$\Phi_s(\boldsymbol{\pi}) := \mathbb{E}_{\tau \sim \boldsymbol{\pi}} \left[\sum_{t=0}^{T} \phi_{s_t}(\boldsymbol{a}) \Big| s_0 = s \right] \tag{11}$$

is a potential function for $G(N)$, which concludes that the MG $G(N)$ is an MPG. $\square$

Given that $G(N)$ is an MPG, the convergence follows the conclusion in (Leonardos et al., 2022).

Proposition A.1.2. *(Convergence of Independent Policy Gradient, Theorem 1.2 in (Leonardos et al., 2022)) Consider the MG $G(N)$. If each agent runs SGA 8 using direct policy parameterization (Eq. 6) on their policies and that the updates are simultaneous, then the learning converges to an approximate Nash policy.*

Note that the above convergence is established under the direct policy parameterization of $\pi_{\boldsymbol{\theta}}$. In practice, such a choice is typically less expressive than using a neural network to represent the policy. However, establishing convergence guarantee for neural network-type parameterization is extremely hard, if not impossible, because neural networks are typically highly non-linear and non-convex/concave. Nonetheless, empirical verification can be conducted by computing the (approximate) NashConv of a trained policy $\pi_{\boldsymbol{\theta}}$, i.e., if the (approximate) NashConv is 0, then the policy $\pi_{\boldsymbol{\theta}}$ is a Nash policy, regardless of the type of parameterization.

In our experiments, we use neural networks to represent the policies of agents. In this context, as the (approximate) NashConv measures the distance of a policy to the Nash policy, we train/generate a policy that has lower (approximate) NashConv, which shows the potential (though not exact) convergence of our approach.

A.2 CONNECTION BETWEEN MG AND MFG

To facilitate the understanding of our proposal, we give some remarks on the connection between the MG and MFG described in Sec. 3.

We attempt to bridge the two research fields (finite-agent MG and infinite-agent MFG) from a finite-to-infinite perspective. That is, we try to envision how will the policy of an MFG behave by investigating a series of finite-agent MGs. In this sense, the finite-agent MGs we considered should

share a similar structure with the MFG, i.e., all agents are homogeneous. Though such game-level connection between MG and MFG is somewhat implicit, MFG provides us the guidance to generate the "correct" finite-agent MGs, i.e., the games that are different only in the number of agents while other elements such as state and action spaces and reward functions are kept identical. Notice that directly generating a game with an infinite number of agents is impractical as it requires infinite computing resources for simulating the behaviors of an infinite number of agents.

On the policy-level connection, we note that it is not directly comparable between our proposed PAPO and the methods for MFGs. In view of the finite-to-infinite perspective, to implement a fair comparison, naturally we first need to generate a game with an infinite number of agents and then train the networks of PAPO by using the data sampled from this game. However, we can neither generate such a game as it requires infinite computing resources for simulating the behaviors of an infinite number of agents nor train the networks as PAPO will need to take $N = \infty$ as input. In this sense, our experiments do not (or more precisely, cannot) implement such a comparison but provide insights on the relationship between the policies generated by PAPO and the policy of the MFG.

On the other hand, much also can be done from an infinite-to-finite perspective that is opposite to ours. This is grounded on the well-known fact that a policy that gives a mean field equilibrium also gives an $\epsilon(N)$-Nash equilibrium for the corresponding game with N agents, where $\epsilon(N)$ goes to 0 as N goes to infinity (Saldi et al., 2018). In this sense, one can first learn a policy in the MFG (under the assumption that the algorithm has access to a simulator which takes the current state, action, and mean-field as inputs and outputs the reward, next state, and next mean-field (Guo et al., 2019)) and then apply it to the finite-agent games with different N's. Essentially, this is analog to the PPO-Naive mentioned in the Introduction. Differently, here the policy is trained in the MFG while in PPO-Naive it is trained in a finite-agent MG. As a consequence, the (approximate) NashConv could be arbitrarily large when N decreases from large to small (ideally, from $N = \infty$ to $N = 2$). In this sense, it is worth interest to propose novel methods to mitigate the loss of applying the policy learned in the MFG to finite-agent MGs, which we leave for future works.

B MORE DETAILS ON PAPO

In this section, we provide more details on PAPO and practical implementations.

B.1 NETWORK ARCHITECTURE

The embedding layer is a linear layer with 128 neurons. The policy network consists of three fully-connected (FC) layers, each with 128 neurons. The activation between layers is ReLU.

The hypernetwork starts with two FC layers, each with 128 neurons. The activation between layers is ReLU. After the two FC layers, three independent heads are used to generate the parameters of the three layers of the policy network. In each head, three linear layers are used to map the output z of the two FC layers to the weights, biases, and scaling factors. Such an architecture is similar to (Sarafian et al., 2021; Littwin & Wolf, 2019). The generated parameters are reshaped to form the structure of the policy network. Take the hidden layer ($l = 2$) of the policy network as an example. Suppose that the output from the input layer is x and the weights, biases, and scaling factors generated by the head corresponding to the hidden layer are $\boldsymbol{w}_2(z)$, $\boldsymbol{b}_2(z)$, and $\boldsymbol{g}_2(z)$, respectively. Then, the output to the next layer is $x' = \text{ReLU}(x\boldsymbol{w}_2(z) \odot (1 + \boldsymbol{g}_2(z)) + \boldsymbol{b}_2(z))$.

B.2 LOSS FUNCTION

Let $\pi_{\boldsymbol{\theta}}$ and $V_{\boldsymbol{\phi}}$ respectively denote a representative agent's actor and critic ($\pi_{\boldsymbol{\theta}_{\text{old}}}$ and $V_{\boldsymbol{\phi}_{\text{old}}}$ respectively denote the old version of actor and critic which are periodically updated by copying from $\boldsymbol{\theta}$ and $\boldsymbol{\phi}$). Similar to PPO (Schulman et al., 2017), the loss function for PAPO is:

$$L_t(\boldsymbol{\beta}^{\text{A}}, \boldsymbol{\beta}^{\text{C}}) = \mathbb{E}\Big[L_t^1(\boldsymbol{\theta} = h_{\boldsymbol{\beta}^{\text{A}}}(N)) - c_1 L_t^2(\boldsymbol{\phi} = h_{\boldsymbol{\beta}^{\text{C}}}(N)) + c_2 \mathcal{H}(\pi_{\boldsymbol{\theta} = h_{\boldsymbol{\beta}^{\text{A}}}(N)})\Big], \qquad (12)$$

where $h_{\boldsymbol{\beta}^{\text{A}}}$ and $h_{\boldsymbol{\beta}^{\text{C}}}$ are respectively the hypernetworks for generating the actor and critic networks. For notation simplicity, here we use $\boldsymbol{\theta}_N$ and $\boldsymbol{\phi}_N$ to represent $\boldsymbol{\theta} = h_{\boldsymbol{\beta}^{\text{A}}}(N)$ and $\boldsymbol{\phi} = h_{\boldsymbol{\beta}^{\text{C}}}(N)$,

respectively. Then, the three terms in the above equation are:

$$L_t^1(\boldsymbol{\theta} = h_{\boldsymbol{\beta}^{\mathrm{A}}}(N)) = \mathbb{E}\left[\min\left(\frac{\pi_{\boldsymbol{\theta}_N}(a_t|s_t)}{\pi_{\boldsymbol{\theta}_{\mathrm{old}}}(a_t|s_t)} A_t, \mathrm{clip}(\frac{\pi_{\boldsymbol{\theta}_N}(a_t|s_t)}{\pi_{\boldsymbol{\theta}_{\mathrm{old}}}(a_t|s_t)}, 1-\epsilon, 1+\epsilon)A_t \right) \right],$$

$$L_t^2(\boldsymbol{\phi} = h_{\boldsymbol{\beta}^{\mathrm{C}}}(N)) = \left(V_{\boldsymbol{\phi}_N}(s_t) - \sum_{t'=t}^{T} r(s_{t'}, a_{t'}, z_{\boldsymbol{s}_{t'}}^N) \right)^2,$$

$$\mathcal{H}(\pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}^{\mathrm{A}}}(N)}(\cdot|s_t)) = -\mathbb{E}_{a_t \sim \pi_{\boldsymbol{\theta}_N}} \log \pi_{\boldsymbol{\theta}_N}(a_t|s_t),$$

where A_t is the truncated version of generalized advantage estimation:

$$A_t = \delta_t + (\gamma\lambda)\delta_{t+1} + \cdots + (\gamma\lambda)^{T-t}\delta_T \text{ with } \delta_t = r_t + \gamma V_{\boldsymbol{\phi}_N}(s_{t+1}) - V_{\boldsymbol{\phi}_N}(s_t),$$

where $r_t = r(s_t, a_t, z_{\boldsymbol{s}_t}^N)$ and δ_t is the TD error (Sutton & Barto, 2018). The expectation $\mathbb{E}$ is taken on a finite batch of experiences sampled by interacting with the environment.

B.3 TRAINING PROCEDURE

We construct a training procedure where the networks of PAPO are trained by using the data sampled from all the games in the target set G. Specifically, at the beginning of each episode, a game $G(N)$ is uniformly sampled from the target set G. Then, PAPO takes N as input and generates a policy which is used by the agents to interact with the environment for T steps. Next, the T experience tuples of the representative agent are stored in the episode buffer $\mathcal{D}$. Finally, every E episodes, we optimize the surrogate loss function $L_t(\boldsymbol{\beta}^{\mathrm{A}}, \boldsymbol{\beta}^{\mathrm{C}})$ with respect to $\boldsymbol{\beta}^{\mathrm{A}}$ and $\boldsymbol{\beta}^{\mathrm{C}}$ (as well as the embedding layers $\boldsymbol{\eta}^{\mathrm{A}}$ and $\boldsymbol{\eta}^{\mathrm{C}}$) for K epochs with the collected ET experience tuples. As the agents are homogeneous, without loss of generality, we choose $i = 1$ as the representative agent. A more detailed description of the training procedure is shown in Algorithm 1.

Algorithm 1: Training Procedure

Input: Hyperparameters
Output: Trained PAPO

1   $\mathcal{D} \leftarrow \emptyset$;
2   **for** *episode* $= 1, 2, \cdots$ **do**
3   Sample a game $G(N) \sim \mathrm{Uniform}[G]$;
4      $s_0^i \leftarrow s_0, \forall i \in \mathcal{N}$;
5   Generate a policy $\pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}^{\mathrm{A}}}(N)}$;
6   **for** $0 \leq t \leq T$ **do**
7   Sample action $a_t^i \sim \pi_{\boldsymbol{\theta}}(\cdot|s_t^i), \forall i \in \mathcal{N}$;
8   Execute a_t^i in $G(N), \forall i \in \mathcal{N}$;
9   Receive reward $r_t = r(s_t^i, a_t^i, z_{\boldsymbol{s}_t}^N), \forall i \in \mathcal{N}$;
10   Observe new state $s_{t+1}^i, \forall i \in \mathcal{N}$;
11   Store data $\mathcal{D} \leftarrow \mathcal{D} \cup \{(s_t^1, a_t^1, r_t, s_{t+1}^1)\}$;
12   **end**
13   **if** *episode*$\%E = 0$ **then**
14   Update $\boldsymbol{\beta}^{\mathrm{A}}$ and $\boldsymbol{\beta}^{\mathrm{C}}$ (and $\boldsymbol{\eta}^{\mathrm{A}}$ and $\boldsymbol{\eta}^{\mathrm{C}}$) by optimizing L_t for K epochs;
15          $\mathcal{D} \leftarrow \emptyset, \boldsymbol{\theta}_{\mathrm{old}} \leftarrow \boldsymbol{\theta}, \boldsymbol{\phi}_{\mathrm{old}} \leftarrow \boldsymbol{\phi}$;
16   **end**
17   **end**

C EXPERIMENTAL DETAILS

C.1 DETAILS ON GAME ENVIRONMENTS

Exploration (Laurière et al., 2022). Consider a grid environment with size $M \times M$. The state of an agent is his coordinate $s_t = (x, y)$ and available actions are: left, right, up, down, and stay. The agent cannot walk through the walls on the boundaries. Given $s_t = (x, y)$, a_t, and μ_t, the reward for the agent is $r(s_t, a_t, \mu_t) = -\log(\mu_t(s_t))$. In experiments, we set $M = 10$.

Taxi Matching (Nguyen et al., 2018). Consider a grid world environment with size $M \times M$. A set of drivers aim to maximize their own revenue by picking orders distributed over the map. As the demand in different zones is varied (e.g., the demand in downtown is higher than that in residential areas), each driver needs to find an optimal roaming policy while taken the competition with other drivers into consideration. The state of a driver is his coordinate $s_t = (x, y)$ and actions are: left, right, up, down, and stay. Given $s_t = (x, y)$, a_t, and μ_t, the reward for a driver is $r(s_t, a_t, \mu_t) = -o_{s_t} \log(\mu_t(s_t))$, where o_{s_t} denotes the total order price in state s_t. In experiments, we set $M = 10$ and consider that there are 100 orders each with a reward of 1 and distributed over the map according to the Gaussian distribution with the mean at the center of the map.

Crowd in Circle (Perrin et al., 2020). Consider a 1D environment with $M = 20$ states denoted as $\mathcal{S} = \{1, 2, \cdots, |\mathcal{S}| = 20\}$ and form a circle. The available actions for an agent is: left, right, and stay. At each time step t, there is a point of interest (PoI, for short) located at $\bar{s}_t$. Given s_t, a_t, and μ_t, the reward for the agent is $r(s_t, a_t, \mu_t) = -\log(\mu_t(s_t)) + 5 \times \mathbf{1}\{s_t = \bar{s}_t\}$, i.e., the agent gets a reward of 5 when he is located on the PoI while still favoring social distancing. In experiments, we consider two PoIs during an episode: for $t \leq \frac{T}{2}$, $\bar{s}_t = 5$ while for $t > \frac{T}{2}$, $\bar{s}_t = 15$.

C.2 BASELINES

In this section, we give some remarks on the baselines. As the network architecture of PAPO is large (has more learnable parameters), in addition to the standard baselines (PPO and AugPPO), we consider three more baselines: PPO-Large, AugPPO-Large, and HyperPPO (note that HyperPPO has a larger number of learnable parameters than PPO and AugPPO and hence, we regard it as a stronger baseline), which have similar numbers of learnable parameters as PAPO by increasing the number of neurons of the hidden layers of the policy network (PPO-Large and AugPPO-Large) or hypernetwork (HyperPPO). This is critical to ensure a fair comparison and demonstrate the effectiveness of our approach. In Table 1, we give the numbers of learnable parameters of different methods in different environments. As the dimensions of the input and output of different environments are different, the numbers are different (notice that for the same environment, the numbers for different methods should be kept similar). In Table 2, we give the numbers of neurons used in different methods to obtain a similar number of learnable parameters. Note that for HyperPPO and PAPO, we change the two FC layers of the hypernetwork as the policy network structure is fixed.

Table 1: The numbers of learnable parameters of different methods in different environments.

Env./Method	PPO	AugPPO	PPO-Large	AugPPO-Large	HyperPPO	PAPO
Exploration	45K	81K	10,159K	10,457K	10,166K	10,176K
Taxi Matching	44K	80K	5,936K	5,918K	5,883K	5,893K
Crowd in Circle	44K	80K	10,146K	10,444K	9,995K	10,076K

Table 2: The numbers of neurons used in different methods.

Env./Method	PPO-Large	AugPPO-Large	HyperPPO	PAPO
Exploration	(2230, 2230, 2230)	(2200, 2200, 2200)	(128, 220)	(128, 128)
Taxi Matching	(1700, 1700, 1700)	(1635, 1635, 1635)	(128, 128)	(128, 74)
Crowd in Circle	(2230, 2230, 2230)	(2200, 2200, 2200)	(128, 220)	(128, 128)

C.3 HYPERPARAMETERS

Table 3 lists the parameters used in our experiments. Unless otherwise specified, the parameters listed in Table 3 are the same in different game environments. The parameters related to the network architectures can be found in Sec. B.1. The parameters related to the environments can be found in the previous section. Without loss of generality, we evaluate the performance of different methods in a subset: $G' = \{10, 20, \cdots, 200\}$. As for generalization to unseen games, we evaluate the methods

in a set of unseen games: $\tilde{G} = \{220, 240, \cdots, 400\}$. The approximate BR policy is obtained by using (single-agent) PPO. Moreover, all experiments are run on a machine with 20 Intel i9-9820X CPUs and 4 NVIDIA RTX2080 Ti GPUs, and averaged over 3 random seeds.

Table 3: Hyperparameters.

Hyperparameter	Value
optimizer	Adam
length of an episode T	20
minimum number of agents $\underline{N}$	2
maximum number of agents $\bar{N}$	200
maximum number of policy training episodes	$2 \cdot 10^7$
maximum number of BR training episodes	$1 \cdot 10^6$
actor learning rate	$3 \cdot 10^{-5}$
critic learning rate	$3 \cdot 10^{-4}$
update every E episodes	5
optimize K epochs at each update	5
critic loss coefficient c_1	0.5
entropy loss coefficient c_2	0.01
batch size m for computing CKA	1000
dimension of binary encoding k	12

C.4 APPROXIMATE NASHCONV

In this section, we provide more details on how to compute the approximate NashConv. Let $\pi_{\boldsymbol{\theta}_N}$ be the policy returned by a method (PAPO or other baselines) for the given game $G(N)$. According to the definition given in the Sec. 3, the NashConv of this policy is as follows:

$$\text{NASHCONV}(\pi_{\boldsymbol{\theta}_N}) = \sum_{i=1}^{N} \max_{\hat{\pi}^i} V^i(s^i, \hat{\pi}^i, \{\pi^j = \pi_{\boldsymbol{\theta}_N}\}_{j=1, j \neq i}^{N}) - V^i(s^i, \{\pi^i = \pi_{\boldsymbol{\theta}_N}\}_{i=1}^{N}). \quad (13)$$

As the agents are homogeneous, without loss of generality, we compute the NashConv of a representative agent i. Specifically, we first train an approximate BR policy for agent i, denoted as $\pi_{\boldsymbol{\theta}}^{i,\text{BR}}$ (deriving the exact BR policy for the agent i is typically difficult in multi-player games). Then, we compute the approximate NashConv of the agent i as:

$$\text{NASHCONV}^i(\pi_{\boldsymbol{\theta}_N}) = V^i(s^i, \pi_{\boldsymbol{\theta}}^{i,\text{BR}}, \{\pi^j = \pi_{\boldsymbol{\theta}_N}\}_{j=1, j \neq i}^{N}) - V^i(s^i, \{\pi^i = \pi_{\boldsymbol{\theta}_N}\}_{i=1}^{N}). \quad (14)$$

Roughly speaking, the approximate NashConv of agent i is the difference between his value function of following the BR policy $\pi_{\boldsymbol{\theta}}^{i,\text{BR}}$ and his value function of following current policy $\pi_{\boldsymbol{\theta}_N}$, given that the other agents are fixed to the current policy $\{\pi^j = \pi_{\boldsymbol{\theta}_N}\}_{j=1, j \neq i}^{N}$.

C.5 SIMILARITY MEASURE: CENTERED KERNEL ALIGNMENT

In this work, we use centered kernel alignment (CKA) (Kornblith et al., 2019) to measure the similarity between two policies generated by PAPO. Specifically, we aim to compute the similarity measure $\rho(N) = \rho(\pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}}(N)}, \pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}}(N+1)})$. Under CKA, the process is as follows. We randomly sample a batch of m states and fed them into the two generated policies $\pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}}(N)}$ and $\pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}}(N+1)}$. Then, we obtain the output of each layer:

$$X_{\text{input}}^N \in \mathbb{R}^{m \times q_{\text{input}}}, \quad X_{\text{hidden}}^N \in \mathbb{R}^{m \times q_{\text{hidden}}}, \quad X_{\text{output}}^N \in \mathbb{R}^{m \times q_{\text{output}}} \quad (15)$$

for $\pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}}(N)}$ and X_{input}^{N+1}, X_{hidden}^{N+1}, and X_{output}^{N+1} for $\pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}}(N+1)}$, where q_{input}, q_{hidden}, and q_{output} are respectively the number of neurons of input, hidden, and output layers of the policies. Now, we can measure the similarity of each layer between the two generated policies, i.e., we have $\rho_{\text{input}}(N) = \text{CKA}(X_{\text{input}}^N, X_{\text{input}}^{N+1})$, $\rho_{\text{hidden}}(N) = \text{CKA}(X_{\text{hidden}}^N, X_{\text{hidden}}^{N+1})$, and $\rho_{\text{output}}(N) = \text{CKA}(X_{\text{output}}^N, X_{\text{output}}^{N+1})$. Details on the computation of the CKA can be found in (Kornblith et al., 2019).

D MORE EXPERIMENTAL RESULTS

In this section, we provide more results and analysis to deepen the understanding of our approach.

D.1 TRAINING CURVES

In Fig. 6, we present the training curves of different methods in different environments. From the results, we can see that all methods have converged after a sufficient number of training episodes $(2 \cdot 10^7)$. Notice that theoretically computing the exact Nash policy is typically difficult in multiplayer games, if not impossible. In this sense, we would expect the methods to return an approximate Nash policy, given that they are trained with a large enough training budget.

During evaluation in a given game, we train a new PPO as the representative agent's BR policy while other agents are fixed to execute the approximate Nash policy. From the representative agent's perspective, the environment is stationary and hence, the problem of learning the BR policy is reduced to an RL problem. In Fig. 7, we present the BR training curves of different methods in a given game. As we can see, the BR training curves have approximately converged, ensuring that the computed approximate NashConv is a reasonable metric to assess the quality of learning.

Figure 6: Training curves of different methods in different environments.

Figure 7: BR training curves of different methods in different environments ($N = 10$).

D.2 CKA ANALYSIS

In this section, we provide a more detailed analysis on the CKA values. In Fig. 3 (B), we consider the function $\rho(N)$ with the form of $\rho(N) = 1 - \frac{a}{N^b}$. In fact, there could be different forms of $\rho(N)$. Intuitively, the most general case is $\rho(N) = 1 - \frac{a}{cN^b+d}$. Note that we choose the function such that it is upper-bounded by 1 because it coincides with the intuition that when N goes to infinity, the similarity between two policies goes to 1. However, for the most general case, by computing the p-values, we found that some parameters (c and d) are less significant and hence, can be removed from $\rho(N)$. In Fig. 8, we show the curves and in Table 4, we present the values of the parameters and their p-values. We can see that, in most cases, only the parameter b has a significant influence on the curve fitting, i.e., has a small p-value. As a result, in Fig. 3 (B), we consider that $\rho(N) = 1 - \frac{a}{N^b}$ and from the results we can see that the two parameters (a and b) are statistically significant, which means that this simpler formula is sufficient to quantitatively characterize the evolution of the CKA values over the population size.

Figure 8: CKA values versus population size. $\rho(N) = 1 - \frac{a}{cN^b+d}$.

Table 4: Values of parameters in $\rho(N) = 1 - \frac{a}{cN^b+d}$ in different game environments.

Exploration				
Layer	$a(p)$	$b(p)$	$c(p)$	$d(p)$
ρ_{input}	$3.81e^{-6}\ (0.97)$	$3.92e^{-5}\ (0.97)$	$4.68e^{+0}\ (\underline{0.00})$	$-4.68e^{+0}\ (\underline{0.00})$
ρ_{hidden}	$4.09e^{-1}\ (0.99)$	$6.74e^{-1}\ (\underline{0.00})$	$2.98e^{+0}\ (0.99)$	$-3.63e^{+0}\ (0.99)$
ρ_{output}	$4.22e^{+0}\ (0.99)$	$8.93e^{-1}\ (\underline{0.00})$	$1.02e^{+1}\ (0.99)$	$-1.09e^{+1}\ (0.99)$

Taxi Matching				
Layer	$a(p)$	$b(p)$	$c(p)$	$d(p)$
ρ_{input}	$8.96e^{-3}\ (0.99)$	$1.11e^{+1}\ (\underline{0.09})$	$5.71e^{+0}\ (0.99)$	$-6.09e^{+0}\ (0.99)$
ρ_{hidden}	$2.90e^{-2}\ (0.99)$	$1.28e^{-1}\ (\underline{0.16})$	$2.32e^{+0}\ (0.99)$	$-2.44e^{+0}\ (0.99)$
ρ_{output}	$8.43e^{-1}\ (0.99)$	$4.52e^{-1}\ (\underline{0.02})$	$1.84e^{+0}\ (0.99)$	$+6.26e^{-1}\ (0.99)$

Crowd in Circle				
Layer	$a(p)$	$b(p)$	$c(p)$	$d(p)$
ρ_{input}	$-2.95e^{-4}\ (0.91)$	$-7.77e^{-1}\ (\underline{0.16})$	$1.75e^{+0}\ (0.91)$	$-1.62e^{+0}\ (0.91)$
ρ_{hidden}	$+1.49e^{-4}\ (0.99)$	$+2.65e^{-4}\ (0.99)$	$1.46e^{+1}\ (0.99)$	$-1.45e^{+1}\ (0.99)$
ρ_{output}	$-5.13e^{-2}\ (0.99)$	$-3.43e^{-1}\ (\underline{0.47})$	$1.05e^{+1}\ (0.99)$	$-1.32e^{+1}\ (0.99)$

D.3 REPRESENTATIONS OF GAME STATES

In this section, we provide more results of the representations of different game states. To this end, we first manually construct some natural and understandable game states according to the position of an agent on the map/circle. For example, the game state "Bottom-left" means the agent is located on the bottom-left of the map at any time. In Fig. 9 – Fig. 11, we show the UMAP embeddings of different game states. We found that the UMAP embeddings of some game states (e.g., bottom-left and upper-right in Exploration, bottom-left and bottom-right in Taxi Matching, center in Crowd in Circle) present a similar trend as mentioned in the main text while the UMAP embeddings of other game states do not have clear patterns. We hypothesize that some manually constructed high-level (coarse-grained) game states may consist of very different underlying (fine-grained) states of the agents. On the other hand, to some extent, the results imply that our PAPO may not be a smooth enough function of the population size. In this sense, in future works, proposing novel techniques to drift PAPO toward a smoother function of the population size is worth interesting and may further improve the performance of PAPO, making it a more elegant solution.

Figure 9: UMAP embeddings of different game states in Exploration.

Figure 10: UMAP embeddings of different game states in Taxi Matching.

Figure 11: UMAP embeddings of different game states in Crowd in Circle.

D.4   EFFECT OF POPULATION-SIZE ENCODING

In this section, we provide more analysis to explore the effect of population-size encoding on the training process. It is well known that increasing the entropy of a policy at the beginning of training can incentivize it to explore the environment more widely and in turn improve the overall performance of the policy (Haarnoja et al., 2018; Ahmed et al., 2019). In this sense, given the initialized PAPO, then we expect that the generated policies have high entropy, regardless of the input population size. More precisely, given any N, the generated policy $\pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}}(N)}$ by the initialized PAPO would output an approximate uniform distribution over the action space $\mathcal{A}$ for a given state s_t. Let $\hat{\pi}$ be the uniform policy, i.e., $\hat{\pi}(a|s_t) = \frac{1}{|\mathcal{A}|}$ for all $a \in \mathcal{A}$. We can compute the KL-divergence between $\pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}}(N)}$ and $\hat{\pi}$, denoted as $\kappa(N) = \mathrm{D}_{\mathrm{KL}}(\pi_{\boldsymbol{\theta}=h_{\boldsymbol{\beta}}(N)}\|\hat{\pi})$. Then, intuitively, at the beginning of training, $\kappa(N)$ is near 0 for different N's. After the neural networks of PAPO are well trained, $\kappa(N)$ will be larger than 0 and vary with N.

In Fig. 12, we present the results to verify the aforementioned conclusions. From the results, we can see that, when using RE, the approximate uniform action distribution only holds for small N's, as shown in the first row. However, $\kappa(N)$ quickly increases when N is increasing, which could severely hamper the training of PAPO (see the comparison between "PAPO w/ RE (initial)" and "PAPO w/ RE (trained)"). In striking contrast, using BE can effectively avoid such a training collapse.

Figure 12: The KL divergence κ versus population size.

D.5 REWARD DISTRIBUTION SHIFT

One of the reasons we hypothesize why PPO performs poorly across different games is the reward distribution shift in the environments. To verify the intuition, for an environment, we use a randomly initialized policy to sample 1,000 trajectories (episodes) and get the reward distribution by statistics. As shown in Fig. 13–Fig. 15, the reward distribution varies sharply with the increasing population size. Intuitively, PPO works poorly across the games as it does not consider the increasing diversity of reward signals resulting from the changes in population size. In contrast, PAPO (and other population-size aware methods) posses the ability to work consistently well across different games by explicitly taking the information of the population size into account during training.

Figure 13: Sampled reward distributions and trajectories in Exploration.

Figure 14: Sampled reward distributions and trajectories in Taxi Matching.

Figure 15: Sampled reward distributions and trajectories in Crowd in Circle.