MetaGFN: Exploring Distant Modes with Adapted Metadynamics for Continuous GFlowNets

Abstract

Generative Flow Networks (GFlowNets) are a class of generative models that sample objects in proportion to a specified reward function through a learned policy. They can be trained either on-policy or off-policy, needing a balance between exploration and exploitation for fast convergence to a target distribution. While exploration strategies for discrete GFlowNets have been studied, exploration in the continuous case remains to be investigated, despite the potential for novel exploration algorithms due to the local connectedness of continuous domains. Here, we introduce Adapted Metadynamics, a variant of metadynamics that can be applied to arbitrary black-box reward functions on continuous domains. We use Adapted Metadynamics as an exploration strategy for continuous GFlowNets. We show several continuous domains where the resulting algorithm, MetaGFN, accelerates convergence to the target distribution and discovers more distant reward modes than previous off-policy exploration strategies used for GFlowNets.

1 Introduction

Generative Flow Networks (GFlowNets) are a type of generative model that samples from a discrete space $\mathcal{X}$ by sequentially constructing objects via actions taken from a learned policy P_F (Bengio et al., 2021a). The policy $P_F(s, s')$ specifies the probability of transitioning from some state s to some other state s'. The policy is parameterised and trained so that, at convergence, the probability of sampling an object $x \in \mathcal{X}$ is proportional to a specified reward function $R(x)$. GFlowNets offer advantages over more traditional sampling methods, such as Markov chain Monte Carlo (MCMC), by learning an amortised sampler, capable of single-shot generation of samples from the desired distribution. Since GFlowNets learn a parametric policy, they can generalise across states, resulting in higher performance across various tasks (Bengio et al., 2021a; Malkin et al., 2022; Zhang et al., 2022; Jain et al., 2022; Deleu et al., 2022; Jain et al., 2023; Hu et al., 2023; Zhang et al., 2023; Shen et al., 2023b) and applications to conditioned molecule generation (Shen et al., 2023b), maximum likelihood estimation in discrete latent variable models (Hu et al., 2023), structure learning of Bayesian networks (Deleu et al., 2022), scheduling computational operations (Zhang et al., 2023), and discovering reticular materials for carbon capture (Cipcigan et al., 2023).

Although originally conceived for discrete state spaces, GFlowNets have been extended to more general state spaces, such as entirely continuous spaces, or spaces that are hybrid discrete-continuous (Lahlou et al., 2023). In the continuous setting, given the current state, the policy specifies a continuous probability distribution over subsequent states, and the probability density over states $x \in \mathcal{X}$ sampled with the policy is proportional to a reward density function $r(x)$. The continuous domain unlocks more applications for GFlowNets, such as molecular conformation sampling (Volokhova et al., 2023) and continuous control problems (Luo et al., 2024).

GFlowNets are trained like reinforcement learning agents. Trajectories of states are generated either on-policy or off-policy, with the terminating state $x \in \mathcal{X}$ providing a reward signal for informing a gradient step on the policy parameters. GFlowNets therefore suffer from the same training pitfalls as reinforcement learning. One such issue is slow temporal credit assignment, which has thus far been addressed by designing more effective loss functions, such as detailed balance (Bengio et al., 2021b), trajectory balance (Malkin et al., 2022) and sub-trajectory balance (Madan et al., 2022). This

latter approach has recently been extended by providing an energy function inductive bias at the early stages of training (Pan et al., 2023).

Besides loss functions, another aspect of GFlowNet training is the exploration strategy for acquiring training samples. Exclusively on-policy learning is generally inadequate as it leads to inefficient exploration of new modes. More successful strategies therefore rely on off-policy exploration. For the discrete setting, numerous exploration strategies have been proposed including ϵ-noisy with a uniform random policy, tempering, Generative Augmented Flow Networks (GAFN) (Pan et al., 2022), Thompson sampling (Rector-Brooks et al., 2023) and Local Search GFlowNets (Kim et al., 2024). While these approaches can be generalised to the continuous domain, there is limited literature benchmarking their effectiveness in this setting.

Sampling in the continuous setting is a common occurrence in various domains such as molecular modelling (Hawkins, 2017; Yang et al., 2019) and Bayesian inference (Shahriari et al., 2016). The local connectedness of a continuous domain allows for novel exploration strategies that are not directly applicable in the discrete setting. Sendera et al. (2024) compared several exploration strategies in the context of diffusion samplers, and proposed alternating between on-policy sampling and backward sampling from a fixed set of MCMC samples when training continuous GFlowNets. These samples were selected prior to training, thereby inducing a fixed pre-training cost but keeping the cost of each training trajectory constant. The authors showed effective exploration, even in high-dimensional problems. However, their MCMC approach requires access to cheap gradients of the reward landscape, which might not always be readily available (Rengarajan et al., 2022). In addition, there are some settings, such as in molecular conformation sampling, where MCMC approaches are known to require significantly longer timescales to overcome energy barriers than methods based on molecular dynamics (MD) simulations (Abrams and Bussi, 2014), thereby making the pre-training cost prohibitively expensive.

In this work, we propose MetaGFN, a novel exploration algorithm for continuous GFlowNets inspired by metadynamics, an enhanced sampling method widely used for molecular modelling (Laio and Parrinello, 2002). Unlike MCMC-based sampling methods, MetaGFN operates in a general black-box setting, relying solely on an oracle for reward values, without requiring access to reward gradients. In common with standard metadynamics, MetaGFN converges quickly when a reduced-dimensional representation of the reward measure, specified by a so-called collective variable (CV) basis, is known. While our method is domain-agnostic, this feature makes MetaGFN particularly well-suited for small molecular systems, where such representations are known and often low-dimensional (Fiorin et al., 2013). MetaGFN requires no pre-training and only introduces a small, constant cost for each training trajectory, which becomes negligible as the cost of reward evaluation increases.

The main contributions of this work are:

- Introducing MetaGFN, an algorithm that adapts metadynamics to black box rewards and continuous GFlowNets;
- Proving that the Adapted Metadynamics formulation underlying MetaGFN is consistent and reduces to standard metadynamics in the appropriate limit;
- Showing empirically that MetaGFN outperforms existing GFlowNets exploration strategies in various continuous environments, including alanine dipeptide conformation sampling.

The rest of the paper is as follows. In Section 2 we review the theory of discrete and continuous GFlowNets. In Section 3, we present the concept of collective variables, as well as Adapted Metadynamics and MetaGFN. In Section 4, we evaluate MetaGFN against other approaches, showing that MetaGFN generally outperforms existing exploration strategies in various continuous environments. We finish with limitations and conclusions in Sections 5 and 6. Code for MetaGFN is available at [link in camera-ready].

2 PRELIMINARIES

2.1 DISCRETE GFLOWNETS

In a GFlowNet, the *network* refers to a directed acyclic graph (DAG), denoted as $G = (\mathcal{S}, \mathcal{A})$. Nodes represent *states* $s \in \mathcal{S}$, and edges represent *actions* $s \to s' \in \mathcal{A}$ denoting one-way transitions between

states. The DAG has two distinguishable states: a unique *source state* s_0, that has no incoming edges, and a unique *sink state* $\perp$, that has no outgoing edges.

The set of states, $\mathcal{X} \subset \mathcal{S}$, that are directly connected to the sink state are known as *terminating states*. GFlowNets learn forward transition probabilities, known as a *forward policy* $P_F(s'|s)$, along the edges of the DAG so that the resulting marginal distribution over the terminal states complete trajectories (the *terminal distribution*), denoted as $P^\perp(x)$, is proportional to a given *reward function* $R : \mathcal{X} \to \mathbb{R}$. GFlowNets also introduce additional learnable objects, such as a *backward policy* $P_B(s|s')$, which is a distribution over the parents of any state of the DAG, to create losses that train the forward policy. Objective functions for GFlowNets include flow matching (FM), detailed balance (DB), trajectory balance (TB) and subtrajectory balance (STB) (Bengio et al., 2021a;b; Malkin et al., 2022; Madan et al., 2022). During training, the parameters of the flow objects are updated with stochastic gradients of the objective function applied to batches of trajectories. These trajectory batches can be obtained either directly from the current forward policy or from an alternative algorithm that encourages exploration. These approaches are known as *on-policy* and *off-policy* training respectively.

2.2 CONTINUOUS GFLOWNETS

Continuous GFlowNets extend the generative problem to continuous spaces (Lahlou et al., 2023), where the analogous quantity to the DAG is a measurable pointed graph (MPG) (Nummelin, 1984). MPGs can model continuous spaces (e.g., Euclidean space, spheres, tori), as well as hybrid spaces, with a mix of discrete and continuous components, as often encountered in robotics, finance, and biology (Bortolussi and Policriti, 2008; Swiler et al., 2012; Neunert et al., 2020).

Definition 2.1 (Measurable pointed graph (MPG)). Let $(\bar{\mathcal{S}}, \mathcal{T})$ be a topological space, where $\bar{\mathcal{S}}$ is the *state space*, $\mathcal{T}$ is the set of open subsets of $\bar{\mathcal{S}}$, and Σ is the Borel σ-algebra associated with the topology of $\bar{\mathcal{S}}$. Within this space, we identify the *source state* $s_0 \in \bar{\mathcal{S}}$ and *sink state* $\perp \in \bar{\mathcal{S}}$, both distinct and isolated from the rest of the space. On this space we define a *reference transition kernel* $\kappa : \bar{\mathcal{S}} \times \Sigma \to [0, +\infty)$ and a *backward reference transition kernel* $\kappa^b : \bar{\mathcal{S}} \times \Sigma \to [0, +\infty)$. The support of $\kappa(s, \cdot)$ are all open sets accessible from s. The support of $\kappa^b(s, \cdot)$ are all open sets where s is accessible from. Additionally, these objects must be well-behaved in the following sense:

  (i) *Continuity*: For all $B \in \Sigma$, the mapping $s \mapsto \kappa(s, B)$ is continuous.

 (ii) *No way back from the source*: The backward reference kernel has zero support at the source state, i.e. for all $B \in \Sigma$, $\kappa^b(s_0, B) = 0$.

(iii) *No way forward from the sink*: When at the sink, applying the forward kernel keeps you there, i.e. $\kappa(\perp, \cdot) = \delta_\perp(\cdot)$, where $\delta_\perp$ is the Dirac measure of the sink state.

(iv) *A fully-explorable space*: The maximum number of steps required to certainly reach any measurable $B \in \Sigma$ from the source state with the forward reference kernel is bounded.

The set of objects $(\bar{\mathcal{S}}, \mathcal{T}, \Sigma, s_0, \perp, \kappa, \kappa^b)$ then defines an MPG.

Note that the support of $\kappa(s, \cdot)$ and $\kappa^b(s, \cdot)$ are analogous to the child and parent sets of a state s in a DAG. Similarly, a discrete GFlowNet's DAG satisfies discrete versions of (ii), (iii), and (iv).

The set of *terminating states* $\mathcal{X}$ are the states that can transition to the sink, given by $\mathcal{X} = \{s \in \mathcal{S} : \kappa(s, \{\perp\}) > 0\}$, where $\mathcal{S} := \bar{\mathcal{S}} \setminus \{s_0\}$. *Trajectories* τ are sequences of states that run from source to sink, $\tau = (s_0, \ldots, s_n, \perp)$. The *forward Markov kernel* $P_F : \bar{\mathcal{S}} \times \Sigma \to [0, \infty)$ and *backward Markov kernel* $P_B : \bar{\mathcal{S}} \times \Sigma \to [0, \infty)$ have the same support as $\kappa(s, \cdot)$ and $\kappa^b(s, \cdot)$ respectively, where being a Markov kernel means states are mapped to probability measure, hence $\int_{\bar{\mathcal{S}}} P_F(s, ds') = \int_{\bar{\mathcal{S}}} P_B(s, ds') = 1$. A *flow* F is a tuple $F = (f, P_F)$, where $f : \Sigma \to [0, \infty)$ is a *flow measure*, satisfying $f(\{\perp\}) = f(s_0) = Z$, where Z is the *total flow*.

The *reward measure* is a positive and finite measure R over the terminating states $\mathcal{X}$, we denote the density of this reward measure as $r(x)$, for $x \in \mathcal{X}$. A flow F is said to satisfy the *reward-matching conditions* if

$$R(dx) = f(dx)P_F(x, \{\perp\}).$$

If a flow satisfies the reward-matching conditions and trajectories are recursively sampled from the Markov kernel P_F starting at s_0, the resulting *measure over terminating states*, $P^\perp(B)$, is proportional to the reward: $P^\perp(B) = \frac{R(B)}{R(\mathcal{X})}$ for any B in the σ-algebra of terminating states (Lahlou et al., 2023).

Objective functions for discrete GFlowNets generalise to continuous GFlowNets. However, in the continuous case, the *forward policy* $\hat{p}_F : \mathcal{S} \times \bar{\mathcal{S}} \to [0, \infty)$, *backward policy* $\hat{p}_B : \mathcal{S} \times \bar{\mathcal{S}} \to [0, \infty)$ and *parameterised flow* $\hat{f} : \mathcal{S} \to [0, \infty)$ parameterise the P_F, P_B transition kernels and flow measure f on an MPG. Discrete GFlowNets parameterise log transition probabilities and flows on a DAG. In this work, we consider DB, TB and STB losses. For a complete trajectory τ, the TB loss can be written as

$$L_{TB}(\tau) = \left(\log \frac{Z_\theta \prod_{t=0}^{n} \hat{p}_F(s_t, s_{t+1}; \theta)}{r(s_n) \prod_{t=0}^{n-1} \hat{p}_B(s_{t+1}, s_t; \theta)} \right)^2,$$

where Z_θ is the parameterised total flow (see Appendix A for the DB and STB loss functions).

2.3 EXPLORATION STRATEGIES FOR GFLOWNETS

GFlowNets can reliably learn using off-policy trajectories, a key advantage over hierarchical variational models (Malkin et al., 2023). For optimal training, it is common to use a replay buffer and alternate between on-policy and off-policy (exploration) batches (Shen et al., 2023a). In the discrete case, proposed techniques to encourage exploration include ϵ-noisy exploration, tempering and the incorporation of intermediate rewards (Bengio et al., 2021a; Pan et al., 2022). Exploration strategies for continuous GFlowNets are less well studied in the literature but several methods designed for discrete GFlowNets can be adapted (Sendera et al., 2024). In this work, we consider:

Local Search GFlowNets (Kim et al., 2024): Explores by backtracking and resampling on-policy trajectories. Reconstructed trajectories with a higher reward than the original are used for training, thus encouraging the learning of high-reward modes.

Thompson sampling. (Rector-Brooks et al., 2023): Explores high-uncertainty regions by using an ensemble of policy heads with a shared torso. A random head generates the on-policy trajectory, and the loss is computed by averaging contributions over heads, where each head is independently included with probability p.

Noisy exploration: Explores by increasing policy uncertainty. A small constant is added to the policy variance which is gradually reduced to zero over the course of training.

Nested Sampling (Lemos et al., 2023): A Markov-Chain Monte Carlo (MCMC) algorithm is used to sample from the reward distribution. Backward sampling from these terminal states are used to generate off-policy trajectories.

2.4 METADYNAMICS AND COLLECTIVE VARIABLES

Molecular dynamics (MD) simulates that dynamics of molecules using *Langevin dynamics* (LD) (Pavliotis, 2014), a stochastic differential equation that models particle motion under friction and random noise. LD trajectories ergodically sample the molecule's Gibbs measure, $\rho_\beta(x) \propto e^{-\beta V(x)}$, where $x \in \mathcal{X}$ represents atomic positions, $V(x)$ is the molecular potential, and β is the thermodynamic beta.[1] However, when $V(x)$ contains multiple, deep local minima, as is common in biomolecules, then LD becomes inefficient, as it tends to get trapped in these minima, slowing exploration of the full state space.

Metadynamics overcomes this by progressively modifying the potential landscape to discourage visits to already-explored regions (Laio and Parrinello, 2002). It achieves this by regularly depositing repulsive Gaussian biases, centered at the current state of the evolving LD trajectory. This modifies the potential to $V_{\text{total}}(x, t) = V(x) + V_{\text{bias}}(x, t)$, where $V_{\text{bias}}(x, t)$ is the cumulative bias at time t. Intuitively, metadynamics thus progressively transforms the landscape into more level surface, in which the system can diffuse more freely, thereby accelerating exploration (Figure 1). In the limit $t \to \infty$, the dynamics approximates free diffusion and uniformly samples the domain of $V(x)$.

---

[1]We review Langevin dynamics in Appendix B.

Figure 1: Illustration of metadynamics in a multi-well potential. Regular deposition of a bias leads to a total potential that gradually flattens, encouraging exploration.

Since biases are typically specified on a numerical grid, this gives rise to a memory cost that grows exponentially with dimension. Therefore, biases are typically applied along low-dimensional coordinates known as *collective variables* (CVs). A collective variable $z(x) : \mathcal{X} \to \mathcal{Z}$ is any mapping from the original (high-dimension) state space $\mathcal{X}$ to a lower-dimensional space $\mathcal{Z}$. For potential $V(x)$ and collective variables z, metadynamics is guaranteed to eventually uniformly sample the domain of the *marginal potential* $V(z') := \int_{\mathcal{X}} \delta(z' - z(x)) V(x) \mathrm{d}x$. In molecular contexts, ideal choices of CVs correspond to the physical reaction coordinates that underly rare-event transitions (e.g. backbone dihedrals, interatomic distances) (Laio and Gervasio, 2008; De Vivo et al., 2016). In more general settings, ideal CVs should resolve rare events dynamics on $V(x)$, simplfy the landscape (retaining its essential features e.g. barriers and basins), and minimise the dimensionality of this representation. For simple systems, CVs can be derived from known symmetries or macroscopic order parameters that describe state changes. However, if the choice of CVs is not obvious, then they can learnt through data-driven methods such as Time-Lagged Independent Component Analysis (TICA) (Molgedey and Schuster, 1994), manifold learning algorithms, neural network autoencoders or variational methods (Mardt et al., 2018; Bonati et al., 2021; Ramaswamy et al., 2021). For an in-depth review on these CV-learning approaches, see Sidky et al. (2020). Metadynamics has seen numerous extensions (Bussi and Laio, 2020). In the next section, we adapt the original metadynamics algorithm to the continuous black box setting. We will assume suitable CVs are given, but the theory we present is agnostic to their form–be it analytical expressions, neural networks, or non-parametric tabular mappings.

3 METAGFN: ADAPTED METADYNAMICS FOR GFLOWNETS

Metadynamics has two properties that make it well-suited as an exploration strategy for continuous GFlowNets. Firstly, the guarantee of eventually uniformly sampling the domain ensures exploration of *all* local minima. In contrast, techniques such as Local Search GFlowNets, Thompson Sampling, and noisy exploration rely on localised strategies that are prone to mode locking (Section 4). Secondly, since metadynamics gradually diffuses away from the starting configuration, it incrementally explores the reward landscape. This can result in more stable training dynamics than exploration strategies that take a global approach, such as Nested Sampling. With this intuition in mind, we outline below how to adapt metadynamics to the black-box reward setting. We call the exploration algorithm *Adapted Metadynamics* (AM) (Section 3.1) and associated training algorithm *MetaGFN* (Section 3.2).

Interpreting reward density as a potential: We assume that $\mathcal{X}$ is a manifold and that the reward density $r(x)$ is bounded and L1-integrable over $\mathcal{X}$ with at most finitely many discontinuities. Thus, the target density over terminal states, $\rho(x) := r(x)/\int_{\mathcal{X}} r(x')\, dx'$, can be expressed as a Gibbs distribution: $\rho(x) = \exp(-\beta' V(x))/\int_{\mathcal{X}} r(x')\, dx'$, where we identify $V(x) = -\frac{1}{\beta'} \ln r(x)$ as the corresponding potential, for some constant scalar $\beta' > 0$. Reward maxima thus correspond to potential energy minima. From simplicity, we set β' equal to the thermodynamic beta (β). Making this choice means that the single parameter β uniquely controls the (unbiased) transition rates between minima of the potential[2]. **Our goal is to use metadynamics to explore $V(x)$, generating high-reward terminal states that guide the GFlowNet to sample all reward density modes.**

---

[2]From the Kramer formula; transition rate $\propto \frac{1}{\beta} \exp(\beta \Delta V)$, where $\Delta V \propto \frac{1}{\beta'} = \frac{1}{\beta}$.

Algorithm 1: Adapted Metadynamics

Input : Manifold environment of terminating states $\mathcal{X}$ with reward density $r : \mathcal{X} \to \mathbb{R}$.
Initial state $(x_t, p_t) \in \mathcal{X} \times T_{x_t}(\mathcal{X})$. Collective variables $z = (z_1, \ldots, z_d)$.
Parameters : Gaussian width $\sigma = (\sigma_1, \ldots, \sigma_d) \in \mathbb{R}^d$. Gaussian height $w > 0$. Stride $n \in \mathbb{Z}^+$.
LD parameters: γ, β. Timestep Δt.

1   $\hat{N} \leftarrow 0$

2   $\hat{R} \leftarrow 0$

3   $\hat{V}(z) \leftarrow 0$

4   $V_{\text{bias}}(z) \leftarrow 0$

5   **every** timestep Δt:

6      $z_t \leftarrow z(x_t)$

7   **every** n timesteps $n\Delta t$:

8         $\hat{N} \leftarrow \hat{N} + \exp\left(-\frac{1}{2}\sum_{i=1}^{d}\frac{(z_i - z_{i,t})^2}{\sigma_i^2}\right)$

9         $\hat{R} \leftarrow \hat{R} + r(x_t) \cdot \exp\left(-\frac{1}{2}\sum_{i=1}^{d}\frac{(z_i - z_{i,t})^2}{\sigma_i^2}\right)$

10        $\hat{V} \leftarrow -\frac{1}{\beta} \log\left(\hat{R}/(\hat{N} + \epsilon) + \epsilon\right)$

11        $V_{\text{bias}}(z) \leftarrow V_{\text{bias}}(z) + n \cdot \Delta t \cdot w \cdot \exp\left(-\frac{1}{2}\sum_{i=1}^{d}\frac{(z_i - z_{i,t})^2}{\sigma_i^2}\right)$

12   **compute** forces:

13        $F \leftarrow -\left(\nabla_z \hat{V}(z)|_{z=z_t} + \nabla_z V_{\text{bias}}(z)|_{z=z_t}\right) \cdot \nabla_x z|_{x=x_t}$

14

   propagate x_t, p_t by Δt using Langevin dynamics with computed force F (Alg. 3, Appendix B).

3.1 ADAPTED METADYNAMICS

Metadynamics requires the gradient of the total potential, where $-\nabla V_{\text{total}}(x, t) = -\nabla(V(x) + V_{\text{bias}}(x, t))$. Using the above assumptions, we have $\nabla V(x) = -\nabla r(x)/(\beta' r(x))$. However, $r(x)$ is often a computationally expensive black-box function, and its gradient, $\nabla r(x)$, is unknown. While finite differences can estimate $\nabla r(x)$ for smooth, low-dimensional reward distributions, this approach is impractical in high-dimensional spaces. Below, we explain how to adapt metadynamics to this black-box setting and avoid finite difference gradient estimates by storing a dynamically-updated kernel density estimate (KDE) of the potential. We call the modified metadynamics algorithm *Adapted Metadynamics* (Algorithm 1).

Let x_t denote the metadynamics sample at time t and $z(x) = (z_1(x), \ldots, z_d(x))$ be a given set of collective variables, where z_i is a one-dimensional coordinate, and $z \in \mathcal{Z}$ is d-dimensional. Let $z_{i,t} := z_i(x_t)$ denote the corresponding i^{th} CV coordinate at time t and assume that the Jacobian $\nabla_x z$ is well-defined. We store a discretisation of the KDE marginal potential and bias potentials in CV space $\mathcal{Z}$. Since these are stored in memory, gradient computations are cheap and require no further evaluations of $r(x)$.

Let $\hat{V}(z, t)$ represent the KDE of the marginal potential at time t. To compute $\hat{V}(z, t)$, we maintain two separate KDEs: $\hat{N}(z, t)$ for visited states (line 8) and $\hat{R}(z, t)$ for cumulative rewards (line 9). We update these KDEs on-the-fly at the same time the bias potential is updated, which occurs every integer n steps of Langevin dynamics (line 7). If $\mathcal{Z} \cong \mathbb{R}^d$, we use Gaussian kernels with kernel width $\sigma = (\sigma_1, \ldots, \sigma_k) \in \mathbb{R}^k$, matching the width of the Gaussian bias (line 11)[3]. This is a reasonable as both are set by the variability length scale of $V(x)$. Finally, the KDE potential $\hat{V}(z, t)$ is then computed as $\hat{V}(z, t) = -\frac{1}{\beta} \log\left(\frac{\hat{R}(z,t)}{\hat{N}(z,t)+\epsilon} + \epsilon\right)$, for a fixed constant $\epsilon > 0$ (line 10). We found empirically that ϵ ensured numerical stability by preventing division by zero and bounding $\hat{V}$ from above. Defining $\hat{V}$ through the ratio $\hat{R}/\hat{N}$ ensures that it rapidly and smoothly adjusts whenever new modes are discovered. Furthermore, we prove that $\hat{V}$ eventually discovers *all* reward modes in the CV space. More precisely,

---

[3] If $\mathcal{Z} \cong \mathbb{T}^d$ (d-torus), we use von Mises distributions.

Theorem 3.1. *If the collective variable $z(x)$ is analytic with a bounded domain, then*

$$\lim_{\epsilon \to 0} \left(\lim_{\sigma \to 0} \left(\lim_{t \to \infty} \hat{V}(z, t) \right) \right) = V, \tag{1}$$

where $V = V(z') := \int_{\mathcal{X}} \delta(z' - z(x)) V(x) \mathrm{d}x$.

The proof is in Appendix C.

Note that the algorithm can be extended to a batch of trajectories, where each metadynamics trajectory evolves independently, but with a shared $\hat{V}$ and V_{bias} which receive updates from every trajectory in the batch. We found empirically that this accelerates exploration and reduces stochastic gradient noise during training and this is the version we use in our experiments (Section 4).

3.2 METAGFN

Each Adapted Metadynamics sample $x_i \in \mathcal{X}$ is an off-policy terminal state sample. To train a GFlowNet, complete trajectories are required. We generate these by backward sampling from the terminal state, giving a trajectory $\tau = (s_0, s_1, \ldots, s_n = x_i)$, where each state s_{i-1} is sampled from the current backward policy distribution $\hat{p}_B(s_{i-1}|s_i; \theta)$, for i from n to 1. This approach means that the generated trajectory τ has reasonable credit according to the loss function, thereby providing a useful learning signal. However, since this requires a backward policy, this is compatible with DB, TB, and STB losses, but not FM loss. Given the superior credit assignment of the former losses, this is not a limitation (Madan et al., 2022).

Additionally, we use a replay buffer. Due to the theoretical guarantee that Adapted Metadynamics will eventually sample all collective variable space (Theorem 3.1), AM samples are ideal candidates for storing in a replay buffer. When storing these trajectories in the replay buffer, there are two obvious choices:

1. Store the entire trajectory the first time it is generated;

2. Store only the Adapted Metadynamics sample and regenerate trajectories using the current backward policy when retrieving from the replay buffer.

We investigate both options in our experiments. We call the overall training algorithm *MetaGFN*, with pseudocode presented in Algorithm 2, below.

Algorithm 2: MetaGFN

Input   : Forward policy P_F. Backwards policy P_B. Loss function L.
Parameters : How often to run Adapted Metadynamics batches, `freqMD`. How often to run
                replay buffer batches, `freqRB`. Batch size, b. Stride, $n \in \mathbb{Z}^+$. Time step, $\Delta t > 0$

1 **for** each episode **do**:
2   **if** episode number is divisible by `freqMD`:
3   Run Adapted Metadynamics (batch size b) for time $n\Delta t$, obtain samples $\{x_1, \ldots, x_b\}$
4   Push $\{x_1, \ldots, x_b\}$ to the replay buffer
5   Backward sample from $\{x_1, \ldots, x_b\}$ using current P_B to obtain trajectories $\{\tau_1, \ldots, \tau_b\}$
6   **elif** episode number is divisible by `freqRB`:
7   Random sample $\{x_1, \ldots, x_b\}$ from the replay buffer
8   Backward sample from $\{x_1, \ldots, x_b\}$ using current P_B to obtain trajectories $\{\tau_1, \ldots, \tau_b\}$
9   **else**:
10   Generate trajectories $\{\tau_1, \ldots, \tau_b\}$ on-policy
11   Compute loss $l = \sum_{i=1}^{b} L(\tau_i, P_F, P_B)$
12   Take gradient step on loss l

---

4 EXPERIMENTS

We compare MetaGFN with Thompson sampling, noisy, local search GFlowNets and nested sampling exploration strategies (Section 2.3). We run experiments in five continuous environments, summarised

below. For each strategy, we use a replay buffer and alternate between an exploration batch and a replay buffer batch. For MetaGFN, we use `freqRB = 2`, `freqMD = 10` and always regenerate MetaGFN training trajectories using the current backward policy. In all environments, the additional computational expense of running Adapted Metadynamics was negligible (<5%) compared to the training time of the models. Full experimental details can be found in Appendix D.1.

Line environment: A one-dimensional environment with state space $\mathcal{S} = \mathbb{R} \times \{t \in \mathbb{N}, 1 \leq t \leq 3\}$, where t indexes the position of a state in a trajectory. The source state is $s_0 = (0, 0)$. The terminal states are therefore $\mathcal{X} = \mathbb{R} \times \{3\} \cong \mathbb{R}$. The collective variable is the identity, i.e. $z = x$. The reward density, plotted in Figure 2, consists of an asymmetric bimodal peak near the origin and an additional distant lone peak. It is given by the Gaussian mixture distribution:

$$r(x) = \begin{cases} \mathcal{N}(-2.0, 1.0) + \mathcal{N}(-2.0, 0.4) + \\ \quad \mathcal{N}(2.0, 0.6) + \mathcal{N}(20.0, 0.1); & -5 \leq x \leq 23 \\ 0; & \text{otherwise,} \end{cases} \quad (2)$$

where $\mathcal{N}(\mu, \sigma^2)$ is a Gaussian density with mean μ and variance σ^2.

Figure 2: Line environment reward density.

Alanine dipeptide environment: One application of continuous GFlowNets is molecular conformation sampling (Volokhova et al., 2023). Here, we train a GFlowNet to sample conformational states of alanine dipeptide (AD), a a small biomolecule of 23 atoms that plays a key role in modelling the dynamics of proteins (Hermans, 2011). The metastable states of AD are distinguished in a 2D CV space defined by the backbone dihedral angles ϕ and ψ. The resulting free energy surface $V(\phi, \psi)$ in explicit water, obtained after extensive sampling with long molecular dynamics simulations, is shown in Figure 3. The metastable states, in increasing energy, are $P_{||}, \alpha_R, C_5,$ $\alpha', \alpha_L,$ and α_D. The state space is $\mathcal{S} = \mathbb{T}^2 \times \{t \in \mathbb{N}, 1 \leq t \leq 3\}$, with source state $s_0 = P_{||} = (-1.2, 2.68)$. Terminal states are $\mathcal{X} = \mathbb{T}^2 \times \{3\} \cong \mathbb{T}^2$. The reward function is the Boltzmann weight, $r(\phi, \psi) = \frac{1}{Z} \exp(-\beta V(\phi, \psi))$, where Z is the normalisation constant.

Figure 3: Free energy surface of alanine dipeptide.

Grid environments: We consider (hyper)grids in 2, 3 and 4 dimensions. The k-dimensional (hyper)grid consists of 2^k modes, located at the corner of a (hyper)cube. The (hyper)grid is centered on the origin with an edge width of 20. The reward modes are Gaussians with variance $\sigma^2 = 2$ (Figure 4). We use trajectory lengths of 3, 5, and 6 for dimensions 2, 3, and 4 respectively. The collective variable is the identity, i.e. $z = x$. The source state is the origin and terminal states are in $\mathcal{X} \cong \mathbb{R}^k$.

Figure 4: Grid environment reward density (2D).

4.1 RESULTS

In each environment, we run experiments with three different loss functions: Detailed Balance (DB), Trajectory Balance (TB) and Subtrajectory Balance (STB). We evaluate performance by computing the L1 error between the known reward distribution and the empirical on-policy distribution during training resulting from 10^4 independent samples. The results, averaged over 10 repeats, are shown in Figure 5. In 12 out of 15 of the experiments, MetaGFN outperformed all other exploration strategies. We give further analysis below.

Line Environment: Among the losses, TB shows the lowest variance, and for all losses, MetaGFN always converges to a lowest error [4]. Indeed, MetaGFN is the only method that consistently samples the distant reward peak at $x = 20$ (Appendix D.2). Although other strategies occasionally sampled the distant peak, MetaGFN alone converges because it *continuously* samples this peak, even if the

---

[4] We do not show results for nested sampling on the line environment as the implementation used did not support one-dimensional environments, see Appendix D.1.

Figure 5: The L1 difference between on-policy and reward distribution during training for different loss functions and exploration strategies. The mean is plotted with standard error over 10 repeats. DB - Detailed Balance loss, TB - Trajectory Balance loss, STB - Subtrajectory Balance loss.

forward policy starts to lock onto the central modes, thus ensuring that the replay buffer is always populated with diverse samples. The slight increase in the loss of MetaGFN around batch number 5×10^3 occurs as the on-policy distribution widens when Adapted Metadynamics first discovers the distant peak. Appendix D.2 provides further analysis of Adapted Metadynamics and compares different MetaGFN variants, with and without noise, and with and without trajectory regeneration. We confirm that the variant of MetaGFN presented in Figure 5 (no added noise, always regenerate trajectories) is the most robust.

Alanine Dipeptide Environment: For each loss, MetaGFN generally converges to a lower error than all other exploration strategies. However, for TB loss, the average L1 error is marginally higher than on-policy training, but this conceals the fact that the best-case error is smaller. To better understand this result, we examined the best and worst training runs (as measured by L1 error) for TB on-policy and TB MetaGFN, shown in Figure 6. Note that, unlike on-policy, the best MetaGFN run learns to sample the rare α_L mode. In the worst case, MetaGFN fails to converge (although this is rare; only one of 10 runs failed). In Table 1, we quantify how often the different AD modes were sampled over the different repeats (a mode is considered sampled if the on-policy distribution has a mode within the correct basin of attraction). TB loss with MetaGFN is the only combination that consistently samples the majority of modes. The only mode not sampled by any method is α_D, which has a natural abundance approximately 10 times less frequent than α_L.

Table 1: Number of correct samples of AD modes in trained GFlowNets over 10 independent repeats for DB, STB, and TB loss functions. OP - On-policy and MD - MetaGFN. The α_D mode wasn't sampled in any model due to its low natural frequency.

	DB		STB		TB	
	OP	MD	OP	MD	OP	MD
$P_{\parallel}$	1	**7**	**6**	5	10	**8**
α_R	6	**9**	7	**10**	10	**9**
C_5	2	**7**	5	**6**	10	**8**
α'	6	**9**	5	**10**	5	**9**
α_L	0	**1**	**1**	0	0	**8**

Figure 6: Learned on-policy distribution for TB on-policy and TB MetaGFN training runs. The colour bar shows the probability density. Red histograms show the marginal distribution along the angular coordinates. Black curves show the marginal distributions of the ground truth. In the best case, MetaGFN is able to learn the α_L mode. In the worst case, MetaGFN fails to converge. On-policy training, although more consistent, fails to learn to sample from the α_L mode.

Grid Environments: MetaGFN achieves the lowest error in 7 of 9 experiments, although note that the performance of all methods generally decreases with increasing dimension. This is unsurprising, since the learning task becomes more difficult. For MetaGFN, this is also an expected outcome of the curse of dimensionality of the replay buffer grid; in high-dimensional spaces metadynamics samples encounter high-reward modes less frequently, leading to a replay buffer with less sample diversity. This is a known limitation of metadynamics (Laio and Parrinello, 2002). Nested Sampling outperforms MetaGFN in one case (Grid 3D, DB loss) but relies on costly MCMC-based pre-training that scales exponentially with dimension and requires reward gradients, unlike MetaGFN. However, the generally favourable performance of MetaGFN could be due to the method discovering an overall larger diversity of off-policy samples, that are refreshed and updated during training, in contrast to the static samples when using Nested Sampling approach.

5 LIMITATIONS

For metadynamics to be an effective sampler, the CVs must be low-dimensional and bounded. Either these CVs should be known analytically (as in our experiments) or learnt from data (Sidky et al., 2020). Alternatively, CVs could be learnt adaptively by parameterising $z(x; \theta)$ by a neural network and updating its parameters by back-propagating through the GFlowNet loss during training. The metadynamics algorithm could also be replaced with a variant with smoother convergence properties, such as well-tempered metadynamics (Barducci et al., 2008) or on-the-fly probability enhanced sampling (OPES) (Invernizzi, 2021). We leave these as extensions for future work.

6 CONCLUSIONS

While exploration strategies for discrete Generative Flow Networks (GFlowNets) have received extensive attention, the methodologies for continuous GFlowNets remain relatively underexplored. To address this gap, we illustrated how metadynamics, a widely used enhanced sampling technique in molecular dynamics, can be adapted as an effective exploration strategy for continuous GFlowNets.

In molecular dynamics, atomic forces can be computed as the gradient of the potential, whereas continuous GFlowNets tackle problems where the reward function is a black box and gradients are inaccessible. We demonstrated how the method could be adapted by updating a kernel density estimate of the reward function on-the-fly, and proved that this is guaranteed to explore the space in an appropriate limit. Our empirical investigations show that MetaGFN offers a computationally efficient means to explore new modes in environments where prior knowledge of collective variables exists. Importantly, this work advocates an approach wherein techniques derived from molecular modelling can be adapted for machine learning tasks. Looking ahead, we anticipate that this could be a fruitful area of cross-disciplinary research, where existing ideas from the enhanced sampling literature can find further applications in generative modelling and reinforcement learning.

REFERENCES

Cameron Abrams and Giovanni Bussi. Enhanced Sampling in Molecular Dynamics Using Metady-namics, Replica-Exchange, and Temperature-Acceleration. *Entropy*, 16(1):163–199, January 2014. ISSN 1099-4300. doi: 10.3390/e16010163. URL https://www.mdpi.com/1099-4300/16/1/163. Number: 1 Publisher: Multidisciplinary Digital Publishing Institute.

Alessandro Barducci, Giovanni Bussi, and Michele Parrinello. Well-Tempered Metadynamics: A Smoothly Converging and Tunable Free-Energy Method. *Physical Review Letters*, 100(2):020603, January 2008. ISSN 0031-9007, 1079-7114. doi: 10.1103/PhysRevLett.100.020603. URL https://link.aps.org/doi/10.1103/PhysRevLett.100.020603.

Emmanuel Bengio, Moksh Jain, Maksym Korablyov, Doina Precup, and Y. Bengio. Flow Network based Generative Models for Non-Iterative Diverse Candidate Generation. *ArXiv*, June 2021a.

Yoshua Bengio, T. Deleu, J. E. Hu, Salem Lahlou, Mo Tiwari, and Emmanuel Bengio. GFlowNet Foundations. *ArXiv*, November 2021b.

Luigi Bonati, GiovanniMaria Piccini, and Michele Parrinello. Deep learning the slow modes for rare events sampling. *Proceedings of the National Academy of Sciences*, 118(44):e2113533118, November 2021. doi: 10.1073/pnas.2113533118. URL https://www.pnas.org/doi/full/10.1073/pnas.2113533118. Publisher: Proceedings of the National Academy of Sciences.

Massimiliano Bonomi, Giovanni Bussi, Carlo Camilloni, Gareth A. Tribello, Pavel Banáš, Alessandro Barducci, Mattia Bernetti, Peter G. Bolhuis, Sandro Bottaro, Davide Branduardi, Riccardo Capelli, Paolo Carloni, Michele Ceriotti, Andrea Cesari, Haochuan Chen, Wei Chen, Francesco Colizzi, Sandip De, Marco De La Pierre, Davide Donadio, Viktor Drobot, Bernd Ensing, Andrew L. Ferguson, Marta Filizola, James S. Fraser, Haohao Fu, Piero Gasparotto, Francesco Luigi Gervasio, Federico Giberti, Alejandro Gil-Ley, Toni Giorgino, Gabriella T. Heller, Glen M. Hocky, Marcella Iannuzzi, Michele Invernizzi, Kim E. Jelfs, Alexander Jussupow, Evgeny Kirilin, Alessandro Laio, Vittorio Limongelli, Kresten Lindorff-Larsen, Thomas Löhr, Fabrizio Marinelli, Layla Martin-Samos, Matteo Masetti, Ralf Meyer, Angelos Michaelides, Carla Molteni, Tetsuya Morishita, Marco Nava, and The PLUMED consortium. Promoting transparency and reproducibility in enhanced molecular simulations. *Nature Methods*, 16(8):670–673, August 2019. ISSN 1548-7091. doi: 10.1038/s41592-019-0506-8.

Luca Bortolussi and Alberto Policriti. Hybrid Systems and Biology. In Marco Bernardo, Pierpaolo Degano, and Gianluigi Zavattaro, editors, *Formal Methods for Computational Systems Biology*, pages 424–448, Berlin, Heidelberg, 2008. Springer Berlin Heidelberg. ISBN 978-3-540-68894-5.

Giovanni Bussi and Alessandro Laio. Using metadynamics to explore complex free-energy landscapes. *Nature Reviews Physics*, 2:200–212, March 2020. doi: 10.1038/s42254-020-0153-0. URL https://ui.adsabs.harvard.edu/abs/2020NatRP...2..200B. ADS Bibcode: 2020NatRP...2..200B.

Flaviu Cipcigan, Jonathan Booth, Rodrigo Neumann Barros Ferreira, Carine Ribeiro dos Santos, and Mathias Steiner. Discovery of Novel Reticular Materials for Carbon Dioxide Capture using GFlowNets, October 2023. URL http://arxiv.org/abs/2310.07671. arXiv:2310.07671 [cond-mat].

Marco De Vivo, Matteo Masetti, Giovanni Bottegoni, and Andrea Cavalli. Role of Molecular Dynamics and Related Methods in Drug Discovery. *Journal of Medicinal Chemistry*, 59(9):4035–4061, May 2016. ISSN 0022-2623. doi: 10.1021/acs.jmedchem.5b01684. URL https://doi.org/10.1021/acs.jmedchem.5b01684. Publisher: American Chemical Society.

Tristan Deleu, António Góis, Chris Emezue, Mansi Rankawat, Simon Lacoste-Julien, Stefan Bauer, and Yoshua Bengio. Bayesian Structure Learning with Generative Flow Networks, June 2022. URL http://arxiv.org/abs/2202.13903. arXiv:2202.13903 [cs, stat].

Peter Eastman, Jason Swails, John D. Chodera, Robert T. McGibbon, Yutong Zhao, Kyle A. Beauchamp, Lee-Ping Wang, Andrew C. Simmonett, Matthew P. Harrigan, Chaya D. Stern,

Rafal P. Wiewiora, Bernard R. Brooks, and Vijay S. Pande. OpenMM 7: Rapid development of high performance algorithms for molecular dynamics. *PLoS computational biology*, 13(7): e1005659, July 2017. ISSN 1553-7358. doi: 10.1371/journal.pcbi.1005659.

Giacomo Fiorin, Michael L. Klein, and Jérôme Hénin. Using collective variables to drive molecular dynamics simulations. *Molecular Physics*, 111(22-23):3345–3362, December 2013. ISSN 0026-8976. doi: 10.1080/00268976.2013.813594. URL https://doi.org/10.1080/00268976.2013.813594. Publisher: Taylor & Francis _eprint: https://doi.org/10.1080/00268976.2013.813594.

Paul C. D. Hawkins. Conformation Generation: The State of the Art. *Journal of Chemical Information and Modeling*, 57(8):1747–1756, August 2017. ISSN 1549-9596. doi: 10.1021/acs.jcim.7b00221. URL https://doi.org/10.1021/acs.jcim.7b00221. Publisher: American Chemical Society.

Jan Hermans. The amino acid dipeptide: Small but still influential after 50 years. *Proceedings of the National Academy of Sciences*, 108(8):3095–3096, February 2011. doi: 10.1073/pnas.1019470108. URL https://www.pnas.org/doi/full/10.1073/pnas.1019470108. Publisher: Proceedings of the National Academy of Sciences.

Edward J. Hu, Nikolay Malkin, Moksh Jain, Katie Everett, Alexandros Graikos, and Yoshua Bengio. GFlowNet-EM for learning compositional latent variable models, June 2023. URL http://arxiv.org/abs/2302.06576. arXiv:2302.06576 [cs, stat].

Michele Invernizzi. OPES: On-the-fly Probability Enhanced Sampling Method. *Il Nuovo Cimento C*, 44(405):1–4, September 2021. ISSN 03905551, 03905551. doi: 10.1393/ncc/i2021-21112-8. URL http://arxiv.org/abs/2101.06991. arXiv:2101.06991 [physics].

Moksh Jain, Emmanuel Bengio, Alex Hernandez-Garcia, Jarrid Rector-Brooks, Bonaventure F. P. Dossou, Chanakya Ajit Ekbote, Jie Fu, Tianyu Zhang, Michael Kilgour, Dinghuai Zhang, Lena Simine, Payel Das, and Yoshua Bengio. Biological Sequence Design with GFlowNets. In *Proceedings of the 39th International Conference on Machine Learning*, pages 9786–9801. PMLR, June 2022. URL https://proceedings.mlr.press/v162/jain22a.html. ISSN: 2640-3498.

Moksh Jain, Sharath Chandra Raparthy, Alex Hernandez-Garcia, Jarrid Rector-Brooks, Yoshua Bengio, Santiago Miret, and Emmanuel Bengio. Multi-Objective GFlowNets, July 2023. URL http://arxiv.org/abs/2210.12765. arXiv:2210.12765 [cs, stat].

William L. Jorgensen, Jayaraman Chandrasekhar, Jeffry D. Madura, Roger W. Impey, and Michael L. Klein. Comparison of simple potential functions for simulating liquid water. *The Journal of Chemical Physics*, 79(2):926–935, July 1983. ISSN 0021-9606. doi: 10.1063/1.445869. URL https://doi.org/10.1063/1.445869.

Minsu Kim, Taeyoung Yun, Emmanuel Bengio, Dinghuai Zhang, Yoshua Bengio, Sungsoo Ahn, and Jinkyoo Park. Local Search GFlowNets, March 2024. URL http://arxiv.org/abs/2310.02710. arXiv:2310.02710 [cs, stat].

Salem Lahlou, Tristan Deleu, Pablo Lemos, Dinghuai Zhang, Alexandra Volokhova, Alex Hernández-García, Léna Néhale Ezzine, Yoshua Bengio, and Nikolay Malkin. A theory of continuous generative flow networks. *Proceedings of the 40th International Conference on Machine Learning*, 2023. doi: 10.48550/ARXIV.2301.12594. URL https://arxiv.org/abs/2301.12594. Publisher: arXiv Version Number: 2.

Alessandro Laio and Francesco L. Gervasio. Metadynamics: a method to simulate rare events and reconstruct the free energy in biophysics, chemistry and material science. *Reports on Progress in Physics*, 71(12):126601, November 2008. ISSN 0034-4885. doi: 10.1088/0034-4885/71/12/126601. URL https://dx.doi.org/10.1088/0034-4885/71/12/126601.

Alessandro Laio and Michele Parrinello. Escaping free-energy minima. *Proceedings of the National Academy of Sciences*, 99(20):12562–12566, October 2002. doi: 10.1073/pnas.202427399. URL https://www.pnas.org/doi/full/10.1073/pnas.202427399. Publisher: Proceedings of the National Academy of Sciences.

Pablo Lemos, Nikolay Malkin, Will Handley, Yoshua Bengio, Yashar Hezaveh, and Laurence Perreault-Levasseur. Improving Gradient-guided Nested Sampling for Posterior Inference, December 2023. URL `http://arxiv.org/abs/2312.03911`. arXiv:2312.03911 [cs, stat].

Shuang Luo, Yinchuan Li, Shunyu Liu, Xu Zhang, Yunfeng Shao, and Chao Wu. Multi-agent Continuous Control with Generative Flow Networks. *Neural Networks*, 174:106243, June 2024. ISSN 0893-6080. doi: 10.1016/j.neunet.2024.106243. URL `https://www.sciencedirect.com/science/article/pii/S0893608024001679`.

Kanika Madan, Jarrid Rector-Brooks, Maksym Korablyov, Emmanuel Bengio, Moksh Jain, Andrei Nica, Tom Bosc, Yoshua Bengio, and Nikolay Malkin. Learning GFlowNets from partial episodes for improved convergence and stability. *Proceedings of the 40th International Conference on Machine Learning*, 2022. doi: 10.48550/ARXIV.2209.12782. URL `https://arxiv.org/abs/2209.12782`. Version Number: 3.

Nikolay Malkin, Moksh Jain, Emmanuel Bengio, Chen Sun, and Y. Bengio. Trajectory Balance: Improved Credit Assignment in GFlowNets. *ArXiv*, January 2022.

Nikolay Malkin, Salem Lahlou, Tristan Deleu, Xu Ji, Edward Hu, Katie Everett, Dinghuai Zhang, and Yoshua Bengio. GFlowNets and variational inference, March 2023. URL `http://arxiv.org/abs/2210.00580`. arXiv:2210.00580 [cs, stat].

Andreas Mardt, Luca Pasquali, Hao Wu, and Frank Noé. VAMPnets for deep learning of molecular kinetics. *Nature Communications*, 9(1):5, January 2018. ISSN 2041-1723. doi: 10.1038/s41467-017-02388-1. URL `https://www.nature.com/articles/s41467-017-02388-1`. Publisher: Nature Publishing Group.

L. Molgedey and H. G. Schuster. Separation of a mixture of independent signals using time delayed correlations. *Physical Review Letters*, 72(23):3634–3637, June 1994. ISSN 0031-9007. doi: 10.1103/PhysRevLett.72.3634. URL `https://link.aps.org/doi/10.1103/PhysRevLett.72.3634`.

Michael Neunert, Abbas Abdolmaleki, Markus Wulfmeier, Thomas Lampe, Tobias Springenberg, Roland Hafner, Francesco Romano, Jonas Buchli, Nicolas Heess, and Martin Riedmiller. Continuous-Discrete Reinforcement Learning for Hybrid Control in Robotics. In *Proceedings of the Conference on Robot Learning*, pages 735–751. PMLR, May 2020. URL `https://proceedings.mlr.press/v100/neunert20a.html`. ISSN: 2640-3498.

Esa Nummelin. *General Irreducible Markov Chains and Non-Negative Operators*. Cambridge Tracts in Mathematics. Cambridge University Press, Cambridge, 1984. ISBN 978-0-521-60494-9. doi: 10.1017/CBO9780511526237. URL `https://www.cambridge.org/core/books/general-irreducible-markov-chains-and-nonnegative-operators/0557D49C011AA90B761FC854D5C14983`.

Ling Pan, Dinghuai Zhang, Aaron Courville, Longbo Huang, and Yoshua Bengio. Generative Augmented Flow Networks, October 2022. URL `http://arxiv.org/abs/2210.03308`. arXiv:2210.03308 [cs].

Ling Pan, Nikolay Malkin, Dinghuai Zhang, and Yoshua Bengio. Better Training of GFlowNets with Local Credit and Incomplete Trajectories. In *Proceedings of the 40th International Conference on Machine Learning*, pages 26878–26890. PMLR, July 2023. URL `https://proceedings.mlr.press/v202/pan23c.html`. ISSN: 2640-3498.

Grigorios A. Pavliotis. *Stochastic Processes and Applications: Diffusion Processes, the Fokker-Planck and Langevin Equations*, volume 60 of *Texts in Applied Mathematics*. Springer, New York, NY, 2014. ISBN 978-1-4939-1322-0. doi: 10.1007/978-1-4939-1323-7. URL `https://link.springer.com/10.1007/978-1-4939-1323-7`.

Venkata K. Ramaswamy, Samuel C. Musson, Chris G. Willcocks, and Matteo T. Degiacomi. Deep Learning Protein Conformational Space with Convolutions and Latent Interpolations. *Physical Review X*, 11(1):011052, March 2021. doi: 10.1103/PhysRevX.11.011052. URL `https://link.aps.org/doi/10.1103/PhysRevX.11.011052`. Publisher: American Physical Society.

Jarrid Rector-Brooks, Kanika Madan, Moksh Jain, Maksym Korablyov, Cheng-Hao Liu, Sarath Chandar, Nikolay Malkin, and Yoshua Bengio. Thompson sampling for improved exploration in GFlowNets, June 2023. URL http://arxiv.org/abs/2306.17693. arXiv:2306.17693 [cs].

Desik Rengarajan, Gargi Vaidya, Akshay Sarvesh, Dileep Kalathil, and Srinivas Shakkottai. Reinforcement Learning with Sparse Rewards using Guidance from Offline Demonstration, February 2022. URL http://arxiv.org/abs/2202.04628. arXiv:2202.04628.

Romelia Salomon-Ferrer, David A. Case, and Ross C. Walker. An overview of the Amber biomolecular simulation package. *WIREs Computational Molecular Science*, 3(2):198–210, 2013. ISSN 1759-0884. doi: 10.1002/wcms.1121. URL https://onlinelibrary.wiley.com/doi/abs/10.1002/wcms.1121. _eprint: https://onlinelibrary.wiley.com/doi/pdf/10.1002/wcms.1121.

Marcin Sendera, Minsu Kim, Sarthak Mittal, Pablo Lemos, Luca Scimeca, Jarrid Rector-Brooks, Alexandre Adam, Yoshua Bengio, and Nikolay Malkin. Improved off-policy training of diffusion samplers, May 2024. URL http://arxiv.org/abs/2402.05098. arXiv:2402.05098 [cs, stat].

Bobak Shahriari, Kevin Swersky, Ziyu Wang, Ryan P. Adams, and Nando De Freitas. Taking the Human Out of the Loop: A Review of Bayesian Optimization. *Proceedings of the IEEE*, 104(1): 148–175, January 2016. ISSN 0018-9219, 1558-2256. doi: 10.1109/JPROC.2015.2494218. URL https://ieeexplore.ieee.org/document/7352306/.

Max W. Shen, Emmanuel Bengio, Ehsan Hajiramezanali, Andreas Loukas, Kyunghyun Cho, and Tommaso Biancalani. Towards Understanding and Improving GFlowNet Training. *Proceedings of the 40th International Conference on Machine Learning*, 2023a. doi: 10.48550/ARXIV.2305.07170. URL https://arxiv.org/abs/2305.07170. Publisher: arXiv Version Number: 1.

Tony Shen, Mohit Pandey, Jason Smith, Artem Cherkasov, and Martin Ester. TacoGFN: Target Conditioned GFlowNet for Structure-Based Drug Design, December 2023b. URL http://arxiv.org/abs/2310.03223. arXiv:2310.03223 [cs].

Hythem Sidky, Wei Chen, and Andrew L. Ferguson. Machine learning for collective variable discovery and enhanced sampling in biomolecular simulation. *Molecular Physics*, 118(5), March 2020. ISSN 0026-8976. doi: 10.1080/00268976.2020.1737742. URL https://www.osti.gov/pages/biblio/1651117. Institution: Argonne National Laboratory (ANL), Argonne, IL (United States) Publisher: Taylor & Francis.

Laura Painton Swiler, Patricia Diane Hough, Peter Qian, Xu Xu, Curtis B. Storlie, and Herbert K. H. Lee. Surrogate models for mixed discrete-continuous variables. Technical Report SAND2012-0491, Sandia National Laboratories (SNL), Albuquerque, NM, and Livermore, CA (United States), August 2012. URL https://www.osti.gov/biblio/1055621.

Alexandra Volokhova, Michał Koziarski, Alex Hernández-García, Cheng-Hao Liu, Santiago Miret, Pablo Lemos, Luca Thiede, Zichao Yan, Alán Aspuru-Guzik, and Yoshua Bengio. Towards equilibrium molecular conformation generation with GFlowNets, October 2023. URL http://arxiv.org/abs/2310.14782. arXiv:2310.14782 [cs].

Yi Isaac Yang, Qiang Shao, Jun Zhang, Lijiang Yang, and Yi Qin Gao. Enhanced sampling in molecular dynamics. *The Journal of Chemical Physics*, 151(7):070902, August 2019. ISSN 0021-9606. doi: 10.1063/1.5109531. URL https://doi.org/10.1063/1.5109531.

David W. Zhang, Corrado Rainone, Markus Peschl, and Roberto Bondesan. Robust Scheduling with GFlowNets, February 2023. URL http://arxiv.org/abs/2302.05446. arXiv:2302.05446 [cs].

Dinghuai Zhang, Nikolay Malkin, Zhen Liu, Alexandra Volokhova, Aaron Courville, and Yoshua Bengio. Generative Flow Networks for Discrete Probabilistic Modeling. In *Proceedings of the 39th International Conference on Machine Learning*, pages 26412–26428. PMLR, June 2022. URL https://proceedings.mlr.press/v162/zhang22v.html. ISSN: 2640-3498.

A LOSS FUNCTIONS

For a complete trajectory τ, the *detailed balanced loss* (DB) is

$$L_{DB}(\tau) = \sum_{t=0}^{n-1} \left(\log \frac{\hat{f}(s_t; \theta) \hat{p}_F(s_t, s_{t+1}; \theta)}{\hat{f}(s_{t+1}; \theta) \hat{p}_B(s_{t+1}, s_t; \theta)} \right)^2,$$

where $\hat{f}(s_{t+1}; \theta)$ is replaced with $r(s_n)$ if s_n is terminal.

The *subtrajectory balance loss* (STB) is

$$L_{STB}(\tau) = \frac{\sum_{0 \le i < j \le n} \lambda^{j-1} \mathcal{L}_{TB}(\tau_{i:j})}{\sum_{0 \le i < j \le n} \lambda^{j-i}},$$

$$\mathcal{L}_{STB}(\tau_{i:j}) := \left(\log \frac{\hat{f}(s_i; \theta) \prod_{t=i}^{j-1} \hat{p}_F(s_{t+1} | s_t; \theta)}{\hat{f}(s_j; \theta) \prod_{t=i+1}^{j} \hat{p}_B(s_{t-1} | s_t; \theta)} \right)^2,$$

where $\hat{f}(s_j; \theta)$ is replaced with $r(s_j)$ if s_j is terminal. In the above, $\lambda < 0$ is a hyperparameter. The limit $\lambda \to 0^+$ leads to average detailed balance. The $\lambda \to \infty$ limit gives the trajectory balance objective. We use $\lambda = 0.9$ in our experiments.

B LANGEVIN DYNAMICS

Langevin dynamics (LD), is defined through the Stochastic Differential Equation (SDE):

$$\mathrm{d}x = M^{-1} p \mathrm{d}t \tag{3}$$

$$\mathrm{d}p = F(x)\mathrm{d}t - \gamma p \mathrm{d}t + \sqrt{2\gamma\beta^{-1}} M^{1/2} \mathrm{d}W. \tag{4}$$

In the above, $x, p \in \mathbb{R}^D$ are vectors of instantaneous position and momenta respectively, $F : \mathbb{R}^D \to \mathbb{R}^D$ is a force function, $W(t)$ is a vector of D independent Wiener processes, $M \in \mathbb{R}^D \times \mathbb{R}^D$ is a constant diagonal mass matrix, and $\gamma, \beta > 0$ are constant scalars which can be interpreted as a friction coefficient and inverse temperature respectively. In conventional Langevin dynamics, the force function is given by the gradient of the potential energy function, $F(x) = -\nabla V(x)$, where $V : \mathbb{R}^D \to \mathbb{R}$ and the dynamics are ergodic with respect to the Gibbs-Boltzmann density

$$\rho_\beta(x, p) \propto e^{-\beta H(x,p)},$$

where $H(x, p) = p^T M^{-1} p / 2 + V(x)$ is the Hamiltonian. Since the Hamiltonian is separable in position and momenta terms, the marginal Gibbs-Boltzmann density is position space is simply $\rho_\beta(x) \propto e^{-\beta V(x)}$, often refered to as the *Gibbs density*.

We present the Euler-Maruyama numerical scheme for integrating equations 3 below. This is called in line 14 of Adapted Metadynamics (Algorithm 1).

Algorithm 3: Euler-Maruyama Langevin Dynamics Step

Input   : Current state (x_t, p_t). Force F.
Parameters: Friction coefficient γ. Thermodynamic beta β. Timestep Δt.
Output   : State $(x_{t+\Delta t}, p_{t+\Delta t})$ at the next timestep.
1 Sample a random vector R, with the same dimension as x_t, where each element is an independent sample from a standard normal.
2 $x_{t+\Delta t} = x_t + p_t \Delta t$
3 $p_{t+\Delta t} = p_t + F\Delta t - \gamma p_t \Delta t + \sqrt{2\gamma\Delta t/\beta} \cdot R$
4 **return** $(x_{t+\Delta t}, p_{t+\Delta t})$

C PROOFS

Lemma C.1. *Let $(f_n(x))$ and $(g_n(x))$ be sequences of real functions where $\lim_{n\to\infty} f_n(x) = \infty$, $\lim_{n\to\infty} g_n(x) = \infty$ and $\lim_{n\to\infty} \frac{f_n(x)}{g_n(x)} = h(x)$. Then, for all $\epsilon > 0$, we have $\lim_{n\to\infty} \frac{f_n(x)}{g_n(x)+\epsilon} = h(x)$.*

Proof.

$$\lim_{n\to\infty} \frac{f_n(x)}{g_n(x)+\epsilon} = \lim_{n\to\infty} \frac{f_n(x)}{g_n(x)} \frac{1}{1+\epsilon/g_n(x)}$$

and the right-hand side is the product of two functions whose limit exists so, by the product rule of limits

$$\lim_{n\to\infty} \frac{f_n(x)}{g_n(x)} \lim_{n\to\infty} \frac{1}{1+\epsilon/g_n(x)} = h(x)\cdot 1 = h(x),$$

so done. $\qquad\square$

Lemma C.2. *Let (X_i) be a sequence of continuous random variables that take values on a bounded domain $D \subset \mathbb{R}^d$ that asymptotically approaches the uniform random variable U on D, i.e. $X_i \to U$ uniformly. Further, suppose*

$$h(x) := \frac{\sum_{i=1}^{\infty} f(x_i)g(x,x_i)}{\sum_{i=1}^{\infty} g(x,x_i)}$$

exists, where $x_i \in D$ is a sample from X_i and $f(x)$ and $g(x,x')$ are analytic functions on D and $D \times D$ respectively. Then,

$$h(x) = \frac{\sum_{i=1}^{\infty} f(u_i)g(x,u_i)}{\sum_{i=1}^{\infty} g(x,u_i)},$$

where the u_i are samples from U. We make no assumption of independence of samples.

Proof. Fix a probability space $(\Omega, \mathcal{F}, P)$ on which (X_i) and U are defined. Recall that a continuous random variable X that takes values on $D \subset \mathbb{R}^d$ is a measurable function $X : \Omega \to D$ where $(D, \mathcal{B})$ is a measure space and $\mathcal{B}$ is the Borel σ-algebra on D. Let $\omega \subset \Omega$ denote an arbitrary element of the sample space. The requirement that $X_i \to U$ uniformly can be written formally as:

$$\forall \epsilon > 0, \exists N(\epsilon) \text{ s.t. } \forall i > N(\epsilon), \forall \omega \subset \Omega, |X_i(\omega) - U(\omega)| < \epsilon.$$

We prove the Lemma by showing that equality holds for all possible sequences of outcomes $\omega_1, \omega_2, \dots$. That is, we prove:

$$\frac{\sum_{i=1}^{\infty} f(X_i(\omega_i))g(x,X_i(\omega_i))}{\sum_{i=1}^{\infty} g(x,X_i(\omega_i))} = \frac{\sum_{i=1}^{\infty} f(U(\omega_i))g(x,U(\omega_i))}{\sum_{i=1}^{\infty} g(x,U(\omega_i))}. \tag{5}$$

Since these are ratios of infinite series, to prove their equality it is sufficient to show that the numerator of the LHS is asymptotically equivalent to the numerator of the RHS and that the denominator of the LHS is asymptotically equivalent to the denominator of the RHS. Recall that two sequences of real functions (a_n) and (b_n) are asymptotically equivalent if $\lim_{n\to\infty} \frac{a_n(x)}{b_n(x)} = c$ where c is a constant. First, we prove that this holds with

$$a_n := \sum_{i=1}^{n} f(X_i(\omega_i))g(x,X_i(\omega_i)) \tag{6}$$

and

$$b_n := \sum_{i=1}^{n} f(U(\omega_i))g(x,U(\omega_i)). \tag{7}$$

We write

$$\frac{a_n}{b_n} = \frac{\sum_{i=1}^{N(\epsilon)} f(X_i(\omega_i))g(x,X_i(\omega_i)) + \sum_{i=N(\epsilon)+1}^{n} f(X_i(\omega_i))g(x,X_i(\omega_i))}{\sum_{i=1}^{N(\epsilon)} f(U(\omega_i))g(x,U(\omega_i)) + \sum_{i=N(\epsilon)+1}^{n} f(U(\omega_i))g(x,U(\omega_i))}.$$

Dividing by $\sum_{i=N(\epsilon)+1}^{n} f(U(\omega_i))g(x,U(\omega_i))$ and taking the limit $n \to \infty$ we have

$$\lim_{n\to\infty} \frac{a_n}{b_n} = \lim_{n\to\infty} \frac{\sum_{i=N(\epsilon)+1}^{n} f(X_i(\omega_i))g(x,X_i(\omega_i))}{\sum_{i=N(\epsilon)+1}^{n} f(U(\omega_i))g(x,U(\omega_i))}.$$

Since f and g are analytic and $i > N(\epsilon)$ for all terms in the sums we have, by Taylor expansion, $f(X_i(\omega_i)) = f(U(\omega_i)) + O(\epsilon)$ and $g(x,X_i(\omega_i)) = g(x,U(\omega_i)) + O(\epsilon)$, hence

$$\lim_{n\to\infty} \frac{a_n}{b_n} = \lim_{n\to\infty} \left(1 + \frac{nO(\epsilon)}{\sum_{i=N(\epsilon)+1}^{n} f(U(\omega_i))g(x,U(\omega_i))}\right) = 1 + \lim_{n\to\infty} \frac{nO(\epsilon)}{O(n)} = 1 + O(\epsilon).$$

Finally, since ϵ can be made arbitrarily small by partitioning the sum at a $N(\epsilon)$ that is sufficiently large, we conclude that $\lim_{n\to\infty} \frac{a_n}{b_n} = 1$, hence (a_n) and (b_n) as defined in equation 6 and equation 7 are asymptotically equivalent. By a similar argument, it can be shown that

$$c_n := \sum_{i=1}^{n} g(x, X_i(\omega_i))$$

and

$$d_n := \sum_{i=1}^{n} g(x, U(\omega_i)))$$

are also asymptotically equivalent. This proves equation 5.

$\square$

Below, we present the proof of Theorem 3.1 that appears in the main text.

Proof. For concreteness, throughout this proof we assume that the kernel function is a Gaussian. We explain at the appropriate stage in the proof, indicated by (*), how this assumption can be relaxed.

First we take the $n \to \infty$ limit. Recall the notation from Section 3, i.e. assume collective variables $z(x) = (z_1(x), \dots, z_d(x))$ where $z : \mathcal{X} \to \mathcal{Z}$, and $\mathcal{Z}$ is d-dimensional. Since the log function is continuous, the limit and log can be interchanged and we have

$$\lim_{n\to\infty} \hat{V}(z, t_n) = -\frac{1}{\beta'} \log \left(\lim_{n\to\infty} \left(\frac{\hat{R}(z, t_n)}{\hat{N}(z, t_n) + \epsilon} \right) + \epsilon \right),$$

where, from Algorithm 1:

$$\hat{R}(z, t_n) = \sum_{i=1}^{n} r(x_{t_i}) \exp\left(-\sum_{j=1}^{d} \frac{(z_j - z_j(x_{t_i}))^2}{2\sigma_j^2} \right), \tag{8}$$

$$\hat{N}(z, t_n) = \sum_{i=1}^{n} \exp\left(-\sum_{j=1}^{d} \frac{(z_j - z_j(x_{t_i}))^2}{2\sigma_j^2} \right). \tag{9}$$

Since the domain is bounded, we know that for fixed z, both equation 8 and equation 9 have limit at infinity, i.e. $\lim_{n\to\infty} \hat{R}(z, t_n) = \infty$ and $\lim_{n\to\infty} \hat{N}(z, t_n) = \infty$. Hence, by Lemma C.1, we have

$$\lim_{n\to\infty} \frac{\hat{R}(z, t_n)}{\hat{N}(z, t_n) + \epsilon} = \lim_{n\to\infty} \frac{\hat{R}(z, t_n)}{\hat{N}(z, t_n)},$$

provided the limit on the RHS exists. Next, we show that this limit exists by computing it explicitly. The limit can be written

$$\lim_{n\to\infty} \frac{\hat{R}(z, t_n)}{\hat{N}(z, t_n)} = \lim_{n\to\infty} \frac{\sum_{i=1}^{n} r(x_{t_i}) \exp\left(-\sum_{j=1}^{d} \frac{(z_j - z_j(x_{t_i}))^2}{2\sigma_j^2} \right)}{\sum_{i=1}^{n} \exp\left(-\sum_{j=1}^{d} \frac{(z_j - z_j(x_{t_i}))^2}{2\sigma_j^2} \right)}.$$

Recall that metadynamics eventually leads to uniform sampling over the domain, independent of the potential. Hence, since R and $z(x)$ are analytic, by Lemma C.2 we may replace the metadynamics samples x_{t_i} with samples u_i from a uniform distribution over $\mathcal{X}$:

$$\lim_{n\to\infty} \frac{\hat{R}(z, t_n)}{\hat{N}(z, t_n)} = \lim_{n\to\infty} \frac{\sum_{i=1}^{n} r(u_i) \exp\left(-\sum_{j=1}^{d} \frac{(z_j - z_j(u_i))^2}{2\sigma_j^2} \right)}{\sum_{i=1}^{n} \exp\left(-\sum_{j=1}^{d} \frac{(z_j - z_j(u_i))^2}{2\sigma_j^2} \right)}.$$

In the limit, the ratio of sums with uniform sampling becomes a ratio of integrals:

$$\lim_{n\to\infty} \frac{\hat{R}(z, t_n)}{\hat{N}(z, t_n)} = \frac{\int_{\mathcal{X}} r(x') \exp\left(-\sum_{j=1}^{d} \frac{(z_j - z_j(x'))^2}{2\sigma_j^2} \right) \mathrm{d}x'}{\int_{\mathcal{X}} \exp\left(-\sum_{j=1}^{d} \frac{(z_j - z_j(x'))^2}{2\sigma_j^2} \right) \mathrm{d}x'}.$$

The limit is therefore a (scaled) convolution of the reward function with a Gaussian in the collective variable space with width vector σ. Taking the limit $\sigma_j \to 0$ for all $j \in \{1, 2, \ldots, d\}$, the Gaussian convergences to a delta distribution in the collective variable space and we have

$$\lim_{\sigma \to 0} \lim_{n \to \infty} \frac{\hat{R}(z, t_n)}{\hat{N}(z, t_n)} = \int_{\mathcal{X}} r(x')\delta(z - z(x'))\mathrm{d}x'.$$

(*) This step also holds for any kernel that becomes distributionally equivalent to a Dirac delta function in the limit that its variance parameter goes to zero. In particular, it also holds for the von Mises distribution that we use in our alanine dipeptide experiment in $\mathbb{T}^2$.

Finally, we take the limit $\epsilon \to 0$ to obtain

$$\lim_{\epsilon \to 0} \lim_{\sigma \to 0} \lim_{n \to \infty} \hat{V}(z, t_n) = -\frac{1}{\beta'} \lim_{\epsilon \to 0} \log \left(\int_{\mathcal{X}} r(x')\delta(z - z(x'))\mathrm{d}x' + \epsilon \right) \tag{10}$$

$$= -\frac{1}{\beta'} \int_{\mathcal{X}} \log \left(r(x') \right) \delta(z - z(x'))\mathrm{d}x' \tag{11}$$

$$= \int_{\mathcal{X}} V(x')\delta(z - z(x'))\mathrm{d}x' := V(z), \tag{12}$$

where we have used the definition $V(x') = -\frac{1}{\beta'} \log(r(x'))$ and in the last step we used the definition of the marginal potential energy in the collective variable space. If $z(x)$ is invertible, then the delta function simplifies to a delta function in the original space and we obtain the original potential instead of the marginal potential. □

D   EXPERIMENT DETAILS

D.1   COMMON EXPERIMENTAL PARAMETERS

Training parameters: For all environments we train for $B = 10^5$ batches use a learning rate with a linear schedule, starting at 10^{-3} and finishing at 0. For the TB loss, we train the $\log Z_\theta$ with a higher initial learning rate of 10^{-1} (also linearly scheduled). For the STB loss, we use $\lambda = 0.9$, a value that has worked well in the discrete setting (Madan et al., 2022). We use the Adam optimiser with gradient clipping. For all loss functions, we clip the minimum log-reward signal at -10. This enables the model to learn despite regions of near-zero reward between the modes of $r(x)$.

Replay buffer: We use a replay buffer with capacity for 10^4 trajectories. Trajectories are stored in the replay buffer only if the terminal state's reward exceeds 10^{-3}. When drawing a replay buffer batch, trajectories are bias-sampled: 50% randomly drawn from the upper 30% of trajectories with the highest rewards, and the remaining 50% randomly drawn from the lower 70%.

Noisy exploration: An additional constant, $\bar{\sigma}$, is added to the standard deviations of the Gaussian distributions of the forward and backward policies. Specifically, the forward policy becomes $\hat{p}_F(s_t, s_{t-1}; \theta) = \sum_{i=1}^{k} w_i \mathcal{N}(\mu_i, (\sigma_i + \bar{\sigma})^2)$, and similarly for the backward policy, where k is the number of Gaussians in the mixture. We schedule the value of $\bar{\sigma}$ so that it decreases during training according to an exponential-flat schedule:

$$\bar{\sigma} = \begin{cases} \bar{\sigma}_0 \left(e^{-2je/(B/2)} - e^{-2e} \right) & j < B/2 \\ 0 & j \geq B/2, \end{cases} \tag{13}$$

where $j \in (1, \ldots, B)$ is the batch number and $\bar{\sigma}_0 = 2$ is the initial noise, plotted in Figure 7. Note that, for the

Figure 7: Exponential noise schedule.

alanine dipeptide environment, the policy is a mixture of bivariate von Mises distributions and the noise $\bar{\sigma}$ is added to the concentration parameter κ, where concentration is related to standard deviation through $\sigma = \frac{1}{\kappa^2}$.

Thompson sampling: We use 10 heads with the bootstrapping probability parameter set to $p = 0.3$.

Local Search GFN: Local search samples trajectories using a forward-backward reconstruction method. First, forward policy samples actions to generate batch size b on-policy trajectories. Then, the backward policy is used to re-sample the last K steps of each trajectory. Finally, the forward policy is used to reconstruct the last K steps, and trajectories in the batch with higher rewards from reconstruction replace the originals. We use $K = 1$ for the line environment, alanine dipeptide environment and two-dimensional grid. We use $K = 2$ and $K = 3$ for the three and four dimensional (hyper)grids, respectively.

Nested sampling: We use the Gradient Based Nested Sampling (GBNS) (Lemos et al., 2023) with a publicly available implementation: `https://github.com/Pablo-Lemos/GGNS`. For each environment, GBNS generates samples from the reward distribution. During training, we alternate between two types of backpropagation: one fully on-policy, and the other using backward-sampled trajectories from the generated samples, guided by the current backward policy.

Compute resources: Experiments are performed in PyTorch on a desktop with 32Gb of RAM and a 12-core 2.60GHz i7-10750H CPU.

D.2 LINE ENVIRONMENT DETAILS

Parameterisation: The forward and backward policies are a mixture of three Gaussians. We parameterise $\hat{p}_F$, $\hat{p}_B$ and the flow $\hat{f}$ through an MLP with 3 hidden layers, 256 hidden units per layer. We use the GELU activation function and dropout probability 0.2 after each layer. This defines the torso of the MLP. Connecting from this common torso, the MLP has three single-layer, fully-connected heads. The first two heads have output dimension 9 and parameterise the 3 means (μ), standard deviations (σ) and weights (w) of the mixture of Gaussians for the forward and backward policies respectively. The third head has output dimension 1 and parameterises the flow function $\hat{f}$. The mean and standard deviation outputs are passed through a sigmoid function and transformed so that they map to the ranges $\mu \in (-14, 14)$ and $\sigma \in (0.1, 1)$. The mixture weights are normalised with the softmax function. The exception to this parameterisation is the backward transition to the source state which is fixed to be the Dirac delta distribution centred on the source, i.e. $\hat{p}_B(s_0|s_1; \theta) = \delta_{s_0}$. For the TB loss, we treat $\log Z_\theta$ as a separate learnable parameter. We use batch size $b = 64$. It takes approximately 1 hour to train a continuous GFlowNet in this environment with $B = 10^5$ batches.

MetaGFN: We use $\Delta t = 0.05$, $n = 2$, $\beta = 1$, $\gamma = 2$, $w = 0.15$, $\sigma = 0.1$, $\epsilon = 10^{-3}$. The domain of Adapted Metadynamics is restricted to $[-5, 23]$ and reflection conditions are imposed at the boundary. The bias and KDE potentials are stored on a uniform grid with grid spacing 0.01. Initial metadynamics samples are drawn from a Gaussian distribution, mean 0 and variance 1, and initial momenta from a Gaussian distribution, mean 0 and variance 0.5.

Evaluation: The L1 error between the known reward distribution, $\rho(x) = r(x)/Z$, and the empirical on-policy distribution, denoted $\hat{\rho}(x)$, estimated by sampling 10^4 on-policy trajectories and computing the empirical distribution over terminal states. Specifically, we compute error $= \frac{1}{2} \int_{-5}^{23} \left| \hat{\rho}(x) - \frac{r(x)}{Z} \right| dx$, where the integral is estimated by a discrete sum with grid spacing 0.01. Note that this error is normalised such that for all valid probability distributions $\hat{\rho}(x)$, we have $0 \le$ error ≤ 1.

On-policy distributions: Figure 9 shows the forward policy and replay buffer distributions (with bias sampling) after training for 10^5 iterations with TB loss. MetaGFN is the only method that can uniformly populate the replay buffer and consistently learn all three peaks.

Adapted Metadynamics: Figure 10a shows the L1 error between the density implied by the KDE potential and the true reward distribution during a typical training run. Figure 10b shows the resulting $\hat{V}$ and V_{bias} at the end of the training. By (1), Adapted Metadynamics has fully explored the central peaks. At (2), the third peak is discovered, prompting rapid adjustment of the KDE potential. By 2.5×10^4 iterations, a steady state is reached and the algorithm is sampling the domain uniformly.

Sensitivity analysis of hyperparameters: We compare MetaGFN performance for various `freqRB` and `freqMD` values, showing the mean and standard deviation of the final L1 error after 10^5 batches (Figure 8). Intuitively, we expect that if `freqRB` is set too large, then MetaGFN focuses predominantly on the on-policy dynamics and may fail to learn to sample distant modes. By contrast, setting `freqRB` $= 1$ means exclusively training on the replay buffer, without any on-policy training

Figure 8: Mean and standard deviation L1 loss after 10^5 training batches over 10 repeats in the line environment. Blue line: changing `freqRB` while `freqMD = 10`. Red line: changing `freqMD` while `freqRB = 2`.

Figure 9: Forward policy and replay buffer distributions after training for 10^5 iterations with TB loss. MetaGFN is the only method that can consistently learn all three peaks.

trajectories, which we would expect to lead to slow convergence. Therefore, an intermediate value of `freqRB` should be optimal. We found that setting `freqRB = 2` (giving an equal weighting to both on-policy and replay buffer trajectories) showed the lowest loss. By contrast, performance is not too sensitive to `freqMD`. `freqMD` should be set so that Adapted Metadynamics explores the reward landscape in a comparable time it takes to train the GFN to convergence, hence only the order of magnitude of `freqMD` is important. For concreteness, we choose `freqMD = 10` but the model performance is not too sensitive to this parameter.

Comparing MetaGFN variants: We consider three MetaGFN variants. The first variant, *always backwards sample*, regenerates the entire trajectory using the current backward policy when pulling from the replay buffer. The second variant, *reuse initial backwards sample*, generates the trajectory when first added to the replay buffer and reuses the entire trajectory if subsequently sampled. The third variant, *with noise*, is to always backwards sample with noisy exploration as per equation equation 13. We plot the L1 policy errors in Figure 11. We observe that *always backward sample* is better than *reuse initial backwards sample* for all loss functions. For DB and TB losses, there is no evidence for any benefit of adding noise, whereas noise improves training for STB loss, performing very similarly to TB loss without noise.

(a)   (b)

Figure 10: (a) L1 error between $\hat{\rho} = \exp(-\beta\hat{V}(x))/Z$ and the reward distribution, $r(x)/Z$ (b) kde potential, bias potential, and positions of final samples after 2.5×10^4 training iterations.

Figure 11: Comparing MetaGFN variants.

D.3 ALANINE DIPEPTIDE ENVIRONMENT DETAILS

Computing the free energy surface: To obtain a ground-truth free energy surface (FES) in ϕ-ψ space, we ran a 250ns NPT well-tempered metadynamics MD simulation of alanine dipeptide at temperature 300K ($\beta = 0.4009$), pressure 1bar with the TIP3P explicit water model (Jorgensen et al., 1983). We used the PLUMMED plugin (Bonomi et al., 2019) for OpenMM (Eastman et al., 2017) with the AMBER14 force field (Salomon-Ferrer et al., 2013).

Figure 12: The potential KDE $\hat{V}$ learnt using MetaGFN on the alanine dipeptide environment, concentration $\kappa = 10$.

Parameterisation: The forward and backward policies are a mixture of three bivariate von Mises distributions. We parameterise $\hat{p}_F$, $\hat{p}_B$ and $\hat{f}$ through three heads of an MLP with 3 hidden layers with 512 hidden units per layer, with GeLU activations and dropout probability 0.2. The first two heads have output dimensions of 15, parameterising the 6 means, 6 concentrations, and 3 weights of the mixture of von Mises policy. The third head has output dimension 1 and parameterises the flow function $\hat{f}$. The means are mapped to the range $(-\pi, \pi)$ through $2\arctan(\cdot)$. Concentrations are parameterised in log space and passed through a sigmoid to map to the range $\ln(\kappa) \in (0, 5)$. Mixture weights are normalised with the softmax function. We use batch size $b = 64$. It takes approximately 10 hours to train a continuous GFlowNet in this environment with $B = 10^5$ batches.

MetaGFN: We use freqRB = 2, freqMD = 10, $\Delta t = 0.01$, $n = 2$, $\beta = 0.4009$, $\gamma = 0.1$, $w = 10^{-5}$, $\kappa = 10$, $\epsilon = 10^{-6}$. The bias and KDE potentials are stored on a uniform grid with grid spacing 0.1. Initial samples are drawn from a Gaussian distribution, mean centred $P_{||}$, variance $\sigma^2 = (0.1, 0.1)$, and initial momenta from a Gaussian, mean $\mu = (0, 0)$, variance $\sigma^2 = (0.05, 0.05)$. In Figure 12 we show the resulting learnt KDE potential with these parameters.

Evaluation: The L1 error of a histogram of on-policy samples, $\hat{\rho}(\phi, \psi)$, is computed via a two-dimensional generalisation of equation D.2; error $= \frac{1}{2} \int_{-\pi}^{\pi} \int_{-\pi}^{\pi} \left| \hat{\rho}(\phi, \psi) - \frac{r(\phi, \psi)}{Z} \right| d\phi d\psi$, estimated by a discrete sum with grid spacing 0.1.

D.4 GRID ENVIRONMENTS DETAILS

Parameterisation: For the two-dimensional grid, we use a mixture of 4 Gaussians. For the three and four dimensional (hyper)grids, we use a mixture of 2 Gaussians (but use longer trajectories, see Section 4). We parameterise $\hat{p}_F$, $\hat{p}_B$ and the flow $\hat{f}$ through an MLP with 3 hidden layers, 512 hidden units per layer, GELU activation function and dropout probability 0.2. The means and standard deviations are mapped to the range $\mu \in (-15, 15)$ and $\sigma \in (0.1, 7)$ through sigmoid functions. Mixture weights are normalised with the softmax function. We use batch size $b = 128$. It takes approximately 10 hours to train a continuous GFlowNet in this environment with $B = 10^5$ batches.

MetaGFN: We use freqRB = 2, freqMD = 10, $\Delta t = 0.35$, $n = 3$, $\beta = 1$, $\gamma = 2$, $w = 0.10$, $\sigma = 2$. The bias and KDE potentials are stored on a uniform grid with grid spacing 0.075/0.3/0.6 (2, 3, and 4 dimensions respectively). Initial samples are drawn from a Gaussian distribution, mean centred at the origin, isotropic variance $\sigma^2 = 1$. Momenta are initialised to zero.

Evaluation: The L1 error between the histogram of the terminal states of 10^4 on-policy samples and the exact distribution is computed, e.g. for the 2D grid, error $= \frac{1}{2} \int_{-15}^{15} \int_{-15}^{15} \left| \hat{\rho}(x, y) - \frac{r(x, y)}{Z} \right| dx dy$, estimated by a discrete sum with grid spacing 0.075.