LORD: LOWER-DIMENSIONAL EMBEDDING OF LOG-SIGNATURE IN NEURAL ROUGH DIFFERENTIAL EQUATIONS

ABSTRACT

The problem of processing very long time-series data (e.g., a length of more than 10,000) is a long-standing research problem in machine learning. Recently, one breakthrough, called neural rough differential equations (NRDEs), has been proposed and has shown that it is able to process such data. Their main concept is to use the log-signature transform, which is known to be more efficient than the Fourier transform for irregular long time-series, to convert a very long time-series sample into a relatively shorter series of feature vectors. However, the log-signature transform causes non-trivial spatial overheads. To this end, we present the method of **LO**we**R**-**D**imensional embedding of log-signature (LORD), where we define an NRDE-based autoencoder to implant the higher-depth log-signature knowledge into the lower-depth log-signature. We show that the encoder successfully combines the higher-depth and the lower-depth log-signature knowledge, which greatly stabilizes the training process and increases the model accuracy. We conduct experiments with multiple very long time-series benchmark datasets and the improvement ratio by our method is up to 75% in terms of various classification and forecasting evaluation metrics.

1 INTRODUCTION

Time-series data occurs frequently in real-world applications (Reinsel, 2003; Fu, 2011; Li et al., 2018; Yu et al., 2018; Wu et al., 2019; Guo et al., 2019; Bai et al., 2019; Song et al., 2020; Huang et al., 2020; Bai et al., 2020; Li & Zhu, 2021; Chen et al., 2021; Fang et al., 2021; Ren et al., 2021; Tekin et al., 2021). However, it is known that very long time-series data (e.g., a time-series length of more than 10,000) is not straightforward to process with deep learning despite various techniques ranging from recurrent neural networks (RNNs) to neural ordinary/controlled differential equations (NODEs and NCDEs). RNNs are known to be unstable when training with such very long sequences and the maximum length that can be processed by NODEs and NCDEs is more or less the same as that by RNNs (Morrill et al., 2021; Aicher et al., 2020; Trinh et al., 2018; Stoller et al., 2019; Bai et al., 2018). However, one breakthrough has been recently proposed, namely neural rough differential equations (NRDEs).

NRDEs are based on the rough path theory which was established to make sense of the controlled differential equation:

$$d\mathbf{z}(t) = f(\mathbf{z}(t))dX(t), \tag{1}$$

where X is a control continuous path, and $\mathbf{z}(t)$ is a hidden vector at time t. A prevalent example of X is a (semimartingale) Wiener process, in which case the equation reduces to a stochastic differential equation. In this sense, the rough path theory also extends stochastic differential equations beyond the semimartingale environment (Lyons et al., 2004).

One key concept in the rough path theory is the *log-signature* of a path. It had been proved that the log-signature of a path with bounded variations is unique under mild conditions (Lyons & Xu, 2018; Geng, 2017) and most time-series data that happens in the field of deep learning has bounded variations. Therefore, one can interpret that the log-signature is a unique feature of the path.

(a) Directly reducing the dimensionality   (b) Combining both log-signature information (our method)

Figure 1: Two possible approaches to reduce the dimensionality of the higher-depth log-signature. The dark gray means a processing in a higher-dimensional space and the light gray means that in a lower-dimensional space. Our embedding method in (b) is better than the baseline in (a) in that i) the higher-dimensional processing is deferred to the decoder which will be discarded after pre-training the autoencoder, and ii) our method does not involve any higher-dimensional processing during the main training and inference processes. We pre-train the autoencoder and in the main training step, we discard the decoder, fix the encoder, and train only the main NRDE for a downstream task (cf. Table 1). In this way, we can exclude the higher-dimensional processing as early as possible.

Given a time-series sample $\{\mathbf{x}_i\}_{i=0}^N$ annotated with its observation time-points $\{t_i\}_{i=0}^N$, where $t_0 = 0$, $t_N = T$, and $t_i < t_{i+1}$, NRDEs construct a continuous path $X(t)$, where $t \in [0, T]$, with an interpolation algorithm, where $X(t_i) = \mathbf{x}_i$ for $t_i \in \{t_i\}_{i=0}^N$. In other words, the path has the same value as the observation $\mathbf{x}_i$ when t is one of the observation time-points and otherwise, interpolated values. As shown in Fig. 1, a log-signature (each dotted yellow box in the figure) is calculate every P-length sub-path, and another time-series of log-signatures, denoted $\{\mathbf{s}_j\}_{j=0}^{\frac{T}{P}-1}$, is created. The log-signature calculation has one important hyperparameter D called *depth* — the higher the depth is, the more accurately represented each sub-path is (cf. Eq. 2). The sub-path length P and the depth D decides the number and the dimensionality of log-signatures, respectively.

However, one downside is $\dim(\mathbf{s}) > \dim(\mathbf{x})$. As a matter of fact, $\dim(\mathbf{s})$ grows exponentially w.r.t. $\dim(\mathbf{x})$ (cf. Eq. 2). Since the dimensionality of the input data is, given a dataset, fixed, we need to decrease D to reduce overheads, e.g., the number of parameters of the original NRDE design in (Morrill et al., 2021) is 298K for $D = 3$ vs. 65K for $D = 2$ in EigenWorms in Table 4. However, it is known that signatures with a higher-depth better represents sub-paths than signatures with a lower-depth, e.g., the best accuracy score is 0.81 for $D = 3$ vs. 0.78 for $D = 2$ in EigenWorms.

Figure 2: The training loss of LORD is much more stable. Other figures are in Appendix.

To this end, we propose to embed the higher-depth signatures onto a lower-dimensional space to i) decrease the complexity of the main NRDE (the solid blue box in Fig. 1), and ii) increase the easiness of training (cf. Fig. 2) and as a result, its model accuracy as well. Fig. 1 shows two possible approaches where we directly reduce the dimensionality of the higher-depth log-signature in Fig. 1 (a) or we adopt the encoder-decoder architecture to combine both the higher-depth and the lower-depth signatures in Fig. 1 (b) — the first approach in Fig. 1 (a) is a baseline model, and our proposed model is the second approach in Fig. 1 (b). Since the higher-depth log-signature should be reconstructed from the embedded vector, one can consider that the higher-depth log-signature is indirectly embedded into the vector. Moreover, the decoder is discarded after its pre-training so our method does not involve any high-cost computation with the higher-depth log-signature in the main training and inference steps as clarified in Table 1.

Table 1: Two phase training in our method

	Pre-trianing	Main training
Decoder	Training	Discarded
Encoder	Training	Fixed
Main NRDE	Not Applicable	Training

Our proposed method, **LOweR-D**imensional embedding of log-signature (LORD), adopts an NRDE-based autoencoder to combine the higher-depth and the lower-depth log-signature knowledge, and utilizes the embedded knowledge by the encoder for a downstream machine learning task as shown in Fig. 1 (b). The encoder embeds the lower-depth log-signature from the continuous path X, and the decoder reconstructs the higher-depth log-signature. This specific design is where our key idea lies in. The encoded lower-depth log-signature will contain both the lower-depth and the higher-depth log-signature knowledge because i) it is an encoding of the lower-depth log-signature and ii) the decoder should recover the higher-depth log-signature from it. After pre-training the autoencoder, we discard the decoder to exclude the higher-dimensional processing as early as possible from our framework. After that, we fix the encoder and train only the main NRDE part in the main training process.

We conduct experiments with six very long time-series benchmark datasets and five baselines including NODE, NCDE, and NRDE-based models. RNN-based models cannot process the very long time-series datasets and we exclude them. Our proposed method significantly outperforms all existing baselines. Our contributions can be summarized as follows:

1. We design an NRDE-based *continuous* autoencoder to combine the higher-depth and the lower-depth log-signature information. Since the decoder is discarded after being trained, we adopt the asymmetric architecture that the encoder is lightweight and the decoder is heavyweight in terms of the number of parameters.

2. Our proposed method outperforms all baselines by large margins (up to 75%) in standard benchmark datasets with much smaller model sizes in comparison with the original NRDE design.

2 RELATED WORK AND PRELIMINARIES

Signature Transform Let $\{\mathbf{x}_i\}_{i=0}^N$ be a sequence of N vectors (i.e., time-series sample) and $\{t_i\}_{i=0}^N$ be their observation time-points. The signature of the time-series sample is defined as follows:

$$S_{r_i,r_{i+1}}^{i_1,\dots,i_k}(X) = \int \cdots \int_{r_i < t_1 < \dots < t_k < r_{i+1}} \prod_{j=1}^k \frac{dX^{i_j}}{dt}(t_j)dt_j,$$

$$Sig_{r_i,r_{i+1}}^D(X) = \Big(\{S_{r_i,r_{i+1}}^i(X)^{(i)}\}_{i=1}^{\dim(\mathbf{x})}, \{S_{r_i,r_{i+1}}^{i,j}(X)\}_{i,j=1}^{\dim(\mathbf{x})}, \dots, \{S_{r_i,r_{i+1}}^{i_1,\dots,i_D}(X)\}_{i_1,\dots,i_D=1}^{\dim(\mathbf{x})} \Big). \tag{2}$$

However, the signature has redundancy, e.g., $S_{a,b}^{1,2}(X) + S_{a,b}^{2,1}(X) = S_{a,b}^1(X)S_{a,b}^2(X)$ and we can know a value if knowing three others. The log-signature $LogSig_{r_i,r_{i+1}}^D(X)$ is then created after dropping the redundancy from the signature. In this work, we use this log-signature definition in default to design our method. We use $LogSig^D$ without the range in the subscript to denote the general concept of the log-signature with depth D.

The log-signature transform is closely related to the Fourier transform. However, the fundamental difference between them is that the Fourier transform models a path as a linear combination within a functional basis whereas the log-signature transform provides a basis itself (Kidger et al., 2019). For complexity reasons, we typically use the log-signature of depth $D \le 3$ (Morrill et al., 2021).

NRDEs Owing to the log-signature transform of time-series, NRDEs (Morrill et al., 2021) are defined as follows:

$$g(X,t) = \frac{LogSig_{r_i,r_{i+1}}^D(X)}{r_{i+1} - r_i} \text{ for } t \in [r_i, r_{i+1}),$$

$$\mathbf{z}(T) = \mathbf{z}(0) + \int_0^T f(\mathbf{z}(t);\theta_f)g(X,t)dt, \tag{3}$$

where $LogSig_{r_i,r_{i+1}}^D(X)$ means the log-signature created from the path X within the interval $[r_i, r_{i+1})$. $\frac{LogSig_{r_i,r_{i+1}}^D(X)}{r_{i+1}-r_i}$ is a piecewise approximation of the time-derivative of the log-signature in the short interval $[r_i, r_{i+1})$. D means the depth of the log-signature. Once we define the sub-path length P, the intervals $\{[r_i, r_{i+1})\}_{i=0}^{\frac{T}{P}-1}$ are decided, i.e., $P = r_{i+1} - r_i$ for all i. Then, the time-series of $LogSig_{r_i,r_{i+1}}^D(X)$ constitutes $\{\mathbf{s}_j\}_{j=0}^{\frac{T}{P}-1}$ in our notation.

NRDEs use Eq. 3 to derive $\mathbf{z}(T)$ from $\mathbf{z}(0)$, which can be considered as a continuous analogue to RNNs since it continuously reads the time-derivative of the log-signature. Therefore, $\mathbf{z}(T)$ is defined by the initial value $\mathbf{z}(0)$ and the sequence of the time-derivative of the log-signature.

NODEs On the other hand, NODEs (Chen et al., 2018) use the following equation:

$$\mathbf{z}(T) = \mathbf{z}(0) + \int_0^T f(\mathbf{z}(t), t; \theta_f)dt, \tag{4}$$

which means $\mathbf{z}(T)$ is solely defined by the initial value $\mathbf{z}(0)$ — the entire evolving path from $\mathbf{z}(0)$ to $\mathbf{z}(T)$ is defined by the initial value in ODEs. The ODE function f approximates $\frac{d\mathbf{z}(t)}{dt}$. NODEs are not considered as a continuous analogue to RNNs but to residual networks (Chen et al., 2018).

NCDEs NCDEs are closer to NRDEs than NODEs in that they use the following equation:

$$\mathbf{z}(T) = \mathbf{z}(0) + \int_0^T f(\mathbf{z}(t); \theta_f)dX(t), \tag{5}$$

$$= \mathbf{z}(0) + \int_0^T f(\mathbf{z}(t); \theta_f)\frac{dX(t)}{dt}dt, \tag{6}$$

where $X(t)$ is a continuous interpolated path from $\{\mathbf{x}_i\}_{i=0}^T$. In this regards, NCDEs can also be considered as a continuous analogue to RNNs. However, it does not adopt the log-signature but process the interpolated path directly. Therefore, NCDEs has an inherent disadvantage that they cannot process very long time-series samples. Recall that by creating a log-signature for every P-length sub-path, the entire sequence length can be reduced — moreover, the log-signature is a unique feature of the sub-path (Lyons & Xu, 2018; Geng, 2017).

Long Sequence Time-series Input (LSTI) The problem of processing very long time-series data is a long standing research problem. There are three ways to solve the LSTI problem. First, it reduces the sequence through truncating/summarizing/sampling from a very long input sequence. However, this method may lose information affecting the prediction accuracy. The second is to give the gradient transformation. As the sequence becomes longer, the gradient vanishing problem occurs. Therefore, in (Aicher et al., 2020), the model is trained using only the gradient of the last step. It also solves the problem using auxiliary losses (Trinh et al., 2018). Finally, CNNs (Stoller et al., 2019; Bai et al., 2018) were used to solve the LSTI problem. The convolutional filter captures long term dependencies, but the receptive fields increase exponentially, breaking the sequence.

3 PROPOSED METHOD

We describe our proposed method, LORD-NRDE. We first clarify the motivation of our work and then describe our proposed model design.

Motivation It is known that NRDEs are a generalization of NCDEs (Morrill et al., 2021, Section 3.2). However, one problem in utilizing NRDEs in real-world environments is that $\dim(LogSig_{r_0,r_1}^D(X(t)))$ is an exponential function of $\dim(X(t))$ (Morrill et al., 2021, Section A). This exponential blow-up of dimensionality causes two problems : i) it hinders us from applying NRDEs to high-dimensional time-series data, and ii) it makes the training process complicated since the hidden representation of the exponentially large input should be made for a downstream task. Therefore, we propose to embed the log-signature onto a lower dimensional space so that the training process becomes more tractable and enhance the applicability of NRDEs to high-dimensional data. After the embedding, in other words, the dimensionality of embedded vector is the same as that of the log-signature with depth D_1 but it has knowledge of the log-signature with depth $D_2 > D_1$.

Figure 3: The proposed NRDE-based autoencoder

Algorithm 1: How to train LORD-NRDE

Input: Training data D_{train}, Validating data D_{val}, Maximum iteration numbers max_iter_{AE} and max_iter_{TASK}

1 Initialize the parameters of the encoder (i.e., θ_f, $\theta_{\phi_\mathbf{e}}$), the decoder (i.e., θ_o, $\theta_{\phi_\mathbf{s}}$), and the main NRDE (i.e., θ_g, $\theta_{\phi_\mathbf{z}}$, $\theta_{\phi_\mathbf{output}}$).;

/* Pre-training of the autoencoder */
2 **for** max_iter_{AE} *iterations* **do**
3 | Train the encoder and the decoder using L_{AE} ;
/* Main-training of LORD-NRDE */
4 **for** max_iter_{TASK} *iterations* **do**
5 | Train the main NRDE using L_{TASK};
6 | Validate the best main NRDE parameters with D_{val};
7 **return** the encoder and the main NRDE parameters;

Overall Architecture We describe our proposed method, LORD-NRDE, which consists of three NRDEs: i) an encoder NRDE, ii) a decoder NRDE and iii) a main NRDE to derive $\mathbf{z}(T)$ from $\mathbf{z}(0)$. The role of each NRDE is as follows:

1. The encoder NRDE *continuously* embeds the log-signature with depth D_1 onto another space. We use $\mathbf{e}(t)$ to denote the vector embedded from the log-signature at time t, denoted $LogSig_{r_0,r_1}^{D_1}(X(t))$.

2. The decoder NRDE reconstructs the log-signature with depth $D_2 > D_1$, denoted $LogSig_{r_0,r_1}^{D_2}(X(t))$, from $\mathbf{e}(t)$.

3. The main NRDE reads $\mathbf{e}(t)$ to evolve $\mathbf{z}(t)$ and derive $\mathbf{z}(T)$. There is an output layer which reads $\mathbf{z}(T)$ and makes inference.

We note that $\dim(LogSig_{r_0,r_1}^{D_2}(X(t))) > \dim(\mathbf{e}(t)) = \dim(LogSig_{r_0,r_1}^{D_1}(X(t)))$, where $t \in [0,T]$. In other words, we require that the encoder produces embedding vectors that contain both the log-signature knowledge with D_1 and D_2 depth.

LORD-NRDE To this end, we propose the following method:

$$\mathbf{z}(T) = \mathbf{z}(0) + \int_0^T g(\mathbf{z}(t); \theta_g) \frac{d\mathbf{e}(t)}{dt} dt, \tag{7}$$

$$\mathbf{e}(T) = \mathbf{e}(0) + \int_0^T f(\mathbf{e}(t); \theta_f) \frac{LogSig_{r_0,r_1}^{D_1}(X(t))}{r_1 - r_0} dt, \tag{8}$$

$$\mathbf{s}(T) = \mathbf{s}(0) + \int_0^T o(\mathbf{s}(t); \theta_o) \frac{d\mathbf{e}(t)}{dt} dt, \tag{9}$$

where $\dim(\mathbf{e}(t)) = \dim(LogSig_{r_0,r_1}^{D_1}(X(t)))$ and $\dim(\mathbf{s}(t)) = \dim(LogSig_{r_0,r_1}^{D_2}(X(t)))$ with $D_2 > D_1$. The term $d\mathbf{e}(t)$ can be considered as an embedding of the log-signature with depth D_1 at time t, and $\mathbf{e}(t)$ as an embedding of $X(t)$ constructed by the log-signature with depth D_1. Similarly, $d\mathbf{s}(t)$ is a reconstructed log-signature with depth D_2 from the embedding, and $\mathbf{s}(t)$ as $X(t)$ reconstructed by the log-signature with depth D_2. Since $\mathbf{e}(0)$ and $\mathbf{s}(0)$ mean the initial values, we set $\phi_\mathbf{e}(X(0); \theta_{\phi_\mathbf{e}})$, $\phi_\mathbf{s}(\mathbf{e}(0); \theta_{\phi_\mathbf{s}})$, where ϕ means a transformation function.

Therefore, $\mathbf{e}(t)$ and $\mathbf{s}(t)$ constitute an autoencoder based on NDREs as shown in Fig. 3. In our design, we use the asymmetrical setting for them, where the encoder RDE is lightweight and the decoder RDE is heavyweight in terms of the number of parameters, considering the applicability of our design to real-world environments. Since the decoder NRDE is discarded after its pre-training, the heavyweight setting causes no problems afterwards — our method requires more resources for the pre-training process though.

There are three functions in Eqs. 7 to 9, denoted g, f, and o, respectively. Their definitions are as follows:

$$g(\mathbf{z}(t); \theta_g) = \text{FC}_{out_g, N_g+1}(\psi(\text{FC}_{h_g, N_g}(...\eta(\text{FC}_{h_g, 1}(\mathbf{z}(t))...))), \tag{10}$$

$$f(\mathbf{e}(t); \theta_f) = \text{FC}_{out_f, N_f+1}(\psi(\text{FC}_{h_f, N_f}(...\eta(\text{FC}_{h_f, 1}(\mathbf{e}(t))...))), \tag{11}$$

$$o(\mathbf{s}(t); \theta_o) = \text{FC}_{out_o, N_o+1}(\psi(\text{FC}_{h_o, N_o}(...\eta(\text{FC}_{h_o, 1}(\mathbf{s}(t))...))), \tag{12}$$

where FC_h is a fully-connected (FC) layer whose output size is h. N_g, N_f, N_o means the number of FC layers. ψ and η are the hyperbolic tangent and rectified linear unit activations, respectively.

Training Method To train the NRDE-based autoencoder, we use the following loss:

$$L_{recon} = \frac{\sum_{i=1}^{N} \|(\mathbf{s}(t_i) - \mathbf{s}(t_{i-1})) - LogSig_{t_{i-1}, t_i}^{D_2}(X(t_i))\|_2^2}{N}, \tag{13}$$

$$L_{AE} = L_{recon} + c_{AE}(\|\theta_f\|_2^2 + \|\theta_o\|_2^2 + \|\theta_{\phi_\mathbf{e}}\|_2^2 + \|\theta_{\phi_\mathbf{s}}\|_2^2) + c_\mathbf{e}\|\mathbf{e}\|_2^2, \tag{14}$$

where t_i is a real observation time-point, and c_{AE} is a coefficient of the L_2 regularization terms. $c_\mathbf{e}$ also regularizes the scale of the learned embedding. In addition to L_{AE}, we also have a task loss L_{TASK} which is the standard cross-entropy (CE) loss or the mean squared loss (MSE) loss. From $\mathbf{z}(T)$, we have an output layer, which is typically a fully-connected layer with an appropriate final activation function such as softmax, to produce a prediction $\hat{y}$. $\theta_{\phi_\mathbf{output}}$ denotes the parameters of the output layer. Using the ground-truth information y, we define the task loss L_{TASK}. Therefore, the final loss can be written as follows:

$$L_{TASK} = CE(y, \hat{y}) + c_{TASK}(\|\theta_g\|_2^2 + \|\theta_{\phi_\mathbf{z}}\|_2^2 + \|\theta_{\phi_\mathbf{output}}\|_2^2), \tag{15}$$

where c_{TASK} is a coefficient of the L_2 regularization terms, and $CE(y, \hat{y})$ means a cross-entropy loss — we assume classification but it can be accordingly changed for other tasks.

To implement, we define the following augmented ODE:

$$\frac{d}{dt} \begin{bmatrix} \mathbf{z}(t) \\ \mathbf{e}(t) \\ \mathbf{s}(t) \end{bmatrix} = \begin{bmatrix} g(\mathbf{z}(t); \theta_g) f(\mathbf{e}(t); \theta_f) \frac{LogSig_{r_0, r_1}^{D_1}(X(t))}{r_1 - r_0} \\ f(\mathbf{e}(t); \theta_f) \frac{LogSig_{r_0, r_1}^{D_1}(X(t))}{r_1 - r_0} \\ o(\mathbf{s}(t); \theta_o) f(\mathbf{e}(t); \theta_f) \frac{LogSig_{r_0, r_1}^{D_1}(X(t))}{r_1 - r_0} \end{bmatrix}, \tag{16}$$

where we replace $\frac{d\mathbf{e}(t)}{dt}$ with $f(\mathbf{e}(t); \theta_f) \frac{LogSig_{r_0, r_1}^{D_1}(X(t))}{r_1 - r_0}$ (as defined in Eq. 8), and the initial values are defined as follows:

$$\begin{bmatrix} \mathbf{z}(0) \\ \mathbf{e}(0) \\ \mathbf{s}(0) \end{bmatrix} = \begin{bmatrix} \phi_\mathbf{z}(X(0)); \theta_{\phi_\mathbf{z}}) \\ \phi_\mathbf{e}(X(0)); \theta_{\phi_\mathbf{e}}) \\ \phi_\mathbf{s}(\mathbf{e}(0); \theta_{\phi_\mathbf{s}}) \end{bmatrix}, \tag{17}$$

where $\phi_\mathbf{z}$ and $\phi_\mathbf{e}$ are transformation functions to produce the initial values from the initial observation $X(0)$, and $\phi_\mathbf{s}$ is a transformation function to produce the initial reconstructed value from the initial embedded vector $\mathbf{e}(0)$. We use a fully-connected layer for each of them.

Alg. 1 shows the training algorithm. In Line 3, we pre-train the autoencoder for max_iter_{AE} iterations. After discarding the decoder and fixing the encoder, we then train the main NRDE in Line 5 for max_iter_{TASK} iterations. Using D_{val}, we validate and choose the best parameters.

4 EXPERIMENTAL EVALUATIONS

We describe our experimental environments and results. The mean and variance of 5 different seeds are reported for model evaluation. We refer to Appendix for reproducibility.

4.1 EXPERIMENTAL ENVIRONMENTS

Datasets We use six real-word dataset which all contain very long time-series samples. There are 3 classification datasets in the University of East Anglia (UEA) repository (Tan & Webb):

`EigenWorms`, `CounterMovementJump`, and `SelfRegulationSCP2`. `EigenWorms` has a time-series length of 17,984 and a channel of 7 which contains the movement data of round-worms. The goal is to classify each worm among 5 worm types. `CounterMovementJump` has 4,250 length and 4 channels which means accelerations data of each 3D-axis. Using accelerations data, the type of jump is predicted among 3 types. The object of `SelfRegulationSCP2` is to classify whether the subject moves the computer's cursor up or down, using 8 channels of the EEG data. Its time-series length is 1,153.

For forecasting, three Beth Israel Deaconess Medical Centre (`BIDMC`) datasets are used, which come from the TSR archive (Tan & Webb). Using the PPG and ECG information, each task is to predict a person's heart rate (`HR`), respiratory rate (`RR`), or oxygen saturation (`SpO2`), respectively. The time-series length is 4,000.

Baselines There are three types of baselines in our Experiments, ranging from NODE to NCDE and NRDE-based baseline models. `ODE-RNN` is one of the state-of-the-art NODE models in processing time-series. Following the suggestion in (Morrill et al., 2021), we merge P observations into one merged observation and feed it into `ODE-RNN`, in which case `ODE-RNN` is able to process much longer time-series, i.e., the dimensionality of the merged observation is P times larger than that of the original observation or equivalently, the length of the merged time-series is P times shorter than that of the original one. `NCDE` is the original NCDE design in (Kidger et al., 2020). Attentive NCDE (`ANCDE`) is an extension of `NCDE` by adding an attention mechanism into it, which significantly outperforms `NCDE` (Jhin et al., 2021). For the NRDE-type baselines, we consider i) the original NRDE design (Morrill et al., 2021), and ii) the one in Fig. 1 (a) which directly embeds the higher-depth log-signature into a lower-dimensional space, each of which is called `NRDE` and `DE-NRDE`, respectively. For those NRDE-based models, we clarify its one important hyperparameter, *depth*, as part of its name, e.g., $NRDE_2$ means `NRDE` with $D = 2$. One important point is that `NRDE` is a generalization of `NCDE`. Therefore, $NRDE_1$ is theoretically identical to `NCDE` and for this reason, we set $D > 1$ for `NRDE`.

Hyperparameters When using NRDEs, there is one crucial hyperparameter, the log-signature depth D. We use two depth settings which were used in (Morrill et al., 2021). For our LORD-NRDE, there are two depths, D_1 and D_2, where $D_1 < D_2$. $LORD_{D_1 \rightarrow D_2}$ means that LORD-NRDE's decoder recovers the D_2-depth log-signature from the D_1-depth log-signature. The number of layers in the encoder, decoder and main NRDE, N_g, N_f, and N_o of Eqs. 10 to 12, are in $\{2, 3\}$. The hidden sizes, h_g, h_f, and h_o of Eqs. 10 to 12, are in $\{32, 64, 128, 192\}$. The coefficients of the L_2 regularizers in Eqs. 14 and 15 are in $\{1 \times 10^{-5}, 1 \times 10^{-6}\}$. The coefficient of the embedding regularizer, $c_\mathbf{e}$ in Eq. 14 is in $\{0, 1, 10\}$. The max iteration numbers, max_iter_{AE} and max_iter_{TASK} in Alg. 1, are in $\{400, 500, 1000, 1500, 2000\}$. The learning rate of the pre-training and main-training is 1×10^{-3}.

We also conduct experiments by setting the sub-path length P to 4, 8, 32, 64, 128, 256, or 512 observations. In other words, we crate one log-signature for every P input observation for NCDE and NRDE-based models. For `ODE-RNN`, as described earlier, we simply concatenate P observations into one observation. The final time T is large in our experiments, e.g., $T > 10,000$, and the number of log-signatures is $\lfloor \frac{T}{P} \rfloor$.

Evaluation Methods We reuse the very long time-series classification and forecasting evaluation methods of (Morrill et al., 2021) and extend the methods by adding more datasets and more evaluation metrics. We use accuracy, macro F1, and ROCAUC for binary classification; accuracy, macro/weighted F1, and ROCAUC for multi-class classification; and R^2, explained variance, mean squared error (MSE), and mean absolute error (MAE) for forecasting — we list the complete results in Appendix after introducing key results in the main manuscript. We also show the number of parameters for each model — for our `LORD`, we exclude the parameter numbers of the decoder since it is discarded after the pre-training. We train and test each model 5 times with different seeds. If the mean of score is the same, the smaller standard deviation is better.

Table 2: Highlights in Classification

Method	Acc.	Mac.F1	ROCAUC	#Params
ODE-RNN	-9%	-19%	-11%	-20%
NCDE	-4%	-8%	-5%	-64%
ANCDE	0%	0%	0%	15%
$NRDE_2$	0%	0%	0%	0%
$NRDE_3$	2%	4%	2%	537%
$DE-NRDE_2$	-4%	-7%	-3%	-48%
$DE-NRDE_3$	-2%	-2%	0%	177%
$LORD_{1\to2}$	16%	23%	11%	-55%
$LORD_{1\to3}$	15%	20%	10%	-46%
$LORD_{2\to3}$	8%	9%	4%	17%

Table 3: Highlights in Forecasting

Method	R^2	MSE	#Params
ODE-RNN	44%	41%	-36%
NCDE	-45%	-55%	-30%
ANCDE	-34%	-45%	-52%
$NRDE_2$	0%	0%	0%
$NRDE_3$	0%	-5%	82%
$DE-NRDE_2$	39%	35%	-20%
$DE-NRDE_3$	62%	59%	31%
$LORD_{1\to2}$	53%	47%	-65%
$LORD_{1\to3}$	51%	46%	-59%
$LORD_{2\to3}$	75%	72%	-39%

4.2 EXPERIMENTAL RESULTS

Summary of Experimental Results Since our main result tables have many items, we quickly summarize their highlights in Tables 2 and 3. To calculate the improvement in evaluation metrics, we use the ratio of improvement over $NRDE_2$ for each metric averaged over all the sub-path lengths and all datasets, e.g., we calculate $\frac{\text{LORD's ROCAUC} - NRDE_2\text{'s ROCAUC}}{NRDE_2\text{'s ROCAUC}}$ and $\frac{NRDE_2\text{'s MSE} - \text{LORD's MSE}}{NRDE_2\text{'s MSE}}$ for all classification cases and average them. The ratio of the number of parameters is calculated similarly.

Overall, LORD outperforms other baselines with smaller numbers of parameters. $LORD_{D_1\to D_2}$ has a larger model size, excluding its decoder, than $NRDE_{D_1}$ whereas it has a much smaller model size than $NRDE_{D_2}$. However, the performance of $LORD_{D_1\to D_2}$ is similar to or better than that of $NRDE_{D_2}$, which proves the efficacy of our method. Using the encoder-decoder structure, the high complexity of processing log-signatures can be reduced and it makes our model smaller and more amenable to train.

Detailed Experimental Results Table 4 show detailed results for some selected evaluation metrics — full tables with all metrics are in Appendix. The best results are in boldface. One point is that many best outcomes are made with moderate P settings. For EigenWorms, ODE-RNN can't achieve good scores for all P settings. Our proposed model, LORD, achieves the best scores. In particular, $LORD_{1\to3}$ with $P = 32$ has a much smaller number of parameters, compared with other baselines that have similar performance. $LORD_{2\to3}$ also significantly outperforms $NRDE_3$ for both accuracy and mode size. For CounterMovementJump and SelfRegulationSCP2, ODE-RNN is better than other NRDE and NCDE-based baselines. However, LORD marks the best scores in all cases.

In all BIDMC experiments, LORD shows outstanding performance. $LORD_{2\to3}$ shows the best performance in almost all cases. Compared with NCDE and NRDE, DE-NRDE has $40 \sim 60\%$ improvements and LORD has $50 \sim 70\%$ improvements. However, LORD's model size is reduced by 60% whereas DE-NRDE's model size is reduced by 20%. Therefore, our proposed method is a better embedding method for log-signatures. Unlike EigenWorms, the time-series length in this dataset is rather short. For that reason, ODE-RNN performs better. Overall, $DE-NRDE_3$ with $P = 128$ has the best performance, among the baseline models. This means that the training difficulty by the large log-signature size can be alleviated by the direct embedding. However, LORD outperforms DE-NRDE.

Figure 4: PCA-based visualization of log-signatures

Additional Results and Visualization Fig. 4 visually compares the three log-signatures and we note that the embedded signature of $d\mathbf{e}(t)$ has the characteristics of both $D_1 = 1$ and $D_2 = 3$. We refer to Appendix for other visualization, detailed results, sensitivity analyses, and reproducibility information.

5 LIMITATIONS AND CONCLUSIONS

The log-signature transform of NRDEs is suitable to irregular and long time-series. However, the log-signature transform requires larger memory footprints and to this end, we presented an autoencoder-based method to embed their higher-dimensional log-signature into a lower-dimensional space, called *LORD*. Our method is carefully devised to eradicate the higher-dimensional computation as early as right after the pre-training of the autoencoder. In the standard

Table 4: Detailed experimental results. The best results regardless of P are in boldface. Moderate configurations of P are needed to see the best results in many cases.

		Accuracy			Macro F1			#Params		
		$P = 4$	32	128	4	32	128	4	32	128
EigenWorms	ODE-RNN	0.35±0.01	0.35±0.03	0.40±0.04	0.11±0.00	0.15±0.07	0.25±0.11	29K	54K	140K
	NCDE	0.68±0.10	0.76±0.05	0.46±0.05	0.61±0.12	0.69±0.07	0.41±0.07	21K	21K	21K
	ANCDE	0.81±0.05	0.77±0.03	0.50±0.06	0.77±0.07	0.73±0.06	0.46±0.07	93K	93K	23K
	NRDE$_2$	0.74±0.04	0.78±0.03	0.73±0.09	0.66±0.08	0.71±0.04	0.66±0.11	65K	65K	65K
	NRDE$_3$	0.72±0.08	0.81±0.04	0.61±0.12	0.62±0.13	0.79±0.05	0.54±0.14	298K	298K	298K
	DE-NRDE$_2$	0.44±0.05	0.73±0.07	0.77±0.07	0.23±0.07	0.63±0.14	0.72±0.08	41K	41K	49K
	DE-NRDE$_3$	0.42±0.07	0.63±0.05	0.84±0.04	0.21±0.10	0.53±0.04	0.81±0.03	179K	179K	241K
	LORD$_{1\to2}$	0.80±0.05	0.84±0.05	0.76±0.06	0.74±0.05	0.84±0.06	0.75±0.08	39K	39K	35K
	LORD$_{1\to3}$	0.77±0.09	**0.86±0.05**	0.74±0.08	0.73±0.12	**0.85±0.06**	0.72±0.09	35K	35K	39K
	LORD$_{2\to3}$	0.82±0.05	0.84±0.02	0.84±0.04	0.78±0.06	0.79±0.05	0.82±0.06	132K	132K	128K
		$P = 64$	128	512	64	128	512	64	128	512
CounterMovementJump	ODE-RNN	0.47±0.02	0.47±0.09	0.45±0.03	0.45±0.03	0.46±0.09	0.44±0.04	25K	214K	139K
	NCDE	0.35±0.06	0.40±0.06	0.41±0.05	0.32±0.09	0.35±0.05	0.38±0.06	58K	25K	47K
	ANCDE	0.35±0.04	0.47±0.06	0.46±0.07	0.34±0.03	0.46±0.07	0.43±0.10	136K	252K	286K
	NRDE$_2$	0.40±0.12	0.40±0.08	0.40±0.09	0.39±0.12	0.38±0.08	0.39±0.09	108K	189K	50K
	NRDE$_3$	0.47±0.09	0.41±0.08	0.47±0.06	0.46±0.09	0.40±0.08	0.45±0.05	529K	522K	2107K
	DE-NRDE$_2$	0.40±0.07	0.38±0.06	0.38±0.05	0.39±0.08	0.33±0.07	0.36±0.06	52K	91K	39K
	DE-NRDE$_3$	0.41±0.07	0.47±0.04	0.42±0.07	0.37±0.07	0.44±0.05	0.40±0.08	204K	279K	731K
	LORD$_{1\to2}$	**0.59±0.04**	0.57±0.06	0.50±0.08	**0.58±0.04**	0.56±0.07	0.49±0.08	87K	51K	65K
	LORD$_{1\to3}$	0.56±0.04	0.53±0.03	0.51±0.03	0.55±0.04	0.52±0.03	0.50±0.03	43K	138K	88K
	LORD$_{2\to3}$	0.40±0.05	0.40±0.08	0.40±0.04	0.38±0.05	0.38±0.08	0.37±0.02	113K	147K	36K
		$P = 32$	64	256	32	64	256	32	64	256
SelfRegulationSCP2	ODE-RNN	0.55±0.05	0.58±0.01	0.56±0.04	0.54±0.06	0.46±0.05	0.48±0.04	57K	41K	139K
	NCDE	0.59±0.07	0.52±0.08	0.54±0.06	0.47±0.12	0.46±0.16	0.54±0.09	42K	215K	316K
	ANCDE	0.60±0.06	0.54±0.04	0.49±0.05	0.55±0.05	0.49±0.05	0.43±0.07	392K	134K	209K
	NRDE$_2$	0.52±0.11	0.56±0.09	0.52±0.11	0.51±0.06	0.45±0.06	0.50±0.07	323K	622K	622K
	NRDE$_3$	0.54±0.05	0.56±0.06	0.50±0.07	0.56±0.05	0.50±0.12	0.48±0.07	3403K	1711K	3438K
	DE-NRDE$_2$	0.59±0.10	0.55±0.06	0.53±0.08	0.53±0.13	0.50±0.08	0.50±0.08	111K	197K	197K
	DE-NRDE$_3$	0.55±0.11	0.51±0.08	0.51±0.10	0.57±0.07	0.54±0.06	0.55±0.03	1092K	542K	1137K
	LORD$_{1\to2}$	0.57±0.10	0.58±0.12	0.53±0.08	0.57±0.06	**0.61±0.06**	0.51±0.08	24K	139K	75K
	LORD$_{1\to3}$	0.57±0.06	**0.62±0.10**	0.53±0.10	0.50±0.06	0.59±0.11	0.56±0.04	139K	123K	161K
	LORD$_{2\to3}$	0.61±0.06	0.61±0.10	0.60±0.07	0.55±0.09	0.56±0.07	0.53±0.06	216K	534K	255K

		R^2			MSE			#Params		
		$P = 8$	128	512	8	128	512	8	128	512
BIDMC32HR	ODE-RNN	0.57±0.29	0.92±0.01	0.81±0.02	0.41±0.28	0.07±0.01	0.18±0.02	4K	15K	52K
	NCDE	0.39±0.04	0.23±0.04	0.19±0.04	0.59±0.04	0.74±0.04	0.78±0.04	50K	50K	50K
	ANCDE	0.44±0.03	0.17±0.06	0.26±0.01	0.54±0.03	0.80±0.06	0.71±0.01	47K	47K	47K
	NRDE$_2$	0.63±0.04	0.67±0.07	0.64±0.07	0.36±0.04	0.32±0.07	0.34±0.07	75K	75K	75K
	NRDE$_3$	0.65±0.08	0.58±0.13	0.40±0.13	0.34±0.08	0.40±0.13	0.58±0.13	141K	141K	141K
	DE-NRDE$_2$	0.82±0.08	0.76±0.05	0.64±0.02	0.17±0.07	0.23±0.05	0.35±0.02	63K	60K	59K
	DE-NRDE$_3$	0.89±0.05	0.93±0.02	0.81±0.09	0.11±0.05	0.07±0.02	0.18±0.08	119K	103K	103K
	LORD$_{1\to2}$	**0.98±0.01**	0.94±0.01	0.44±0.04	**0.02±0.01**	0.06±0.01	0.54±0.04	27K	34K	34K
	LORD$_{1\to3}$	**0.98±0.01**	0.92±0.01	0.45±0.03	**0.02±0.01**	0.07±0.01	0.53±0.03	27K	65K	55K
	LORD$_{2\to3}$	**0.98±0.01**	0.95±0.01	0.85±0.04	**0.02±0.01**	0.04±0.01	0.15±0.04	36K	52K	54K
BIDMC32RR	ODE-RNN	0.54±0.20	0.72±0.01	0.65±0.02	0.45±0.19	0.27±0.01	0.34±0.02	54K	123K	344K
	NCDE	0.21±0.03	0.34±0.05	0.24±0.03	0.76±0.03	0.64±0.05	0.74±0.03	87K	87K	87K
	ANCDE	0.30±0.06	0.39±0.10	0.27±0.03	0.68±0.06	0.59±0.09	0.70±0.03	47K	47K	56K
	NRDE$_2$	0.27±0.04	0.52±0.08	0.50±0.16	0.70±0.04	0.46±0.08	0.48±0.16	124K	124K	124K
	NRDE$_3$	0.34±0.04	0.65±0.14	0.42±0.13	0.64±0.03	0.34±0.13	0.56±0.13	223K	223K	223K
	DE-NRDE$_2$	0.64±0.01	0.58±0.06	0.55±0.06	0.34±0.01	0.40±0.06	0.43±0.06	88K	101K	100K
	DE-NRDE$_3$	0.70±0.06	0.70±0.02	0.57±0.05	0.29±0.05	0.29±0.02	0.41±0.05	139K	164K	163K
	LORD$_{1\to2}$	**0.81±0.02**	0.66±0.01	0.45±0.04	**0.18±0.02**	0.33±0.01	0.53±0.04	27K	27K	40K
	LORD$_{1\to3}$	0.80±0.02	0.67±0.02	0.45±0.03	0.20±0.02	0.32±0.01	0.53±0.03	27K	45K	45K
	LORD$_{2\to3}$	0.80±0.01	0.74±0.01	0.66±0.01	0.19±0.01	0.25±0.01	0.33±0.01	36K	136K	104K
BIDMC32SpO2	ODE-RNN	0.55±0.11	0.90±0.03	0.75±0.02	0.46±0.11	0.10±0.03	0.26±0.03	4K	15K	52K
	NCDE	0.24±0.07	0.21±0.07	0.33±0.04	0.79±0.07	0.81±0.08	0.69±0.05	87K	87K	87K
	ANCDE	0.31±0.03	0.33±0.05	0.37±0.03	0.71±0.03	0.70±0.05	0.65±0.03	47K	47K	47K
	NRDE$_2$	0.22±0.08	0.47±0.10	0.61±0.18	0.81±0.08	0.55±0.10	0.41±0.19	124K	124K	124K
	NRDE$_3$	0.13±0.09	0.68±0.15	0.60±0.18	0.90±0.09	0.33±0.15	0.42±0.19	223K	223K	223K
	DE-NRDE$_2$	0.85±0.01	0.74±0.05	0.59±0.04	0.15±0.01	0.27±0.05	0.43±0.04	88K	100K	100K
	DE-NRDE$_3$	0.90±0.08	0.93±0.03	0.76±0.07	0.10±0.08	0.08±0.03	0.25±0.07	139K	163K	163K
	LORD$_{1\to2}$	0.97±0.00	0.91±0.01	0.58±0.05	0.03±0.00	0.09±0.01	0.43±0.05	27K	34K	62K
	LORD$_{1\to3}$	**0.98±0.01**	0.89±0.03	0.52±0.04	**0.02±0.01**	0.12±0.03	0.49±0.05	27K	27K	38K
	LORD$_{2\to3}$	**0.98±0.01**	0.94±0.01	0.83±0.03	**0.02±0.01**	0.06±0.01	0.18±0.03	36K	56K	69K

benchmark experiments of very long time-series, our proposed method significantly outperforms existing methods and shows relatively smaller model sizes in terms of the number of parameters. Nonetheless, it is still in its early phase to enhance NRDEs and there exist a couple of items to be studied further, e.g., processing long time-series with many channels.

6 ETHICS STATEMENT

Time-series classification and forecasting is closely related to our daily life, ranging from stock price forecasting, weather forecasting to patient mortality classification and so on. Therefore, our enhanced technology has many benefits to our society. It is hard to say that deep neural networks processing time-series have ethical problems.

7 REPRODUCIBILITY STATEMENT

We include detailed reproducibility information in Appendix. In particular, we clarify the neural network architectures we used and their best hyperparameter sets for all experiments in our paper. We also submit our source codes and data with appropriate shell scripts to easily reproduce some selected results due to the 100MB limitation of the supplementary zip file.

REFERENCES

Christopher Aicher, Nicholas J Foti, and Emily B Fox. Adaptively truncating backpropagation through time to control gradient bias. In *Uncertainty in Artificial Intelligence*, pp. 799–808. PMLR, 2020.

Lei Bai, Lina Yao, Salil S. Kanhere, Xianzhi Wang, and Quan Z. Sheng. Stg2seq: Spatial-temporal graph to sequence model for multi-step passenger demand forecasting. In *IJCAI*, pp. 1981–1987, 7 2019. doi: 10.24963/ijcai.2019/274. URL https://doi.org/10.24963/ijcai.2019/274.

Lei Bai, Lina Yao, Can Li, Xianzhi Wang, and Can Wang. Adaptive graph convolutional recurrent network for traffic forecasting. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *NeurIPS*, volume 33, pp. 17804–17815, 2020.

Shaojie Bai, J Zico Kolter, and Vladlen Koltun. Convolutional sequence modeling revisited. 2018.

Ricky T. Q. Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. In *NeurIPS*. 2018.

Yuzhou Chen, Ignacio Segovia-Dominguez, and Yulia R Gel. Z-gcnets: Time zigzags at graph convolutional networks for time series forecasting. *arXiv preprint arXiv:2105.04100*, 2021.

Zheng Fang, Qingqing Long, Guojie Song, and Kunqing Xie. Spatial-temporal graph ode networks for traffic flow forecasting. *arXiv preprint arXiv:2106.12931*, 2021.

Tak-chung Fu. A review on time series data mining. *Engineering Applications of Artificial Intelligence*, 24(1):164–181, 2011.

Xi Geng. Reconstruction for the signature of a rough path. *Proceedings of the London Mathematical Society*, 114(3):495–526, 2017.

Shengnan Guo, Youfang Lin, Ning Feng, Chao Song, and Huaiyu Wan. Attention based spatial-temporal graph convolutional networks for traffic flow forecasting. *AAAI*, 33(01):922–929, Jul. 2019. doi: 10.1609/aaai.v33i01.3301922.

Rongzhou Huang, Chuyin Huang, Yubao Liu, Genan Dai, and Weiyang Kong. Lsgcn: Long short-term traffic prediction with graph convolutional networks. In *IJCAI*, pp. 2355–2361, 2020.

Sheo Yon Jhin, Heejoo Shin, Seoyoung Hong, Solhee Park, , and Noseong Park. Attentive neural controlled differential equations for time-series classification and forecasting. In *ICDM*, 2021.

Patrick Kidger, Patric Bonnier, Imanol Perez Arribas, Cristopher Salvi, and Terry Lyons. Deep signature transforms. In *NeurIPS*, 2019.

Patrick Kidger, James Morrill, James Foster, and Terry Lyons. Neural controlled differential equations for irregular time series. In *NeurIPS*, 2020.

Mengzhang Li and Zhanxing Zhu. Spatial-temporal fusion graph neural networks for traffic flow forecasting. *AAAI*, 35(5):4189–4196, May 2021.

Yaguang Li, Rose Yu, Cyrus Shahabi, and Yan Liu. Diffusion convolutional recurrent neural network: Data-driven traffic forecasting. In *ICLR*, 2018.

Terry Lyons and Weijun Xu. Inverting the signature of a path, 2018.

Terry Lyons, M. Caruana, and T. Lévy. *Differential Equations Driven by Rough Paths*. Springer, 2004. École D'Eté de Probabilités de Saint-Flour XXXIV - 2004.

James Morrill, Cristopher Salvi, Patrick Kidger, James Foster, and Terry Lyons. Neural rough differential equations for long time series. 2021.

Gregory C Reinsel. *Elements of multivariate time series analysis*. Springer Science & Business Media, 2003.

Xiaoli Ren, Xiaoyong Li, Kaijun Ren, Junqiang Song, Zichen Xu, Kefeng Deng, and Xiang Wang. Deep learning-based weather prediction: A survey. *Big Data Research*, 23, 2021.

Chao Song, Youfang Lin, Shengnan Guo, and Huaiyu Wan. Spatial-temporal synchronous graph convolutional networks: A new framework for spatial-temporal network data forecasting. *AAAI*, 34(01):914–921, Apr. 2020. doi: 10.1609/aaai.v34i01.5438.

Daniel Stoller, Mi Tian, Sebastian Ewert, and Simon Dixon. Seq-u-net: A one-dimensional causal u-net for efficient sequence modelling. *arXiv preprint arXiv:1911.06393*, 2019.

Bagnall A. Bergmeir C. Keogh E. Petitjean F. Tan, C. W. and G. I. Monash Webb. Uea classification/regression datasets. http://www.timeseriesregression.org/, http://www.timeseriesclassification.com/.

Selim Furkan Tekin, Oguzhan Karaahmetoglu, Fatih Ilhan, Ismail Balaban, and Suleyman Serdar Kozat. Spatio-temporal weather forecasting and attention mechanism on convolutional lstms. *arXiv preprint*, 2021.

Trieu Trinh, Andrew Dai, Thang Luong, and Quoc Le. Learning longer-term dependencies in rnns with auxiliary losses. In *International Conference on Machine Learning*, pp. 4965–4974. PMLR, 2018.

Zonghan Wu, Shirui Pan, Guodong Long, Jing Jiang, and Chengqi Zhang. Graph wavenet for deep spatial-temporal graph modeling. In *IJCAI*, pp. 1907–1913, 7 2019.

Bing Yu, Haoteng Yin, and Zhanxing Zhu. Spatio-temporal graph convolutional networks: A deep learning framework for traffic forecasting. In *IJCAI*, pp. 3634–3640, 7 2018. doi: 10.24963/ijcai.2018/505. URL https://doi.org/10.24963/ijcai.2018/505.

Table 5: The best hyperparameter in `ODE-RNN`

Data	P	Hidden Path Size
Counter-MovementJump	64	64
	128	256
	512	64
Self-RegulationSCP2	32	128
	64	64
	256	64

Table 6: The best hyperparameter in `NCDE` and `NRDE`

Data	P	Hidden Path Size			CDE Function's Hidden Size			#Hidden Layers		
		$D=1$	2	3	1	2	3	1	2	3
Counter-MovementJump	64	64	64	128	128	128	128	3	2	3
	128	64	256	256	64	64	64	3	2	3
	512	128	64	256	64	64	256	3	2	3
Self-RegulationSCP2	32	64	64	128	64	128	128	2	2	2
	64	64	256	128	256	64	64	3	2	2
	256	256	256	64	128	64	256	3	2	3

Table 7: The best hyperparameter in `ANCDE`

Data	P	Hidden Path Size	#Hidden Layers	Attention Channel Size
EigenWorms	4	128	3	64
	32	128	3	64
	128	64	2	32
Counter-MovementJump	64	128	2	128
	128	256	3	128
	512	64	2	256
Self-RegulationSCP2	32	256	3	128
	64	64	2	128
	256	128	2	128
BIDMC32HR	8	128	2	64
	128	128	2	64
	512	128	2	64
BIDMC32RR	8	128	2	64
	128	128	2	64
	512	128	3	64
BIDMC32SpO2	8	128	2	64
	128	128	2	64
	512	128	2	64

Table 8: The best hyperparameter in `DE-NRDE`

Data	P	Compression Ratio		#Hidden Layers		Hidden Size	
		$D=2$	3	2	3	2	3
EigenWorms	4	0.5	0.5	1	1	128	128
	32	0.5	0.5	1	1	128	128
	128	0.7	0.7	1	1	64	128
Counter-MovementJump	64	0.3	0.3	1	2	128	128
	128	0.3	0.5	2	2	128	64
	512	0.7	0.3	1	1	64	128
Self-RegulationSCP2	32	0.3	0.3	1	2	64	128
	64	0.3	0.3	2	2	64	64
	256	0.3	0.3	2	2	64	128
BIDMC32HR	8	0.7	0.7	2	2	64	128
	128	0.7	0.7	1	1	128	128
	512	0.7	0.7	1	1	64	128
BIDMC32RR	8	0.5	0.5	1	1	128	128
	128	0.7	0.7	1	1	128	128
	512	0.7	0.7	1	1	64	64
BIDMC32SpO2	8	0.5	0.5	1	1	128	128
	128	0.7	0.7	1	1	64	64
	512	0.7	0.7	1	1	64	64

A BEST HYPERPARAMETERS

Our software and hardware environments are as follows: UBUNTU 18.04 LTS, PYTHON 3.7.10, PYTORCH 1.8.1, CUDA 11.4, and NVIDIA Driver 470.42.01, i9 CPU, and NVIDIA RTX A6000.

A.1 BASELINE

There are 5 baselines in our experiments. Each model has its own hyerparameters. `ODERNN` method has a hyperparameter of hidden path size. `NCDE` and `NRDE` have also the same hyperparameter, and in addition, the size of hidden dimension and the number of hidden layers in their CDE and RDE functions. The Attentive NCDE (`ANCDE`) has all of those hyperparameters and in addition, the attention channel size. In `DE-NRDE`, there are addition hyperparameters related to embedding, which are the embedding compression ratio, the size of hidden dimension, and the number of hidden layers in the embedding layer.

In (Morrill et al., 2021), there are three models, `ODE-RNN`, `NCDE` and `NRDE`, and four datasets, `EigenWorms`, `BIDMC32HR`, `BIDMC32RR`, and `BIDMC32SpO2`. For these combinations, we set the hyperparameters as reported in (Morrill et al., 2021). In other cases, we find the best hyperparameters in the following range. All kinds of hidden size in `ODERNN`, `NCDE`, `ANCDE`, and `NRDE` are in {32, 64, 128, 256}. The number of hidden layers in those is in {2,3}. In `DE-NRDE`, the embedding compression ratio, the hidden size, and the number of hidden layers in the embedding layer are in {0.3, 0.5, 0.7}, {64, 128}, and {1,2}, respectively. Tables 5 to 8 show the best hyperparameters of the baselines.

A.2 LORD-NRDE

Table 9 shows the best hyperparameter configuration of our method in each dataset.

Table 9: The best hyperparameter in `LORD`

Method	Data	P	N_f	N_g	N_o	h_f	h_g	h_o	c_{AE}	c_{TASK}	$c_{\mathbf{e}}$	max_iter AE	max_iter TASK
$\text{LORD}_{1\to2}$	EigenWorms	4	3	3	3	64	64	64	1×10^{-6}	1×10^{-6}	0	400	400
		32	3	3	3	64	64	64	1×10^{-6}	1×10^{-6}	0	2000	400
		128	3	2	3	64	64	64	1×10^{-6}	1×10^{-6}	0	2000	400
	Counter-MovementJump	64	2	3	2	32	128	32	1×10^{-6}	1×10^{-6}	1	500	400
		128	3	3	3	64	64	64	1×10^{-6}	1×10^{-6}	1	500	400
		512	2	2	2	64	128	64	1×10^{-6}	1×10^{-6}	1	1500	400
	Self-RegulationSCP2	32	3	3	3	32	32	32	1×10^{-6}	1×10^{-6}	1	1000	400
		64	3	2	3	128	128	128	1×10^{-6}	1×10^{-6}	1	500	400
		256	3	3	3	128	32	128	1×10^{-6}	1×10^{-6}	1	500	400
	BIDMC32HR	8	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	400	2000
		128	3	3	3	32	64	32	1×10^{-5}	1×10^{-5}	0	1000	500
		512	3	3	3	32	64	32	1×10^{-5}	1×10^{-5}	0	1000	500
	BIDMC32RR	8	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	400	2000
		128	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	1000	500
		512	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	1000	500
	BIDMC32SpO2	8	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	400	2000
		128	3	3	3	32	64	32	1×10^{-5}	1×10^{-5}	0	1000	500
		512	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	1000	500
$\text{LORD}_{1\to3}$	EigenWorms	4	3	2	3	64	64	64	1×10^{-6}	1×10^{-6}	0	400	400
		32	3	2	3	64	64	64	1×10^{-6}	1×10^{-6}	0	2000	400
		128	3	3	3	64	64	64	1×10^{-6}	1×10^{-6}	0	2000	400
	Counter-MovementJump	64	2	3	2	32	64	32	1×10^{-6}	1×10^{-6}	1	500	400
		128	3	3	3	128	128	128	1×10^{-6}	1×10^{-6}	1	500	400
		512	3	2	3	32	128	32	1×10^{-6}	1×10^{-6}	1	500	400
	Self-RegulationSCP2	32	2	3	2	32	128	32	1×10^{-6}	1×10^{-6}	1	500	400
		64	3	3	3	32	128	32	1×10^{-6}	1×10^{-6}	1	1500	400
		256	3	3	3	128	128	128	1×10^{-6}	1×10^{-6}	1	1500	400
	BIDMC32HR	8	3	3	3	128	64	128	1×10^{-5}	1×10^{-5}	0	400	2000
		128	3	3	3	32	64	32	1×10^{-5}	1×10^{-5}	0	1000	500
		512	3	3	3	32	64	32	1×10^{-5}	1×10^{-5}	0	1000	500
	BIDMC32RR	8	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	400	2000
		128	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	1000	500
		512	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	1000	500
	BIDMC32SpO2	8	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	400	2000
		128	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	1000	500
		512	3	3	3	32	64	32	1×10^{-5}	1×10^{-5}	0	1000	500
$\text{LORD}_{2\to3}$	EigenWorms	4	3	3	3	64	64	64	1×10^{-6}	1×10^{-6}	0	400	400
		32	3	3	3	64	64	64	1×10^{-6}	1×10^{-6}	0	2000	400
		128	3	2	3	64	64	64	1×10^{-6}	1×10^{-6}	0	2000	400
	Counter-MovementJump	64	3	2	3	128	128	128	1×10^{-6}	1×10^{-6}	1	1500	400
		128	2	2	2	64	128	64	1×10^{-6}	1×10^{-6}	1	1000	400
		512	3	2	3	64	32	64	1×10^{-6}	1×10^{-6}	1	1000	400
	Self-RegulationSCP2	32	3	2	3	32	64	32	1×10^{-6}	1×10^{-6}	1	500	400
		64	2	3	2	128	128	128	1×10^{-6}	1×10^{-6}	1	1000	400
		256	2	3	2	32	128	32	1×10^{-6}	1×10^{-6}	1	500	400
	BIDMC32HR	8	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	400	2000
		128	3	3	3	32	64	32	1×10^{-5}	1×10^{-5}	0	1000	500
		512	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	1000	500
	BIDMC32RR	8	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	400	2000
		128	3	3	3	64	192	64	1×10^{-5}	1×10^{-5}	0	1000	500
		512	3	3	3	128	64	128	1×10^{-5}	1×10^{-5}	0	1000	500
	BIDMC32SpO2	8	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	400	2000
		128	3	3	3	64	64	64	1×10^{-5}	1×10^{-5}	0	1000	500
		512	3	3	3	128	64	128	1×10^{-5}	1×10^{-5}	0	1000	500

B Visualization

We show other PCA based visualizations of the log-signatures. Using PCA, we extract the distributions of $LogSig^{D_1}$, $LogSig^{D_2}$, and $d\mathbf{e}(t)$ of the most important principle components. If two paths have similar distributions on those components, the information contained by the two paths is similar. In Fig. 5, $d\mathbf{e}(t)$ has a similar distribution to that of $LogSig^{D_2}$, not $LogSig^{D_1}$, although $d\mathbf{e}(t)$ is directly made from $LogSig^{D_1}$. From the encoder-decoder learning, $d\mathbf{e}(t)$ can learn the information of $LogSig^{D_2}$.

Figure 5: Examples of the $LogSig^{D_1}$, $LogSig^{D_2}$, and $d\mathbf{e}(t)$ paths in EigenWorms and BIDMC. By Eq. 2, $LogSig^{D_2}$ includes $LogSig^{D_1}$, where $D_2 > D_1$.

C Full Experimental results

In Tables 10 to 15, all experimental results are shown. #Params(D) and #Params(R) denote the number of parameters in the decoder part and in the rest parts except the decoder, respectively.

Table 10: `EigenWorms`

Method	P	Accuracy	Macro F1	Weighted F1	ROCAUC	#Params(D)	#Params(R)
ODE-RNN	4	0.354±0.011	0.107±0.002	0.193±0.004	0.511±0.054	Not Applicable	28707
	32	0.349±0.029	0.150±0.065	0.232±0.064	0.439±0.027	Not Applicable	53795
	128	0.395±0.043	0.249±0.110	0.304±0.095	0.517±0.068	Not Applicable	139811
NCDE	4	0.677±0.099	0.610±0.122	0.665±0.105	0.913±0.018	Not Applicable	21253
	32	0.759±0.047	0.690±0.065	0.756±0.052	0.907±0.016	Not Applicable	21253
	128	0.456±0.046	0.415±0.066	0.458±0.051	0.678±0.055	Not Applicable	21253
ANCDE	4	0.815±0.046	0.770±0.065	0.810±0.046	0.957±0.012	Not Applicable	92726
	32	0.774±0.033	0.727±0.060	0.770±0.033	0.925±0.021	Not Applicable	92726
	128	0.497±0.064	0.456±0.074	0.501±0.063	0.705±0.038	Not Applicable	22806
$NRDE_2$	4	0.744±0.044	0.655±0.076	0.725±0.059	0.915±0.032	Not Applicable	64933
	32	0.779±0.029	0.713±0.044	0.774±0.027	0.934±0.011	Not Applicable	64933
	128	0.728±0.088	0.661±0.106	0.726±0.092	0.908±0.037	Not Applicable	64933
$NRDE_3$	4	0.718±0.083	0.616±0.127	0.695±0.101	0.914±0.023	Not Applicable	297893
	32	0.810±0.043	0.787±0.051	0.814±0.044	0.911±0.020	Not Applicable	297893
	128	0.610±0.117	0.544±0.142	0.600±0.120	0.862±0.063	Not Applicable	297893
$DE-NRDE_2$	4	0.436±0.048	0.230±0.073	0.303±0.066	0.538±0.045	Not Applicable	41331
	32	0.728±0.074	0.631±0.141	0.711±0.095	0.918±0.026	Not Applicable	41331
	128	0.769±0.068	0.723±0.078	0.770±0.070	0.939±0.016	Not Applicable	49304
$DE-NRDE_3$	4	0.421±0.074	0.206±0.096	0.281±0.091	0.583±0.086	Not Applicable	179371
	32	0.626±0.047	0.528±0.038	0.585±0.054	0.878±0.036	Not Applicable	179371
	128	0.841±0.042	0.810±0.029	0.840±0.038	0.960±0.022	Not Applicable	241223
$LORD_{1\to2}$	4	0.795±0.051	0.744±0.051	0.787±0.053	0.948±0.009	24299	38973
	32	0.841±0.053	0.841±0.058	0.843±0.051	0.957±0.016	24299	38973
	128	0.759±0.064	0.748±0.082	0.760±0.061	0.900±0.009	24299	34813
$LORD_{1\to3}$	4	0.774±0.088	0.733±0.122	0.759±0.101	0.944±0.023	86907	34813
	32	0.862±0.053	0.855±0.058	0.861±0.054	0.963±0.021	86907	34813
	128	0.744±0.081	0.716±0.087	0.737±0.076	0.892±0.044	86907	38973
$LORD_{2\to3}$	4	0.821±0.054	0.783±0.062	0.815±0.056	0.960±0.011	278679	132465
	32	0.841±0.021	0.793±0.053	0.835±0.027	0.963±0.008	278679	132465
	128	0.841±0.038	0.823±0.055	0.835±0.049	0.949±0.023	278679	128305

Table 11: `CounterMovementJump`

Method	P	Accuracy	Macro F1	Weighted F1	ROCAUC	#Params(D)	#Params(R)
ODE-RNN	64	0.474±0.023	0.453±0.027	0.455±0.026	0.589±0.018	Not Applicable	24737
	128	0.470±0.093	0.458±0.094	0.459±0.094	0.617±0.055	Not Applicable	213537
	512	0.449±0.032	0.436±0.037	0.436±0.039	0.593±0.031	Not Applicable	139425
NCDE	64	0.351±0.057	0.317±0.091	0.318±0.091	0.473±0.024	Not Applicable	58371
	128	0.404±0.064	0.350±0.050	0.352±0.050	0.520±0.007	Not Applicable	25475
	512	0.411±0.047	0.379±0.064	0.378±0.065	0.496±0.026	Not Applicable	46723
ANCDE	64	0.355±0.041	0.342±0.034	0.342±0.035	0.526±0.033	Not Applicable	135852
	128	0.467±0.060	0.457±0.065	0.457±0.065	0.604±0.031	Not Applicable	252332
	512	0.458±0.073	0.428±0.102	0.428±0.102	0.588±0.074	Not Applicable	285740
$NRDE_2$	64	0.396±0.116	0.391±0.118	0.391±0.118	0.560±0.089	Not Applicable	107907
	128	0.396±0.076	0.379±0.079	0.379±0.078	0.513±0.052	Not Applicable	189059
	512	0.396±0.091	0.388±0.092	0.388±0.092	0.546±0.076	Not Applicable	50435
$NRDE_3$	64	0.465±0.088	0.462±0.093	0.463±0.093	0.616±0.062	Not Applicable	529411
	128	0.409±0.084	0.399±0.081	0.400±0.081	0.573±0.070	Not Applicable	521859
	512	0.465±0.055	0.453±0.050	0.453±0.051	0.618±0.045	Not Applicable	2107395
$DE-NRDE_2$	64	0.398±0.075	0.390±0.076	0.389±0.075	0.573±0.076	Not Applicable	51910
	128	0.384±0.058	0.334±0.071	0.334±0.071	0.567±0.054	Not Applicable	90886
	512	0.375±0.054	0.359±0.064	0.359±0.064	0.525±0.055	Not Applicable	39114
$DE-NRDE_3$	64	0.409±0.072	0.373±0.073	0.373±0.074	0.568±0.068	Not Applicable	204300
	128	0.474±0.038	0.437±0.053	0.437±0.054	0.626±0.030	Not Applicable	279378
	512	0.425±0.069	0.396±0.076	0.398±0.076	0.571±0.059	Not Applicable	730892
$LORD_{1\to2}$	64	0.589±0.038	0.580±0.041	0.580±0.041	0.717±0.023	3262	87191
	128	0.566±0.061	0.563±0.066	0.563±0.066	0.676±0.058	12158	51063
	512	0.501±0.080	0.495±0.082	0.495±0.082	0.638±0.053	7998	65399
$LORD_{1\to3}$	64	0.555±0.041	0.551±0.042	0.550±0.042	0.688±0.038	7282	43127
	128	0.528±0.029	0.523±0.027	0.523±0.027	0.656±0.024	53746	137879
	512	0.508±0.033	0.499±0.028	0.499±0.028	0.637±0.020	8338	88439
$LORD_{2\to3}$	64	0.396±0.049	0.383±0.052	0.383±0.052	0.540±0.061	77158	113265
	128	0.396±0.078	0.384±0.083	0.385±0.083	0.542±0.068	27110	146737
	512	0.400±0.044	0.374±0.022	0.375±0.022	0.537±0.047	31270	36369

Table 12: `SelfRegulationSCP2`

Method	P	Accuracy	F1	ROCAUC	#Params(D)	#Params(R)
ODE-RNN	32	0.551±0.054	0.540±0.064	0.603±0.041	Not Applicable	57375
	64	0.579±0.012	0.462±0.051	0.564±0.019	Not Applicable	40991
	256	0.558±0.045	0.480±0.039	0.533±0.055	Not Applicable	139295
NCDE	32	0.586±0.071	0.471±0.124	0.577±0.130	Not Applicable	42241
	64	0.516±0.079	0.459±0.156	0.557±0.129	Not Applicable	214657
	256	0.544±0.058	0.537±0.087	0.578±0.086	Not Applicable	316161
ANCDE	32	0.604±0.064	0.552±0.048	0.646±0.041	Not Applicable	391698
	64	0.544±0.039	0.490±0.048	0.575±0.074	Not Applicable	134034
	256	0.488±0.052	0.427±0.067	0.461±0.073	Not Applicable	208914
$NRDE_2$	32	0.519±0.110	0.513±0.058	0.572±0.092	Not Applicable	322689
	64	0.561±0.090	0.449±0.062	0.575±0.071	Not Applicable	622209
	256	0.516±0.110	0.498±0.071	0.564±0.096	Not Applicable	622209
$NRDE_3$	32	0.537±0.052	0.560±0.050	0.561±0.049	Not Applicable	3402753
	64	0.558±0.059	0.504±0.118	0.586±0.107	Not Applicable	1710977
	256	0.498±0.066	0.483±0.074	0.543±0.079	Not Applicable	3438465
$DE-NRDE_2$	32	0.589±0.095	0.525±0.130	0.596±0.072	Not Applicable	111051
	64	0.551±0.063	0.496±0.081	0.566±0.073	Not Applicable	196747
	256	0.530±0.078	0.501±0.078	0.538±0.088	Not Applicable	196747
$DE-NRDE_3$	32	0.551±0.109	0.570±0.074	0.655±0.076	Not Applicable	1092158
	64	0.505±0.076	0.539±0.059	0.566±0.110	Not Applicable	542462
	256	0.512±0.100	0.547±0.031	0.591±0.069	Not Applicable	1137022
$LORD_{1\to2}$	32	0.570±0.105	0.566±0.058	0.652±0.059	14572	24361
	64	0.582±0.119	0.613±0.057	0.681±0.071	76684	139433
	256	0.530±0.081	0.512±0.081	0.536±0.087	76684	74857
$LORD_{1\to3}$	32	0.572±0.058	0.501±0.056	0.584±0.036	70132	138761
	64	0.618±0.099	0.591±0.109	0.659±0.094	71188	123241
	256	0.526±0.105	0.558±0.038	0.607±0.061	278452	161161
$LORD_{2\to3}$	32	0.607±0.059	0.552±0.087	0.645±0.093	260580	216405
	64	0.607±0.095	0.555±0.072	0.619±0.060	999684	534037
	256	0.596±0.075	0.529±0.055	0.623±0.064	259524	254549

Table 13: `BIDMC32HR`

Method	P	R^2	Explained Variance	MSE	MAE	#Params(D)	#Params(R)
ODE-RNN	8	0.569±0.290	0.570±0.290	0.415±0.279	0.457±0.172	Not Applicable	3871
	128	0.924±0.011	0.925±0.011	0.073±0.011	0.167±0.009	Not Applicable	15391
	512	0.811±0.024	0.811±0.025	0.182±0.024	0.285±0.019	Not Applicable	52255
NCDE	8	0.388±0.042	0.388±0.042	0.590±0.041	0.552±0.023	Not Applicable	49921
	128	0.227±0.042	0.231±0.046	0.745±0.040	0.638±0.017	Not Applicable	49921
	512	0.191±0.041	0.192±0.041	0.779±0.039	0.654±0.018	Not Applicable	49921
ANCDE	8	0.437±0.031	0.440±0.031	0.542±0.030	0.527±0.019	Not Applicable	47194
	128	0.173±0.062	0.174±0.062	0.796±0.060	0.666±0.019	Not Applicable	47194
	512	0.264±0.011	0.270±0.012	0.709±0.011	0.628±0.016	Not Applicable	47194
$NRDE_2$	8	0.630±0.044	0.631±0.044	0.356±0.042	0.452±0.030	Not Applicable	74689
	128	0.665±0.072	0.665±0.072	0.323±0.069	0.409±0.047	Not Applicable	74689
	512	0.642±0.071	0.643±0.071	0.344±0.069	0.419±0.054	Not Applicable	74689
$NRDE_3$	8	0.650±0.082	0.650±0.082	0.337±0.079	0.430±0.054	Not Applicable	140737
	128	0.582±0.131	0.583±0.131	0.402±0.126	0.458±0.085	Not Applicable	140737
	512	0.395±0.131	0.396±0.131	0.582±0.126	0.535±0.087	Not Applicable	140737
$DE-NRDE_2$	8	0.822±0.077	0.822±0.077	0.171±0.074	0.279±0.080	Not Applicable	63045
	128	0.758±0.051	0.759±0.052	0.233±0.049	0.332±0.045	Not Applicable	59589
	512	0.640±0.024	0.643±0.023	0.346±0.023	0.412±0.016	Not Applicable	58885
$DE-NRDE_3$	8	0.885±0.049	0.885±0.049	0.111±0.048	0.222±0.050	Not Applicable	119050
	128	0.927±0.016	0.928±0.016	0.070±0.016	0.176±0.024	Not Applicable	102538
	512	0.810±0.085	0.810±0.086	0.183±0.082	0.299±0.080	Not Applicable	102538
$LORD_{1\to2}$	8	0.979±0.006	0.979±0.006	0.020±0.005	0.084±0.014	10285	27277
	128	0.937±0.009	0.937±0.009	0.061±0.008	0.119±0.005	3277	34189
	512	0.441±0.039	0.443±0.041	0.538±0.038	0.479±0.033	3277	34189
$LORD_{1\to3}$	8	0.982±0.005	0.982±0.005	0.018±0.005	0.079±0.008	12645	27277
	128	0.922±0.012	0.923±0.013	0.075±0.012	0.129±0.013	40997	65293
	512	0.450±0.031	0.452±0.029	0.530±0.030	0.474±0.007	4613	54925
$LORD_{2\to3}$	8	0.978±0.006	0.979±0.006	0.021±0.006	0.078±0.009	15471	35563
	128	0.954±0.006	0.954±0.006	0.045±0.006	0.121±0.007	6095	51915
	512	0.848±0.043	0.849±0.043	0.146±0.041	0.216±0.028	15471	54283

Table 14: `BIDMC32RR`

Method	P	R^2	Explained Variance	MSE	MAE	#Params(D)	#Params(R)
ODE-RNN	8	0.536±0.195	0.540±0.193	0.447±0.188	0.494±0.124	Not Applicable	53791
	128	0.721±0.010	0.722±0.011	0.269±0.010	0.360±0.006	Not Applicable	122911
	512	0.651±0.018	0.652±0.017	0.337±0.018	0.413±0.016	Not Applicable	344095
NCDE	8	0.215±0.028	0.215±0.028	0.757±0.027	0.663±0.010	Not Applicable	86913
	128	0.337±0.053	0.339±0.053	0.639±0.051	0.595±0.015	Not Applicable	86913
	512	0.236±0.026	0.237±0.026	0.736±0.025	0.626±0.008	Not Applicable	86913
ANCDE	8	0.298±0.062	0.302±0.064	0.677±0.060	0.625±0.033	Not Applicable	47194
	128	0.386±0.097	0.387±0.098	0.592±0.094	0.576±0.036	Not Applicable	47194
	512	0.270±0.028	0.271±0.028	0.704±0.027	0.619±0.010	Not Applicable	55514
NRDE$_2$	8	0.274±0.037	0.274±0.037	0.700±0.035	0.637±0.019	Not Applicable	123969
	128	0.521±0.082	0.521±0.082	0.462±0.079	0.500±0.035	Not Applicable	123969
	512	0.498±0.162	0.498±0.162	0.484±0.156	0.512±0.075	Not Applicable	123969
NRDE$_3$	8	0.337±0.035	0.338±0.035	0.639±0.034	0.600±0.019	Not Applicable	222785
	128	0.646±0.138	0.647±0.138	0.341±0.133	0.403±0.087	Not Applicable	222785
	512	0.424±0.130	0.424±0.130	0.556±0.126	0.537±0.071	Not Applicable	222785
DE-NRDE$_2$	8	0.644±0.013	0.647±0.012	0.343±0.013	0.388±0.017	Not Applicable	88196
	128	0.584±0.061	0.586±0.060	0.401±0.059	0.440±0.036	Not Applicable	100677
	512	0.552±0.063	0.554±0.061	0.432±0.061	0.474±0.033	Not Applicable	99973
DE-NRDE$_3$	8	0.699±0.055	0.699±0.055	0.290±0.053	0.351±0.041	Not Applicable	139144
	128	0.703±0.017	0.703±0.017	0.287±0.016	0.352±0.015	Not Applicable	164106
	512	0.574±0.053	0.575±0.054	0.411±0.051	0.454±0.025	Not Applicable	162570
LORD$_{1\rightarrow2}$	8	0.808±0.021	0.809±0.022	0.185±0.020	0.272±0.011	10285	27277
	128	0.662±0.007	0.664±0.007	0.326±0.006	0.386±0.012	10285	27277
	512	0.448±0.044	0.450±0.044	0.532±0.042	0.522±0.012	10285	39757
LORD$_{1\rightarrow3}$	8	0.798±0.017	0.799±0.017	0.195±0.016	0.277±0.014	12645	27277
	128	0.671±0.016	0.672±0.015	0.318±0.015	0.376±0.012	12645	44973
	512	0.451±0.026	0.453±0.023	0.530±0.025	0.520±0.012	12645	44973
LORD$_{2\rightarrow3}$	8	0.800±0.007	0.801±0.007	0.192±0.007	0.281±0.008	15471	35563
	128	0.744±0.011	0.744±0.011	0.247±0.010	0.315±0.010	15471	136459
	512	0.662±0.015	0.664±0.014	0.326±0.014	0.386±0.011	46511	103531

Table 15: `BIDMC32SpO2`

Method	P	R^2	Explained Variance	MSE	MAE	#Params(D)	#Params(R)
ODE-RNN	8	0.551±0.108	0.552±0.108	0.464±0.112	0.487±0.082	Not Applicable	3871
	128	0.899±0.025	0.901±0.023	0.104±0.026	0.225±0.015	Not Applicable	15391
	512	0.749±0.024	0.749±0.024	0.259±0.025	0.365±0.021	Not Applicable	52255
NCDE	8	0.240±0.071	0.245±0.067	0.785±0.073	0.686±0.034	Not Applicable	86913
	128	0.215±0.074	0.217±0.072	0.811±0.077	0.694±0.035	Not Applicable	86913
	512	0.328±0.046	0.332±0.045	0.694±0.046	0.639±0.007	Not Applicable	86913
ANCDE	8	0.311±0.034	0.313±0.035	0.712±0.035	0.662±0.014	Not Applicable	47194
	128	0.327±0.049	0.327±0.049	0.696±0.050	0.631±0.017	Not Applicable	47194
	512	0.372±0.033	0.374±0.034	0.648±0.034	0.592±0.013	Not Applicable	47194
NRDE$_2$	8	0.218±0.078	0.219±0.078	0.807±0.080	0.694±0.036	Not Applicable	123969
	128	0.470±0.100	0.471±0.100	0.547±0.103	0.559±0.048	Not Applicable	123969
	512	0.607±0.180	0.607±0.180	0.406±0.186	0.455±0.123	Not Applicable	123969
NRDE$_3$	8	0.131±0.091	0.134±0.090	0.898±0.094	0.720±0.027	Not Applicable	222785
	128	0.681±0.147	0.681±0.147	0.330±0.151	0.410±0.126	Not Applicable	222785
	512	0.596±0.181	0.596±0.181	0.417±0.187	0.463±0.139	Not Applicable	222785
DE-NRDE$_2$	8	0.854±0.013	0.854±0.013	0.151±0.013	0.252±0.015	Not Applicable	88196
	128	0.740±0.047	0.740±0.048	0.269±0.049	0.313±0.039	Not Applicable	99973
	512	0.586±0.042	0.586±0.042	0.428±0.043	0.453±0.033	Not Applicable	99973
DE-NRDE$_3$	8	0.903±0.079	0.903±0.079	0.100±0.082	0.192±0.090	Not Applicable	139144
	128	0.926±0.026	0.927±0.026	0.076±0.027	0.164±0.024	Not Applicable	162570
	512	0.759±0.067	0.761±0.067	0.249±0.069	0.357±0.061	Not Applicable	162570
LORD$_{1\rightarrow2}$	8	0.975±0.003	0.976±0.002	0.025±0.003	0.096±0.009	10285	27277
	128	0.909±0.009	0.910±0.009	0.094±0.009	0.172±0.013	3277	34189
	512	0.583±0.047	0.583±0.047	0.431±0.048	0.435±0.024	10285	61549
LORD$_{1\rightarrow3}$	8	0.981±0.005	0.981±0.004	0.020±0.005	0.086±0.006	12645	27277
	128	0.889±0.025	0.889±0.025	0.115±0.026	0.186±0.029	12645	27277
	512	0.521±0.045	0.522±0.044	0.495±0.046	0.459±0.024	4613	38349
LORD$_{2\rightarrow3}$	8	0.981±0.005	0.981±0.005	0.019±0.005	0.088±0.007	15471	35563
	128	0.940±0.007	0.940±0.007	0.062±0.007	0.145±0.004	15471	56395
	512	0.829±0.027	0.830±0.027	0.177±0.028	0.236±0.016	46511	69323

Table 16: Sensitivity of max_iter_{AE} in `EigenWorms` ($P = 128$)

Method	max_iter_{AE}	Accuracy	Macro F1	Weighted F1	ROCAUC
$\text{LORD}_{1\to2}$	0	0.656±0.094	0.588±0.107	0.649±0.100	0.847±0.056
	100	0.713±0.042	0.716±0.058	0.713±0.046	0.862±0.023
	300	0.744±0.048	0.727±0.059	0.744±0.051	0.893±0.029
	500	0.733±0.105	0.725±0.104	0.738±0.111	0.889±0.035
	700	0.774±0.049	0.773±0.070	0.777±0.056	0.908±0.026
	900	0.723±0.091	0.702±0.092	0.722±0.083	0.891±0.054
$\text{LORD}_{1\to3}$	0	0.600±0.140	0.513±0.215	0.561±0.188	0.820±0.068
	100	0.713±0.056	0.636±0.139	0.694±0.085	0.884±0.030
	300	0.733±0.069	0.725±0.053	0.730±0.063	0.868±0.036
	500	0.733±0.039	0.722±0.054	0.730±0.046	0.872±0.035
	700	0.744±0.031	0.730±0.043	0.741±0.034	0.872±0.021
	900	0.744±0.048	0.724±0.040	0.740±0.053	0.884±0.015
$\text{LORD}_{2\to3}$	0	0.477±0.059	0.338±0.105	0.420±0.078	0.764±0.051
	100	0.667±0.091	0.591±0.127	0.642±0.106	0.888±0.044
	300	0.790±0.042	0.754±0.060	0.783±0.050	0.927±0.017
	500	0.826±0.071	0.789±0.113	0.825±0.072	0.951±0.029
	700	0.846±0.101	0.816±0.126	0.847±0.103	0.928±0.046
	900	0.856±0.067	0.833±0.087	0.857±0.067	0.949±0.027

D SENSITIVITY EXPERIMENTS

Fig. 6 and Table 16 show that in general, the performance of `LORD` is improved as max_iter_{AE} gets larger in `EigenWorms` ($P = 128$). Our encoder-decoder structure can successfully integrate the lower-depth log-signature and the higher-depth log-signature information into the embedding vector **e**, and the well-integrated information helps the model perform better. In general, the lower-depth and the higher-depth log-signature information are blended better as the encoder-decoder structure are more trained.

(a) $\text{LORD}_{1\to2}$ (b) $\text{LORD}_{1\to3}$ (c) $\text{LORD}_{2\to3}$

Figure 6: Sensitivity to max_iter_{AE}

E TRAIN LOSS

Fig. 7 visualizes several training cases for our method and the original NRDE design. In general, our method shows much better stability across the entire training period.

Figure 7: Train loss of NRDE_3 and $\text{LORD}_{2\to3}$