FedEED: Efficient Federated Distillation with Ensemble of Aggregated Models

Abstract

Knowledge distillation has been applied to federated learning (FL) to tackle the data and device heterogeneity issues. In this paper, we study the key components of distillation-based model aggregation in FL. For that purpose, we first propose a generalized distillation framework which divides the federated distillation process into three key stages and includes existing methods as special cases. By investigating the contribution of each stage, we propose a novel distillation-based FL scheme, named Federated Efficient Ensemble Distillation (FedEED). Different from existing approaches, the ensemble teacher of FedEED is constructed by aggregated models, instead of the client models, to achieve improved scalability in large-scale systems. Due to the use of aggregated models, FedEED also achieves higher level of privacy protection, because the access to client models is no longer required. Furthermore, the knowledge distillation in FedEED only happens from the ensemble teacher to a designated model such that the diversity among different aggregated models is maintained. Experiment results showed that FedEED outperforms the state-of-the-art FL schemes, including FedAvg and FedDF, on the benchmark datasets. Besides the performance advantage, the designated distillation also allows for parallelism between server-side distillation and clients-side local training, which could speed up the training of large-scale learning systems.

1 Introduction

Federated learning (FL) (McMahan et al., 2017) allows users to jointly train a deep learning model without sharing their own data. Recent works (Lin et al., 2020; Zhang et al., 2022; Huang et al., 2022; Cho et al., 2022) adopted knowledge distillation (Hinton et al., 2015) for model aggregation to tackle device and data heterogeneity issues. These distillation-based aggregation methods have been shown to outperform weight averaging methods like FedAvg (McMahan et al., 2017). However, they also caused extra burden in computation due to the server-side training and additional implementation complexity due to the extra components and hyper-parameters, introduced by distillation. Furthermore, existing works (Lin et al., 2020; Zhang et al., 2022; Huang et al., 2022; Cho et al., 2022) utilized all client models to build the ensemble for knowledge distillation, leading to poor scalability in real world applications with a large number, e.g., thousands, of clients. As a result, the server may not be able to perform the required distillation efficiently. Lastly, existing methods built the ensemble teacher from a set of similar client models, where the low diversity among the compositing models will limit the performance of the ensemble and thus the global model.

To tackle the above issues, in this paper we will study the key components of distillation based FL and propose an efficient and scalable distillation method. For that purpose, we first introduce a generalized federated distillation framework, which consists of three major components, namely local trainers, the ensemble trainer and the global trainer. The local trainers perform local training on the clients-side, there each local trainer handles a sub-group of participating clients. After that, each local trainer collects and aggregates the updated client models, and constructs one global model. Existing FL algorithms like FedAvg (McMahan et al., 2017) can be used in-place as a local trainer. Then, the ensemble trainers combine the updated global models and local models into an ensemble, which has a higher capacity than the stand-alone global models. Finally, the global trainer will utilize the ensemble to further enhance the global models via knowledge distillation.

With the generalized framework, we investigate the contributions of each key component. In particular, we compare the performance of the distillation-based FL with different local, ensemble, and global trainers. Based on the results, we tackle the limitations of the existing methods in a bottom-up manner. In particular, we focus on improving several aspects of the distillation framework including: 1.) Improving scalability and privacy by building the ensemble from a set of aggregated models; 2.) Maximizing the capacity of the ensemble and global models by maintaining the diversity among models utilized to create the ensemble; 3.) Reducing the computation overhead by maximizing the parallelism between server-side and client-side training. By integrating the above ideas together, we propose a new learning algorithm named Federated Efficient Ensemble Distillation (FedEED), where we focus on the ensemble building and distillation steps, i.e. the ensemble trainer and global trainer in the generalized framework. FedEED is a highly scalable, distillation-based FL algorithm and unlike the existing methods, FedEED does not require direct access to the client models, which provides further protection to the user privacy. The proposed FedEED achieved state-of-the-art results in CIFAR10/100 (Krizhevsky et al., 2009) with the non-independent and identically distributed (Non-IID) data.

The contributions of this paper include:

1) We propose a generalized federated distillation framework, which can be viewed as a generalization of the existing distillation-based FL algorithms. With the proposed framework, the contribution of each key component can be easily investigated to build up different algorithms, which makes the implementation of FL easier.

2) By investigating the contribution of each component in the generalized framework, we propose FedEED, a highly efficient and scalable, distillation-based FL algorithm with improved privacy and model diversity. Experiment results demonstrated that FedEED can achieve the state-of-the-art performance with lower complexity and latency than existing federated distillation algorithms.

2 RELATED WORKS

Federated learning. Deep learning has obtained great success in the last decade. However, in practice, large amount of user data are not shared to the central server due to the privacy and communication constraints, which limits the use of deep learning in real world systems. To tackle the above issues, federated learning (McMahan et al., 2017) was proposed to perform on-device training on the clients side and aggregate the resulting models. The simplest approach is FedAvg (McMahan et al., 2017), which performs multiple local epochs of training on the client-side, and then aggregates the models updated by the clients with weight averaging. Other approaches, such as FedProx (Li et al., 2020), also utilize weight averaging to perform model aggregation, but with added regularization to tackle data heterogeneity issues. In this paper, we focus on distillation-based model aggregation in FL. However, for both the proposed generalized framework and FedEED, the global models are obtained by local trainers, for which available weight averaging methods such as FedAvg and FedProx can be directly utilized. This makes the proposed framework and FedEED compatible with different weight averaging methods.

Knowledge distillation. Knowledge distillation has been utilized in deep learning to compress deep neural networks. Student models, which typically have a smaller size, are forced to mimic the teacher models output. In recent works, knowledge distillation has been applied in FL. There are two types of approaches to apply knowledge distillation in FL. The first type utilizes distillation to perform model aggregation. For example, FedDF (Lin et al., 2020) and FedBE (Chen & Chao, 2021) utilized client models as a teacher to update the global model on the server, and the purpose is to improve the model aggregation performance with heterogeneous data. Some other works, including FedFTG(Zhang et al., 2022) and Fed-ET (Cho et al., 2022), utilized distillation for the same purpose, but in a different setting, i.e. in a data-free or model heterogeneous environment. The second type shares model predictions between clients and the server for training purses. For example, in FD (Jeong et al., 2018), model predictions are shared between clients to regularize the local training. In FedAD (Gong et al., 2021), models outputs on the client-side are used to train a global model on a server through distillation.

The proposed generalized framework and FedEED in this paper can be classified into the first type. In fact, the framework is a generalization of the works in the first type. However, the mechanisms

---

Algorithm 1 Generalized Federated Distillation Framework

---

function LOCALTRAINER($w_0^l, ..., w_{N-1}^l$)
    // Update local models $w_0^{l*}, ..., w_{N-1}^{l*}$
    // Update global model w^g
    return $w^g, w_0^{l*}, ..., w_{N-1}^{l*}$
end function
function ENSEMBLETRAINER($w_0^g, ..., w_{K-1}^g, w_{0,0}^l, ..., w_{K-1,N_{K-1}-1}^l$)
    // Update ensemble w^{e*}
    return w^{e*}
end function
function GLOBALTRAINER($w^{e*}, w_0^g, ..., w_{K-1}^g$)
    // Update global models $w_0^{g*}, ..., w_{K-1}^{g*}$
    return $w_0^{g*}, ..., w_{K-1}^{g*}$
end function
// Initialize K global models $w_{-1,0}^{g*}, ..., w_{-1,K-1}^{g*}$
for $t \in \{0, ..., T-1\}$ **do**
    // Split clients into sets $S_{t,0}, ..., S_{t,K-1}$ with sizes $N_{t,0}, ..., N_{t,K-1}$
    for $k \in \{0, ..., K-1\}$ **do in parallel**
        $w_{t,k,0}^l, ..., w_{t,k,N_{t,k}-1}^l \leftarrow w_{t-1,k}^{g*}$
        $w_{t,k}^g, w_{t,k,0}^{l*}, ..., w_{t,k,N_{t,k}-1}^{l*} \leftarrow LocalTrainer(w_{t,k,0}^l, ..., w_{t,k,N_k-1}^l)$
    end for
    $w_t^{e*} \leftarrow EnsembleTrainer(w_{t,0}^g, ..., w_{t,K-1}^g, w_{t,0,0}^{l*}, ..., w_{t,K-1,N_{K-1}-1}^{l*})$
    $w_{t,0}^{g*}, ..., w_{t,K-1}^{g*} \leftarrow GlobalTrainer(w_t^{e*}, w_{t,0}^g, ..., w_{t,K-1}^g)$
end for

FedEED utilizes to improve its scalability, privacy and performance are orthogonal to those of the existing works, and can be combined with existing methods to further improve the performance.

3 THE GENERALIZED FEDERATED DISTILLATION FRAMEWORK

To investigate the potential of utilizing distillation in FL, we propose the generalized federated distillation framework, which includes K local trainers, an ensemble trainer, and a global trainer. Note that the generalized framework keeps and updates K global models simultaneously, which includes the existing methods as a special case when $K = 1$. In every training round, each of the local trainers will distribute one of the global models to a subset of clients, perform local training, and aggregate the trained client models into a updated global model. Then, the ensemble trainer will aggregate the trained client models and the updated global models into an ensemble model. Finally, the global trainer will compress the knowledge of the ensemble and update the global models.

Many existing algorithms can be view as special cases of the proposed generalized framework. For example, by utilizing single FedAvg (McMahan et al., 2017) as the local trainer, combining all client models as the ensemble, and implementing the conventional knowledge distillation (Hinton et al., 2015), FedDF (Lin et al., 2020) can be realized. By applying multiple local trainers, each of which maintains a different global model, the heterogeneous learning setting (Huang et al., 2022) can be implemented.

By generalizing existing algorithms, the framework makes the design and implementation of FL systems easier, where different components can be changed depending on the actual problem. Furthermore, knowledge distillation (Hinton et al., 2015) is still an active topic in research, and the generalized framework allows easier integration of different distillation methods into FL. In this paper, we will investigate a diverse set of configurations and show that by carefully study the individual configuration, a better distillation algorithm can be built. For instance, we compared the performance between using client models, sampled models, and averaged models. We also compare different distillation algorithms. In the following, we introduce the components of the generalized framework, i.e. the local trainers, the ensemble trainer and the global trainer. The overall workflow of the framework is illustrated in Algo. 1.

3.1 LOCAL TRAINER

In each communication round, a set of available clients will be partitioned in to K groups, where each group of clients will be handled by one local trainer. For example, in the $t-$th round, the task of

the $k-$th local trainer is to update a global model, weighted by $w_{t-1,k}^{g*}$, by performing local training. In particular, the local trainer first distributes the weight of the global model, $w_{t-1,k}^{g*}$, to its clients to initialize the client model weights $w_{t,k,0}^l, ..., w_{t,k,N_{t,k}-1}^l$, where $N_{t,k}$ denotes the number of clients associated with the $k-$th local trainer at the t-th round. Then, the local trainer performs training on the client-side with the clients' private dataset, where the updated client model of the n-th client is denoted by $w_{t,k,n}^{l*}$. Lastly, the local trainer collects and aggregates model weights from its clients to the new global model weights $w_{t,k}^g$. Note that each of local trainer can be associated with a global model that has a different model architecture, which allows the framework to learn heterogeneous models. In this paper, we only consider the random partition scheme for mapping clients to the local trainers.

Many existing FL algorithms can be directly utilized as a local trainer, e.g. FedAvg (McMahan et al., 2017), and each of the local trainers can be a different learning algorithm. Moreover, learning algorithms with local regularization can be used in-place to tackle the Non-IID issue, e.g. FedProx (Li et al., 2020) and SCCAFOLD (Karimireddy et al., 2020). In this work, we consider three options for the local trainer, including FedAvg, FedProx and SCCAFOLD. We expect the local trainer to have relatively simple relation with the higher level trainers, such that faster local training can speed up the training of the ensemble and hence, the global model. We will evaluate the compatibility of these trainers with different higher level trainers.

3.2 ENSEMBLE TRAINER

After updating the global models by the local trainers, the ensemble trainer constructs the ensemble teacher model (Hinton et al., 2015) with weight w_t^{e*} by the the client models and global models obtained by the local trainers. In some cases, a fine-tuning can be applied on the server after building the ensemble, for example, if a labelled server dataset exists. Composed by multiple models, the ensemble typically has better performance than the individual models. It can serve as the teacher model for knowledge distillation in the later stage, and also be directly utilized for inference on the server or some high power devices.

There are multiple ways to build an ensemble. For example, FedDF (Lin et al., 2020) utilized all client models in a round to construct the ensemble; FedBE (Chen & Chao, 2021) sampled new models from the distribution built from client models, and utilized both the sampled models and client models to construct the ensemble for a higher capacity. Fed-ensemble (Shi et al., 2021) learned multiple global models and utilized them to build the ensemble for inference, but the ensemble is larger than the individual global models and may not be suitable to be deployed on the client devices.

3.3 GLOBAL TRAINER

At the last stage of each communication round, the ensemble obtained from the ensemble trainer is utilized as the teacher model for knowledge distillation to enhance the global models. We update the weights of the global models from $w_{t,0}^g, ..., w_{t,K-1}^g$ to $w_{t,0}^{g*}, ..., w_{t,K-1}^{g*}$, by mimicking the ensemble teacher's outputs with some sample inputs. For example, we can minimize the KL-divergence to enhance the global models for a classification task (Hinton et al., 2015). Existing works have shown that distillation can be utilized to perform model aggregation in FL. For instances, FedDF (Lin et al., 2020) utilized a basic knowledge distillation scheme in each round of training. On the other hand, FedBE (Chen & Chao, 2021) applied SWA (Izmailov et al., 2018) to prevent the global model from being over-fitted with the noisy teacher output.

4 EXPERIMENTS: THE GENERALIZED FRAMEWORK

In the experiment, we focus on building the ensemble trainer and the global trainer.

4.1 EXPERIMENTS: ENSEMBLE TRAINER

There are three critical issues in constructing the ensemble trainers, namely privacy, scalability, and model diversity. Existing distillation-based aggregation methods (Lin et al., 2020; Chen & Chao, 2021) require all client models to build the ensemble, causing privacy concerns. Furthermore, their

(a) $\alpha = 1.0$ (b) $\alpha = 0.1$

Figure 1: Comparison between different ensemble strategies with CIFAR-10. Note that we applied smoothing to the curves to improve the visibility.

scalability is limited, because the cost of inference with the ensemble is proportional to the number of compositing models and the server may not be able to efficiently perform the training if the number client models is too large. Lastly, in FedDF (Lin et al., 2020) and FedBE (Chen & Chao, 2021), the diversity between the models in the ensemble is determined by the local training in a single round, and may be limited, which reduces the capacity of the ensemble.

To this end, we noticed the idea of Fed-ensemble (Shi et al., 2021), which builds the ensemble from multiple global models for inference purposes. This solves the privacy and scalability issues. More-over, the diversity of the models constructing the ensemble is maintained across the whole training, because different global models experience different training sequences. We may borrow the idea to building the ensemble from global models for distillation purposes, which allows for different en-semble complexity, determined by the hyper-parameter K. However, increasing K will also reduce the number of clients per global model, and thus slows down the convergence. A simple solution is to utilize multiple checkpoints of the global models to build the ensemble, which increases the capacity of the ensemble without slowing down the training of the individual global models.

In this paper, we consider five ways to build the ensemble:

1) Vanilla Ensemble. Similar to FedDF (Lin et al., 2020), we utilize all client models to build the ensemble and only train one global model (i.e. $K = 1$). For an input x, we denote the ensemble function by F and compute the output y by $y = F(x|w_{t,0,0}^{l*}, ..., w_{t,0,N_0-1}^{l*})$.

2) Bayesian Ensemble. Following FedBE (Chen & Chao, 2021), we train a global model and build ensembles by combining the client models, the averaged model, and S sampled models from the Gaussian distribution or the Dirichlet distribution with $y = F(x|w_{t,0,0}^{l*}, ..., w_{t,0,N_0-1}^{l*}, w_{t,0}^{g}, w_{t,0}^{s}, ..., w_{t,S-1}^{s})$.

3) Ensemble from multiple global models. Like Fed-ensemble (Shi et al., 2021), we train K global models, each with different initialization seeds and local training sequences, and combine them into an ensemble with $y = F(x|w_{t,0}^{g}, ..., w_{t,K-1}^{g})$.

4) Ensemble from client models, which are initialized from different global models (Lin et al., 2020; Shi et al., 2021). This scheme is similar to 3), except that we utilize the client models to build the ensemble with $y = F(x|w_{t,0}^{l*}, ..., w_{t,K-1,N_{K-1}-1}^{l*})$.

5) Ensemble from multiple aggregated global models in multiple rounds. In addition to scheme 3), we use the global models from the last R checkpoints to build the ensemble with $y = F(x|w_{t,0}^{g}, ..., w_{t,K-1}^{g}, ..., w_{t-R+1,0}^{g}, ..., w_{t-R+1,K-1}^{g})$.

We perform performance comparison between the above ensemble strategies on CIFAR10 dataset with Non-IID settings. We performed two runs, where we trained one ($K = 1$) and four ($K = 4$) global models with the generalized framework, respectively. We used FedAvg (McMahan et al., 2017) as the local trainer and skipped the global trainer, i.e. we did not perform distillation. For the run with $K = 1$, we built 1) vanilla ensembles, including a variant which is weighted by the number

Table 1: CIFAR10 results of the generalized framework with different ensemble trainers.

Model	Method	CIFAR10	
		$\alpha = 1.0$	$\alpha = 0.1$
ResNet20	Global model ($K = 1$)	88.53 ± 0.31	78.72 ± 2.31
	Global model ($K = 4$)	86.69 ± 0.54	70.74 ± 5.11
	Ensemble ($K = 1$, Clients)	88.82 ± 0.21	80.22 ± 0.88
	Ensemble ($K = 1$, Clients, Weighted)	88.79 ± 0.16	80.11 ± 0.95
	Ensemble ($K = 1$, Bayesian, Gaussian)	88.72 ± 0.14	79.60 ± 1.26
	Ensemble ($K = 1$, Bayesian, Dirichlet)	88.70 ± 0.11	80.25 ± 1.43
	Ensemble ($K = 4$, Aggregated)	90.58 ± 0.31	81.76 ± 2.40
	Ensemble ($K = 4$, Clients)	90.49 ± 0.17	82.12 ± 1.65
	Ensemble ($K = 4$, $R = 2$, Aggregated)	$\underline{90.75 \pm 0.24}$	83.50 ± 1.56
	Ensemble ($K = 4$, $R = 4$, Aggregated)	90.69 ± 0.19	$\underline{83.99 \pm 0.88}$

of training samples held by the client, and 2) Bayesian ensembles (both Gaussian and Dirichlet). We also performed similar evaluation for the runs with $K = 4$, where we built the 3) ensembles from global models, 4) ensembles form client models and 5) ensembles from multiple checkpoints of the global models (with $R = 2$ or $R = 4$). For the details of the experiment setting, see Sec. 6.

The results are shown in Fig. 1 and Table 1. With low degree of Non-IID ($\alpha = 1.0$), despite slowing down the convergence of the individual global models, increasing the number of global models provides the best results. All ensembles with $K = 4$ perform closely, where the ensembles built by global models from last four checkpoints provide slightly higher accuracy. With $K = 1$, all methods do not show clear performance advantage over the global model, with agrees with our understanding about the diversity among the compositing models.

With highly Non-IID data, all ensemble strategies showed significant improvement over the global model with $K = 1$. However, even with only global models of a single round, the ensemble with $K = 4$ performed similarly as the strategies with $K = 1$, which requires access to the client models. By increasing R from 1 to 2 or 4, we observed substantial performance improvements by the ensemble with $K = 4$, outperforming all methods with $K = 1$ by a large margin. Moreover, with $K = 4$ and $R = 1$, the ensembles built from global models and client models perform closely. By increasing R, the ensembles based on global models outperformed their counterparts based on client models. It indicates that accessing client models is not necessary to build a high performance ensemble.

In the experiment, ensembles built by following option 5) achieved the best performance, with better privacy protection and higher scalability. Thus, we consider option 5) the candidate ensemble trainer.

4.2 EXPERIMENTS: GLOBAL TRAINER

In Sec. 4.1, it was shown that the best performance can be achieved by learning multiple global models and using multiple check-points of these models. However, if we are interested in a single and compact model for inference, we need to compress the ensemble into a global model. In the cases with multiple global models in the generalized framework, there is no clear rule for applying distillation, and we consider multiple distillation schemes here.

Firstly, we consider a basic knowledge distillation scheme, i.e. we utilize the ensemble as the teacher and all global models are trained by mimicking the output of the ensemble. Note that we fix the weight of the ensemble during the distillation process. This is similar to the heterogeneous version of FedDF (Lin et al., 2020), where all global models will be improved by knowledge distillation.

One possible drawback of the basic scheme is that it may reduce the diversity among the global models and thus hurts the performance of the ensemble, since the global models are forced to produce similar outputs. Thus, we consider another scheme following Codistillation (Anil et al., 2018), where we skip the distillation in the early rounds of training, such that the models will not learn from each other at the beginning to maintain potentially higher diversity.

Lastly, we consider an asymmetric scheme, where only one designated global model will serve as the student and be enhanced by the global trainer. Although there is only one global model being enhanced by distillation in each round of training, the scheme can fit most of the scenarios where only one global model is required for inference, and reduce the cost of distillation. We note that prior

Table 2: CIFAR10/100 results of the generalized framework with different global trainers.

| Model | Method | CIFAR10 | |
		$\alpha = 1.0$	$\alpha = 0.1$
ResNet20	w/o distillation	86.69 ± 0.54	70.74 ± 5.11
	Basic distillation	88.63 ± 0.34	79.98 ± 2.42
	Basic distillation w/ warm-up (20 rounds)	88.66 ± 0.22	$\underline{80.20 \pm 1.81}$
	Basic distillation w/ warm-up (40 rounds)	88.47 ± 0.04	79.27 ± 2.14
	Designated distillation	$\underline{89.06 \pm 0.19}$	80.18 ± 2.38
ResNet20 (Ensemble)	w/o distillation	$\underline{90.58 \pm 0.31}$	$\underline{81.76 \pm 2.40}$
	Basic distillation	89.23 ± 0.36	80.57 ± 2.24
	Basic distillation w/ warm-up (20 rounds)	89.38 ± 0.42	80.80 ± 1.95
	Basic distillation w/ warm-up (40 rounds)	89.19 ± 0.24	80.32 ± 2.55
	Designated distillation	90.31 ± 0.20	81.39 ± 2.54

Table 3: Comparison between methods. The ratios are relative to FedAvg.

Method	Communication cost	Ensemble size	No access to client models	Parallelism for server training
FedAvg	1.0x	-	✓	-
FedProx	1.5x	-	✓	-
SCAFFOLD	1.5x	-	✓	-
FedDF	1.0x	C	✗	✗
FedBE	1.0x	$C + S + 1$	✗	✗
FedEED (w/ FedAvg)	1.0x	KR	✓	✓

K: Number of global models R: Number of rounds of time ensemble C: Number of active clients S: Number of sampled models

work in knowledge distillation (Chen et al., 2020) has applied a similar scheme where a model is chosen to be the main student during distillation, where attention (Vaswani et al., 2017) was utilized to maintain the difference between models. The all-to-one scheme here is simpler and able to reduce the computation complexity.

In the experiments, we compared performance of different distillation settings discussed above, including: 1) Simple distillation, where we treat all global model as the student model; 2) Simple distillation with warm-up rounds, which skips the distillation in the early rounds of training; 3) Designated distillation, where we only transfer the knowledge from the ensemble to one designated global model, which keeps the diversity between the global models, reduces the computation complexity, and allows for parallelism between server-side and client-side computation. We use 20 and 40 warm-up rounds for 2).

Results in Table 2 show that, the global model trained by the designated scheme outperformed its counterparts with low degree of Non-IID, and performed similarly to the others with high degree of Non-IID. On the other hand, the ensembles trained by the designated scheme obtained the best results in all the cases, which is close to the ensemble without distillation. The performance of other ensembles by distillation is much worse than that without distillation. These results support our expectation that asymmetric scheme can help keep the models diversity, and thus improve the performance of both the ensemble and the distilled global model.

5 FEDEED

In the Sec 4, we showed that two simple schemes: 1) building ensemble from the aggregated global models; 2) designated distillation from the ensemble to the one global model, lead to a competitive instance of the generalized framework, with improved privacy and scalability. We refer the above instance as Federated Efficient Ensemble Distillation (FedEED). FedEED tackled two limitations of the existing distillation-based aggregation methods by utilizing multiple aggregated global models to build the ensemble. Firstly, FedEED does not require direct access to the client models or the model outputs, which is compatible to the mechanism that ensures the users privacy, including secure aggregation (Bonawitz et al., 2017). Secondly, the number of global models is a hyper-parameter, which makes FedEED applicable to large scale FL system with potentially thousands of clients.

Another key advantage of FedEED is the designated distillation scheme. In FedEED, the knowledge of the ensemble will only be transferred to one picked global model with weights $w_{t,0}^{g*}$, such that the

Table 4: CIFAR10/100 results.

Model	Method	CIFAR10		CIFAR100	
		$\alpha = 1.0$	$\alpha = 0.1$	$\alpha = 1.0$	$\alpha = 0.1$
ResNet20	FedAvg	88.53 ± 0.31	78.72 ± 2.31	58.84 ± 0.42	52.98 ± 1.41
	FedProx	88.36 ± 0.18	79.44 ± 2.17	58.76 ± 0.93	53.57 ± 0.37
	SCAFFOLD	89.85 ± 0.50	80.08 ± 1.53	61.09 ± 0.46	54.74 ± 1.26
	FedDF	87.98 ± 0.16	80.04 ± 1.87	59.74 ± 0.38	51.83 ± 0.83
	FedEED	89.06 ± 0.19	80.18 ± 2.38	61.90 ± 0.83	$54.60 \pm 1.20*$
	FedEED ($R = 2$)	89.01 ± 0.18	81.27 ± 2.16	62.42 ± 0.57	56.39 ± 1.10
	FedEED ($R = 4$)	89.01 ± 0.07	82.21 ± 1.10	62.84 ± 0.45	56.90 ± 0.77
ResNet56	FedAvg	89.25 ± 0.11	80.05 ± 2.65	59.47 ± 1.23	54.37 ± 1.24
	FedProx	89.65 ± 0.23	80.84 ± 1.32	61.01 ± 1.02	57.18 ± 0.92
	SCAFFOLD	90.73 ± 0.27	82.22 ± 0.92	62.94 ± 0.91	56.36 ± 0.31
	FedDF	88.87 ± 0.29	81.10 ± 2.31	60.71 ± 0.68	52.52 ± 1.37
	FedEED	89.86 ± 0.14	81.30 ± 2.17	62.95 ± 2.43	57.48 ± 2.03
	FedEED ($R = 2$)	90.23 ± 0.23	82.77 ± 1.67	65.28 ± 0.64	59.37 ± 0.64
	FedEED ($R = 4$)	90.00 ± 0.26	83.20 ± 0.99	65.63 ± 0.89	59.56 ± 0.43
WRN16-2	FedAvg	90.26 ± 0.33	81.52 ± 2.66	63.57 ± 1.06	58.77 ± 0.55
	FedProx	90.38 ± 0.29	81.78 ± 2.58	63.75 ± 0.84	59.24 ± 1.00
	SCAFFOLD	91.32 ± 0.11	82.90 ± 2.19	65.33 ± 0.48	60.66 ± 0.85
	FedDF	89.52 ± 0.10	81.32 ± 2.91	63.54 ± 0.53	56.89 ± 1.28
	FedEED	90.69 ± 0.41	82.62 ± 2.46	66.46 ± 0.30	61.16 ± 1.20
	FedEED ($R = 2$)	90.77 ± 0.16	83.39 ± 2.17	67.11 ± 0.41	62.37 ± 0.84
	FedEED ($R = 4$)	90.70 ± 0.31	84.02 ± 1.75	67.48 ± 0.22	63.05 ± 0.80

*: result with only one or two runs. To be updated in the camera-ready version.

diversity between $w_{t,0}^{g*}, ..., w_{t,K-1}^{g*}$ won't be lost after multiple rounds of training. During inference, either the main global model or the ensemble model can be utilized, depending on the device capacity. Besides maintaining the diversity between the models in the ensemble, the designated scheme also allows for parallelism between client-side and server-side computation. In particular, during the computation of $w_{t,0}^{g*}$, other weights $w_{t,1}^{g*}, ..., w_{t,K-1}^{g*}$ are ready to be distributed to the clients for the $t + 1$-th round training, because they will not be enhanced by distillation. This can improve the system throughput by a large factor, especially if the server side training time is not negligible and the clients are not always available.

In summary, the key idea of FedEED is to ensure privacy and scalability, and maintain the diversity between models throughout the whole training process. See Table. 3 for the comparison between FedEED and other methods (McMahan et al., 2017; Li et al., 2020; Karimireddy et al., 2020; Lin et al., 2020; Chen & Chao, 2021).

Remark 1: To perform distillation, a server dataset or generator is mandatory. In this paper, we consider the use of FedEED with unlabelled server dataset, following Lin et al. (2020); Chen & Chao (2021). Since the dataset is not labelled and does not have any assumption with the client datasets, it can be cheap to collect. Note that extending FedEED to labelled dataset or generator is straightforward. We can also extend FedEED to the model heterogeneous setting (Lin et al., 2020; Cho et al., 2022), in which we can pick one global model from each model type as the student models. As long as the ratio of the picked global models is only a small portion of all models, the diversity among them can be preserved.

6 EXPERIMENTS: FEDEED

Image Classification with CIFAR10/100. Our experiments of image classification task followed Lin et al. (2020). We trained the models on CIFAR10/100 dataset (Krizhevsky et al., 2009), and utilized CIFAR100 and ImageNet (resized to 32×32) (Deng et al., 2009) as the unlabelled datasets for the CIFAR10/100 experiments, respectively. There are 100 rounds of training with 20 clients, where 40% of them are active in each round. We sampled data for each of the clients with the Dirichlet distribution (Hsu et al., 2019), with $\alpha = \{1.0, 0.01\}$ for different levels of data heterogeneity. For each setting, we reported the average of three runs with different seeds, where the seeds are shared across different methods to generate the same data partition and sequence of client's for a fair comparison. We trained ResNet20/56 (He et al., 2016) and WRN16-2 (Zagoruyko & Komodakis, 2016), which are proven capable to achieve high accuracy on CIFAR10/100. For the optimizer, we used SGD with

Table 5: CIFAR10 results of FedEED with different local trainers.

Model	Method	CIFAR10 (8 clients per round)		CIFAR10 (20 clients per round)	
		$\alpha = 1.0$	$\alpha = 0.1$	$\alpha = 1.0$	$\alpha = 0.1$
ResNet20	FedAvg	88.53 ± 0.31	78.72 ± 2.31	88.59 ± 0.28	79.84 ± 1.50
	FedProx	88.36 ± 0.18	79.44 ± 2.17	88.52 ± 0.07	79.63 ± 2.48
	SCAFFOLD	$\underline{89.85 \pm 0.50}$	80.08 ± 1.53	90.10 ± 0.07	82.83 ± 2.40
	FedEED w/ FedAvg	89.06 ± 0.19	80.18 ± 2.38	89.04 ± 0.11	82.89 ± 1.30
	FedEED w/ FedProx	88.98 ± 0.22	$\underline{81.21 \pm 1.30}$	$89.18 \pm 0.08^*$	$81.71 \pm 2.59^*$
	FedEED w/ SCAFFOLD	88.80 ± 0.16	76.51 ± 3.74	$\underline{90.66 \pm 0.04}$	$85.91 \pm 0.00^*$

*: result with only one or two runs. To be updated in the camera-ready version.

learning rate of 0.8 and 0.1, batch size of 64 and 256 for the client-side and the server-side training, respectively. We did not apply weight decay or learning rate scheduling in our experiments.

We compared FedEED with FedAvg (McMahan et al., 2017), FedProx(Li et al., 2020), SCAF-FOLD(Karimireddy et al., 2020) and FedDF(Lin et al., 2020). We set the number of local training epoch to be 40, and the regularizer parameter μ of FedProx to be 0.001. For FedEED, we set the number of global model K to be 4 and used one round of models to build the ensemble, i.e., $R = 1$, unless otherwise specified. For both FedDF and FedEED, we performed distillation with 5000 steps in each training round, with the temperature τ to be 4.

The results are shown in Table 4. It can be observed that FedEED outperformed all other methods on the harder dataset, CIFAR100, and all settings with high degree of Non-IID. It suggests that FedEED is a good candidate for tackling the Non-IID issue. We also found that the value of R does not affect the performance of FedEED significantly in the CIFAR10 experiments with low degree of Non-IID, but a higher value of R improved the performance of FedEED significantly in the CIFAR10 runs with high degree of Non-IID, and on CIFAR100 datasets with both high and low degree of Non-IID.

6.1 COMPATIBILITY OF FEDEED WITH DIFFERENT LOCAL TRAINERS

To evaluate the compatibility of FedEED with different local trainers, we performed experiments by combining FedEED with FedAvg (McMahan et al., 2017) (default option in this paper), FedProx (Li et al., 2020) and SCAFFOLD (Karimireddy et al., 2020). The results in Table 5 show that FedEED is compatible with FedProx and the combination achieves better performance with high degree of Non-IID. However, the combination of FedEED and SCAFFOlD did not improve the performance. We expect this is due to the fact that the number of clients per global model is too small in FedEED, e.g., 2. We thus performed additional experiments by increasing the ratio of active clients from 0.4 to 1.0, which increases the clients per global model to 5. In these experiments, the combination of FedEED and SCCAFOLD achieved much higher accuracy than the stand-alone FedEED and SCCAFFOLD.

6.2 ABLATION STUDY

Ablation study will be provided in the appendix.

7 CONCLUSION

In this paper, we studied the key components of distillation-based model aggregation in federated learning. By generalizing the existing methods to a universal framework, we investigated the contribution of different components. It was shown that constructing the ensemble teacher by aggregated models improves the privacy and scalability of the distillation-based federated learning system and designated distillation, which transfers the knowledge of the ensemble to one global model, helps maintain the diversity among different models used to build the ensemble. Based on these observations, we propose a novel, efficient ensemble distillation method called FedEED, whose performance advantage over existing methods was validated by extensive experiments over the benchmark datasets. The proposed FedEED scheme provides an efficient and scalable way for model aggregation in large-scale learning systems, with improved privacy protection.

REFERENCES

Rohan Anil, Gabriel Pereyra, Alexandre Passos, Robert Ormandi, George E Dahl, and Geoffrey E Hinton. Large scale distributed neural network training through online distillation. *arXiv preprint arXiv:1804.03235*, 2018.

Keith Bonawitz, Vladimir Ivanov, Ben Kreuter, Antonio Marcedone, H Brendan McMahan, Sarvar Patel, Daniel Ramage, Aaron Segal, and Karn Seth. Practical secure aggregation for privacy-preserving machine learning. In *proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*, pp. 1175–1191, 2017.

Defang Chen, Jian-Ping Mei, Can Wang, Yan Feng, and Chun Chen. Online knowledge distillation with diverse peers. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 3430–3437, 2020.

Hong-You Chen and Wei-Lun Chao. Fedbe: Making bayesian model ensemble applicable to federated learning. In *ICLR*, 2021.

Yae Jee Cho, Andre Manoel, Gauri Joshi, Robert Sim, and Dimitrios Dimitriadis. Heterogeneous ensemble knowledge transfer for training large models in federated learning. *arXiv preprint arXiv:2204.12703*, 2022.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Xuan Gong, Abhishek Sharma, Srikrishna Karanam, Ziyan Wu, Terrence Chen, David Doermann, and Arun Innanje. Ensemble attention distillation for privacy-preserving federated learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 15076–15086, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Geoffrey Hinton, Oriol Vinyals, and Jeffrey Dean. Distilling the knowledge in a neural network. In *NIPS Deep Learning and Representation Learning Workshop*, 2015. URL `http://arxiv.org/abs/1503.02531`.

Tzu-Ming Harry Hsu, Hang Qi, and Matthew Brown. Measuring the effects of non-identical data distribution for federated visual classification. *arXiv preprint arXiv:1909.06335*, 2019.

Wenke Huang, Mang Ye, and Bo Du. Learn from others and be yourself in heterogeneous federated learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10143–10153, 2022.

Pavel Izmailov, Dmitrii Podoprikhin, Timur Garipov, Dmitry Vetrov, and Andrew Gordon Wilson. Averaging weights leads to wider optima and better generalization. *arXiv preprint arXiv:1803.05407*, 2018.

Eunjeong Jeong, Seungeun Oh, Hyesung Kim, Jihong Park, Mehdi Bennis, and Seong-Lyun Kim. Communication-efficient on-device machine learning: Federated distillation and augmentation under non-iid private data. *arXiv preprint arXiv:1811.11479*, 2018.

Sai Praneeth Karimireddy, Satyen Kale, Mehryar Mohri, Sashank Reddi, Sebastian Stich, and Ananda Theertha Suresh. Scaffold: Stochastic controlled averaging for federated learning. In *International Conference on Machine Learning*, pp. 5132–5143. PMLR, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. Federated optimization in heterogeneous networks. *Proceedings of Machine Learning and Systems*, 2:429–450, 2020.

Tao Lin, Lingjing Kong, Sebastian U Stich, and Martin Jaggi. Ensemble distillation for robust model fusion in federated learning. *Advances in Neural Information Processing Systems*, 33:2351–2363, 2020.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pp. 1273–1282. PMLR, 2017.

Naichen Shi, Fan Lai, Raed Al Kontar, and Mosharaf Chowdhury. Fed-ensemble: Improving generalization through model ensembling in federated learning. *arXiv preprint arXiv:2107.10663*, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Lin Zhang, Li Shen, Liang Ding, Dacheng Tao, and Ling-Yu Duan. Fine-tuning global model via data-free knowledge distillation for non-iid federated learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10174–10183, 2022.

A APPENDIX

A.1 FEDEED WITH DIFFERENT COMMUNICATION INTERVALS

Table 6: CIFAR10 results with different communication intervals

# rounds / # local epochs	Model	Method	CIFAR10 $\alpha = 1.0$	$\alpha = 0.1$
25 / 160	ResNet20	FedAvg	85.81 ± 0.12	73.17 ± 3.66
		FedDF	86.78 ± 0.12	77.79 ± 1.73
		FedEED	86.27 ± 0.68	73.99 ± 2.15
100 / 40	ResNet20	FedAvg	88.53 ± 0.31	78.72 ± 2.37
		FedDF	87.98 ± 0.16	80.04 ± 1.87
		FedEED	89.06 ± 0.19	80.18 ± 2.38
400 / 10	ResNet20	FedAvg	89.69 ± 0.27	79.19 ± 0.42
		FedDF	88.90 ± 0.19	78.92 ± 0.59
		FedEED	90.37 ± 0.08	81.34 ± 0.81

We compared the performance of FedEED with FedAvg (McMahan et al., 2017) and FedDF (Lin et al., 2020), with difference communication intervals. We fixed the total amount of computation, where we set the number of rounds and the number of local epochs to be 25/100/400 and 160/40/10, respectively. We also scaled the number of distillation steps to 20000/5000/1250. From Table 6, we can observe that FedEED always performed better than FedAvg. But with 25 communication rounds, FedDF outperformed FedEED. We expect this is due to the extremely small number of clients per global models in FedEED, i.e. there are only two clients per global models, which slowed down the convergence in the case with extreme high communication intervals.

A.2 FEDEED WITH DIFFERENT NUMBER OF GLOBAL MODELS

Table 7: CIFAR10 results of FedEED with different number of global models.

Model	Method	K	CIFAR10 $\alpha = 1.0$	$\alpha = 0.1$
ResNet20	FedEED	2	88.34 ± 0.32	79.38 ± 2.54
		3	88.89 ± 0.22	79.63 ± 6.15
		4	89.06 ± 0.19	80.18 ± 2.38

Table 8: CIFAR10 results of FedEED with different scaling schemes.

# Clients	Model	Method	K	CIFAR10 $\alpha = 1.0$	$\alpha = 0.1$
8	ResNet20	FedAvg	—	88.53 ± 0.31	78.72 ± 2.37
		FedDF	—	87.98 ± 0.16	80.04 ± 1.87
		FedEED	4	89.06 ± 0.19	80.18 ± 2.38
14	ResNet20	FedAvg	—	88.67 ± 0.22	80.25 ± 1.64
		FedDF	—	88.38 ± 0.16	81.61 ± 1.94
		FedEED	4	89.14 ± 0.09	81.26 ± 1.99
			7	89.31 ± 0.06	81.90 ± 1.80
20	ResNet20	FedAvg	—	88.59 ± 0.28	79.84 ± 1.50
		FedDF	—	88.12 ± 0.25	81.55 ± 2.02
		FedEED	4	89.04 ± 0.11	82.89 ± 1.30
			10	89.14 ± 0.11	81.97 ± 1.54

In the main paper, we used $K = 4$ as our default options of FedEED. Here, we provide results with $K = 2$ to $K = 4$. Note that there are only 8 clients per round in the default configuration, and with $K = 4$ there are only two clients per global model. For $K = 3$, we allocated one more client to the main global model in FedEED. The results in Table 7 show that $K = 4$ is the best configuration of FedEED in the experiment. However, as we mentioned above, there is a trade-off between the speed of convergence and the performance of the ensemble teacher, so the optimal value of K may vary with the different tasks.

In Table 8, we further provided the results to show how the performance of FedEED scales with the number of clients, and compared it with FedAvg (McMahan et al., 2017) and FedDF (Lin et al., 2020). As the number of clients increases, we consider two options: 1.) scaling the number of clients per global model, i.e. fixing the value of K, 2.) scaling the number of global models, i.e. varying the value of K ($K = 7$ and 10 in Table 8). We found that FedEED outperformed FedAvg and FedDF with both scaling schemes, and obtained the best result when scaling with the number of global models, except the case with high Non-IID with 20 clients. However, in practice, the scaling scheme may be subject to the server capacity, as increasing the number will also increase the cost of distillation.

A.3 IMPROVEMENT FROM FEDDF

Table 9: The difference between FedDF and FedEED. The method in the last row is identical to the FedEED with $R = 1$.

| | | CIFAR10 | |
Model	Method	$\alpha = 1.0$	$\alpha = 0.1$
ResNet20	FedDF	82.53 ± 0.24	68.72 ± 4.23
	+ improved configuration	87.93 ± 0.47	79.01 ± 2.15
	+ removal of drop-worst & early-stopping	87.42 ± 0.19	78.55 ± 3.00
	+ aggregated ensemble & $K = 4$	88.35 ± 0.18	79.59 ± 2.93

FedEED is similar to FedDF (Lin et al., 2020), because both of them utilize knowledge distillation for model fusion with an unlabelled dataset. In this section, we progressively modify FedDF into FedEED, and show the effect of each of the individual changes. Note that we keep 10% of the training data from CIFAR10 as the validation set of the server in this experiment, following Lin et al. (2020).

The original FedDF utilized Adam optimizer (Kingma & Ba, 2014) for server training, and applied the 'drop-worst' mechanism and the early-stopping. We perform the following modification: 1) adapt the configuration from the main paper (including the use of SGD optimizer), 2) remove the use of 'drop-worst' and early-stopping, and 3) utilize four aggregated global models to build the ensemble with the designated distillation scheme. By introducing these three modifications, FedDF achieved the same perforamnce as FedEED with $R = 1$.

Table 9 shows the results of different modifications and we have three observations. First, the configuration we used in this paper improved FedDF a lot. Second, the removal of the 'drop-worst' and the early-stopping led to a worse result, but it saved the need of a server validation set. Third, the main mechanisms we used in FedEED, i.e. the ensemble from aggregated model and the designated distillation scheme, provided significant performance improvement.