A FRAMEWORK OF DEEP NEURAL NETWORKS VIA THE SOLUTION OPERATOR OF PARTIAL DIFFERENTIAL EQUATIONS

ABSTRACT

There is a close connection between deep neural networks (DNN) and partial differential equations (PDEs). Many DNN architectures can be modeled by PDEs and have been proposed in the literature. However, their neural network design space is restricted due to the specific form of PDEs, which prevents the design of more effective neural network structures. In this paper, we attempt to derive a general form of PDEs for the design of ResNet-like DNN. To achieve this goal, we first formulate DNN as an adjustment operator applied on the base classifier. Then based on several reasonable assumption, we show the adjustment operator for ResNet-like DNN is the solution operator of PDEs. To show the effectiveness for general form of PDEs, we show that several effective networks can be interpreted by our general form of PDEs and design a training method motivated by PDEs theory to train DNN models for better robustness and less chance of overfitting. Theoretically, we prove that the robustness of DNN trained with our method is certifiable and our training method reduces the generalization gap for DNN. Furthermore, we demonstrate that DNN trained with our method can achieve better generalization and is more resistant to adversarial perturbations than baseline model.

1   INTRODUCTION

Deep neural networks (DNN) have achieved success in tasks such as image classification (Simonyan & Zisserman, 2015), speech recognition (Dahl et al., 2012), video analysis (Bo et al., 2011), and action recognition (Wang et al., 2016). Residual learning (He et al., 2016a;b) has revolutionized DNN architecture design, making it practical to train ultra-deep DNN, and it is also introduced to avoid gradient vanishing. The idea of residual learning has motivated the development of powerful DNN such as WideResNet (Zagoruyko & Komodakis, 2016), ResNeXt (Xie et al., 2017), and DenseNet (Huang et al., 2017).

Compared to other shallow models, such as softmax classifier $\mathrm{softmax}(\boldsymbol{w}\boldsymbol{x})$ (a linear transformation parameterized by $\boldsymbol{w}$ and followed by a softmax function), DNN have the technical issues (which may be the reasons for their excellent performance) of function composition and complicated parameterization. First, it is well known that the architecture of a DNN model includes a hidden layer and output layer. The hidden layer can be formulated as $\rho_L \circ \cdots \circ \rho_1$, where ρ_l is the i-th intermediate map $(l = 0, \cdots, L)$. Intermediate maps of standard DNN can usually be expressed as $\rho_l = \boldsymbol{w}^{l1}\rho(\boldsymbol{w}^{l2}\boldsymbol{x})$, where ρ is activation function and $\boldsymbol{w}^{l1}, \boldsymbol{w}^{l2}$ are the parameters of layer l. The output layer is usually a linear transformation followed by a softmax function. Hence, the output of DNN can be expressed as $\mathrm{softmax}(\boldsymbol{w}[\rho_L \circ \cdots \circ \rho_1(\boldsymbol{x})])$. In this setting, DNNs can be viewed as an evolution from a softmax model. Without loss of generality, we indicate this evolutive relationship by an adjustment operator,

$$T_L : \mathrm{softmax}(\boldsymbol{w}\boldsymbol{x}) \rightarrow \mathrm{softmax}(\boldsymbol{w}[\rho_L \circ \cdots \circ \rho_1(\boldsymbol{x})]).$$

If we denote the softmax model by f, then the DNN model can be expressed as $T_L(f)$, and we can interpret its performance by the adjustment operator T_L, which can guide the design of new DNN architectures.

ResNet-like DNN architectures as one of the most important DNN architectures have been widely studied. So, a natural question is "for ResNet-like DNN, what will the adjustment operator be?". Observe that each residual block of ResNet can be written as one step of forward Euler discretization of an ordinary differential equation (ODE) (Weinan, 2017). It has been shown (Lu et al., 2018) that PolyNet (Zhang et al., 2017) and FractalNet (Larsson et al., 2016) can also be respectively considered numerical schemes to solve an ODE system. This suggests the hidden layer of ResNet-like DNN can be viewed as a solution of ODE. These hidden layer of DNN were regarded as ODE systems that are the characteristic lines of a transport equation (TE) on the distribution of a dataset (Sonoda & Murata, 2018). If we consider the whole architecture of ResNet-like DNN including hidden layer and output layer, the testing process of these networks is a process of numerically solving partial differential equations (PDEs). For details of the relationship, reader can refer subsection 2.2. As a result, the adjustment operator mentioned in paragraph 2 for ResNet-like DNN can be expressed as a solution operator of PDEs.

Many design process of new DNN architectures can be modeled by the solution operator of PDEs, these methods bridge the capacity of DNN and the property of the PDEs to which they correspond and strengthen the theoretical understanding of deep learning. However, these methods are not systematic, their DNN design space is restricted due to the specific form of PDEs, which prevents the use of more effective DNN structures. And whether there is a general form of PDEs to guide the design of effective DNN is still questionable.

1.1 OUR CONTRIBUTION

In this paper, given a base classifier f, we can formulate a DNN as a continuous dynamic system, $T_t(f)$. To obtain the general form of the PDEs corresponding to these DNN, we list a series of formal properties likely to be satisfied by the operator T_t, and we deduce an explicit formulation from them. We see that under reasonable assumptions, the new DNN models $u(\boldsymbol{x}, t) = (T_t f)(\boldsymbol{x})$ are solutions of convection diffusion equations. Then, motivated by the theory of PDEs, we design a training method for DNN models under this framework for better robustness and less overfitting risk. Our training method is to choose a DNN model with natural training $f(\boldsymbol{x})$ as the base classifier, and approximate $T_t(f)(\boldsymbol{x})$ by another DNN model, $g(\boldsymbol{x}, T)$, which is our final classifier.

We make the following contributions:

- Under reasonable assumptions, we build a PDEs framework for ResNet-like DNN and show some effective models can be modeled by our framework.

- We design a training method for DNN based on the theory of PDEs. This is an important contribution of this paper due to certified adversarial robustness and theoretical analysis of generalization ability for our training method.

- We verify our training method on a synthetic dataset and the CIFAR-10/CIFAR-100 dataset, then demonstrate that a ResNet trained by our method is more resistant to multistep ℓ^2 and ℓ^∞ adversarial attacks than natural trained ResNet.

1.2 RELATED WORK

Differential equations are powerful tools used in fields such as data analysis (Belkin & Niyogi, 2003), machine learning (Coifman et al., 2005), and image processing (Gu et al., 2004). The link between differential equations and DNNs has been discussed (Li & Shi, 2017; Haber et al., 2018; Li et al., 2017). A continuous form for ResNet, Neural ODE (Chen et al., 2018) has hidden and final states (output from the neural network) that can be solved by a standard ODE solver, and has been theoretically analyzed (Thorpe & van Gennip, 2018; Avelin & Nyström, 2021; Zhang et al., 2019a). Various deep network architectures to improve testing accuracy have been inspired by the stability theory of differential equations (Ruthotto & Haber, 2019; Haber & Ruthotto, 2017; Chang et al., 2018; Zhang & Schaeffer, 2020) or a numerical scheme of ODEs (Zhu et al., 2018; Tao et al., 2018). Many architectural have been proposed to build more robust deep networks (Zhang et al., 2019b; Yan et al., 2019; Reshniak & Webster, 2021) derived from the dynamical systems perspective.

We seek the general form of a PDEs corresponding to a DNN model, and use the theory of PDEs to design a method to train DNN with better robustness and less overfitting risk.

1.3 ORGANIZATION

This paper is organized in the following way: In subsection 2.1, we build a PDE framework for ResNet-like DNN. In subsection 2.2, we introduce several existing models which can be interpreted by our framework. Then we design a training method for DNN and theoretically analyze the robustness and generalization ability of our training method in subsection 2.3 and 2.4 respectively. In section 3, we present a algorithm based on our theory for real applications. In section 4, we test the performance of the our training method on both Half-moon and CIFAR-10/CIFAR-100 dataset. Our paper ends up with some concluding remarks.

1.4 NOTATIONS

We denote scalars, vectors, and matrices by lowercase and uppercase letters, where vectors and matrices are bolded. We denote the ℓ_2 and ℓ^∞ norms of the vector $\boldsymbol{x} = (x_1, \cdots, x_d) \in \mathbb{R}^d$ by $\|\boldsymbol{x}\|_2 = (\sum_{i=1}^{d} |x_i|^2)^{1/2}$ and $\|\boldsymbol{x}\|_\infty = \max_{i=1}^{d} |x_i|$, respectively. We use $\|\mathbf{A}\|_2$ to denote the induced norm by the vector ℓ^2 norm of the matrix $\mathbf{A}$. We denote the nabla and Laplace calculators by $\nabla = (\frac{\partial}{\partial x_1}, \cdots, \frac{\partial}{\partial x_d})$ and $\Delta = \sum_{i=1}^{d} \frac{\partial^2}{\partial x_i^2}$, respectively. For a function $f : \mathbb{R}^d \to \mathbb{R}$, $D^\alpha f$ denotes its α-order derivative, $\|f(\boldsymbol{x})\|_{L^\infty} = \sup_{\boldsymbol{x} \in \mathbb{R}^d} |f(\boldsymbol{x})|$ its L^∞ norm, and $\|f(\boldsymbol{x})\|_{C^1} = \|f(\boldsymbol{x})\|_{L^\infty} + \|\nabla f(\boldsymbol{x})\|_{L^\infty}$ its C^1 norm. $\mathcal{N}(\mathbf{0}, \sigma^2 \mathbf{I})$ denotes Gaussian noise with mean $\mathbf{0}$ and variance σ^2. Let $C_b^\infty = L^\infty \cap C^\infty$, where L^∞ and C^∞ denote the sets of bounded and infinitely differentiable functions, respectively.

2 MAIN RESULTS

We show under several reasonable assumptions that the adjustment operator T_t is the solution operator of convection diffusion equations. Based on the regularity theory of PDEs, we design a training method for DNN models and theoretically illustrate its benefits for improving the robustness of models and reducing the generalization gap.

2.1 GENERAL FORM OF PDEs

We denote the base DNN model by $f_{\boldsymbol{w}}(\boldsymbol{x})$, which is uniformly continuous. We assume data points are distributed in $\mathcal{D} \subset \mathbb{R}^d$, and label function $l(\boldsymbol{x})$ is defined in $\mathcal{D}$ but known only in training set $S_N \in \mathcal{D}$. Our method formulates the DNN as a continuous dynamic system, namely $u(\boldsymbol{x}, t) = T_t(f), t \in [0, T]$. To get the expression of the adjustment operator T_t, we assume it has some fundamental properties.

[Locality] $(T_t(f) - T_t(g))(\boldsymbol{x}) = o(t)$ as $t \to 0^+$, for all f, g such that $D^\alpha f(\boldsymbol{x}) = D^\alpha g(\boldsymbol{x})$ for all $|\alpha| \geq 0$.

[Comparison Principle] $T_t(f) \leq T_t(g)$ for all $t \geq 0$ and f, g such that $f \leq g$.

[Markov property] $T_{t+s} = T_{t+s,s} \circ T_s$, for all $s, t \geq 0$ and $t + s \leq T$. $T_{t+s,s}$ denotes the flow from time s to time $t + s$.

[Spatial Regularity] There exist a positive constant C such that $\|T_t(\tau_{\boldsymbol{h}} f) - \tau_{\boldsymbol{h}}(T_t f)\|_{L^\infty} \leq Ch$ for all $\boldsymbol{h}$ in $\mathbb{R}^d$, $t \geq 0$, where $(\tau_h f)(\boldsymbol{x}) = f(\boldsymbol{x} + \boldsymbol{h})$ and $\|\boldsymbol{h}\|_2 = h$.

[Temporal Regularity] The following two property hold:
1) For all $t, s, t + s \in [0, T]$ and all $g \in Q$, there exist a constant $C \geq 0$ depending only on Q such that $\|T_{t+s,s}(g) - g\|_{L^\infty} \leq Ct$, where Q is the subset of C_b^∞ defined by

$$Q = \{f \in C_b^\infty, \forall n \geq 0, \|D^\alpha f\|_{L^\infty} \leq C_n \text{ for all } |\alpha| = n\}.$$

2) For all $t, s, t + s \in [0, T]$, there exist a constant $C \geq 0$ such that $\|T_{t+s,t}(f) - T_{s,0}(f)\|_{L^\infty} \leq Cst$ uniformly in $s \in (0, T]$.

[Ensemble Additivity] $T_t(f + g) = T_t(f) + T_t(g)$, and if C is a constant, then $T_t(C) = C$.

To illustrate the reasonableness of these assumptions above, we give following explanation. We first require that T_t can be expressed as a solution operator of PDEs and for small enough t, the value of $T_t(f)$ at any point $\boldsymbol{x}$ is determined by the behavior of the base classifier f near $\boldsymbol{x}$, which implies

[Locality]. We then require the operator T_t is provided with an order-preserving property which means that no enhancement is made. Thus if the confidence level for an event of one base classifier g is higher than another base classifier f, this ordering is preserved, which implies **[Comparison Principle]**. Next we require T_{t+s} can be computed from T_t for any $s \leq t$, and T_0 is of course the identity. This is natural, since the future behaviour of the adjustment process at terminal time $t+s$ is likely to be deduced from the state at intermediate time t without any dependence upon the original model f, which implies **[Markov property]**. We need function $T_t(f)$ is spatial stable. If we add a perturbation $\boldsymbol{h}$ to data point $\boldsymbol{x}$, the output $T_t(f)(\boldsymbol{x} + \boldsymbol{h})$ will not change a lot, which implies **[Spatial Regularity]**. We also need an additional property for giving some temporal stability to the operator T_t. Namely, in any time interval, the adjustment will not be rapid, which implies **[Temporal Regularity]**. Assume an ensemble classifier F consists of base classifiers f and g, and another ensemble classifier consists of base classifiers $T_t(f)$ and $T_t(g)$. We require the prediction $T_t(F)$ to equal $T_t(f) + T_t(g)$, which implies **[Ensemble Additivity]**.

Theorem 1. *Under above conditions, there exists Lipschitz continuous function $v : \mathbb{R}^d \times [0, T] \to \mathbb{R}^d$ and Lipschitz continuous positive function $\sigma : \mathbb{R}^d \times [0, T] \to \mathbb{R}^{d \times d}$ such that for any bounded and uniformly continuous base model $f_{\boldsymbol{w}}(\boldsymbol{x})$, $u(\boldsymbol{x}, t) = T_t(f_{\boldsymbol{w}})(\boldsymbol{x})$ is the unique viscosity solution of the following convection diffusion equation:*

$$\begin{cases} \frac{\partial u(\boldsymbol{x},t)}{\partial t} = v(\boldsymbol{x},t) \cdot \nabla u(\boldsymbol{x},t) + \frac{1}{2} \sum_{i,j} \sigma_{i,j} \frac{\partial^2 u}{\partial x_i \partial x_j}(\boldsymbol{x},t), \\ u(\boldsymbol{x}, 0) = f_{\boldsymbol{w}}(\boldsymbol{x}), \end{cases} \tag{1}$$

where $\boldsymbol{x} \in \mathbb{R}^d, t \in [0, T]$. Here $\sigma_{i,j}$ is the i, j-th element of matrix function $\sigma(\boldsymbol{x}, t)$.

We will provide the proof of the Theorem 1 in Appendix B. In this subsection, we introduce a PDEs framework for DNN models. The framework is quite general, many existing models with residual connections can be modeled by our framework. As examples, we briefly list some of them in the next subsection.

2.2 SEVERAL MODELS

In this subsection, we will show ResNet and Gaussian noise injection(Wang et al., 2020; Liu et al., 2019) can be interpreted by our framework. And we will show randomized smoothing(Cohen et al., 2019; Li et al., 2018; Salman et al., 2019) can be interpreted by our framework in Appendix A.

ResNet: ResNet are composed of a series of residual mapping. Each residual block is realized by adding shortcut connection to connect the input and output of the original mapping ($\mathcal{F}$). Mathematically, the n-th residual mapping can be formulated as

$$\boldsymbol{x}_{n+1} = \boldsymbol{x}_n + \mathcal{F}(\boldsymbol{x}_n, \boldsymbol{w}_n) \tag{2}$$

with $\boldsymbol{x}_0 \in \mathbb{R}^d$ be a data point. $\boldsymbol{x}_n$ is the input to the n-th residual mapping and $\mathcal{F}(\boldsymbol{x}_n, \boldsymbol{w}_n)$ is a non-linear function parameterized by $\boldsymbol{w}_n$ which can be learned by back propagating the training error. The prediction of the data point $\boldsymbol{x}_0$ can be expressed by $\hat{y} = \mathrm{softmax}(\boldsymbol{w}^{\mathrm{FC}} \boldsymbol{x}_L)$. By introducing a temporal partition: $t_n = nT/L$, for $n = 0, 1, .., L$ with the time interval $\Delta t = T/L$ and let $\boldsymbol{x}(t_n) = \boldsymbol{x}_n$ and $\boldsymbol{w}(t_n) = \boldsymbol{w}_n$. Without considering the dimensional consistency, ResNet can be formulated as :

$$\boldsymbol{x}(t_{n+1}) = \boldsymbol{x}(t_n) + \frac{\mathcal{F}(\boldsymbol{x}(t_n), \boldsymbol{w}(t_n))}{\Delta t} \Delta t, n = 0, 1, \cdots, L,$$

which is the forward Euler discretization of the following equations with time step Δt, that is,

$$d\boldsymbol{x}(t) = v(\boldsymbol{x}(t), t)dt, \ \ t \in [0, T], \tag{3}$$

where $v(\boldsymbol{x}(t_n), t_n) = \mathcal{F}(\boldsymbol{x}(t_n), \boldsymbol{w}(t_n))/\Delta t$ and L is the number of resdiual mapping in a ResNet architecture. The prediction can be expressed by $\hat{y} = \mathrm{softmax}(\boldsymbol{w}^{\mathrm{FC}} \boldsymbol{x}(T))$. The equation 3 defines the characteristic curves of the following TE

$$\frac{\partial u}{\partial t}(\boldsymbol{x}, t) = v(\boldsymbol{x}, t)\nabla u(\boldsymbol{x}, t), \ \boldsymbol{x} \in \mathbb{R}^d. \tag{4}$$

So the prediction $\hat{y}$ can be seen as the solution $u(\boldsymbol{x}, T)$ of following TE:

$$\begin{cases} \frac{\partial u}{\partial t}(\boldsymbol{x}, t) = v(\boldsymbol{x}, t)\nabla u(\boldsymbol{x}, t), \ x \in \mathbb{R}^d. \\ u(\boldsymbol{x}, 0) = \mathrm{softmax}(\boldsymbol{w}^{\mathrm{FC}} \boldsymbol{x}). \end{cases} \tag{5}$$

Gaussian noise injection: Gaussian noise injection is a effective regularization mechanisms for a DNN model. For a base ResNet, a residual mapping with Gaussian noise injected can be written as

$$\boldsymbol{x}_{n+1} = \boldsymbol{x}_n + \mathcal{F}(\boldsymbol{x}_n, \boldsymbol{w}_n) + a\varepsilon_n, \ \ \varepsilon_n \sim \mathcal{N}(0, \mathbf{I}),$$

where the parameter a is a noise coefficient. Let $a = \sigma\sqrt{\Delta t}$ and $\mathcal{F}(\boldsymbol{x}_n, \boldsymbol{w}_n)/\Delta t = v(\boldsymbol{x}, t)$. This noise injection techniques in discrete neural network can be viewed as the approximation of continuous dynamic

$$d\boldsymbol{x}(t) = v(\boldsymbol{x}_n, t)dt + \sigma d\mathbf{B}(t)$$

where $\mathbf{B}(t)$ is multidimensional Brownian motion. An ensemble prediction over all the possible sub-networks with shared parameters can be written as

$$\hat{y} = \mathbb{E}(\text{softmax}(\boldsymbol{w}^{\text{FC}}\boldsymbol{x}(T))|\boldsymbol{x}(0) = \boldsymbol{x}_0). \tag{6}$$

According to Feynman-Kac formula(Mao, 2007), equation equation 6 is known to solve the following convection diffusion equation

$$\begin{cases} \frac{\partial u(\boldsymbol{x},t)}{\partial t} = v(\boldsymbol{x}, t) \cdot \nabla u + \sigma^2 \Delta u, \boldsymbol{x} \in \mathbb{R}^d, t \in [0, T] \\ u(\boldsymbol{x}, 0) = \text{softmax}(\boldsymbol{w}^{\text{FC}}\boldsymbol{x}) \end{cases}$$

In fact, ResNet with stochastic depth(Huang et al., 2016) and ResNet with stochastic dropping out the hidden state of residual block(Srivastava et al., 2014; Sun et al., 2018) can also be modeled by our framework, due to space constraints, we will not make more introduction.

The viewpoint that forward propagation of a ResNet is the solution process of a TE enables us to interpret poor robustness and generalization ability as the irregularity of the solution. To mitigate this issue, based on our PDE framework and the theory of PDEs, we use the ResNet $f_{\boldsymbol{w}}(\boldsymbol{x})$ as the base classifier and use the solution operator of the diffusion equation

$$\begin{cases} \frac{\partial u(\boldsymbol{x},t)}{\partial t} = v(\boldsymbol{x}, t) \cdot \nabla u(\boldsymbol{x}, t) + \sigma^2 \Delta u, \boldsymbol{x} \in \mathbb{R}^d, t \in [0, T] \\ u(\boldsymbol{x}, 0) = f_{\boldsymbol{w}}(\boldsymbol{x}). \end{cases} \tag{7}$$

as the adjustment operator T_t to smooth the ResNet to improve the robustness and generalization ability of the new classifier $T_t(f_{\boldsymbol{w}}(\boldsymbol{x}))$, as we discuss below.

2.3 ROBUSTNESS GUARANTEE

Consider a classification problem from $\mathbb{R}^d$ to classes $\mathcal{Y}$. Let G be a classifier defined by $G(\boldsymbol{x}) = \arg\max_{i \in \mathcal{Y}} u^i(\boldsymbol{x}, T)$, where $u^i(\boldsymbol{x}, T)$ is the i-th element of $u(\boldsymbol{x}, T)$. Suppose that the new DNN classifies $\boldsymbol{x}$ the most probable class c_A is returned with probability $p_A = u^{c_A}(\boldsymbol{x}, T)$, and the "runner-up" class is returned with probability p_B. Our main result of this subsection is to estimate around the data point $\boldsymbol{x}$ how large ℓ^p radius can make the classifier $G(\boldsymbol{x})$ be robust, where $1 < p \le \infty$.

Theorem 2. *Let the base model $f_{\boldsymbol{w}}(\boldsymbol{x})$ be a compactly supported function and velocity $v(\boldsymbol{x}, t) \in C^1(\mathbb{R}^d \times [0, T])$. Let the new DNN $u(\boldsymbol{x}, T)$ be the solution of equation 7. Suppose $c_A \in \mathcal{Y}$ and*

$$u^{c_A}(\boldsymbol{x}, T) = p_A \ge p_B = \max_{i \ne c_A} u^i(\boldsymbol{x}, T),$$

then $G(\boldsymbol{x} + \boldsymbol{\delta}) = c_A$ for all $\|\boldsymbol{\delta}\|_p \le R$, where

$$R = \frac{e^{\sigma^2 T}(p_A - p_B)}{2d^{1/q}e^{\gamma T}\max_i \|f_{\boldsymbol{w}}^i(\boldsymbol{x})\|_{C^1}},$$

$1/p + 1/q = 1$ and γ is a constant depend on ∇v.

We provide the proof of Theorem 2 in Appendix C. According to Theorem 2, we can obtain the certified radius R is large when the diffusion coefficient σ^2 and the probability of the top class is high. Not only robustness, comparing to the base classifier, we will show the generalization ability of model 7 will be better in next subsection.

2.4 GENERALIZATION GAP

For simplicity, we consider binary classification problems. Suppose $S_N = \{(\boldsymbol{x}_i, y_i)\}_{i=1}^N$ is drawn from $X \times Y \subset \mathcal{D} \times \{-1, +1\}$ with X and Y being the input data and label spaces, respectively. Assume $\mathcal{D}$ is the underlying distribution of $X \times Y$, which is unknown. Let $\mathcal{H} \subset V^X$ be the hypothesis class of the DNN model, where V is another space that might be different from Y. Let $\ell : V \times Y \to [0, B]$ be the loss function and B is a positive constant. Denote function class $\ell_{\mathcal{H}} := \{(\boldsymbol{x}, y) \to \ell(h(\boldsymbol{x}), y) : h \in \mathcal{H}\}$. Rademacher complexity is one of the classic measures of generalization error. We first recap on the definition of Rademacher complexity.

Definition 1. *(Ledoux & Talagrand, 2013)Let $\mathcal{H} : X \to \mathbb{R}$ be the space of real-valued functions on the space X. For a given sample $S_N = \{(\boldsymbol{x}_i, y_i)\}_{i=1}^N$, the empirical Rademacher complexity of $\mathcal{H}$ is defined as*

$$R_{S_N}(\mathcal{H}) := \frac{1}{N}\mathbb{E}_\sigma[\sup_{h \in \mathcal{H}} \sum_{i=1}^N \sigma_i h(\boldsymbol{x}_i)],$$

where $\sigma_1, \sigma_2, \cdots, \sigma_N$ are i.i.d. Rademacher random variables with $\mathbb{P}(\sigma_i = 1) = \mathbb{P}(\sigma_i = -1) = \frac{1}{2}$.

Rademacher complexity is a tool to bound the generalization error. The smaller the generalization gap is, the less overfitting the model is. For $\forall \boldsymbol{x}_i \in \mathbb{R}^d$ and constant $c \geq 0$, we consider the following two function classes:

$$\mathcal{F} := \left\{ f(\boldsymbol{x}) | \|f\|_{C^1} \leq c \right\},$$

and

$$\mathcal{G}_\sigma := \left\{ g(\boldsymbol{x}) = u(\boldsymbol{x}, 1) | \frac{\partial u(\boldsymbol{x}, t)}{\partial t} = v(\boldsymbol{x}, t)\nabla u(\boldsymbol{x}, t) + \sigma^2 \Delta u, u(\boldsymbol{x}, 0) = f(\boldsymbol{x}) \text{ where } f \in \mathcal{F} \right\}$$

The function class $\mathcal{F}$ represents the continuous analogue of ResNet, and function class $\mathcal{G}_\sigma$ denotes $\mathcal{F}$ adjusted by operator T_t. Then we have the following theorem.

Theorem 3. *Given a training set $S_N = \{(\boldsymbol{x}_i, y_i)\}_{i=1}^N$. With probability at least $1 - 1/(2N)$ we have*

$$R_{S_N}(\mathcal{F}) \leq \frac{C}{\sqrt{N}}[(\log c + \log N)^{1/2} + c]$$

$$R_{S_N}(\mathcal{G}_\sigma) \leq \frac{C}{\sqrt{N}}[(-\sigma^2 + \ln c + \ln N)^{1/2} + \exp(-\sigma^2)c]$$

Here C is a positive constant depend on $\mathcal{D}$ and dimension d.

We provide the proof of Theorem 3 in Appendix D. According to Theorem 3, we can obtain that for function class $\mathcal{G}_\sigma$, the upper bound of Rademacher complexity is low when the diffusion coefficient σ^2 is high. We next present a practical algorithm for real applications to verify our main results.

3 ALGORITHMS

Let $S_N = \{(\boldsymbol{x}_1, y_1), \cdots, (\boldsymbol{x}_n, y_n)\}$ be training set, where $\boldsymbol{x}_i$ is a data point and y_i is the corresponding label. Then denote the ResNet with natural training by $f_{\boldsymbol{w}}(\boldsymbol{x})$. For convenience, we assume the velocity $v(\boldsymbol{x}, t)$ is zero and the diffusion term $\sigma(\boldsymbol{x}, t)$ is $\sigma^2 \mathbf{I}$. We can rewrite equation 1 as

$$\begin{cases} \frac{\partial u(\boldsymbol{x}, t)}{\partial t} = \sigma^2 \Delta u(\boldsymbol{x}, t), x \in \mathbb{R}^d, t \in [0, T] \\ u(\boldsymbol{x}, 0) = f_{\boldsymbol{w}}(\boldsymbol{x}) \end{cases} \tag{8}$$

where σ^2 is a hyperparameter. In this model, we set the natural trained ResNet as the initial value. Instead of calculating the solution of equation 8, we train a DNN $g_{\boldsymbol{w}}(\boldsymbol{x}, t)$ to approximate the real solution. Therefore, to train the DNN model $g_{\boldsymbol{w}}(\boldsymbol{x}, t)$, we design loss terms on training set S_N for the initial condition and differential equation.

We use $l^{CE}(g_{\boldsymbol{w}}(\boldsymbol{x}_i, 0), f_{\boldsymbol{w}}(\boldsymbol{x}_i))$ to fit the initial condition of equation 8, where $l^{CE} = -\log g_k(\boldsymbol{x})$ is cross-entropy loss, k is the label of data point $\boldsymbol{x}$, and $g_k(\boldsymbol{x})$ is the output probability for category k. To

improve the natural accuracy, we enhance the terminal value to fit the label, i.e., $l^{CE}(g_{\boldsymbol{w}}(\boldsymbol{x}_i, T), y_i)$. We can write the first loss term as

$$L_1(g_{\boldsymbol{w}}, S_N) = \frac{1}{N} \sum_{i=1}^{N} [l^{CE}(g_{\boldsymbol{w}}(\boldsymbol{x}_i, 0), f_{\boldsymbol{w}}(\boldsymbol{x}_i)) + l^{CE}(g_{\boldsymbol{w}}(\boldsymbol{x}_i, T), y_i)]. \tag{9}$$

We use mean square error loss to fit the differential equation and improve the robustness of our model,

$$L_2(g_{\boldsymbol{w}}, S_N) = \frac{1}{N} \sum_{i=1}^{N} \int_0^T \left(\frac{\partial g_{\boldsymbol{w}}}{\partial t}(\boldsymbol{x}_i, s) - \sigma^2 \Delta g_{\boldsymbol{w}}(\boldsymbol{x}_i, s) \right)^2 \mathrm{d}s. \tag{10}$$

According to the trapezoid formula, the integral term equation 10 is approximated by

$$L_2(g_{\boldsymbol{w}}, S_N) \approx \frac{1}{2N} \sum_{i=1}^{N} \sum_{s=0,T} \left(\frac{\partial g_{\boldsymbol{w}}}{\partial t}(\boldsymbol{x}_i, s) - \sigma^2 \Delta g_{\boldsymbol{w}}(\boldsymbol{x}_i, s) \right)^2. \tag{11}$$

Using Taylor formula, the $\Delta g_{\boldsymbol{w}}(\boldsymbol{x}_i, s)$ can be approximated as

$$\Delta g_{\boldsymbol{w}}(\boldsymbol{x}_i, s) \approx \frac{1}{M} \sum_{j=1}^{M} \left(\frac{g_{\boldsymbol{w}}(\boldsymbol{x}_i + h\boldsymbol{\varepsilon}_{i,j}, s) + g_{\boldsymbol{w}}(\boldsymbol{x}_i - h\boldsymbol{\varepsilon}_{i,j}, s) - 2g_{\boldsymbol{w}}(\boldsymbol{x}_i, s)}{h^2} \right). \tag{12}$$

where $\{\boldsymbol{\varepsilon}_{i,j}\}$ is i.i.d and M is the average number. In practical, we choose the number of average M equals 1 to reduce the computation cost, and set h to 0.1 because training converges with difficulty when h is too small. We denote the right hand of equation 12 by $\Delta_{h,\boldsymbol{\varepsilon}} g_{\boldsymbol{w}}(\boldsymbol{x}_i, s)$. Combining equation 11 and equation 12, the integral term equation 10 can be approximated by

$$L_2^{h,M}(g_{\boldsymbol{w}}, S_N) = \frac{1}{N} \sum_{i=1}^{N} \sum_{s=0,T} \left(\frac{\partial g_{\boldsymbol{w}}}{\partial t}(\boldsymbol{x}_i, 0) - \sigma^2 \Delta_{h,\boldsymbol{\varepsilon}} g_{\boldsymbol{w}}(\boldsymbol{x}_i, s) \right)^2. \tag{13}$$

Putting the two objective functions together, our training loss combines $L_1(g_{\boldsymbol{w}}, S_N)$ and $L_2^{h,M}(g_{\boldsymbol{w}}, S_N)$, i.e., $\mathrm{Loss}(g_{\boldsymbol{w}}, S_N) = L_1(g_{\boldsymbol{w}}, S_N) + \lambda L_2^{h,M}(g_{\boldsymbol{w}}, S_N)$, where $\lambda > 0$ is a coefficient to trade off the two loss terms. In practice, we use stochastic gradient descent to optimize $g_{\boldsymbol{w}}(\boldsymbol{x}, t)$, and we use $g_{\boldsymbol{w}}(\boldsymbol{x}, T)$ as the final model.

4 EXPERIMENTS

In this section, we will numerically verify that 1) can our method improve the robustness and reduce overfitting risk of DNN? 2) what is the advantage of our method over the Gaussian noise injection and randomized smoothing?

4.1 PRELIMINARIES

Datasets. In our experiments, we consider both Half-moon and CIFAR10/CIFAR100 (Krizhevsky et al., 2009) datasets. Half-moon dataset is a randomly generated 2d synthetic dataset in which we randomly generate 500 points and 1000 points with a standard deviation of 0.3 as training set and testing set, respectively. Both CIFAR10 and CIFAR100 contain 60K 32×32 color images with 50K and 10K of them used for training and test, respectively. CIFAR10 and CIFAR100 contain 10 and 100 different classes, respectively.

Project gradient descent attack (PGD). To verify the efficiency of our method for improving the robustness of DNN, we consider the project gradient descent (PGD)(Madry et al., 2017) in all the experiments below. Before introducing PGD, we first introduce fast gradient sign method attack (FGSM). The FGSM attack searches the adversarial image $\boldsymbol{x}'$ by maximizing the linearized loss function function $\mathcal{L}(\boldsymbol{x}', y) \approx \mathcal{L}(\boldsymbol{x}, y) + \nabla \mathcal{L}(\boldsymbol{x}, y)^T (\boldsymbol{x}' - \boldsymbol{x})$ with constraint $\|\boldsymbol{x}' - \boldsymbol{x}\|_p \leq \epsilon$, where ϵ is the maximum perturbation and $p = 2, \infty$. PGD with step size α and clips the perturbed image to generate the enhanced adversarial attack,

$$\ell^{\infty} : \boldsymbol{x}^{(m)} = \mathrm{Clip}_{\boldsymbol{x}, \epsilon} \{ \boldsymbol{x}^{(m-1)} + \alpha \mathrm{sign}(\nabla \mathcal{L}(\boldsymbol{x}^{(m-1)}, y)) \},$$

(a)Natural training   (b) $\lambda = 0.01, \sigma^2 = 0.01$ (c) $\lambda = 0.1, \sigma^2 = 0.01$ (d) $\lambda = 0.1, \sigma^2 = 0.1$

Figure 1: Decision boundary of natural trained ResNet and ResNet trained by our method with different hyperparameters λ and σ^2.

(a)$\mathcal{A}_{nat}^{test}(\%)$ (b) $\mathcal{A}_{rob}^{test}(\%)$ (c) $\mathcal{A}_{nat}^{train} - \mathcal{A}_{nat}^{test}(\%)$

Figure 2: Performance of ResNet trained by our model with different hyperparameters λ and σ^2 on Half-moon dataset.

$$\ell^2 : \boldsymbol{x}^{(m)} = \text{Clip}_{\boldsymbol{x},\epsilon}\{\boldsymbol{x}^{(m-1)} + \alpha(\frac{\nabla \mathcal{L}(\boldsymbol{x}^{(m-1)}, y)}{\|\nabla \mathcal{L}(\boldsymbol{x}^{(m-1)}, y)\|_2})\},$$

where $m = 1, \cdots, K$, $\boldsymbol{x}^{(0)} = \boldsymbol{x}$, and let the adversarial image be $x' = x^{(K)}$ with K being the total number of iterations. For Half-moon dataset, we apply 20 iterations PGD attack (PGD^{20}) with step size 0.01. The perturbation is constrained to be 0.2 under l^∞ norm. For CIFAR-10/CIFAR-100 dataset, when under ℓ^∞ norm attack, we apply 20 iterations PGD attack with step size $1/255$ and when under ℓ^2 norm attack and we apply 50 iterations PGD attack (PGD^{50}) with step size 0.1.

Performance evaluations. For Half-moon dataset, we consider three indicators to evaluate the performance of the model: natural testing accuracy ($\mathcal{A}_{nat}^{test}$), robust testing accuracy ($\mathcal{A}_{rob}^{test}$), and the gap between training accuracy and testing accuracy($\mathcal{A}_{nat}^{train} - \mathcal{A}_{nat}^{test}$). The natural accuracy and robust accuracy are measured on clean and adversarial images, respectively. The robust accuracy is used to evaluate the robustness of the models, and the difference between training and testing accuracy is used to evaluate overfitting risk of the models. For CIFAR-10/CIFAR-100 dataset, we consider $\mathcal{A}_{nat}^{test}$ and $\mathcal{A}_{rob}^{test}$.

4.2 EXPERIMENTS ON SYNTHETIC DATASET

In this subsection, we numerically verify that the efficacy of our training method in improving robustness and generalization ability of ResNet on the Half-moon dataset.

We first varied hyperparameters λ and σ^2 and present the final results in Figure 2. The three indicators (natural accuracy, robust accuracy, and difference between training accuracy and testing accuracy) for ResNet with natural training were 88.6%, 62.3%, and 10.4%, respectively. Comparing natural trained ResNet, the robustness and generalization ability of ResNet trained with our method were improved. On the other hands, when λ and σ^2 increased, the natural and robust accuracy increased, while the gap between training and test accuracies decreased. Thus we can conclude that increasing λ and σ^2 are helpful for improving the performance of the models.

We plot the decision boundary of ResNet trained with different λ, σ^2 and natural trained ResNet in Figure 1. From Figure 1, we can see that the decision boundary of natural training is irregular, while that of our models is smoother. These experimental results are consistent with our theory.

4.3 EXPERIMENT ON CIFAR-10/CIFAR-100 DATASET

We further test the performance of ResNet20/ResNet56 trained with our method on the CIFAR10/CIFAR100 dataset. During training, we apply data augmentation including random crops and flips. We run 200 epochs. The batch size is 128 and the initial learning rate is 0.1, which decays by a factor of 10 at the 100th, and 150th epochs.

Models	Hyperparameters	$\mathcal{A}_{nat}^{test}$	$\mathcal{A}_{rob}^{test}$		
			$\epsilon = 4/255\,(l^\infty)$	$\epsilon = 8/255\,(l^\infty)$	$\epsilon = 0.5\,(l^2)$
CIFAR-10 Dataset					
ResNet20	$\lambda = 0.01, \sigma^2 = 1$	86.72%	40.13%	7.8%	45.33%
	$\lambda = 0.05, \sigma^2 = 1$	84.78%	45.25%	13.03%	50.57%
	$\lambda = 0.05, \sigma^2 = 2$	82.49%	48.29%	17.79%	53.87%
ResNet56	$\lambda = 0.01, \sigma^2 = 1$	87.76%	41.85%	8.1%	46.17%
	$\lambda = 0.05, \sigma^2 = 1$	86.01%	47.42%	14.73%	53.05%
	$\lambda = 0.05, \sigma^2 = 2$	83.03%	48.73%	18.02%	55%
CIFAR-100 Dataset					
ResNet20	$\lambda = 0.01, \sigma^2 = 1$	58.77%	19.56%	3.91%	23.98%
	$\lambda = 0.05, \sigma^2 = 1$	55.7%	21.79%	5.56%	26.55%
	$\lambda = 0.05, \sigma^2 = 2$	52.73%	23.33%	8.27%	28.42%
ResNet56	$\lambda = 0.01, \sigma^2 = 1$	60.2%	19.75%	4.49%	24.93%
	$\lambda = 0.05, \sigma^2 = 1$	57.82%	23.26%	6.8%	27.82%
	$\lambda = 0.05, \sigma^2 = 2$	53.99%	25.19%	9.41%	29.55%

Table 1: Natural and robust accuracies of ResNets trained using our methods with different hyperparameters on the CIFAR-10/CIFAR-100.

Models	$\mathcal{A}_{nat}^{test}$	$\mathcal{A}_{rob}^{test}$		
		$\epsilon = 4/255\,(l^\infty)$	$\epsilon = 8/255\,(l^\infty)$	$\epsilon = 0.5\,(l^2)$
Gaussian noise injection	89.9%	22.81%	12.38%	0.1%
Our ResNet110	84.35%	**50.76%**	**19.4%**	**56.38%**
ResNet110	**93.58%**	0%	0%	0.01%

Table 2: Comparing the robustness against ℓ^∞-norm and ℓ^2-norm constrained adversarial perturbations on CIFAR-10.

There are two hyperparameters $\lambda.\sigma^2$ in our algorithm that need to be determined by a large number of experiments. In order to demonstrate the influence of the two hyperparameters, we train ResNet by using our algorithm with different λ, σ^2, then list the result in Table 1. On one hands, from Table 1, we can see that the parameter σ^2 is fixed, the nature accuracy decreases and robust accuracy increases as the increasing of parameters λ and the converse to be true. On the other hands, comparing to the result of ResNet20 and ResNet56, we can see the performance of our proposed method will be better in deeper networks.

In order to quantitatively measure the performance of our proposed method, we compare the proposed method with other defensive method without adversarial training. The result of comparison is showned in Table 2. For our method, we choose $\sigma^2 = 2$ and $\lambda = 0.5$ to train ResNet110. For Gaussian noise injection mentioned in subsection 2.2, the standard error of the Gaussian noise equals to 0.5. The experiment result shows that our method is more resistant to adversarial attack than other methods.

5 CONCLUDING REMARKS

In this paper, we derived a general form of PDE that can correspond to a DNN model. Motivated by PDE theory, we proposed a training method for ResNet. We theoretically showed that using our training methods, we obtain a model with better robustness and lower overfitting risk. Based on these theoretical results, we developed an algorithm to train DNN models, and we verified them through experiments. There are numerous avenues for future work: 1) Scale our training method to networks that are large and expressive enough to solve problems like ImageNet. 2) Study other more complex equations for DNN models and solve more challenging real tasks.

REFERENCES

Luis Alvarez, Frédéric Guichard, Pierre-Louis Lions, and Jean-Michel Morel. Axioms and fundamental equations of image processing. *Archive for rational mechanics and analysis*, 123(3):199–257, 1993.

Benny Avelin and Kaj Nyström. Neural odes as the deep limit of resnets with constant weights. *Analysis and Applications*, 19(03):397–437, 2021.

Mikhail Belkin and Partha Niyogi. Laplacian eigenmaps for dimensionality reduction and data representation. *Neural computation*, 15(6):1373–1396, 2003.

Liefeng Bo, Kevin Lai, Xiaofeng Ren, and Dieter Fox. Object recognition with hierarchical kernel descriptors. In *CVPR 2011*, pp. 1729–1736, 2011. doi: 10.1109/CVPR.2011.5995719.

Bo Chang, Lili Meng, Eldad Haber, Lars Ruthotto, David Begert, and Elliot Holtham. Reversible architectures for arbitrarily deep residual neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

Ricky T. Q. Chen, Yulia Rubanova, Jesse Bettencourt, and David Duvenaud. Neural ordinary differential equations. *Advances in Neural Information Processing Systems*, 2018.

Jeremy Cohen, Elan Rosenfeld, and Zico Kolter. Certified adversarial robustness via randomized smoothing. In *International Conference on Machine Learning*, pp. 1310–1320. PMLR, 2019.

Ronald R Coifman, Stephane Lafon, Ann B Lee, Mauro Maggioni, Boaz Nadler, Frederick Warner, and Steven W Zucker. Geometric diffusions as a tool for harmonic analysis and structure definition of data: Diffusion maps. *Proceedings of the national academy of sciences*, 102(21):7426–7431, 2005.

George E. Dahl, Dong Yu, Li Deng, and Alex Acero. Context-dependent pre-trained deep neural networks for large-vocabulary speech recognition. *IEEE Transactions on Audio, Speech, and Language Processing*, 20(1):30–42, 2012. doi: 10.1109/TASL.2011.2134090.

Xianfeng Gu, Yalin Wang, Tony F Chan, Paul M Thompson, and Shing-Tung Yau. Genus zero surface conformal mapping and its application to brain surface mapping. *IEEE transactions on medical imaging*, 23(8):949–958, 2004.

Eldad Haber and Lars Ruthotto. Stable architectures for deep neural networks. *Inverse problems*, 34 (1):014004, 2017.

Eldad Haber, Lars Ruthotto, Elliot Holtham, and Seong-Hwan Jun. Learning across scales—multiscale methods for convolution neural networks. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2016a.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. In *European conference on computer vision*, pp. 630–645. Springer, 2016b.

Gao Huang, Yu Sun, Zhuang Liu, Daniel Sedra, and Kilian Q Weinberger. Deep networks with stochastic depth. In *European conference on computer vision*, pp. 646–661. Springer, 2016.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Gustav Larsson, Michael Maire, and Gregory Shakhnarovich. Fractalnet: Ultra-deep neural networks without residuals. *arXiv preprint arXiv:1605.07648*, 2016.

Michel Ledoux and Michel Talagrand. *Probability in Banach Spaces: isoperimetry and processes*. Springer Science & Business Media, 2013.

Bai Li, Changyou Chen, Wenlin Wang, and Lawrence Carin. Certified adversarial robustness with additive noise. *arXiv preprint arXiv:1809.03113*, 2018.

Qianxiao Li, Long Chen, Cheng Tai, et al. Maximum principle based algorithms for deep learning. *arXiv preprint arXiv:1710.09513*, 2017.

Zhen Li and Zuoqiang Shi. Deep residual learning and pdes on manifold. *arXiv preprint arXiv:1708.05115*, 2017.

Xuanqing Liu, Si Si, Qin Cao, Sanjiv Kumar, and Cho-Jui Hsieh. Neural sde: Stabilizing neural ode networks with stochastic noise. *arXiv preprint arXiv:1906.02355*, 2019.

Yiping Lu, Aoxiao Zhong, Quanzheng Li, and Bin Dong. Beyond finite layer neural networks: Bridging deep architectures and numerical differential equations. In *International Conference on Machine Learning*, pp. 3276–3285. PMLR, 2018.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Xuerong Mao. *Stochastic differential equations and applications*. Elsevier, 2007.

Andreas Maurer. A vector-contraction inequality for rademacher complexities. In *International Conference on Algorithmic Learning Theory*, pp. 3–17. Springer, 2016.

Shahar Mendelson. A few notes on statistical learning theory. In *Advanced lectures on machine learning*, pp. 1–40. Springer, 2003.

Mehryar Mohri, Afshin Rostamizadeh, and Ameet Talwalkar. *Foundations of machine learning*. MIT press, 2018.

Bernt Oksendal. *Stochastic differential equations: an introduction with applications*. Springer Science & Business Media, 2013.

Viktor Reshniak and Clayton G Webster. Robust learning with implicit residual networks. *Machine Learning and Knowledge Extraction*, 3(1):34–55, 2021.

Lars Ruthotto and Eldad Haber. Deep neural networks motivated by partial differential equations. *Journal of Mathematical Imaging and Vision*, pp. 1–13, 2019.

Hadi Salman, Greg Yang, Jerry Li, Pengchuan Zhang, Huan Zhang, Ilya Razenshteyn, and Sebastien Bubeck. Provably robust deep learning via adversarially trained smoothed classifiers. *arXiv preprint arXiv:1906.04584*, 2019.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition, 2015.

Sho Sonoda and Noboru Murata. Transport analysis of infinitely deep neural network, 2018.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

Qi Sun, Yunzhe Tao, and Qiang Du. Stochastic training of residual networks: a differential equation viewpoint. *arXiv preprint arXiv:1812.00174*, 2018.

Yunzhe Tao, Qi Sun, Qiang Du, and Wei Liu. Nonlocal neural networks, nonlocal diffusion and nonlocal modeling. *arXiv preprint arXiv:1806.00681*, 2018.

Matthew Thorpe and Yves van Gennip. Deep limits of residual neural networks. *arXiv preprint arXiv:1810.11741*, 2018.

Bao Wang, Binjie Yuan, Zuoqiang Shi, and Stanley J Osher. Enresnet: Resnets ensemble via the feynman–kac formalism for adversarial defense and beyond. *SIAM Journal on Mathematics of Data Science*, 2(3):559–582, 2020.

Limin Wang, Yuanjun Xiong, Zhe Wang, Yu Qiao, Dahua Lin, Xiaoou Tang, and Luc Van Gool. Temporal segment networks: Towards good practices for deep action recognition. In Bastian Leibe, Jiri Matas, Nicu Sebe, and Max Welling (eds.), *Computer Vision – ECCV 2016*, pp. 20–36, Cham, 2016. Springer International Publishing. ISBN 978-3-319-46484-8.

E Weinan. A proposal on machine learning via dynamical systems. *Communications in Mathematics and Statistics*, 5(1):1–11, 2017.

Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1492–1500, 2017.

Hanshu Yan, Jiawei Du, Vincent YF Tan, and Jiashi Feng. On robustness of neural ordinary differential equations. *arXiv preprint arXiv:1910.05513*, 2019.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Han Zhang, Xi Gao, Jacob Unterman, and Tom Arodz. Approximation capabilities of neural ordinary differential equations. *arXiv preprint arXiv:1907.12998*, 2(4):3–1, 2019a.

Jingfeng Zhang, Bo Han, Laura Wynter, Kian Hsiang Low, and Mohan Kankanhalli. Towards robust resnet: A small step but a giant leap. *arXiv preprint arXiv:1902.10887*, 2019b.

Linan Zhang and Hayden Schaeffer. Forward stability of resnet and its variants. *Journal of Mathematical Imaging and Vision*, 62(3):328–351, 2020.

Xingcheng Zhang, Zhizhong Li, Chen Change Loy, and Dahua Lin. Polynet: A pursuit of structural diversity in very deep networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 718–726, 2017.

Mai Zhu, Bo Chang, and Chong Fu. Convolutional neural networks combined with runge-kutta methods. *arXiv preprint arXiv:1802.08831*, 2018.

APPENDIX

A SEVERAL MODELS

Randomized Smoothing: Consider to transform a base classifier into a new smoothed classifier by adding Gaussian noise to the input when inference time. If we denote the base classifier by $f(\boldsymbol{x})$ and denote the new smoothed classifier by $g(\boldsymbol{x})$. Then $f(\boldsymbol{x})$ and $g(\boldsymbol{x})$ have the following relation:

$$g(\boldsymbol{x}) = \frac{1}{N} \sum_{i=1}^{N} f(\boldsymbol{x} + \boldsymbol{\varepsilon}_i) \approx \mathbb{E}_{\boldsymbol{\varepsilon} \sim \mathcal{N}(0,I)}[f(\boldsymbol{x} + \boldsymbol{\varepsilon})] \tag{14}$$

According to Feynman-Kac formula, $g(\boldsymbol{x})$ can be viewed as the solution of the following PDEs

$$\begin{cases} \frac{\partial u(\boldsymbol{x},t)}{\partial t} = \Delta u, t \in [0,1] \\ u(\boldsymbol{x},0) = f(\boldsymbol{x}). \end{cases} \tag{15}$$

Especially, when $f(\boldsymbol{x})$ is ResNet, the smoothed classifier $g(\boldsymbol{x}) = u(\boldsymbol{x}, T+1)$ can be expressed as

$$\begin{cases} \frac{\partial u(\boldsymbol{x},t)}{\partial t} = \Delta u, t \in [T, T+1] \\ \frac{\partial u(\boldsymbol{x},t)}{\partial t} = v(\boldsymbol{x},t) \cdot \nabla u(\boldsymbol{x},t), \boldsymbol{x} \in \mathbb{R}^d, t \in [0,T] \\ u(\boldsymbol{x},0) = \text{softmax}(\boldsymbol{w}^{\text{FC}}\boldsymbol{x}). \end{cases}$$

B PROOF OF THEOREM 1

Proof. (Alvarez et al., 1993) The proof of Theorem 1 consists of several steps. First we set

$$\delta_{t,s}(f) = \frac{T_t(f) - T_s(f)}{t - s}, \ \delta_t(f) = \delta_{t,0}(f).$$

Using **[Temporal Regularity]**, for all $h, t \in [0,T]$ and all $f, g \in Q$, we can get

$$\|\delta_t(f + hg) - \delta_t(f)\|_{L^\infty} \leq Ch. \tag{16}$$

Step 1. We begin the proof of Theorem 1 by proving the following conclusion

(A1) the functions $\delta_t(f)$ are Lipschitz continuous uniformly for $t \in (0,1]$(and uniformly for f

belonging to a set Q).
Let $\boldsymbol{z}$ be in $\mathbb{R}^d$ and $\|\boldsymbol{z}\|_2 = 1$, we wish to bound $\|\tau_{h\boldsymbol{z}}[\delta_t(f)] - \delta_t(f)\|_{L^\infty}$ for $h \in [0,1]$. According to **[Spatial Regularity]**, for $f \in Q$, we have

$$\|\tau_{h\boldsymbol{z}}[\delta_t(f)] - \delta_t(f)\|_{L^\infty} \leq Ch + \|\delta_t[f(\boldsymbol{x} + h\boldsymbol{z})] - \delta_t[f(\boldsymbol{x})]\|_{L^\infty} \leq Ch.$$

Then the conclusion of **(A1)** is proved.
Step 2. From the preceding steps, we can already deduce a compactness property for $\delta_t(f)$ as $t \to 0$. Now we need more, since we want the whole sequence to converge to the same limit. So we need a Cauchy estimate. Our next step is to prove the following conclusion.

(A2) For all t, s in $[0, \frac{1}{2}]$ we have $\|\delta_{t+s,t}(f) - \delta_s(f)\|_{L^\infty} \leq m(t)$, where $m(t)$ is some continuous,

nonnegative, nondecreasing function on $[0, \frac{1}{2}]$ such that $m(0) = 0$, and $m(t)$ depends only on bounds

of derivatives of f.
First, we can rewrite $\delta_s(f)$ as $\delta_s(f) * K_\varepsilon - [\delta_s(f) * K_\varepsilon - \delta_s(f)]$, where $K \geq 0$, $\int_{\mathbb{R}^d} K \mathrm{d}\boldsymbol{y} = 1$, $K \in C_0^\infty(\mathbb{R}^d)$ and $K_\varepsilon = \varepsilon^{-d} K(\cdot/\varepsilon)$ and $*$ denote the convolution. Using the conclusion of **(A1)**, we can obtain for all $\varepsilon > 0$, there exist a positive constant C_1 such that

$$\|\delta_s(f) * K_\varepsilon - \delta_s(f)\|_\infty \leq C_1 \varepsilon. \tag{17}$$

Then because of **[Markov property]**, **[Temporal Regularity]** and **[Comparison Principle]**, we have

$$
\begin{aligned}
&\|\frac{T_{t+s}(f) - T_t(f + s\delta_s * K_\varepsilon)}{s}\|_{L^\infty} \\
\leq\quad & \|\frac{T_{t+s,s} \circ T_s(f) - T_t \circ T_s(f)}{s}\|_{L^\infty} + \|\frac{T_t \circ T_s(f) - T_t(f + s\delta_s * K_\varepsilon)}{s}\|_{L^\infty} \\
\leq\quad & Ct + \|\frac{T_s(f) - f - s\delta_s * K_\varepsilon}{s}\|_{L^\infty} \\
\leq\quad & Ct + C_2\varepsilon
\end{aligned}
\tag{18}
$$

On the other hand, since $\delta_s(f) * K_\varepsilon \in C_b^\infty$, **[Temporal Regularity]** implies that

$$
\|T_t(f + s\delta_s(f) * K_\varepsilon) - T_t(f) - s\delta_s(f) * K_\varepsilon\|_{L^\infty} \leq C_\varepsilon st
\tag{19}
$$

for some positive constant C_ε depending only on ε. Combining equation 17, equation 18 and equation 19, we finally deduce that

$$
\|\delta_{s+t,t}(f) - \delta_s(f)\|_\infty \leq 2C_1\varepsilon + C_\varepsilon t.
$$

The **(A2)** holds by setting $m(t) = \inf_{\varepsilon \in (0,1]}(2C_1\varepsilon + C_\varepsilon t)$.

Step 3. Now we give a Cauchy estimate in $0 < h \leq t \leq \frac{1}{2}$ for $\delta_s(f)$

$$
\|\delta_t(f) - \delta_h(f)\|_{L^\infty} \leq 2\frac{C_0 r}{t} + m(t) \quad \text{where } r = t - [\frac{t}{h}]h.
\tag{20}
$$

Observe that

$$
\delta_t(f) = \frac{Nh}{t}\delta_{Nh}(f) + \frac{r}{t}\delta_{Nh+r,Nh}(f).
$$

Using **(A2)** with $s = r$, $t = Nh$ and let $N = [\frac{t}{h}]$, we have

$$
\|\delta_{Nh+r}(f) - \frac{Nh}{Nh+r}\delta_{Nh}(f) - \frac{r}{Nh+r}\delta_r(f)\|_{L^\infty} \leq \frac{r}{Nh+r}m(Nh)
\tag{21}
$$

Notice that

$$
\delta_{Nh}(f) = \frac{(N-1)h}{Nh}\delta_{Nh}(f) + \frac{h}{Nh}\delta_{Nh,(N-1)h}(f).
$$

Using **(A2)** with $s = h$, $t = (N-1)h$, we have

$$
\|\delta_{Nh}(f) - \frac{N-1}{N}\delta_{(N-1)h}(f) - \frac{1}{N}\delta_h(f)\|_{L^\infty} \leq \frac{1}{N}m((N-1)h)
\tag{22}
$$

Combining this inequality with equation 22, we obtain

$$
\begin{aligned}
&\|\delta_t(f) - (N-1)\frac{h}{t}\delta_{(N-1)h}(f) - \frac{h}{t}\delta_h(f) - \frac{r}{t}\delta_r(f)\|_{L^\infty} \\
&\leq \frac{r}{t}m(Nh) + \frac{h}{t}m((N-1)h)
\end{aligned}
\tag{23}
$$

Reiterating the argument which lends to equation 22, we obtain after $(N-1)$ more steps that

$$
\|\delta_t(f) - \frac{Nh}{t}\delta_h(f) - \frac{r}{t}\delta_r(f)\|_\infty \leq \frac{r}{t}m(Nh) + \frac{h}{t}\sum_{j=1}^{N-1}m(jh)
\tag{24}
$$

Since $m(t)$ is nondecreasing and equation 23, we deduce

$$
\begin{aligned}
\|\delta_t(f) - \delta_h(f)\|_{L^\infty} &\leq \|\delta_t(f) - \frac{Nh}{t}\delta_h(f) - \frac{r}{t}\delta_r(f)\|_{L^\infty} + \frac{r}{t}\|\delta_h(f) - \delta_r(f)\|_{L^\infty} \\
&\leq \frac{r}{t}m(Nh) + \frac{(N-1)h}{t}m(t) + \frac{r}{t}(\|\delta_h(f)\|_{L^\infty} + \|\delta_r(f)\|_{L^\infty}) \\
&\leq m(t) + 2\frac{C_0 r}{t}
\end{aligned}
\tag{25}
$$

Because of equation 25, we can pick h_n going to 0 and $\delta_{h_n}(f)$ converges uniformly on compact sets to a bounded Lipschitz function on $\mathbb{R}^d$ which we denote by $A[f]$

$$\lim_{n \to \infty} \|\delta_t(f) - \delta_{h_n}(f)\|_{L^\infty} \leq \lim_{n \to \infty} m(t) + 2\frac{C_0 r}{t}$$
$$\Rightarrow \|\delta_t(f) - A[f]\|_{L^\infty} \leq m(t).$$

So $\delta_t(f)$ converges uniformly to $A[f]$ when t goes to 0.

Step 4. The goal of this step is to show the expression of $A[f]$.

Let $f, g \in C_b^\infty$ and satisfy $f(0) = g(0) = 0$, $Df(0) = Dg(0) = p \in \mathbb{R}^d$, $D^2 f(0) = D^2 g(0) = A \in S^d$. Then we set $f^\varepsilon = f + \varepsilon \|\boldsymbol{x}\|_2^2$. Using Taylor formula, there exist a positive constant c such that for $\|\boldsymbol{x}\|_2 \leq c\varepsilon$ we have $f^\varepsilon \geq g$. Let $w_\varepsilon = w(\boldsymbol{x}/\varepsilon)$ where $w \in C_b^\infty(\mathbb{R}^d)$ and $0 \leq w \leq 1$ on $\mathbb{R}^d$,

$$\begin{cases} w = 0 & \|\boldsymbol{x}\|_2 \leq c/2 \\ w = 1 & \|\boldsymbol{x}\|_2 \geq c \end{cases} \tag{26}$$

Then we introduce $f_0^\varepsilon = w_\varepsilon f^\varepsilon + (1 - w_\varepsilon)g$ and it is obviously that $f_0^\varepsilon \geq g$. Because of **[Comparison principle]**, $T_t(f_0^\varepsilon) \geq T_t(g)$. Due to

$$f_0^\varepsilon(0) = f^\varepsilon(0) = f(0) = g(0) = 0 \tag{27}$$

we can also get

$$A(f_0^\varepsilon)(0) \geq A(g)(0), A(f^\varepsilon)(0) \geq A(g)(0) \tag{28}$$

Because there exists a neighborhood of 0 that $f_0^\varepsilon = f^\varepsilon$, we have $D^\alpha f_0^\varepsilon(0) = D^\alpha f^\varepsilon(0)$ for $\forall |\alpha| \geq 0$. In view of [Locality] we have $A(f_0^\varepsilon)(0) = A(f^\varepsilon)(0)$. And considering the continuity of A, we can deduce $A(f_0^\varepsilon)$ converges to $A(f)$ in L^∞ when ε goes to 0. This means $A(f)(0) \geq A(g)(0)$. By similar method, we can get $A(f)(0) \leq A(g)(0)$. So we finally get

$$A(f) = F(Du, D^2 u, \boldsymbol{x}). \tag{29}$$

Here F is a continuous function. In the same way, we can get

$$A_t(f) = F(Du, D^2 u, \boldsymbol{x}, t). \tag{30}$$

According to **[Ensemble Additivity]**, we can finally there exist Lipschitz continuous functions $v : \mathbb{R}^d \times [0, T] \to \mathbb{R}^d$ and Lipschitz continuous positive definite functions $\sigma : \mathbb{R}^d \times [0, T] \to \mathbb{R}^{d \times d}$ such that $u(\boldsymbol{x}, t) = T_t(f)$ is the solution of the equation

$$\begin{cases} \frac{\partial u(\boldsymbol{x}, t)}{\partial t} = v(\boldsymbol{x}, t) \cdot \nabla u(\boldsymbol{x}, t) + \sum_{i,j} \sigma_{i,j}(\boldsymbol{x}, t) \frac{\partial u}{x_i, x_j}(\boldsymbol{x}, t), \boldsymbol{x} \in \mathbb{R}^d, t \in [0, 1] \\ u(\boldsymbol{x}, 0) = f(\boldsymbol{x}), \end{cases}$$

where $\sigma_{i,j}(\boldsymbol{x}, t)$ is the i, j-th element of matrix function $\sigma(\boldsymbol{x}, t)$. $\qquad \square$

The existence and uniqueness of equation 1 are guaranteed by the following theorem

Theorem 4. *(**Kolmogorov's backward equation**)(Theorem 8.1.1 in (Oksendal, 2013)) Assume Itô process $\boldsymbol{x}(t)$ satisfies SDE*

$$d\boldsymbol{x}(t) = v(\boldsymbol{x}(t), t)dt + \sigma(\boldsymbol{x}(t))d\mathbf{B}(t), \; \boldsymbol{x}(0) = \boldsymbol{x},$$

where $\mathbf{B}(t)$ is d-m Brownian motion and $v : \mathbb{R}^d \to \mathbb{R}^d$, $\sigma : \mathbb{R}^d \to \mathbb{R}^{d \times d}$ are all Lipschitz continuous function. Let $f_{\boldsymbol{w}}(\boldsymbol{x}) \in C_0^2(\mathbb{R}^d)$. Then $u(\boldsymbol{x}, t) = \mathbb{E}[f_{\boldsymbol{w}}(\boldsymbol{x}(t)|\boldsymbol{x}(0) = \boldsymbol{x}]$ is the unique solution of equation 1.

C   PROOF OF THEOREM 2

Proof. Let $w(\boldsymbol{x}, t) = (\mu u^2(\boldsymbol{x}, t) + \|\nabla u(\boldsymbol{x}, t)\|^2)e^{-2\lambda t}$, where μ and λ are constants which will be defined later.

Note that $u^2(\boldsymbol{x}, t)$ satisfies

$$\frac{\partial (u^2)}{\partial t} + v(\boldsymbol{x}, t)\nabla(u^2) = \sigma^2 \Delta(u^2) - 2\sigma^2 \|\nabla u\|^2,$$

and $\|\nabla u\|^2$ satisfies

$$\frac{\partial \|\nabla u\|^2}{\partial t} + v(\boldsymbol{x}, t)\nabla \|\nabla u\|^2 = -2\nabla u \nabla v(\boldsymbol{x}, t)\nabla u + \sigma^2 \Delta \|\nabla u\|^2 - 2\sigma^2 (\Delta u)^2,$$

therefore,

$$\frac{\partial w}{\partial t} + v(\boldsymbol{x}, t)\nabla w - \sigma^2 \Delta w$$
$$= e^{-2\lambda t}[-2\lambda(\mu u^2 + \|\nabla u\|^2) - 2\mu\sigma^2 \|\nabla u\|^2 - 2\nabla u \nabla v(\boldsymbol{x}, t)\nabla u - 2\sigma^2 (\Delta u)^2].$$

Next, let $\gamma(\boldsymbol{x}, t) = \min_{\|\xi\|=1} \xi^T \nabla v(\boldsymbol{x}, t)\xi$ and $\gamma = \min_{\boldsymbol{x}, t} \gamma(\boldsymbol{x}, t)$, and let $Lw := \frac{\partial w}{\partial t} + v(\boldsymbol{x}, t)\nabla w - \sigma^2 \Delta w$ then we have

$$Lw \leq -2e^{-2\lambda t}[\lambda\mu u^2 + (\lambda + \mu\sigma^2 - \gamma)\|\nabla u\|^2].$$

If we choose λ and μ large enough, such that $\lambda + \mu\sigma - \gamma \geq 0$, then

$$Lw \leq 0.$$

From the maximum principle, we know $\max_{\boldsymbol{x}} w(\boldsymbol{x}, 1) \leq \max_{\boldsymbol{x}} w(\boldsymbol{x}, 0)$. Let $\mu = 1$ and $\lambda = \gamma - \sigma^2$, we can easily get

$$\|u(\boldsymbol{x}, T)\|_{C^1} \leq e^{-\sigma^2 T} e^{\gamma T} \|f_{\boldsymbol{w}}(\boldsymbol{x})\|_{C^1}, \tag{31}$$

According to the Taylor formula and Hölder inequality, we can get that for any $\|\boldsymbol{\delta}\|_p = \delta$, we have

$$|f_{\boldsymbol{w}}(\boldsymbol{x}) - f_{\boldsymbol{w}}(\boldsymbol{x} + \boldsymbol{\delta})| \leq \|\nabla f_{\boldsymbol{w}}(\boldsymbol{x})\|_q \delta \leq d^{1/q} \|f_{\boldsymbol{w}}(\boldsymbol{x})\|_{C^1} \delta, \tag{32}$$

and

$$|u(\boldsymbol{x}, T) - u(\boldsymbol{x} + \boldsymbol{\delta}, T)| \leq \|\nabla u(\boldsymbol{x}, T)\|_q \delta \leq d^{1/q} \|u(\boldsymbol{x}, T)\|_{C^1} \delta, \tag{33}$$

Then combining equation 31, equation 32 and equation 33, we can easily prove the theorem. □

D PROOF OF THEOREM 3

The goal of the learning problem is to find $h \in \mathcal{H}$ such that **population risk** $E(h) := \mathbb{E}_{(\boldsymbol{x}, y)}[\ell(h(\boldsymbol{x}), y)]$ is minimized. We consider the supervised learning setting where one has access to n i.i.d. training examples S_N. A learning algorithm maps the N training examples to a hypothesis $h \in \mathcal{H}$. In this section, we are interested in the gap between the **empirical risk** $E_N(h) := \frac{1}{N} \sum_{i=1}^{N} \ell(h(\boldsymbol{x}_i), y_i)$ and the population risk $E(h)$, known as the generalization error. We start with the following theorem which connects the population and empirical risks via Rademacher complexity.

Lemma 1. *(Theorem 3.5 in (Mohri et al., 2018)) Let $S_N = \{\boldsymbol{x}_i, y_i\}_{i=1}^N$ be samples chosen i.i.d. according to the distribution $p(\boldsymbol{x})$. If the loss function ℓ is bounded by $B > 0$. Then for any $\delta \in (0, 1)$, with probability at least $1 - \delta$, the following holds for all $h \in \mathcal{H}$,*

$$E(h) \leq E_{S_N}(h) + 2R_{S_N}(\ell_{\mathcal{H}}) + 3B\sqrt{(\log(2/\delta)/(2N)}.$$

In addition, according to the Ledoux-Talagrand contraction inequality(Maurer, 2016) and assume loss function is L-Lipschitz, we have

$$R_{S_N}(\ell_{\mathcal{H}}) \leq LR_{S_N}(\mathcal{H}).$$

Next, we begin to prove Theorem 3.

Theorem 5. *(Theorem 2.3 in (Mendelson, 2003)) Let $\mathcal{F}$ be a class of functions from $\mathcal{D}$ to $[-1, 1]$ and set p to be a probability measure on $\mathcal{D}$. Let $(\boldsymbol{x}_i)_{i=1}^n$ be independent random variables distributed according to μ. Let (Y, d) be a metric space and set $F \subset Y$. For every $\epsilon > 0$ and any $n \geq 8/\epsilon^2$,*

$$\mathbb{P}\left(\sup_{f \in \mathcal{F}} |\frac{1}{n}\sum_{i=1}^{n} f(\boldsymbol{x}_i) - \int_{\mathcal{D}} f(\boldsymbol{x})\mu(\boldsymbol{x})\mathrm{d}\boldsymbol{x}| > \epsilon\right) \leq 8\mathbb{E}_{\mu}[N(\epsilon/8, \mathcal{F}, L_1(\mu_n))]\exp(-n\epsilon^2/128) \tag{34}$$

In above theorem, $N(\epsilon, \mathcal{F}, L_p(\mu_n)$ denotes the covering numbers of $\mathcal{F}$ at scale ϵ with respect to the $L_p(\mu_n)$ norm. μ_n is the empirical measure supported on one sample of $(\boldsymbol{x}_i)_{i=1}^n$. For every $\epsilon > 0$, denote by $N(\epsilon, \mathcal{F}, d)$ the minimal number of open balls (with respect to the metric d) needed to cover $\mathcal{F}$. That is, the minimal cardinality of the set $\{y_1, \cdots, y_m\} \subset Y$ with the property that every $f \in \mathcal{F}$ has some y_i such that $d(f, y_i) < \epsilon$. The set $\{y_1, \cdots, y_m\}$ is called an ϵ-cover of $\mathcal{F}$. The logarithm of the covering numbers is called the entropy of the set. For every sample $\{\boldsymbol{x}_1, \cdots, \boldsymbol{x}_n\}$ let μ_n be the empirical measure supported on that sample. For $1 \leq p < \infty$ and a function f, $\|f\|_{L_p(\mu_n)} = \left(\frac{1}{n}\sum_{i=1}^n |f(x_i)|^p\right)^{1/p}$ and $\|f\|_\infty = \max_{1 \leq i \leq n} |f(x_i)|$.

Notice that

$$L_1(\mu_n) \leq L_\infty(\mu_n) \leq L_\infty.$$

We get one immediate corollary of Theorem 5.

Corollary 1. *Let $\mathcal{F}$ be a class of functions from $\mathcal{D}$ to $[-1, 1]$ and set $p(\boldsymbol{x})$ to be a probability measure on $\mathcal{D}$. Let $\{\boldsymbol{x}_i\}_{i=1}^N$ be independent random variables distributed according to $p(\boldsymbol{x})$. For every $\epsilon > 0$ and any $n \geq 8/\epsilon^2$,*

$$\mathbb{P}\left(\sup_{f \in \mathcal{F}} |\frac{1}{N}\sum_{i=1}^n f(\boldsymbol{x}_i) - \int_\mathcal{D} f(\boldsymbol{x})p(\boldsymbol{x})\mathrm{d}\boldsymbol{x}| > \epsilon\right) \leq 8N(\epsilon/8, \mathcal{F}, L_\infty)\exp(-N\epsilon^2/128) \qquad (35)$$

where $N(\epsilon, \mathcal{F}, L_\infty)$ be the covering numbers of $\mathcal{F}$ at scale ϵ with respect to the L_∞ norm

Then, we get an upper bound of $\sup_{f \in \mathcal{F}} |\frac{1}{N}\sum_{i=1}^N f(\boldsymbol{x}_i) - \int_\mathcal{D} f(\boldsymbol{x})p(\boldsymbol{x})\mathrm{d}\boldsymbol{x}|$.

Corollary 2. *Let $\mathcal{F}$ be a class of functions from $\mathcal{D}$ to $[-1, 1]$. Let $\{\boldsymbol{x}_i\}_{i=1}^N$ be independent random variables distributed according to p, where p is the probability distribution whose C^1 norm is bounded. Then with probability at least $1 - \delta$,*

$$\sup_{f \in \mathcal{F}} |p(f) - p_N(f)| \leq \sqrt{\frac{128}{N}\left(\ln N(\sqrt{\frac{2}{N}}, \mathcal{F}, L_\infty) + \ln\frac{8}{\delta}\right)},$$

where

$$p(f) = \int_\mathcal{D} f(\boldsymbol{x})p(\boldsymbol{x})\mathrm{d}\boldsymbol{x}, \quad p_N(f) = \frac{1}{N}\sum_{i=1}^N f(\boldsymbol{x}_i). \qquad (36)$$

Proof. Using Corollary 1, with probability at least $1 - \delta$,

$$\sup_{f \in \mathcal{F}} |p(f) - p_N(f)| \leq \epsilon_\delta,$$

where ϵ_δ is determined by

$$\epsilon_\delta = \sqrt{\frac{128}{N}\left(\ln N(\epsilon_\delta/8, \mathcal{F}, L_\infty) + \ln\frac{8}{\delta}\right)}.$$

Obviously,

$$\epsilon_\delta \geq \sqrt{\frac{128}{N}} = 8\sqrt{\frac{2}{N}}$$

which gives that

$$N(\epsilon_\delta/8, \mathcal{F}, L_\infty) \leq N(\sqrt{\frac{2}{N}}, \mathcal{F}, L_\infty)$$

Then, we have

$$\epsilon_\delta \leq \sqrt{\frac{128}{N}\left(\ln N(\sqrt{\frac{2}{N}}, \mathcal{F}, L_\infty) + \ln\frac{8}{\delta}\right)}$$

which proves the corollary. $\qquad \square$

If the entropy bound of $\mathcal{F}$ is known, the upper bound of $\sup_{f \in \mathcal{F}} |p(f) - p_N(f)|$ follows from Corollary 2. Now, the key point left becomes bounding the entropy of some given function class $\mathcal{F}$.

Let us start from the function class $\mathcal{F}$. To apply above corollary, we need to normalize $\mathcal{F}$ to make it lie in $[-1, 1]$. Here we also use $\mathcal{F}$ to denote the normalized function class and absorb the bound of $\mathcal{F}$ into the generic constant C.

According to Taylor formula, we have for any $\boldsymbol{x}, \boldsymbol{z} \in \mathcal{D}$

$$|f(\boldsymbol{x}) - f(\boldsymbol{z})| \leq \sqrt{d} \sup_{f \in \mathcal{F}} \|f\|_{C^1} \|\boldsymbol{x} - \boldsymbol{z}\|_2.$$

Where d is the dimension of $\boldsymbol{x}$. This gives an easy bound of $N(\epsilon, \mathcal{F}, L_\infty)$,

$$N(\epsilon, \mathcal{F}, L_\infty) \leq C \left(\frac{\sup_{f \in \mathcal{F}} \|f\|_{C^1}}{\epsilon} \right)^d \tag{37}$$

Using Corollary 2, with probability at least $1 - 1/(2N)$,

$$\sup_{f \in \mathcal{F}} |p(f) - p_N(f)| \leq \frac{C}{\sqrt{N}} \left(\ln N + \ln(\sup_{f \in \mathcal{F}} \|f\|_{C^1}) + 1 \right)^{1/2} \tag{38}$$

According to the Theorem 2, we can get the following theorem.

Theorem 6. *With probability at least $1 - 1/(2N)$,*

$$\sup_{f \in \mathcal{F}} |p(f) - p_N(f)| \leq \frac{C}{\sqrt{N}} \left(\ln N + \ln c + 1 \right)^{1/2},$$

$$\sup_{f \in \mathcal{G}_\sigma} |p(f) - p_N(f)| \leq \frac{C}{\sqrt{N}} \left(\ln N + \ln c - \sigma^2 + 1 \right)^{1/2}$$

$$p(f) = \int_{\mathcal{D}} f(\boldsymbol{x}) p(\boldsymbol{x}) \mathrm{d}\boldsymbol{x}, \quad p_N(f) = \frac{1}{N} \sum_{\boldsymbol{x}_i \in S_N} f(\boldsymbol{x}_i),$$

$\mathcal{F}$ and $\mathcal{G}_\sigma$ is a function class defined as

$$\mathcal{F} := \left\{ f(\boldsymbol{x}) | \|f\|_{C^1} \leq c \right\},$$

and

$$\mathcal{G}_\sigma := \left\{ g(\boldsymbol{x}) = u(\boldsymbol{x}, 1) | \frac{\partial u(\boldsymbol{x}, t)}{\partial t} = v(\boldsymbol{x}, t) \cdot \nabla u(\boldsymbol{x}, t) + 1/2\sigma^2 \Delta u(\boldsymbol{x}, t), u(\boldsymbol{x}, 0) = f(\boldsymbol{x}) \text{ where } f \in \mathcal{F} \right\}.$$

For the purpose of proving Theorem 3, we give a inequality about Rademacher complexity as following.

Theorem 7. *(Theorem 2.23 in (Mendelson, 2003)) Let $p(\boldsymbol{x})$ be a probability distribution function and set $\mathcal{F}$ to be a class of functions on $\mathcal{D}$. Denote*

$$Z = \sup_{f \in \mathcal{F}} |\frac{1}{N} \sum_{i=1}^{N} f(\boldsymbol{x}_i) - \mathbb{E}_{\boldsymbol{x} \sim p(\boldsymbol{x})}(f)|,$$

where $\{\boldsymbol{x}_i\}_{i=1}^N$ are independent random variables distributed according to $p(\boldsymbol{x})$. Then we have

$$\frac{1}{2} \mathbb{E}_{\boldsymbol{x} \sim p(\boldsymbol{x})} Z \leq R_{S_N}(\mathcal{F}) \leq 2\mathbb{E}_{\boldsymbol{x} \sim p(\boldsymbol{x})} Z + \frac{1}{\sqrt{n}} |\sup_{f \in \mathcal{F}} \mathbb{E}_{\boldsymbol{x} \sim p(\boldsymbol{x})} f|.$$

Then combining Theorem 6, Theorem 7 and using Khinchin inequality, we can easily proof the Theorem 3.

Figure 3: Boundary decision of ResNet trained by our model with different hyper parameters λ and σ^2.

E   MORE EXPERIMENTAL DETAILS ON HALF-MOON DATASET

In this susection, we plot the decision boundary of ResNet trained with different hyperparameters in Figure 3. As drawn in Figure 1, we can see as the hyperparameters λ and σ^2 increasing, the decision boundary becomes more smooth, which implies the overfitting risk reduce. These experiment results are also consistent with the conclusion of Theorem 3.

F   ARCHITECTURES OF THE USED DNNS

Figure 4 shows the architectures of ResNets used in this paper. We also plot the inputs for the ResNet used on CIFAR-10 dataset in Figure 5 and every element of the matrix tt equals to t.

Figure 4: Architectures of the ResNet used in our experiments.

Figure 5: The inputs for the ResNet used in CIFAR-10 dataset.