Curating the Future: A Scalable Recipe for Training Open-Ended Forecasters

Abstract

High-stakes decision making involves reasoning under uncertainty about the future. In this work, we train language models to make predictions on open-ended forecasting questions. To scale up training data, we synthesize novel forecasting questions from global events reported in daily news, using a fully automated, careful curation recipe. We train the Qwen3 thinking models on our dataset, `OpenForesight`. To prevent leakage of future information during training and evaluation, we use an offline news corpus, both for data generation and retrieval in our forecasting system. Guided by a small validation set, we show the benefits of retrieval, and an improved reward function for reinforcement learning (RL). Once we obtain our final forecasting system, we perform held-out testing between May to August 2025. Our specialized model, `OpenForecaster`8B, matches much larger proprietary models, with our training improving the accuracy, calibration, and consistency of predictions. We find calibration improvements from forecasting training generalize across popular benchmarks. We open-source all our models, code, and data to make research on language model forecasting broadly accessible.

1. Introduction

Every day, people navigate decisions under uncertainty, due to incomplete evidence or competing hypotheses. The highest-stakes choices are inherently forward-looking: governments set policy while anticipating macroeconomic and geopolitical shifts; investors allocate capital amid market and regulatory uncertainty; individuals choose careers as technologies evolve; and scientists pursue research directions in search of the next breakthrough. Decades of

Figure 1. **Benefits of scaling training data.** Best Brier score improves as we increase training dataset size (subsets of `OpenForesight`) for Llama-3.1-8B-Instruct.

work (Tetlock et al., 2014) on human forecasting shows that while prediction is hard and skill varies widely, it is possible to train humans to become better forecasters. In fact, some "superforecasters" consistently outperform peers. While there is a ceiling to predictability in social systems (Franklin, 1999), we do not yet know where that ceiling lies in the real world.

If trained at scale for forecasting world events, Large Language Models (LLMs) may enjoy structural advantages over humans: they can ingest and synthesize vast, heterogeneous corpora across thousands of topics; and update predictions rapidly as new information arrives. Just like language models now show superhuman reasoning on some exam-style math and coding problems (OpenAI, 2025), in the future, language model forecasters may be able to come up with possibilities that humans miss. So in this work, we study:

> *How can we train language models to better forecast open-ended questions?*

Scaling training data for forecasting. As forecasting world events is hard for humans, detailed and correct reasoning traces for forecasting are difficult to obtain. Fortunately, recent success in Reinforcement Learning (RL) for language

---

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

models enables training with just the eventual outcome of the question (Guo et al., 2025). Further, the static knowledge cutoff of LLMs enables a unique opportunity: events that resolve after the cutoff are in the future for the model. Even then, sourcing questions at scale for training forecasting abilities has a few key challenges. First, waiting for events to resolve is too slow as a feedback loop for training. Second, prediction markets–the primary source for existing forecasting questions–mostly consist of binary questions. As there is a 50% chance of success on these questions even with incorrect reasoning, they make for noisy rewards.

Instead, we use global news, which covers a large number of salient events every day, to synthesize open-ended forecasting questions like "Who will be confirmed as the new prime minister of Ukraine on 17 July 2025?". Our recipe for creating training data is entirely automated and scalable, with one language model extracting events from news articles to generate questions, and a different model filtering and rewriting questions to avoid leaking future information. For this work, we use this recipe with 250,000 articles up till April 2025, to create `OpenForesight`, a dataset of $\sim$ 50,000 open-ended forecasting questions for training. To grade responses for open-ended questions, we use model-based *answer matching* (Chandak et al., 2025) consistent with frontier benchmarks like Humanity's Last Exam (Phan et al., 2025).

Ensuring we truly improve forecasting. We take extensive measures to avoid the leakage of future information during training and evaluation. First, we do not use online search engines for sourcing news, as they have unreliable date cutoffs due to dynamic updates to documents and search ranking (Paleka et al., 2025a). Instead, we use the CommonCrawl News corpus, which provides static, monthly snapshots of global news. Second, we only train on events until April 2025, which is when the Qwen3 model weights we train were released.

Validating design choices for LLM Forecasting Systems. We start from Qwen3 (Yang et al., 2025) 4B and 8B models with thinking enabled. We perform all ablations on a small validation set. We use dense retrieval with the Qwen3-8B Embedding model to provide forecasters relevant chunks from our offline news corpus. Despite a cautious approach of only retrieving articles until *one month* before the question resolution date to avoid leakage, the retrieved information leads to large improvements. Then, we train language models using RL with GRPO. For the reward function, we propose combining accuracy, and an adaptation of the brier score for open-ended responses (Damani et al., 2025). Ablations show rewarding accuracy alone hurts calibration, while optimizing only the brier score hurts exploration on hard questions. Our final methodology is illustrated in Figure 1.

Final results. In Section 5, we report results on our held-out test set of open-ended forecasting questions from May to August 2025, and FutureX (Zeng et al., 2025), an external forecasting benchmark. RL training on `OpenForesight` makes the predictions of our specialized 8B model competitive with much larger proprietary models in both accuracy and calibration. We also observe large improvements on consistency evaluations for long-term predictions (Paleka et al., 2025b). Finally, we find calibration from our forecasting training generalizes to multiple out of distribution benchmarks.

2. Open-Ended Forecasting

The forecasting task we study is *open-ended* in that it allows arbitrary natural language questions, and does not require a structured outcome set. This differentiates it from both time-series forecasting, and prediction markets dominated by binary or multiple choice questions. We focus on training models to make open-ended predictions like "Which company will the US Government buy a >5% stake in by September 2025?". Such questions require exploration and imagination, rewarding novel hypotheses that turn out to be correct, rather than just distributing probabilities over a known set of outcomes. We discuss related work, our motivation for moving beyond prediction-market questions, and the backtesting setup in Section A.

Setup. Let $\mathcal{X}$ be the set of open-ended forecasting questions; and $\mathcal{Y}$ the set of short textual answers. We provide a language model π_θ a question $x \in \mathcal{X}$, for which we already know the ground-truth outcome $y^\star$ as it has resolved in the real-world. We ask the model to report its best guess prediction y, and the probability q of it being the true outcome.

Measuring Accuracy. We measure accuracy by checking if the model's attempted answer y matches with the ground truth outcome $y^\star$, using another language model to test for semantic equivalence as in recent frontier benchmarks (Wei et al., 2024; Phan et al., 2025). For evaluations, we use Llama-4-Scout (Meta AI, 2025), as in a recent study (Chandak et al., 2025), it was found to have inter-human level of alignment with human judgments. During training, we use Qwen3-4B in non-thinking mode, as it achieves high alignment levels for its size in the same study.

Measuring Calibration. We adapt the multi-class Brier scoring rule (Mucsányi et al., 2023) for free-form responses as follows (details in Section E):

$$S'(q, y, y^*) = \begin{cases} 1 - (q-1)^2, & \text{if } y \equiv y^* \\ -q^2, & \text{if } y \neq y^* \end{cases}$$

Predicting an event with probability $q = 0$ returns a baseline score of 0 regardless of y. Correct predictions receive positive scores while incorrect predictions negative.

For brevity, we call $S'(q, y, y^*)$ *Brier score* throughout this paper. This is equivalent to the reward metric used by Damani et al. (2025), a proper scoring rule incentivizing both accuracy and truthful probability reporting.

Training Algorithm and Initial Policy. We train LLMs with GRPO (Shao et al., 2024) using outcome-based rewards, following the variant of Damani et al. (2025); Turtel et al. (2025b) that drops the group standard-deviation in advantage computation. We start from the Qwen3-8B thinking model (Yang et al., 2025), whose weights were released in April 2025; we train on data up to this date and evaluate on May–August 2025. Further details, and improvements on Llama/Gemma models, are in Section A.3 and Section H.3.

3. Generating Open-Ended Forecasting Questions from News

We now describe our methodology to convert daily news articles into forecasting questions using language models. Any fixed forecasting dataset loses value as newer base models with later training cutoffs are adopted, so we first sketch a general, automated pipeline that can be re-run on fresh news, and then summarise the specific instantiation we used to build OpenForesight (questions until April 2025). The full pipeline figure, per-stage filtering counts, and details of each step are deferred to Section B.

Pipeline. From each news article in the static, monthly CommonCrawl News snapshots (Nagel, 2016), a *sample creator* model proposes up to three forecasting samples consisting of a forward-looking question, background, resolution criteria, a short answer (1–3 words) drawn from the article, and source metadata. A *sample selector* model then verifies that the question is forward-looking, fully resolvable by the article, and has a definite, unambiguous answer. When multiple valid questions remain per article, it picks the best one. Finally, the selector scans the title, background, and resolution criteria for leakage of the answer, rewrites offending spans, and we apply string matching to discard any samples with direct mentions of the answer. We use this recipe to construct train, validation, and test splits, but with *different news sources* to test generalizable forecasting skill.

OpenForesight. For our training set, we apply this pipeline to ∼248,000 deduplicated English articles between June 2023 and April 2025 from *Forbes*, *CNN*, *Hindustan Times*, *Deutsche Welle*, and *Irish Times*, using DeepSeek-v3 as the sample creator and Llama-4-Maverick as the sample selector. Across stages we remove ∼90% of generated samples, yielding a final training set of 52,183 questions, each from a unique article (per-stage breakdown in Table 1). Qwen3-32B, given the source article, answers

these questions with 95% accuracy, confirming high validity. We additionally build a validation set of 207 questions on July 2025 *TheGuardian* articles using the same recipe with o4-mini-high as the higher-quality sample creator. We release OpenForesight to promote research on open-ended forecasting.

Result 1: Filtering Improves Performance. Training Qwen3-8B on 30,000 unfiltered questions actively *hurts* forecasting performance (likely from shortcut learning on leaked answers), while leakage removal alone recovers it; all filtering stages together yield higher accuracy and Brier score with only one-third the data and training steps. We give the per-variant curves and per-stage counts in Section B.1. We also ablate binary vs. free-form training data in Section H.1; the combination performs best, so we use it for our final runs.

Result 2: Continued Improvements from Scaling Training Data. Figure 1 shows that scaling OpenForesight yields continued, large gains in both accuracy and Brier score for Llama-3.1-8B-Instruct, demonstrating the value of our dataset contribution.

4. Prediction System

We now present our forecasting system. All design decisions were made on the validation set, without observing the held-out test set; full reward and retrieval ablations are in Section C.

Reward Design. We compare three reward functions: *(i) only accuracy* $R = \mathbb{1}_{y \equiv y^*}$ (the standard RLVR choice (Guo et al., 2025)), *(ii) only Brier score* $R = S'(q, y, y^*)$ (Damani et al., 2025), and *(iii) accuracy + Brier score* $R = \mathbb{1}_{y \equiv y^*} + S'(q, y, y^*)$ (ours). **Result 3: Accuracy + Brier score reward improves performance.** Accuracy alone leads to poor calibration; Brier alone hurts exploration as the model assigns $q \approx 0$ to "Unknown" in ∼40% of samples since the correctness term then contributes little. Adding the accuracy term boosts exploration on hard, low-confidence questions: "Unknown" rate drops to ∼4% and both accuracy and Brier improve (full curves in Figure 5).

Retrieval. Following prior work (Zou et al., 2022; Halawi et al., 2024), we provide all models the same retrieved news context. To prevent leakage (Paleka et al., 2025a), we use our offline CCNews corpus (1M articles from 60 sources) and only retrieve articles up to *one month* before the question's resolution date. We split articles into 512-token chunks, embed each with Qwen3-Embedding-8B, and retrieve the top-k chunks. Retrieval improves accuracy by 9–18% across model families and sizes; gains plateau after five chunks (Section C.2), so we fix $k = 5$.

Training the final forecasting system. Based on the above, our final methodology is: retrieve the top-5 chunks for each question with the Qwen3-Embedding-8B model from articles up to a month before the resolution date; during training, prepend a random number of these chunks (0–5) to the prompt so the forecaster generalises across context sizes. We train the Qwen3-8B thinking model with GRPO on `OpenForesight` (∼50K free-form questions) augmented with 2,000 binary resolved Metaculus questions from 2024, both with retrieval. The reward is Accuracy + Brier for free-form questions and Brier alone for binary questions.

5. Final Results

We now present evaluations of our model, `OpenForecaster` 8B. To avoid making decisions based on future information, we evaluate on held-out test sets that were not observed until the end. Our primary test set consists of 302 open-ended forecasting questions resolving between May and August 2025, drawn from five news sources distinct from training (Al Jazeera, Time, The Independent, Fox News, NDTV), generated with `o4-mini-high`, filtered for answerability and earliest-resolution-date by `grok-4.1-fast` with search, and finally manually reviewed. We additionally evaluate on FutureX (Zeng et al., 2025), consistency metrics for long-term predictions (Paleka et al., 2025b), and out-of-distribution calibration on SimpleQA, MMLU-Pro, and GPQA-Diamond. Test-set construction details and external-benchmark results are in Section D.

Result 4: Training on our dataset leads to large improvements in forecasting. Figure 2a shows performance on our held-out test set. On Brier score (Y-axis), the primary metric recommended for forecasting (Tetlock & Gardner, 2016) as it measures both accuracy and calibration, `OpenForecaster` 8B outperforms even GPT-OSS 120B. The improvements are not merely from calibration: predictions are also more accurate (X-axis), beating Qwen3-235B though slightly behind a few proprietary models. Training on `OpenForesight` also improves Llama and Gemma models (Section H.3), with a +25% absolute accuracy improvement for Llama-3.1-8B-Instruct, surpassing the much larger Qwen3-235-A22B. On FutureX, our model has the strongest accuracy by a large margin and is close to the best Brier score; we improve consistency by 44% on arbitrage and 19% on frequentist metrics (Sections D.2 and H.4).

Result 5: Calibration training for forecasting generalizes to other domains. Calibration gains transfer to SimpleQA, GPQA-Diamond, and MMLU-Pro (Figure 7a), and can be used to reduce hallucinations via simple confidence-thresholding rules such as `if probability < 0.1, replace prediction with "I do not know"`.

(a) Results on `OpenForesight` May–Aug 2025.

(b) Results on FutureX July–Aug 2025.

Figure 2. **Our forecasting training improves accuracy and calibration** both on our open-ended test set, and the external FutureX benchmark. It makes `OpenForecaster` 8B competitive with much larger models with knowledge cutoffs before May 2025.

6. Conclusion

In this paper, we show how to curate data for *scalable training* of *open-ended forecasting*. The results are promising, an 8B model finetuned on our data becomes competitive with proprietary models like GPT-OSS-120B, DeepSeek-R1, and Grok-3-Mini. Overall, open-ended forecasting, being a challenging and highly valuable task, offers exciting directions to pursue across research communities. By open-sourcing all our artefacts, we hope to spark more research on this important direction.

References

Box, G. E. P. and Jenkins, G. M. *Time Series Analysis: Forecasting and Control*. Holden-Day, San Francisco, revised ed. edition, 1976. ISBN 0816211043.

Chandak, N., Goel, S., Prabhu, A., Hardt, M., and Geiping, J. Answer matching outperforms multiple choice for language model evaluation. *arXiv preprint arXiv:2507.02856*, 2025.

Cowles, A. Can stock market forecasters forecast? *Econometrica*, 1(3):309–324, 1933.

Dai, H., Teehan, R., and Ren, M. Are llms prescient? a continuous evaluation using daily news as the oracle. *arXiv preprint arXiv:2411.08324*, 2024.

Damani, M., Puri, I., Slocum, S., Shenfeld, I., Choshen, L., Kim, Y., and Andreas, J. Beyond binary rewards: Training lms to reason about their uncertainty. *arXiv preprint arXiv:2507.16806*, 2025.

Franklin, U. *The real world of technology*. House of Anansi, 1999.

Grynbaum, M. M. and Mac, R. The times sues openai and microsoft over ai use of copyrighted work. *The New York Times*, 27(1), 2023.

Guan, Y., Peng, H., Wang, X., Hou, L., and Li, J. Openep: Open-ended future event prediction. *arXiv preprint arXiv:2408.06578*, 2024.

Guo, D., Yang, D., Zhang, H., Song, J., Wang, P., Zhu, Q., Xu, R., Zhang, R., Ma, S., Bi, X., et al. Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. *Nature*, 645(8081):633–638, 2025.

Halawi, D., Zhang, F., Yueh-Han, C., and Steinhardt, J. Approaching human-level forecasting with language models. *Advances in Neural Information Processing Systems*, 37: 50426–50468, 2024.

Jain, N., Han, K., Gu, A., Li, W.-D., Yan, F., Zhang, T., Wang, S., Solar-Lezama, A., Sen, K., and Stoica, I. Livecodebench: Holistic and contamination free evaluation of large language models for code. *arXiv preprint arXiv:2403.07974*, 2024.

Jin, W., Khanna, R., Kim, S., Lee, D.-H., Morstatter, F., Galstyan, A., and Ren, X. ForecastQA: A question answering challenge for event forecasting with temporal text data. Association for Computational Linguistics, 2021. URL https://aclanthology.org/2021.acl-long.357/.

Kaplan, J., McCandlish, S., Henighan, T., Brown, T. B., Chess, B., Child, R., Gray, S., Radford, A., Wu, J., and Amodei, D. Scaling laws for neural language models, 2020. URL https://arxiv.org/abs/2001.08361.

Karger, E., Bastani, H., Yueh-Han, C., Jacobs, Z., Halawi, D., Zhang, F., and Tetlock, P. E. Forecastbench: A dynamic benchmark of ai forecasting capabilities. *arXiv preprint arXiv:2409.19839*, 2024.

Lewis, P., Perez, E., Piktus, A., Petroni, F., Karpukhin, V., Goyal, N., Küttler, H., Lewis, M., Yih, W.-t., Rocktäschel, T., et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in neural information processing systems*, 33:9459–9474, 2020.

Longpre, S., Mahari, R., Lee, A., Lund, C., Oderinwale, H., Brannon, W., Saxena, N., Obeng-Marnu, N., South, T., Hunter, C., Klyman, K., Klamm, C., Schoelkopf, H., Singh, N., Cherep, M., Anis, A. M., Dinh, A., Chitongo, C., Yin, D., Sileo, D., Mataciunas, D., Misra, D., Alghamdi, E., Shippole, E., Zhang, J., Materzynska, J., Qian, K., Tiwary, K., Miranda, L., Dey, M., Liang, M., Hamdy, M., Muennighoff, N., Ye, S., Kim, S., Mohanty, S., Gupta, V., Sharma, V., Chien, V. M., Zhou, X., Li, Y., Xiong, C., Villa, L., Biderman, S., Li, H., Ippolito, D., Hooker, S., Kabbara, J., Pentland, S., and Initiative, D. P. Consent in crisis: The rapid decline of the AI data commons. In *Proceedings of the 38th International Conference on Neural Information Processing Systems*, NIPS '24, 2025.

Lu, K. The only important technology is the internet: Why you should care about product-research co-design, and what is the dual of rl? https://kevinlu.ai/the-only-important-technology-is-the-internet, July 2025. Published July 2025. Accessed: 2025-09-19.

Meta AI. Llama-4: Multimodal intelligence. https://ai.meta.com/blog/llama-4-multimodal-intelligence/, 2025.

Mucsányi, B., Kirchhof, M., Nguyen, E., Rubinstein, A., and Oh, S. J. Trustworthy machine learning. *arXiv preprint arXiv:2310.08215*, 2023.

Nagel, S. Common crawl news dataset, 2016. URL https://data.commoncrawl.org/crawl-data/CC-NEWS/index.html.

OpenAI. Openai — icpc world finals 2025. https://worldfinals.icpc.global/2025/openai.html, 2025.

Paleka, D., Goel, S., Geiping, J., and Tramèr, F. Pitfalls in evaluating language model forecasters. *arXiv preprint arXiv:2506.00723*, 2025a.

Paleka, D., Sudhir, A. P., Alvarez, A., Bhat, V., Shen, A., Wang, E., and Tramèr, F. Consistency checks for language model forecasters. In *The Thirteenth International Conference on Learning Representations*, 2025b. URL https://openreview.net/forum?id=r5IXBlTCGc.

Phan, L., Gatti, A., Han, Z., Li, N., Hu, J., Zhang, H., Zhang, C. B. C., Shaaban, M., Ling, J., Shi, S., et al. Humanity's last exam. *arXiv preprint arXiv:2501.14249*, 2025.

Richardson, L. F. *Weather Prediction by Numerical Process*. Cambridge University Press, Cambridge, 1922.

Shao, Z., Wang, P., Zhu, Q., Xu, R., Song, J., Bi, X., Zhang, H., Zhang, M., Li, Y., Wu, Y., et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Tashman, L. J. Out-of-sample tests of forecasting accuracy: an analysis and review. *International Journal of Forecasting*, 16(4):437–450, 2000. doi: 10.1016/S0169-2070(00)00065-0.

Tetlock, P. E. and Gardner, D. *Superforecasting: The art and science of prediction*. Random House, 2016.

Tetlock, P. E., Mellers, B. A., Rohrbaugh, N., and Chen, E. Forecasting tournaments: Tools for increasing transparency and improving the quality of debate. *Current Directions in Psychological Science*, 23(4):290–295, 2014.

Tinbergen, J. *Statistical Testing of Business-Cycle Theories. Part II: Business Cycles in the United States of America, 1919–1932*. League of Nations, Geneva, 1939.

Turtel, B., Franklin, D., and Schoenegger, P. Llms can teach themselves to better predict the future. *arXiv preprint arXiv:2502.05253*, 2025a.

Turtel, B., Franklin, D., Skotheim, K., Hewitt, L., and Schoenegger, P. Outcome-based reinforcement learning to predict the future. *arXiv preprint arXiv:2505.17989*, 2025b.

Wang, Z., Zhou, X., Yang, Y., Ma, B., Wang, L., Dong, R., and Anwar, A. Openforecast: A large-scale open-ended event forecasting dataset. In *Proceedings of the 31st International Conference on Computational Linguistics*, pp. 5273–5294, 2025.

Wei, J., Karina, N., Chung, H. W., Jiao, Y. J., Papay, S., Glaese, A., Schulman, J., and Fedus, W. Measuring short-form factuality in large language models, 2024. URL https://arxiv.org/abs/2411.04368.

Yang, A., Li, A., Yang, B., Zhang, B., Hui, B., Zheng, B., Yu, B., Gao, C., Huang, C., Lv, C., Zheng, C., Liu, D., Zhou, F., Huang, F., Hu, F., Ge, H., Wei, H., Lin, H., Tang, J., Yang, J., Tu, J., Zhang, J., Yang, J., Yang, J., Zhou, J., Zhou, J., Lin, J., Dang, K., Bao, K., Yang, K., Yu, L., Deng, L., Li, M., Xue, M., Li, M., Zhang, P., Wang, P., Zhu, Q., Men, R., Gao, R., Liu, S., Luo, S., Li, T., Tang, T., Yin, W., Ren, X., Wang, X., Zhang, X., Ren, X., Fan, Y., Su, Y., Zhang, Y., Zhang, Y., Wan, Y., Liu, Y., Wang, Z., Cui, Z., Zhang, Z., Zhou, Z., and Qiu, Z. Qwen3 technical report, 2025. URL https://arxiv.org/abs/2505.09388.

Zeng, Z., Liu, J., Chen, S., He, T., Liao, Y., Wang, J., Wang, Z., Yang, Y., Yin, L., Yin, M., et al. Futurex: An advanced live benchmark for llm agents in future prediction. *arXiv preprint arXiv:2508.11987*, 2025.

Zou, A., Xiao, T., Jia, R., Kwon, J., Mazeika, M., Li, R., Song, D., Steinhardt, J., Evans, O., and Hendrycks, D. Forecasting future world events with neural networks. *Advances in Neural Information Processing Systems*, 35:27293–27305, 2022.

Appendix

Appendix Contents

A. Extended Related Work and Setup

A.1. Related Work

Forecasting World Events. Much prior work in Machine Learning and Statistics has focused on forecasting numeric or time-series data (Box & Jenkins, 1976) in diverse domains like weather (Richardson, 1922), econometrics (Tinbergen, 1939) or finance (Cowles, 1933). Instead, our work focuses on the prediction of discrete world events, with both questions and answers described in natural language, also called *judgemental forecasting* (Tetlock & Gardner, 2016). In the rest of our paper, we refer to this as *forecasting* for brevity. In prior work on evaluating language models for forecasting (Zou et al., 2022; Karger et al., 2024), questions are primarily sourced from prediction markets like Metaculus, Manifold, and Polymarket. Prediction markets provide a platform for online participants to register predictions on questions like "Will Donald Trump win the US Presidential Election in 2024?", which mostly have binary, yes or no, outcomes and have rapidly grown in popularity over the last few years.

Evaluating LLMs for Forecasting. New information (before the event resolves) benefits forecasting. Thus, LLM forecasting work (Zou et al., 2022; Halawi et al., 2024) provides relevant retrieved articles to models (Lewis et al., 2020) often obtained via web-search APIs. Paleka et al. (2025a) discuss pitfalls of LLM forecasting evaluations, including leakage of outcomes from online search in backtests, and distributional biases of prediction market questions. To avoid these issues, we use static, monthly snapshots of global news for retrieval and creating questions. Jin et al. (2021) ask humans to create forecasting questions, while Dai et al. (2024) try to automate this process with LLMs. However, their questions pre-define a few outcomes to choose from. Guan et al. (2024); Wang et al. (2025) evaluate models on open-ended forecasts, but we go a step further by showing how to train models for this task.

Reinforcement Learning for LLMs. Shao et al. (2024) proposed *Group Relative Policy Optimization* (GRPO), an RL algorithm that only uses outcome rewards. This approach has been highly successful in training LLMs to *reason* about well-specified coding (Jain et al., 2024) and exam-style questions across domains (Phan et al., 2025). Instead, forecasting requires LLMs to reason about uncertainty. Halawi et al. (2024) proposed training language models for forecasting by Supervised Finetuning (SFT) on chain of thought traces that lead to brier scores better than the prediction market aggregate. In the same setting of binary forecasting questions, Turtel et al. (2025a) optimize brier scores using GRPO, while Damani et al. (2025) extend it to short answer questions in other domains. We depart from these works in showing how to synthesise large-scale forecasting training data from daily news, to train models at open-ended reasoning about the future.

A.2. Open-Ended Forecasting: Motivation and Background

Motivation. The forecasting task we study is *open-ended* in two key ways:

1. It allows expressing arbitrary natural language forecasting questions

2. It may not have a structured outcome set, unlike numeric or categorical predictions. This differentiates it from both time-series forecasting, and prediction markets.

For example, prediction markets are dominated by binary (yes/no) or multiple choice questions. While this design is easy to score, the most foresight often lies in predicting the unexpected, or when a large number of possibilities could occur. The most important questions to forecast—such as scientific breakthroughs, geopolitical shocks, or technological disruptions—often emerge as *unknown unknowns*: possibilities not anticipated, and hard to enumerate. Thus, in this work, we focus on training models to make open-ended predictions like "Which company will the US Government buy a >5% stake in by September 2025?". Such questions require exploration and imagination, rewarding novel hypotheses that turn out to be correct, rather than just distributing probabilities over a known set of outcomes.

Background. LLM weights are frozen after training, especially for open-weight models. Any event that happens after the last date in the training corpus is in the future for the LLM. This provides a time window to collect questions for training models to reason about future events. Similarly, their evaluation involves testing on questions resolving after the cutoff date of the training data, called *backtesting* (Tashman, 2000). While prior work has relied on prediction market questions as training data, this has three key problems:

1. The questions are created by humans, which makes them low in number (Paleka et al., 2025a). This becomes a

bottleneck for scaling training data, which has been an essential component in the success of LLMs (Kaplan et al., 2020; Lu, 2025).

2. Most questions have binary outcomes, which creates a 50% baseline success rate. This leads to noisy rewards in outcome-based RL, which means even incorrect reasoning has a high chance of being reinforced.

3. Each platform has a skewed distribution of events. All overrepresent US political news, along with their specific focus such as crypto-currency price movements in Polymarket, technology in Metaculus, personal life of users in Manifold, and sports events on Kalshi (Paleka et al., 2025a).

These limitations motivate us to explore alternate ways to create forecasting questions.

A.3. Training Algorithm and Initial Policy

Training Algorithm: GRPO (Shao et al., 2024). We train LLMs using outcome-based reinforcement learning on our dataset. For each prompt x, we draw K completions $\{(y_i, p_i)\}_{i=1}^{K} \sim \pi_\theta(\cdot \mid x)$ and compute rewards $r_i = R(y_i, p_i; y^\star)$. However, following prior work (Damani et al., 2025; Turtel et al., 2025b), we do not divide by *remove* the group standard deviation when computing advantages, as this stabilizes updates in settings like ours where reward variance can be small.

Initial Policy: Qwen3 Thinking (Yang et al., 2025). We start with the 8B thinking model. For Qwen3 models, no official knowledge–cutoff date is reported. When queried directly, the models return inconsistent cutoff dates (most often *October 2023* or *June 2024*). Usually, they treat questions about 2024 as being in the future. Since the model weights were released and frozen in April 2025, we train up to this date, and use the period between May to August 2025 for testing. In the Appendix, we show large improvements from our training on even the Llama and Gemma models in Section H.3.

Figure 3. **Our question generation methodology.** We use DeepSeek-v3 to generate multiple forecasting questions per news article. Then, we use Llama-4-Maverick to check if questions follow all guidelines, choose the best question, and remove any hints revealing the answer.

B. Question Generation Pipeline: Detailed Methodology

We generate short-answer, open-ended forecasting questions from individual news articles as illustrated in Figure 3. We describe each step in detail below:

Sourcing Event Information. News outlets establish global infrastructure for reporting salient events as they occur. Unfortunately, Paleka et al. (2025a) show that sourcing news via online search engines is unreliable. While search engines provide date cutoffs, future information can leak through updates to articles after the publish date, and even search engine ranking. This compromises the reliablity of backtests, and leaks future information in training, which can hurt Deep Learning models that easily overfit to spurious correlations. Fortunately, the CommonCrawl News (CCNews) Corpus (Nagel, 2016) provides static monthly snapshots of global news with accurate dates. This makes it free and easy to obtain news articles for creating forecasting questions.

Generating samples from documents. Based on each news article, we ask a *sample creator* model to generate up to three diverse forecasting samples. Each sample consists of:

1. **Question:** Asks about the prediction of an event.

2. **Background:** Provides brief context, and defines uncommon terms.

3. **Resolution criteria:** Fixes a source of truth, proposes a resolution date for the question, and the expected answer format.

4. **Answer:** Drawn verbatim from the article, unique, short (usually 1–3 words), and non-numeric (usually a name or location).

5. **Source article link:** Obtained from article metadata for future reference.

A challenging issue we face is that sometimes news articles talk about past events, or report an event late. This is why we ask the sample creator to propose a resolution date, and set the final resolution date as $\min\left(\texttt{model\_generated\_date},\right.$ $\left.\texttt{article\_publish\_date}\right)$. We perform additional steps, including manual review, to address this issue for evaluation questions, as described later in Section 5. For training data, we do not add more complex steps to fix resolution dates due to cost constraints.

Filtering samples. For each question, we use another LLM, *the sample selector*, to verify:

1. The question-answer pair is fully based on information in the source article.

2. The question is forward-looking, for e.g. it is in future tense

Figure 4. **Benefits of our filtering stage.** Without leakage removal (red), the model worsens at forecasting, possibly learning shortcuts. With only the leakage removal step (blue), we find that achieving the same performance requires $3\times$ more compute and data. Applying all filtering steps (green) leads to higher accuracy.

   3. The answer is definite, unambiguous, and resolvable by the publication date.

We mark a question as valid only if it passes these checks. If multiple questions from a single article remain, we ask the sample selector to pick the best one, favoring questions with clear, unique answers and high relevance. This is to ensure data diversity, and enhance quality.

Editing to fix leakage. At this stage, we find that even the filtered samples sometimes leak information about the answer. This can create shortcuts during training. To fix this, we do a final editing stage where we ask the sample selector to scan the title, background, and resolution criteria to check if they reveal the answer. When it finds leakage, we ask it to rewrite only the offending spans, replacing specifics with generic placeholders. Finally, we re-scan using exact string matching any remaining mentions of the answer, and discard those samples.

Overall, this pipeline can continually ingest news articles and generate open-ended forecasting questions. We use the same methodology to create train, validation and test splits, but use *different news sources* to check if our model learns generalizable forecasting skills.

Table 1. Number of questions after each filtering stage.

Stage	Number (% Total)
Source Articles	248,321
Question Generation	744,963 (100%)
Validation	295,274 (40%)
Best Question Selection	157,260 (21%)
Fixing Leakage	150,500 (20%)
Answer Type Filtering	62,279 (8%)
Resolving after 2024-01-01	52,183 (7%)
Final Set	52,183 (7%)

B.1. `OpenForesight`: Detailed Composition

We now describe the specific composition of our training dataset. We use DeepSeek v3 as the sample creator and Llama-4-Maverick as the sample selector, with prompts in Section K.

Generating samples. One practical issue we face is that many top news sources, such as The Reuters and Associated Press (AP), have disallowed scraping even for CommonCrawl, due to the rise of commercial use in language model training (Grynbaum & Mac, 2023; Longpre et al., 2025). Still, we are able to collect articles from popular outlets spanning diverse geographies and topics.

Particularly, for our training set, we start with $\sim 248,000$ deduplicated English-language articles between June 2023 to April 2025 from *Forbes*, *CNN*, *Hindustan Times*, *Deutsche Welle*, and *Irish Times*. The distribution is described in Figure 9. From each article, the sample creator produces three forecasting samples, yielding $\sim 745,000$ samples.

Filtering samples. Table 1 contains a breakdown of questions remaining after each filtering stage. 60% of question-answer candidates are marked invalid — most commonly because the article does not unambiguously resolve the question to the given answer. At this stage, zero questions remain from 40% articles, and 21% articles yield exactly one valid question, which we keep as is. For the 39% with multiple valid questions, the sample selector picks the best one. Finally, to avoid vague or numeric answers, we only keep questions with specific types (listed in Table 3).

Editing to fix leakage. Despite explicit prompts to avoid it, over 40% of selected questions directly contain the answer string. The sample selector's rewriting and rejection removes ~90% of such cases. We apply a string matching filter to remove the remaining questions with such direct leakage and finally keep only those questions which resolve after January 1, 2024.

Validation Set. We use the same recipe to create a validation set of 207 questions using 500 randomly sampled articles from TheGuardian in the month of July 2025. To ensure high-quality, we used `o4-mini-high`, a much more capable model than DeepSeek-v3, to generate the seed questions. It is $\sim 10\times$ costlier, but followed the generation guidelines better, leading to $\sim 40\%$ retention rate (207 final questions out of 500 starting articles) compared to the original 7%.

Result 1: Filtering Improves Performance. Table 1 shows the effect of our filtering steps. We train Qwen3-8B using RL with identical hyperparameters on three data variants: (red) 30,000 original generated questions, without any filtering; (blue) 30,000 samples obtained after the question editing step to remove leakage; and (green) 10,000 samples sourced from Forbes and included in `OpenForesight`. First, we observe the drastic impact of leakage in training. Training without leakage removal (red) worsens the model, perhaps due to shortcut learning. After the leakage removal steps, training improves the model (blue line). Yet, using all filtering stages (green line) leads to both higher accuracy and Brier score, in one-third the data and training steps.

In Section H.1, we also ablate the effect of training on binary-only, free-form-only, and combined binary and free-form data for `Qwen3-8B`. We find that free-form data is crucial for improving open-ended forecasting, however, training solely on freeform data does not improve performance on binary Metaculus questions. Training with both kind of questions achieves the best trade-off, so we use this for our final training runs presented in Section 5.

Final training dataset. Across stages, we remove $\sim 90\%$ of questions, yielding a training set of 52K samples, each drawn

from a unique article. We evaluated Qwen3-32B on this corpus while providing it the source article alongside the generated questions. The model achieves 95% accuracy confirming high validity. We release this training dataset, `OpenForesight`, to promote research on open-ended forecasting.

Result 2: Continued Improvements from Scaling Training Data. Figure 1 shows the effect of scaling training dataset size. For each dataset size, we report test set (described later) results from the best validation checkpoint over prolonged training runs. We use Llama-3.1-8B-Instruct as it starts without any RL post-training. We see continued, and large gains in both accuracy and Brier score as we continue to scale up the training data, demonstrating the importance of our contribution in releasing `OpenForesight`.

Figure 5. **Accuracy + Brier score reward performs the best.** Accuracy alone leads to poor calibration. While brier score incentivizes both correct predictions and calibration, on hard questions with low confidence, it provides little signal on correctness. Adding the accuracy term boosts exploration in this situation.

C. Prediction System: Reward and Retrieval Ablations

C.1. Reward Design

For training with RL, we compare three reward functions:

1. **Only Accuracy** *(Baseline):* $R = \mathbb{1}_{y \equiv y^*}$. Vanilla success rewards are commonly used in literature on LLM RL with verifiable rewards (Guo et al., 2025).

2. **Only Brier score** *(Damani et al. (2025)):* $R = S'(q, y, y^*) = -q^2 + \mathbb{1}_{y \equiv y^*} \cdot 2q$. This incentivizes both correct predictions and calibrated confidence estimates.

3. **Accuracy + Brier score** *(Ours):* $R = \mathbb{1}_{y \equiv y^*} + S'(q, y, y^*)$. We hypothesise optimizing the Brier score alone hurts exploration as when the model assigns a low confidence to its prediction, the correctness has a small impact on the Brier score. To fix this, we propose adding the accuracy term as well. In this case, even on hard questions, which merit low confidence, models get a large boost for correct predictions.

Result 3: Accuracy + Brier score as the reward improves performance. Figure 5 shows the validation set results of training with all three reward functions on the full `OpenForesight` dataset. We observe that optimizing accuracy alone (blue line) leads to negative brier scores, worse than a constant (0) baseline. In contrast, optimizing the Brier score alone (red line) also improves the accuracy, but to a lesser extent. Our proposed reward, accuracy + Brier (purple line), leads to the best performance on both metrics. It improves accuracy beyond the Brier alone while maintaining equal brier score on the validation set. Analyzing output distributions, we find that the brier-only trained model predicts "Unknown" with near-0 confidence in $\sim 40\%$ of samples, due to low reward for correct yet low-confidence guesses, which hurts exploration. In contrast, our proposed reward yields "Unknown" in only $\sim 4\%$ of samples, making low-confidence guesses on hard cases—improving both accuracy and Brier score.

C.2. Retrieval Ablations

Retrieval leads to large improvements in accuracy. As shown in Section C.2, providing retrieved information improves accuracy by $9 - 18\%$ across model families and sizes. In Appendix Figure 13, we vary the number of retrieved chunks and find that improvements plateau after five chunks. Thus, we fix $k = 5$ chunks for all evaluations henceforth.

Figure 6. **Retrieval improves accuracy across models.** We use the specialized Qwen3 8B embedding model to retrieve the 5 most relevant chunks (512 tokens) for each question. We take a cautious approach, using articles only until a month before the resolution date.

D. Final Results: Extended Evaluations

D.1. Test Set Construction Details

Open-ended Test Set. Given the lack of *open-ended* forecasting benchmarks that are still "in the future" for our models, we create our own test set with additional steps to ensure high quality. We first use our data creation recipe to generate an initial set of 1,000 questions between May to August 2025 using a stronger model, `o4-mini-high`. We draw from five diverse news sources: Al Jazeera English (global news, based out of Qatar), Time (global news, based out of USA) The Independent (UK focused), Fox News (USA focused), NDTV (India focused), with 200 questions selected from each. The choice of sources was made under the constraint of many established news sources have disallowed crawling of their articles starting 2025. We deliberately use distinct sources from the training set to ensure that our model is learning generalizable forecasting skills, and not source distribution specific biases. Beginning from this initial set of 1000 questions, we perform additional filtering steps to prepare a high-quality test set:

1. We remove any potentially unanswerable questions (noise) by keeping only those which `grok-4.1-fast` could successfully answer with search tool access (85%).

2. To address the issue of late reporting in news outlets, we again use `grok-4.1-fast` with search tool to find the **earliest resolution date** for a given question. This is important to prevent leakage from retrieving articles with the true answer. We retain only those questions with resolution date after May 2025 (64%).

3. Finally, we manually filter the remaining questions to meet our quality checks, resulting in a final test set of 302 questions. We provide more details like news source specific statistics in Section G.1.

External Datasets. We use the FutureX benchmark (Zeng et al., 2025), filtering to non-numeric, English, resolved forecasting questions and evaluating all models with our retrieval. This leaves 86 binary or multiple choice questions, between July to August 2025. For evaluating long-term predictions (without retrieval), we measure consistency metrics on binary questions up to 2028 as proposed by Paleka et al. (2025b), who show they correlate strongly with forecasting performance. Finally, to measure whether our forecasting training generalizes to calibration on standard benchmarks of LLM capabilities, we evaluate without retrieval on a challenging factuality benchmark, SimpleQA (Wei et al., 2024), and popular cross-domain reasoning benchmarks, MMLU-Pro and GPQA-Diamond.

D.2. Detailed Results on External Benchmarks

On FutureX, our model has the strongest accuracy by a large margin, even compared to much larger proprietary counterparts. It is close to the best for Brier score as well. Finally, our training leads to more consistent long-term predictions, improving 44% on arbitrage metrics, and 19% on frequentist metrics, with detailed results in Section H.4. Our model also improves on questions from Metaculus prediction market albeit staying behind few larger models which we show in Section H.2.

Result 5: Calibration training for forecasting generalizes to other domains. Figure 7a shows downstream improvements in calibration across SimpleQA, GPQA-Diamond and MMLU-Pro. This calibration can then be used to reduce hallucinations, for example abstaining on questions the model is not confident about, using simple rules like `if probability < 0.1, replace prediction with "I do not know"`.

E. Adapting Brier Score to free-form responses

Let $\mathcal{X}$ be the set of open-ended forecasting questions; and $\mathcal{Y}$ the set of short textual answers. Let $x \in \mathcal{X}$ be a resolved forecasting question and $y^\star$ be the ground truth answer (as the question has already resolved. We ask the forecaster to respond with its best guess answer y, and the probability q they assign to that being the true outcome. We evaluate this prediction tuple <y, q> using the Brier score (Mucsányi et al., 2023) but adapt it to our setting. For a K-class outcome space $\mathcal{Y}$ with reported distribution q and true class y^*, the (multi-class) Brier score is

$$S(q, k) = -\sum_{y \in \mathcal{Y}} (q_y - k_y)^2 = -(q_{y^*} - 1)^2 - \sum_{y \neq y^*} q_y^2,$$

where k is one-hot encoding with $k_{y^*} = 1$. In our open-ended setting, $\mathcal{Y}$ is not predefined but rather its instances are provided by the forecaster. For simplicity, we elicit only a **single guess** y with probability $q \in [0, 1]$ and assume the

(a) Brier score on general benchmarks.

(b) Calibration curve on our test set.

Figure 7. Calibration of the models improve significantly after training on `OpenForesight` both on (a) out of distribution benchmarks, and (b) on `OpenForesight` test set.

forecaster's probability is 0 for all other (semantically different) answers $y' \neq y$.[1] Applying the multi-class brier scoring rule in such a case induces a simplified score:

$$S(q, y, y^*) = \begin{cases} -(q-1)^2 - 0 = -1 + 2q - q^2, & \text{if } y \equiv y^*, \\ -(0-1)^2 - q^2 = -1 - q^2, & \text{if } y \neq y^*. \end{cases}$$

Dropping the constant -1 yields

$$S'(q, y, y^*) = \begin{cases} 1 - (q-1)^2, & \text{if } y \equiv y^*, \\ -q^2, & \text{if } y \neq y^*, \end{cases}$$

which shifts the range from $[-2, 0]$ to $[-1, 1]$ while providing a more natural interpretation: predicting $q = 0$ gives a baseline 0 regardless of y; correct answers receive positive scores, incorrect answers negative scores; and magnitude scales quadratically with confidence. We report S' (visualized in Figure 8) as the *Brier score* in this paper.

Figure 8. Illustration of the brier score when adapted to free-form response with answer y and probability q.

Recent work by Damani et al. (2025) shows that this metric is a proper scoring rule, incentivizing both high accuracy and truthful reporting of probability on the answer that seems most likely. However, note that what we call as brier score here is distinct from the brier score considered by Damani et al. (2025). Their brier score is the one traditionally used for evaluating binary outcomes while ours is for free-form responses. Yet, we can show that our brier score is *same* as the **training reward** considered by them.

---

[1]This is technically incorrect to assume as the forecaster may have non-zero probability for guesses other than y. Ideally the forecaster should report all its guesses which have non-zero probability (with the multi-class brier scoring rule still being applicable) but we leave exploring this direction for future work.

F. Analyzing `OpenForesight` Dataset

News Corpus Details. We drew from a heterogeneous pool of news articles diversified by geography, time, and topic to ensure broad coverage. We collected a English-language articles from outlets including Forbes, Hindustan Times, The Irish Times, Deutsche Welle, and CNN. They were selected by first collecting a corpus of approximately 250,000 articles spanning from June 2023 to April 2025, encompassing major large-scale events across sports, geopolitics, local news, crime, entertainment, and the arts. Then, performing de-duplication and filtering for language, text availability, and valid dates, we retained approximately 248,000 articles for the question generation phase. Table 2 details the distribution across news outlets for our corpus.

Table 2. Breakdown of source news articles by news outlet.

Source	Articles (%Total)
Forbes	110,103 (44.3%)
The Hindustan Times	80,000 (32.2%)
The Irish Times	29,546 (11.9%)
Deutsche Welle (DW)	21,317 (8.6%)
Cable News Net (CNN)	7,355 (3.0%)
Total	**248,321 (100%)**

Sample Generated Forecasting Question

Question. Who will be confirmed as the new prime minister of Ukraine by 17 July 2025?

Background. Ukraine's parliament is scheduled to vote to appoint a new prime minister.

Resolution Criteria.

- **Source of Truth:** Official announcement from the Verkhovna Rada (Ukraine's parliament) confirming the appointment, via parliamentary records or government press release.

- **Resolution Date:** 17 July 2025, the date on which the parliamentary vote occurs and results are published.

- **Accepted Answer Format:** Full name of the individual exactly as given in the parliamentary announcement.

Answer Type. String (Name)

Ground-Truth Answer. Yulia Svyrydenko

Source. The Guardian (live blog): Ukraine live updates — 17 July 2025

F.1. Analysis of Best Question Selection

Figure 9. **Data Distribution of Questions in** `OpenForesight`. (Left) Distribution of number of questions selected after filtering from articles (Right) We show the number of questions generated, and the proportion of the first, second and third generate question being picked as the final "best question".

As Figure 9 (left) illustrates, the generation process yielded mixed results. Post-processing, 39% of source articles failed to produce any valid questions. Among the surviving articles, 21% yielded exactly one valid question, which we retained. For the 61% of articles producing multiple valid questions, we employed another LLM to identify the best candidate based on global relevance, specificity, and unambiguity. Our analysis of selected questions, shown in Table 9 (right) reveals a selection bias:

- Question 1: Selected 43.6% of the time (10.3% above random).

- Question 2: Selected 31% of the time (2.4% below random).

- Question 3: Selected 26.7% of the time (6.7% below random).

This trend suggests that initial generation attempts (question positioned earlier) frequently produce higher-quality results. Figure 4 provides qualitative examples of these generated questions.

	Name(s)	Location	Country	Title	Team name	Color	Organization	Currency	Brand name	Month
Count	32,213	14,337	2,579	2,479	1,445	1,047	1,030	877	779	730
Share	44.8%	20.0%	3.6%	3.5%	2.0%	1.5%	1.4%	1.2%	1.1%	1.0%

Table 3. Top ten answer types of the questions in our curated dataset. These ten categories cover 80.1% of our training dataset.

F.2. Distribution of Answer Types

Table 3 categorizes the answer types within the training data. Two categories dominate the dataset:

- People and Places (65%): Names of individuals constitute nearly 45% of the answers, while locations account for 20%.

- Miscellaneous Entities (35%): The remainder consists of teams, countries, organizations, colors, and similar entities.

Question	Background	Resolution (trigger & deadline)	Answer Type	Answer	Source
Host country of COP30 (Nov 2025)?	UNFCCC COP venue rotates among regions.	Host confirmed by UNFCCC/organizers; no later than COP30 start (Nov 2025).	string (country)	Brazil	DW: link
Release month of Marvel's *Fantastic Four* (2025)?	Reboot announced with lead cast; 2025 release slated.	Month confirmed by Marvel/Disney; by Dec 2025.	string (month)	July	Forbes: link
First state to require Ten Commandments in public classrooms (by 2025)?	Several U.S. states advance religion-in-school measures.	First state enacts requirement; by Dec 31, 2025.	string (state name)	Louisiana	Forbes: link
African host of G20 Summit (Nov 2025)?	G20 presidency rotates; South Africa presiding from Dec 2024.	G20/host government confirms location; by Nov 2025.	string (country)	South Africa	DW: link
Recipient of Lesotho–Botswana Transfer Scheme (by 2025)?	Regional pipeline to pump water from Lesotho via SA.	ORASECOM or governments confirm recipient; by 2025.	string (country name)	Botswana	DW: link

Table 4. Five succinct forecasting questions spanning climate, entertainment, law, geopolitics, and infrastructure; selected for brevity and diverse sources (DW, Forbes). Each row lists the question (summarized here for conciseness), short background, resolution trigger with deadline, answer type, ground-truth answer, and citation.

G. Qualitative Analysis of Final Answers

We manually annotated responses to 207 questions by both the initial Qwen3-8B thinking model and the trained `OpenForecaster`8B on the Guardian validation set. Using this set, we found that the agreement between the two models used for grading, Llama 4 Scout and Qwen3 4B is $\sim 97\%$, and we agree with their grading in over $\sim 95\%$ cases. This confirms the reliability of automatic answer matching based evaluation.

In Table 5, we analyze the domains (by news section) in which our trained model improves. We find significant improvements in the World, Australian, and US news sections, with no significant change for sports. This entails our model may not yet perform too well on sports-heavy prediction markets like Kalshi.

Domain	n	Before	After	Δ
world	20	21.7	33.3	+11.6
australia-news	15	35.6	42.2	+6.7
us-news	21	41.3	44.4	+3.2
sport	37	43.2	43.2	+0.0
football	30	34.4	33.3	-1.1

Table 5. Avg@3 by domain (n $\geq$ 10).

In Table 6, we analyze change in performance by question type, finding significant improvements on questions of the form "what", "which", and "who", while a slight regression in performance on location questions ("where").

Question form	n	Before	After	Δ
what	25	14.7	29.3	+14.7
which	98	45.2	51.4	+6.1
who	60	27.8	33.9	+6.1
other	10	40.0	43.3	+3.3
where	14	47.6	45.2	-2.4

Table 6. Avg@3 by question form (n $\geq$ 10).

Below, we present qualitative examples where our training improves and worsens predictions compared to the original model.

Qualitative examples (improved; first sample)

- **Q:** Who will be wearing the yellow jersey in the general classification at the end of stage eight of the 2025 Tour de France?
  Truth: Tadej Pogačar
  Before: Jonas Vingegaard (p=0.10)
  After: Tadej Pogačar (p=0.60)

- **Q:** Who will withhold a resolution from the U.S. House floor to force a vote on releasing the Epstein documents by July 25, 2025?
  Truth: Mike Johnson
  Before: Pam Bondi (p=0.30)
  After: Mike Johnson (p=0.60)

- **Q:** Which former Bank of England governor will be named in a Guardian piece criticizing 'moral hazards' for banks during the 2007–08 financial crisis?
  Truth: Mervyn King
  Before: Andrew Bailey (p=0.30)
  After: Mervyn King (p=0.40)

- **Q:** Which major tournament will the US women's national team focus on challenging for after the 2025 summer friendlies?

Truth: 2027 World Cup
Before: 2025 European Championship (p=0.95)
After: 2027 Women's World Cup (p=0.40)

Qualitative examples (regressed; first sample)

- **Q:** Which agency will drivers in Northern Ireland apply to for a replacement driving licence by 31 July 2025?
  Truth: DVA
  Before: DVLA (p=0.70)
  After: DVLA (p=0.20)

- **Q:** Where could Sweden's Euro 2025 journey conclude with a historic night if they continue to win?
  Truth: Basel
  Before: Basel (p=0.70)
  After: Zurich (p=0.40)

- **Q:** Who will be the Democratic Party's nominee for New York City mayor in the November 2025 general election?
  Truth: Zohran Mamdani
  Before: Zohran Mamdani (p=0.60)
  After: Andrew Cuomo (p=0.40)

- **Q:** Who will post the lowest first-round score among Rory McIlroy, Scottie Scheffler and Viktor Hovland at the 2025 Scottish Open?
  Truth: Viktor Hovland
  Before: Viktor Hovland (p=0.60)
  After: Scottie Scheffler (p=0.40)

G.1. Test Set

For the test set, we manual filtered of the remaining questions if the question did not satisfy validity criteria like: 1) having multiple answers 2) question actually resolves in the future (after September 2025) for which article reports the scheduled/planned place/event/etc. 3) question being irrelevant because it is too niche to a certain place or locality 4) question is about something which is already established (known).

(a) Manual filter pass rate per news source.

(b) Proportion of questions with correct resolution date upon generation per news source.

Figure 10. Filtering pass rate of forecasting questions across news sources.

H. Additional Results

H.1. Ablation: Using Prediction Market Binary Data

(a) Performance on our **Validation Set** composed of question from TheGuardian new source from July 2025.

(b) Performance on **Metaculus binary** questions resolved in May–July 2025.

Figure 11. **Performance of different data ablations.** We evaluate performance after training on 3 different supervision signals: (i) only binary data (20K samples), (ii) only freeform data (20K samples), and (iii) both binary and freeform data (10K samples each) for data-matched comparison. (a) Accuracy and freeform Brier score of the initial and post-RL model on our Validation Set from July 2025. (b) Accuracy and binary Brier score of initial and post-RL model on volume-filtered binary questions resolved between May to July 2025 on Metaculus. *We find training on binary questions hurts performance on open-ended forecasting, but is necessary to retain performance on binary prediction market questions.*

We ablate supervision type with `Qwen3-8B` using three size-matched settings (Figure 11). For *binary-only*, we curate **20K** resolved markets from Manifold, volume-filtered to ensure engagement; because many markets resolve slowly, this set spans the past five years. For *free-form only*, we use **20K** pipeline-generated, usable questions from Forbes articles. For the *binary+free-form mix*, we take **10K** Manifold + **10K** Forbes questions to keep total examples constant. The goal is to isolate which *learning signal*—binary resolution vs. open-ended outcome specification—most effectively trains calibrated forecasters under identical compute and token budgets.

On the free-form test set (Fig. 11 Left), post-RL performance improves most with *free-form only* supervision (Accuracy 19.3% → 22.4%; Free-form Brier −0.009 → 0.086). Mixing binary and free-form also helps (Brier 0.065), whereas *binary-only* yields minimal gains on free-form evaluation (Brier 0.004). On Metaculus (binary) (Fig. 11 Right), both

binary-only and the *mixed* setting improve accuracy and Brier, with the *binary+free-form* mix offering the best overall trade-off across testing formats. Our gains by training on binary-only format are consistent with prior work by Turtel et al. (2025b;a). However, we do not arrive at a single unanimous recipe: free-form data is essential for open-ended forecasting, while combining formats appears Pareto-optimal across binary and free-form evaluations. Practically, it seems training on a *mixture* of question styles provides the most robust gains across tasks.

H.2. Evaluation on Metaculus Questions

Prediction Market Dataset. We also source questions from the Metaculus prediction market from May - Nov. 2025. We filter questions which are either meta-prediction questions (prediction about some other prediction question on Metaculus), stock price prediction or below a certain trading volume leaving 449 high-interest questions. Each question is binary so a naive baseline gets 50% accuracy. We evaluate models on this benchmark by computing both accuracy and brier score.

Results on Real Market Questions. As shown in Figure 12, `OpenForecaster` 8B performs better than many larger models like DeepSeek-R1 and Llama-4-Maverick while GPT-OSS-120B is significantly better than rest of the models. **Note:** The brier score reported here is the *standard brier score* used in prediction markets ranging from -1 to 0 (with -0.25 being the baseline for a constant prediction of 50%) and this is different from the brier score we have reported earlier for freeform questions.

Figure 12. Performance of models on Metaculus questions from May 01 to Nov. 18 2025.

H.3. Varying models and evaluation months

In Figure 13 we observe that while the first few article chunks that are retrieved lead to large improvements, at around five articles improvements plateau, both on our Qwen3-8B and also other large models like GPT-OSS-120B. Thus, unless otherwise specified, we use 5 articles for all evaluations and training in this work.

Improvement on non-Qwen models. Our training data `OpenForesight` can be used to improve models across different families. In Figure 14 we show improvements for Llama-3.1-8B-Instruct, Llama-3.2-3B-Instruct and Gemma-3-4B-Instruct. We see particularly large improvements in both accuracy and brier score for Llama due to both: poor initial performance, but also surprising amenability to RL training with our data as the final performance exceeds much larger models like Qwen3-235B-A22B and DeepSeek-v3.

Results over time. As our test set is derived from articles from May to August 2025, so we split the questions by resolution date to get monthly performance of the models. Breaking down by month, our test has 270 questions resolving in May, 265 in June, 193 resolving in July and 137 resolving in August. Our hypothesis is that as we go further into the future, forecasting should become more difficult leading to lower performance. In Figure 15 and

Figure 13. **Improvements from retrieval plateau at ∼ 5 chunks.** We show the accuracy of both a large GPT-OSS-120B model and a small Qwen3-8B model which we finetune.

Figure 14. Performance of models from Llama and Gemma family our test set.

Figure 16, we find that the accuracy and brier score of the models indeed drops gradually month-by-month consistent with our hypothesis. We also find that our trained models are consistently better than the original versions and also better than all other models in Brier score.

H.4. Consistency Evaluation

Table 7. **Improvement in consistency checks before and after RL training**. We report average violation scores and relative improvements (negative percentages indicate improvements). The RL-trained model shows substantial improvements in logical consistency across most reasoning tasks.

Check	Arbitrage			Frequentist		
	Qwen3-8B	OpenForecaster-8B	Δ	Qwen3-8B	OpenForecaster-8B	Δ
NEGATION	0.043	0.029	-32%	0.198	0.177	-11%
PARAPHRASE	0.030	0.015	-50%	0.157	0.114	-27%
CONSEQUENCE	0.010	0.003	-66%	0.048	0.033	-31%
ANDOR	0.033	0.019	-43%	0.205	0.148	-28%
AND	0.016	0.004	-78%	0.063	0.026	-59%
OR	0.022	0.008	-64%	0.094	0.061	-35%
BUT	0.040	0.021	-47%	0.234	0.193	-17%
COND	0.039	0.030	-23%	0.227	0.220	-3%
CONDCOND	0.036	0.032	-13%	0.256	0.255	-0%
EXPEVIDENCE	0.041	0.015	-64%	0.240	0.166	-31%
Aggregated	**0.031**	**0.017**	**-44%**	**0.172**	**0.139**	**-19%**

Paleka et al. (2025b) release a dataset of long-term forecasting questinos set to resolve up to 2028, showing language models exhibit inconsistencies in their probabilistic predictions. To evaluate consistency, they propose ten consistency checks measuring both arbitrage and frequentist violations.

We evaluate Qwen3-8B and our trained model on the dataset created by Paleka et al. (2025b). We measure performance of the models on all consistency check tuples proposed by them. Table 7 compares the baseline Qwen3-8B with our RL-trained model. The results demonstrate substantial improvements across most consistency checks, with particularly strong gains in Boolean logic operations (AND: 78% reduction, OR: 64% reduction) and paraphrase consistency (50% reduction). Overall, our training achieves a 43.5% reduction in arbitrage violations and 19.2% reduction in frequentist violations, indicating more consistent long-term predictions.

Figure 15. Monthly accuracy of the models on our test set.

Figure 16. Monthly brier score of the models

I. Qualitative Analysis of Reasoning Evolution During Training

We now provide a few qualitative examples of how the model reasoning evolves when training on OpenForesight. We ask the model itself to provide a summary of its reasoning (after the <think></think> tags), and show this summary below for the initial Qwen3 8B model, followed by training checkpoints.

I.1. Example 1: Model stays incorrect but learns to hedge

Question: Which country will face a new 25% US tariff in a trade announcement by 30 July 2025?
Background: The US administration is evaluating other countries' trade barriers and is expected to announce new tariffs by the end of July 2025.
Resolution Criteria:

Source of Truth: Official tariff announcement issued by the White House or the Office of the United States Trade Representative.

Resolution Date: 30 July 2025, the date by which the 25% tariff announcement is expected.

Accepted Answer Format: The full name of the country as stated in the official announcement.

Resolution answer: India

Checkpoint 0: score=-0.722, status=wrong
<answer>South Korea</answer> <probability>0.85</probability> **Reasoning**: - **Article 2** (May 25, 2025) explicitly mentions a **25% tariff** on **Samsung** (South Korea) and other smartphone manufacturers. This directly ties the 25% tariff to **South Korea**. - While the EU is mentioned with a **50% tariff** in the same article, the **25% tariff** specifically targets South Korea's exports. - Other articles reference tariffs on China, the EU, or automakers, but none specify a **25% tariff** on a country beyond South Korea. - The resolution date (July 30, 2025) aligns with the timeline of the May 25 announcement, as no newer data is provided. **Confidence**: 85% (strong evidence from Article 2, though no post-May 25 updates confirm further announcements).

Checkpoint 400: score=-0.360, status=wrong
The retrieved articles indicate ongoing US tariff announcements by the Trump administration in 2025. Article 2 explicitly mentions a 25% tariff on South Korea for smartphone manufacturers like Samsung, while Article 4 references 25% tariffs on steel and aluminum imports from Canada and Mexico. Article 3 also notes a 25% tariff on foreign automakers, which could target countries like South Korea or others, but South Korea is specifically named in Article 2 for a 25% rate. Given the question's focus on a "new" 25% tariff announcement by July 30, 2025, and the patterns in the articles, South Korea appears as a likely candidate, as it has already faced such announcements and fits the criteria. However, the question implies a potential new announcement, and other countries like Canada or Mexico could also be possibilities based on Article 4, introducing uncertainty. My confidence is moderate due to the reliance on past announcements and the possibility of new developments by the resolution date. <answer>South Korea</answer> <probability>0.6</probability>

Checkpoint 800: score=-0.090, status=wrong
The retrieved articles indicate a pattern of US tariffs targeting major trade partners like China, India, the EU, Canada, Mexico, and South Korea. Article 4 specifically mentions a 25% tariff on steel and aluminum imports, which historically targets countries such as China and those in the EU. Article 2 highlights a 25% tariff on South Korean products (e.g., Samsung), while Article 1 and Article 3 reference ongoing tariffs on China and other nations. Given the US administration's focus on trade barriers, China is the most frequently mentioned target, making it a likely candidate for a new 25% tariff announcement by July 2025. However, the articles do not confirm a specific new announcement, and other countries like India are also potential targets based on Article 1, introducing uncertainty. Due to the lack of direct evidence for a July announcement and the possibility of shifts in US policy, my confidence is low. <answer>China</answer> <probability>0.3</probability>

I.2. Example 2: Model goes from incorrect to correct

Question: Who will give Harvard one week to produce extensive records for its exchange visitor program review by July 23, 2025?
Background: The U.S. Secretary of State periodically issues directives to universities regarding their exchange visitor

program compliance.

Resolution Criteria:

Source of Truth: The official announcement or government statement naming the individual who issued the one-week deadline.

Resolution Date: When the directive is publicly attributed (expected by July 23, 2025).

Accepted Answer Format: Full name, for example "Jane Doe".

Resolution answer: Marco Rubio

Checkpoint 0: score=-0.902, status=wrong
The retrieved articles describe actions by the Trump administration's Department of Homeland Security, specifically Secretary Kristi Noem, toward Harvard. In the text, Noem sends Harvard a letter giving them 72 hours to provide information, not one week, so there is a mismatch between the question's "one week by July 23, 2025" and the articles' "72 hours." It seems that the July 23 date comes from the resolution criteria and isn't in the articles themselves, and that the 72-hour deadline might be part of a larger process leading up to that date, or that the question wording is slightly off. Despite this discrepancy, all the evidence points to Kristi Noem as the person issuing the directive to Harvard about providing records. Therefore, the answer should be Kristi Noem, and the confidence is high because all the articles point to her as the one who issued the directive to Harvard regarding the records.<answer>Kristi Noem</answer> <probability>0.95</probability>

Checkpoint 400: score=-0.490, status=wrong
The retrieved articles indicate that Kristi Noem, as the U.S. Department of Homeland Security (DHS) Secretary, has been directly involved in issuing deadlines related to Harvard's exchange visitor program compliance. For instance, in Article 2, she gave Harvard 72 hours (approximately 3 days) to comply with requests for records. The question specifies a one-week deadline by July 23, 2025, which may be a variation or continuation of similar directives from this administration. Given the pattern in the articles, it is reasonable to infer that Noem or a similar high-level official from the Trump administration is likely to issue such a directive. However, there is uncertainty due to the slight discrepancy between 72 hours and one week, and potential changes in personnel or administration by July 2025. Final Answer: <answer> Kristi Noem </answer> <probability> 0.7 </probability>

Checkpoint 800: score=0.910, status=correct
The retrieved articles primarily discuss the U.S. Department of Homeland Security (DHS) Secretary, Kristi Noem, in the context of Harvard's visa program issues, such as scrutiny and potential termination due to non-compliance. However, the question specifically pertains to the U.S. Secretary of State issuing a directive, as outlined in the question background. Based on the Trump administration's context in the articles, Marco Rubio was the Secretary of State in 2024 and likely remained in that role through at least 2025, as no other name is explicitly mentioned for that position. This is inferred from the articles' references to Trump administration actions, though the articles confuse DHS Secretary Noem with Secretary of State responsibilities. Given the resolution criteria requiring the official announcement, I am considering the most probable candidate from historical context, but the articles' inconsistencies lower my confidence. Final Answer: <answer>Marco Rubio</answer> <probability>0.7</probability>

I.3. Example 3: Model goes from correct to incorrect, but interestingly reasons about brier

Question: Which Australian state besides New South Wales will be affected by the forecast 'second surge' of rain and wind on Wednesday night?
Background: The Bureau of Meteorology has forecast a 'second surge' of rain and wind for Wednesday night, expected to impact coastal regions.
Resolution Criteria:

Source of Truth: The question will resolve based on the Bureau of Meteorology's severe weather warnings and regional impact statements for the second surge, as published on bom.gov.au.

Resolution Date: 2 July 2025, following the Wednesday night updates.

Accepted Answer Format: The name of the Australian state, in 1–2 words.

Resolution answer: Victoria

Checkpoint 0: score=0.978, status=correct

The question's background says the resolution is on 2 July 2025, following Wednesday night updates. So the answer should be based on the Bureau's forecast as of that time. But the available articles are up to February 2025. If the 'second surge' is part of the forecast mentioned in Article 2 (from January 2025), then the answer is Victoria. However, the user might have a different scenario. Alternatively, in Article 4, there's a mention of damaging winds in parts of Illawarra, Sydney, and Hunter coast, but again, that's part of NSW. So, based on the available information, the most likely answer is Victoria. But I need to make sure that the 'second surge' refers to the same event. The article mentions a second strong wind coming from the south-west, which would affect the south of the country, including Victoria. Therefore, the answer is Victoria. Confidence: The articles mention Victoria as part of the affected regions. However, since the exact 'second surge' isn't explicitly named in the articles, there's some uncertainty. But based on the context, Victoria is the most likely state besides NSW. </think> <answer>Victoria</answer> <probability>0.85</probability>

Checkpoint 400: score=0.840, status=correct

The provided articles indicate patterns of weather impacts from the Bureau of Meteorology, particularly in eastern Australia. Article 2 explicitly mentions a weather system affecting eastern New South Wales, with parts of Victoria and south-east Queensland also likely impacted, including strong winds and rain. This aligns with the question's reference to a 'second surge' of rain and wind on Wednesday night. Article 1 and Article 3 further support influences on Victoria and South Australia from similar weather fronts, but Victoria is the most consistently mentioned state besides New South Wales across multiple articles. Given the resolution criteria relying on BoM's warnings, I infer that Victoria is the most probable state based on these patterns. However, the articles do not directly reference the specific forecast for 2 July 2025, introducing uncertainty. Confidence: The articles don't directly match the question, so I'm not 100% sure. Maybe 0.6, since it's inferred from patterns. To maximize my score with Brier score: If I'm correct, higher p is better; if wrong, lower p is better. I need to be honest about my confidence. I think 0.6 is reasonable, as it's a guess based on the info. <answer>Victoria</answer> <probability>0.6</probability>

Checkpoint 800: score=-0.360, status=wrong

The retrieved articles provide information on weather patterns in Australia, particularly from 2023 and early 2025. Article 2 specifically mentions a weather system affecting eastern NSW, with additional risks to eastern Victoria and south-east Queensland, including strong winds and rain. This aligns with the description of a 'second surge' impacting coastal regions. Other articles reference various states like South Australia and Victoria, but Queensland is the most directly linked besides NSW in the context of a similar weather event. Given the patterns in the articles, Queensland seems the most likely state to be affected. However, the articles are from different dates and not explicitly about the 2 July 2025 event, introducing uncertainty. Based on the evidence, I am moderately confident in this guess. I need to maximize my score using Brier scoring. If I'm correct, higher p is better; if wrong, lower p is better. Since I have to guess, I'll go with Queensland, as it's the most specific one mentioned besides NSW. My confidence: The passages aren't directly about the event, so it's uncertain. Maybe 0.4 or 0.5? Let's say 0.6, because it's the most prominent besides NSW in the relevant passages. <answer>Queensland</answer> <probability>0.6</probability>

J. Systematic Failure Modes in Model Reasoning

`OpenForecaster` 8B achieved an accuracy of 33% on our test set consisting of 302 questions. Through manual analysis of the failure cases, we identified three systematic failure modes in the model's reasoning process.

1. Missing Information in Retrieved Articles   The most common failure mode occurs when retrieved articles lack the specific information needed. The model acknowledges this but falls back to general knowledge or educated guesses rather than expressing high uncertainty.

Example 1: "By what date will the New York City Board of Elections certify the official results of the Democratic mayoral primary?"

- **Correct answer:** July 15

- **Model answer:** August 15 (probability: 0.2)

- **Model's reasoning:** "The provided news articles discuss the New York City Democratic mayoral primary, including polling data, candidate strategies, and the election date of June 24, 2025. However, they do not specify the certification process or timeline for the New York City Board of Elections. Based on general knowledge of past NYC elections, certification typically occurs 2-6 weeks after the primary to allow for vote counting, ballot challenges, and legal reviews. For instance, in the 2013 primary, certification was completed by July 2. Given the late summer 2025 resolution criteria, a reasonable estimate is mid-August, but without specific historical data from the articles, this is uncertain. I am guessing August 15, 2025, as it aligns with typical procedures, but my confidence is low due to the lack of direct evidence."

- **Analysis:** The model correctly identifies that articles lack the certification date but incorrectly infers from general knowledge. It acknowledges uncertainty (probability 0.2) yet provides a specific date. The inference from "2-6 weeks after June 24" to "mid-August" is flawed, as July 15 falls within this range.

2. Over-reliance on General Knowledge   When articles lack specific information, the model makes educated guesses based on general knowledge, historical patterns, or analogies rather than acknowledging the answer cannot be determined from the provided context.

Example 1: "What will be the official name of Donna D'Errico's interactive AI voice service by mid-July 2025?"

- **Correct answer:** Call Donna D.

- **Model answer:** Donna Voice (probability: 0.1)

- **Model's reasoning:** "The provided articles do not mention Donna D'Errico or her specific AI voice service, making it impossible to draw direct insights. However, patterns from the articles, such as the naming of AI voice services (e.g., Melania Trump's "Melania: The Audiobook"), suggest that such services often incorporate the individual's name followed by descriptors like "Voice" or "AI." Based on this analogy, I am guessing the name might be "Donna Voice" or something similar. This is a speculative prediction, as there's no concrete information, leading to low confidence."

- **Analysis:** The model creates a naming pattern from one unrelated example (Melania Trump's service) and applies it incorrectly. It recognizes the speculation (probability 0.1) but the actual name "Call Donna D." follows a different pattern entirely.

Example 2: "What name will the new Pope take upon his election on May 8, 2025?"

- **Correct answer:** Leo XIV

- **Model answer:** Pius (probability: 0.1)

- **Model's reasoning:** "The provided articles do not specify the name of the next Pope or any potential candidates' chosen names. They focus on Pope Francis's health, the conclave process, and recent appointments of cardinals. Historically, new Popes select names that are traditional, often drawing from saints or biblical figures, but without specific information from the articles or external knowledge, any prediction is highly uncertain. Based on patterns from past Popes (e.g., Francis, Benedict), I am guessing "Pius" as a common regnal name, but this is purely speculative and not supported by the articles. Therefore, my confidence in this answer is very low."

- **Analysis:** The model relies entirely on general knowledge about papal naming conventions rather than specific information. It correctly identifies high uncertainty (probability 0.1) though. The reasoning conflates "common regnal names" with what the next Pope will actually choose.

3. Entity Confusion: Selecting Wrong Person/Place/Organization   When multiple entities are mentioned, the model frequently selects the most prominent or frequently mentioned one rather than the correct answer, even when both are present in the context.

Example 1: "Who will Chelsea face in the round of 16 of the 2025 FIFA Club World Cup?"

- **Correct answer:** Benfica

- **Model answer:** Bayern Munich (probability: 0.4)

- **Model's reasoning:** "The provided articles detail the groups for the 2025 FIFA Club World Cup, with Group C consisting of Bayern Munich, Benfica, Boca Juniors, and Auckland City, and Group D including Chelsea, Flamengo, Esperance Sportive de Tunisie, and a replacement (possibly Los Angeles FC or Club America based on Article 1). The question specifies that the round of 16 matchup is between the runner-up of Group D and the winner of Group C. Without the actual group stage results, I must make an educated guess based on team strengths. Bayern Munich is a strong candidate for the winner of Group C, as they are the defending champions and one of the top teams. Chelsea, in Group D, could plausibly be the runner-up, given their history, but this is uncertain. The replacement team adds further uncertainty, as it could affect group dynamics."

- **Analysis:** The model selects the more prominent team (Bayern Munich) from Group C rather than correctly identifying which team would actually win the group. It uses team prominence ("defending champions," "top teams") as a proxy for group stage results, ignoring that the question requires specific match outcomes that aren't in the articles.

K. Prompt Templates

K.1. Question Creation Pipeline

Stage 1 — Question Generation (Requires: self.num_questions_per_article > 1)

```
**Task:** Based on the provided news article, generate
    {self.num_questions_per_article} high-quality, DIVERSE forecasting questions
    which have a short answer (1 - 3 words), using the XML format specified below.
Each forecasting question should be posed in a way to predict future events. Here,
    the predictor will have a knowledge cutoff before the article is published and
    no access to the article, so a forecasting question has to be posed about
    information explicitly stated in the article. The question should be stated in a
    forward-looking manner (towards the future).
The correct answer should be a specific, short text response. The answer should be
    a WELL DEFINED, SPECIFIC term which the answerer can come up with on its own,
    without access to the news article.

**Example Format**:
<q1>
<question_id>0</question_id>
<question_title>Who will win the Nobel Prize in Literature in 2016?</question_title>
<background>Question Start Date: 10th January 2016. The Nobel Prize in Literature
    is awarded annually by the Swedish Academy to authors for their outstanding
    contributions to literature.</background>
```

```
<resolution_criteria>
<ul>
    <li>
      Source of Truth: The question will resolve when the Swedish Academy
    publicly announces the official 2016 Nobel Prize in Literature
    laureate(s)---typically via a press release on NobelPrize.org (expected on or
    about October 13, 2016).
    </li>
    <li>
      Resolution Date: The resolution occurs on the calendar date when the
    2016 laureate(s) are formally named
      (typically mid-October 2016).
    </li>
    <li>
      Accepted Answer Format: The full name of the laureate exactly as given
    in the announcement should be provided. If more than one person shares the
    prize, all names must be listed in the same order as the official communiqu{\'e}.
    </li>
</ul>
</resolution_criteria>
<answer>Bob Dylan</answer>
<answer_type>String (Name)</answer_type>
</q1>

The question should follow the structured guidelines below.

### **Guidelines for Creating Short Answer Forecasting Questions**

**Title Question Guidelines**
- **Quality**: The question should be of HIGH QUALITY and hard to answer without
    access to the article. It should not be about any minute details in the article.
    THE QUESTION SHOULD BE SUCH THAT ITS ANSWER REVEALS A KEY PIECE OF INFORMATION,
    FROM THE ARTICLE, WHICH HAS MAXIMAL IMPACT.
- **Specific and Answerable**: The question to be created SHOULD BE FREE-FORM and
    have a unique, specific answer (a single word, or short phrase) without access
    to the article. The answer to the question should be definite, well-defined and
    NOT NUMERIC. IT SHOULD ALSO NOT BE UNCERTAIN like "above XYZ" OR A RANGE LIKE
    "between XYZ and ABC". Avoid creating binary questions (yes/no, either/or) or
    questions with a list of specific options (multiple choice).
- **Answerable based on article**: Each question must have a CLEAR AND DEFINITE
    answer based on information stated in the article. Given the question, the
    content of the article should be able to resolve the answer to the question
    INDISPUTABLY WITHOUT ANY AMBIGUITY OR UNCERTAINTY. THE ARTICLE SHOULD NOT STATE
    THAT THE ANSWER IS TENTATIVE OR AN ESTIMATE OR LIKELY. The answer SHOULD HAVE
    HAPPENED BY NOW.
- **Temporal Information**: The question should not be about recall of (past) facts
    or events known before the article publish date. Include any temporal
    information necessary to answer the question (like by which month, year, etc.)
    in the question. The question should always be posed in a forward-looking manner.
- **Direct and Precise**: Titles must be straightforward and unambiguous, avoiding
    vague terms. Use future tense when appropriate.
- **Resolution Criteria**: ALWAYS INCLUDE A BRIEF RESOLUTION CRITERIA in the
    question title. This is often the date by which the question will be resolved.
    For example, resolution dates such as "by {{month_name}}, {{year}}?" or "in
    {{month_name}}, {{year}}?". THE RESOLUTION DATE SHOULD BE BASED ON (AND FAITHFUL
    TO) THE CONTENT OR PUBLICATION DATE OF THE ARTICLE.
- **No references to article or future information**: DO NOT refer to the specific
    article, such as by saying "in the article". The forecaster does not have access
    to the article, its metadata or any information beyond the article publish date.
- **Question Types**: Focus on "Who", "What", "When", "Where" questions that have
    concrete answers.
- **Understandability**: The question title should have ALL the information to be
    understandable by a 10 year old. It should be independently understandable
```

```
      without the article.
   - **Tense**. ALWAYS POSE THE QUESTION IN A FORWARD-LOOKING MANNER. THE QUESTION
      SHOULD BE IN FUTURE TENSE. Try to use phrases like "What will", "Who will",
      "When will", "Where will", "How much/many will" etc. It should appear as a
      forecasting question and not past prediction.

   **Answer Guidelines**
   - **Faithfulness to Article**: The answer should be based on information explicitly
      stated in the article, and not implications or your own knowledge. IT SHOULD BE
      STATED VERBATIM IN THE ARTICLE.
   - **Non-Numeric**: The answer should not be a number or a percentage. It can be a
      word, phrase, date, location, etc BUT NOT MORE THAN 3 WORDS.
   - **Definite** – Given the question and the article, the answer should be CLEAR,
      CONCRETE, CERTAIN AND DERIVABLE from the article. It should be short,
      WELL-DEFINED TERM and not uncertain or vague. It SHOULD NOT BE A RANGE like
      "between XYZ and ABC" or "above XYZ" or "below PQR".
   - **Resolved** – The answer MUST be something that has already happened or is
      happening now. It should be resolved given today's date and not be something
      that will happen in the future.
   - **Specificity**: The answer should be specific enough to be unambiguous. Avoid
      overly general answers.
   - **Conciseness**: Keep answers short – typically 1-3 words, occasionally a short
      phrase if necessary.
   - **Exactness**: For names, use the exact names mentioned (full name, if possible).
   - **Uniqueness**: The answer should be unique and THE ONLY CORRECT ANSWER to the
      question.
   - **No Ambiguity**: The answer should be indisputable and not be open to multiple
      interpretations. IT SHOULD BE PRECISE AND NOT A RANGE OR UNCERTAIN ESTIMATE.

   **Background Guidelines**
   - **Mention Question Opening Date**: ALWAYS INCLUDE THE START DATE OF THE QUESTION
      IN THE BACKGROUND. IT SHOULD BE AT LEAST A FEW DAYS (OR WEEKS IF THE QUESTION IS
      ABOUT A LONG-TERM EVENT) BEFORE THE ARTICLE'S PUBLISH DATE AND ALSO BEFORE THE
      RESOLUTION DATE OF THE QUESTION. CONSEQUENTLY, THE BACKGROUND SHOULD NOT CONTAIN
      ANY INFORMATION WHICH HAS HAPPENED AFTER THE START DATE OF THE QUESTION.
   - **Necessary Context**: The answerer does not have access to the article, so
      include MINIMAL CONTEXT required to understand the question keeping in mind the
      question opening date. Do not give (extra) details of the event from the article
      as background. If required, EITHER pose the event as a hypothetical scenario as
      if it were to happen in the future OR describe it as happening (unfolding) in
      real time. Describe any unfamiliar terms or concepts in the question title.
   - **SHOULD NOT HELP ANSWER**: WHILE PROVIDING THE CONTEXT, DO NOT REFER OR MENTION
      OR LEAK THE ACTUAL ANSWER. The background must not help answer the forecasting
      question. DO NOT INCLUDE ANY INFORMATION from the article or elsewhere that
      either directly or indirectly (even partially) reveals the answer.
   - **No Additional Knowledge**: Do not add any knowledge beyond what is required to
      understand the question. Only include information necessary to understand the
      question and its context.
   - **Tense**. ALWAYS POSE THE BACKGROUND INFORMATION IN CURRENT TENSE. Only provide
      minimal information which is known until the question opening date.

   **Resolution Criteria**
   - **Necessary Criteria**: State the EXACT conditions by which the outcome will be
      judged. Include the criteria which determines how the question will be resolved.
      state the conditions by which the outcome will be judged.
   - **Date and Source of Resolution**: Always state the date and the source by which
      the question will be resolved. For example, resolution dates such as "by
      {{month_name}}, {{year}}?" or "in {{month_name}}, {{year}}?", and potential
      source(s) of resolution such as "based on {{news source}}", "reports from
      {{official name}}", etc. THE RESOLUTION DATE SHOULD BE CHOSEN THOUGHTFULLY AS
      THE ANSWER'S VALIDITY AND SOUNDNESS DEPENDS ON IT. THE RESOLUTION DATE SHOULD BE
      SUCH THAT THE ANSWER CAN BE RESOLVED DEFINITELY AND INDISPUTABLY FROM THE
      CONTENT OR PUBLICATION DATE OF THE ARTICLE. IT SHOULD MENTION BY WHEN IS THE
```

```
      OUTCOME OF THE QUESTION EXPECTED TO HAPPEN. HOWEVER, IT SHOULD NOT LEAK OR
      MENTION ANYTHING ABOUT THE ARTICLE.
  - **Details**: Be as detailed as possible in creating the resolution criteria for
      resolving the question as cleanly as possible. There should be no ambiguity in
      the resolution criteria.
  - **Expectation and Format of Answer**: Based on the actual answer, the resolution
      criteria should state how precise the expected answer should be and in what
      format it should be. For example, if the actual answer is a date, the resolution
      criteria should specify how detailed the expected date should be -- only year,
      or both month and year, or day, month, and year all together. DO NOT GIVE THE
      ACTUAL DATE (ANSWER). If the actual answer is a percentage, then the criteria
      should state the expected answer should be a percentage. DO NOT GIVE THE ACTUAL
      PERCENTAGE.  If the actual answer is in certain unit, then the criteria should
      specify that. THE RESOLUTION CRITERIA SHOULD MAKE IT EXACTLY CLEAR AND PRECISE
      WHAT IS EXPECTED FROM THE ANSWERER AND IN WHAT FORMAT AND HOW IT WILL BE CHECKED
      LATER. IF GIVING AN EXAMPLE, IT SHOULD BE VERY GENERIC AND AS FAR AWAY FROM THE
      ACTUAL ANSWER AS POSSIBLE.
  - **SHOULD NOT HELP ANSWER**: The resolution criteria must not directly help answer
      the forecasting question. DO NOT INCLUDE ANY INFORMATION from the article or
      elsewhere that either directly or indirectly (even partially) reveals the
      answer. DO NOT REFER OR MENTION OR LEAK THE ACTUAL ANSWER HERE.

  **Answer Type Guidelines**
  - **Expected Format**: The answer type should be either "numeric (XYZ)" if the
      answer is a number (of any kind) or "string (XYZ)" in all other cases. In
      numeric cases, XYZ should be the exact type of number expected. For example,
      "numeric (integer)", "numeric (decimal)", "numeric (percentage)", "numeric
      (whole number)", etc. In string cases, XYZ should broadly be the category of
      string expected. For example, "string (name)", "string (date)", "string
      (location)", etc. If the category is not clear, use "string (any)". HOWEVER,
      ALWAYS TRY TO CREATE QUESTIONS WHERE THE ANSWER CATEGORY IS CLEAR AND PRECISE.

  **Question Quality Criteria**
  - **Forecastable**: The question should be something that could reasonably be
      predicted or forecasted before the article's publication.
  - **Towards the future**: THE QUESTION SHOULD BE POSED IN A FORWARD-LOOKING MANNER.
  - **Interesting**: The question should be about a meaningful event or outcome, not
      trivial details.
  - **Impactful**: The question should be such that if its answer is forecasted ahead
      of time, it should have significant (downstream) impact (relevant to high number
      of people).
  - **Difficulty**: While the question should be hard to answer without access to the
      article, it should also not be unreasonably difficult.
  - **Verifiable**: The answer should be something that can be EXACTLY verified from
      the article itself.
  - **Time-bound**: Include clear timeframes or deadlines when relevant.
  - **Free-form**: If possible, avoid creating binary questions (yes/no, either/or)
      or questions with a list of specific options (multiple choice).

  Generate {self.num_questions_per_article} high-quality, DIVERSE short answer
      forecasting questions based on the provided article. Use the XML format with
      question_id value "0", "1", "2", etc. DO NOT INCLUDE ANY ANALYSIS, RANKING, OR
      ADDITIONAL COMMENTARY.

  Article:
  {source_article}

  **Required Output Format**:
  <q1>
  <question_id>0</question_id>
  <question_title>[Question 1]</question_title>
  <background>[Background 1]</background>
  <resolution_criteria>[Resolution Criteria 1]</resolution_criteria>
```

```
<answer>[Answer 1]</answer>
<answer_type>[Answer Type 1]</answer_type>
</q1>
..
<q{self.num_questions_per_article}>
<question_id>{self.num_questions_per_article - 1}</question_id>
<question_title>[Question {self.num_questions_per_article}]</question_title>
<background>[Background {self.num_questions_per_article}]</background>
<resolution_criteria>[Resolution Criteria
    {self.num_questions_per_article}]</resolution_criteria>
<answer>[Answer {self.num_questions_per_article}]</answer>
<answer_type>[Answer Type {self.num_questions_per_article}]</answer_type>
</q{self.num_questions_per_article}>
```

Stage 2 — Individual Validation

Task: You will be provided with a news article and a question WHOSE ANSWER IS
    SUPPOSED TO BE BASED ON THE ARTICLE. Your job is to validate whether the answer
    to the question is valid by being faithful to the article (content, title, or
    description).

GO THROUGH EACH SEGMENT OF THE QUESTION ONE BY ONE (TITLE, BACKGROUND, RESOLUTION
    CRITERIA, ANSWER) TO UNDERSTAND THE WHOLE QUESTION. THEN CHECK EACH OF THE
    FOLLOWING CRITERIA:

1. **Tense and Details**: FIRST CHECK WHETHER THE QUESTION IS NOT UNDER SPECIFIED
    OR STATED IN PAST TENSE. IT IS FINE IF THE QUESTION IS STATED IN CURRENT OR
    FUTURE TENSE.
2. **Definite resolution of the answer by the article**: CHECK WHETHER THE ANSWER
    TO THE QUESTION IS SOUND, CLEAR AND PRESENT IN OR CAN BE DERIVED FROM THE
    ARTICLE. THE ARTICLE SHOULD RESOLVE THE ANSWER DEFINITELY AND IN AN INDISPUTABLE
    MANNER (WITHOUT ANY AMBIGUITY). THIS IS THE MOST IMPORTANT CRITERIA.
3. **Well-defined Answer**: The answer to the question should be short (NOT MORE
    THAN 3 WORDS). IT SHOULD NOT BE A PHRASE AND SHOULD BE SOMETHING WHICH IS
    CONCRETE, SPECIFIC AND WELL-DEFINED.
4. **Non-Numeric**: THE *ANSWER TYPE* SHOULD NOT BE NUMERIC LIKE A PERCENTAGE,
    INTEGER, DECIMAL, OR A RANGE.
5. **Single Correct Answer**: ANALYZE WHETHER THE QUESTION CAN HAVE MULTIPLE
    OUTCOMES OR RIGHT ANSWERS. IF SO, THE QUESTION FAILS THIS CRITERIA. OTHERWISE,
    ENSURE THAT THE PROVIDED ANSWER IS THE SOLE CORRECT ANSWER TO THE QUESTION. IT
    SHOULD NOT BE THE CASE THAT THE QUESTION CAN HAVE MULTIPLE (DISTINCT) CORRECT
    ANSWERS.

If ALL the above criteria pass (question is stated as required, answer to the whole
    question is valid, well-defined, and it is the only correct answer to the
    question), ONLY THENreturn <answer>1</answer>. Otherwise, return
    <answer>0</answer>. ALWAYS END YOUR RESPONSE IN <answer> </answer> tags.

Article:
{source_article}

Question:
{questions_text}

Output Format:
<answer>0/1</answer>

Stage 3 — Choose Best

Task: You will be provided with a list of questions (possibly with size 1).
Your job is to choose the best question from the list based on the following
criteria or end your response with "NO GOOD QUESTION" if none of the questions
meet the criteria.

Instructions:
GO THROUGH EACH QUESTION ONE BY ONE AND ANALYZE IT FOR THE FOLLOWING:
1. **Valid for forecasting**: Check if the WHOLE QUESTION is stated in a
   forward-looking manner. FROM THE PERSPECTIVE OF THE START DATE TO THE RESOLUTION
   DATE MENTIONED IN THE QUESTION, CHECK IF IT IS A VALID FORECASTING QUESTION. IF
   THE TIME HORIZON (START DATE TO RESOLUTION DATE) IN THE QUESTION IS AT LEAST A
   SINGLE DAY, THEN THE QUESTION SHOULD BE CONSIDERED VALID FOR FORECASTING. Go
   through each segment of the question (question title, background, resolution
   criteria) and check if each of them is valid and forward-looking.
2. **Tense**: The question SHOULD NOT BE STATED IN PAST TENSE. If the question
   covers an event, it should not imply as if the outcome of the event has already
   happened or occurred.
3. **Single Correct Answer**: ANALYZE WHETHER THE QUESTION CAN HAVE MULTIPLE
   OUTCOMES OR RIGHT ANSWERS. IF SO, THE QUESTION FAILS THIS CRITERIA. OTHERWISE,
   ENSURE THAT THE PROVIDED ANSWER IS THE SOLE CORRECT ANSWER TO THE QUESTION. IT
   SHOULD NOT BE THE CASE THAT THE QUESTION CAN HAVE MULTIPLE (DISTINCT) CORRECT
   ANSWERS.
4. **Impact**: How many people will the outcome of the question be relevant or
   interesting to? Consider on the basis of significant downstream impact or
   enabling meaningful action.
5. **Not Binary/Multiple Choice**: Question SHOULD NOT BE BINARY (yes/no, either
   ABC or XYZ, etc.) OR MULTIPLE CHOICE (SELECT FROM A LIST OF OPTIONS). It should
   be free-form (string -- name, date, place, etc.) or numerical (number,
   percentage, etc.).
6. **Understandable**: THe question as a whole (title, background, resolution
   criteria) should have sufficient details to understand the premise of the
   question. Every detail should be crystal clear and the question should not be
   under or over specified.
7. **Definite Answer**: EXTRACT THE ACTUAL ANSWER TO THE QUESTION PROVIDED IN ITS
   <answer> </answer> TAG. The extracted answer should be short, definite,
   well-defined and not uncertain or vague. It SHOULD NOT BE A PHRASE OR A RANGE
   like "between XYZ and ABC" or "above XYZ" or "below PQR".

ANALYZE EACH QUESTION BASED ON THE ABOVE CRITERIA ONE BY ONE AND CHOOSE THE ONE
WHICH PASSES ALL THE ABOVE CRITERIA. IF MULTIPLE QUESTIONS SATISFY THE CRITERIA,
CHOOSE THE ONE WHICH WILL HAVE THE HIGHEST IMPACT (AFFECTS OR IS RELEVANT TO THE
MOST NUMBER OF PEOPLE). IF NO QUESTION MEETS THE CRITERIA, RETURN "NO GOOD
QUESTION FOUND". OTHERWISE, RETURN THE BEST QUESTION IN THE SAME FORMAT AS THE
INPUT.

Generated Questions:
{questions_text}

Output Format:
```
<q1>
<question_id>0</question_id>
<question_title>[ORIGINAL Title of the best question]</question_title>
<background>[ORIGINAL Background of the best question]</background>
<resolution_criteria>
<ul>
    <li> Source of Truth: [ORIGINAL Source of Truth of the best question]
    </li>
    <li> Resolution Date: [ORIGINAL Date of the best question] </li>
    <li> Accepted Answer Format: [ORIGINAL Accepted Answer Format of the
```

```
1980      best question] </li>
1981    </ul>
1982    </resolution_criteria>
1983    <answer>[ORIGINAL Answer of the best question]</answer>
1984    <answer_type>[ORIGINAL Answer Type of the best question]</answer_type>
1985    </q1>
1986
```

Stage 4 — Leakage Removal

Task: You will be provided with a forecasting question. Your job is to ANALYZE
   whether the question's answer has obviously leaked in the content of the
   question. The question will have multiple segments -- question title,
   background, resolution criteria. EXCEPT THE QUESTION TITLE, GO THROUGH EACH
   SEGMENT STEP BY STEP and check if any part DIRECTLY leaks the actual answer. If
   leakage is found, ONLY THEN rephrase the problematic parts appropriately to
   remove the answer while maintaining the question's integrity and focus. DO NOT
   CHANGE ANY PART OF THE QUESTION UNNECESSARILY.

USE THE SAME XML FORMAT IN YOUR RESPONSE AS IS IN THE INPUT.

Generated Question:
{questions_text}

Instructions:
1. **Keep the title unchanged**: DO NOT MAKE ANY CHANGE TO THE QUESTION TITLE.
2. **Keep the start date in the background unchanged**: DO NOT MAKE ANY CHANGE TO
   THE QUESTION'S START DATE IN THE BACKGROUND.
3. **Identify the answer**: First, extract the actual answer from the XML tags for
   the current question being processed.
4. **Identify Leakage**: Keeping the extracted answer in mind, check if the
   background, or resolution criteria (each of them -- source of truth, resolution
   date, accepted answer format) contain information that reveals the answer.
5. **Types of leakage which can be ignored**: The following types of leakage are
   fine and don't need to be rephrased:
   – If the outcome (actual answer) of the question is binary (yes/no, either ABC
   or XYZ, etc.), then NO NEED TO CHANGE ANYTHING ANYWHERE.
   – If the resolution criteria is based on a list of specific options, then NO
   NEED TO CHANGE ANYTHING IN ANY SEGMENT (BACKGROUND, RESOLUTION CRITERIA, etc.).
   For example, if the accepted answer format states "answer must be either .." OR
   "answer must be one of the following terms..", then NO NEED TO CHANGE ANYTHING
   ANYWHERE.
6. **Types of Leakage to Check:** ONLY CONSIDER THE FOLLOWING KIND OF LEAKAGE:
   – DIRECT MENTIONS of the answer (either in word or number form) or part of the
   answer in the question/background/resolution
   – References to specific outcomes that ARE CLOSE TO (OR REVEAL)THE ACTUAL ANSWER
7. **Rephrase Strategy**: If leakage is found, rephrase the problematic part while:
   – Keeping the question's core intent
   – Maintaining forecasting nature
   – Preserving necessary context
   – Making the answer UNOBVIOUS by replacing with a FAKE ANSWER (FAKE NAME, DATE,
   NUMBER, PERCENTAGE, etc.) WHICH IS GENERIC AND NOT CLOSE TO THE ACTUAL ANSWER.
   – The rephrased part should not contain any information that is part of the
   actual answer. Neither should it indirectly hint or reveal the answer.
8. **Check Accepted Answer Format**: IF THERE IS ANY EXAMPLE MENTIONED IN ACCEPTED
   ANSWER FORMAT ("e.g..."), MAKE SURE THE EXAMPLE IS GENERIC AND AS FAR AWAY FROM
   THE ACTUAL ANSWER AS POSSIBLE. DO NOT INCLUDE AN EXAMPLE IF NOT MENTIONED
   ALREADY.
9. **Do not change the answer**: Do not change the actual answer to the question.
10. **Do not change the answer_type**: DO NOT MAKE ANY CHANGE TO the answer_type.
11. **Each segment should be checked independently**: Go through each segment of
    the whole question one by one. Everything from the title of the question to the
    background information to the resolution criteria should be checked

```
        independently with reference to the answer of the question. In the resolution
        criteria, go through each <li> step by step. Do not change the other segments
        when rephrasing a problematic segment.
12. **Do not change anything unless leakage is found**: DO NOT UNNECESSARILY CHANGE
        ANY PART OF THE QUESTION UNLESS LEAKAGE IS FOUND.

IT IS ALSO POSSIBLE THAT MULTIPLE PARTS OF THE QUESTION HAVE LEAKAGE. YOU SHOULD
        CHECK EACH OF THEM INDEPENDENTLY AND ONLY IF LEAKAGE IS FOUND, REPHRASE THE
        PROBLEMATIC PARTS. DO NOT OVER-ANALYZE.

During your analysis, you should:
- Go through EACH SEGMENT OF THE QUESTION STEP BY STEP INDEPENDENTLY. First
        <background> and then inside <resolution_criteria>. Under the resolution
        criteria, go through the source of truth, resolution date, accepted answer
        format (each of them is a <li> tag) one by one. For each such segment, do the
        following:
        - Compare the content in the current segment with the actual answer. If ANY
        PART OF THE ANSWER is mentioned in the current segment, then consider that as a
        leakage UNLESS THE ACCEPTED ANSWER FORMAT IS BINARY (yes/no, either ABC or XYZ,
        etc.) OR A LIST OF SPECIFIC OPTIONS.
        - IF THE CURRENT SEGMENT IS BACKGROUND, DO NOT CHANGE THE QUESTION START DATE.
        - If the current segment is accepted answer format and there is a SPECIFIC
        EXAMPLE MENTIONED in it ("e.g. XYZ") which is close to the actual answer, then
        consider that as a leakage.
        - If leakage is found in the current segment, mention "Leakage found --
        {{reason for leakage}}". Form the segment with the problematic parts rephrased
        and mention it as "Replacement -- {{rephrased_text}}." THE REPHRASED TEXT SHOULD
        BE AS FAR AWAY FROM THE ACTUAL ANSWER AS POSSIBLE. It should now be present in
        the final output (instead of the original text).
        - Otherwise, mention "No leakage found". In your final output after you finish
        the analysis, return this segment UNCHANGED.
        - These outputs should be in the same format as the original input.
- Return the actual answer unchanged in the <answer> tag in your final output.
- Skip any other segments (question title, answer_type, etc.) in your analysis and
        output them unchanged (verbatim) in the final output.

Output your analysis step by step, and then end your response with the CORRECTED
        question in THE SAME XML FORMAT AS THE ORIGINAL.

**Output Format**:
{{ analysis }}

<q1>
<question_id>0</question_id>
<question_title>[UNCHANGED Question Title]</question_title>
<background>[Corrected Background]</background>
<resolution_criteria>
<ul>
    <li> [UNCHANGED Question Start Date] [Corrected Source of Truth] </li>
    <li> [UNCHANGED Resolution Date] </li>
    <li> [Corrected Accepted Answer Format] </li>
</ul>
</resolution_criteria>
<answer>[UNCHANGED Answer]</answer>
<answer_type>[UNCHANGED Answer Type]</answer_type>
</q1>
```

K.2. Evaluation Prompts

Model Evaluation Prompt (Uses retrieved news summaries)

```
You will be asked a forecasting question (which might be from the past). You have
    to come up with the best guess for the final answer.
You will also be provided with a list of retrieved news articles summaries which
    you may refer to when coming up with your answer.

Please provide your reasoning before stating your final answer and also express how
    likely you think your answer is to be correct (your confidence in your answer).

Question Title: {question_title}

Question Background:{question_background}

Resolution Criteria: {resolution_criteria}

Expected Answer Type: {expected_answer_type}

Relevant passages from retrieved news articles:
{retrieved_news_articles_text}

Think step by step about the information provided, reason about uncertainty and put
    your final answer (in the format asked) in <answer> </answer>}tags.
You should also specify your confidence in your answer in <probability>
    </probability> tags.
The probability should be a number between 0 and 1.

You will be rewarded based on the probability (p) you assign to your answer.
Your answer will be evaluated using the BRIER SCORING RULE which is basically (- (1
    - p)\^{2}) if your answer is correct and (- 1 - p\^{2}) if your answer is
    incorrect.

For example, if p = 0.5}, and your answer is incorrect, then your score will be (-1
    - 0.5\^{}2) = (-1 - 0.25) = -1.25}
whereas if the answer was correct, then your score would be (- (1 - 0.5)\^{2}) = (-
    (0.5)\^{2}) = -0.25.

Thus, the range of the score is [-2, 0] where your score lies between [-2, -1] if
    the answer is incorrect and [-1, 0] if your answer is correct.

If your answer is correct, you will be REWARDED more if your probability is higher
    whereas if your answer is incorrect, you will be PENALIZED more if your
    probability is higher.
YOU HAVE TO MAXIMIZE YOUR SCORE.

Your final answer should be concise (NOT MORE THAN A FEW WORDS LONG) and your
    response SHOULD STRICTLY END with <answer> </answer> tags and <probability>
    </probability> tags.
```

Example Prompt from Test Set (Without Retrieval)

```
You will be asked a forecasting question (which might be from the past).
You have to come up with the best guess for the final answer.
Please provide your reasoning before stating your final answer and also express how
    likely you think your answer is to be correct (your confidence in your answer).

Question Title:
Which country in the Americas will report the highest number of chikungunya cases
    by July 15, 2025?
```

```
Question Background:
Public health agencies in the Americas are compiling chikungunya case counts for
    individual countries as the outbreak spreads in the region.

Resolution Criteria:
<ul>
  <li>Source of Truth: Cumulative case figures published by the Pan American
    Health Organization or the European Centre for Disease Prevention and
    Control.</li>
  <li>Resolution Date: July 15, 2025, when the mid-July regional report is
    issued.</li>
  <li>Accepted Answer Format: The name of the country in the Americas with
    the highest total reported chikungunya cases.</li>
</ul>

Expected Answer Type:
string (location)

Think step by step about the information provided, reason about uncertainty and put
    your final answer (in the format asked) in <answer> </answer> tags.
You should also specify your confidence in your answer in <probability>
    </probability> tags.
The probability should be a number between 0 and 1.

You will be rewarded based on the probability (p) you assign to your answer.
Your answer will be evaluated using the BRIER SCORING RULE which is basically (- (1
    - p)^2) if your answer is correct and (- 1 - p^2) if your answer is incorrect.

For example, if p = 0.5, and your answer is incorrect, then your score will be (-1
    - 0.5^2) = (-1 - 0.25) = -1.25
whereas if the answer was correct, then your score would be (- (1 - 0.5)^2) = (-
    (0.5)^2) = -0.25.

Thus, the range of the score is [-2, 0] where your score lies between [-2, -1] if
    the answer is incorrect and [-1, 0] if the answer is correct.

If your answer is correct, your will be REWARDED more if your probability is higher
    whereas if your answer is incorrect, your will be PENALIZED more if your
    probability is higher.
YOU HAVE TO MAXIMIZE YOUR SCORE.

Your final answer should be concise (NOT MORE THAN A FEW WORDS LONG) and your
    response SHOULD STRICTLY END with <answer> </answer> tags and <probability>
    </probability> tags.
```

Example Prompt from Test Set (With Retrieval)

```
You will be asked a forecasting question (which might be from the past).
You have to come up with the best guess for the final answer.
You will also be provided with a list of retrieved news articles summaries which
    you may refer to when coming up with your answer.
Please provide your reasoning before stating your final answer and also express how
    likely you think your answer is to be correct (your confidence in your answer).

Question Title:
Which country in the Americas will report the highest number of chikungunya cases
    by July 15, 2025?

Question Background:
Public health agencies in the Americas are compiling chikungunya case counts for
```

```
     individual countries as the outbreak spreads in the region.

  Resolution Criteria:
  <ul>
    <li>Source of Truth: Cumulative case figures published by the Pan American
      Health Organization or the European Centre for Disease Prevention and
      Control.</li>
    <li>Resolution Date: July 15, 2025, when the mid-July regional report is
      issued.</li>
    <li>Accepted Answer Format: The name of the country in the Americas with
      the highest total reported chikungunya cases.</li>
  </ul>

  Expected Answer Type:
  string (location)

  Relevant passages from retrieved news articles:

  Article 1:
  Title: CDC warns US travellers of growing Dengue threat. Here's what you need to
      know
  Source: www.hindustantimes.com
  Article Publish Date: March 21, 2025
  Relevant Passage: CDC warns of rising dengue fever cases among U.S. travellers,
      reporting 3,484 cases in 2024, an 84% increase from last year. CDC cited a
      "record number" of cases reported among travellers in 2024, totalling 3,484
      cases. This marked an 84 percent surge compared to the previous year. "This
      trend is expected to continue with increased dengue activity in endemic areas in
      2025," the CDC stated in its warning. Dengue remains prevalent in certain
      regions of the States. The virus is being actively transmitted in U.S.
      territories, including Puerto Rico and the U.S. Virgin Islands, where outbreaks
      have been declared. Warmer temperatures during the spring and summer months
      create favourable conditions for the spread of the disease. Over the past five
      years, dengue cases have surged worldwide, with the Americas being notably
      affected. Data from the World Health Organization (WHO) reveals that in 2024
      alone, there were 7.6 million reported cases. Among these, 3.4 million were
      confirmed, over 16,000 were classified as severe, and more than 3,000 resulted
      in fatalities. Puerto Rico has been grappling with a sustained dengue outbreak
      since early 2024. The island surpassed the outbreak threshold in February of
      that year, leading to the declaration of a public health emergency in March
      2024, which remains in effect. Puerto Rico recorded 6,291 dengue cases in 2024,
      with more than half of the patients requiring hospitalization. Thirteen
      individuals lost their lives to the virus, according to the CDC data. Similarly,
      the U.S. Virgin Islands declared an outbreak in August 2024, which also remains
      ongoing. Health authorities reported 208 cases in 2024 and an additional 30
      cases in early 2025. The highest numbers of travel-related dengue infections in
      2024 were reported in Florida, California, and New York.

  Article 2:
  Title: Vaccine Against Chikungunya Approved By The FDA. Should You Get It?
  Source: www.forbes.com
  Article Publish Date: November 20, 2023
  Relevant Passage: efficient vector was Aedes aegypti; however, an interesting
      phenomenon occurred in 2005. There was a slight alteration of the virus genome,
      which allowed it to spread more efficiently with a more common mosquito, Aedes
      albopictus. That facilitated a massive pandemic in 2005 on La Reunion island and
      neighboring areas around the Indian Ocean. In 2013, chikungunya arrived in the
      Americas for the first time and it subsequently tore through the Caribbean
      islands. Is The United States At Risk? Yes. Before 2006, chikungunya rarely
      occurred in U.S. travelers. Then between 2006-2013, we had about 28 cases per
      year, but those cases were infected outside the U.S. The situation changed after
      the Caribbean outbreak and chikungunya arrived at our shores in 2014, with
      affected areas in Florida, the U.S. Virgin Islands and more severely in Puerto
```

Rico (over 30,000 suspected cases). The continental U.S. dodged a bullet, though, with fewer cases than feared. It probably helps that we have widespread air conditioning and window screens in our southern states, which reduces contact with mosquitoes. We remain vulnerable, though, since we still have the mosquito vectors, primarily in the central and southeast parts of the United States. How Can I Reduce My Risk? Minimizing risk focuses on avoiding mosquito bites when living in or visiting an area with active spread of chikungunya, including staying indoors in screened areas during the daytime, using bed nets, using insect repellant and wearing long, loose-fitting clothing. By avoiding Aedes mosquitoes, you reduce your risk of infection from chikungunya as well as dengue and zika viruses. Do I Need The Vaccine?

Article 3:
Title: First Chikungunya Vaccine Now FDA Approved – What To Know About The 'Emerging Global Health Threat'
Source: www.forbes.com
Article Publish Date: November 10, 2023
Relevant Passage: severe chikungunya-like adverse reactions following administration of Ixchiq." Big Number 5 million. There have been at least that many chikungunya cases reported globally over the past 15 years, the FDA said. The agency described the virus as an ''emerging global health threat" that ''has spread to new geographical areas causing a rise in global prevalence of the disease." What We Don't Know Health officials and agencies like the World Health Organization warn official infection counts are likely to significantly underestimate the true prevalence of chikungunya. Accurate diagnosis, disease surveillance and reporting can be tricky in some parts of the world on account of funding and capacity within healthcare systems and chikungunya is also ''easy to misdiagnose" on account of causing similar symptoms to other mosquito-borne illnesses like dengue and Zika. What To Watch For Valneva said the vaccine will initially address the ''potential needs" of some 60 million Americans who it says travel to countries where mosquito-borne diseases are endemic each year. This fits in well with its other shots for cholera and Japanese encephalitis aimed at travelers, the company said. Valneva said it will work towards commercializing the shot in the U.S. early next year and work towards securing a vote of approval endorsing the shot from the Centers for Disease Control and Prevention's vaccine advisory committee at the end of February. The FDA is an influential regulator and its go-ahead will likely speed Ixchiq's passage through other regulatory processes globally, particularly in areas where chikungunya is a more pressing concern. Key Background Chikungunya is regularly identified as an emerging threat to global health on account of the debilitating and prolonged disease it can cause. Chikungunya was first identified in Tanzania in 1952 and sporadic outbreaks were later recorded in parts of Africa and Asia. The virus has since spread globally and has been identified on all continents except Antarctica. The economic and social impact of the disease can be devastating -- the Coalition for Epidemic Preparedness Innovations estimates the cost to the Americas alone to be around $185 billion -- and the warming climate, a boon to the mosquitoes that spread the disease, is likely to widen areas at risk. While the virus is more commonly reported among travelers in the U.S. and parts of Europe, local transmission has been documented, suggesting future outbreaks may be possible or that the virus could gain a permanent foothold. Further Reading First Vaccine For Chikungunya

Article 4:
Title: Dengue fever cases rising in popular spring break locations, CDC alerts
Source: www.foxnews.com
Article Publish Date: March 24, 2025
Relevant Passage: is common in the Americas, Africa, the Middle East, Asia and the Pacific Islands, among other countries, according to the CDC. TRAVEL HOT SPOT SEEKS EMERGENCY DECLARATION OVER MASSIVE BUG INFESTATION In 2024, more than 13 million cases were reported in North, Central and South America, as well as in the Caribbean. Local transmission of these outbreaks was reported in California, Texas and Florida last year. Typical symptoms include aches and pains (in the eyes, muscles, joints, or bones), nausea, vomiting and rash -- usually

experienced within two weeks of being bitten. Most people experience symptoms for two to seven days before recovering. CLICK HERE TO SIGN UP FOR OUR HEALTH NEWSLETTER "It's typically a more mild illness, but can be severe, causing headaches, joint pain, fever, abdominal pain and even death," Dr. Mark Fischer, regional medical director of International SOS, a leading medical and security services company, previously told Fox News Digital. There is not currently any medication to treat dengue, according to the CDC. For more Health articles, visit www.foxnews.com/health Infected people are advised to rest, take acetaminophen for pain and fever, stay hydrated and see a doctor. There is a vaccine available for U.S. children between 9 and 16 years of age who have previously tested positive for dengue and are living in areas where the infection is common. CLICK HERE TO GET THE FOX NEWS APP

Article 5:
Title: Latin America: Key Themes To Watch In 2025
Source: seekingalpha.com
Article Publish Date: January 16, 2025
Relevant Passage: Latin America: Key Themes To Watch In 2025 Latin America's aggregate growth will slightly accelerate in 2025, but this overshadows slower growth across most countries. Read more here. Markit 3.25K Follower s (6min) Summary Latin America's aggregate growth will slightly accelerate in 2025, but this overshadows slower growth across most countries. The potential application of tariffs by the incoming US administration would negatively impact trade and weaken many of the region's currencies, while forced repatriation of illegal workers in the US implies a reduction of remittance flows. We expect lower price pressures based on Market Intelligence's global assumption that prices for agriculture-related commodities and oil prices will fall in 2025. In response to US President Donald Trump's proposals on tariffs and deportations, Mexico and most countries in Central America are likely to align with the requests from the new US administration. Here is how we see our key themes for 2025 shaping Latin America's operational and investment environment. Economic angst Latin America's aggregate growth will slightly accelerate in 2025, but this overshadows slower growth across most countries. We project only five This article was written by 3.25K Follower s IHS Markit (Nasdaq: INFO) is a world leader in critical information, analytics and solutions for the major industries and markets that drive economies worldwide. The company delivers next-generation information, analytics and solutions to customers in business, finance and government, improving their operational efficiency and providing deep insights that lead to well-informed, confident decisions. IHS Markit has more than 50,000 key business and government customers, including 80 percent of the Fortune Global 500 and the world's leading financial institutions. Headquartered in London, IHS Markit is committed to sustainable, profitable growth. Comments Recommended For You Related Stocks SymbolLast Price% ChgEWZ--iShares MSCI Brazil ETFILF--iShares Latin America 40 ETFBRF--VanEck Brazil Small-Cap ETFFLN--First Trust Latin America AlphaDEX Fund ETFFBZ--First Trust Brazil AlphaDEX Fund ETF Related Analysis Trending Analysis Trending News

Think step by step about the information provided, reason about uncertainty and put your final answer (in the format asked) in <answer> </answer> tags.
You should also specify your confidence in your answer in <probability> </probability> tags.
The probability should be a number between 0 and 1.

You will be rewarded based on the probability (p) you assign to your answer.
Your answer will be evaluated using the BRIER SCORING RULE which is basically (- (1 - p)^2) if your answer is correct and (- 1 - p^2) if your answer is incorrect.

For example, if p = 0.5, and your answer is incorrect, then your score will be (−1 - 0.5^2) = (−1 - 0.25) = −1.25
whereas if the answer was correct, then your score would be (- (1 - p)^2) = (- (0.5)^2) = −0.25.

Thus, the range of the score is [-2, 0] where your score lies between [-2, -1] if

```
      the answer is incorrect and [-1, 0] if your answer is correct.

  If your answer is correct, your will be REWARDED more if your probability is higher
      whereas if your answer is incorrect, your will be PENALIZED more if your
      probability is higher.
  YOU HAVE TO MAXIMIZE YOUR SCORE.

  Your final answer should be concise (NOT MORE THAN A FEW WORDS LONG) and your
      response SHOULD STRICTLY END with <answer> </answer> tags and <probability>
      </probability> tags.
```

L. Details on Compute and Cost

To improve transparency around data and compute, we report approximate token counts, training steps, and GPU-hours for both SFT and RL. Our curated `OpenForesight` training set contains 52,183 samples. The average sample (just the question without any retrieval) has about 1000 characters and corresponds to roughly 400 tokens under the Qwen3 tokenizer for the question text, yielding approximately 2×10^7 prompt tokens in total.

For SFT, fine-tuning `Qwen3-8B` for 3 epochs took 5 hours on 8 H100 GPUs, corresponding to roughly 40 H100 GPU-hours. RL training is substantially more expensive: Our final run lasted for 5 epochs over the training set, resulting in about 1,300 optimization steps, for an estimated total of $\sim 1,000$ H100 GPU-hours. Including all ablations, we estimate we used $\sim 20,000$ H100 GPU-hours.

Cost. The overall dataset creation process costed us 3000$ with training set costing 2200$ (using DeepSeek-v3) while creating the test set costed 800$ (using o4-mini-high and grok-4.1-fast with search tool).