Differentially Private Online-to-Batch for Smooth Losses

Abstract

1 We develop a new reduction that converts any online convex optimization algorithm
2 suffering $O(\sqrt{T})$ regret into an ϵ-differentially private stochastic convex optimiza-
3 tion algorithm with the optimal convergence rate $\tilde{O}(1/\sqrt{T} + \sqrt{d}/\epsilon T)$ on smooth
4 losses in linear time, forming a direct analogy to the classical non-private "online-
5 to-batch" conversion. By applying our techniques to more advanced adaptive
6 online algorithms, we produce adaptive differentially private counterparts whose
7 convergence rates depend on apriori unknown variances or parameter norms.

1   Introduction

8

9 Solving stochastic convex optimization (SCO) problems forms a core component of training models
10 in machine learning, and is the topic of this paper. The SCO problem is to optimize an objective $\mathcal{L}$:

$$\min_{x \in W} \mathcal{L}(x) = \mathop{\mathbb{E}}_{z \sim P_z} [\ell(x, z)] \tag{1}$$

11 Here, x represents model parameters or weights lying in a convex domain $W \subset \mathbb{R}^d$, P_z is some
12 unknown distribution over examples z and $\ell(x, z)$ represents a loss function we will assume to be
13 convex and smooth in x. Although we do not know P_z, we do know the loss ℓ, and we have access to
14 an i.i.d. dataset $Z = (z_1, \ldots, z_T)$ that may have been obtained via user surveys or volunteer tests.
15 Using this information, we would like to solve the optimization problem (1). The quality of a putative
16 solution $\hat{x}$ is measured by the *suboptimality* gap $\mathcal{L}(\hat{x}) - \mathcal{L}(x_\star)$ for $x_\star \in \text{argmin}_{x \in W} \mathcal{L}(x)$.

17 In addition to solving (1), we also wish to *preserve privacy* for the people who contributed to the
18 dataset Z. To this end, we require our algorithms to be *differentially private* (Dwork et al., 2006;
19 Dwork and Roth, 2014), which means that replacing any one z_t with a different z'_t has a negligible
20 effect on $\hat{x}$. There is a delicate interplay between privacy, dataset size, and solution quality. As T
21 grows, the influence of any individual z_t on $\hat{x}$ decreases, increasing privacy. However, for any finite
22 T, one must necessarily leak *some* information about the dataset in order to achieve a nontrivial
23 $\mathcal{L}(\hat{x}) - \mathcal{L}(x)$. The goal, then, is to minimize $\mathcal{L}(\hat{x}) - \mathcal{L}(x)$ subject to the privacy constraint.

24 This problem has been well-studied in the literature, and by now the optimal tradeoffs are known
25 and achievable[1]. In particular, Bassily et al. (2019) exhibits a polytime algorithm that achieves
26 $\mathcal{L}(\hat{x}) - \mathcal{L}(x_\star) \le \tilde{O}(1/\sqrt{T} + \sqrt{d}/\epsilon T)$ where ϵ is a measure of privacy loss (large ϵ means less
27 private), and moreover they show that this bound is tight in the worst case. Then, Feldman et al.
28 (2020) provides an improved algorithm that obtains the same guarantee in $O(T)$ time. Further work

---

[1]We focus on the harder stochastic optimization problem rather than empirical risk minimization, which is
also well-studied, e.g. (Chaudhuri et al., 2011; Kifer et al., 2012).

on this problem considers assumptions on the geometry (Asi et al., 2021), gradient distributions (Kamath et al., 2021), or smoothness (Bassily et al., 2020; Kulkarni et al., 2021).

All private optimization algorithms we are aware of fall into one of two camps: either they employ some simple pre-processing that "sanitizes" the inputs to a non-private optimization algorithm (e.g. the empirically popular DP-SGD of Abadi et al. (2016)), or they make a careful analysis of the dynamics of their algorithm (e.g. bounding the sensitivity of a single step of stochastic gradient descent). In the former case, the algorithm typically does *not* achieve the optimal convergence rate for stochastic optimization. In the latter case, the algorithm becomes more rigidly tied to the privacy analysis, resulting in delicate "theory-crafted" methods that are less popular in practice.

In contrast, in the non-private setting, there is a simple and general technique to produce stochastic optimization algorithms with optimal convergence guarantees: the *online-to-batch conversion* (Cesa-Bianchi et al., 2004). This method directly converts any *online convex optimization* (OCO)(Shalev-Shwartz, 2011; Hazan, 2019; Orabona, 2019) algorithm into a stochastic optimization algorithm. OCO is a simple and elegant game-theoretic formulation of the optimization problem that has witnessed an explosion of diverse algorithms and techniques , so that this conversion result immediately implies a vast array of practical optimization algorithms. In summary: producing *private* stochastic optimization algorithms with optimal convergence rates is currently delicate and difficult, while producing non-private algorithms is essentially trivial.

Our goal is to rectify this issue. To do so, we produce a new *differentially private* online-to-batch conversion. In direct analogy to the non-private conversion, our method converts any OCO algorithm into a *private* stochastic optimization algorithm. After using our conversion, any OCO algorithm that achieves the optimal regret (the standard measure of algorithm quality in OCO), will automatically achieve the optimal suboptimality gap of $\tilde{O}(1/\sqrt{T} + \sqrt{d}/\epsilon T)$. Our conversion has additional desirable properties: although convexity is required for the guarantee on suboptimality, it is *not* required for the privacy guarantee, meaning that the method can be easily applied to non-convex tasks (e.g. in deep learning). Further, by largely decoupling the privacy analysis from the algorithm design through this reduction, we can leverage the rich literature of OCO to build private algorithms with new *adaptive* guarantees. For two explicit examples, (1) we construct an algorithm guaranteeing $\mathcal{L}(\hat{x}) - \mathcal{L}(x_\star) \leq \tilde{O}(\sigma/\sqrt{T} + \sqrt{d}/\epsilon T)$, where σ is the apriori unknown standard deviation in the gradient $\nabla\ell(w, z)$, and (2), we construct an algorithm guaranteeing $\mathcal{L}(\hat{x}) - \mathcal{L}(x_\star) \leq \tilde{O}(\|\hat{x} - x_1\|/\sqrt{T} + \sqrt{d}/\epsilon T)$, where x_1 is any user-supplied point. This last guarantee may have applications in private *fine tuning* (Li et al., 2022; Yu et al., 2021; Hoory et al., 2021; Kurakin et al., 2022; Mehta et al., 2022), as the bound automatically improves when the algorithm is provided with a good initialization point.

1.1 Preliminaries

Problem setup We define the loss function as $\ell : W \times Z \to \mathbb{R}$ where $W \subseteq \mathbb{R}^d$ is a convex domain and $Z = (z_1, \ldots, z_T)$ is an element of $\mathcal{Z}^T$ for some dataspace $\mathcal{Z}$. We assume Z is an i.i.d. dataset and $z_t \sim P_z$ for some unknown disribution over $\mathcal{Z}$. We then define $\mathcal{L}(x) = \mathbb{E}_{z \sim P_z}[\ell(x, z)]$.

Let $\|\cdot\|$ be a norm on $\mathbb{R}^d$, with dual norm $\|\cdot\|_*$ defined by $\|g\|_* = \sup_{\|x\| \leq 1}\langle g, x\rangle$. By definition, $\langle g, x\rangle \leq \|g\|_*\|x\|$, (*Fenchel-Young's inequality*). We make the following assumptions:

Assumption 1. $\|\cdot\|^2$ is λ-strongly convex: for all $x, y \in \mathbb{R}^d$ and $g \in \partial\|x\|^2$,

$$\|x - y\|^2 \geq \|y\|^2 + \langle g, y - x\rangle + \frac{\lambda}{2}\|y - x\|^2.$$

Assumption 2. W has diameter at most D: $\forall x, y \in W$, $\|x - y\| \leq D$.

Assumption 3. $\ell(x, z)$ is G-Lipschitz in x: $\forall x \in W, z \in Z$, $\|\nabla\ell(x, z)\|_* \leq G$.

Assumption 4. $\ell(x, z)$ is H-smooth in x: $\forall x, y \in W, z \in Z$, $\|\nabla\ell(x, z) - \nabla\ell(y, z)\|_* \leq H\|x - y\|$.

Assumption 5. $\mathbb{E}[\|\nabla\mathcal{L}(x) - \nabla\ell(x, z)\|_*^2] \leq \sigma_G^2$ for all x, z.

Assumption 6. $\mathbb{E}[\|[\nabla\mathcal{L}(x) - \nabla\mathcal{L}(y)] - [\nabla\ell(x, z) - \nabla\ell(y, z)]\|_*^2] \leq \sigma_H^2\|x - y\|^2$ for all x, y, z.

Note that if ℓ is G-Lipschitz and H-smooth in x, then so it $\mathcal{L}$, and Assumption 5 and 6 hold with $\sigma_G \leq 2G$ and $\sigma_H \leq 2H$. Moreover, notice that Assumption 2 - 6 depend on the norm $\|\cdot\|$.

Differential Privacy We now provide a formal definition of our privacy metric, differential privacy (DP). The definition hinges on the notion of *neighboring datasets*: datasets $Z = (z_1, \ldots, z_T)$ and $Z' = (z'_1, \ldots, z'_T)$ in $\mathcal{Z}^T$ are said to be neighbors if $|Z - Z'| \triangleq |\{t \mid z_t \neq z'_t\}| = 1$.

Definition 1 ((ϵ, δ)-DP (Dwork and Roth, 2014)). A randomized algorithm $M : \mathcal{Z}^T \to \mathbb{R}^d$ is (ϵ, δ)-differentially private for $\epsilon, \delta \geq 0$ if for any neighboring $Z, Z' \in \mathcal{Z}^T$ and $S \in \mathbb{R}^d$:

$$\mathcal{P}\{M(Z) \in S\} \leq \exp(\epsilon)\, \mathcal{P}\{M(Z') \in S\} + \delta$$

An alternative definition is *Rényi differential privacy* (RDP), which is a generalization of DP that allows us to compose mechanisms more easily and achieve tighter privacy bounds in certain cases.

Definition 2 ((α, ϵ)-RDP (Mironov, 2017)). A randomized mechanism $M : \mathcal{Z}^T \to \mathbb{R}^d$ is said to be (α, ϵ)-Rényi differentially private for $\alpha > 1, \epsilon \geq 0$ if for any neighboring datasets $Z, Z' \in \mathcal{Z}^T$:

$$D_\alpha(M(Z)||M(Z')) \leq \epsilon$$

where $D_\alpha(P||Q) \triangleq \frac{1}{\alpha-1} \log \mathbb{E}_{x \sim Q} \left(\frac{P(x)}{Q(x)} \right)$.

RDP can be easily converted to the usual (ϵ, δ)-DP as follows (Mironov, 2017): if a randomized algorithm M is (α, ϵ)-RDP, then it is also ($\epsilon + \frac{\log 1/\delta}{\alpha-1}, \delta$)-DP for all $\delta \in (0, 1)$. In particular, if M is ($\alpha, \alpha\rho^2/2$)-RDP for all $\alpha > 1$, then it is also ($2\rho\sqrt{\log(1/\delta)}, \delta$)-DP for all $\delta \geq \exp(-\rho^2)$.

Throughout the paper, we also frequently use the notion of sensitivity:

Definition 3 (Sensitivity). The sensitivity of a function $f : \mathcal{Z}^T \to \mathbb{R}^d$ w.r.t. norm $\|\cdot\|$ is:

$$\Delta_f = \sup_{|Z-Z'|=1} \|f(Z) - f(Z')\|_*.$$

Almost all methods for ensuring differential privacy involve injecting noise whose scale increases with the sensitivity of the output. In other words, small sensitivity implies high privacy.

2 Diffentially Private Online-to-Batch

In this section, we present our main differentially private online-to-batch algorithm. To start, we need to define *online convex optimization* (OCO). OCO is a "game" in which for T rounds, $t = 1, \ldots, T$, an algorithms predicts a parameter $w_t \in W$. It then receives a convex loss $\ell_t : W \to \mathbb{R}$ and pays the loss $\ell_t(w_t)$. The quality of the algorithm is measured by the regret w.r.t. a competitor u, defined as $\text{Regret}_T(u) = \sum_{t=1}^{T} \ell_t(w_t) - \ell_t(u)$.

Online-to-batch algorithms (Cesa-Bianchi et al., 2004) convert OCO algorithms (online learners) into stochastic convex optimization algorithms. In particular, $\beta_1, \ldots, \beta_T > 0$, the anytime online-to-batch conversion (Cutkosky, 2019) defines the t-th loss as $\ell_t(w) = \langle \beta_t \nabla \ell(x_t, z_t), w \rangle$, where $x_t = \sum_{i=1}^{t} \frac{\beta_i w_i}{\beta_{1:t}}$. Throughout this paper, we denote $\beta_{1:t} = \sum_{i=1}^{t} \beta_i$. Convergence of anytime online-to-batch builds on the following key result, and its proof is in Appendix A for completeness.

Theorem 1 (Cutkosky (2019)). *For any sequence of $\beta_t > 0, g_t \in \mathbb{R}^d$, suppose an online learner predicts w_t and receives t-th loss $\ell_t(w) = \langle g_t, w \rangle$. Define $x_t = \sum_{i=1}^{t} \frac{\beta_i w_i}{\beta_{1:t}}$ where $\beta_{1:t} = \sum_{i=1}^{t} \beta_i$. Then for any convex and differentiable $\mathcal{L}$,*

$$\beta_{1:T}(\mathcal{L}(x_T) - \mathcal{L}(u)) \leq \text{Regret}_T(u) + \sum_{t=1}^{T} \langle \beta_t \nabla \mathcal{L}(x_t) - g_t, w_t - u \rangle, \forall u \in \mathbb{R}^d.$$

A tighter bound is possible (Joulani et al., 2020), but the simpler expression above suffices for our analysis. As an immediate result, choosing $\beta_t = 1$ and $g_t = \beta_t \nabla \ell(x_t, z_t)$ satisfies $\mathbb{E}[g_t|x_t] = \beta_t \nabla \mathcal{L}(x_t)$, so $\mathbb{E}[\mathcal{L}(x_T) - \mathcal{L}(u)] \leq \mathbb{E}[\text{Regret}_T(u)]/T$. Therefore, any online learner with sub-linear regret guarantees convergence for the last iterate x_T. Notice that due to the formulation of the anytime online-to-batch, the iterate x_t is *stable*. Consider the case where $\beta_t = 1$ for all t. Then, we have

$\|x_t - x_{t-1}\| = \|w_t - x_{t-1}\|/t \leq D/t$ *regardless of what the online learner does.* This guarantee is significantly stronger than the classical online-to-batch result of Cesa-Bianchi et al. (2004). We would like to take advantage of this stability to design our private online-to-batch algorithm. Intuitively, the algorithm has much lower sensitivity due to the stability of the iterates, which can be exploited to improve privacy.

Our goal will be to make the entire sequence $g_1, \ldots, g_T$ private, which, in turn, makes the entire algorithm private. To do so, we would like to add noise to the g_t's while still having g_t be a good estimate of $\nabla \mathcal{L}(x_t)$. Directly adding noise to the stochastic gradient $\nabla \ell(x_t, z_t)$ (update of DP-SGD) is not a good idea because its sensitivity is $O(1)$ (more specifically $\Delta \leq 2G$ by Lipschitzness). Instead, we express $g_t = \sum_{i=1}^{t} \delta_i$, where $\delta_i = \beta_i \nabla \ell(x_i, z_i) - \beta_{i-1} \nabla \ell(x_{i-1}, z_i)$. Since we assume ℓ is smooth, if we set $\beta_i = 1$ then $\|\delta_i\|_* \leq H \|x_i - x_{i-1}\| \leq DH/i$. As a result, we can privately estimate g_t with error roughly $\tilde{O}(D/t\epsilon)$ using the *tree aggregation mechanism* (Dwork et al., 2010; Chan et al., 2011), an advanced technique that privately estimates running sums, such as our $\sum_{i=1}^{t} \delta_i$. Compared to directly adding noise to $\nabla \ell(x_t, z_t)$, this method adds less noise and thus allows us to achieve the optimal rate. On the other hand, after using these advanced aggregation techniques, g_t is no longer an unbiased estimator of $\beta_t \nabla \mathcal{L}(x_t)$. Thus, we need a more careful analysis for convergence. Moreover, although we mostly discuss the $\beta_t = 1$ case above for intuition, our algorithm is analyzed using the general case $\beta_t = t^k$ for $k \geq 1$. The pseudo-code is presented in Algorithm 1.

Algorithm 1 Differentially-Private Online-to-Batch

1: **Input:** OCO algorithm $\mathcal{A}$ with domain W, positive sequence $\{\beta_t\}$, distribution $\mathcal{D}$, dataset Z.
2: **Initialize:** Set $\beta_0 = 0, x_0 = 0$ and $g_0 = 0$. Set global variable $\mathcal{R} = \{\}$.
3: **for** $t = 1, \ldots, T$ **do**
4:     Get w_t from $\mathcal{A}$ and compute $x_t = (\beta_{1:t-1} x_{t-1} + \beta_t w_t)/\beta_{1:t}$.
5:     Compute gradient difference $\delta_t = \beta_t \nabla \ell(x_t, z_t) - \beta_{t-1} \nabla \ell(x_{t-1}, z_t)$.
6:     Update $g_t = g_{t-1} + \delta_t$ and generate noise $\gamma_t = \text{NOISE}(t)$.
7:     Send $\ell_t(w) = \langle g_t + \gamma_t, w \rangle$ to $\mathcal{A}$ as the t-th loss.

8: **function** NOISE(t)
9:     **Initialize:** Set $k = 0, I_t = \{\}$, $\text{bin}(t)$ be the binary expression of t, and $n = \lfloor \log_2 t \rfloor + 1$.
10:     **for** $i = 1, \ldots, n$ **do**
11:         If $\text{bin}(t)[i] = 1$, update $k = k + 2^{n-i}$ and $I_t = I_t \cup \{k\}$.
12:     Generate noise $\tilde{R}_t \sim \mathcal{D}$, compute $R_t = \sigma_t \tilde{R}_t$, and update $\mathcal{R} = \mathcal{R} \cup \{R_t\}$.
13:     **Return** $\gamma_t = \sum_{i \in I_t} R_i$.

Convergence Following Theorem 1 and Fenchel-Young's inequality, Algorithm 1 satisfies:

$$\beta_{1:T}(\mathcal{L}(x_T) - \mathcal{L}(x^*)) \leq \text{Regret}_T(x^*) + \sum_{t=1}^{T} \langle \beta_t \nabla \mathcal{L}(x_t) - g_t - \gamma_t, w_t - x^* \rangle \qquad (2)$$

$$\leq \text{Regret}_T(x^*) + \sum_{t=1}^{T} D \|\beta_t \nabla \mathcal{L}(x_t) - g_t\|_* + \sum_{t=1}^{T} D \|\gamma_t\|_*. \qquad (3)$$

(3) decomposes the suboptimality gap $\mathcal{L}(x_T) - \mathcal{L}(x^*)$ into three components: (i) regret $\text{Regret}_T(x^*)$, (ii) error associated with variance of g_t, measured by $\|\beta_t \nabla \mathcal{L}(x_t) - g_t\|_*$, and (iii) error from DP mechanism, measured by $\|\gamma_t\|_*$. To get a tight bound, we observe that $\beta_t \nabla \mathcal{L}(x_t) - g_t$ and γ_t are sums of conditionally mean-zero random vectors (Lemma 15 in Appendix A). With a martingale bound in high dimension with general norm (Lemma 13), we can derive the following bounds. In particular, we show (Lemma 15) that if Assumption 1 - 6 hold and set $\beta_t = t^k$, then

$$\mathbb{E}[\|\beta_t \nabla \mathcal{L}(x_t) - g_t\|_*^2] \leq 4(k+1)^2(\sigma_G^2 + D^2 \sigma_H^2)t^{2k-1}/\lambda, . \qquad (4)$$

Moreover, we show (Lemma 16) that if $\mathbb{E}[R_t] = 0$ and $\mathbb{E}[\|R_t\|_*^2] \leq \bar{\sigma}_t^2$, then

$$\mathbb{E}[\|\gamma_t\|_*^2] \leq 2(\max_{i \leq t} \bar{\sigma}_i^2) \log_2(2t)/\lambda. \qquad (5)$$

Privacy The next step is to determine how much noise is sufficient for Algorithm 1 to be RDP. We first make the following assumption on the distribution $\mathcal{D}$.

Definition 4 ((V, α)-RDP distribution). *A distribution $\mathcal{D}$ on $\mathbb{R}^d$ is said to be a (V, α)-RDP distribution on $\|\cdot\|$ if it satisfies that for $R \sim \mathcal{D}$ (i) $\mathbb{E}[R] = 0$, (ii) $\mathbb{E}[\|R\|_*^2] \leq V$, and (iii) for all $\rho > 0$ and $\mu, \mu' \in \mathbb{R}^d$, if $\sigma^2 \geq \|\mu - \mu'\|_*^2/\rho^2$, then $D_\alpha(\sigma R + \mu \| \sigma R + \mu') \leq \alpha\rho^2/2$.*[2]

Remark 2. A standard (V, α)-RDP distribution on the L_2 norm is the multivariate normal distribution. Let $R \sim \mathcal{N}(0, I)$ then it is clear that $\mathbb{E}[R] = 0$ and $\mathbb{E}[\|R\|_2^2] = d$. For the third condition, we can show that for all μ, μ' and $\alpha > 1$, $D_\alpha(\mathcal{N}(\mu, \sigma^2 I)\|\mathcal{N}(\mu', \sigma^2 I)) \leq \alpha\|\mu - \mu'\|_2^2/2\sigma^2$, which is further bounded by $\alpha\rho^2/2$ for all $\sigma^2 \geq \|\mu - \mu'\|_2^2/\rho^2$ (Lemma 18) . Therefore, $\mathcal{N}(0, I)$ is a (d, α)-RDP distribution for all $\alpha > 1$.

As its name suggests, adding noise sampled from RDP distribution is sufficient to make a deterministic algorithm RDP. Consider function $\hat{f}(Z) = f(Z) + \sigma R$, where $R \sim \mathcal{D}$ and $\mathcal{D}$ is a (V, α)-RDP distribution on $\|\cdot\|$. Let Δ be the sensitivity of f w.r.t $\|\cdot\|$. Set $\sigma^2 \geq \Delta^2/\rho^2$, then by Definition 4,

$$D_\alpha(\hat{f}(Z)\|\hat{f}(Z')) = D_\alpha(f(Z) + \sigma R\|f(Z') + \sigma R) \leq \alpha\rho^2/2.$$

Thus, $\hat{f}$ is $(\alpha, \alpha\rho^2/2)$-RDP. Moreover, we can compose RDP mechanisms via the tree aggregation mechanism. Specifically, we set $\beta_t = t^k$ and define the variance σ_t^2 in Algorithm 1 as follows:

$$\sigma_t^2 = \frac{4(k+1)^2}{\rho^2}(G + H\max_{i\in[t]}\|w_i - x_{i-1}\|)^2 \log_2(2T)t^{2k-2}, \tag{6}$$

We assume $\|w_i - x_{i-1}\| \leq D$. Upon substituting (6) into (5), we get $\mathbb{E}[\|R_t\|_*^2] \leq \bar{\sigma}_t^2 \leq V\sigma_t^2$ and:

$$\mathbb{E}[\|\gamma_t\|_*^2] \leq \frac{8(k+1)^2 V(G + DH)^2}{\lambda\rho^2}\log_2^2(2T)t^{2k-2}. \tag{7}$$

The following theorem shows that Algorithm 1 is Rényi differentially private if we define σ_t^2 as in (6). Its proof is presented in Appendix B. Note that the privacy guarantee does *not* require i.i.d. Z.

Theorem 3. *Suppose $\|\cdot\|^2$ is λ-strongly convex, W is bounded by D, ℓ is G-Lipschitz and H-smooth, and $\mathcal{D}$ is a (V, α)-RDP distribution. If $\beta_t = t^k$ and σ_t^2 is as defined in (6), then Algorithm 1 is $(\alpha, \alpha\rho^2/2)$-DP for all datasets Z.*

Main Result. Now we can combine all the previous results to prove the privacy and convergence guarantee of our algorithm.

Theorem 4. *Suppose Assumption 1 - 6 hold, and $\mathcal{D}$ is a (V, α)-RDP distribution. If we set $\beta_t = t^k$ and define σ_t^2 as in (6), then Algorithm 1 is $(\alpha, \alpha\rho^2/2)$-RDP and $\mathbb{E}[\mathcal{L}(x_T) - \mathcal{L}(x^*)]$ is bounded by:*

$$\frac{(k+1)\mathbb{E}[\text{Regret}_T(x^*)]}{T^{k+1}} + \frac{2(k+1)^2 D}{\sqrt{\lambda}}\left(\frac{\sigma_G + D\sigma_H}{\sqrt{T}} + \frac{\sqrt{2V}(G + DH)\log_2(2T)}{\rho T}\right).$$

Moreover, recall that the online learner receives t-th loss $\ell_t(w) = \langle g_t + \gamma_t, w \rangle$. It holds that

$$\mathbb{E}[\|g_t + \gamma_t\|_*^2] \leq 3t^{2k}\left(G^2 + \frac{4(k+1)^2}{\lambda}\left(\frac{(\sigma_G + D\sigma_H)^2}{t} + \frac{2V(G + DH)^2 \log_2^2(2T)}{\rho^2 t^2}\right)\right).$$

Remark 5. As an example, let's consider the Gaussian distribution $\mathcal{N}(0, I)$ on the 2-norm, which is a (d, α)-RDP distribution for all $\alpha > 1$ (Remark 2). For many popular online learners (OSD, OMD, FTRL), if $\mathbb{E}[\|\nabla\ell_t(w_t)\|_*^2] \leq \hat{G}^2$ for all t, then $\mathbb{E}[\text{Regret}_T(x^*)] \leq O(D\hat{G}\sqrt{T})$. Hence, Theorem 4 with $\mathcal{D} = \mathcal{N}(0, I)$ implies that

$$\mathbb{E}[\mathcal{L}(x_T) - \mathcal{L}(x^*)] = O\left(\frac{D(G + D\sigma_H)}{\sqrt{T}} + \frac{\sqrt{d}D(G + DH)\log T}{\rho T}\right).$$

This bound is of $\tilde{O}(1/\sqrt{T} + \sqrt{d}/\rho T)$, which can be translated to an equivalent $(\epsilon, \delta)-$DP bound of $\tilde{O}(1/\sqrt{T} + \sqrt{d\log(1/\delta)}/\epsilon T)$. This bound matches the optimal rate for private stochastic optimization with convex and smooth losses (Bassily et al. (2019)).

---

[2]Here we slightly abuse the notation. For random vectors X, Y, $D_\alpha(X\|Y)$ denotes the Rényi divergence of the underlying distributions of X and Y.

Proof of Theorem 4. From Eq. (3), we have:

$$\mathbb{E}[\mathcal{L}(x_T) - \mathcal{L}(x^*)] \leq \frac{1}{\beta_{1:T}} \mathbb{E}\left[\text{Regret}_T(x^*) + D\sum_{t=1}^{T}(\|\beta_t \nabla \mathcal{L}(x_t) - g_t\|_* + \|\gamma_t\|_*)\right]$$

Recall the bounds of $\mathbb{E}[\|\beta_t \nabla \mathcal{L}(x_t) - g_t\|_*^2]$ and $\mathbb{E}[\|\gamma_t\|_*^2]$ in (4) and (7). By Jensen's inequality, $\mathbb{E}[\|X\|_*] \leq \sqrt{\mathbb{E}[\|X\|_*^2]}$. Moreover, since $\beta_t = t^k$ and $k \geq 1$, it holds that $\beta_{1:T} \geq T^{k+1}/k + 1$, so:

$$\leq \frac{\mathbb{E}[\text{Regret}]}{\beta_{1:T}} + \frac{D}{\beta_{1:T}}\sum_{t=1}^{T}\frac{2(k+1)(\sigma_G + D\sigma_H)t^{k-\frac{1}{2}}}{\sqrt{\lambda}} + \frac{\sqrt{8V}(k+1)(G+DH)\log_2(2T)t^{k-1}}{\sqrt{\lambda}\rho}$$

$$\leq \frac{(k+1)\mathbb{E}[\text{Regret}_T(x^*)]}{T^{k+1}} + \frac{2(k+1)^2 D}{\sqrt{\lambda}}\left(\frac{\sigma_G + D\sigma_H}{\sqrt{T}} + \frac{\sqrt{2V}(G+DH)\log_2(2T)}{\rho T}\right).$$

For the second part of the theorem,

$$\mathbb{E}[\|g_t + \gamma_t\|_*^2] \leq 3\,\mathbb{E}[\|\beta_t \nabla \mathcal{L}(x_t)\|_*^2 + \|g_t - \beta_t \nabla \mathcal{L}(x_t)\|_*^2 + \|\gamma_t\|_*^2]$$

We bound the first term by Lipschitzness, the second by (4), and the third by (7)

$$\leq 3t^{2k}G^2 + \frac{12(k+1)^2(\sigma_G^2 + D^2\sigma_H^2)t^{2k-1}}{\lambda} + \frac{24V(k+1)^2(G+DH)^2\log_2^2(2T)t^{2k-2}}{\lambda\rho^2}$$

$$= 3t^{2k}\left(G^2 + \frac{4(k+1)^2}{\lambda}\left(\frac{(\sigma_G + D\sigma_H)^2}{t} + \frac{2V(G+DH)^2\log_2^2(2T)}{\rho^2 t^2}\right)\right).$$

□

3 The Optimistic Case

In this section, we show that choosing an optimistic online learner (Chiang et al., 2012; Rakhlin and Sridharan, 2013; Steinhardt and Liang, 2014) will accelerate our DP online-to-batch algorithm. Optimistic algorithms are provided with additional "hints" in the form of $\hat{\ell}_t(w) = \langle \hat{g}_t, w\rangle$ as an approximation of the true loss $\ell_t(w) = \langle g_t, w\rangle$, and they can incorporate $\hat{\ell}_t$ to decide w_t. The regret of an optimistic algorithm depends on the quality of hints: if $\hat{g}_t \approx g_t$, then it achieves a low regret. Formally, in this paper, we say an online learning algorithm is *optimistic w.r.t. norm* $\|\cdot\|$ if its regret is the following:

$$\text{Regret}_T(x^*) \leq O\left(D\sqrt{\sum_{t=1}^{T}\|\hat{g}_t - g_t\|_*^2}\right), \tag{8}$$

where D denotes the diameter of the learner's domain.

A common choice of the hint $\hat{g}_t$ is g_{t-1}, the gradient in the last round since intuitively, one could expect $g_{t-1} \approx g_t$ when the loss functions are smooth. In this section, we also follow this choice. Recall that in Algorithm 1, the online learner receives t-th loss $\ell_t(w) = \langle g_t + \gamma_t, w\rangle$, where $g_t = \sum_{i=1}^{t}\delta_i$ is the sum of gradient differences, and γ_t is some noise. Therefore, we define the t-th hint as $\hat{g}_t = g_{t-1} + \gamma_{t-1}$.

Theorem 6. *Suppose Assumption 1 - 4 hold, and $\mathcal{D}$ is a (V, α)-RDP distribution. Set $\beta_t = t^k$ and σ_t^2 as defined in (6), If the online learner is optimistic (satisfying (8)) with t-th gradient $\bar{g}_t = g_t + \gamma_t$ and t-th hint $\hat{g}_t = \bar{g}_{t-1}$, then*

$$\frac{\mathbb{E}[\text{Regret}_T(x^*)]}{\beta_{1:T}} \leq O\left(D(G+DH)\left(1 + \frac{\sqrt{V}\log T}{\sqrt{\lambda}\rho}\right)\frac{1}{T^{3/2}}\right).$$

The proof is in Appendix D. As an immediate corollary, if we further assume Assumption 5 and 6, then Theorem 4 applies. Together with this theorem, they imply that optimistic learners achieve the following convergence rate that is adaptive to the variance:

$$\mathbb{E}[\mathcal{L}(x_T) - \mathcal{L}(x^*)] = O\left(\frac{D(\sigma_G + D\sigma_H)}{\sqrt{T}} + \frac{\sqrt{d}D(G+DH)\log T}{\rho T}\right).$$

 4 The Strongly Convex Case

In this section, we prove that in the case of strong convexity, our algorithm can be improved by regularizing the loss of online learner. If $\mathcal{L}$ is strongly convex, then we can prove a similar result to Theorem 1 (the proof is in Appendix E).

Lemma 7. *Suppose $\mathcal{L}$ is μ-strongly convex w.r.t. $\|\cdot\|$. If we replace $\ell_t(w) = \langle g_t + \gamma_t, w \rangle$ with $\bar{\ell}_t(w) = \ell_t(w) + \frac{\beta_t \mu}{4} \|w - x_t\|^2$ in Algorithm 1, and denote the associated regret by $\overline{\mathrm{Regret}}_T$, then*

$$\beta_{1:T}(\mathcal{L}(x_T) - \mathcal{L}(x^*)) \leq \overline{\mathrm{Regret}}_T(x^*) + \sum_{t=1}^{T} \langle \beta_t \nabla \mathcal{L}(x_t) - g_t - \gamma_t, w_t - x^* \rangle - \frac{\beta_t \mu}{8} \|w_t - x^*\|^2$$

$$\leq \overline{\mathrm{Regret}}_T(x^*) + \sum_{t=1}^{T} \frac{2\|\beta_t \nabla \mathcal{L}(x_t) - g_t - \gamma_t\|_*^2}{\beta_t \mu}.$$

Compared to Lemma 1 and Equation 3, in the strongly convex case, there is an additional term $-\frac{\beta_t \mu}{8} \|w_t - x^*\|^2$, which allows the improved convergence rate:

Theorem 8. *Suppose Assumption 1 - 6 hold, and $\mathcal{D}$ is a (V, α)-RDP distribution. Also suppose $\mathcal{L}$ is μ-strongly convex. Set $\beta_t = t^k$ and σ_t^2 as defined in (6). Then $\mathbb{E}[\mathcal{L}(x_T) - \mathcal{L}(x^*)]$ is bounded by:*

$$\frac{(k+1)\mathbb{E}[\overline{\mathrm{Regret}}_T(x^*)]}{T^{k+1}} + \frac{16(k+1)^3}{\lambda \mu} \left(\frac{(\sigma_G + D\sigma_H)^2}{T} + \frac{2V(G + DH)^2 \log_2^2(2T)}{\rho^2 T^2} \right).$$

Moreover, for all $\bar{g}_t \in \partial \bar{\ell}_t(w_t)$,

$$\mathbb{E}[\|\bar{g}_t\|_*^2] \leq t^{2k} \left(4G^2 + \mu^2 D^2 + \frac{16(k+1)^2}{\lambda} \left(\frac{(\sigma_G + D\sigma_H)^2}{t} + \frac{2V(G + DH)^2 \log_2^2(2T)}{\rho^2 t^2} \right) \right).$$

Remark 9. As an example, again consider the case $\mathcal{D} = \mathcal{N}(0, I)$ with L_2 norm. Online subgradient descent (OSD) with appropriate learning rate on μ_t-strongly convex losses ℓ_t achieves:

$$\mathrm{Regret}_T(u) \leq \sum_{t=1}^{T} \frac{\|g_t\|_2^2}{2\sum_{i=1}^{t} \mu_i},$$

where $g_t \in \partial \ell_t(w_t)$. In our case, $\|\cdot\|_2^2$ is 2-strongly convex and the regularized loss $\bar{\ell}_t$ is $\frac{\beta_t \mu}{2}$-strongly convex, i.e. $\mu_t = \mu t^k/2$ and $\sum_{i=1}^{t} \mu_i = O(\mu t^{k+1})$. Therefore, by Theorem 8,

$$\mathbb{E}[\overline{\mathrm{Regret}}_T(x^*)] \leq O\left(\frac{T^k}{\mu} \left(G^2 + \mu^2 D^2 + \frac{(\sigma_G + D\sigma_H)^2}{T} + \frac{d(G + DH)^2 \log^2 T}{\rho^2 T^2} \right) \right).$$

Consequently,

$$\mathbb{E}[\mathcal{L}(x_T) - \mathcal{L}(x^*)] \leq O\left(\frac{(G + \mu D + D\sigma_H)^2}{\mu T} + \frac{d(G + DH)^2 \log^2 T}{\mu \rho^2 T^2} \right).$$

This again matches the optimal private convergence rates.

Proof of Theorem 8. We have already bounded $\mathbb{E}[\|\beta_t \nabla \mathcal{L}(x_t) - g_t\|_*^2]$ and $\mathbb{E}[\|\gamma_t\|_*^2]$ in (4) and (7) respectively, so

$$\mathbb{E}[\|\beta_t \nabla \mathcal{L}(x_t) - g_t - \gamma_t\|_*^2] \leq 2\mathbb{E}[\|\beta_t \nabla \mathcal{L}(x_t) - g_t\|_*^2 + \|\gamma_t\|_*^2]$$

$$\leq \frac{8(k+1)^2 t^{2k-1}}{\lambda} \left((\sigma_G + D\sigma_H)^2 + \frac{2V(G + DH)^2 \log_2^2(2T)}{\rho^2 t} \right).$$

Upon substituting this into Lemma 7 and replace $\beta_t = t^k$, we get:

$$\beta_{1:T} \mathbb{E}[\mathcal{L}(x_T) - \mathcal{L}(x^*)]$$

$$\leq \mathbb{E}[\overline{\mathrm{Regret}}_T(x^*)] + \sum_{t=1}^{T} \frac{16(k+1)^2 t^{k-1}}{\lambda \mu} \left((\sigma_G + D\sigma_H)^2 + \frac{2V(G + DH)^2 \log_2^2(2T)}{\rho^2 t} \right)$$

$$\leq \mathbb{E}[\overline{\mathrm{Regret}}_T(x^*)] + \frac{16(k+1)^2}{\lambda \mu} \left((\sigma_G + D\sigma_H)^2 T^k + \frac{2V(G + DH)^2 \log_2^2(2T) T^{k-1}}{\rho^2} \right).$$

216 Dividing both sides by $\beta_{1:T} \geq T^{k+1}/(k+1)$ proves the first part of the theorem.

217 For the second part, recall that $\bar{\ell}_t(w) = \langle g_t + \gamma_t, w \rangle + \frac{\beta_t \mu}{4}\|w - x_t\|^2$. Therefore, for all $\bar{g}_t \in \partial \bar{\ell}_t(w)$,

218 $\bar{g}_t = g_t + \gamma_t + \frac{\beta_t \mu}{4}v$, where $v \in \partial \|w_t - x_t\|^2$. We follow the same argument in Theorem 4:

$$\mathbb{E}[\|\bar{g}_t\|_*^2] \leq 4\,\mathbb{E}[\|\beta_t \nabla \mathcal{L}(x_t)\|_*^2 + \|\beta_t \nabla \mathcal{L}(x_t) - g_t\|_*^2 + \|\gamma_t\|_*^2 + \|\tfrac{\beta_t \mu}{4}v\|_*^2]$$

Here $v \in \partial \|w_t - x_t\|^2$. We bound the first term by Lipschitz, the second by (4), and the third by (7).
219 Moreover, by chain rule (Proposition 21), we can show that $\|v\|_* \leq 2D$, so:

$$\leq 4t^{2k}G^2 + \frac{16(k+1)^2(\sigma_G + D\sigma_H)^2 t^{2k-1}}{\lambda}$$
$$+ \frac{32V(k+1)^2(G+DH)^2 t^{2k-2}\log_2^2(2T)}{\lambda\rho^2} + \mu^2 D^2 t^{2k}$$
$$\leq t^{2k}\left(4G^2 + \mu^2 D^2 + \frac{16(k+1)^2}{\lambda}\left(\frac{(\sigma_G + D\sigma_H)^2}{t} + \frac{2V(G+DH)^2\log_2^2(2T)}{\rho^2 t^2}\right)\right).$$

220 $\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\square$

5 Parameter-free Algorithm

222 In this section, we apply Algorithm 1 with a "parameter-free" online learner. These are algorithms
223 that guarantee $\text{Regret}_T(u) \leq \tilde{O}(\|u\|\sqrt{T})$ for all competitors u simultaneously (Orabona and Pál,
224 2016; Cutkosky and Orabona, 2018; Mhammedi and Koolen, 2020). By shifting coordinates, it is
225 possible to obtain $\text{Regret}_T(u) \leq \tilde{O}(\|u - x_0\|\sqrt{T})$ for any pre-specified point x_0. Thus, if $x_0 \approx u$ is
226 some good initialization, perhaps generated by pretraining, this bound yields significantly smaller
227 regret than if we had used the worst-case diameter bound $\|u - x_0\| \leq D$.

228 In order to obtain this refined bound with privacy, we need to make a small modification to our
229 conversion. For simplicity, we focus on Euclidean space with 2-norm, and we assume the distribution
230 $\mathcal{D}$ is in addition sub-Gaussian, i.e.,

$$\mathcal{P}\{\sup_{\|a\|_2=1} \langle R_i, a \rangle \geq \epsilon\} \leq \exp\left(-\frac{\epsilon^2}{2\sigma^2}\right).$$

231 In general, the proof extends to any Banach space and any distribution $\mathcal{D}$ that concentrates on it.

232 In previous analysis (Equation (3)), we roughly bound $\|w_t - x^*\| \leq D$. However, in this section,
233 we come up with a finer high probability bound that maintains a dependence on $\|w_t\|, \|x^*\|$. We
234 then replace the loss $\ell_t(w)$ in Algorithm 1 with a regularized loss $\ell_t(w) + \xi_t\|w\|_2 + \nu_t\|w\|_2^2$, and we
235 show that the new algorithm with regularized loss can achieve a parameter-free bound. The complete
236 proof is presented in Appendix F.

237 **Theorem 10.** *Suppose w.r.t. 2-norm, W is bounded by D and ℓ is G-Lipschitz and H-smooth.*
238 *Suppose $\mathcal{D}$ is (V, α)-RDP distribution and is $\sigma_\mathcal{D}$-sub-Gaussian. If we set $\beta_t = t^3$ (i.e. $k=3$) and set*
239 *σ_t^2 as defined in (6), then with probability at least $1 - \delta$,*

$$\mathcal{L}(x_T) - \mathcal{L}(x^*) \leq \frac{4}{T^4}\left(\text{Regret}_T(x^*) + \sum_{t=1}^T \xi_t(\|w_t\|_2 + \|x^*\|_2) + \nu_t(\|w_t\|_2^2 + \|x^*\|_2^2)\right).$$

240 *where C is a universal constant, $A = 8\sqrt{2}C^2$, $A' = 8\sqrt{d}\sigma_\mathcal{D} C^2$, $\kappa = 1 + DH/G$, and*

$$\xi_t = AG\Phi t^{5/2} + A'(G+DH)\frac{\Phi \log_2(2T)t^2}{\rho}, \ \nu_t = 28AH\Phi t^{5/2}, \ \Phi = \sqrt{\log\frac{20dT\log(2\kappa T)}{\delta}}.$$

241 **Theorem 11.** *Following the assumptions and notations in Theorem 10, if we replace $\ell_t(w)$ in*
242 *Algorithm 1 with regularized loss $\bar{\ell}_t(w) = \ell_t(w) + \xi_t\|w\|_2 + \nu_t\|w\|_2^2$ and denote the associated*
243 *regret as $\overline{\text{Regret}}_t$, then with probability at least $1 - \delta$, $\mathcal{L}(x_T) - \mathcal{L}(x^*)$ is bounded by:*

$$\frac{4\overline{\text{Regret}}_T(x^*)}{T^4} + \frac{8A\|x^*\|(G + 28\|x^*\|H)\Phi}{\sqrt{T}} + \frac{8A'\|x^*\|(G+DH)\Phi\log_2(2T)}{\rho T}.$$

Moreover, with probability at least $1 - \delta$, for all t and for all $w \in W, \bar{g}_t \in \partial \bar{\ell}_t(w)$,

$$\|\bar{g}_t\|_2 \leq Gt^3 + A(2G + 57DH)\Phi t^{5/2} + 2A'(G + DH)\frac{\Phi \log_2(2T)t^2}{\rho}.$$

Remark 12. If $\|\bar{g}_t\|_2 \leq \hat{G}$ for all t, parameter-free algorithms achieve regret bound $\text{Regret}_T(u) = \tilde{O}(\|u\|_2 \hat{G}\sqrt{T})$. Therefore, with $\mathcal{D} = \mathcal{N}(0, I)$, $\mathcal{D}$ is 1-sub-Gaussian and $A' = O(\sqrt{d})$, so Theorem 11 implies that with probability $1 - \delta$,

$$\frac{\overline{\text{Regret}}_T(x^*)}{T^4} = \tilde{O}\left(\frac{\|x^*\|_2 G}{\sqrt{T}} + \frac{\|x^*\|_2(G + DH)}{T} + \frac{\|x^*\|_2\sqrt{d}(G + DH)}{\rho T^{3/2}}\right).$$

Consequently,

$$\mathcal{L}(x_T) - \mathcal{L}(x^*) \leq \tilde{O}\left(\frac{\|x^*\|_2(G + DH)}{\sqrt{T}} + \frac{\|x^*\|_2\sqrt{d}(G + DH)}{\rho T}\right).$$

Proof of Theorem 11. The regularized regret satisfies

$$\overline{\text{Regret}}_T(x^*) = \text{Regret}_T(x^*) + \sum_{t=1}^{T} \xi_t(\|w_t\|_2 - \|x^*\|_2) + \nu_t(\|w_t\|_2^2 - \|x^*\|_2^2).$$

Hence, upon substituting this equation into Theorem 10, we get: with probability at least $1 - \delta$,

$$\mathcal{L}(x_T) - \mathcal{L}(x^*) \leq \frac{4\overline{\text{Regret}}_T(x^*)}{T^4} + \frac{8}{T^4}\sum_{t=1}^{T} \xi_t\|x^*\|_2 + \nu_t\|x^*\|_2^2$$

$$\leq \frac{4\text{Regret}_T(x^*)}{T^4} + \frac{8(AG\Phi\|x^*\|_2 + 28AH\Phi\|x^*\|_2^2)}{\sqrt{T}} + \frac{8A'(G + DH)\Phi \log_2(2T)\|x^*\|}{\rho T}.$$

The second inequality is from $\sum_{t=1}^{T} \xi_t \leq T\xi_T$ because ξ_t is increasing with t (so is ν_t).

For the second part of the theorem, for each fixed t and for all $\bar{g}_t \in \bar{\ell}_t(w_t)$, $\bar{g}_t = g_t + \gamma_t + \xi_t u + 2\nu_t w_t$, where $u \in \partial\|w_t\|_2$ and thus $\|u\|_2 \leq 1$. Therefore,

$$\|\bar{g}_t\|_2 \leq \|g_t - \beta_t \nabla \mathcal{L}(x_t)\|_2 + \|\beta_t \nabla \mathcal{L}(x_t)\|_2 + \|\gamma_t\|_2 + \|\xi_t u\|_2 + \|2\nu_t w\|_2$$

By Lipschitzness, $\|\beta_t \nabla \mathcal{L}(x_t)\|_2 \leq Gt^3$. Since W is bounded, $\|2\nu_t w_t\|_2 \leq 2D\nu_t$. Also, $\|\xi_t u\|_2 \leq \xi_t$. Moreover, we can prove (in Eq. 14 and 17) that for each t, with probability at least $1 - \delta/2T$,

$$\|\beta_t \nabla \mathcal{L}(x_t) - g_t\|_2 \leq 8C^2\Phi\sqrt{\sum_{i=1}^{t} i^4(G + H\|w_i - x_{i-1}\|_2)^2} \leq A\Phi(G + DH)t^{5/2},$$

$$\|\gamma_t\|_2 \leq \frac{A'}{\rho}(G + DH)\Phi \log_2(2T)t^2.$$

Upon taking the union bound for all t and the definition of ξ_t, ν_t, we get the desired bound. $\qquad\square$

6 Conclusion

We have presented a new online-to-batch conversion that produces private stochastic optimization algorithms on smooth losses. Online algorithms achieving the optimal $O(\sqrt{T})$ regret automatically achieve the optimal $\tilde{O}(1/\sqrt{T} + \sqrt{d}/\epsilon T)$ convergence rate. Combining this technique with the literature on online learning can yield new private optimization algorithms.

Limitations: Our algorithm requires smoothness, and unlike some other bounds, we cannot tolerate large H. Removing this restriction would significantly improve the generality of the procedure.

References

Abadi, M., Chu, A., Goodfellow, I., McMahan, H. B., Mironov, I., Talwar, K., and Zhang, L. (2016). Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC conference on computer and communications security*, pages 308–318.

Asi, H., Duchi, J., Fallah, A., Javidbakht, O., and Talwar, K. (2021). Private adaptive gradient methods for convex optimization. In *International Conference on Machine Learning*, pages 383–392. PMLR.

Bassily, R., Feldman, V., Guzmán, C., and Talwar, K. (2020). Stability of stochastic gradient descent on nonsmooth convex losses. *Advances in Neural Information Processing Systems*, 33:4381–4391.

Bassily, R., Feldman, V., Talwar, K., and Thakurta, A. (2019). Private stochastic convex optimization with optimal rates. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, pages 11282–11291.

Bauschke, H. H., Combettes, P. L., et al. (2011). *Convex analysis and monotone operator theory in Hilbert spaces*, volume 408. Springer.

Cesa-Bianchi, N., Conconi, A., and Gentile, C. (2004). On the generalization ability of on-line learning algorithms. *Information Theory, IEEE Transactions on*, 50(9):2050–2057.

Chan, T.-H. H., Shi, E., and Song, D. (2011). Private and continual release of statistics. *ACM Transactions on Information and System Security (TISSEC)*, 14(3):1–24.

Chaudhuri, K., Monteleoni, C., and Sarwate, A. D. (2011). Differentially private empirical risk minimization. *Journal of Machine Learning Research*, 12(3).

Chiang, C.-K., Yang, T., Lee, C.-J., Mahdavi, M., Lu, C.-J., Jin, R., and Zhu, S. (2012). Online optimization with gradual variations. In *Conference on Learning Theory*, pages 6–1.

Cutkosky, A. (2019). Anytime online-to-batch, optimism and acceleration. In *International Conference on Machine Learning*, pages 1446–1454.

Cutkosky, A. and Orabona, F. (2018). Black-box reductions for parameter-free online learning in banach spaces. In *Conference On Learning Theory*, pages 1493–1529.

Dwork, C., McSherry, F., Nissim, K., and Smith, A. (2006). Calibrating noise to sensitivity in private data analysis. In *Theory of cryptography conference*, pages 265–284. Springer.

Dwork, C., Naor, M., Pitassi, T., and Rothblum, G. N. (2010). Differential privacy under continual observation. In *Proceedings of the forty-second ACM symposium on Theory of computing*, pages 715–724.

Dwork, C. and Roth, A. (2014). The algorithmic foundations of differential privacy. *Found. Trends Theor. Comput. Sci.*, 9(3-4):211–407.

Feldman, V., Koren, T., and Talwar, K. (2020). Private stochastic convex optimization: optimal rates in linear time. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing*, pages 439–449.

Hazan, E. (2019). Introduction to online convex optimization. *arXiv preprint arXiv:1909.05207*.

Hoory, S., Feder, A., Tendler, A., Erell, S., Peled-Cohen, A., Laish, I., Nakhost, H., Stemmer, U., Benjamini, A., Hassidim, A., et al. (2021). Learning and evaluating a differentially private pre-trained language model. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 1178–1189.

Jin, C., Netrapalli, P., Ge, R., Kakade, S. M., and Jordan, M. I. (2019). A short note on concentration inequalities for random vectors with subgaussian norm. *arXiv preprint arXiv:1902.03736*.

Joulani, P., Raj, A., György, A., and Szepesvári, C. (2020). A simpler approach to accelerated stochastic optimization: Iterative averaging meets optimism. *Internation Conference on Machine Learning*.

Kamath, G., Liu, X., and Zhang, H. (2021). Improved rates for differentially private stochastic convex optimization with heavy-tailed data. *arXiv preprint arXiv:2106.01336*.

Kifer, D., Smith, A., and Thakurta, A. (2012). Private convex empirical risk minimization and high-dimensional regression. In *Conference on Learning Theory*, pages 25–1. JMLR Workshop and Conference Proceedings.

Kulkarni, J., Lee, Y. T., and Liu, D. (2021). Private non-smooth empirical risk minimization and stochastic convex optimization in subquadratic steps. *arXiv preprint arXiv:2103.15352*.

Kurakin, A., Chien, S., Song, S., Geambasu, R., Terzis, A., and Thakurta, A. (2022). Toward training at imagenet scale with differential privacy. *arXiv preprint arXiv:2201.12328*.

Li, T., Zaheer, M., Reddi, S. J., and Smith, V. (2022). Private adaptive optimization with side information. *arXiv preprint arXiv:2202.05963*.

Mehta, H., Thakurta, A., Kurakin, A., and Cutkosky, A. (2022). Large scale transfer learning for differentially private image classification. *arXiv preprint arXiv:2205.02973*.

Mhammedi, Z. and Koolen, W. M. (2020). Lipschitz and comparator-norm adaptivity in online learning. *Conference on Learning Theory*.

Mironov, I. (2017). Rényi differential privacy. In *2017 IEEE 30th Computer Security Foundations Symposium (CSF)*, pages 263–275. IEEE.

Orabona, F. (2019). A modern introduction to online learning. *arXiv preprint arXiv:1912.13213*.

Orabona, F. and Pál, D. (2016). Coin betting and parameter-free online learning. In Lee, D. D., Sugiyama, M., Luxburg, U. V., Guyon, I., and Garnett, R., editors, *Advances in Neural Information Processing Systems 29*, pages 577–585. Curran Associates, Inc.

Rakhlin, A. and Sridharan, K. (2013). Online learning with predictable sequences. In *Conference on Learning Theory (COLT)*, pages 993–1019.

Shalev-Shwartz, S. (2011). Online learning and online convex optimization. *Foundations and Trends in Machine Learning*, 4(2):107–194.

Steinhardt, J. and Liang, P. (2014). Adaptivity and optimism: An improved exponentiated gradient algorithm. In *International Conference on Machine Learning (ICML)*.

Yu, D., Naik, S., Backurs, A., Gopi, S., Inan, H. A., Kamath, G., Kulkarni, J., Lee, Y. T., Manoel, A., Wutschitz, L., et al. (2021). Differentially private fine-tuning of language models. *arXiv preprint arXiv:2110.06500*.