GOGGLE: Generative Modelling for Tabular Data by Learning Relational Structure

Abstract

Deep generative models learn highly complex and non-linear representations to generate realistic synthetic data. While they have achieved notable success in computer vision and natural language processing, similar advances have been less demonstrable in the tabular domain. This is partially because generative modelling of tabular data entails a particular set of challenges, including heterogeneous relationships, limited number of samples, and difficulties in incorporating prior knowledge. Additionally, unlike their counterparts in image and sequence domain, deep generative models for tabular data almost exclusively employ fully-connected layers, which encode weak inductive biases about relationships between inputs. Real-world data generating processes can often be represented using relational structures, which encode sparse, heterogeneous relationships between variables. In this work, we learn and exploit relational structure underlying tabular data to better model variable dependence, and as a natural means to introduce regularization on relationships and include prior knowledge. Specifically, we introduce GOGGLE, an end-to-end *message passing* scheme that jointly learns the relational structure and corresponding functional relationships as the basis of generating synthetic samples. Using real-world datasets, we provide empirical evidence that the proposed method is effective in generating realistic synthetic data and exploiting domain knowledge for downstream tasks.

1 Introduction

Learning generative models to create synthetic data is an important area in machine learning with many applications. For example, synthetic data can be used to simulate settings where real data is scarce or unavailable (Che et al., 2017; Choi et al., 2017), support better supervised learning by increasing diversity in datasets (Chen et al., 2021), improving robustness and predictive performance (Tremblay et al., 2018; Sehwag et al., 2021), and promoting fairness (van Breugel et al., 2021). In addition, synthetic data is increasingly being used to overcome data usage restrictions while preserving privacy (Jordon et al., 2018; Yoon et al., 2020).

Deep generative models have achieved notable success in approximating complicated, high-dimensional distributions as encountered in computer vision, natural language processing, and more (Nikolenko, 2021). A key contributor to this success is that learning architectures can relatively easily exploit *relational inductive bias* that enhance the learning of joint distributions. Informally, relational inductive biases encode assumptions about the relational structure, which describes variables, and their relationships (Battaglia et al., 2018). For example, image variables (pixels) have high covariance within a local region and relational rules that are invariant across regions—properties which are exploited by kernels in convolutional neural networks (CNN) to better model image distributions (LeCun et al., 1989). Similarly, sequence variables are highly dependent on sequentiality and relational rules are invariant across time-steps—recurrence relations leveraged by recurrent neural networks (RNNs) to capture distributions over time (Hochreiter & Schmidhuber, 1997).

In this work, we hope to exploit similar relational inductive biases to better model tabular data distributions. However, while images and sequences are homogeneous data formats with known relational structure, tabular data commonly contain more heterogeneous relationships (e.g. variables are only correlated with a small subset of other variables), where the exact relational structure is obscured by domain-specific knowledge (Shwartz-Ziv & Armon, 2022). Without an obvious

relational structure, deep generative models almost exclusively employ multilayer perceptrons (MLP) to learn representations on tabular data. This is less than ideal as MLPs encode virtually no relational information—indeed, all variables can interact to determine any other variable's value.

However, this all-to-all relational structure is often unnecessary, the *data generating process* (DGP) of tabular data is better described using sparse relational structures (Koller & Friedman, 2009). Variable dependencies can be more accurately captured by considering them as edges and learning representations over the resulting relational structure. We hypothesize that generative models exploiting the relational structure can more adequately address certain challenges that arise during modelling distributions for tabular data, including ▶ **heterogeneous relationships** between variables, ▶ **smaller datasets**, which are more prone to overfitting, and ▶ the lack of mechanism to incorporate **prior knowledge** that can improve modelling performance.

Contributions. We introduce Generative MOdellinG with Graph LEarning (GOGGLE), an end-to-end framework that learns an approximate relational structure as the foundation of generative modelling. More specifically, we devise a general *message passing* scheme that models tabular data by jointly learning (1) the *relational structure* and (2) the corresponding *functional relationships* (*dependencies*) in the learned structure. To the best of our knowledge, this is the first work to jointly learn the relational structure and the parameters of a generative model to model tabular data. Additionally, we propose regularization on variable dependencies to reduce model overfitting on smaller tabular datasets and propose a simple mechanism to include prior knowledge into the generative process.

We demonstrate the advantages of our approach in a series of experiments on multiple real-world datasets. We employ both qualitative and quantitative approaches to demonstrate that GOGGLE achieves consistent improvements over state-of-the-art benchmarks in generating synthetic data and exploiting prior knowledge for better downstream performance.

2 CHALLENGES IN TABULAR DATA GENERATION

While deep generative models have seen notable success in image and sequence domains, tabular data is ubiquitous in many salient applications, including medicine, finance, and economics. Generative modelling for tabular data presents a distinct set of challenges, which are largely open research questions. Here, we highlight them in turn:

1. **Complicated relational structure.** Tabular data commonly contain heterogeneous relational structures, including sparse dependencies (variables only dependent on a small subset of other variables), and heterogeneous functional relationships (dependencies) between variables (Shwartz-Ziv & Armon, 2022). Unlike in images and sequences, where the relational structures (locality and sequentiality respectively) are better understood (and arguably generalizable), variable dependencies in tabular datasets are domain specific and rarely known.
2. **Overfitting and memorization.** Modern deep generative models are over-parameterized, thus requiring large datasets to learn the underlying distribution without overfitting (Alaa et al., 2021). This is especially demanding on tabular datasets that are smaller and where collection is difficult/expensive. Real-world DGPs are sparse in structure, and we address overfitting concerns by enforcing sparsity in variable dependencies, thus achieving a *regularization* effect by restricting the hypothesis space. Additionally, as variables can only be generated using their neighborhoods, the model is incentivized to find informative neighbors.
3. **Domain knowledge.** In many fields, such as medicine or social sciences, we have rich domain knowledge on dependence between variables, sparsity, or importance of specific variables (i.e. degree of connectivity (Waples & Gaggiotti, 2006)). Incorporating prior knowledge is especially useful in practical settings where we may not have large datasets but can obtain expert knowledge to aid in model learning. As far as we know, this is a capability that is currently lacking in tabular deep generative models. Our generative process takes into account the relational structure, allowing a diverse range of (partial) *domain knowledge* to be incorporated.

A distinction. We emphasize that the goal of our work is not *probabilistic structure discovery*, which aims to discover the *unique* probabilistic graph from observed data (Drton & Maathuis, 2017; Zhou, 2011). As there is generally a set of plausible graphs that have equal likelihood on the training data, such methods make assumptions about the graph type, variable distribution, and functional relations, which are necessary to disambiguate a unique graph. In contrast, the aim of GOGGLE is to learn an

Table 1: **Overview of generative models in the tabular domain.** Comparisons are made on underlying **model class** and deep learning **module**, generative **model distribution** p_θ, and the following desiderata: model is capable of **(1)** generating in-distribution samples, **(2)** regularizing variable dependencies, **(3)** incorporating prior knowledge.

Model	Model Class / Module	Generative model p_θ	(1)	(2)	(3)
\multicolumn{6}{c}{*Non-neural methods*}					
BN	BN / None	$\prod_i^d p_\theta(x_i \| Pa(x_i))$	✓	✓	✓
MM	MM / None	$\sum_{k=1}^K \pi_k \mathcal{N}(\mu_k, \sigma_k; \theta)$	✓	✗	✗
\multicolumn{6}{c}{*Neural methods*}					
CopulaGAN	GAN / MLP		✓	✗	✗
TableGAN	GAN / MLP	$\int p_\theta(x\|z)p(z)\,dz \; ; \; p(z) \in \mathcal{P}_Z$	✓	✗	✗
CTGAN	GAN / MLP		✓	✗	✗
TVAE	VAE / MLP		✓	✗	✗
GOGGLE	VAE / MPNN	$\prod_i^d p_\theta(x_i\|\mathcal{N}(i); G) \; ; \; G \in \mathcal{G}$	✓	✓	✓

approximate relational structure to guide generative modelling, and where any graph belonging to the set is sufficient (see Appendix D).

3   RELATED WORKS

Traditionally, generative modelling was performed through explicit parameterisation and estimation of a joint probability distributions. Examples of this include Bayesian networks (BN) (Young et al., 2009; Kaur et al., 2021), mixture models (MM) (Roberts et al., 1998; Hu et al., 2018) and copulas (CP) (Sun et al., 2019; Patki et al., 2016). These models are limited in more complex distributions, where it is difficult to learn high-dimensional dependencies correctly.

Recent advances in deep generative modelling (including VAEs (Kingma & Welling, 2013), GANs (Goodfellow et al., 2014), normalizing flows (NFs) (Rezende & Mohamed, 2015) have seen models that can generate realistic synthetic data from complex, high-dimensional distributions. Specifically for tabular synthetic data, (Xu et al., 2019) introduced CTGAN and TVAE, which are GAN-based and VAE-based models respectively that tackled many practical issues of modelling tabular data, including multimodality and mixed data types. Similarly, TableGAN (Park et al., 2018) employed a GAN framework with an auxiliary classifier to predict the label of a generated sample. medGAN (Choi et al., 2017) and ehrGAN (Che et al., 2017) are more specialist methods developed for healthcare specifically. Instead of generating synthetic data, neural methods have also been employed to perform data imputation (Gondara & Wang, 2018; Yoon et al., 2018). Perhaps most similar to our work, Kocaoglu et al. (2017) (and its tabular variant (Wen et al., 2021)) learn a causal graph in the representation space to generate synthetic data, but assume access to the true causal graph.

The aforementioned methods resort to MLPs to model complex dependencies in an all-to-all fashion. Additionally, they employ regularization in the weight space (e.g. L2 regularization (Schmidhuber, 2015) and Dropout (Srivastava et al., 2014)) to reduce overfitting. These effects, as we will discover in §5, are unlikely to be optimal for generative performance. The key contribution of this work is in taking a different perspective, and learning the relational structure jointly with deep representation learning modules to improve generative modelling. We provide an overview in Table 1, evaluating related methods based on their ability to address the previously described challenges.

4   GOGGLE: GENERATIVE MODELLING WITH GRAPH LEARNING

4.1   PROBLEM FORMULATION

Generative modelling. Generative modelling for tabular data attempts to uncover a probability distribution p_X over $X \in \mathcal{X} \subseteq \mathbb{R}^d$.[1] We have access to a training dataset $\mathcal{D}$, which consists of N i.i.d. samples $x \sim p_X$. The goal is to learn the parameters θ of a generative model such that the model distribution p_θ is close to p_X. Most deep generative models employ a set of noise variables $Z \in \mathcal{Z} \subseteq \mathbb{R}^q$, which follows a *tractable* distribution $p_Z \in \mathcal{P}_Z$ (e.g. Gaussian distribution). Instead of learning p_X directly, the model learns a mapping $g_\theta : \mathcal{Z} \to \mathcal{X}$ where the transformed variable $g_\theta(z)$ has the same distribution as X. The mapping g_θ can either be a surjective function (as in

---

[1] Generative modelling for high-dimensional datasets, as those encountered in genomics (where d typically > 1000) is outside the scope of this work.

Figure 1: **Key components of GOGGLE Framework.** ① Simultaneous learning of relational structure G_ϕ and F_θ s.t. generative process respects relational structure. ② Injection of prior knowledge and regularization on variable dependence. ③ Synthetic sample generated using $\hat{x} = F_\theta(z; G_\phi)$, $z \sim p_Z$.

GANs (Goodfellow et al., 2014)), a bijective function (as in normalizing flows (Rezende & Mohamed, 2015)), or a stochastic mapping (as in VAEs (Kingma & Welling, 2013)) (Nielsen et al., 2020).

Relational structures as graphs. A graph $G = (X, E)$ is a representation of the relational structure between variables, where X denotes random variables and E edges that encode relationships between variables. The most general type of graph is a *mixed graphs*, which contain both directed and undirected edges, where an undirected edge e.g. $X_i - X_j$ is encoded as two directed edges $X_i \rightarrow X_j$ and $X_j \rightarrow X_i$. Importantly, a graph admits a *sparse* and *compact* representation, which underlies many real-world generative processes (Bullmore & Bassett, 2011; Kwon & Bessler, 2011; Farasat et al., 2015). Specifically, we can say that a variable X_i is only dependent on other variables with directed edges into X_i, $\mathcal{N}(i) = \{X_j : (X_j \rightarrow X_i) \in E\}$. In light of simplicity, we will refer to $\mathcal{N}(i)$ as the neighborhood of X_i. Formally, we can state that each variable is determined by a specific *functional relationship*: $X_i = f_i(\mathcal{N}(i), \varepsilon_i)$, where ε_i is a noise variable.

4.2 OVERVIEW

We hypothesize that sparse, heterogeneous dependencies in a tabular dataset can be more accurately captured through a relational structure. To that end, we propose a novel framework of generative modelling that is guided by an underlying relational structure. While tabular generative models are conventionally constructed with MLPs, we introduce a *message passing* scheme that operates on a learned graph, better capturing heterogeneous variable relationships, and allowing regularization and prior knowledge to be injected through the adjacency matrix. As the underlying structure is not known a priori (or partially observed at best) in realistic settings, we design an end-to-end generative model to learn the relational structure simultaneously with the corresponding functional relationships.

Figure 1 provides a schematic overview of GOGGLE. The four key components are: ▶ **learnable relational structure**, which is parameterized by a graph and represented using a *weighted* adjacency matrix G_ϕ that indicates dependence between variables; ▶ **generative model** $F_\theta(\cdot)$ that maps from noise vector $z \sim p_Z$ such that the transformed variable $F_\theta(z; G_\phi)$ has the same distribution as X. The way the relational structure and the generative model interacts is that the generative model only allows the set of relations deemed important by the learned relational structure G_ϕ to influence the generation of a variable. Additionally, there are the ▶ **loss function** $\mathcal{L}(\cdot)$ and **regularization term** $\mathcal{R}(G_\phi)$ used to train the model and encode prior knowledge, respectively.

4.3 LEARNING THE RELATIONAL STRUCTURE

The process of learning the relational structure entails exploring possible adjacency matrices based on relationships between variables. In the absence of informative prior knowledge, we make the key (but minimal) assumption of *sparsity* (viz. Assumption 1), or that the relational structure is

sparser than a fully-connected graph. Intuitively, one can consider MLPs that represent all-to-all relationships as being described by a *fully-connected* relational structure. The sparsity assumption encourages learning of a sparse structure that also determines the most informative neighborhood that generates each variable with the highest likelihood. When we have some prior knowledge about variable dependencies, we will incorporate it through the adjacency matrix and a regularization term in the loss function.

Assumption 1 (Graph sparsity). *We assume there exists a graph G such that the adjacency matrix $A = \mathcal{A}(G) \in \{0,1\}^{d \times d}$ has at least one instance where $A_{ij} = A_{ji} = 0$, indicating variables X_i and X_j are not connected.*

In our graphs, nodes are random variables and edges denote dependence between them. We represent an undirected edge $X_i - X_j$ as two directed edges, one from $X_i \to X_j$, and one from $X_j \to X_i$. Specifically, we learn the entries in the unnormalized adjacency matrix, $\tilde{G}_\phi \in \mathcal{R}^{d \times d}$, which is then normalized through an element-wise `sigmoid` function to obtain $G_\phi \in [0,1]^{d \times d}$. $G_\phi[i,j]$ represents the strength of the dependence between $X_i \to X_j$. [2]

4.4 LEARNING THE FUNCTIONAL RELATIONSHIPS

The generative process must be consistent with the relational dependencies specified by the learned relational structure G_ϕ. We learn a generative model $F_\theta : \mathcal{Z} \to \mathcal{X}$ by learning the mapping from a tractable noise distribution (that can be easily sampled from) to the data distribution. For the ease of exposition, we can informally say that the generative model describes the set of functional relationships between variables $F_\theta = \{f_1, \cdots, f_d\}$, where each f_i describes how X_i depends on its neighborhood $\mathcal{N}(i)$ in G_ϕ.

Learning challenges. Learning F_θ leads to two challenges. ▶ **Computational complexity:** G_ϕ is continuously updated during training, possibly resulting in different dependencies (different set of d functional relationships) that has to be learned, limiting the scalability of the approach. ▶ **Cycles in the graph:** Consider an undirected edge between two variables $X_i - X_j$. In this example, X_i is in the neighborhood of X_j, and the generation of X_i will have to depend on the values of X_j. The reverse is also true. This highlights that $F_\theta(\cdot)$ should be able to work with potential cycles in the G_ϕ to ensure the functional relationships in the model are faithful to the learned graph.

A flexible parameterization. To address these challenges, we employ a *message passing neural network* (MPNN) as a flexible and expressive parameterisation of the functional relationships model (Gilmer et al., 2017). This scheme addresses the aforementioned challenges by naturally handling cycles in the graph and relaxing the computational burden of learning functional relations by applying a common information propagation procedure. The proposed message passing scheme performs L rounds of message passing and generates each variable $\hat{x}_i$ from an initial embedding $h_i^{(0)}$, which is initialized using the noise term z_i. Each round $l \in [L]$ of message passing is defined in terms of a *message* function $\sigma^{(l)}$, an *aggregation* function $\oplus^{(l)}$ and an *update* function $\gamma^{(l)}$.

During each round l, a message $m_j^{(l)}$ is constructed for each of the variables in the neighborhood $\forall j \in \mathcal{N}(i)$, using the message function $\sigma^{(l)}$:

$$m_j^{(l)} = \sigma^{(l)} \left(h_j^{(l-1)} \right) \tag{1}$$

Then, the aggregation function $\oplus^{(l)}$ combines all incoming messages from the neighborhood through weighing each individual message by the learned weight in G_ϕ:

$$h_{\mathcal{N}(i)}^{(l)} = \oplus^{(l)} \left(\{ G_{j,i} m_j^{(l)}, \forall j \in \mathcal{N}(i) \} \right) \tag{2}$$

The variable embeddings $h_i^{(l)}$ are then updated using the aggregated neighborhood messages and its previous embedding $h_i^{(l-1)}$ through the update function $\gamma^{(l)}$:

$$h_i^{(l)} = \gamma^{(l)} \left(h_{\mathcal{N}(i)}^{(l)}, h_i^{(l-1)} \right) \tag{3}$$

---

[2] One could also interpret $G_\phi[i,j]$ as the probability of an edge existing from $X_i \to X_j$ and obtain a binary adjacency matrix by sampling, where the parameters could be learned through the Gumbel-Softmax trick (Jang et al., 2016).

Figure 2: **Generative architecture.** The generative model is consistent with the learned relational structure by generating each variable using its neighborhood. GOGGLE adopts a VAE architecture with a MPNN to gradually generate synthetic data through L rounds of message passing.

Each round of message passing exploits the relationships and sparsity in the learned structure by generating each variable using solely information from variables it depends on.

We add the variable type as a one-hot encoded vector to the embeddings $h_i \leftarrow \text{concat}[h_i, \mathbb{1}_i]$, where $\mathbb{1}_i$ is the one-hot vector for the variable i and concat is the concatenation function. This enables message function and embedding update function to encode meaningful variable-specific information into messages and embeddings. Using this scheme, the learning problem is drastically simplified from learning d functional relationships in each round to just two message passing functions.

Here, $\sigma^{(l)}$ and $\gamma^{(l)}$ are arbitrary, learnable functions, and $\oplus^{(l)}$ is a permutation-invariant function, including mean, max pooling, or sum. In other words, $F_\theta = \{(\sigma^{(l)}, \gamma^{(l)}, \oplus^{(l)}) \, \forall \, l \in L\}$. The output of the last round is taken to be the generation $\hat{x}_i = h_i^{(L)}$. The number of rounds L of message passing, the choice of $\sigma, \gamma, \oplus$, and the construction of the initial embeddings $h^{(0)}$ are design choices that should be made to suit each task specifically. Additionally, the scheme can be *synchronous*, which is useful when all the variables are being generated jointly, or *asynchronous*, which is more suitable when the variables are being generated sequentially.

4.5 PUTTING IT TOGETHER

We adopt a VAE style architecture (Kingma & Welling, 2013) and perform amortized inference on the initial noise vectors. [3] Specifically, the noise vector is sampled from an encoder $z \sim q(z|x)$ using the standard reparameterization trick $z = \mu + \sigma\varepsilon, \varepsilon \sim \mathcal{N}(0, I)$. The functional relationships model $F_\theta(\cdot)$ plays the role of the decoder to generate $\hat{x} = F_\theta(z; G_\phi) \sim p(x|z)$. The exact design of the method is visually illustrated in Figure 2.

Loss function and regularization. The generative model and learnable graph are jointly trained end-to-end with a combination of the classic ELBO loss function with graph regularization term $\mathcal{R}(G_\theta)$. The training objective is described below, where λ is a hyperparameter controlling the regularization strength.

$$\mathcal{J}(\theta, \phi) = ELBO(X, \hat{X}; \theta, \phi) + \lambda \mathcal{R}(G_\phi)$$
$$= \underbrace{\mathbb{E}_{q(z|x)}[\ln p_\theta(x|z; G_\phi)]}_{\text{Likelihood}} - \underbrace{D_{KL}[q(z|x)||p(z)]}_{\text{KL}} + \underbrace{\lambda \mathcal{R}(G_\theta)}_{\text{Regularisation}} \quad (4)$$

A key advantage of GOGGLE is that we can easily incorporate prior knowledge about the graph through the regularization term $\mathcal{R}(G_\phi)$. This term will encourage the adjacency matrix to have certain characteristics. In general, a sparsity prior $\mathcal{R}(G_\phi) = ||G_\phi||_p$ will reward sparse graphs, and partial knowledge of feature relationships can be encoded through the prior $\mathcal{R}(G_\phi) = ||G_\phi - G_0||_p$, where $|| \cdot ||_p$ denotes the p-norm. We provide a more thorough discussion on the types of prior knowledge that can be incorporated in Appendix B.

Training and generation. We adopt an iterative optimization scheme, where either the generative model or learnable graph is kept frozen, and the other component is updated in turn. We implement

---

[3]We note that while we consider a VAE architecture, the appropriate generative architecture and loss functions (e.g. GANs, normalizing flows) should be designed with the application in mind and such extensions are left for future works.

message construction and embedding update functions using single-layer ReLU-activated MLP. Specifically, $\sigma^{(l)} = ReLU\left(W_m^{(l)} \times h_j^{(l-1)}\right)$ and $\gamma^{(l)} = ReLU\left(W_u^{(l)} \times \text{concat}\left[h_{\mathcal{N}(i)}^{(l)}, h_i^{(l-1)}\right]\right)$. Here, W_m and W_u are weight matrices of their respective MLPs. Additionally, we aggregate messages using the mean, which can be viewed as taking a weighted average over messages from a neighborhood.

We use a standard normal prior for $p_Z = \mathcal{N}(0, I)$. The entries in the adjacency matrix are initialized by sampling from the standard normalization distribution. In practice, we apply a hard threshold on the learned adjacency matrices, where entries < 0.1 are zeroed out (similar to ReLU activation). In the absence of prior knowledge, we impose a sparsity penalty $\mathcal{R}(G_\phi) = ||G_\phi||_1$. Once the training is complete, a synthetic sample can be generated by first sampling a noise vector $z \sim p_Z$ and passing it through the functional relationships model: $\hat{x} = F_\theta(z; G_\phi)$.

4.6 A Remark on Data Augmentation

Moreover, and this might be of independent interest, we show that by using the blueprint presented, we can also construct a generative model that can perform *data augmentation*. We consider data augmentation as the ability to conditionally generate synthetic data when conditioned on *any* variable to be a specific value, i.e. $\hat{x} = F_\theta(z, X_i = x_i; G_\phi)$. To do so, we assume the DGP can be represented by a *directed, acyclic graph* (DAG), meaning that variables are generated sequentially (*asynchronous message passing*), following a topological order π_{G_ϕ} obtained from the learned graph. Specifically, the generation of each variable is described through a structural equation model: $\hat{x}_i = f_i(\hat{\mathcal{N}}_i, z_i)$ (Pearl, 2009). During generation, we can condition specific variables on a particular value to allow sampling from the conditional distribution. We elaborate more on this method in Appendix A.

5 Experiments

The core claim in this work is that exploring relational inductive biases can better capture the sparsity and heterogeneous relationships in tabular data, and consequentially lead to enhanced learning of generative models. We quantitatively evaluate aspects of our method to support this claim:

1. **Synthetic data quality**: *How good is the synthetic data?* §5.1 quantitatively evaluates the characteristics of the synthetic data with respect to a variety of state-of-the-art benchmarks.
2. **Prior knowledge**: *Does prior knowledge improve performance?* §5.2 evaluates whether prior knowledge about variable dependence can improve generation performance.
3. **Gains**: *Why does it work?* §5.3 investigates the dynamics of relational structure learning and generative model, and to what extent the relational structure contributes to performance gains.

In the interest of limited space, we attach additional results in Appendix C. Specifically, we include: 4. **Additional datasets**: evaluating synthetic data performance on 6 more datasets; 5. **t-SNE and graph visualizations**: t-SNE visualization on synthetic datasets to qualitatively investigate quality (Van der Maaten & Hinton, 2008); we also examine the graphs learned in our experiments; 6. **Sensitivity analysis**: to better evaluate the performance of our method on different dataset sizes and number of features; 7. **Data augmentation**: assesses an alternative implementation of our method to perform data augmentation.

Benchmarks. We compare against state-of-the-art tabular synthetic data models, including Bayesian Networks (BN) (Pearl, 2011) and GAN-based models: CTGAN (Xu et al., 2019) and TableGAN (Park et al., 2018); VAE-based models: TVAE (Patki et al., 2016); and normalising flows NFLOW (Rezende & Mohamed, 2015).

Datasets. Following the experiment design in recent works (Patki et al., 2016; Xu et al., 2019), we employ 8 real-world datasets from the UCI machine learning repository (Dua & Graff, 2017), and 2 datasets from the BN-Repository (Koller & Friedman, 2009). We employ datasets with different number of samples (ranging from 569 to 581012) and different feature counts (ranging from 12 to 168) to gain a better understanding of our method's performance profile.

We provide additional information about benchmarks, datasets, hyperparameters, and evaluation methods in Appendix B. For all results, we average performance over 10 runs and report mean $\pm$ std in our results.

Table 2: **Diversity, fidelity, and utility of synthetic data.** Bold indicates the best performance.

	Dataset	Adult	Breast	Covertype	Credit
Diversity (the higher the better)	BN	0.63 ± 0.04	0.59 ± 0.02	$\mathbf{0.62 \pm 0.02}$	0.68 ± 0.03
	CTGAN	0.61 ± 0.01	0.38 ± 0.01	0.59 ± 0.04	0.63 ± 0.09
	TableGAN	0.59 ± 0.01	0.35 ± 0.06	0.63 ± 0.04	0.61 ± 0.06
	TVAE	0.60 ± 0.05	0.48 ± 0.02	$\mathbf{0.62 \pm 0.07}$	0.53 ± 0.03
	NFLOW	0.62 ± 0.01	0.53 ± 0.02	0.58 ± 0.02	0.66 ± 0.05
	GOGGLE	$\mathbf{0.66 \pm 0.02}$	$\mathbf{0.64 \pm 0.01}$	0.62 ± 0.06	$\mathbf{0.73 \pm 0.07}$
Fidelity (the lower the better)	BN	0.57 ± 0.03	0.55 ± 0.01	$\mathbf{0.67 \pm 0.03}$	0.58 ± 0.02
	CTGAN	0.67 ± 0.05	0.80 ± 0.02	0.81 ± 0.06	0.59 ± 0.02
	TableGAN	0.69 ± 0.02	0.81 ± 0.02	0.78 ± 0.06	0.65 ± 0.03
	TVAE	0.73 ± 0.03	0.72 ± 0.01	0.74 ± 0.06	0.77 ± 0.02
	NFLOW	0.69 ± 0.01	0.70 ± 0.04	0.79 ± 0.05	0.54 ± 0.01
	GOGGLE	$\mathbf{0.56 \pm 0.03}$	$\mathbf{0.49 \pm 0.02}$	0.69 ± 0.03	$\mathbf{0.52 \pm 0.02}$
Utility (the higher the better)	BN	$\mathbf{0.01 \pm 0.00}$	-0.01 ± 0.00	-0.03 ± 0.00	0.02 ± 0.00
	CTGAN	-0.03 ± 0.00	-0.26 ± 0.08	-0.32 ± 0.02	-0.11 ± 0.02
	TableGAN	-0.03 ± 0.00	-0.32 ± 0.15	-0.37 ± 0.03	-0.21 ± 0.07
	TVAE	-0.05 ± 0.00	-0.07 ± 0.01	0.00 ± 0.00	-0.05 ± 0.00
	NFLOW	0.00 ± 0.00	-0.02 ± 0.00	-0.10 ± 0.02	-0.02 ± 0.00
	GOGGLE	$\mathbf{0.01 \pm 0.00}$	$\mathbf{0.02 \pm 0.00}$	$\mathbf{0.00 \pm 0.00}$	$\mathbf{0.04 \pm 0.01}$

5.1 EVALUATION OF SYNTHETIC DATA

To assess the quality of synthetic data, we observe three desiderata (similar to (Yoon et al., 2019; Xu et al., 2019)): ▶ **diversity**—samples should be distributed to cover the real data. We evaluate using the three-dimensional metric (α-precision, β-recall, authenticity) proposed in (Alaa et al., 2021), reporting their average. ▶ **fidelity**—samples should be indistinguishable from the real data. We report the AUROC performance of three post-hoc classifiers to distinguish real and generated samples. Finally, ▶ **utility**—samples should be just as useful as the real data on predictive tasks (i.e. train-on-synthetic, test-on-real) (Esteban et al., 2017). Utility is evaluated based on average AUROC change of three downstream prediction models trained on synthetic data relative to real data.

As indicated in Table 2, GOGGLE consistently generates higher diversity and higher fidelity synthetic data in comparison to benchmarks. This improvement is especially noticeable on smaller datasets (i.e. breast and credit). In this regime, conventional generative models will overfit to the limited $\mathcal{D}_{train}$, whereas GOGGLE exploits sparsity to achieve better generalization performance. We note that BN emerge as our strongest competitors in this setting (also noted in (Xu et al., 2019)), frequently out-performing deep generative models. The logical hypothesis is that BN generalize well to smaller datasets due to their stricter assumptions on the underlying graph, adding a strong regularization effect. However, on larger-scale datasets, learning a high-quality BN is more difficult. GOGGLE, however, maintains superior performance on larger, more complex datasets as our assumptions are less restrictive. On the utility aspect, indicates superior predictive performance on all datasets. Remarkable, the predictive scores on GOGGLE's synthetic data are very close to those on real data.

5.2 GENERATION WITH PRIOR KNOWLEDGE

Next, we investigate whether incorporating partial knowledge through the relational structure can lead to enhanced performance. We evaluate on ECOLI an MAGIC, where we know the true underlying graph a-prior. Specifically, we investigate three settings: ▶ **zero knowledge** $GOGGLE_0$, where no domain knowledge is used, ▶ **partial knowledge** $GOGGLE_{50}$, where 50% of edges are known (by randomly sub-sampling 50% of the edges), and ▶ **complete knowledge** $GOGGLE_{100}$ where the complete graph is known. We are interested in evaluating in each setting when different amounts of data are available to train a model. We visually depict the effect of prior knowledge on synthetic data quality in Figure 3.

As the ground truth generative model is a Bayesian network, it is encouraging to see that our method achieves comparable performance to BN methods. Notably, GOGGLE, even with partial knowledge, achieves significant performance gain when no prior knowledge is employed. The performance gains from prior knowledge are especially noticeable in lower data regimes, i.e. when $|\mathcal{D}_{train}| < 500$ samples. This highlights a key advantage of our model—to the best of our knowledge, it is the first generative model that can leverage prior knowledge to generate more realistic synthetic samples.

Table 3: **Ablation study.** Bold indicates the best performance.

	Adult Diversity	Adult Fidelity	Adult Utility	Credit Diversity	Credit Fidelity	Credit Utility
GOGGLE-ER	0.41 ± 0.07	0.81 ± 0.05	-0.54 ± 0.08	0.46 ± 0.03	0.71 ± 0.03	-0.05 ± 0.01
GOGGLE-COV	0.53 ± 0.06	0.74 ± 0.05	-0.07 ± 0.01	0.55 ± 0.04	0.67 ± 0.07	-0.03 ± 0.01
GOGGLE-BN	0.56 ± 0.04	0.69 ± 0.05	-0.05 ± 0.01	0.41 ± 0.09	0.67 ± 0.04	-0.06 ± 0.01
GOGGLE-DENSE	0.49 ± 0.09	0.69 ± 0.04	-0.14 ± 0.03	0.56 ± 0.03	0.62 ± 0.08	-0.07 ± 0.01
GOGGLE-NMP	0.53 ± 0.07	0.72 ± 0.08	-0.15 ± 0.03	0.60 ± 0.04	0.65 ± 0.05	-0.03 ± 0.00
GOGGLE	$\mathbf{0.66 \pm 0.02}$	$\mathbf{0.58 \pm 0.03}$	$\mathbf{0.01 \pm 0.00}$	$\mathbf{0.73 \pm 0.07}$	$\mathbf{0.52 \pm 0.02}$	$\mathbf{0.04 \pm 0.01}$

Figure 3: **Prior knowledge and generation.** ECOLI **(top row)** and MAGIC **(bottom row)**.

5.3 ABLATION STUDY

GOGGLE is designed with the joint learning of both graph and functional relationships model. Having empirically demonstrated strong overall results, an immediate question is how important the dynamics of the two parts are for performance. Specifically, we consider the performance gain due to joint learning over learning the two parts separately. This includes the case where a graph is first learned separately: (1) sparse graph initialized using a sparse Erdos-Renyi random graph, with 10% connectivity (**GOGGLE-ER**) (Erdős et al., 1960), (2) initialized using cross-correlation matrix between variables (**GOGGLE-COV**), (3) learnt using the PC algorithm (**GOGGLE-BN**) (Spirtes & Glymour, 1991). We also consider the case (4) when a graph is not learned but initialised as a fully connected dense graph (**GOGGLE-DENSE**); and (5) when the functional relationships model is replaced by a predictor that generates each variable using its neighborhood (**GOGGLE-NMP**). We perform an ablation study to report the performance achieved by each of these settings in Table 3.

We empirically observe that, the joint learning of both components is crucial to achieve consistently good performance. More specifically, we note that GOGGLE-ER achieves the worst performance across all settings. This is expected as the graph is randomly initialized. GOGGLE-COV learns an undirected graph, and only considers first order dependencies, leading to worse performance, while GOGGLE-BN learns a directed graph, which is too restrictive an inductive bias if incorrect. GOGGLE-DENSE employs a fully connected graph, and is equivalent to MLP-based generative models. While it achieved better fidelity on Credit, it is prone to overfit, resulting in lower diversity and utility scores. Lastly, GOGGLE-NMP generates each variable using only its immediate neighbors and ignores information from variables more than *1*-hop away, leading to worse performance.

6 DISCUSSION

In summary, we proposed GOGGLE, a novel tabular data generative model that jointly learns the relational structure and functional relationships through a message passing scheme to better capture the sparsity and heterogeneous relationships in tabular data. The explicit use of relational structure to guide generation allows prior knowledge and regularization on variable dependencies to be directly modelled. **Limitations and future work.** In this work, we focus on tabular data regime, where $d < 100$, future works can focus on higher-dimensional tabular data (e.g. genomics) or time series, where graphs are often used to model temporal correlations. Additionally, while we propose learning a graph in the input space, a direction for future research is to extend the approach to learning graphs in the representation space.

ETHICS AND REPRODUCIBILITY STATEMENT

Ethics statement. This paper addresses a fundamental and well-established problem in ML. Synthetic data has the potential for social good, by allowing unfettered access to otherwise private data, an aspect which should be explored in future works. However, we provide a word of caution as synthetic data will inherit potential bias (if any) in the original dataset and inclusion of incorrect prior knowledge can lead to unintended downstream effects.

Reproducibility statement. We detailed exact implementation details, including dataset preprocessing, implementation of benchmark methods, architecture design, hyperparameter tuning, and evaluation methods in Section 4, Section 5, and Appendix B. We will release code upon acceptance of the paper for the camera-ready version.

REFERENCES

Ahmed M Alaa, Boris van Breugel, Evgeny Saveliev, and Mihaela van der Schaar. How faithful is your synthetic data? sample-level metrics for evaluating and auditing generative models. *arXiv preprint arXiv:2102.08921*, 2021.

Onureena Banerjee, Laurent El Ghaoui, and Alexandre d'Aspremont. Model selection through sparse maximum likelihood estimation for multivariate gaussian or binary data. *The Journal of Machine Learning Research*, 9:485–516, 2008.

Peter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, et al. Relational inductive biases, deep learning, and graph networks. *arXiv preprint arXiv:1806.01261*, 2018.

Jock A Blackard and Denis J Dean. Comparative accuracies of artificial neural networks and discriminant analysis in predicting forest cover types from cartographic variables. *Computers and electronics in agriculture*, 24(3):131–151, 1999.

Edward T Bullmore and Danielle S Bassett. Brain graphs: graphical models of the human brain connectome. *Annual review of clinical psychology*, 7:113–140, 2011.

Zhengping Che, Yu Cheng, Shuangfei Zhai, Zhaonan Sun, and Yan Liu. Boosting deep learning risk prediction with generative adversarial networks for electronic health records. In *2017 IEEE International Conference on Data Mining (ICDM)*, pp. 787–792. IEEE, 2017.

Richard J Chen, Ming Y Lu, Tiffany Y Chen, Drew FK Williamson, and Faisal Mahmood. Synthetic data in machine learning for medicine and healthcare. *Nature Biomedical Engineering*, 5(6): 493–497, 2021.

David Maxwell Chickering. Optimal structure identification with greedy search. *Journal of machine learning research*, 3(Nov):507–554, 2002.

Edward Choi, Siddharth Biswal, Bradley Malin, Jon Duke, Walter F Stewart, and Jimeng Sun. Generating multi-label discrete patient records using generative adversarial networks. In *Machine learning for healthcare conference*, pp. 286–305. PMLR, 2017.

CKCN Chow and Cong Liu. Approximating discrete probability distributions with dependence trees. *IEEE transactions on Information Theory*, 14(3):462–467, 1968.

Paulo Cortez, António Cerdeira, Fernando Almeida, Telmo Matos, and José Reis. Modeling wine preferences by data mining from physicochemical properties. *Decision support systems*, 47(4): 547–553, 2009.

Terrance DeVries and Graham W Taylor. Dataset augmentation in feature space. *arXiv preprint arXiv:1702.05538*, 2017.

Mathias Drton and Marloes H Maathuis. Structure learning in graphical modeling. *Annual Review of Statistics and Its Application*, 4:365–393, 2017.

Dheeru Dua and Casey Graff. UCI machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.

Conor Durkan, Artur Bekasov, Iain Murray, and George Papamakarios. Neural spline flows. *Advances in neural information processing systems*, 32, 2019.

Paul Erdős, Alfréd Rényi, et al. On the evolution of random graphs. *Publ. Math. Inst. Hung. Acad. Sci*, 5(1):17–60, 1960.

Cristóbal Esteban, Stephanie L Hyland, and Gunnar Rätsch. Real-valued (medical) time series generation with recurrent conditional gans. *arXiv preprint arXiv:1706.02633*, 2017.

Alireza Farasat, Alexander Nikolaev, Sargur N Srihari, and Rachael Hageman Blair. Probabilistic graphical models in modern social network analysis. *Social Network Analysis and Mining*, 5(1): 1–18, 2015.

Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *International conference on machine learning*, pp. 1263–1272. PMLR, 2017.

Lovedeep Gondara and Ke Wang. Mida: Multiple imputation using denoising autoencoders. In *Pacific-Asia conference on knowledge discovery and data mining*, pp. 260–272. Springer, 2018.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

David Heckerman, Dan Geiger, and David M Chickering. Learning bayesian networks: The combination of knowledge and statistical data. *Machine learning*, 20(3):197–243, 1995.

Clara Higuera, Katheleen J. Gardiner, and Krzysztof J. Cios. Self-Organizing Feature Maps Identify Proteins Critical to Learning in a Mouse Model of Down Syndrome. *PLOS ONE*, 10(6):e0129126, June 2015. ISSN 1932-6203. doi: 10.1371/journal.pone.0129126. URL https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0129126. Publisher: Public Library of Science.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Hans Hofmann. Statlog (german credit data) data set. *UCI Repository of Machine Learning Databases*, 53, 1994.

Jingchen Hu, Jerome P Reiter, and Quanli Wang. Dirichlet process mixture models for modeling and generating synthetic versions of nested categorical data. *Bayesian Analysis*, 13(1):183–200, 2018.

Michael Jahrer. Porto seguro's safe driver prediction, 2019. URL https://www.kaggle.com/c/porto-seguro-safe-driver-prediction/discussion/44629.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. *arXiv preprint arXiv:1611.01144*, 2016.

James Jordon, Jinsung Yoon, and Mihaela Van Der Schaar. Pate-gan: Generating synthetic data with differential privacy guarantees. In *International conference on learning representations*, 2018.

Dhamanpreet Kaur, Matthew Sobiesk, Shubham Patil, Jin Liu, Puran Bhagat, Amar Gupta, and Natasha Markuzon. Application of bayesian networks to generate synthetic health data. *Journal of the American Medical Informatics Association*, 28(4):801–811, 2021.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Murat Kocaoglu, Christopher Snyder, Alexandros G Dimakis, and Sriram Vishwanath. Causal-gan: Learning causal implicit generative models with adversarial training. *arXiv preprint arXiv:1709.02023*, 2017.

Ron Kohavi et al. Scaling up the accuracy of naive-bayes classifiers: A decision-tree hybrid. In *Kdd*, volume 96, pp. 202–207, 1996.

Daphne Koller and Nir Friedman. *Probabilistic graphical models: principles and techniques*. MIT press, 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25, 2012.

Dae-Heum Kwon and David A Bessler. Graphical methods, inductive causal inference, and econometrics: A literature review. *Computational Economics*, 38(1):85–106, 2011.

Yann LeCun, Bernhard Boser, John S Denker, Donnie Henderson, Richard E Howard, Wayne Hubbard, and Lawrence D Jackel. Backpropagation applied to handwritten zip code recognition. *Neural computation*, 1(4):541–551, 1989.

Nicolai Meinshausen and Peter Bühlmann. High-dimensional graphs and variable selection with the lasso. *The annals of statistics*, 34(3):1436–1462, 2006.

Didrik Nielsen, Priyank Jaini, Emiel Hoogeboom, Ole Winther, and Max Welling. Survae flows: Surjections to bridge the gap between vaes and flows. *Advances in Neural Information Processing Systems*, 33:12685–12696, 2020.

Sergey I Nikolenko. *Synthetic data for deep learning*, volume 174. Springer, 2021.

Noseong Park, Mahmoud Mohammadi, Kshitij Gorde, Sushil Jajodia, Hongkyu Park, and Youngmin Kim. Data synthesis based on generative adversarial networks. *Proceedings of the VLDB Endowment*, 11(10):1071–1083, 2018.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

Neha Patki, Roy Wedge, and Kalyan Veeramachaneni. The synthetic data vault. In *2016 IEEE International Conference on Data Science and Advanced Analytics (DSAA)*, pp. 399–410. IEEE, 2016.

Judea Pearl. *Causality*. Cambridge university press, 2009.

Judea Pearl. Bayesian networks. 2011.

Jonas Peters and Peter Bühlmann. Structural intervention distance for evaluating causal graphs. *Neural computation*, 27(3):771–799, 2015.

Danilo Rezende and Shakir Mohamed. Variational inference with normalizing flows. In *International conference on machine learning*, pp. 1530–1538. PMLR, 2015.

Stephen J Roberts, Dirk Husmeier, Iead Rezek, and William Penny. Bayesian approaches to gaussian mixture modeling. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 20(11):1133–1142, 1998.

Juliane Schäfer and Korbinian Strimmer. A shrinkage approach to large-scale covariance matrix estimation and implications for functional genomics. *Statistical applications in genetics and molecular biology*, 4(1), 2005.

Jürgen Schmidhuber. Deep learning in neural networks: An overview. *Neural networks*, 61:85–117, 2015.

Marco Scutari, Phil Howell, David J Balding, and Ian Mackay. Multiple quantitative trait analysis using bayesian networks. *Genetics*, 198(1):129–137, 2014.

Vikash Sehwag, Saeed Mahloujifar, Tinashe Handina, Sihui Dai, Chong Xiang, Mung Chiang, and Prateek Mittal. Robust learning meets generative models: Can proxy distributions improve adversarial robustness? *arXiv preprint arXiv:2104.09425*, 2021.

Shohei Shimizu, Takanori Inazumi, Yasuhiro Sogawa, Aapo Hyvärinen, Yoshinobu Kawahara, Takashi Washio, Patrik O Hoyer, and Kenneth Bollen. Directlingam: A direct method for learning a linear non-gaussian structural equation model. *The Journal of Machine Learning Research*, 12: 1225–1248, 2011.

Ravid Shwartz-Ziv and Amitai Armon. Tabular data: Deep learning is not all you need. *Information Fusion*, 81:84–90, 2022.

Peter Spirtes and Clark Glymour. An algorithm for fast recovery of sparse causal graphs. *Social science computer review*, 9(1):62–72, 1991.

Peter Spirtes, Clark N Glymour, Richard Scheines, and David Heckerman. *Causation, prediction, and search*. MIT press, 2000.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

W Nick Street, William H Wolberg, and Olvi L Mangasarian. Nuclear feature extraction for breast tumor diagnosis. In *Biomedical image processing and biomedical visualization*, volume 1905, pp. 861–870. SPIE, 1993.

Yi Sun, Alfredo Cuesta-Infante, and Kalyan Veeramachaneni. Learning vine copula models for synthetic data generation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 5049–5057, 2019.

Jonathan Tremblay, Aayush Prakash, David Acuna, Mark Brophy, Varun Jampani, Cem Anil, Thang To, Eric Cameracci, Shaad Boochoon, and Stan Birchfield. Training deep networks with synthetic data: Bridging the reality gap by domain randomization. In *Proceedings of the IEEE conference on computer vision and pattern recognition workshops*, pp. 969–977, 2018.

Ioannis Tsamardinos, Laura E Brown, and Constantin F Aliferis. The max-min hill-climbing bayesian network structure learning algorithm. *Machine learning*, 65(1):31–78, 2006.

Boris van Breugel, Trent Kyono, Jeroen Berrevoets, and Mihaela van der Schaar. Decaf: Generating fair synthetic data using causally-aware generative networks. *Advances in Neural Information Processing Systems*, 34, 2021.

Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.

Robin S Waples and Oscar Gaggiotti. Invited review: What is a population? an empirical evaluation of some genetic methods for identifying the number of gene pools and their degree of connectivity. *Molecular ecology*, 15(6):1419–1439, 2006.

Bingyang Wen, Luis Oliveros Colon, KP Subbalakshmi, and Rajarathnam Chandramouli. Causal-tgan: Generating tabular data using causal generative adversarial networks. *arXiv preprint arXiv:2104.10680*, 2021.

Lei Xu and Kalyan Veeramachaneni. Synthesizing tabular data using generative adversarial networks. *arXiv preprint arXiv:1811.11264*, 2018.

Lei Xu, Maria Skoularidou, Alfredo Cuesta-Infante, and Kalyan Veeramachaneni. Modeling tabular data using conditional gan. *Advances in Neural Information Processing Systems*, 32, 2019.

Jinsung Yoon, James Jordon, and Mihaela Schaar. Gain: Missing data imputation using generative adversarial nets. In *International conference on machine learning*, pp. 5689–5698. PMLR, 2018.

Jinsung Yoon, Daniel Jarrett, and Mihaela Van der Schaar. Time-series generative adversarial networks. *Advances in Neural Information Processing Systems*, 32, 2019.

Jinsung Yoon, Lydia N Drumright, and Mihaela Van Der Schaar. Anonymization through data synthesis using generative adversarial networks (ads-gan). *IEEE journal of biomedical and health informatics*, 24(8):2378–2388, 2020.

Jim Young, Patrick Graham, and Richard Penny. Using bayesian networks to create synthetic data. *Journal of Official Statistics*, 25(4):549, 2009.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *International Conference on Learning Representations*, 2018.

Xun Zheng, Bryon Aragam, Pradeep K Ravikumar, and Eric P Xing. Dags with no tears: Continuous optimization for structure learning. *Advances in Neural Information Processing Systems*, 31, 2018.

Yang Zhou. Structure learning of probabilistic graphical models: a comprehensive survey. *arXiv preprint arXiv:1111.6925*, 2011.

A   DATA AUGMENTATION MODEL

The data augmentation model conditionally generates augmented data, i.e. $\hat{x} = F_\theta(z, X_i = x_i; G_\phi)$. To allow conditioning on any variable during the generation stage, we assume a directed acyclic graph (DAG). This means that variables are generated sequentially, following topological order π_{G_ϕ}, which can be described through a SEM (Pearl, 2009):

$$\hat{x}_i = f_i(\hat{\mathcal{N}}(i), z_i)$$

In contrast to the synthetic data model, the generation of each variable is conditioned on the predicted value of its parents. [4] Each variable is transformed through a specific embedding function $h_i^{(0)} = f_{\theta_i}(\hat{x}_i) \, \forall \, i \in [d]$, where $h_i^{(0)} \in \mathbb{R}^{d_0}$ and we implement f_{θ_i} using a one layer MLP. This is followed by one round of message passing, where the embedding update function is implemented using a single-layer MLP. We aggregate parent embeddings using the mean, equivalent to taking a weighted average:

$$m_j^{(1)} = \sigma_\theta^{(1)}(\cdot) = h_j^{(0)}$$
$$h_{\mathcal{N}(i)}^{(1)} = \oplus^{(1)}(\cdot) = \text{mean}\left(\{G_{j,i} m_j^{(1)}, \, \forall \, j \in \mathcal{N}(i)\}\right)$$
$$\hat{x}_i = \gamma_\theta^{(1)}(\cdot) = \tanh\left(W_u^{(1)} \times h_{\mathcal{N}(i)}^{(1)}\right)$$

The output after message passing is taken to be the prediction of the current variable $\hat{x}_i$. This model is trained using the GAN adversarial loss (eq. (5)). Additionally, we use the continuous DAG penalty introduced in (Zheng et al., 2018) to force a DAG to be recovered:

$$\max_{F_\theta} \min_D \underbrace{\mathbb{E}[\log D(F_\theta(Z; G_\phi)) + \log(1 - D(X))]}_{GAN\,Loss} + \underbrace{\lambda(\text{tr}(\exp(G_\phi \circ G_\phi)) - d)}_{Regularisation} \quad (5)$$

To generate augmented data, we randomly sample a subset of the variables, and for each of which, we sample a conditioning value *uniformly* from the support of that variable, $a \sim \mathcal{U}(\min(X_i), \max(X_i))$. We then generate augmented data by conditioning chosen variables on sampled values, $\hat{x} \sim p(X|X_i = a) = F_\theta(z, X_i = a; G_\phi)$ (Pearl, 2009). We note that this conditional generation corresponds to sampling *out-of-distribution*, as we are sampling from a different distribution that is defined on the same support as the training.

B   IMPLEMENTATION DETAILS

B.1   MODELS AND EVALUATION

Models. All models are implemented in PyTorch (Paszke et al., 2017). The likelihood term is computed using Cross Entropy or MSE Loss for categorical and continuous variables, respectively. We use $d_0 = 3$ for all experiments and $d_1 \in \{32, 64, 128\}$ depending on the complexity of the data. Hyperparameters include batch size $\in \{64, 128, 256\}$, learning rate $\in \{1e-3, 1e-2\}$, and are chosen through cross-validation. The data is split 60-20-20 into train, validation and test sets and reported results are averaged over 10 runs. Training is performed using the Adam (Kingma & Ba, 2014). All experiments are run on an NVIDIA Tesla K40C GPU, taking less than an hour to complete.

For the synthetic data model, we consider regularization penalty $\lambda \in \{1e-3, 1e-2, 1e-1\}$. For data augmentation, we gradually increase the value of λ as optimization proceeds, so that non-DAGs are heavily penalized (similar to (Zheng et al., 2018)). A specific schedule is employed to increase λ: in each stage of the schedule, the objective is optimized with fixed values of λ for t steps, before λ is updated, $\lambda' \leftarrow \alpha * \lambda$, and the process repeats. We consider starting values $\lambda_0 \in \{10, 100, 1000\}$, $\alpha = 10$ and $t = 1000$. The topological ordering of the nodes is obtained by running a topological sort on the adjacency matrix. All models are trained for a maximum of 5000 epochs, with early stopping if no improvements on the validation set for 100 epochs.

Evaluation. We partition the observed dataset $\mathcal{D}$ into a training set $\mathcal{D}_{train}$ and a test set $\mathcal{D}_{test}$, and train generative models on $\mathcal{D}_{train}$. Using the trained models, we generate a synthetic data set $\mathcal{D}_{syn}$,

---

[4]$\mathcal{N}(i) = Pa(i)$, the neighborhood is strictly the set of parent variables due to the DAG.

which has the same number of samples as $\mathcal{D}_{test}$. We then evaluate the aforementioned desiderata on $(\mathcal{D}_{test}, \mathcal{D}_{syn})$. To evaluate **diversity**, we employ the three-dimensional metric, α-precision, β-recall, and authenticity, which assesses whether the samples are realistic, diverse enough to cover the variability in real data, and generalization performance respectively (Alaa et al., 2021). Each metric evaluates a different aspect of synthetic data diversity, and we average the three metrics to obtain a holistic score. **Fidelity** is evaluated by training post-hoc classifiers to distinguish samples from the original and generated datasets. Specifically, we train a two-layer MLP, XGB classifier and GMM classifier and average the classification AUROC. To evaluate **utility**, we report average performance achieved by three downstream prediction models (linear model, two-layer MLP, and XGB model) train on the $\mathcal{D}_{syn}$ and evaluated on $\mathcal{D}_{test}$. We report the change in AUROC of models trained on $\mathcal{D}_{syn}$ and those trained on $\mathcal{D}_{train}$.

B.2 SYNTHETIC DATA BENCHMARKS

In this subsection, we provide further details on the benchmarks we compare against: including Bayesian networks (BN) (Pearl, 2011), GAN-based (Xu et al., 2019), TableGAN (Park et al., 2018) and VAE-based (Xu et al., 2019; Patki et al., 2016) and a normalizing flow NFLOW (Rezende & Mohamed, 2015). Additionally, we also consider data augmentation methods: Gaussian noise InNoise (Krizhevsky et al., 2012); MixUp (Zhang et al., 2018) and SwapNoise (Jahrer, 2019).

BN (Pearl, 2011). We train BN in two stages, where the first stage learns the network structure and the second stage performs learning based on the returned DAG. For structure learning, we consider constraint-based PC algorithm (Spirtes & Glymour, 1991), Hill-Climb algorithm (Heckerman et al., 1995) and Max-Min Hill-Climb (Tsamardinos et al., 2006). Once a DAG is returned, the conditional probabilities are learned through maximum likelihood estimation, where continuous variables are assumed to come from a linear Gaussian conditional probability distribution (CPD) and discrete variables from a discrete CPD.

CTGAN (Xu et al., 2019), TableGAN (Park et al., 2018). For CTGAN, we use an MLP with two ReLU-activated hidden layers to implement the generator. The number of units in each layer, $\in \{128, 256\}$ depending on the complexity of the data. Similarly, we employ an MLP with two ReLU-activated hidden layers to implement the discriminator, where the number of hidden units $\in \{128, 256\}$. The hyperparameters are tuned according to the recommended settings in (Patki et al., 2016). TableGAN is implemented using a Deep Convolution GAN with recommended settings in (Park et al., 2018), where the generator has three deconvolutional layers, and the discriminator has three convolutional layers.

TVAE (Patki et al., 2016). The VAE-based model is implemented with an encoder with two ReLU-activated layers, where the number of units in each layer of the encoder $\in \{128, 256\}$, depending on complexity. The decoder similarly has two hidden layers with dimensionality $\in \{128, 256\}$. We use a d_h dimensional latent space that is normally distributed and a standard normal prior, where $d_h \in \{32, 64\}$.

NFLOW (Rezende & Mohamed, 2015). We implement the normalizing flows using the rational-quadratic transform introduced in (Durkan et al., 2019). Specifically, it is implemented using an MLP with 2, 128-dimensional hidden layers and permutation operations. A standard normal base distribution is employed, and the flow is run with 500 steps.

B.3 DATA AUGMENTATION BENCHMARKS

InNoise (Krizhevsky et al., 2012), MixUp (Zhang et al., 2018), SwapNoise (Jahrer, 2019). For InNoise, we add zero-centered Gaussian noise $\varepsilon \sim N(0, \sigma^2)$ to the inputs, where we consider $\sigma \in \{0.01, 0.1, 1\}$. For SwapNoise, we randomly swap 10% of elements between two inputs. MixUp is implemented by randomly combining two samples $\hat{x} = \lambda x' + (1 - \lambda)x''$, where $x', x'' \sim \mathcal{D}_{train}$ and $\lambda \sim \text{Beta}(0.2, 0.2)$.

DAFS (DeVries & Taylor, 2017). We train an autoencoder, where the encoder and decoder are both implemented as MLPs with two ReLU-activated hidden layers. We take the feature vector at the output of the encoder c_i and randomly apply one of three possible operations (1) add Gaussian noise $\varepsilon \sim (0, \sigma^2)$, (2) interpolation $\lambda(c_j - c_i) + c_i$, or (3) extrapolation $\lambda(c_i - c_j) + c_i$ where $\lambda = 0.5$ as

Table 4: **Experimental datasets.** Description of experimental datasets.

Dataset	Description	Number of instances	Number of features
Adult (Kohavi et al., 1996)	Census data	48842	15
Breast (Street et al., 1993)	Breast cancer	569	32
Covertype (Blackard & Dean, 1999)	Forest cover	581012	54
Credit (Hofmann, 1994)	Credit risk	1000	20
ECOLI (Schäfer & Strimmer, 2005)	Functional genomics	2000	46
MAGIC-IRRI (Scutari et al., 2014)	Plant genetics	2000	64
Red (Cortez et al., 2009)	Wine quality	1599	12
White (Cortez et al., 2009)	Wine quality	4898	12
Mice (Higuera et al., 2015)	Protein expression	1080	82
Musk (Dua & Graff, 2017)	Musk molecules	6598	168

suggested by the authors. Augmented samples x' are then obtained by passing the altered feature vector through the decoder.

B.4 DATASETS

We use 10 datasets in total, including 8 UCI datasets (Dua & Graff, 2017),[5] specifically `Adult`, `Breast`, `Covertype`, `Credit`, `White`, `Red`, `Mice`, `Musk` and 2 Bayesian Network repository datasets (Koller & Friedman, 2009),[6] specifically `ECOLI` and `MAGIC-IRRI`. A summary of the datasets, including dataset description, the dimensionality, and number of samples, is presented in Table 4.

B.5 PRIOR KNOWLEDGE

The use of an explicit graph to guide generation allows for a variety of prior knowledge to be incorporated through the adjacency matrix. Here, we describe a few options of incorporating domain expertise:

- **Sparsity.** The learned graph can be sparse such that variables only depend on a small subset of other variables. Mathematically, $\mathcal{R}(G_\phi) = ||G_\phi||_p$, where $|| \cdot ||_p$ denotes the L_p matrix norm.
- **Dependence.** Partial knowledge about the dependencies between features can be encoded through a graph prior G_0, i.e., $\mathcal{R}(G_\phi) = ||G_\phi - G_0||_p$.
- **Graph types.** Graphs of specific types can be learned. For example, if an undirected graph is assumed, we can employ a symmetric prior $||G_\phi - G_\phi^T||_p$. Alternatively, we can use the DAG penalty (Zheng et al., 2018) to encourage learning a directed, acyclic graph (DAG), $\mathcal{R}(G_\phi) = \mathrm{tr}(\exp(G_\phi \circ G_\phi) - D)$, where $tr(\cdot)$ is the matrix trace and D is the number of variables.
- **Connectivity.** Encourage different patterns of connectivity through penalty on degree of each variable $||D_\phi - D_0||_p$, where $D \in \mathbb{R}^d$ is the degree of each variable.

C ADDITIONAL EXPERIMENTS

In this section, we provide additional results to comprehensively evaluate our proposed methods, specifically:

1. **Additional datasets**: §C.1 evaluates synthetic data performance on 4 additional datasets.
2. **Visualizations**:§C.2 visualizes t-SNE projections on original and synthetic datasets to qualitatively investigate quality and examines learned adjacency matrices.
3. **Sensitivity**: §C.3 investigates performance sensitivities according to data size and feature counts.
4. **Data augmentation**: §C.4 describes the best model performance after data augmentation.

.

---

[5]https://archive.ics.uci.edu/ml/datasets.php
[6]https://www.bnlearn.com/bnrepository/

Table 5: **Diversity, fidelity, and utility of synthetic data.** Bold indicates the best performance.

	Dataset	ECOLI	MAGIC-IRRI	Red	White	Mice	Musk
Diversity (the higher the better)	BN	$\mathbf{0.57 \pm 0.06}$	$\mathbf{0.67 \pm 0.04}$	0.64 ± 0.05	0.63 ± 0.07	$\mathbf{0.63 \pm 0.02}$	0.60 ± 0.06
	CTGAN	0.38 ± 0.06	0.33 ± 0.10	0.45 ± 0.08	0.51 ± 0.03	0.42 ± 0.02	0.51 ± 0.05
	TableGAN	0.38 ± 0.08	0.33 ± 0.07	0.46 ± 0.08	0.53 ± 0.02	0.41 ± 0.04	0.56 ± 0.03
	TVAE	0.45 ± 0.09	0.61 ± 0.02	0.59 ± 0.05	0.61 ± 0.03	0.57 ± 0.03	0.58 ± 0.05
	NFLOW	0.56 ± 0.08	0.62 ± 0.07	0.59 ± 0.04	0.63 ± 0.03	0.54 ± 0.06	0.62 ± 0.08
	GOGGLE	$\mathbf{0.57 \pm 0.05}$	0.63 ± 0.09	$\mathbf{0.69 \pm 0.07}$	$\mathbf{0.67 \pm 0.05}$	$\mathbf{0.63 \pm 0.04}$	$\mathbf{0.65 \pm 0.04}$
Fidelity (the lower the better)	BN	$\mathbf{0.39 \pm 0.07}$	$\mathbf{0.40 \pm 0.03}$	0.56 ± 0.07	$\mathbf{0.58 \pm 0.01}$	0.61 ± 0.04	0.83 ± 0.03
	CTGAN	0.74 ± 0.09	0.73 ± 0.07	0.77 ± 0.09	0.79 ± 0.04	0.72 ± 0.02	0.78 ± 0.06
	TableGAN	0.74 ± 0.02	0.73 ± 0.06	0.77 ± 0.05	0.82 ± 0.07	0.85 ± 0.02	0.77 ± 0.05
	TVAE	0.74 ± 0.02	0.69 ± 0.05	0.67 ± 0.07	0.63 ± 0.05	0.73 ± 0.01	0.79 ± 0.02
	NFLOW	0.70 ± 0.03	0.70 ± 0.08	0.67 ± 0.04	0.73 ± 0.05	0.77 ± 0.05	0.80 ± 0.03
	GOGGLE	0.60 ± 0.03	0.69 ± 0.09	$\mathbf{0.55 \pm 0.03}$	0.65 ± 0.06	$\mathbf{0.60 \pm 0.03}$	$\mathbf{0.73 \pm 0.05}$
Utility (the higher the better)	BN	$\mathbf{0.01 \pm 0.00}$	$\mathbf{0.05 \pm 0.00}$	0.00 ± 0.00	-0.15 ± 0.05	$\mathbf{0.00 \pm 0.00}$	-0.18 ± 0.04
	CTGAN	-0.20 ± 0.03	-0.13 ± 0.01	0.02 ± 0.00	-0.08 ± 0.00	-0.10 ± 0.02	-0.13 ± 0.05
	TableGAN	-0.18 ± 0.06	-0.10 ± 0.05	0.02 ± 0.00	-0.14 ± 0.02	-0.19 ± 0.03	-0.13 ± 0.04
	TVAE	-0.06 ± 0.01	0.00 ± 0.00	-0.07 ± 0.01	-0.02 ± 0.00	-0.07 ± 0.03	$\mathbf{-0.06 \pm 0.02}$
	NFLOW	-0.05 ± 0.01	-0.02 ± 0.00	0.01 ± 0.00	-0.15 ± 0.05	-0.04 ± 0.01	-0.16 ± 0.04
	GOGGLE	-0.02 ± 0.00	0.01 ± 0.00	$\mathbf{0.02 \pm 0.00}$	$\mathbf{-0.01 \pm 0.00}$	$\mathbf{0.00 \pm 0.01}$	-0.12 ± 0.02

| (a) BN | (b) CTGAN | (c) TableGAN | (d) TVAE | (e) NFLOW | (f) GOGGLE |

Figure 4: **t-SNE projection on Breast dataset.**

C.1 ADDITIONAL RESULTS

We assess the quality of synthetic dataset using the same desiderata introduced in §5.1, namely *diversity*, *fidelity*, and *utility*. We use six additional datasets, ECOLI, MAGIC-IRRI, Red, White, Mice, and Musk. The results are reported in Table 5.

We note that BN achieves the best performance on ECOLI and MAGIC-IRRI, which is reasonable as those datasets are generated according to a known Bayesian network, and BN models have a natural advantage. On those two datasets, GOGGLE is able to consistently outperform other deep generative models. On Red and White, GOGGLE achieves superior performance against other benchmarks. On the contrary, BN, our closest competitor, achieve worse performance as the underlying DAG assumptions become too restrictive. Additionally, we highlight that models trained on synthetic data generated by GOGGLE consistently achieves similar performance to those trained on real datasets, indicating strong data utility

C.2 VISUALIZATION OF SYNTHETIC DATA RESULTS

In Figures 4 to 7, we observe that synthetic data generated by GOGGLE exhibit markedly better overlap with the original dataset than other benchmarks using t-SNE for visualization. We note that the GAN-based models, specifically CTGAN and TableGAN exhibit mode collapse behaviour and the TVAE and NFLOW can fail to match the underlying distribution (on ECOLI and Breast, respectively). Additionally, we plot the adjacency matrix of trained models in Figure 8, where a sparsity regularization term was applied to all models to encourage sparsely connected graphs.

We visualize the learned graphs on Credit and Breast in Figure 9. The Breast dataset (Dua & Graff, 2017) contains numeric features extracted from images of a breast mass. We note that the *target* variable (diagnosis of tumor) has a high degree of connectivity, and dependent on various physical properties of the tumor, including *mean perimeter* and *mean compactness*. We similarly observe informative variables identified in the Credit dataset (Dua & Graff, 2017) , where the *account balance* depends on *occupation*, *credit amount*, and *length of current employment*.

Figure 5: **t-SNE projection on Red dataset.**

Figure 6: **t-SNE projection on ECOLI dataset.**

Figure 7: **t-SNE projection on White dataset.**

Figure 8: **Learned adjacency matrices.**

Figure 9: **Learned graphs.**

C.3 SENSITIVITY ANALYSIS

Lastly, we are interested in identifying settings where GOGGLE excel as a generative model. Specifically, we are interested in understanding sensitivities of model performance with respect to the effects of feature counts and number of samples in the dataset. We compare our model against the

Table 6: **Data augmentation**. AUROC on $\mathcal{D}_{test}$ of models trained on augmented data. Bold indicates the best performance.

Dataset	Adult	Breast	Covertype	Credit
Baseline	0.70 ± 0.09	0.96 ± 0.01	0.59 ± 0.13	0.65 ± 0.02
InNoise	0.68 ± 0.05	0.97 ± 0.01	0.61 ± 0.10	0.64 ± 0.03
MixUp	0.66 ± 0.08	0.90 ± 0.01	0.56 ± 0.09	0.65 ± 0.02
SwapNoise	0.65 ± 0.05	0.91 ± 0.01	0.58 ± 0.08	0.63 ± 0.01
FSAug	0.71 ± 0.06	0.96 ± 0.01	0.60 ± 0.13	$\mathbf{0.67 \pm 0.02}$
GOGGLE-SD	0.70 ± 0.05	0.97 ± 0.01	0.60 ± 0.10	0.66 ± 0.01
GOGGLE	$\mathbf{0.72 \pm 0.03}$	$\mathbf{0.98 \pm 0.00}$	$\mathbf{0.62 \pm 0.10}$	$\mathbf{0.67 \pm 0.02}$

(a) Feature Count

(b) Number of Samples

Figure 10: **Sensitivity analysis.** Evaluating synthetic data based on **(left) diversity** (the higher, the better), **(middle) fidelity** (the lower, the better), and **(right) utility** (the higher, the better). Datasets are sorted according to **(a)** increasing feature counts, and **(b)** increasing number of samples.

benchmarks in Figure 10. Here, the datasets are shown on the x-axis and are sorted in order of increasing feature count, and increasing number of samples (see Table 4 for more on datasets). We note that the advantage of GOGGLE is more noticeable when there are less number of samples (i.e., on Breast, Credit and Red). In the regime with larger number of samples, all models exhibit similar performance, although GOGGLE still achieves performance improvements. Furthermore, models achieve similar performance when the number of features is low. However, when the number of features increases, the performance of GAN-based models deteriorate. This is interesting, and a potential logical explanation is that they are overfitting to the training data.

C.4   EVALUATION OF AUGMENTED DATA

We compare popular tabular data augmentation methods by inspecting downstream model performance. Specifically, we generate augmented data $\mathcal{D}_{aug}$ from $\mathcal{D}_{train}$ (and has the same number of samples), train predictive models on the combined $\mathcal{D}_{comb} = \{\mathcal{D}_{train}, \mathcal{D}_{aug}\}$, and evaluate performance on $\mathcal{D}_{test}$. We train four downstream prediction models, including linear model, two-layer MLP, RF classifier, and XGB model and report the averaged performance achieved by the four models. We perform data augmentation on GOGGLE by randomly selecting variables to condition on and sampling uniformly from the marginal support of the variable. In Table 6, we observe that augmented data generated by GOGGLE leads to improved generalization performance across all datasets.

D CONNECTION TO PROBABILISTIC STRUCTURE DISCOVERY

There are several parallels between our work and *probabilistic graph discovery*, which aims to recover the true probabilistic graphical model (PGM) underlying observed data (Zhou, 2011; Drton & Maathuis, 2017). We propose a generative model for tabular data that learns and leverages an underlying graph to improve the performance of data synthesis. Importantly, our model does not recover the true PGM from data if the data is indeed generated by a PGM (i.e. it does not perform PGM structural discovery). Additionally, the message passing computation is not an instance of or an approximation to a probabilistic inference routine. Specifically, we take advantage of the sparse and compact representations of graphical models to learn better generative models, incorporate prior knowledge, and perform conditional generation. We do so by incorporating a graph as explicit structure into the generative process. We summarize the key distinctions between our work and the probabilistic structure learning literature.

The graph learned in GOGGLE encodes conditional dependence structure between variables (global Markov property), in the same sense that PGMs reflect allowed conditional dependencies. The key distinction between our approach and probabilistic structural learners is that we only require an approximate structure. In contrast, structural learners aim to recover unique graphs that are close to the true DGP. This learned graph is used to answer probabilistic inference queries, e.g. $P(Y|X = x)$, which requires the graph to be correct. In order to recover a unique graph, structural learns generally assume certain graph, or distributions, or relationships between variables.

Our objective is to learn an approximate graph that models associational dependence and can guide generation. Therefore, we do not need to make similar assumptions that unnecessarily restrict the class of learnable distributions and can lead to a miss-specified model. Additionally, we emphasize that our proposed method is not designed to perform sampling-based probabilistic inference. Due to the different objectives, we make minimal assumptions on the *graph type*, *variable distribution*, and *functional relations*.

	Probabilistic Graph Discovery	GOGGLE
Commonality	Edges reflect allowed conditional dependencies between variables	
Objective	Recover unique probabilistic graph underlying observed data	Learn approximate graph describing dependencies between variables
Evaluation Metric	Quality of discovered graph: graph distance measure (Peters & Bühlmann, 2015; Shimizu et al., 2011), edge classification metric	Quality of synthetic data: diversity, fidelity, and utility (Alaa et al., 2021)
Application	Probabilistic inference $P(Y|X = x)$	Generate conditional synthetic data $x \sim P_\theta(X)$
Assumptions	Specific graph types (i.e. directed or undirected)	Arbitrary graph types (i.e. mixed, directed, or undirected)
	Distributional assumptions on variables (e.g. Gaussian)	No assumptions on variable distribution
	Assumptions on functional relationships between variables (e.g. Linear with Gaussian additive noise)	No assumptions on functional relationships model
Representative Works	**UGM**: Chow-Liu algorithm (Chow & Liu, 1968), graphical LASSO (Banerjee et al., 2008), neighborhood selection (Meinshausen & Bühlmann, 2006). **DGM**: score-based (Chickering, 2002), constraint-based (Spirtes et al., 2000), hybrid (Tsamardinos et al., 2006)	**Deep generative**: GAN-based (Xu et al., 2019), VAE-based (Xu & Veeramachaneni, 2018). **Non-neural**: BN, mixture models, copula