Dynamic Capability Scoping for Enterprise AI Agents: A Synthetic Dataset and Three-Source Permission Architecture

Halil Burak Noyan [1]

Abstract

Enterprise AI agents are typically granted static credential sets at configuration time, holding every tool the role might need for every task they perform. This persistent over-privilege expands the attack surface. We argue that capability scoping must follow a dynamic least-privilege principle and be treated as a prevention mechanism before a detection one. A credential that does not exist in an agent's context cannot be misused regardless of the agent's reasoning or evasion sophistication. We outline a three-source architecture instantiating this principle: role-based ceilings, a task-context classifier, and policy-derived combination prohibitions creating a layered proactive defense against LLM agent misalignment and misuse cases. The architecture supports both enforcing and observe-only deployment; the latter records agent permission requests inconsistent with task context, producing a behavioral signal usable in misalignment research.

As a first step toward evaluating this architecture, we contribute a synthetic dataset of 600 enterprise task prompts grounded in a multi-department company policy, labeled with minimum required permissions across a 15-permission tool-based taxonomy designed to map directly to deployable credentials or enforceable guardrails. The dataset is constructed via a two-pass pipeline that separates prompt generation from permission labeling to avoid circularity, and is validated against a 60-record/688 decisions human-reviewed sample (Cohen's $\kappa = 0.917$ pre-review and $\kappa = 0.967$ post-review). Iterating between dataset and policy reduced ceiling violations from 46 to 3, a 93% reduction. This doesn't prove architectural performance but shows that synthetic prompt gen-

eration can drive policy refinement when the two are developed together. The dataset, environment specification, and generation pipeline are released to support evaluation of dynamic scoping mechanisms by the broader community.

1. Introduction

Enterprise deployments of AI agents typically grant a static capability envelope at configuration time. A fixed set of tools (file access, code execution, database queries, network calls, external email) are deployed at provision time that the agent holds for every task in its session, building on foundational architecture choices where models learn to invoke external APIs (Schick et al., 2023; Yao et al., 2022). The envelope reflects what the role might ever need, not what any individual task actually requires. We call this gap *context-privilege mismatch*. Preemptively deploying the permissions creates an unnecessary attack surface. A documentation-summarization task with no business reason to make a network call still has `http_request` available, and a compromised or manipulated agent can use any tool that is already deployed on the agent environment or simply exfiltrate them. Recent work on alignment faking (Greenblatt et al., 2024) and frontier-model scheming (Meinke et al., 2024) shows that this is not a theoretical concern. Agents capable of reasoning about monitoring systems can adapt their behavior to evade detection, but they cannot use a credential that does not exist.

Existing approaches (Inan et al., 2023; Rebedea et al., 2023) to agent capability scoping treat the problem as one of input/output filtering or runtime monitoring. Policy-as-Prompt (Kholkar & Ahuja, 2025) automates the translation of design documents into prompt-based classifiers that enforce least privilege at the agent boundary. Output filters and behavioral monitors observe agent actions and intervene when something looks wrong. Although detection mechanisms present a necessary layer of defense, they are reactive countermeasures instead of threat elimination at source. Against agents that reason about monitoring and adapt to evade it, detections have a structural ceiling because the attacker only needs to find one phrasing the monitor misses. Security risk and potential blast radius can be proac-

[1]Independent Researcher, London, United Kingdom. Correspondence to: Halil Burak Noyan <contact@buraknoyan.com>.

Published at the Second Workshop on Agents in the Wild: Safety, Security, and Beyond (AIWILD) at ICML 2026. Copyright 2026 by the author(s).

tively minimized by implementing a dynamic least-privilege methodology. For example, if `http_request` permission does not exist in the agent's context for the current task, a misaligned or compromised agent will lose the most straightforward capability to perform HTTP exfiltration. The attack surface is eliminated at the source, reducing the risk earlier in the cyber kill-chain than detective measures.

Effective capability scoping for AI agents requires multiple complementary layers, in the spirit of the Swiss cheese model of defense in depth (Reason, 1990): a role-based ceiling that constrains an agent to the credentials its function legitimately requires, a task-context classifier that further narrows the permission set to what the current task actually needs, and a policy-derived prohibition layer that eliminates dangerous permission combinations regardless of any individual permission's legitimacy. The third layer specifically targets the *lethal trifecta* (Willison, 2025; Greshake et al., 2023) of private data access, exposure to untrusted content, and external communication, the conditions under which indirect prompt injection (Greshake et al., 2023) enables silent exfiltration. Each layer addresses a unique failure mode: role ceilings cannot distinguish between tasks, task classifiers can be manipulated by injection, and combination prohibitions are deterministic but coarse. Therefore they must be used in combination for effective attack surface minimization. The architecture supports both enforcing and observe-only deployment, described in Section 3.4.

This paper presents the first of two contributions toward evaluating this architecture. We construct a synthetic dataset of 600 enterprise task prompts grounded in a multi-department company policy, labeled with minimum required permissions across a 15-permission taxonomy designed to map either directly to deployable credentials or agent guardrails. During validation, we observed that the two-pass pipeline inherently stress-tests the policy, exposing realistic workflow gaps that the policy fails to authorize. Iterating between the dataset and the policy reduced ceiling violations from 46 to 3 across the dataset, a 93% reduction, demonstrating that synthetic prompt generation can drive policy refinement when the two are co-evolved. We release the dataset, the policy, and the validation results to support future evaluation of the full three-source architecture.

Our threat model consists of several LLM agent nodes deployed in hosts of an enterprise environment which has access to the inference model as well as various tools and capabilities to perform business-level operations on behalf of employees. For simplicity we are not including fully-autonomous service agents due to identity-without-role complications. The company has following departments: Engineering, Data and Analytics, Security, Customer Success, Finance, and Legal and Compliance. Expected workflow of each department is detailed in policy document both

for policy-making and for automated enforcement. Departments have access to the following assets, which can contain business intellectual property, user data, employee information, and security-sensitive data: source code repositories (GitHub), issue tracking and project management (Jira), internal knowledge base (Confluence), customer relationship data (Salesforce), the analytics data warehouse (Snowflake, PostgreSQL), team communication channels (Slack), internal and external email, code execution environments, the public internet (HTTP), and uploaded session files. We are assuming tasks will have no gradual scope creep and discuss this limitation in the Section 6. Threat model assumes the task-context classifier, credential deployment service, and orchestrator are trusted components. Trusting an LLM-based classifier is a stronger assumption than trusting the deterministic orchestrator and credential service, and tightening it is left to future work.

Threat actors we are enumerating are misaligned LLM or a compromised agent. The attacker can attempt to invoke any tool the agent currently holds. The attack vectors within scope are indirect prompt injection, side-task execution, tool-output poisoning, malicious tool definition, LLM supply-chain attacks targeting the agent (as special case of misalignment). The mitigations against the misalignment and misuse are identical in our research context.

2. Related Work

Capability-based security is a methodology rooted in computer science since the 1960s (Dennis & Van Horn, 1966), with foundational work on least privilege (Saltzer & Schroeder, 1975) and systems such as CapDesk (Miller, 2006) and EROS (Shapiro et al., 1999). Classical capability-based systems trust the agent to hold its own credentials and attenuate them when delegating. In LLM agent security, the agent itself must not be trusted. We frame our research on how capability-based security applies to agentic workflows in AI control.

OWASP LLM Top 10 LLM06 (Excessive Agency) (OWASP Foundation, 2025) defines over-privileged agents as a fundamental problem in the AI safety domain. NIST SP 800-207 (Rose et al., 2020) specifies a zero trust architecture which treats each entity as untrusted by default regardless of perimeter. This forms the baseline of our research.

PCAS (Palumbo et al., 2026) proposes a policy compiler that provides an authorization layer based on a policy specification. This is the same idea as the policy enforcement component of our three-source permission scoping architecture detailed in Section 3. The significant difference is that whereas PCAS relies on the Datalog formal policy language, we argue LLM-generated rules compiled from official company policy are more performant and maintainable, in the

spirit of Policy-as-Prompt (Kholkar & Ahuja, 2025).

Siu et al. (2026) outline a framework for the contextual security of LLM agents and point to the utility-security trade-off our overshoot/undershoot metrics measure directly. Our work contributes to that research direction by providing a realistic enterprise prompt dataset that can support evaluation of permission classifiers as one form of contextual defense.

3. Three-Source Architecture

3.1. Role-Based Ceiling

The first source is a deterministic lookup: given the agent's department, return the maximum permission set that role is authorized to hold. An Engineering agent may receive a database read credential because Engineering workflows include database queries; a Legal agent may not, because no Legal workflow in the company policy involves direct database access. The mapping is derived once from the organization's access policy. Source 1 is not a classifier and does no inference at runtime. Its function is to set a hard upper bound that no downstream source can exceed. Source 1 alone cannot distinguish between tasks within the same role: an Engineering agent summarizing a README and an Engineering agent debugging a production incident receive the same ceiling, even though their actual capability needs differ.

In multi-agent and autonomous deployments the agent is not necessarily tied to an employee role, and may have no department at all. We argue these cases should be modeled as service-level principals with their own IAM policies and their own ceilings, structurally identical to department-level ceilings but scoped to the agent's service identity rather than a human role. AWS implements this distinction directly through its IAM principal model (Amazon Web Services, 2024): a principal is any entity (human or service) that can be authenticated and authorized, and ceilings attach to the principal regardless of its type. The Source 1 mechanism is the same in both cases, only the principal that owns the ceiling differs.

3.2. Task-Context Classifier

The second source narrows the role-based ceiling to the permissions the current task actually requires. Given the user's task description and the agent's department context, a fine-tuned multi-label classifier predicts which of the 15 permissions in the taxonomy the task needs. Permissions outside that prediction are denied even when the role ceiling permits them. An Engineering agent asked to summarize a Confluence page receives `confluence_read` and nothing else, despite the role ceiling allowing twelve other tools.

The classifier is a separate component from the agent itself.

The agent does not declare its own required permissions or interact with the permissions classifier in any capacity. A compromised or deceptive agent would fabricate justifications to acquire maximum permissions. Source 2 reasons over the task description independently and produces a prediction the agent cannot influence at runtime. This differs from prior context-aware approaches such as Conseca (Tsai & Bagdasarian, 2025), which generates just-in-time policies per action from trusted context but evaluates the agent's own action attempts. Source 2 instead predicts the full task-required permission set up front from the user's task description.

The classifier outputs confidence scores per permission, and the orchestrator applies asymmetric thresholds based on permission risk: high-risk permissions such as `database_read` or `email_send_external` are only granted at high confidence, while low-risk permissions such as `confluence_read` are granted under lower confidence to avoid breaking common tasks. This dataset is the training input for that classifier; the architecture's empirical performance depends directly on the dataset's quality.

Source 2 has a known weakness due to operating on natural language. An attacker who can influence the task description through prompt injection, document pollution, or context manipulation can make the classifier grant higher permissions. Therefore we claim the task classifier is not a sufficient defense mechanism on its own, and must be complemented by role ceiling and policy based limitations. Source 2 is the most precise of the three mechanisms but also the most susceptible to attacks. A manipulated Source 2 can at worst grant permissions up to the role ceiling, excluding combinations prohibited by Source 3.

3.3. Policy-Based Combination Prohibitions

The third source is a deterministic filter applied to the output of Sources 1 and 2. It removes permission combinations that violate the organization's data handling policy. The motivating threat is the *lethal trifecta* described by Willison (2025): an agent simultaneously holding access to private data, exposure to untrusted content, and the ability to communicate externally is unconditionally exploitable via indirect prompt injection. Source 3 makes the "trifecta" structurally impossible by prohibiting the co-occurrence of permissions that complete it. In Tech-Corp's policy, `database_read` cannot co-occur with `email_send_external` or `http_request`; when Sources 1 and 2 produce such a set, Source 3 removes the external-communication permission.

The prohibition rules can be authored manually from policy documents, but a more scalable approach uses Policy-as-Prompt (Kholkar & Ahuja, 2025) to generate them automatically. A classifier reads the company policy and the

expected workflow descriptions, then derives the set of permission combinations that fall within authorized workflows. Anything outside those combinations is either flagged or denied. This is a dynamic version of Source 3, the rules are not hand-written but inferred from the same policy document the rest of the architecture is grounded in. Updating the policy automatically updates the prohibitions.

Source 3 is a complementary mechanism that prevents inherently insecure workflows from being executed at the policy level. Consider a hypothetical vulnerability management agent with service-level privileges, tasked with a prompt such as "search the internet for CVE-2026-1462 and check if our training pipeline uses the vulnerable Keras library." Such an agent may legitimately have access to model weights and the ability to make HTTP connections, providing a direct path for model weight exfiltration. A deceptive agent could exploit these permissions to execute a side task that bypasses Sources 1 and 2 entirely. Limiting internet access for agents that touch model weights is a policy-level decision that a policy-processing classifier can encode as a concrete prohibition rule.

3.4. Combined Application of the Three-Source Architecture

The three sources combine through intersection: a permission is granted only if Source 1 permits it (within the role ceiling), Source 2 predicts it (the task requires it), and Source 3 does not prohibit it (the combination is policy-compliant).

Each source's contribution can be measured independently by stepping through the layers. A baseline that grants the full department ceiling (Source 1 only) and a configuration that adds the task classifier (Sources 1 and 2) differ in exactly what Source 2 contributes; adding the policy filter on top isolates Source 3. We outline this evaluation as the empirical follow-up to this paper.

The architecture supports two deployment modes. In enforcing mode the orchestrator deploys only the predicted credentials and blocks tool calls outside that set. In observe-only mode it deploys the full role-based ceiling and lets the agent execute against it, but still computes the task-context and policy outputs and emits a structured event whenever the agent invokes a tool that the full system would have denied. Observe-only mode mirrors the permissive-mode pattern of access control systems such as SELinux (Smalley et al., 2001), where policy is evaluated and logged before being enforced, and provides a deployment path that does not expose production workflows to undershoot. It also produces a behavioral signal that complements semantic monitors such as chain-of-thought review or output filtering. We see observe-only deployment as a route by which capability scoping contributes to alignment research, beyond its

direct enforcement role.

4. Synthetic Dataset Construction

4.1. Dataset Overview

The dataset contains 600 enterprise task prompts grounded in a synthetic six-department company policy and labeled with the minimum permissions required from a 15-permission tool-based taxonomy. Prompts are generated through a two-pass pipeline that separates prompt generation from permission labeling to avoid circularity. A 60-record sample (10%) was validated against expert review, achieving Cohen's $\kappa = 0.917$ pre-review and $\kappa = 0.967$ after disagreement resolution. The full dataset, the underlying company policy, the generation and labeling scripts, and the validation outputs are released at https://github.com/0xballistics/mostargate under GPL-3.0.

4.2. The Company Policy

The grounding policy describes a fictional mid-sized SaaS company, *TechCorp*, with six departments: Engineering, Data and Analytics, Security, Customer Success, Finance, and Legal and Compliance. Each department's section in the policy specifies its tooling stack, typical workflows, and external communication patterns. A single-department policy would not exercise the full taxonomy, since no individual role needs every permission. Six departments produce natural coverage of the 15 permissions through workflow diversity rather than synthetic profile construction. The complete policy text is included in the released repository.

4.3. Two Pass Generation Pipeline

The dataset is generated in two passes by separate LLM calls. Pass 1 produces prompts only, given the company policy and a fixed department allocation, with no knowledge of the permission taxonomy. The Pass 1 prompt also injects situational seeds (end-of-quarter crunch, production incidents, ad-hoc executive requests) alongside tone variations and occasional typos to drive prompt diversity, so the dataset reflects the texture of real enterprise messages with the diverse nature of the problems and communication styles. It includes both simple requests and complex multi-stage tasks that require reasoning and chained execution of tools.

Pass 2 takes each prompt and labels it with the minimum required permissions, given the policy, the prompt, and the full 15-permission taxonomy with labeling rules. Pass 2 labels permissions independently of the policy's combination prohibitions explicitly, as those are enforced by Source 3 at inference time, not encoded into the ground-truth labels.

This separation prevents spilling of prompt generation logic

to labeling. A single pass approach would cause the model to produce prompts whose labels reflect how the prompt was phrased rather than what the task genuinely requires.

The Pass 1 department allocation is fixed at 5 Engineering, 4 Customer Success, 3 each for Data and Analytics, Security, and Finance, and 2 Legal per batch of 20 prompts. Allocation is not proportional to headcount, smaller departments produce the highest-value high-sensitivity and external-communication tasks, so they are over-represented relative to size. Thirty batches yield 600 prompts. Generation prompts, labeling rules, and the full pipeline are released in the repository.

4.4. Permission Taxonomy

The 15 permissions can be grouped into five conceptual categories:

- **Code:** `github_read`, `pull_request_create`, `code_execute`

- **Knowledge:** `confluence_read`, `jira_read`, `jira_write`

- **Communication:** `slack_read`, `slack_write`, `email_read`, `email_send_external`

- **Data:** `salesforce_read`, `database_read`, `http_request`

- **Session:** `file_read_uploaded`, `export_file`

These categories are descriptive, not structural — the underlying taxonomy is a flat set of 15 tools.

The taxonomy follows two design rules. First, every permission corresponds to a deployable credential type (e.g. a Slack bot token, a GitHub PAT, a database access certificate) so the classifier output maps directly to what an orchestrator would actually issue at runtime. A grouped permission like `internal_search` cannot be deployed as a single credential and was rejected for this reason. Second, read and write are split wherever the security implications differ: read operations primarily create exfiltration risk, while write operations create persistence and impersonation risk. The split is applied where the company policy distinguishes the two operations as separate workflows; for `database_read` no corresponding write permission is included, because the TechCorp policy does not authorize agents to write to databases under any circumstances.

Each permission is assigned to one of three risk tiers, used by the classifier to apply asymmetric confidence thresholds at inference time: Tier 1 (default deny), Tier 2 (grant with justification), Tier 3 (default permit). Tier assignments do not align with the conceptual categories above — for example, `pull_request_create` is Tier 1 despite belonging to the Code category, and the two Session permissions split across Tier 2 (`export_file`) and Tier 3 (`file_read_uploaded`). The full taxonomy with credential types, risk tiers, and per-department ceilings is defined in `mostargate/constants.py` in the released repository.

4.5. Adaptive Policy Refinement

After the first complete generation run, validation against the department permission ceilings revealed 46 instances where a generated prompt required a permission absent from the requesting department's ceiling. These ceiling violations were not malformed prompts, in fact every flagged prompt described a plausible workflow for the department it was assigned to. The violations indicated that the ceilings, derived from a top-down reading of the company policy, were systematically under-specified relative to realistic enterprise workflows.

The two-pass pipeline made this mismatch visible. Pass 1 generates prompts without knowledge of the permission taxonomy, so it has no incentive to stay within ceiling boundaries. The prompts it produces reflect what employees in the policy's described departments would plausibly ask for, regardless of what the ceiling permits. When Pass 2's labels disagreed with the ceiling, the disagreement was diagnostic: either the prompt was unrealistic, or the ceiling was incomplete. We found the latter dominated.

Each violation was reviewed against the company policy and the relevant department's stated workflows. Five resolutions emerged: three ceiling expansions and two policy clarifications. The expansions added `email_read` to Engineering, Security, and Data and Analytics (all three departments routinely receive external email despite the initial ceilings only granting `email_read` to externally-corresponding roles); added `http_request` to Data and Analytics (analysts fetch live external data to enrich reports); and added `jira_read` and `jira_write` to Finance (finance operations require issue tracking the initial policy did not describe). The two clarifications were the inverse case; workflows the model surfaced that should not be authorized. Salesforce CRM data is replicated to the Snowflake warehouse and should be queried via `database_read` rather than `salesforce_read`; Legal's GDPR data subject requests must be routed through Data and Analytics rather than direct database access. In both cases the policy was updated to describe the correct workflow, and the model was constrained at the source rather than by ceiling expansion.

After regeneration with the refined policy and ceilings, ceiling violations dropped from 46 to 3, a 93% reduction. The remaining three were genuine edge cases that did not warrant either policy or ceiling change.

Synthetic prompt generation is not only a labeling-data source. When generation is decoupled from the policy that constrains the labels, the prompts function as a stress test of the policy itself, surfacing workflow gaps that top-down policy authoring routinely misses. The 93% reduction shows that policy and dataset must be co-evolved: a fixed policy paired with a generated dataset will produce ceiling violations that corrupt the Source 1 signal, while iterating between them produces a policy aligned with how the organization actually operates and a dataset whose labels are internally consistent with that policy.

5. Validation Results

A 10% random sample (60 records) was independently re-labeled by a single expert reviewer, with no access to the LLM's permission decisions for those records. Disagreements between the human and LLM labels were identified computationally afterwards. Each disagreement was then asked to the reviewer in a separate pass; the reviewer analyzed the LLM justification and tagged each as either *llm_correct* (human labeling error), *human_correct* (LLM prediction error), or *ambiguous*. The corrected labels form the post-review ground truth.

Independent re-labeling prevents anchoring bias. A review-style validation, where the human inspects the LLM's labels and accepts or rejects them, anchors the human to the LLM's prior decisions. Our labeling process produces the human's own assessment of what the task requires, which the LLM's labels are then compared against. Later the disagreements are surfaced and resolved as a separate step. Both pre-review and post-review statistics are used to evaluate the results of the research.

Because most permissions are denied for most tasks (only 2-4 of the 15 are typically required), raw agreement shows inflated misleading accuracy. We used Cohen's κ which is the standard reliability metric for two-rater categorical labeling and has been since Cohen introduced it in 1960 (Cohen, 1960). We compute κ over the in-ceiling decision space which means for each record, only permissions within the agent's department ceiling are evaluated. Otherwise out-of-ceiling permissions would be trivially denied by both raters and would inflate both observed and chance agreement. Adjusting department ceilings across 60 records yields 688 binary human-LLM decisions. The reported κ is computed once over those decisions; per-tool κ values are also released for diagnostic use, but the headline figure is the overall κ. We additionally report the 95% confidence interval using the standard error formula for Cohen's κ from Fleiss, Cohen & Everitt (Fleiss et al., 1969).

Two metric sets are reported within the scope of research. **Pre-review** metrics treat the human labels as ground truth.

Post-review metrics treat the reviewed labels as ground truth, which proved more accurate once the resolution data showed that human labels themselves contain errors. Both pre-review and post-review sets are released as part of this research.

Relying on a single labeler is a methodological limitation. Self-review bias is unavoidable here as the same researcher who produced the human labels also resolved their disagreements with the LLM. Cohen's κ alone cannot rule out unconscious confirmation of prior decisions. We mitigate this by releasing the full disagreement log with per-case notes, so external reviewers can audit the resolution data directly. A second independent labeler would let us compute true inter-rater κ and is noted as the most direct strengthening of the validation argument.

5.1. Permission Metrics

Table 1 reports the LLM's permission-labeling metrics under both ground-truth definitions.

Metric	Pre-review	Post-review
Exact match rate	68.3%	85.0%
Hamming accuracy	97.1%	98.8%
Macro F1	0.920	0.966
Cohen's κ	0.917	0.967
95% CI on κ	[0.882, 0.953]	[0.944, 0.990]
Overshoot rate	1.3%	0.2%
Undershoot rate	8.1%	4.4%
Weighted overshoot	15.0	2.0
N (decisions evaluated)	688	686

Table 1. LLM labeling performance metrics on the 60-record validated sample. Pre-review treats the human labels as ground truth; post-review treats the adjudicated labels as ground truth, with the two ambiguous cases excluded from computation.

The pre-review κ of 0.917 (computed under the conservative assumption that human labels are always correct) places agreement firmly within the "almost perfect" agreement band of Landis and Koch (Landis & Koch, 1977). Its lower CI bound of 0.882 demonstrates that even the worst-case interpretation of the validation data places agreement well above the 0.80 threshold commonly cited as a benchmark for substantial agreement in two-rater categorical labeling. Post-review $\kappa = 0.967$, with the 95% confidence interval bounded below at 0.944, reflects the accuracy of the released labels after disagreement resolution.

The most security-relevant finding is the severity-weighted overshoot drop from 15.0 to 2.0, an 86.7% reduction. Severity-weighted overshoot counts incorrectly granted permissions, weighted by their risk tier: a Tier 1 (default deny) over-grant counts three times a Tier 3 over-grant. It essentially performs as a security risk score. The disagreement

resolution attributed 10 of the 20 disagreements to human labeling error rather than LLM error, with the corrections concentrated on the high-risk permissions that drive the severity score. The post-review Figure 1 reflects the LLM's residual rate of high-risk over-granting on this sample.

The remaining error after resolution is conservative undershoot at 4.4%, corresponding to cases where the LLM denies a permission that should have been granted. For a permission classifier, undershoot is the preferred failure mode in principle: an unwarranted grant expands the attack surface, while a missed grant only degrades task performance. In real-world deployments undershoot disrupts workflow, so we expect production classifiers to be tuned with a directional bias matched to the deployment mode: undershoot bias under no enforcement, overshoot bias under enforcement, in both cases biased toward denying high-risk tools and permitting low-risk ones.

The two metric sets operate on slightly different decision spaces: pre-review evaluates 688 in-ceiling human–LLM decisions, while post-review evaluates 686 after excluding the two ambiguous cases that the disagreement resolution could not resolve. Both numbers exclude out-of-ceiling permissions, which are trivially denied by both raters and would inflate observed and chance agreement together.

Figure 1. Pre-review vs post-review permission metrics on the 60-record validated sample. Both κ values sit in the "almost perfect" agreement band ($\kappa \geq 0.81$). The metric improvements after adjudication are modest in absolute terms (κ moves 0.05), but the severity-weighted overshoot collapses from 15.0 to 2.0 (an 86.7% reduction), which is the operationally consequential change.

Figure 1 visualizes the comparison.

5.2. Disagreement Resolution

20 of the 60 records contained at least one permission disagreement between the human and LLM labels. Each disagreement was reviewed in the resolution pass: 10 (50%) were attributed to human labeling error, 8 (40%) to LLM prediction error, and 2 (10%) were judged ambiguous and excluded from post-review computation.

The near-parity between LLM-correct and human-correct cases is the methodological justification for using the reviewed labels as ground truth rather than the raw human labels. A clean oracle assumption would predict that the

human "wins" disagreements most of the time; the actual 10/8 split shows that human labels contain errors at a rate comparable to LLM predictions on this sample.

The full disagreement log, including the resolution decision and a one-sentence rationale per case, is released with the dataset. External readers can audit the review directly.

5.3. Sensitivity Tier Labels

In addition to permissions, each generated record carries a sensitivity tier label - LOW, MEDIUM, or HIGH - assigned by the LLM at generation time based on the data being handled by the task. The tiers were originally intended to map to standard data-classification levels such as those in NIST SP 800-60 (National Institute of Standards and Technology, 2008), on the principle that more sensitive data implies higher security risk for any task that touches it. The validation pass found the label too subjective for that purpose: human-LLM raw agreement on sensitivity was 60%, substantially below the corresponding figure for permission decisions on the same sample. The instability concentrates on the MEDIUM tier, which the confusion matrix shows is split nearly evenly across all three human assignments. The boundary between MEDIUM and the adjacent tiers is genuinely ambiguous in many enterprise tasks rather than a labeling defect. Of the 24 sensitivity disagreements adjudicated, the human was correct in 17 cases (71%) and the LLM in 6 (25%) with 1 ambiguous case (4%), confirming that the LLM's sensitivity assignments are systematically less reliable than its permission assignments.

Sensitivity tier labels are therefore excluded from all classifier metrics and from the severity-weighted delta computation. They are retained in the dataset as descriptive metadata only.

6. Discussion and Limitations

The release of this synthetic dataset and the methodology of adaptive policy refinement provide an empirical baseline toward evaluating dynamic capability scoping.

Our findings must be interpreted alongside several methodological considerations. First, our dataset validation currently relies on a single expert reviewer; while we released the full adjudication log to audit self-review bias, formal multi-rater validation is required to establish true inter-rater reliability. This will be handled in a future iteration. Second, despite careful grounding in a multi-department policy, synthetic data inherently lacks the full ecological validity, implicit context, and noise of real-world corporate communications. Third, because the task classifier relies on natural language processing, it inherits standard vulnerabilities to prompt injection. This reinforces our core design principle: dynamic scoping cannot function reliably in isolation and

must be paired with deterministic ceilings and prohibitions. Finally, assigning data sensitivity tiers yielded lower human-to-LLM agreement (60%), indicating that automating data classification requires more structured rubrics to be reliable.

A significant architectural limitation arises in the context of autonomous, multi-step agent workflows, such as Re-Act (Yao et al., 2022) or iterative tool-calling loops. Source 2, the task-context classifier, predicts required permissions based solely on the initial natural language prompt. However, complex open-ended tasks such as debugging a production incident often exhibit expanding permission scopes. An agent might initially only appear to need `jira_read` to triage an alert, but upon reading the ticket, dynamically discover it requires `github_read` to inspect a repository and `code_execute` to reproduce a bug. Because Source 2 currently evaluates only the upfront request, it cannot anticipate downstream requirements discovered during the agent's reasoning loop. The orchestrator must either strictly undershoot (breaking the workflow) or preemptively over-provision tools for complex prompts, which risks increasing the dynamic scope back into the broad Source 1 role ceiling. We argue even open-ended tasks can still benefit from scope reduction in majority of cases (e.g., `slack_write` permission within "debugging context").

The effectiveness of Source 3's prohibitions depends directly on the precision of the underlying rule mechanism and the workflow definitions in the organizational policy. Our baseline taxonomy blocks the co-occurrence of tools like `database_read` and `http_request` to prevent exfiltration. However, enterprise workflows frequently combine internal database reads with internal HTTP webhooks. If the rule mechanism lacks parameter-level scoping (e.g., distinguishing internal Virtual Private Cloud (VPC) endpoints from public IP addresses) or if the policy fails to explicitly distinguish authorized internal communication from prohibited external access, binary tool prohibitions will disrupt operations. Our adaptive policy refinement methodology directly addresses this requirement. Iterating between generated task prompts and policy definitions forces organizations to surface and resolve these network-scoping ambiguities prior to deployment, ensuring the architecture scales to complex enterprise environments.

Future work will advance this architecture from a design proposal to an empirically validated system. As an immediate next step, we will train a dedicated task-context classifier on this dataset to establish baseline overshoot and undershoot statistics. We will then evaluate the complete architecture across a phased progression (C0–C3): from an unenforced baseline (C0), to role ceilings only (C1), adding the task classifier (C2), and finally enforcing the policy prohibitions (C3). To further advance AI control against misalignment, we plan to deploy this setup as a custom micro-protocol

within the ControlArena (UK AI Security Institute & Redwood Research, 2026) framework. Testing against deceptive model organisms (Hubinger et al., 2024) will empirically evaluate the system's capacity to deterministically prevent hidden exfiltration side tasks. Lastly, we will explore practical operational integration via Just-in-Time credentialing and observe-only telemetry for enterprise security platforms.

7. Conclusion

Recent security incidents involving OpenClaw (Wang et al., 2026) demonstrate that agentic LLM deployments carry substantial security risks. As increasingly capable models are deployed within critical infrastructure, the impact of emerging misalignment grows exponentially. Anthropic reports that Claude Mythos (Anthropic, 2026)—their latest frontier model at the time of writing—demonstrates complex vulnerability exploitation and autonomous sandbox escape capabilities. Furthermore, sandbagging and alignment faking (Greenblatt et al., 2024) have the potential to bypass standard safety evaluations; a compromised agent that retains broad permissions can therefore cause severe damage. Substantial investment in AI control measures is required to mitigate these exploding risk factors.

Our proposal reduces the blast radius of these failure modes by removing the credentials a deceptive agent would require to execute an attack. A tool that does not exist in the agent's context cannot be misused, regardless of the agent's reasoning or strategic capabilities. This creates a partially-deterministic confinement layer that serves as a robust safety primitive, complementing existing alignment, monitoring, and detection solutions.

While the architecture introduces operational costs detailed in the Section 6, we expect these to be minimized through targeted fine-tuning. Despite current limitations in evaluating complex, open-ended tasks, we believe this architecture provides a critical component for the practical implementation of AI control measures in high-stakes environments.

References

Amazon Web Services. IAM identifiers: Principals. https://docs.aws.amazon.com/IAM/latest/UserGuide/reference_identifiers.html, 2024. AWS Identity and Access Management User Guide.

Anthropic. Claude Mythos Preview System Card. Technical report, Anthropic, PBC, April 2026. URL https://www-cdn.anthropic.com/53566bf5440a10affd749724787c8913a2ae0841.pdf. Assesses advanced cybersecurity capabilities and autonomous sandbox escape behaviors.

Cohen, J. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20(1):37–46, 1960.

Dennis, J. B. and Van Horn, E. C. Programming semantics for multiprogrammed computations. *Communications of the ACM*, 9(3), 1966.

Fleiss, J. L., Cohen, J., and Everitt, B. S. Large sample standard errors of kappa and weighted kappa. *Psychological Bulletin*, 72(5):323–327, 1969.

Greenblatt, R., Denison, C., Wright, B., Roger, F., MacDiarmid, M., Marks, S., Treutlein, J., Belonax, T., Chen, J., Duvenaud, D., Khan, A., Michael, J., Mindermann, S., Perez, E., Petrini, L., Uesato, J., Kaplan, J., Shlegeris, B., Bowman, S. R., and Hubinger, E. Alignment faking in large language models. *arXiv preprint arXiv:2412.14093*, 2024.

Greshake, K., Abdelnabi, S., Mishra, S., Endres, C., Holz, T., and Fritz, M. More than you've asked for: A comprehensive analysis of novel prompt injection threats to application-integrated large language models. In *AISec '23 (Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security)*, pp. 115–126, 2023.

Hubinger, E., Denison, C., Mu, J., Lambert, M., Tong, M., MacDiarmid, M., Lanham, T., Ziegler, D. M., Maxwell, T., Cheng, N., Jermyn, A., Askell, A., Radhakrishnan, A., Anil, C., Duvenaud, D., Ganguli, D., Barez, F., Clark, J., Ndousse, K., Sachan, K., Sellitto, M., Sharma, M., DasSarma, N., Grosse, R., and Kravec, S. Sleeper agents: Training deceptive llms that persist through safety training. *arXiv*, 2024. doi: 10.48550/arxiv.2401.05566.

Inan, H., Upasani, K., Chi, J., Rungta, R., Iyer, K., Mao, Y., Tontchev, M., Hu, Q., Fuller, B., Testuggine, D., and Khabsa, M. Llama guard: Llm-based input-output safeguard for human-ai conversations, 2023. URL https://arxiv.org/abs/2312.06674.

Kholkar, G. and Ahuja, R. Policy-as-prompt: Turning ai governance rules into guardrails for ai agents, 2025.

Landis, J. R. and Koch, G. G. The measurement of observer agreement for categorical data. *Biometrics*, 33(1):159–174, 1977.

Meinke, A., Schoen, B., Scheurer, J., Balesni, M., Shah, R., and Hobbhahn, M. Frontier models are capable of in-context scheming. *arXiv preprint arXiv:2412.04984*, 2024. Apollo Research.

Miller, M. S. *Robust Composition: Towards a Unified Approach to Access Control and Concurrency Control*. PhD thesis, 2006.

National Institute of Standards and Technology. Guide for mapping types of information and information systems to security categories. Technical Report NIST SP 800-60 Volume I Revision 1, U.S. Department of Commerce, 2008.

OWASP Foundation. OWASP top 10 for LLM applications 2025. https://genai.owasp.org/llm-top-10/, 2025.

Palumbo, N., Choudhary, S., Choi, J., Chalasani, P., and Jha, S. Policy compiler for secure agentic systems, 2026.

Reason, J. *Human error*. Cambridge University Press, Cambridge, UK, 1990.

Rebedea, T., Dinu, R., Sreedhar, M. N., Parisien, C., and Cohen, J. Nemo guardrails: A toolkit for controllable and safe llm applications with programmable rails. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pp. 431–445. Association for Computational Linguistics, 2023. doi: 10.18653/v1/2023.emnlp-demo.40. URL https://aclanthology.org/2023.emnlp-demo.40.

Rose, S., Borchert, O., Mitchell, S., and Connelly, S. Zero trust architecture. Technical Report NIST SP 800-207, National Institute of Standards and Technology, 2020.

Saltzer, J. H. and Schroeder, M. D. The protection of information in computer systems. *Proceedings of the IEEE*, 63(9):1278–1308, 1975.

Schick, T., Dwivedi-Yu, J., Dessì, R., Raileanu, R., Lomeli, M., Zettlemoyer, L., Cancedda, N., and Scialom, T. Toolformer: Language models can teach themselves to use tools. *arXiv*, 2023. doi: 10.48550/arxiv.2302.04761.

Shapiro, J. S., Smith, J. M., and Farber, D. J. EROS: A fast capability system. In *Proceedings of the 17th ACM Symposium on Operating Systems Principles (SOSP)*, 1999.

Siu, V., He, J., Montgomery, K., Wang, Z., Gong, N., Wang, C., and Song, D. A framework for formalizing LLM agent security, 2026.

Smalley, S., Vance, C., and Salamon, W. Implementing SELinux as a Linux security module. Technical report, NAI Labs, 2001. NAI Labs Report #01-043.

Tsai, L. and Bagdasarian, E. Contextual agent security: A policy for every purpose. In *Proceedings of the Workshop on Hot Topics in Operating Systems (HotOS '25)*, 2025. doi: 10.1145/3713082.3730378.

UK AI Security Institute and Redwood Research. Controlarena: A library for running AI control experiments.

https://github.com/UKGovernmentBEIS/
control-arena, 2026. Accessed: 2026-04-29.

Wang, Y., Gao, H., Niu, Z., Liu, Z., Zhang, W., Wang, X., and Lian, S. A systematic security evaluation of openclaw and its variants. *arXiv preprint arXiv:2604.03131*, 2026.

Willison, S. The lethal trifecta for ai agents: Private data, untrusted content, and external communication. https://simonwillison.net/2025/Jun/16/the-lethal-trifecta/, June 2025. Blog post.

Yao, S., Zhao, J., Yu, D., Du, N., Shafran, I., Narasimhan, K., and Cao, Y. React: Synergizing reasoning and acting in language models. *arXiv*, 2022. doi: 10.48550/arxiv.2210.03629.