Bandit Phase Retrieval

Abstract

We study a bandit version of phase retrieval where the learner chooses actions $(A_t)_{t=1}^n$ in the d-dimensional unit ball and the expected reward is $\langle A_t, \theta_\star \rangle^2$ where $\theta_\star \in \mathbb{R}^d$ is an unknown parameter vector. We prove that the minimax cumulative regret in this problem is $\tilde{\Theta}(d\sqrt{n})$, which improves on the best known bounds by a factor of $\sqrt{d}$. We also show that the minimax simple regret is $\tilde{\Theta}(d/\sqrt{n})$ and that this is only achievable by an adaptive algorithm. Our analysis shows that an apparently convincing heuristic for guessing lower bounds can be misleading and that uniform bounds on the information ratio for information-directed sampling Russo and Roy [2018] are not sufficient for optimal regret.

1 Introduction

We study an instantiation of the low-rank bandit problem [Jun et al., 2019] that in the statistical setting is called phase retrieval. Although this model is interesting in its own right, our main focus is on the curious information structure of this problem and how it impacts algorithm design choices. Notably, we were not able to prove optimal regret for standard approaches based on optimism, Thompson sampling or even information-directed sampling using standard approaches. Instead, our algorithm is a variant of explore-then-commit with an adaptive exploration phase that learns to gain information at a faster rate than what is achievable with non-adaptive exploration.

Problem setting Let $\| \cdot \|$ be the standard euclidean norm and $\mathbb{B}_r^d = \{x \in \mathbb{R}^d : \|x\| \le r\}$ and $\mathbb{S}_r^{d-1} = \{x \in \mathbb{R}^d : \|x\| = r\}$. At the start of the game the environment secretly chooses a vector $\theta_\star \in \mathbb{S}_r^{d-1}$ with $r \in [0, 1]$ a constant that is known to the learner. The assumption that r is known to the learner can be relaxed at no cost (Section 8). The game then proceeds over n rounds. In round t the learner chooses an action $A_t \in \mathbb{B}_1^d$ and observes a reward

$$X_t = \langle A_t, \theta_\star \rangle^2 + \eta_t \,,$$

where $(\eta_t)_{t=1}^n$ is a sequence of independent standard Gaussian random variables. As is standard in bandit problems, A_t should be chosen as a (measurable) function of the previous actions $(A_s)_{s=1}^{t-1}$ and rewards $(X_s)_{s=1}^{t-1}$. The performance of a policy π is measured in terms of the expected regret,

$$\mathfrak{R}_n(\pi, \theta_\star) = \max_{a \in \mathbb{B}_1^d} \mathbb{E}\left[\sum_{t=1}^n \left(\langle a, \theta_\star \rangle^2 - \langle A_t, \theta_\star \rangle^2 \right)\right] = r^2 - \mathbb{E}\left[\sum_{t=1}^n \langle A_t, \theta_\star \rangle^2\right] \,.$$

The minimax regret is $\mathfrak{R}_n^\star = \sup_{r \in [0,1]} \inf_\pi \sup_{\theta_\star \in \mathbb{S}_r^{d-1}} \mathfrak{R}_n(\pi, \theta_\star)$, where the infimum is over all policies.

We also study the pure exploration setting, where at the end of the game the learner uses the observed data $(A_t)_{t=1}^n$ and $(X_t)_{t=1}^n$ to make a prediction $\widehat{A}_\star \in \mathbb{B}_1^d$ of the optimal action. The simple regret of

policy π is

$$\mathfrak{r}_n(\pi, \theta_\star) = \max_{a \in \mathbb{B}_1^d} \mathbb{E}\left[\langle a, \theta_\star \rangle^2 - \langle \widehat{A}_\star, \theta_\star \rangle^2\right] = r^2 - \mathbb{E}\left[\langle \widehat{A}_\star, \theta_\star \rangle^2\right].$$

As expected, the minimax simple regret is $\mathfrak{r}_n^\star = \sup_{r \in [0,1]} \inf_\pi \sup_{\theta_\star \in \mathbb{S}^{d-1}} \mathfrak{r}_n(\pi, \theta_\star)$.

Contributions   Our main contribution is nearly matching upper and lower bounds on $\mathfrak{R}_n^\star$. For the simple regret we provide a near-optimal upper bound and a lower bound showing that non-adaptive policies must be at least a factor of $\Omega(\sqrt{d})$ suboptimal. In all of the following, const is a universal non-negative constant that may vary from one expression to the next.

Theorem 1. $\mathfrak{R}_n^\star \leq \text{const}\, d\sqrt{n \log(n) \log(d)}$.

Theorem 2. $\mathfrak{R}_n^\star \geq \text{const}\, d\sqrt{n}$ *whenever d is larger than a suitable universal constant and n is sufficiently large.*

Theorem 3. $\mathfrak{r}_n^\star \leq \text{const}\, d\sqrt{\log(n) \log(d)/n}$.

Theorem 4. *Assume that $n \geq d \geq 8$. Then there exists an $r \in [0,1]$ such that for all policies π with $(A_t)_{t=1}^n$ independent of $(X_t)_{t=1}^n$, $\sup_{\theta_\star \in \mathbb{S}_r^{d-1}} \mathfrak{r}_n(\pi, \theta_\star) \geq \text{const}\, \sqrt{d^3/n}$.*

We also show that worse-case bounds on the information ratio for information-directed sampling are *not* sufficient to achieve optimal regret. Our results suggest that the conjectured lower bounds for low-rank bandits [Jun et al., 2019, Lu et al., 2021] are not true and that existing upper bounds are loose. The same phenomenon may explain the gap between upper and lower bounds for bandit principle component analysis [Kotłowski and Neu, 2019], as we discuss in Section 8.

Notation   The first n integers are $[n] = \{1, 2, \ldots, n\}$ and the standard basis vectors in $\mathbb{R}^d$ are $e_1, \ldots, e_d$. The span of a collection of vectors is denoted by $\text{span}(v_1, \ldots, v_m)$ and the orthogonal complement of a linear subspace $V \subset \mathbb{R}^d$ is $V^\perp = \{x \in \mathbb{R}^d : \langle x, y \rangle = 0 \text{ for all } y \in V\}$. The mutual information between random elements X and Y on the same probability space is $I(X; Y)$ and the relative entropy between probability measures P and Q on the same measurable space is $\text{KL}(P, Q)$. The dimension of a set $\Theta \subset \mathbb{R}^d$ is defined as the dimension of the affine hull of Θ.

2   Related work

Phase retrieval   Phase retrieval is a classical problem in signal processing and statistics [Candès et al., 2015b,a, Cai et al., 2016, Chen and Candès, 2017, Chen et al., 2019, Sun et al., 2018]. These works are focused on learning $\theta_\star$ where the covariates $(A_t)_{t=1}^n$ are uncontrolled, either random or fixed design.

Linear bandits   Our problem can be written as a stochastic linear bandit by noticing that $\langle A_t, \theta_\star \rangle^2 = \langle A_t A_t^\top, \theta_\star \theta_\star^\top \rangle$, where the inner product between matrices on the right-hand side should be interpreted coordinate-wise and the action set is $\{aa^\top : a \in \mathbb{B}_1^d\}$. There is an enormous literature on stochastic linear bandits [Auer, 2002, Dani et al., 2008, Rusmevichientong and Tsitsiklis, 2010, Chu et al., 2011, Abbasi-Yadkori et al., 2011]. This reduction immediately yields an upper bound on the minimax regret of $O(d^2\sqrt{n}\log(n))$.

Low-rank bandits   Low-rank bandits are a kind of linear bandit where the environment is determined by an unknown matrix and the actions of the learner are also matrices. Let $\mathcal{E} \subset \mathbb{R}^{d_1 \times d_2}$ and $\mathcal{A} \subset \mathbb{R}^{d_1 \times d_2}$. A low-rank bandit problem over $\mathcal{E}$ and with actions $\mathcal{A}$ is characterised by a matrix $\Theta_\star \in \mathcal{E}$. The learner plays actions $A_t \in \mathcal{A}$ and the reward is $X_t = \langle A_t, \Theta_\star \rangle + \eta_t$, where η_t is noise and the inner product between matrices is interpreted coordinate-wise. So far this is nothing more than a complicated way of defining a linear bandit. The name comes from the fact that in general elements of $\mathcal{E}$ are assumed to be low-rank. The precise nature of the problem is determined by assumptions on $\mathcal{E}$ and the action set $\mathcal{A}$. Our setup is recovered by assuming that $\mathcal{E} = \{xx^\top : x \in \mathbb{S}_r^{d-1}\}$ and $\mathcal{A} = \{xx : x \in \mathbb{B}_1^d\}$.

Jun et al. [2019] assume that $\mathcal{E}$ consists of rank p matrices and $\mathcal{A} = \{xy^\top : x \in \mathcal{X}, y \in \mathcal{Y}\}$ for some reasonably bounded sets $\mathcal{X} \subset \mathbb{R}^{d_1}$ and $\mathcal{Y} \subset \mathbb{R}^{d_2}$. They prove that the regret is bounded by

Table 1: For the low-rank bandits column, p is the rank. We ignore logarithmic factors and universal constant. Note, the $dp\sqrt{n}$ lower bound derived by Lu et al. [2021] does not apply to bandit phase retrieval because it makes use of the richer structure of the more general model.

Upper bounds	Bandit phase retrieval	Low-rank bandits	Pure exploration
Abbasi-Yadkori et al. [2011]	$O(d^2\sqrt{n})$	$O(d^2\sqrt{n})$	N/A
Jun et al. [2019], Lu et al. [2021]	$O(d^{3/2}\sqrt{n})$	$O(d^{3/2}\sqrt{pn})$	N/A
This work	$O(d\sqrt{n})$	N/A	$O(d/\sqrt{n})$
Lower bounds			
Lu et al. [2021]	N/A	$\Omega(dp\sqrt{n})$	N/A
This work	$\Omega(d\sqrt{n})$	$\Omega(d\sqrt{n})$	$\Omega(d/\sqrt{n})$
This work (non-adaptive learning)	N/A	N/A	$\Omega(d^{3/2}/\sqrt{n})$

$\tilde{O}((d_1 + d_2)^{3/2}\sqrt{pn})$. These results cannot be applied directly to the phase retrieval bandit because of the product assumption on the action set. Lu et al. [2021] retain the assumption that $\mathcal{E}$ consists of rank-p matrices, but relax the product form of the action set (while also allowing for generalised linear models). Relying only on mild boundedness assumptions, they show that the regret can be bounded by $\tilde{O}((d_1 + d_2)^{3/2}\sqrt{pn})$. For the bandit phase retrieval problem, $d_1 = d_2 = d$ and $p = 1$, so this algorithm yields an upper bound on the regret for this problem of $\tilde{O}(d^{3/2}\sqrt{n})$. Both Jun et al. [2019] and Lu et al. [2021] conjecture that their upper bounds are optimal. Our results show that this is not true for this sub-problem, despite the fact that the heuristic argument holds in this case, as we explain in Section 3. We summarize these comparisons in Table 1.

Some authors use a model where the noise is in the parameter noise rather than additive, which means the reward is $\langle A_t, \Theta_t \rangle$ with $(\Theta_t)_{t=1}^n$ an independent and identically distributed sequence of low-rank matrices (with unknown distribution). For example, Katariya et al. [2017b,a] and Trinh et al. [2020] assume that Θ_t is rank-1 almost surely and $\mathcal{A} = \{e_i e_j^\top : 1 \leq i, j \leq d\}$, which means the learner is trying to identify the largest entry in a matrix.

Adversarial setting A similar problem has been studied in the adversarial framework by Kotłowski and Neu [2019]. They assume that $(\theta_t)_{t=1}^n$ is a sequence of vectors chosen in secret by an adversary at the start of the game and the learner observes $\langle A_t, \theta_t \rangle^2$. They design an algorithm for which the regret is at most $O(d\sqrt{n})$, while the best lower bound is $\Omega(\sqrt{dn})$.

3 Information-theoretic heuristics and information-directed sampling

Jun et al. [2019, §5] argue by comparing the signal to noise ratios between linear and low-rank bandits the minimax regret for problems like bandit phase retrieval should be lower bounded by $\Omega(d^{1.5}\sqrt{n})$. We make this argument a little more formal and explain why it does not yield the right answer in this instance. Suppose that $\theta_\star$ is sampled uniformly from $\mathbb{S}_r^{d-1}$ and the learner takes an action $A \in \mathbb{B}_1^d$ and observes $X = \langle A, \theta_\star \rangle^2 + \eta$ with $\eta \sim N(0, 1)$. What is the information gained by the learner? A symmetry argument shows that all actions on the unit sphere have the same information gain, so let's just fix some $A \in \mathbb{S}_1^{d-1}$. A Taylor series expansion yields the approximation

$$I(\theta_\star; Y) = \mathbb{E}[\text{KL}(\mathbb{P}_{X|\theta_\star}, \mathbb{P}_X)] \approx \frac{1}{2}\mathbb{E}\left[(\mathbb{E}[X|\theta_\star] - \mathbb{E}[X])^2\right] = \frac{r^4}{2}\left(\frac{3}{d^2 + 2d} - \frac{1}{d^2}\right) \leq \frac{r^4}{d^2}. \quad (1)$$

Note that $\frac{d}{2}\log(n)$ bits are needed to code $\theta_\star$ to reasonable accuracy. So if we presume that the rate of information learned *stays the same* throughout the learning process, then over n rounds the learner can only obtain $O(nr^4/d^2)$ bits by Eq. (1). By setting $r^2 = d^{3/2}\sqrt{\log(n)/n}$ one could be led to believe that the learner cannot identify the optimal direction and the regret would be $\Omega(nr^2) = \Omega(d^{3/2}\sqrt{n\log(n)})$. The main point is that the rate of information accumulated by a careful learner *increases* over time.

Information-directed sampling Our upper bound and the observation above has an important implication. Suppose as above that $\theta_\star$ is sampled uniformly from $\mathbb{S}_r^{d-1}$ and let A be a possibly randomised action. Since the learner cannot know the realisation of $\theta_\star$ initially, her expected regret

for any action $a \in \mathbb{B}_1^d$ is $\Delta(a) = r^2 - \mathbb{E}[\langle a, \theta_\star \rangle^2] = r^2(1 - \|a\|^2/d) \geq r^2(1 - 1/d)$. On the other hand, as outlined above, the information gain about $\theta_\star$ is about r^4/d^2. Together these results show that the information ratio is bounded by

$$\Psi \triangleq \frac{\mathbb{E}[\Delta(A)]^2}{I(\theta_\star; X, A)} = \Theta(d^2)\,.$$

Since the entropy of a suitable approximation of the optimal action is about $\frac{d}{2}\log(n)$, an application of the information theoretic analysis by Russo and Van Roy [2014] suggests that the Bayesian regret can be bounded by $O(d^{3/2}\sqrt{n\log(n)})$, which is suboptimal. This time the problem is that we have used the worst-case bound on the information ratio, without taking into account the possibility that the information ratio might decrease over time. We should mention here that a decreasing information ratio was exploited by Devraj et al. [2021] in a recent analysis of Thompson sampling, but there the gain was less dramatic (a logarithm of the number of arms) and no changes to the algorithm were required.

4 Algorithm for bandit phase retrieval

We start by showing that Theorem 1 holds if the learner is given an action that is constant-factor optimal. In the next section we explain how such an action can be identified with low regret. Our algorithm uses the explore-then-commit design principle, which is usually only sufficient for $O(n^{2/3})$ regret. The reason we are able to obtain $O(n^{1/2})$ regret is because of the curvature of the action set, a property that was exploited in a similar way by in online learning by Huang et al. [2017] and in partial monitoring by Kirschner et al. [2020].

Theorem 5. *Suppose the learner is given an action $\widehat{A}_w \in \mathbb{B}_1^d$ such that $\langle \widehat{A}_w, \theta_\star \rangle^2 \geq \alpha r^2$ for some universal constant $\alpha \in (0, 1]$. Then there exists a policy π for which the regret is at most $\mathfrak{R}_n(\pi, \theta_\star) \leq \text{const} \cdot d\sqrt{n\log(n)}$.*

Proof. By choosing the sign of $\theta_\star$, assume without loss of generality that $\langle \widehat{A}_w, \theta_\star \rangle \geq r\sqrt{\alpha}$. Let

$$m = \left\lceil 4d\sqrt{n\log(n)}/r^2 \right\rceil \qquad \text{and} \qquad \lambda = \min\left(\frac{1}{2}, \frac{\sqrt{\alpha}}{4}\right)\,.$$

If $m \geq n$, then the regret of any policy is upper bounded $nr^2 \leq \text{const}\, d\sqrt{n\log(n)}$, so for the rest of the proof we assume that $m < n$. For the first m rounds the policy cycles over the $2d$ actions $\{(1-\lambda)\widehat{A}_w \pm \lambda e_k : k \in [d]\}$. The constrained least squares estimator of $\theta_\star$ based on the data collected over m rounds is

$$\hat{\theta} = \arg\min\{\mathcal{L}(\theta) : \theta \in \mathbb{B}_r^d \text{ and } \langle \widehat{A}_w, \theta \rangle \geq r\sqrt{\alpha}\}\,, \tag{2}$$

where $\mathcal{L}(\theta) = \frac{1}{2}\sum_{t=1}^m (X_t - \langle A_t, \theta \rangle^2)^2$. For the remaining $n - m$ rounds the algorithm plays $A_t = \widehat{A} = \hat{\theta}/\|\hat{\theta}\|$. Then,

$$\beta \triangleq 9 + d\log(98m) \geq \mathbb{E}\left[\sum_{t=1}^m \langle A_t, \hat{\theta} - \theta_\star \rangle^2 \langle A_t, \hat{\theta} + \theta_\star \rangle^2\right] \qquad \text{(by Corollary 11)}$$

$$\geq \frac{\alpha\|\theta_\star\|^2}{4}\mathbb{E}\left[\sum_{t=1}^m \langle A_t, \hat{\theta} - \theta_\star \rangle^2\right] \tag{3}$$

$$\geq \frac{\alpha\lambda^2\|\theta_\star\|^2}{2}\left(\frac{m}{2d} - 1\right)\mathbb{E}\left[\|\hat{\theta} - \theta_\star\|^2\right]\,. \tag{4}$$

where in Eq. (3) we used that for some $k \in [d]$,

$$\langle A_t, \hat{\theta} + \theta_\star \rangle = \langle (1-\lambda)\widehat{A}_w \pm \lambda e_k, \hat{\theta} + \theta_\star \rangle \geq (1-\lambda)\langle \widehat{A}_w, \hat{\theta} + \theta_\star \rangle - \lambda\|\hat{\theta} + \theta_\star\|$$

$$\geq 2(1-\lambda)\sqrt{\alpha}r - 2\lambda r \geq \frac{\sqrt{\alpha}}{2}\|\theta_\star\|\,. \qquad \text{(by definition of }\lambda\text{)}$$

Eq. (4) follows because for any $k \in [d]$,

$$\sum_{\sigma \in \pm 1} \langle (1-\lambda)\widehat{A}_w + \sigma \lambda e_k, \hat{\theta} - \theta_\star \rangle^2 = 2(1-\lambda)^2 \langle \widehat{A}_w, \hat{\theta} - \theta_\star \rangle^2 + 2\lambda^2 \langle e_k, \hat{\theta} - \theta_\star \rangle^2$$

$$\geq 2\lambda^2 \langle e_k, \hat{\theta} - \theta_\star \rangle^2 \,,$$

which implies that

$$\sum_{t=1}^{m} \langle A_t, \hat{\theta} - \theta_\star \rangle^2 \geq \left\lfloor \frac{m}{2d} \right\rfloor \sum_{k=1}^{d} \left(2\lambda^2 \langle e_k, \hat{\theta} - \theta_\star \rangle^2 \right) \geq 2\lambda^2 \left(\frac{m}{2d} - 1 \right) \|\hat{\theta} - \theta_\star\|^2 \,.$$

Rearranging Eq. (4) and using the definition of β shows that

$$\mathbb{E}\left[\|\hat{\theta} - \theta\|^2 \right] \leq \frac{2\beta}{\alpha \lambda^2 \|\theta_\star\|^2} \frac{1}{\frac{m}{2d} - 1} \leq \text{const} \, \frac{d^2 \log(m)}{m \|\theta_\star\|^2} \,.$$

Letting $a_\star = \theta_\star / \|\theta_\star\|$ be the optimal action, the regret is bounded by

$$\mathfrak{R}_n(\pi, \theta_\star) \leq m\|\theta_\star\|^2 + n\mathbb{E}\left[\langle a_\star, \theta_\star \rangle^2 - \langle \widehat{A}, \theta_\star \rangle^2 \right] = m\|\theta_\star\|^2 + n\mathbb{E}\left[\langle a_\star - \widehat{A}, \theta_\star \rangle \langle a_\star + \widehat{A}, \theta_\star \rangle \right]$$

$$\leq m\|\theta_\star\|^2 + 2n\mathbb{E}\left[\left| \langle a_\star - \widehat{A}, \theta_\star \rangle \right| \|\theta_\star\| \right]$$

$$\leq m\|\theta_\star\|^2 + 4n\mathbb{E}\left[\|\theta_\star - \hat{\theta}\|^2 \right] \qquad \text{(by Lemma 7)}$$

$$\leq m\|\theta_\star\|^2 + \text{const} \, \frac{nd^2 \log(m)}{m\|\theta_\star\|^2} \leq \text{const} \, d\sqrt{n\log(n)} \,. \qquad \square$$

5 Finding a constant-factor optimal action

To establish Theorem 1 we show there exists an algorithm that interacts with the bandit for a random number of rounds and outputs an action $\widehat{A}$ with $\langle a, \theta_\star \rangle^2 \geq \text{const} \, \|\theta_\star\|^2$. Furthermore, the procedure suffers small regret in expectation.

Theorem 6. *Let T be the random number of rounds that Algorithm 1 interacts with the bandit, which cannot be more than n, and let $\widehat{A}_w \in \mathbb{S}_1^{d-1}$ be its output. Then,*

1. $\mathbb{E}[T] \leq \text{const} \, \frac{d^2}{r^4} \log(n) \log(d)$.

2. *With probability at least $1 - 1/n$, either $T = n$ or $\langle \widehat{A}_w, \theta_\star \rangle^2 \geq \frac{r^2}{64}$.*

What is interesting about Algorithm 1 is that it uses what it has learned in early iterations to increase the statistical efficiency of its estimation.

Proof. Note that the vectors u and v computed in each iteration are orthogonal, which means that $\|(u + v)/\sqrt{2}\| = \|(u - v)/\sqrt{2}\| = \|v\| = 1$, which means that the actions of the algorithm are always in $\mathbb{B}_1^d$. The main argument of the proof is based on an induction to show that with high probability when the execution of the algorithm ends, there exists an $s \in \{\pm 1\}$ such that for all $w \in \mathcal{E}$,

(a) $w \in \mathcal{E}, \|w\|^2 \geq \tau^2$; and

(b) $s\langle w, \theta_\star \rangle \in [\frac{1}{2}\|w\|^2, 2\|w\|^2]$.

We proceed in five steps. First we prove that if the above holds and the algorithm halts before n rounds are over, then the vector returned is a suitable approximation of $\theta_\star / \|\theta_\star\|$. We upper bound the probability of certain bad events. In the third and fourth steps we prove the base case and induction step for (a) and (b) and in the last step we bound the expected running time.

```
1   τ = r/√d  and  m = 8/τ⁴ log (2n²)
2   do
3      sample v uniformly from 𝕊₁^{d-1}
4      play Aₜ = v for m rounds and compute average reward X̄
5   loop until  X̄ ≥ τ²
6   ℰ = {v√X̄}
7   for k = 2 to d

8      β = 9(log(98) + 4 log(n))  and  m = 32d²β/(kr⁴)  and  u = (Σ_{w∈ℰ} w)/(‖Σ_{w∈ℰ} w‖)

9      do
10        sample v uniformly from span(ℰ)^⊥ ∩ 𝕊₁^{d-1}
11        play Aₜ ∈ {(u + v)/√2, (u − v)/√2, u} for 3m rounds
12        find least squares estimator θ̂ constrained to 𝔹₁^d
13      loop until  ⟨v, θ̂⟩² ≥ τ²
14      ℰ = ℰ ∪ {⟨v, θ̂⟩v}
15   loop until  Σ_{w∈ℰ} ‖w‖² ≥ r²/16
16   return  Â_w = (Σ_{w∈ℰ} w)/(‖Σ_{w∈ℰ} w‖)
```

Algorithm 1: The procedure operates in d iterations. The first iteration is implemented in Lines 1–5 and the remaining $d − 1$ iterations in Lines 7–15.

Step 1: Correctness Suppose that (a) and (b) above hold and the algorithm halts at the end of iteration k. Then,

$$\langle \widehat{A}_w, \theta_\star \rangle^2 = \left\langle \frac{\sum_{w\in\mathcal{E}} w}{\|\sum_{w\in\mathcal{E}} w\|}, \theta_\star \right\rangle^2 \geq \frac{1}{4} \sum_{w\in\mathcal{E}} \|w\|^2 \geq \frac{r^2}{64}.$$

where the first inequality follows from orthogonality of $w \in \mathcal{E}$ and (b) above. The second inequality follows from the stopping condition in Line 15 of Algorithm 1, (a) above and the definition of τ. Part (2) of the theorem follows by showing that (a) and (b) above hold with probability $1 − 1/n$.

Step 2: Failure events The algorithm computes some kind of estimator at the end of each do/loop. Since the algorithm cannot play more than n actions, the number of estimators computed is naively upper bounded by n. A union bound over all estimates and the concentration bounds in Lemma 8 and Corollary 11 show that with probability at least $1 − 1/n$ the following both hold:

- For all v sampled in the first iteration and corresponding average rewards $\bar{X}$,

$$\left| \bar{X} - \langle v, \theta_\star \rangle^2 \right| \leq \sqrt{\frac{2\log(2n^2)}{m}} = \frac{\tau^2}{2}, \tag{5}$$

  where m is defined in Line 1 of Algorithm 1.

- Let $\mathcal{D} = (A_s)_s$ be the actions played in the inner loop of some iteration $k \geq 2$ and $\hat{\theta}$ be the corresponding least-squares estimator. Then,

$$\sum_{a\in\mathcal{D}} \langle a, \hat{\theta} - \theta_\star \rangle^2 \langle a, \hat{\theta} + \theta_\star \rangle^2 \leq 9(\log(98) + 4\log(n)) \triangleq \beta. \tag{6}$$

We assume both of the above hold in all relevant iterations for the remainder.

Step 3: Base case The next step is to show that (a) and (b) hold with high probability when $k = 1$. Consider the operation of the algorithm in the inner loop. After sampling $v \in \mathbb{S}_1^{d-1}$, the algorithm plays v for m rounds and computes the average reward. Let v be the last sampled action before the

iteration halts and $w = v\sqrt{\bar{X}}$. By the stopping condition in Line 5, $\|w\|^2 = \bar{X} \geq \tau^2$. Without loss of generality, we choose the sign of $\theta_\star$ so that $\langle v, \theta_\star \rangle \geq 0$. Then by Eq. (5),

$$\langle w, \theta_\star \rangle = \sqrt{\bar{X}} \langle v, \theta_\star \rangle \in \left[\frac{1}{2} \|w\|^2, 2\|w\|^2 \right] .$$

This establishes the base case.

Step 4: Inductive step Assume that (a) and (b) above hold for $\mathcal{E}$ at the end of iteration k. Let u be the value computed in Line 8 of Algorithm 1. Then,

$$\langle u, \theta_\star \rangle = \frac{\sum_{w \in \mathcal{E}} \langle w, \theta_\star \rangle}{\sqrt{\sum_{w \in \mathcal{E}} \|w\|^2}} \geq \frac{1}{2} \sqrt{\sum_{w \in \mathcal{E}} \|w\|^2} \geq \frac{\tau \sqrt{k}}{2} .$$

Let $\mathcal{A} = \{(u+v)/\sqrt{2}, (u-v)/\sqrt{2}, v\}$, which is the set of actions played in the inner loop of iteration $k+1$ after sampling v for the last time. Let $\hat{\theta}$ be the corresponding least-squares estimate. We consider two cases. First, if $\langle u, \hat{\theta} + \theta_\star \rangle \geq 2|\langle v, \hat{\theta} + \theta_\star \rangle|$, then by Eq. (6),

$$\frac{\beta}{m} \geq \sum_{a \in \mathcal{A}} \langle a, \theta_\star - \hat{\theta} \rangle^2 \langle a, \theta_\star + \hat{\theta} \rangle^2 \geq \frac{1}{16} \langle u+v, \theta_\star - \hat{\theta} \rangle^2 \langle u, \theta_\star \rangle^2 + \frac{1}{16} \langle u-v, \theta_\star - \hat{\theta} \rangle^2 \langle u, \theta_\star \rangle^2$$

$$\geq \frac{1}{8} \langle v, \theta_\star - \hat{\theta} \rangle^2 \langle u, \theta_\star \rangle^2 \geq \frac{kr^2}{8d} \langle v, \theta_\star - \hat{\theta} \rangle^2 .$$

Rearranging shows that

$$\langle v, \theta_\star - \hat{\theta} \rangle^2 \leq \frac{8d\beta}{mkr^2} \leq \frac{\tau^2}{4} . \tag{7}$$

For the second case, $\langle u, \hat{\theta} + \theta_\star \rangle \leq 2|\langle v, \hat{\theta} + \theta_\star \rangle|$. Then,

$$\frac{\beta}{m} \geq \sum_{a \in \mathcal{A}} \langle a, \theta_\star - \hat{\theta} \rangle^2 \langle a, \theta_\star + \hat{\theta} \rangle^2 \geq \frac{1}{4} \langle v, \hat{\theta} - \hat{\theta} \rangle^2 \langle u, \hat{\theta} + \theta_\star \rangle \geq \frac{kr^2}{8d} \langle v, \theta_\star - \hat{\theta} \rangle^2 .$$

And again, Eq. (7) holds. Summarising, $\langle v, \hat{\theta} \rangle$ is an estimator of $\langle v, \theta_\star \rangle$ up to accuracy $\tau/2$. By the definition of the algorithm, the iteration only ends if $|\langle v, \hat{\theta} \rangle| \geq \tau$. Therefore, with $w = \langle v, \hat{\theta} \rangle v$, we have $\|w\|^2 = \langle v, \hat{\theta} \rangle^2 \geq \tau^2$. Furthermore, $\langle w, \theta_\star \rangle = \langle v, \hat{\theta} \rangle \langle v, \theta_\star \rangle \in [\|w\|^2/2, 2\|w\|^2]$. Therefore if (a) and (b) hold for $\mathcal{E}$ computed after iteration k, they also hold for $\mathcal{E}$ computed after iteration $k+1$.

Step 5: Running time The length of an iteration is determined by the corresponding value of m and the number of samples of v. The former is an iteration-dependent constant, while the latter depends principally on how many samples are needed before $|\langle v, \theta_\star \rangle|$ is suitably large. The law of σ is the uniform distribution on $\mathbb{S}_1^{d-1} \cap \text{span}(\mathcal{E})$, which is the uniform distribution on a sphere of dimension $d-1-|\mathcal{E}|$ embedded in $\mathbb{R}^d$. The squared norm of the projection of $\theta_\star$ onto $\text{span}(\mathcal{E})^\perp$ is

$$\|\theta_\star\|^2 - \sum_{w \in \mathcal{E}} \frac{\langle \theta_\star, w \rangle^2}{\|w\|^2} \geq r^2 - 2 \sum_{w \in \mathcal{E}} \|w\|^2 \geq \frac{r^2}{2} ,$$

where we used (a) of the induction and the stopping condition in Line 15. Therefore, when v is sampled uniformly from $\mathbb{S}_1^{d-1} \cap \text{span}(\mathcal{E})^\perp$, by Lemma 9,

$$\mathbb{P}\left(\langle v, \theta_\star \rangle^2 \geq 3\tau^2/2 \right) = \mathbb{P}\left(\langle v, \theta_\star \rangle^2 \geq \frac{3r^2}{2d} \right) \geq \text{const} > 0 ,$$

Furthermore, by the concentration analysis in the previous step, an iteration will end once a v has been sampled for which $\langle v, \theta_\star \rangle^2 \geq 3\tau^2/2$. Hence, the expected number of times the algorithm samples v per iteration is constant and a simple calculation using the definition of m in Lines 1 and 8 shows that the expected number of rounds used by the algorithm is at most

$$\mathbb{E}[T] \leq \text{const} \frac{d^2}{r^4} \log(n) \log(d) . \qquad \square$$

6 Proof of Theorem 1 and Theorem 3

Proof of Theorem 1. Run Algorithm 1 and if it halts, feed the returned action to the input of the explore-then-commit algorithm analysed in Theorem 5. Algorithm 1 fails to return suitable action with probability at most $1/n$, so the contribution of this event to the regret is negligible. By Theorem 6, the regret incurred by Algorithm 1 is bounded by

$$\mathbb{E}\left[\sum_{t=1}^{T}\left(r^2 - \langle A_t, \theta_\star \rangle^2\right)\right] \leq r^2 \mathbb{E}[T]$$

$$\leq \min\left(nr^2, \text{const}\,\frac{d^2}{r^4}\log(d)\log(n)\right) \leq \text{const}\,d\sqrt{n\log(d)\log(n)}\,.$$

Combining this with the regret bound established in Theorem 5 yields the result. □

Proof of Theorem 3. We use a standard reduction [Lattimore and Szepesvári, 2020, Chapter 33]. Let π be the policy used in the proof of Theorem 1 with $\widehat{A}_\star$ sampled uniformly from $(A_t)_{t=1}^n$. By Theorem 1,

$$\mathfrak{r}_n(\pi, \theta_\star) = \frac{1}{n}\left(nr^2 - \mathbb{E}\left[\sum_{t=1}^{n}\langle A_t, \theta_\star \rangle^2\right]\right) = \frac{\mathfrak{R}_n(\pi, \theta_\star)}{n} \leq \text{const}\,d\sqrt{\frac{\log(n)\log(d)}{n}}\,. \qquad □$$

7 Lower bounds

The proof of Theorem 2 is based on a direct analysis of the Bayesian regret via a change of measure argument. Compared to the usual arguments based on Pinsker's inequality, the idea used here does not rely on any boundedness assumptions. What is important to show is that when $\theta_\star$ is sampled uniformly from $\mathbb{S}_r^{d-1}$, then for suitably small r the learner cannot learn much about $\theta_\star$. The proof of Theorem 4 makes use of Fano's inequality and can be found in Appendix C. The technique used in the proof below also yields a lower bound that matches the upper bound in Theorem 3 up to logarithmic factors.

Proof of Theorem 2. Let r be a positive constant to be tuned subsequently and σ be the uniform (Haar) measure on $\mathbb{S}_r^{d-1}$. Let π be an arbitrary policy. Given $\theta \in \mathbb{R}^d$, let $\mathbb{P}_\theta$ be the measure on interaction sequences induced by the interaction between a π and the bandit determined by θ. Let $\mathbb{P} = \sigma \otimes \mathbb{P}_\theta$ be the product of σ and probability kernel $(\mathbb{P}_\theta : \theta \in \mathbb{S}_r^{d-1})$. As usual, let $\mathbb{E}_\theta$ denote the expectation with respect to $\mathbb{P}_\theta$ and $\mathbb{E}$ the expectation with respect to $\mathbb{P}$. Let $Z_t = \sum_{s=1}^{t} X_s \langle A_s, \theta \rangle^2 - \frac{1}{2}\langle A_s, \theta \rangle^4$. Then,

$$\mathbb{E}[\langle A_t, \theta \rangle^4 \mathbf{1}(Z_{t-1} \leq \gamma)] = \int_{\mathbb{S}_r^{d-1}} \mathbb{E}_\theta[\langle A_t, \theta \rangle^4 \mathbf{1}(Z_{t-1} \leq \gamma)]\,d\sigma(\theta)$$

$$= \int_{\mathbb{S}_r^{d-1}} \mathbb{E}_{\mathbf{0}}\left[\langle A_t, \theta \rangle^4 \mathbf{1}(Z_{t-1} \leq \gamma) \exp\left(-\frac{1}{2}\sum_{s=1}^{t-1}\left((X_s - \langle A_s, \theta \rangle^2)^2 - X_s^2\right)\right)\right]d\sigma(\theta)$$

$$= \int_{\mathbb{S}_r^{d-1}} \mathbb{E}_{\mathbf{0}}\left[\langle A_t, \theta \rangle^4 \mathbf{1}(Z_{t-1} \leq \gamma) \exp(Z_{t-1})\right]d\sigma(\theta)$$

$$\leq \exp(\gamma)\int_{\mathbb{S}_r^{d-1}} \mathbb{E}_{\mathbf{0}}\left[\langle A_t, \theta \rangle^4\right]d\sigma(\theta) = \frac{3\exp(\gamma)r^4}{d^2 + 2d}\,.$$

Next, define a random time

$$\tau = \min\left\{t : Z_t \geq \gamma \text{ or } \sum_{s=1}^{t}\langle A_s, \theta \rangle^4 \geq 1\right\} \quad \text{with } \gamma = 1 + \log(4)\,.$$

Now,

$$\{\tau \leq n\} \subset \left\{\sum_{t=1}^{\tau} X_s \langle A_s, \theta \rangle^2 - \frac{3}{2}\langle A_s, \theta \rangle^4 \geq \gamma - 1\right\} \cup \left\{\sum_{t=1}^{n}\langle A_s, \theta \rangle^4 \mathbf{1}(\tau \geq t) \geq 1\right\}\,.$$

231 By a union bound,

$$\mathbb{P}(\tau \leq n) \leq \underbrace{\mathbb{P}\left(\sum_{t=1}^{\tau} X_s \langle A_s, \theta \rangle^2 - \frac{3}{2}\langle A_s, \theta \rangle^4 \geq \gamma - 1\right)}_{(A)} + \underbrace{\mathbb{P}\left(\sum_{t=1}^{n} \langle A_s, \theta \rangle^4 \mathbf{1}(\tau \geq t) \geq 1\right)}_{(B)}.$$

232 By the definition of X_s, Markov's inequality and the moment generating function of a Gaussian,

$$(A) \leq \exp(1 - \gamma)\mathbb{E}\left[\exp\left(\sum_{t=1}^{\tau} X_s \langle A_s, \theta \rangle^2 - \frac{3}{2}\langle A_s, \theta \rangle^4\right)\right] \leq \exp(1 - \gamma) = \frac{1}{4}.$$

233 Meanwhile, by Markov's inequality,

$$(B) \leq \mathbb{E}\left[\sum_{t=1}^{n} \langle A_t, \theta \rangle^4 \mathbf{1}(\tau \geq t)\right] \leq \frac{6\exp(\gamma)nr^4}{d^2 + 2d} = \frac{24\exp(1)nr^4}{d^2 + 2d} = \frac{1}{4},$$

234 where the last equality follows by choosing $r^2 = \sqrt{(d^2 + 2d)/(96\exp(1)n)}$. Hence, $\int_{\mathbb{S}_r^{d-1}} \mathbb{P}_\theta(\tau \leq$
235 $n)\,\mathrm{d}\sigma(\theta) = \mathbb{P}(\tau \leq n) \leq 1/2$ and so there exists a $\theta \in \mathbb{S}_r^{d-1}$ such that

$$\mathbb{P}_\theta\left(\sum_{t=1}^{n} \langle A_t, \theta \rangle^4 \leq 1\right) \geq 1/2.$$

236 Suppose that $\sum_{t=1}^{n} \langle A_t, \theta \rangle^4 \leq 1$, then by Cauchy-Schwarz, $\sum_{t=1}^{n} \langle A_t, \theta \rangle^2 \leq \sqrt{n \sum_{t=1}^{n} \langle A_t, \theta \rangle^4} \leq$
237 $\sqrt{n}$. Therefore, $\mathbb{P}_\theta(\sum_{t=1}^{n} \langle A_t, \theta \rangle^2 \leq \sqrt{n}) \geq 1/2$ and

$$\mathfrak{R}_n(\pi, \theta) = \mathbb{E}_\theta\left[\sum_{t=1}^{n}\left(r^2 - \langle A_t, \theta \rangle^2\right)\right] \geq \mathbb{P}_\theta\left(\sum_{t=1}^{n} \langle A_t, \theta \rangle^2 \leq \sqrt{n}\right)(nr^2 - \sqrt{n}) \geq \frac{nr^2 - \sqrt{n}}{2}.$$

238 The result follows from choice of r. $\qquad\square$

8 Discussion

240 **Unknown radius** The assumption that $r = \|\theta_\star\|$ is known to the learner is easily relaxed by estimat-
241 ing $\|\theta_\star\|$. Note first that all our analysis holds with only trivial modifications if $r \in [\frac{1}{2}\|\theta_\star\|, \|\theta_\star\|]$.
242 Next, if A is sampled uniformly from $\mathbb{S}_1^{d-1}$ and $X = \langle A, \theta_\star \rangle^2 + \eta$ and η is a standard Gaussian, then
243 $\mathbb{E}[X] = \frac{1}{d}\|\theta_\star\|^2$ and $\mathbb{V}[X] = 1 + 2(d-1)/(d^3 + 2d^2) = \Theta(1)$. Therefore $\|\theta_\star\|$ can be estimated to
244 within an arbitrary multiplicative factor and at confidence level $1 - 1/n$ using $\mathrm{const}\, d^2/\|\theta_\star\|^4 \log(n)$
245 interactions with the bandit.

246 **Computation complexity** The only computational challenge is finding the least squares estimates,
247 which is a non-convex optimisation problem. Candès et al. [2015b] proposed a Wirtinger flow
248 algorithm that starts with a spectral initialization, and then refines this initial estimate using a local
249 update like gradient descent. The computational complexity of the Wirtinger flow algorithm with
250 ε-accuracy is $O(nd^2 \log(1/\varepsilon))$ where n is the number of samples.

251 **Adversarial setting** Kotłowski and Neu [2019] study the adversarial version of this problem, where
252 the learner observes $\langle A_t, \theta_t \rangle^2$ and $(\theta_t)_{t=1}^{n}$ is an adversarially sequence with $\theta_t \in B^d$ for all t. They
253 prove an upper bound of $\mathfrak{R}_n = O(d\sqrt{n \log(n)})$ and a lower bound of $\Omega(\sqrt{dn})$. Natural attempts at
254 improving the lower bound all fail. We believe that the upper bound is loose, but proving this remains
255 delicate. No warm starting procedure will work anymore because the information gained may be
256 useless in the presence of a change point. New ideas are needed.

257 **Rank-p** Perhaps the most natural open question is whether or not our analysis can be extended to
258 the low rank bandit problem without our particular assumptions on the action set and environments
259 matrices.

260 **Principled algorithms** Can optimism or information-directed sampling be made to work? The main
261 challenge is to understand the sample paths of these algoritms *before* learning takes place.

References

Y. Abbasi-Yadkori, D. Pál, and Cs. Szepesvári. Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems*, pages 2312–2320, 2011.

P. Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3(Nov):397–422, 2002.

S. Boucheron, G. Lugosi, and P. Massart. *Concentration inequalities: A nonasymptotic theory of independence*. OUP Oxford, 2013.

T. Cai, X. Li, and Z. Ma. Optimal rates of convergence for noisy sparse phase retrieval via thresholded wirtinger flow. *The Annals of Statistics*, 44(5):2221–2251, 2016.

E. J. Candès, Y. C. Eldar, T. Strohmer, and V. Voroninski. Phase retrieval via matrix completion. *SIAM review*, 57(2):225–251, 2015a.

E. J. Candès, X. Li, and M. Soltanolkotabi. Phase retrieval via Wirtinger flow: Theory and algorithms. *IEEE Transactions on Information Theory*, 61(4):1985–2007, 2015b.

Y. Chen and E. J. Candès. Solving random quadratic systems of equations is nearly as easy as solving linear systems. *Communications on pure and applied mathematics*, 70(5):822–883, 2017.

Y. Chen, Y. Chi, J. Fan, and C. Ma. Gradient descent with random initialization: Fast global convergence for nonconvex phase retrieval. *Mathematical Programming*, 176(1):5–37, 2019.

W. Chu, L. Li, L. Reyzin, and R. Schapire. Contextual bandits with linear payoff functions. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pages 208–214, 2011.

V. Dani, T. Hayes, and S. Kakade. Stochastic linear optimization under bandit feedback. 2008.

S. Dasgupta and A. Gupta. An elementary proof of a theorem of johnson and lindenstrauss. *Random Structures & Algorithms*, 22(1):60–65, 2003.

A. M. Devraj, B. Van Roy, and K. Xu. A bit better? quantifying information for bandit learning. *arXiv preprint arXiv:2102.09488*, 2021.

S. Gerchinovitz, P. Ménard, and G. Stoltz. Fano's inequality for random variables. *Statistical Science*, 35(2):178–201, 2020.

R. Huang, T. Lattimore, A. György, and Cs. Szepesvári. Following the leader and fast rates in online linear prediction: Curved constraint sets and other regularities. *Journal of Machine Learning Research*, 18:1–31, 2017.

K-S Jun, R. Willett, S. Wright, and R. Nowak. Bilinear bandits with low-rank structure. In *International Conference on Machine Learning*, pages 3163–3172. PMLR, 2019.

S. Katariya, B. Kveton, Cs. Szepesvári, C. Vernade, and Z. Wen. Bernoulli rank-1 bandits for click feedback. In *Proceedings of the 26th International Joint Conference on Artificial Intelligence*, pages 2001–2007, 2017a.

S. Katariya, B. Kveton, Cs. Szepesvári, C. Vernade, and Z. Wen. Stochastic rank-1 bandits. In *Artificial Intelligence and Statistics*, pages 392–401. PMLR, 2017b.

J. Kirschner, T. Lattimore, and A. Krause. Information directed sampling for linear partial monitoring. In Jacob Abernethy and Shivani Agarwal, editors, *Proceedings of Thirty Third Conference on Learning Theory*, volume 125 of *Proceedings of Machine Learning Research*, pages 2328–2369. PMLR, 2020.

W. Kotłowski and G. Neu. Bandit principal component analysis. In Alina Beygelzimer and Daniel Hsu, editors, *Proceedings of the Thirty-Second Conference on Learning Theory*, volume 99 of *Proceedings of Machine Learning Research*, pages 1994–2024, Phoenix, USA, 25–28 Jun 2019. PMLR.

T. Lattimore and Cs. Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.

B. Laurent and P. Massart. Adaptive estimation of a quadratic functional by model selection. *Annals of Statistics*, pages 1302–1338, 2000.

Y. Lu, A. Meisami, and A. Tewari. Low-rank generalized linear bandit problems. In *International Conference on Artificial Intelligence and Statistics*, pages 460–468. PMLR, 2021.

P. Rusmevichientong and J. N. Tsitsiklis. Linearly parameterized bandits. *Mathematics of Operations Research*, 35(2):395–411, 2010.

D. Russo and B. Van Roy. Learning to optimize via information-directed sampling. *Operations Research*, 66(1):230–252, 2018.

D. Russo and B. Van Roy. Learning to optimize via information-directed sampling. In *Advances in Neural Information Processing Systems*, pages 1583–1591. Curran Associates, Inc., 2014.

Ju Sun, Qing Qu, and John Wright. A geometric analysis of phase retrieval. *Foundations of Computational Mathematics*, 18(5):1131–1198, 2018.

C. Trinh, E. Kaufmann, C. Vernade, and R. Combes. Solving bernoulli rank-one bandits with unimodal thompson sampling. *31st International Conference on Algorithmic Learning Theory*, pages 1–28, 2020.