Parameter-free Regret in High Probability with Heavy Tails

Abstract

We present new algorithms for online convex optimization over unbounded domains that obtain parameter-free regret in high-probability given access only to potentially heavy-tailed subgradient estimates. Previous work in unbounded domains considers only in-expectation results for subexponential subgradients. Unlike in the bounded domain case, we cannot rely on straight-forward martingale concentration due to exponentially large iterates produced by the algorithm. We develop new regularization techniques to overcome these problems.

1   Introduction

In this paper, we consider the problem of online learning with convex losses, also called online convex optimization, with heavy-tailed stochastic subgradients. In the classical online convex optimization setting, given a convex set $\mathcal{W}$, a learning algorithm must repeatedly output a vector $\mathbf{w}_t \in \mathcal{W}$, and then observe a convex loss function $\ell_t : \mathcal{W} \to \mathbb{R}$ and incur a loss of $\ell_t(\mathbf{w}_t)$. After T such rounds, the algorithm's quality is measured by the *regret* with respect to a fixed competitor $\mathbf{u} \in \mathcal{W}$:

$$R_T(\mathbf{u}) = \sum_{t=1}^{T} \ell_t(\mathbf{w}_t) - \sum_{t=1}^{T} \ell_t(\mathbf{u})$$

Online convex optimization is widely applicable, and has been used to design popular stochastic optimization algorithms ([Duchi et al., 2010a, Kingma and Ba, 2014, Reddi et al., 2018]), for control of linear dynamical systems [Agarwal et al., 2019], or even building concentration inequalities [Vovk, 2007, Waudby-Smith and Ramdas, 2020, Orabona and Jun, 2021].

A popular approach to this problem reduces it to *online linear optimization* (OLO): if $\mathbf{g}_t$ is a subgradient of ℓ_t at $\mathbf{w}_t$, then $R_T(\mathbf{u}) \leq \sum_{t=1}^{T} \langle \mathbf{g}_t, \mathbf{w}_t - \mathbf{u} \rangle$ so that it suffices to design an algorithm that considers only linear losses $\mathbf{w} \mapsto \langle \mathbf{g}_t, \mathbf{w} \rangle$. Then, by assuming that the domain $\mathcal{W}$ has some finite diameter D, standard arguments show that online gradient descent [Zinkevich, 2003] and its variants achieve $R_T(\mathbf{u}) \leq O(D\sqrt{T})$ for all $\mathbf{u} \in \mathcal{W}$. See the excellent books Cesa-Bianchi and Lugosi [2006], Shalev-Shwartz [2011], Hazan [2019], Orabona [2019] for more detail.

Deviating from the classical setting, we study the more difficult case in which, (1) the domain $\mathcal{W}$ may have *infinite* diameter (such as $\mathcal{W} = \mathbb{R}^d$), and (2) instead of observing the loss ℓ_t, the algorithm is presented only with a potentially heavy-tailed stochastic subgradient estimate $\mathbf{g}_t$ with $\mathbb{E}[\mathbf{g}_t | \mathbf{w}_t] \in \partial \ell_t(\mathbf{w}_t)$. Our goal is to develop algorithms that, with high probability, obtain essentially the same regret bounds that would be achievable even if the full information was available.

Considering only the setting of infinite diameter $\mathcal{W}$ with *exact* subgradients $\mathbf{g}_t \in \partial \ell_t(\mathbf{w}_t)$, past work has achieved bounds of the form $R_T(\mathbf{u}) \leq \tilde{O}(\epsilon + \|\mathbf{u}\|\sqrt{T})$ for all $\mathbf{u} \in \mathcal{W}$ simultaneously for any user-specified ϵ, directly generalizing the $O(D\sqrt{T})$ rate available when $D < \infty$ [Orabona and Pál,

2016, Cutkosky and Orabona, 2018, Foster et al., 2017, Mhammedi and Koolen, 2020, Chen et al., 2021]. As such algorithms do not require knowledge of the norm $\|\mathbf{u}\|$ that is usually used to specify a learning rate for gradient descent, we will call them *parameter-free*. Note that such algorithms typically guarantee constant $R_T(0)$, which is not achieved by any known form of gradient descent.

While parameter-free algorithms appear to fully generalize the finite-diameter case, they fall short when $\mathbf{g}_t$ is a stochastic subgradient estimate. In particular, lower-bounds suggest that parameter-free algorithms must require Lipschitz ℓ_t [Cutkosky and Boahen, 2017], which means that care must be taken when using $\mathbf{g}_t$ with unbounded noise as this may make ℓ_t "appear" to be non-Lipschitz. In the case of *subexponential* $\mathbf{g}_t$, Jun and Orabona [2019], van der Hoeven [2019] provide parameter-free algorithms that achieve $\mathbb{E}[R_T(\mathbf{u})] \leq \tilde{O}(\epsilon + \|\mathbf{u}\|\sqrt{T})$, but these techniques do not easily extend to heavier-tailed $\mathbf{g}_t$ or to high-probability bounds. The high-probability statement is particularly elusive (even with subexponential $\mathbf{g}_t$) because standard martingale concentration approaches appear to fail spectacularly. This failure may be counterintuitive: for *finite diameter* $\mathcal{W}$, one can observe that $\langle \mathbf{g}_t - \mathbb{E}[\mathbf{g}_t], \mathbf{w}_t - \mathbf{u} \rangle$ forms a martingale difference sequence with variance determined by $\|\mathbf{w}_t - \mathbf{u}\| \leq D$, which allows for relatively straightforward high-probability bounds. However, parameter-free algorithms typically exhibit *exponentially growing* $\|\mathbf{w}_t\|$ in order to compete with all possible scales of $\|\mathbf{u}\|$, which appears to stymie such arguments.

Our work overcomes these issues. Requiring only that $\mathbf{g}_t$ have a bounded $\mathfrak{p}$th moment for some $\mathfrak{p} \in (1, 2]$, we devise a new algorithm whose regret with probability at least $1 - \delta$ is $R_T(\mathbf{u}) \leq \tilde{O}(\epsilon + \|\mathbf{u}\|T^{1/\mathfrak{p}}\log(1/\delta))$ for all $\mathbf{u}$ simultaneously. The $T^{1/\mathfrak{p}}$ dependency is unimprovable Bubeck et al. [2013a], Vural et al. [2022]. Moreover, we achieve these results simply by adding a novel and carefully designed regularizers to the losses ℓ_t in a way that converts any parameter-free algorithm with sufficiently small regret into one with the desired high probability guarantee.

Contribution and Organization: After formally introducing and discussing our setup in Sections 2 and 3, we then proceed to conduct an initial analysis for the 1-D case $\mathcal{W} = \mathbb{R}$. First (Section 4), we introduce a parameter-free algorithm for *supexponential* $\mathbf{g}_t$ that achieves regret $\tilde{O}(\epsilon + |u|\sqrt{T})$ in high probability. This already improves significantly on prior work, and is accomplished by introducing a novel regularizer that "cancels" some unbounded martingale concentration terms, a technique that may have wider application. Secondly (Section 5), we extend to heavy tailed $\mathbf{g}_t$ by employing clipping, which has been used in prior work on optimization [Bubeck et al., 2013a, Gorbunov et al., 2020, Zhang et al., 2020, Cutkosky and Mehta, 2021] to convert heavy-tailed estimates into subexponential ones. This clipping introduces some bias that must be carefully offset by yet another novel regularization (which may again be of independent interest) in order to yield our final $\tilde{O}(\epsilon + |u|T^{1/\mathfrak{p}})$ parameter-free regret guarantee. Finally (Section 6), we extend to arbitrary dimensions via the reduction from Cutkosky and Orabona [2018].

2 Preliminaries

Our algorithms interact with an adversary in which for $t = 1 \ldots T$ the algorithm first outputs a vector $\mathbf{w}_t \in \mathcal{W}$ for $\mathcal{W}$ a convex subset of some real Hilbert space, and then the adversary chooses a convex and G-Lipschitz loss function $\ell_t : \mathcal{W} \to \mathbb{R}$ and a distribution P_t such that for $\mathbf{g}_t \sim P_t$, $\mathbb{E}[\mathbf{g}_t] \in \partial \ell_t(\mathbf{w}_t)$ and $\mathbb{E}[\|\mathbf{g}_t - \mathbb{E}[\mathbf{g}_t]\|^\mathfrak{p}] \leq \sigma^\mathfrak{p}$ for some $\mathfrak{p} \in (1, 2]$. The algorithm then observes a random sample $\mathbf{g}_t \sim P_t$. After t rounds, we compute the *regret*, which is a function $R_t(\mathbf{u}) = \sum_{i=1}^{t} \ell_i(\mathbf{w}_i) - \ell_i(\mathbf{u})$. Our goal is to guarantee $R_T(\mathbf{u}) \leq \epsilon + \tilde{O}(\|\mathbf{u}\|T^{1/\mathfrak{p}})$ for all $\mathbf{u}$ simultaneously with high probability.

Throughout this paper we will employ the notion of a *subexponential* random sequence:

Definition 1. *Suppose $\{X_t\}$ is a sequence of random variables adapted to a filtration $\mathcal{F}_t$ such that $\{X_t, \mathcal{F}_t\}$ is a martingale difference sequence. Further, suppose $\{\sigma_t, b_t\}$ are random variables such that σ_t, b_t are both $\mathcal{F}_{t-1}$-measurable for all t. Then, $\{X_t, \mathcal{F}_t\}$ is $\{\sigma_t, b_t\}$ subexponential if*

$$\mathbb{E}[\exp(\lambda X_t)|\mathcal{F}_{t-1}] \leq \exp(\lambda^2 \sigma_t^2/2)$$

almost everywhere for all $\mathcal{F}_{t-1}$-measurable λ satisfying $\lambda < 1/b_t$.

We will use bold font ($\mathbf{g}_t$) to refer to vectors and normal font (g_t) to refer to scalars. Occasionally, we abuse notation to write $\nabla \ell_t(w_t)$ for an abitrary element of $\partial \ell_t(\mathbf{w}_t)$.

82 We present our results using $O(\cdot)$ to hide constant factors, and $\tilde{O}(\cdot)$ to hide $\log$ factors (such as some
83 power of $(\log(T))$ dependence) in the main text, the exact results are left at the last line of proof for
84 interested readers.

85 Finally, observe that by the unconstrained-to-constrained conversion of Cutkosky and Orabona [2018],
86 we need only consider the case that $\mathcal{W}$ is an entire vector space. By solving the problem for this case,
87 the reduction implies a high-probability regret algorithm for any convex $\mathcal{W}$.

3 Challenges

89 A reader experienced with high probability bounds in online optimization may suspect that one could
90 apply fairly standard approaches such as clipping and martingale concentration to easily achieve high
91 probability bounds with heavy tails. While such techniques do appear in our development, the story is
92 far from straightforward. In this section, we will outline these non-intuitive difficulties. For a further
93 discussion, see Section 3 of Jun and Orabona [2019].

94 For simplicity, consider a $1d$ problem. Before attempting a high probability bound, one may try to
95 derive a regret bound in expectation with heavy-tailed gradient g_t via the following calculation:

$$\mathbb{E}[R_T(u)] = \mathbb{E}\left[\sum_{t=1}^{T} \ell_t(w_t) - \ell_t(u)\right] \le \sum_{t=1}^{T} \mathbb{E}\left[\langle g_t, w_t - u\rangle\right] + \sum_{t=1}^{T} \mathbb{E}\left[\langle \nabla \ell_t(w_t) - g_t, w_t - u\rangle\right]$$

96 The second sum above vanishes, so one is tempted to send g_t directly to some existing parameter-free
97 algorithm to obtain low regret. Unfortunately, most parameter-free algorithms require a uniform
98 bound on $|g_t|$ - even a *single* bound-violating g_t could be catastrophic [Cutkosky and Boahen, 2017].
99 With heavy-tailed g_t, we are quite likely to encounter such a g_t for any reasonable uniform bound. In
100 fact, the issue is difficult even for light-tailed g_t, as described in detail by Jun and Orabona [2019].

101 A natural approach to overcome this uniform bound issue is to incorporate some form of clipping, a
102 commonly used technique controlling for heavy-tailed data. We defined the clipped subgradient $\hat{g}_t$
103 with a positive clipping parameter τ as:

$$\hat{g}_t = \frac{g_t}{|g_t|} \min(\tau, |g_t|)$$

104 The expected regret can now be written as:

$$\mathbb{E}[R_T(u)] \le \sum_{t=1}^{T} \mathbb{E}\left[\langle \hat{g}_t, w_t - u\rangle\right] + \underbrace{\sum_{t=1}^{T} \mathbb{E}\left[\langle \mathbb{E}[\hat{g}_t] - \hat{g}_t, w_t - u\rangle\right]}_{\text{martingale concentration?}} + \underbrace{\sum_{t=1}^{T} \mathbb{E}\left[\langle \nabla \ell_t(w_t) - \mathbb{E}[\hat{g}_t], w_t - u\rangle\right]}_{\text{bias}}$$

(1)

105 Since $|\hat{g}_t| \le \tau$, the first term can in fact be controlled for appropriate τ at a $\epsilon + \tilde{O}(|u|\sqrt{T})$ rate using
106 sufficiently advanced parameter-free algorithms (e.g. Cutkosky and Orabona [2018]). However, now
107 bias accumulates in the last term, which is difficult to bound due to the dependency on w_t, which on
108 the surface appears to require detailed (and difficult) analysis of the dynamics of the parameter-free
109 algorithm. In fact, from naive inspection of the updates for standard parameter-free algorithms, one
110 expects that $|w_t|$ could actually grow exponentially fast in t, leading to a very large bias term.

111 Finally, disregarding these challenges faced even in expectation, to derive a high-probability bound
112 the natural approach is to bound the middle sum in (1) via some martingale concentration argument.
113 Unfortunately, the variance process for this martingale depends on w_t just like the bias term. In
114 fact, this issue appears even if the original g_t already have bounded norm! Thus, we again appear to
115 encounter a need for small w_t, which may instead grow exponentially. In summary, the unbounded
116 nature of w_t makes dealing with any kind of stochasticity in the g_t very difficult. In this work we will
117 develop techniques based on regularization that intuitively force the w_t to behave well, eventually
118 enabling our high-probability regret bounds.

4 Bounded Sub-exponential Noise via Cancellation

120 In this section, we describe a how to obtain regret bound in high probability for stochastic subgradients
121 g_t for which $\mathbb{E}[g_t^2] \le \sigma^2$ and $|g_t| \le b$ for some σ and b (in particular, g_t exhibits $(\sigma, 4b)$-sub-

exponential noise). We focus on the 1-dimensional case with $\mathcal{W} = \mathbb{R}$. The extension to more general $\mathcal{W}$ is covered in Section 6. Our method involves two coordinated techniques. First, we introduce a carefully designed regularizer ψ_t such that *any algorithm* that achieves low regret with respect to the losses $w \mapsto g_t w + \psi_t(w)$ will automatically ensure low regret with high probability on the original losses ℓ_t. Unfortunately, ψ_t is not Lipschitz and so it is still not obvious how to obtain low regret. We overcome this final issue by an "implicit" modification of the optimistic parameter-free algorithm of Cutkosky [2019]. Our overall goal is a regret bound of $R_T(u) \leq \tilde{O}(\epsilon + |u|(\sigma + G)\sqrt{T} + b|u|)$ for all u with high probability. Note that with this bound, b can be $O(\sqrt{T})$ before it becomes a significant factor in the regret.

Let us proceed to sketch the first (and most critical) part of this procedure: the regularizer ψ_t. Define $\epsilon_t = \nabla \ell_t(w_t) - g_t$, so that ϵ_t captures the "noise" in the gradient estimate g_t. In this section, we will assume that ϵ_t is (σ, b)-subexponential for all t for some given σ, b and $|g_t| \leq b/2$. Then we can write:

$$
\begin{aligned}
R_T(u) &\leq \sum_{t=1}^{T} \langle \nabla \ell_t(w_t), w_t - u \rangle = \sum_{t=1}^{T} \langle g_t, w_t - u \rangle + \sum_{t=1}^{T} \langle \epsilon_t, w_t \rangle - \sum_{t=1}^{T} \langle \epsilon_t, u \rangle \\
&\leq \sum_{t=1}^{T} \langle g_t, w_t - u \rangle + \underbrace{\left| \sum_{t=1}^{T} \epsilon_t w_t \right| + |u| \left| \sum_{t=1}^{T} \epsilon_t \right|}_{\text{"noise term", NOISE}}
\end{aligned}
\tag{2}
$$

Now, the natural strategy is to run an OLO algorithm $\mathcal{A}$ on the observed g_t, which will obtain some regret $R_T^{\mathcal{A}}(u) = \sum_{t=1}^{T} \langle g_t, w_t - u \rangle$, and then show that the remaining NOISE terms are small. To this end, from subexponential martingale concentration, we might hope to show that with probability $1 - \delta$, we have an identity similar to:

$$
\text{NOISE} \leq \sigma \sqrt{\sum_{t=1}^{T} w_t^2 \log(1/\delta)} + b \max_t |w_t| \log(1/\delta) + |u|\sigma\sqrt{T \log(1/\delta)} + |u| b \log(1/\delta)
$$

The dependency of $|u|$ above appears to be relatively innocuous it only contributes $\tilde{O}(|u|\sigma\sqrt{T} + |u|b)$ to the regret. The w_t-dependent term is more difficult as it involves a dependency on the algorithm $\mathcal{A}$. This captures the complexity of our unbounded setting: in a *bounded domain*, the situation is far simpler as we can uniformly bound $|w_t| \leq D$, ideally leaving us with an $\tilde{O}(D\sqrt{T})$ bound overall.

Unfortunately, in the unconstrained case, $|w_t|$ could grow exponentially ($|w_t| \sim 2^t$) even when u is very small, so we cannot rely on a uniform bound. In fact, even in the finite-diameter case, if we wish to guarantee $R_T(0) \leq \epsilon$, the bound $|w_t| \leq D$ is still too coarse. The resolution is to instead feed the algorithm $\mathcal{A}$ a *regularized* loss $\hat{\ell}_t(w) = \langle g_t, w \rangle + \psi_t(w)$, where ψ_t will "cancel" the w_t dependency in the martingale concentration. That is, we now re-define $R_T^{\mathcal{A}}(u) = \sum_{t=1}^{T} \hat{\ell}_t(w_t) - \hat{\ell}_t(u)$ and compute:

$$
\sum_{t=1}^{T} \langle g_t, w_t - u \rangle \leq R_T^{\mathcal{A}}(u) - \sum_{t=1}^{T} \nabla \psi_t(w_t) + \sum_{t=1}^{T} \nabla \psi_t(u)
\tag{3}
$$

And now combine equations (2) and (3):

$$
\begin{aligned}
R_T(u) &\leq R_T^{\mathcal{A}}(u) + \text{NOISE} - \sum_{t=1}^{T} \nabla \psi_t(w_t) + \sum_{t=1}^{T} \nabla \psi_t(u) \\
&\leq R_T^{\mathcal{A}}(u) + \sigma \sqrt{\sum_{t=1}^{T} w_t^2 \log(1/\delta)} + b \max_t |w_t| \log(1/\delta) - \sum_{t=1}^{T} \nabla \psi_t(w_t) \\
&\quad + |u|\sigma\sqrt{T \log(1/\delta)} + |u| b \log(1/\delta) + \sum_{t=1}^{T} \nabla \psi_t(u)
\end{aligned}
\tag{4}
$$

From this, we can read off the desired properties of ψ_t: (1) ψ_t should be large enough that $\sum_{t=1}^{T} \psi_t(w_t) \geq \sigma \sqrt{\sum_{t=1}^{T} w_t^2 \log(1/\delta)} + b \max_t |w_t| \log(1/\delta)$, (2) ψ_t should be small enough

that $\sum_{t=1}^{T} \psi_t(u) \leq \tilde{O}(|u|\sqrt{T})$, and (3), ψ_t should be such that $R_T^{\mathcal{A}}(u) = \tilde{O}(\epsilon + |u|\sqrt{T})$ for an appropriate algorithm $\mathcal{A}$. If we can exhibit a ψ_t satisfying all three properties, we will have developed a regret bound of $\tilde{O}(\epsilon + |u|\sqrt{T})$ in high probability.

It turns out that the modified Huber loss $r_t(w)$ defined in equation (5) and (6) with appropriately chosen constants $c_1, c_2, p_1, p_2, \alpha_1, \alpha_2$ satisfies criterion (1) and (2).

$$r_t(w; c, p, \alpha_0) = \begin{cases} c\left(p|w| - (p-1)|w_t|\right) \frac{|w_t|^{p-1}}{\left(\sum_{i=1}^{t} |w_i|^p + \alpha_0^p\right)^{1-1/p}}, & |w| > |w_t| \\ c|w|^p \frac{1}{\left(\sum_{i=1}^{t} |w_i|^p + \alpha_0^p\right)^{1-1/p}}, & |w| \leq |w_t| \end{cases} \tag{5}$$

$$\psi_t(w) = r_t(w; c_1, p_1, \alpha_1) + r_t(w; c_2, p_2, \alpha_2) \tag{6}$$

Let us take a moment to gain some intuition for these functions r_t and ψ_t. First, observe that r_t is always continuously differentiable, and that r_t's definition requires knowledge of w_t. This is acceptable because online learning algorithms must be able to handle even adaptively chosen losses. In particular, consider the $p = 2$ case, $r_t(w; c, 2, \alpha)$ for some positive constants c and α. We plot this function in Figure 1, where one can see that r_t grows quadratically for $|w| \leq |w_t|$, but grows only linearly afterwards so that r_t is Lipschitz.

Figure 1: $r_t(w; 1, 2, 1)$ when $\sum_{i=1}^{t} w_i^2 = 10$ and $w_t = 2$. The dashed line has slope $cp \frac{|w_t|^{p-1}}{\left(\sum_{i=1}^{t} |w_i|^p + \alpha_0^p\right)^{1/p}}$, so that r_t is quadratic for $|w| \leq |w_t|$ and linear otherwise. Notice that w_t is a constant used to define r_t - it is not the argument of the function.

Eventually, in Lemma 13 we will show that this functions satisfies

$$\sum_{t=1}^{T} r_t(w_t; c, 2, \alpha) \geq c\sqrt{\sum_{t=1}^{T} w_t^2} - \alpha$$

$$\sum_{t=1}^{T} r_t(u : c, 2, \alpha) \leq \tilde{O}(u\sqrt{T})$$

so that for appropriate choice of c and α, $r_t(w; c, 2, \alpha)$ will cancel the $O(\sqrt{\sum_{t=1}^{T} w_t^2})$ martingale concentration term while not adding too much to the regret - it satisfies criteria (1) and (2). The lower-bound follows from the standard inequality $\sqrt{a+b} \leq \sqrt{a} + \frac{b}{\sqrt{a+b}}$ since $r_t(w_t) = c\frac{w_t^2}{\sqrt{\alpha^2 + \sum_{i=1}^{t} w_i^2}}$. The upper-bound is more subtle, and involves the piece-wise definition. For simplicity, suppose it were true that either $|w_t| < |u|$ for all t or $|w_t| \geq |u|$ for all t. In the former case, $\sum_{t=1}^{T} r_t(u) = O\left(|u| \sum_{t=1}^{T} \frac{|w_t|}{\sqrt{\alpha + \sum_{i=1}^{t} w_i^2}}\right)$,

which via algebraic manipulation can be bounded as $\tilde{O}(|u|\sqrt{T})$. In the latter case, we have $\sum_{t=1}^{T} \frac{|u|^2}{\sqrt{\alpha^2 + \sum_{i=1}^{t} w_t^2}} \leq \sum_{t=1}^{T} \frac{|u|^2}{\sqrt{\alpha^2 + tu^2}} = \tilde{O}(|u|\sqrt{T})$ so that both cases result in the desired bound on $\sum_{t=1}^{T} r_t(u)$. The general setting is handled by partitioning the sum into two sets depending on whether $|w_t| \leq |u|$. In order to cancel the $\max_t |w_t|$ term in the martingale concentration, we employ $p = \log(T)$. This choice is motivated by the observation that $\|\mathbf{v}\|_{\log(T)} \in [\|\mathbf{v}\|_\infty, \exp(1)\|\mathbf{v}\|_\infty]$ for all $\mathbf{v} \in \mathbb{R}^{\log(T)}$. With this identity in hand, the argument is very similar to the $p = 2$ case.

The correct values for the constants are provided in Theorem 3. Again, at a high level, the important constants are p_1 and p_2. With $p_1 = 2$, we allow $\sum_t r_t(w_t; p = 2)$ to cancel out the $\sqrt{\sum_t w_t^2}$ martingale concentration term, while with $p_2 = \log(T)$, $\sum_t r_t(w_t; p = \log(T))$ cancels that $\max_t |w_t|$ term.

It remains to show that ψ_t also allows for small $R_T^{\mathcal{A}}(u)$ and so satisfies criterion (3). Unfortunately, our setting for c_2 in the definition of ψ_t is $\tilde{O}(b)$, which means that ψ_t is $\tilde{O}(b)$-Lipschitz. Since we wish to allow for $b = \Theta(\sqrt{T})$, this means that we cannot simply let $\mathcal{A}$ linearize ψ_t and apply an arbitrary OLO algorithm. Instead, we must exploit the fact that ψ_t is known *before* g_t is revealed. That is, algorithm $\mathcal{A}$ is chosen to exploit the structure composite loss $\hat{\ell}_t(w)$. Intuitively, the regret of

a composite loss should depend only on the non-composite g_t terms (as in e.g. Duchi et al. [2010b]). Our situation is slightly more complicated as ψ_t depends on w_t as well, but we nevertheless achieve the desired result via a modification of the parameter-free optimistic reduction in Cutkosky [2019]. For technical reasons, this algorithm still requires $|g_t| \leq b$ with probability 1, but will obtain regret only $R_T^{\mathcal{A}}(u) \leq \tilde{O}(\epsilon + |u|\sigma\sqrt{T} + |u|b)$. This technical limitation is lifted in the following section.

We display the method as Algorithm 1, which provides a regularization that cancels the $|w_t|$ dependent part of the NOISE term in (7). It also allows us to control $R_T^{\mathcal{A}}(u)$ to order $\tilde{O}(\epsilon + |u|\sigma\sqrt{T} + b|u|)$ by taking account into the predictable structure of regularizer $\psi_t(w)$. The algorithm requires black-box access to two base online learning algorithms, which we denote $\mathcal{A}_1$ and $\mathcal{A}_2$. These can be any algorithm that obtain so-called "second-order" parameter-free regret bounds, such as available in Cutkosky and Orabona [2018], van der Hoeven [2019], Kempka et al. [2019].

Following the intuition previously outlined in this section, We first provide a deterministic regret guarantee on the quantity $R_T^{\mathcal{A}}(u)$ as an intermediate result (Theorem 2). Then, we provide the analysis of the full procedure of Algorithm 1 for the final high probability result (Theorem 3). Missing proofs are provided in the appendix A and B.

Algorithm 1 Subexponential Noisy Gradients with Optimistic Online Learning

---

Require: $E[g_t] = \nabla \ell_t(w_t)$, $|g_t| \leq b$, $\mathbb{E}[g_t|w_t] \leq \sigma^2$ almost surely. Two independent online learning algorithms (e.g. copies of Algorithm 1 from Cutkosky and Orabona [2018]) labelled as $\mathcal{A}_1, \mathcal{A}_2$. Time horizon T, $0 < \delta \leq 1$.
1: **Initialize:**
     Constants $\{c_1, c_2, p_1, p_2, \alpha_1, \alpha_2\}$ from Theorem 3.   ▷ for defining ψ_t in equation (6)
     $H = c_1 p_1 + c_2 p_2$
2: **for** $t = 1$ to T **do**
3:     Receive x_t' from $\mathcal{A}_1$, y_t' from $\mathcal{A}_2$
4:     Rescale $x_t = (b+H)x_t'$, $y_t = H(b+H)y_t'$
5:     Solve for w_t: $w_t = x_t - y_t \nabla \psi_t(w_t)$ ▷ The solution exists by Lemma 6
6:     Play w_t to, suffer loss $\ell_t(w_t)$
7:     Receive g_t with $\mathbb{E}[g_t] \in \partial \ell_t(w_t)$
8:     Compute $\psi_t(w) = r_t(w; c_1, p_1, \alpha_1) + r_t(w; c_2, p_2, \alpha_2)$ and $\nabla \psi_t(w_t)$ ▷ equations (5), (6)
9:     Send $(g_t + \nabla \psi_t(w_t))/(b+H)$ to $\mathcal{A}_1$
10:    Send $-\langle g_t + \nabla \psi_t(w_t), \nabla \psi_t(w_t)\rangle / H(b+H)$ to $\mathcal{A}_2$
11: **end for**

Theorem 2. *Suppose both $\mathcal{A}_1$ and $\mathcal{A}_2$ ensure that given some $\epsilon > 0$ and a sequence c_t with $|c_t| \leq 1$:*

$$\sum_{t=1}^{T} \langle c_t, w_t - u \rangle \leq \epsilon + A|u|\sqrt{\sum_{t=1}^{T} |c_t|^2 \left(1 + \log\left(\frac{|u|^2 T^C}{\epsilon^2} + 1\right)\right)} + B|u|\log\left(\frac{|u|T^C}{\epsilon} + 1\right)$$

for some positive constant A, B, C. Then for $|g_t| \leq b$, $|\nabla \psi_t(w_t)| \leq H$, we have the following guarantee from Algorithm 1,

$$R_T^{\mathcal{A}}(u) \leq O\left[\epsilon + |u|\left(\sqrt{\max\left(0, \sum_{t=1}^{T} |g_t|^2 - |\nabla \psi_t(w_t)|^2\right)} + (b+H)\log T\right)\right]$$

Although this Theorem 2 is rather technical, the overall message is not too complicated. If we ignore the negative $|\nabla \psi_t(w_t)|^2$ terms, the bound simply says that the regret on the "composite" loss $\langle g_t, w\rangle + \psi_t(w)$ only increase with the apriori-unknown g_t, and *not* with $\nabla \psi_t(w_t)$. With this result, we can formalize the intuition in this section to provide the following high probability regret bound:

Theorem 3. *Suppose $\{g_t\}$ are stochastic subgradients such that $\mathbb{E}[g_t] \in \partial \ell_t(w_t)$, $|g_t| \leq b$ and $\mathbb{E}[g_t^2|w_t] \leq \sigma^2$ almost surely for all t. Set the following constants for $\psi_t(w)$ shown in equation (6) for any $0 < \delta \leq 1$, $\epsilon > 0$,*

$$c_1 = 2\sigma\sqrt{\log\left(\frac{16}{\delta}\left[\log\left(2^{T+1}\right) + 2\right]^2\right)}, \quad c_2 = 32b\log\left(\frac{112}{\delta}\left[\log\left(1 + \frac{b}{\sigma}2^{T+2}\right) + 2\right]^2\right),$$
$$p_1 = 2, \quad p_2 = \log T, \quad \alpha_1 = \epsilon/c_1, \quad \alpha_2 = \epsilon\sigma/(4b(b+H))$$

216 *where $H = c_1 p_1 + c_2 p_2$, $|\nabla \psi_t(w_t)| \leq H$. Then, with probability at least $1 - \delta$, algorithm 1*
217 *guarantees*

$$R_T(u) \leq \tilde{O}\left[\epsilon \log \frac{1}{\delta} + |u| b \log \frac{1}{\delta} + |u| \sigma \sqrt{T \log \frac{1}{\delta}}\right]$$

218 Note that this result is *already* of interest: prior work on parameter-free algorithms with subexponen-
219 tial noise only achieve in-expectation rather than high probability results. Of course, there is a caveat:
220 our bound requires that $|g_t|$ be uniformly bounded by b. Even though b could be as large as $\sqrt{T}$, this
221 is still a mild restriction. In the next section, we remove both this restriction as well as the light tail
222 assumption all together.

5   Heavy-tails via Truncation

224 In this section, we aim to give a high probability bound for heavy tailed stochastic gradients $\mathbf{g}_t$. Our
225 approach builds on Section 4 by incorporating gradient clipping with a clipping parameter $\tau \in \mathbb{R}^+$.

$$\hat{\mathbf{g}}_t = \mathbf{g}_t / \|\mathbf{g}_t\| \min(\tau, \|\mathbf{g}_t\|)$$

226 We will continue to consider a $1d$ problem in this section, replacing the norm $\|\cdot\|$ with absolute value
227 $|\cdot|$ and $\mathbf{g}_t$ with g_t. The key insight is that the clipped $\hat{g}_t$ satisfies $\mathbb{E}[\hat{g}_t^2] \leq 2^{\mathfrak{p}-1} \tau^{2-\mathfrak{p}} (\sigma^{\mathfrak{p}} + G^{\mathfrak{p}})$ and
228 of course $|\hat{g}_t| \leq \tau$. Hence, a high probability bound could be obtained by feeding $\hat{g}_t$ into Algorithm 1
229 from Section 4. Let us formally quantify the effect of this clipping:

$$R_T(u) \leq \sum_{t=1}^{T} \langle \nabla \ell_t(w_t), w_t - u \rangle = \underbrace{\sum_{t=1}^{T} \langle \nabla \ell_t(w_t) - \mathbb{E}[\hat{g}_t], w_t - u \rangle}_{\text{bias}} + \underbrace{\sum_{t=1}^{T} \langle \mathbb{E}[\hat{g}_t], w_t - u \rangle}_{\text{Section 4}} \quad (7)$$

230 Without clipping, we would have $\mathbb{E}[\hat{g}_t] = \nabla \ell_t(w_t)$, and so if we were satisfied with an in-expectation
231 result, the first sum above would vanish. However, with clipping, the first sum actually represents
232 some "bias" that must be controlled even to obtain an in-expectation result, let alone high probability.
233 We control this bias using a cancellation-by-regularization strategy analogous at a high level to the
234 one developed in Section 4, although technically quite distinct. After dealing with the bias, we must
235 handle the second sum. Fortunately, since $\hat{g}_t$ is subexponential, bounding the second sum in high
236 probability is precisely the problem solved in Section 4. We introduce the analysis in two elementary
237 steps. For the purpose of bias cancellation, we define a linearized loss $\tilde{\ell}_t(w)$ with regularization
238 function $\phi(w)$

$$\tilde{\ell}_t(w) = \langle \mathbb{E}[\hat{g}_t], w \rangle + \phi(w), \qquad \phi(w) = 2^{\mathfrak{p}-1}(\sigma^{\mathfrak{p}} + G^{\mathfrak{p}})|w|/\tau^{\mathfrak{p}-1} \quad (8)$$

239 the regret in equation (7) can be re-written as

$$= \underbrace{\sum_{t=1}^{T} \left(\langle \nabla \ell_t(w_t) - \mathbb{E}[\hat{g}_t], w_t - u \rangle - \phi(w_t) + \phi(u) \right)}_{\text{bias cancellation}} + \underbrace{\sum_{t=1}^{T} \tilde{\ell}_t(w_t) - \tilde{\ell}_t(u)}_{\text{Section 4}} \quad (9)$$

240 We will be able to show that the w_t-dependent terms of the first summation sum to a negative number
241 and so can be dropped. This leaves only the u-dependent terms, which for appropriate choice of τ
242 will be $\tilde{O}(\|u\| T^{1/\mathfrak{p}})$.

243 Note that at this point, if we were satisfied with an *in expectation* bound for heavy-tailed subgradient
244 estimates (which would already be an interesting new result), we would not require the techniques
245 of Section 4: we could instead define $\hat{\ell}_t(w) = \langle \hat{g}_t, w \rangle + \psi(w)$, so that the last sum is equal to
246 $\sum_{t=1}^{T} \hat{\ell}_t(w_t) - \hat{\ell}_t(u)$ in expectation. Then, since $|\hat{\ell}_t(w_t)| \leq O(\tau)$ with probability 1, we can control
247 $\sum_{t=1}^{T} \hat{\ell}_t(w_t) - \hat{\ell}_t(u)$ using a parameter-free algorithm obtaining regret $\tilde{O}(|u|\sqrt{\sum_{t=1}^{T} |\hat{\ell}_t'(w_t)|^2} +$
248 $\tau|u|)$ to bound the total expected regret, yielding a simple way to recover prior work on expected
249 regret with subexponential subgradients (up to logs), while extending the results to heavy-tailed
250 subgradients.

However, since we *do* aim for a high probability bound, we need to be more careful with the second summation. Fortunately, given that $\hat{g}_t$ is subexponential and bounded, and $\nabla\phi(w_t)$ is deterministic, we can supply $\hat{g}_t + \nabla\phi(w_t)$ to Algorithm 1 and then bound the sum in high probability by Theorem 3. We formalize the procedure as Algorithm 2, and its guarantee is stated in Theorem 4. The exact regret guarantee (including constants) can be found in appendix C.

Algorithm 2 Gradient clipping for $(\sigma, G)-$Heavy tailed gradients

---

Require: $\mathbb{E}[g_t] = \nabla\ell_t(w_t)$, $|\mathbb{E}[g_t]| \le G$, $\mathbb{E}[|g_t - \mathbb{E}[g_t]|^{\mathfrak{p}}] \le \sigma^{\mathfrak{p}}$ for some $\mathfrak{p} \in (1, 2]$, Time horizon T, gradient clipping parameter τ.
1: Initialize Algorithm 1 using the parameters of Theorem 3.
2: **for** $t = 1$ to T **do**
3:      Receive w_t from Algorithm 1.
4:      Suffer loss $\ell_t(w_t)$, receive g_t
5:      Truncate $\hat{g}_t = \frac{g_t}{|g_t|}\min(\tau, |g_t|)$.
6:      Compute $\tilde{g}_t = \hat{g}_t + \nabla\phi(w_t)$ $\triangleright$ $\phi(w)$ is defined in (8), $\mathbb{E}[\tilde{g}_t] \in \partial\tilde{\ell}_t(w_t)$.
7:      Send $\tilde{g}_t$ to Algorithm 1 as tth subgradient.
8: **end for**

Theorem 4. *Suppose $\{g_t\}$ are heavy tailed stochastics gradient such that $\mathbb{E}[g_t] \in \partial\ell_t(w_t)$, $|\mathbb{E}[g_t]| \le G$, $\mathbb{E}[|g_t - \mathbb{E}[g_t]|^{\mathfrak{p}}] \le \sigma^{\mathfrak{p}}$ for some $\mathfrak{p} \in (1, 2]$. If we set $\tau = T^{1/\mathfrak{p}}(\sigma^{\mathfrak{p}} + G^{\mathfrak{p}})^{1/\mathfrak{p}}$ then with probability at least $1 - \delta$ Algorithm 2 guarantees:*

$$R_T(u) \le O\left[\epsilon\log\frac{1}{\delta} + |u|T^{1/\mathfrak{p}}(\sigma + G)\log\frac{T}{\delta}\log\frac{|u|T}{\epsilon}\right]$$

Theorem 4 suggests regret with heavy-tailed gradients $\mathbf{g}_t$ has a $\mathfrak{p}$ dependence of $\tilde{O}(T^{1/\mathfrak{p}})$, which is optimal [Bubeck et al., 2013b, Vural et al., 2022].

6 Dimension-free Extension

So far, we have only considered $1d$ problems. In this section, we demonstrate the extension to dimension-free, which is achieved by using a reduction from Cutkosky and Orabona [2018]. The original reduction extends a $1d$ algorithm to a dimension-free one by dissecting the problem into a 1d "magnitude" and a "direction" learner. The direction learner is a constrained OLO algorithm $\mathcal{A}^{nd}$ which outputs a vector $\mathbf{v}_t$ with $\|\mathbf{v}_t\| \le 1$ in response to $\mathbf{g}, \ldots, \mathbf{g}_{t-1}$, while the magnitude learner is an unconstrained OLO algorithm $\mathcal{A}^{1d}$ which outputs $x_t \in \mathbb{R}$ in response to $\langle\mathbf{g}_1, \mathbf{v}_1\rangle, \ldots \langle\mathbf{g}_{t-1}, \mathbf{v}_{t-1}\rangle$. The output of the entire algorithm is $\mathbf{w}_t = x_t\mathbf{v}_t$. Suppose $\mathcal{A}_{1d}$ and $\mathcal{A}_{nd}$ have regret guarantee of $R_T^{1d}(u)$ and $R_T^{nd}(\mathbf{u})$, respectively. Then regret of the dimension-free reduction is bounded by $R_T(\mathbf{u}) \le \|\mathbf{u}\|R_T^{\mathcal{A}^{nd}}(\mathbf{u}/\|\mathbf{u}\|) + R_T^{\mathcal{A}^{1d}}(\|\mathbf{u}\|)$. Thus, in order to apply this reduction we need to exhibit a $\mathcal{A}^{1d}$ and $\mathcal{A}^{nd}$ that achieves low regret on heavy-tailed losses. For the magnitude learner $\mathcal{A}^{1d}$, we use can use the 1d Algorithm 2 that we just developed. The remaining question is how to develop a direction learner that can handle heavy tailed subgradients. Fortunately, this is much easier since the direction learner is constrained to the unit ball.

To build this direction learner, we again apply subgradient clipping, and feed the clipped subgradients to the standard FTRL algorithm with quadratic regularizer (i.e. "lazy" online gradient descent). This procedure is described in Algorithm 3. Note although $\hat{\mathbf{g}}_t$ induces bias, no regularization is required in Algorithm 3. Since $\mathcal{A}^{nd}$ runs on the unit ball, careful tuning of τ is sufficient to control the bias - a concrete demonstration of how much more intricate the unconstrained case is! Finally, the full dimension-free reduction is displayed in algorithm 4 with its high probability guarantee stated in Theorem 5. The details are presented in appendix D.

Algorithm 3 Unit Ball Gradient clipping with FTRL

Require: $\mathbb{E}[\mathbf{g}_t] = \nabla\ell_t(\mathbf{w}_t)$, $\|\mathbb{E}[\mathbf{g}_t]\| \leq G$, $\mathbb{E}[\|\hat{\mathbf{g}}_t - \mathbb{E}[\mathbf{g}_t]\|^{\mathfrak{p}}] \leq \sigma^{\mathfrak{p}}$, time horizon T, gradient clipping parameter τ, regularizer weight η

  1: Set $\eta = 1/\tau$
  2: **for** $t = 1$ to T **do**
  3:      Compute $\mathbf{v}_t \in \mathrm{argmin}_{\mathbf{v}:\|\mathbf{v}\|\leq 1} \sum_{i=1}^{t-1}\langle\hat{\mathbf{g}}_t, \mathbf{v}\rangle + \frac{1}{2\eta}\|\mathbf{v}\|^2$
  4:      Output $\mathbf{v}_t$, receive gradient $\mathbf{g}_t$
  5:      Set $\hat{\mathbf{g}}_t = \frac{\mathbf{g}_t}{\|\mathbf{g}_t\|}\min(\tau, \|\mathbf{g}_t\|)$
  6: **end for**

Algorithm 4 Dimension-free Gradient clipping for $(\sigma, G)-$Heavy tailed gradients

---

Require: $\mathfrak{p}^{th}$ moment bound σ, time horizon T, Set algorithm 2 as $\mathcal{A}^{1d}$, Set algorithm 3 as $\mathcal{A}^{nd}$.

  1: Set $\sigma_{1d} = (\sigma^{\mathfrak{p}} + 2G^{\mathfrak{p}})^{1/\mathfrak{p}}$ and $\tau_{1d} = T^{1/\mathfrak{p}}(\sigma_{1d}^{\mathfrak{p}} + G^{\mathfrak{p}})^{1/\mathfrak{p}} = T^{1/\mathfrak{p}}(\sigma^{\mathfrak{p}} + 3G^{\mathfrak{p}})^{1/\mathfrak{p}}$
  2: Initialize $\mathcal{A}^{1d}$ with parameters $\sigma \leftarrow \sigma_{1d}$ and $\tau \leftarrow \tau_{1d}$
  3: Initialize $\mathcal{A}^{nd}$ with parameters $\sigma \leftarrow \sigma$ and $\tau \leftarrow T^{1/\mathfrak{p}}(\sigma^{\mathfrak{p}} + G^{\mathfrak{p}})^{1/\mathfrak{p}}$.
  4: **for** $t = 1$ to T **do**
  5:      Receive $x_t \in \mathbb{R}$ from $\mathcal{A}^{1d}$,
  6:      Receive $\mathbf{v}_t \in \mathbb{R}^d$, $\|\mathbf{v}_t\| \leq 1$ from $\mathcal{A}^{nd}$
  7:      Play output $\mathbf{w}_t = x_t\mathbf{v}_t$
  8:      Suffer loss $\ell_t(\mathbf{w}_t)$, receive gradients $\mathbf{g}_t$
  9:      Send $g_t^{1d} = \langle\mathbf{g}_t, \mathbf{v}_t\rangle$ as the t^{th} gradient to $\mathcal{A}^{1d}$
  10:     Send $\mathbf{g}_t$ as the t^{th} gradient to $\mathcal{A}^{nd}$
  11: **end for**

Theorem 5. *Suppose that for all t, $\mathbf{g}_t$ is a heavy-tailed stochastic subgradient satisfying $\mathbb{E}[\mathbf{g}_t] \in \partial\ell_t(\mathbf{w}_t)$, $\|\mathbb{E}[\mathbf{g}_t]\| \leq G$ and $\mathbb{E}[\|\mathbf{g}_t - \mathbb{E}[\mathbf{g}_t]\|^{\mathfrak{p}}] \leq \sigma^{\mathfrak{p}}$ for some $\mathfrak{p} \in (1, 2]$. Then, with probability at least $1 - \delta$ Algorithm 4 guarantees*

$$R_T(\mathbf{u}) = \sum_{t=1}^{T}\ell_t(\mathbf{w}_t) - \ell_t(\mathbf{u}) \leq O\left[\epsilon\log\frac{1}{\delta} + \|\mathbf{u}\|T^{1/\mathfrak{p}}(\sigma + G)\log\frac{T}{\delta}\log\frac{\|u\|T}{\epsilon}\right]$$

7 Conclusion

We have presented a framework for building parameter-free algorithms that achieve high probability regret bounds for heavy-tailed subgradient estimates. This improves upon prior work in several ways: high probability bounds were previously unavailable even for the restricted setting of *bounded* subgradient estimates, while even in-expectation bounds were previously unavailable for heavy-tailed subgradients. Our development required two new techniques: first, we described a regularization scheme that effectively "cancels" potentially problematic iterate-dependent variance terms arising in standard martingale concentration arguments. This allows for high probability bounds with bounded subexponential estimates, and we hope may be of use in other scenarios where the iterates appear in variance calculations. The second combines clipping with another new regularization scheme that "cancels" another problematic iterate-dependent *bias* term. On its own, this technique actually can be used to recover in-expectation bounds for heavy-tailed estimates.

Limitations: Our algorithm has several limitations that suggest open questions: first, our two regularization schemes each introduce potentially suboptimal logarithmic factors. The first one introduces a higher logarithmic dependence on T, while the second introduces a higher logarithmic dependence on $\|\mathbf{u}\|$ because the optimal clipping parameter τ depends on $\log(\|\mathbf{u}\|)$. Beyond this, our algorithms require knowledge of the parameters σ and τ. Adapting to an unknown value of even one of these parameters remains a challenging problem.

References

N. Agarwal, B. Bullins, E. Hazan, S. Kakade, and K. Singh. Online control with adversarial disturbances. In *International Conference on Machine Learning*, pages 111–119. PMLR, 2019.

A. Balsubramani. Sharp finite-time iterated-logarithm martingale concentration. *arXiv preprint arXiv:1405.2639*, 2014.

S. Bubeck, N. Cesa-Bianchi, and G. Lugosi. Bandits with heavy tail. *IEEE Transactions on Information Theory*, 59(11):7711–7717, 2013a.

S. Bubeck, N. Cesa-Bianchi, and G. Lugosi. Bandits with heavy tail. *IEEE Trans. Inf. Theor.*, 59, 2013b.

N. Cesa-Bianchi and G. Lugosi. *Prediction, learning, and games*. Cambridge University Press, 2006.

L. Chen, H. Luo, and C.-Y. Wei. Impossible tuning made possible: A new expert algorithm and its applications. In *Conference on Learning Theory*, pages 1216–1259. PMLR, 2021.

A. Cutkosky. *Algorithms and Lower Bounds for Parameter-free Online Learning*. PhD thesis, Stanford University, 2018.

A. Cutkosky. Combining online learning guarantees. In *Proceedings of the Thirty-Second Conference on Learning Theory*, pages 895–913, 2019.

A. Cutkosky and K. Boahen. Online learning without prior information. In *Conference on Learning Theory*, pages 643–677, 2017.

A. Cutkosky and H. Mehta. High-probability bounds for non-convex stochastic optimization with heavy tails. In *Proceedings of the 35st International Conference on Neural Information Processing Systems*, 2021.

A. Cutkosky and F. Orabona. Black-box reductions for parameter-free online learning in banach spaces. In *Conference On Learning Theory*, pages 1493–1529, 2018.

J. Duchi, E. Hazan, and Y. Singer. Adaptive subgradient methods for online learning and stochastic optimization. In *Conference on Learning Theory (COLT)*, 2010a.

J. C. Duchi, S. Shalev-Shwartz, Y. Singer, and A. Tewari. Composite objective mirror descent. In *COLT*, volume 10, pages 14–26. Citeseer, 2010b.

D. J. Foster, S. Kale, M. Mohri, and K. Sridharan. Parameter-free online learning via model selection. In *Advances in Neural Information Processing Systems*, pages 6020–6030, 2017.

E. Gorbunov, M. Danilova, and A. Gasnikov. Stochastic optimization with heavy-tailed noise via accelerated gradient clipping. *Advances in Neural Information Processing Systems*, 33:15042–15053, 2020.

E. Hazan. Introduction to online convex optimization. *arXiv preprint arXiv:1909.05207*, 2019.

S. R. Howard, A. Ramdas, J. McAuliffe, and J. Sekhon. Time-uniform, nonparametric, nonasymptotic confidence sequences. *The Annals of Statistics*, 49(2):1055–1080, 2021.

K.-S. Jun and F. Orabona. Parameter-free online convex optimization with sub-exponential noise. In *Conference on Learning Theory*, pages 1802–1823. PMLR, 2019.

M. Kempka, W. Kotlowski, and M. K. Warmuth. Adaptive scale-invariant online algorithms for learning linear models. In *International Conference on Machine Learning*, pages 3321–3330, 2019.

D. Kingma and J. Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Z. Mhammedi and W. M. Koolen. Lipschitz and comparator-norm adaptivity in online learning. *Conference on Learning Theory*, 2020.

F. Orabona. A modern introduction to online learning. *arXiv preprint arXiv:1912.13213*, 2019.

F. Orabona and K.-S. Jun. Tight concentrations and confidence sequences from the regret of universal portfolio. *arXiv preprint arXiv:2110.14099*, 2021.

F. Orabona and D. Pál. Coin betting and parameter-free online learning. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems 29*, pages 577–585. Curran Associates, Inc., 2016.

S. J. Reddi, S. Kale, and S. Kumar. On the convergence of adam and beyond. In *International Conference on Learning Representations*, 2018.

S. Shalev-Shwartz. Online learning and online convex optimization. *Foundations and Trends in Machine Learning*, 4(2):107–194, 2011.

J. Tropp. Freedman's inequality for matrix martingales. *Electronic Communications in Probability*, 16:262–270, 2011.

D. van der Hoeven. User-specified local differential privacy in unconstrained adaptive online learning. In *Advances in Neural Information Processing Systems*, pages 14103–14112, 2019.

J. Ville. Etude critique de la notion de collectif, gauthier-villars, paris, 1939. *Monographies des Probabilités. Calcul des Probabilités et ses Applications*, 1939.

V. Vovk. Hoeffding's inequality in game-theoretic probability. *arXiv preprint arXiv:0708.2502*, 2007.

N. M. Vural, L. Yu, K. Balasubramanian, S. Volgushev, and M. A. Erdogdu. Mirror descent strikes again: Optimal stochastic convex optimization under infinite noise variance. *arXiv preprint arXiv:2202.11632*, 2022.

I. Waudby-Smith and A. Ramdas. Estimating means of bounded random variables by betting. *arXiv preprint arXiv:2010.09686*, 2020.

J. Zhang, S. P. Karimireddy, A. Veit, S. Kim, S. Reddi, S. Kumar, and S. Sra. Why are adaptive methods good for attention models? *Advances in Neural Information Processing Systems*, 33, 2020.

M. Zinkevich. Online convex programming and generalized infinitesimal gradient ascent. In *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, pages 928–936, 2003.