Local Causal Discovery for Estimating Causal Effects

Shantanu Gupta   SHANTANG@CMU.EDU
David Childers   DCHILDERS@CMU.EDU
Zachary C. Lipton   ZLIPTON@CMU.EDU
Carnegie Mellon University

Editors: Mihaela van der Shaar, Dominik Janzing and Cheng Zhang

Abstract

Even when the causal graph underlying our data is unknown, we can use observational data to narrow down the possible values that an average treatment effect (ATE) can take by (1) identifying the graph up to a Markov equivalence class; and (2) estimating that ATE for each graph in the class. While the PC algorithm can identify this class under strong faithfulness assumptions, it can be computationally prohibitive. Fortunately, only the local graph structure around the treatment is required to identify the set of possible ATE values, a fact exploited by local discovery algorithms to improve computational efficiency. In this paper, we introduce Local Discovery using Eager Collider Checks (LDECC), a new local causal discovery algorithm that leverages unshielded colliders to orient the treatment's parents differently from existing methods. We show that there exist graphs where LDECC exponentially outperforms existing local discovery algorithms and vice versa. Moreover, we show that LDECC and existing algorithms rely on different faithfulness assumptions, leveraging this insight to weaken the assumptions for identifying the set of possible ATE values.

Keywords: Local causal discovery, local structure learning, causal inference, causal discovery

1. Introduction

Estimating an average treatment effect (ATE) from observational data typically requires structural knowledge, which can be represented in the form of a causal graph. While a rich literature offers methods for identifying and estimating causal effects given a *known* causal graph (Tian and Pearl, 2002; Pearl, 2009; Jaber et al., 2019), many applications require that we investigate the values that an ATE could possibly take when the causal graph is unknown. In such cases, we can (i) perform causal discovery, using observational data to identify the graph up to a Markov equivalence class (MEC); and (ii) estimate the desired ATE for every graph in the MEC, thus identifying the set of possible ATE values. We denote this (unknown) set of identified ATE values by Θ^*.

Causal discovery has been investigated under a variety of assumptions (Glymour et al., 2019; Squires and Uhler, 2022). Under causal sufficiency (i.e., no unobserved variables) and faithfulness, the PC algorithm (Spirtes et al., 2000, Sec. 5.4.2) can identify the MEC of the true graph from observational data (and thus Θ^*). However, fully characterizing the MEC can be computationally expensive. Addressing this concern, Maathuis et al. (2009) proved that the local structure around the treatment node is sufficient for identifying Θ^*. Leveraging this insight, existing local causal discovery algorithms (e.g., PCD-by-PCD (Yin et al., 2008), MB-by-MB (Wang et al., 2014)) discover just enough of the graph to identify any parents and children of the treatment that PC would have discovered. These methods sequentially discover the local structure around the treatment, its neighbors, and so on, terminating whenever all neighbors of the treatment are oriented (or no remaining neighbors can be oriented).

In this work, we introduce Local Discovery with Eager Collider Checks (LDECC), a new local causal discovery algorithm that provides an alternative method to orient the parents of a treatment X (Sec. 4). Initially, LDECC performs local discovery around X to discover its neighbors. Subsequently, LDECC chooses the same Conditional Independence (CI) tests as PC would choose given the state of the graph, with one crucial exception: whenever we find two nodes A and B such that $A \perp\!\!\!\perp B|\mathbf{S}$ for some set $\mathbf{S}$ with $X \notin \mathbf{S}$, LDECC immediately checks whether they become dependent when X is added to the conditioning set. If the test reveals dependence $A \not\!\perp\!\!\!\perp B|\mathbf{S} \cup \{X\}$, then X must either be a collider or a descendant of a collider that lies at the intersection of some path from A to X or from B to X. On this basis, LDECC can orient the smallest subset of X's neighbors that d-separate it from $\{A, B\}$ as parents. We prove that, under faithfulness, the identified ATE set is equal to Θ^*.

We represent the ideas underlying existing local causal discovery algorithms using a simple algorithm that we call Sequential Discovery (SD) that sequentially runs the PC algorithm locally for local structure learning. While existing algorithms differ from SD in subtle ways, they share key steps with SD allowing us to compare LDECC to this existing class of algorithms. We highlight LDECC's complementary strengths to SD in terms of computational requirements. We present classes of causal graphs where LDECC performs exponentially fewer CI tests than SD, and vice versa (Sec. 4.1). Thus, the methods can be combined profitably (by running LDECC and SD in parallel and terminating when either algorithm terminates), avoiding exponential runtimes if either algorithm's runtime is subexponential, thereby expanding the class of graphs where efficient local discovery is possible.

We also compare SD and LDECC based on their faithfulness requirements (Sec. 4.2). We show that both SD and PC require weaker assumptions to identify Θ^* than to identify the entire MEC. We also find that LDECC and SD rely on different sets of faithfulness assumptions. There are classes of faithfulness violations where one algorithm will correctly identify Θ^* while the other will not. Under the assumption that one of the algorithms' faithfulness assumptions is correct, we propose a procedure that recovers a conservative bound on the ATE set. Aiming to make this bound sharp, we prove that LDECC and SD can be combined to construct a procedure that can identify Θ^* under strictly weaker assumptions, again highlighting LDECC's complementary nature relative to existing methods. Finally, we empirically test LDECC on synthetic as well as semi-synthetic graphs (Sec. 5) and show that it performs comparably to SD (and PC) and typically runs fewer CI tests than SD [1].

2. Related Work

Several works have developed procedures for identifying the set of possible ATE values Θ^* using local information. Maathuis et al. (2009) propose IDA, an algorithm that outputs a set of ATE values by only using the local structure around the treatment X: For a given MEC, Θ^* can be identified by adjusting for all possible parent sets of X such that no new unshielded colliders get created at X. IDA has been extended to account for multiple interventions (Nandy et al., 2017), background information (Perković et al., 2017; Fang and He, 2020), and hidden variables (Malinsky and Spirtes, 2016). Hyttinen et al. (2015) combine causal discovery and inference by presenting a SAT solver-based approach to do-calculus with an unknown graph. Geffner et al. (2022) propose a deep learning based end-to-end method that learns a posterior over graphs and estimates the ATE by marginalizing over the graphs. Toth et al. (2022) propose a Bayesian active learning approach to jointly learn a posterior over causal models and some target query of interest. However, these works do not propose local discovery methods.

---

1. The code and data are available at https://github.com/acmi-lab/local-causal-discovery.

Other works attempt to perform causal inference under weaker assumptions than requiring the entire graph or MEC. Some works propose methods to find valid adjustment sets under the assumption that the observed covariates are pre-treatment (De Luna et al., 2011; VanderWeele and Shpitser, 2011; Entner et al., 2012, 2013; Witte and Didelez, 2019; Gultchin et al., 2020). Cheng et al. (2022a) use an anchor variable (which they call COSO) and Shah et al. (2022) use a known causal parent of the treatment to identify a valid adjustment set. Other works present data-driven methods to find valid instrumental variables (Silva and Shimizu, 2017; Cheng et al., 2022b). Watson and Silva (2022) propose a method to learn the causal order amongst variables that are descendants of some covariate set. By contrast, we do not make any partial ordering assumptions.

A complementary line of work focuses on only discovering the local structure around a given node. Many works attempt to find the Markov blanket (MB) or the parent-child set of a target node (Aliferis et al., 2003; Tsamardinos et al., 2006; Yu et al., 2020; Ling et al., 2021). Unlike our work, they do not distinguish between the parent and child identities of nodes inside the MB (see Aliferis et al. (2010) for a review of these methods). For determining these causal identities, existing works use sequential approaches by repeatedly finding local structures like a MB or a parent-child set starting from the target node and then propagating edge orientations within the discovered subgraph (Yin et al., 2008; Zhou et al., 2010; Wang et al., 2014; Gao and Ji, 2015; Ling et al., 2020). These methods typically differ in how they discover the local structure around each node. Cooper (1997) present an algorithm to learn pairwise causal relationships by leveraging a node that is not caused by any other nodes. Some works use independence patterns in Y-structures around a given node to find local causal relationships (Mani et al., 2012; Mooij et al., 2015; Versteeg et al., 2022).

3. Preliminaries

We assume that the causal structure of the observational data can be encoded using a DAG $\mathcal{G}^*(\mathbf{V}, \mathbf{E})$, where $\mathbf{V}$ and $\mathbf{E}$ are the set of nodes and edges. Each edge $A \to B \in \mathbf{E}$ indicates that A is a direct cause of B. We denote the treatment node by X and the outcome node by Y. For a node V, we denote its Markov blanket, neighbors, parents, children, and descendants by $\mathrm{MB}(V), \mathrm{Ne}(V), \mathrm{Pa}(V), \mathrm{Ch}(V)$, and $\mathrm{Desc}(V)$ (with $\mathrm{MB}(V) = \mathrm{Ne}(V) \cup_{N \in \mathrm{Ch}(V)} \mathrm{Pa}(N)$). Let $\mathrm{Ne}^+(V) = \mathrm{Ne}(V) \cup \{V\}$ and $\mathrm{MB}^+(V) = \mathrm{MB}(V) \cup \{V\}$. An unshielded collider (UC) is a triple $P \to R \leftarrow Q$ s.t. P—$Q \notin \mathbf{E}$. For a UC $\alpha = (P \to R \leftarrow Q)$, let $\mathrm{sep}(\alpha) = \min\{|\mathbf{S}| : \mathbf{S} \subseteq \mathbf{V} \setminus \{P, Q\} \text{ and } P \perp\!\!\!\perp Q | \mathbf{S}\}$.

A DAG entails a set of CIs via *d-separation* (Pearl, 2009, Sec. 1.2.3). DAGs that entail the same set of CIs form an MEC, which can be characterized by a *completed partially directed acyclic graph* (CPDAG). For the true DAG $\mathcal{G}^*$, we denote by Θ^* the set of ATE values (of X on Y) in each DAG in the MEC corresponding to $\mathcal{G}^*$. The causal faithfulness assumption (CFA) holds iff all CIs satisfied by the observational joint distribution $\mathbb{P}(\mathbf{V})$ are entailed by $\mathcal{G}^*$. Throughout this work, we focus on causally sufficient graphs. Under the CFA, the PC algorithm recovers this MEC roughly as follows (demonstrated for the DAG in Fig. 1(a)): (i) estimate the skeleton by running CI tests; (ii) find UCs in this skeleton (Fig. 1(b) red edges); and (iii) orient additional edges using Meek's rules (Meek, 2013) (Fig. 1(b) blue edges) to get a CPDAG (full details on the PC algorithm are in Appendix A).

We instantiate the key ideas of existing local discovery algorithms using SD (Fig. 3). SD sequentially finds the local structure around nodes (*LocalPC* in Fig. 2) starting from X, then its neighbors, and so on (Lines 3–7). After each such local discovery step, SD orients nodes in the subgraph discovered until that point using UCs and Meek's rules like PC (Line 8; see Fig. 12 for *GetCPDAG* and Fig. 15 for *Nbrs*). If at any point all neighbors of X get oriented, SD terminates.

(a) True DAG $\mathcal{G}^*$ (b) CPDAG from PC   (c) SD's output   (d) LDECC

Figure 1: Demonstration of the PC, SD, and LDECC algorithms for the graph in (a).

Figure 2: Additional subroutines.

```
def LocalPC(Skeleton U, Target V):
    s ← 0;
    while |Ne_U(V)| > s do
        for B ∈ Ne_U(V), S ⊆ Ne_U(V) \ {B}
        s.t. |S| = s do
            if V ⊥⊥ B|S then
                U.removeEdge(V—B);
                DSep(V, B) ← S;
                break;
        end
        s ← s + 1;
    end
    return U, Ne_U(V), DSep;
def isLocallyValid(X, S):
    for every A, B ∈ S do
        if isNonCollider(A—X—B) then
            return False;
    end
    return True;
```

Figure 3: The SD algorithm.

```
Input: Treatment X.
1  Fully connected undirected graph U;
2  queue ← [X], done ← ∅;
3  while queue is not empty do
4      V ← queue.removeFirstItem();
5      U, Ne_U(V), DSep ← LocalPC(U, V);
6      done ← done ∪ {V};
7      queue.append(Ne_U(V) \ (done ∪ queue));
8      G ← GetCPDAG(U[done], DSep);
9      parents, children, unoriented ← Nbrs(G, X);
10     if unoriented = ∅ then break ;
11 end
12 Θ_SD ← ∅;
13 for S ⊆ (unoriented ∪ parents) do
14     if isLocallyValid(X, S) then
15         Θ_SD.add(θ_{X→Y|S});
16 end
17 return Θ_SD;
```

The ATE set is estimated by applying the backdoor adjustment (Pearl, 2009, Thm. 3.3.2) with every *locally valid* parent set of X, i.e., one that does not create a new UC at X (see Lines 12–16 and *isLocallyValid* in Fig. 2). The ATE estimated using each such parent set $\mathbf{S}$ is denoted as $\theta_{X→Y|\mathbf{S}}$ (Line 15). Consider the DAG in Fig. 1(a). Here, SD will use *LocalPC* to sequentially discover the neighbors of X, W, M, A, and B. Then the UC $A → W ← B$ will be detected and, after propagating orientations via Meek's rules, both W and M will be oriented and SD will terminate (Fig. 1(c)) and output $\Theta_{SD} = \{\theta_{X→Y|\{W\}}\} = \Theta^*$.

4. Local Discovery using Eager Collider Checks (LDECC)

In this section, we propose LDECC, a local causal discovery algorithm that orients the parents of X by leveraging UCs differently from SD (Prop. 4). We prove its correctness under the CFA (Thm. 5) and show its complementary nature relative to SD in terms of computational (Sec. 4.1) and

Figure 4 (left):

```
1  def UCChildren(MB(X), Ne(X), DSep):
2      spousesX ← MB(X) \ Ne(X);
3      children ← ∅;
4      for D ∈ spousesX do
5          for C ∈ Ne(X) \ DSep(D, X) do
6              if C ⫫̸ D|DSep(D, X) then
                   children.add(C) ;
7          end
8      end
9      return children;
10 def GetMNS(V ∉ Ne⁺(X)):
11     s ← 0;
12     while |Ne(X)| > s do
13         for S ⊆ Ne(X) s.t. |S| = s do
14             if V ⫫ X|S then  return S ;
15         end
16         s ← s + 1;
17     end
18     return MNS not found;
19 def ECCParents(A, B, check=False):
20     if check and {A, B} ∩ Ne(X) = ∅ then
21         m_A ← GetMNS(A) ;
22         m_B ← GetMNS(B);
23         if m_A = m_B then return m_A;
24         else return ∅;
25     parents ← ∅;
26     for V ∈ {A, B} do
27         if V ∈ Ne(X) then parents.add(V);
28         else parents.add(GetMNS(V));
29     end
30     return parents;
```

Figure 4: Subroutines used by LDECC.

Figure 5 (right):

```
   Input: Treatment X.
1  MB(X) ← FindMarkovBlanket(X);
2  _, Ne(X), DSep ← LocalPC(MB⁺(X), X);
3  children ← UCChildren(MB(X), Ne(X), DSep);
4  parents ← ∅, unoriented ← ∅;
5  Completely connected undirected graph 𝒰;
6  for (A ⫫ B|S) ∈ PCTest(𝒰) s.t. A, B ≠ X do
7      if A, B ∈ Ne(X) and X ∉ S then
8          parents.add({A, B});
9          parents.add(S ∩ Ne(X));
10     else if A, B ∈ Ne(X) and X ∈ S then
11         MarkNonCollider(A—X—B);
12         for V ∈ Ne(X) \ (S ∪ {A, B}) do
13             if A ⫫̸ B|{S, V} then
                   children.add(V) ;
14         end
15     else if A ⫫̸ B|{S, X} and X ∉ S then
16         parents.add(ECCParents(A, B, S));
17     end
18     for P ∈ parents, C ∈ unoriented do
19         if isNonCollider(P—X—C) then
               children.add(C) ;
20     end
21     unoriented ← Ne(X)\ (parents ∪ children);
22     if unoriented = ∅ then  break ;
23 end
24 Θ_LDECC ← ∅;
25 for S ⊆ (unoriented ∪ parents) do
26     if isLocallyValid(S) then
27         Θ_LDECC.add(θ_{X→Y|S});
28 end
   Output: Θ_LDECC
```

Figure 5: The LDECC algorithm.

faithfulness (Sec. 4.2) requirements. We defer the proofs to Appendix B.1. We first define a *Minimal Neighbor Separator* (MNS) which plays a key role in LDECC.

Definition 1 (Minimal Neighbor Separator) *For a DAG $\mathcal{G}(\mathbf{V}, \mathbf{E})$ and nodes X and $A \notin Ne^+(X)$, $mns_X(A) \subseteq Ne(X)$ is the unique set (see Prop. 3) of nodes such that (i) (d-separation) $A \perp\!\!\!\perp X|mns_X(A)$, and (ii) (minimality) for any $\mathbf{S} \subset mns_X(A)$, $A \not\perp\!\!\!\perp X|\mathbf{S}$.*

For the graph in Fig. 1(a), we have $mns_X(A) = mns_X(B) = mns_X(C) = \{W\}$ and $mns_X(Y) = \{W, M\}$. While an MNS need not exist for every node (see Example 6 in Appendix B), $mns_X(V)$ always exists $\forall V \notin Desc(X)$ (which is sufficient for correctness of LDECC):

Proposition 2 *For any node $V \notin (Desc(X) \cup Ne^+(X))$, $mns_X(V)$ exists and $mns_X(V) \subseteq Pa(X)$.*

Proposition 3 (Uniqueness of MNS) *For every node V such that $mns_X(V)$ exists, it is unique.*

Proposition 4 (Eager Collider Check) *For nodes $A, B \in \mathbf{V} \setminus Ne^+(X)$ and $\mathbf{S} \subseteq \mathbf{V} \setminus \{A, B, X\}$, if (i) $A \perp\!\!\!\perp B | \mathbf{S}$; and (ii) $A \not\perp\!\!\!\perp B | \mathbf{S} \cup \{X\}$; then $A, B \notin Desc(X)$ and $mns_X(A), mns_X(B) \subseteq Pa(X)$.*

Prop. 4 suggests a different strategy for orienting parents of X: if two nodes that are d-separated by $\mathbf{S}$ become d-connected by $\mathbf{S} \cup \{X\}$, the MNS of such nodes contains the parents of X (see proof in Appendix B.1). Thus, unlike PC and SD, the skeleton is not needed to propagate orientations via Meek's rules. Similar ideas have been used in prior work for causal discovery. Claassen and Heskes (2012) use minimal (in)dependencies to develop a logic-based causal discovery algorithm that also avoids graphical orientation rules. Magliacane et al. (2016) extend this and propose an algorithm that only reasons over ancestral relations rather than the space of DAGs. While these works do not study local causal discovery, their results can be used to derive an alternative proof of Prop. 4.

The LDECC algorithm (Fig. 5) first finds the Markov blanket $MB(X)$ (Line 1): we use the IAMB algorithm (Tsamardinos et al., 2003, Fig. 2) in our experiments (see Fig. 14 in Appendix B.1). Next, we run *LocalPC* within the subgraph containing $MB(X)$ to prune this set to obtain $Ne(X)$ (Line 2). We then use the nodes in $MB(X) \setminus Ne(X)$ to detect children C of X that are part of UCs of the form $X \to C \leftarrow D$ (Line 3 and *GetUCChildren* in Fig. 4). LDECC then starts running CI tests in the same way as PC would but excluding tests for X since we already know $Ne(X)$ (the for-loop in Line 6; see Fig. 12 for *PCTest*). Every time we detect a CI $A \perp\!\!\!\perp B | \mathbf{S}$, we check the following cases: (i) if $A, B \in Ne(X)$ and $X \notin \mathbf{S}$, then there must be a UC $A \to X \leftarrow B$ and so we mark A and B as parents (Lines 7, 8); (ii) if $A, B \in Ne(X)$ and $X \in \mathbf{S}$, then we mark A—X—B as a non-collider (Lines 10, 11); and (iii) **Eager Collider Check (ECC):** if $X \notin \mathbf{S}$ and $A \not\perp\!\!\!\perp B | \mathbf{S} \cup \{X\}$, then, by leveraging Prop. 4, we apply *GetMNS* (Fig. 4) to mark $mns_X(A), mns_X(B)$ as parents (Lines 15, 16; *ECCParents* in Fig. 4). Next, for each oriented parent, we use the non-colliders detected in Case (ii) to mark children (Lines 18, 19). LDECC terminates if there are no unoriented neighbors. The ATE set is computed similarly to SD by applying the backdoor adjustment with every *locally valid* parent set. Lines 9,12–14 are inserted to account for Meek's rules $3, 4$. The *check=True* argument in *ECCParents* aims to make it more robust to faithfulness violations (see Remark 21 in Sec. 4.2).

Consider the running example of the DAG in Fig. 1(*a*). We first find the local structure around X. Then we start running CI tests in the same way as PC. After we run $A \perp\!\!\!\perp B | C$, we do an ECC and find $A \not\perp\!\!\!\perp B | \{C, X\}$. Since $mns_X(A) = mns_X(B) = \{W\}$, we mark W as a parent of X. Next, we find that $W \perp\!\!\!\perp M | X$ and mark W—X—M as a non-collider which lets us mark M as a child (because W is a parent). LDECC terminates as all neighbors of X are oriented (Fig. 1(*d*)) and the ATE set is computed by using $\{W\}$ as the backdoor adjustment set: $\Theta_{\text{LDECC}} = \{\theta_{X \to Y | \{W\}}\} = \Theta^*$.

Theorem 5 (Correctness) *Under the CFA and with access to a CI oracle, we have $\Theta_{LDECC} \overset{set}{=} \Theta^*$.*

Remark *A DAG can have multiple valid adjustment sets. We show that local information suffices for identifying the optimal adjustment set according to the asymptotic variance criterion in Henckel et al. (2019) and we present a procedure to discover it (see Fig. 20, Prop. 44 in Appendix D.2).*

In summary, LDECC differs from SD in two key ways: (i) LDECC runs tests in a different order—SD runs *LocalPC* by recursively considering nodes starting from X whereas LDECC runs CI tests in the same order as PC; and (ii) SD uses the skeleton to orient edges from a UC via Meek's rules (like the PC algorithm) whereas LDECC uses an ECC to orient the parents of X.

(*a*) LDECC outperforms SD   (*b*) SD outperforms LDECC

Figure 6: Classes of graphs where LDECC and SD have different runtimes.

4.1. Comparison of computational requirements

In this section, we compare PC, SD, and LDECC based on the number of CI tests they perform. There are classes of DAGs where LDECC is polynomial time while SD is not, and vice versa (Props. 7,8). Using this insight, we construct an algorithm that runs in polynomial time on a larger class of DAGs (Remark 13). We defer proofs to Appendix B.2. We make the following assumption in this section:

Assumption 1 *The CFA holds and we have access to a CI oracle.*

Let the number of CI tests performed by PC, SD, and LDECC be T_{PC}, T_{SD}, and T_{LDECC}. We first show that, in the worst case, LDECC only runs a polynomial (in $|\mathbf{V}|$) number of extra CI tests compared to PC when $|\text{Ne}(X)|$ is bounded. In practice, we observe that the upper bound is quite loose: Even when $|\text{Ne}(X)|$ is large, PC also has to run a large number of tests for X.

Proposition 6 (PC vs LDECC) *We have $T_{LDECC} \leq T_{PC} + \mathcal{O}(|\mathbf{V}|^2) + \mathcal{O}\left(|\mathbf{V}| \cdot 2^{|Ne(X)|}\right)$.*

Proposition 7 (LDECC exponentially better) *There exist classes of graphs such that $T_{LDECC} + \Theta(2^{|\mathbf{V}|}) \leq T_{PC}$; and $T_{LDECC} + \Theta(2^{|\mathbf{V}|}) \leq T_{SD}$.*

Proof Consider the class of graphs shown in Fig. 6(*a*) where there is a clique of size N on the path from the UC $A \to C \leftarrow B$ to W. Both PC and SD will perform $\Theta(2^N)$ CI tests due to this clique. Thus, when $N \asymp |\mathbf{V}|$, SD is exponential time. By contrast, since LDECC runs tests in the same order as PC, it unshields the UC, orients W as a parent via an ECC, and terminates in $\mathcal{O}(|\mathbf{V}|^2)$ tests. ■

Qualitatively, the result shows that if there is a dense region between a UC and the parent it orients, SD might perform poorly because it has to wade through this dense region to get to the UC. By contrast, LDECC can avoid the CI tests in these dense regions as it uses an ECC to orient parents of X instead of the skeleton. However, LDECC does *not* uniformly dominate SD. There are classes of DAGs where LDECC performs exponentially more CI tests than SD:

Proposition 8 (SD exponentially better) *Let $\mathbf{U}$ be the set of UCs in $\mathcal{G}^*$ and $M = \max_{U \in \mathbf{U}} sep(U)$. There exist classes of graphs such that $T_{SD} + \Theta(2^{M-1}) \leq T_{PC}$; and $T_{SD} + \Theta(2^{M-1}) \leq T_{LDECC}$.*

Proof Consider the class of graphs shown in Fig. 6(*b*) with a UC with a separating set of size M and a clique of size N upstream of that UC. Since LDECC runs CI tests in the same order as PC, if $N \geq M$, LDECC performs $\Theta(2^{M-1})$ CI tests for nodes inside the clique (all tests of the form $V_i \perp\!\!\!\perp V_j | \mathbf{S}$ s.t. $\mathbf{S} \subseteq \{V_1, \ldots, V_N\} \setminus \{V_i, V_j\}$ and $|\mathbf{S}| < M$ will be run) before the UC is unshielded

via the test $A \perp\!\!\!\perp B | \{S_1, \ldots, S_M\}$. By contrast, SD terminates before even getting to the clique, thus avoiding these tests. So if $M \asymp |\mathbf{V}|$, LDECC will perform exponentially more tests than SD. ∎

Qualitatively, this shows that if UCs have large separating sets and there are dense regions upstream of such UCs, LDECC might perform poorly whereas SD can avoid tests in these regions since it would not reach these dense regions.

Next, we present upper bounds for the computational requirements of LDECC and SD for a restricted class of graphs that we call *Locally Orientable Graphs*.

Definition 9 (Locally Orientable Graph.) *A DAG $\mathcal{G}$ is said to be* locally orientable *with respect to a node X if, $\forall V \in Ne(X)$, the edge $X—V$ is oriented in the CPDAG for the MEC of $\mathcal{G}$. Since all nodes in $Ne(X)$ can be oriented, the ATE is point identified, i.e., $|\Theta^*| = 1$.*

Definition 10 (Parent Orienting Collider (POC)) *Consider a DAG $\mathcal{G}^*$. For each $P \in Pa(X)$, let $POC(P)$ be the set of UCs that can orient P, i.e., either (i) P is a part of that UC; or (ii) applying Meek's rules from that UC in the undirected skeleton of $\mathcal{G}^*$ will orient $P \to X$.*

In Props. 11,12, we provide sufficient graphical conditions for when both the algorithms run in polynomial time. For LDECC, we show that the time complexity of orienting the parents depends only on the size of the separating sets for the UCs, i.e., *sep* (Prop. 11). Importantly, the bound is agnostic to how far away the UCs are from the parents.

Proposition 11 (LDECC upper bound) *For a locally orientable DAG $\mathcal{G}^*$, let $D = \max_{V \in MB^+(X)} |Ne(V)|$ and $S = \max_{P \in Pa(X)} \min_{\alpha \in POC(P)} sep(\alpha)$. Then $T_{LDECC} \leq \mathcal{O}(|\mathbf{V}|^{\max\{S,D\}})$.*

For SD, we show that the time complexity of orienting a parent is upper bounded by (i) the *sep* of the closest UC that orients that parent and (ii) the complexity of discovering the neighbors of nodes on the path to that collider (Prop. 12). Importantly, this bound is agnostic to the structure of the nodes that are upstream of the closest colliders.

Proposition 12 (SD upper bound) *For a locally orientable DAG $\mathcal{G}^*$, let $\pi : \mathbf{V} \to \mathbb{N}$ be the order in which nodes are processed by SD (Line 4 of SD). For $P \in Pa(X)$, let $CUC(P) = \text{argmin}_{\alpha \in POC(P)} \pi(\alpha)$ denote the closest UC to P. Let $C = \max_{P \in Pa(X)} sep(CUC(P))$, $D = \max_{V \in MB^+(X)} |Ne(V)|$, and $E = \max_{\{V : \pi(V) < \pi(CUC(P))\}} |Ne(V)|$. Then $T_{SD} \leq \mathcal{O}(|\mathbf{V}|^{\max\{C,D,E\}})$.*

Remark 13 *The following procedure demonstrates one way that LDECC and SD can be combined to broaden the class of graphs where local causal discovery can be performed efficiently: Run both SD and LDECC in parallel and terminate when either algorithm terminates. The number of CI tests performed will be $T_{combined} \leq 2 \min \{T_{SD}, T_{LDECC}\}$. This procedure will be subexponential if at least one of the algorithms is subexponential.*

4.2. Comparison of faithfulness requirements

In this section, we show that SD and LDECC rely on different faithfulness assumptions (Props. 18,20). The CFA is controversial (Uhler et al., 2013) and some works attempt to test or weaken it (Zhang and Spirtes, 2008; Ramsey et al., 2012; Zhang and Spirtes, 2016). Sharing a similar motivation, we show that LDECC and SD can be fruitfully combined to strictly weaken the faithfulness assumptions needed to identify Θ^* (Prop. 25). We defer the proofs to Appendix B.3.

Definition 14 (Adjacency Faithfulness (AF)) *Given a DAG $\mathcal{G}(\mathbf{V}, \mathbf{E})$, AF holds for node $A \in \mathbf{V}$ iff $\forall A$—$B \in \mathbf{E}$, we have $\forall \mathbf{S} \subseteq \mathbf{V} \setminus \{A, B\}$, $A \not\perp\!\!\!\perp B | \mathbf{S}$.*

Definition 15 (Orientation Faithfulness (OF)) *Given a DAG $\mathcal{G}(\mathbf{V}, \mathbf{E})$, OF holds for an unshielded triple A—C—B (where A—$B \notin E$) iff (i) when it is a UC, $A \not\perp\!\!\!\perp B | \mathbf{S}$ for any $\mathbf{S} \subseteq \mathbf{V} \setminus \{A, B\}$ s.t. $C \in \mathbf{S}$; and (ii) when it is a non-collider, $A \not\perp\!\!\!\perp B | \mathbf{S}$ for any $\mathbf{S} \subseteq V \setminus \{A, B\}$ s.t. $C \notin \mathbf{S}$.*

Definition 16 (Local Faithfulness (LF)) *Given a DAG $\mathcal{G}(\mathbf{V}, \mathbf{E})$, LF holds for node X iff (i) AF holds for X; and (ii) OF holds for every unshielded triple A—X—$B \in \mathcal{G}$.*

Proposition 17 *PC will identify the MEC of $\mathcal{G}^*$ if LF holds for all nodes.*

If the goal is to identify Θ^* (and not the entire MEC), weaker faithfulness conditions than those of Prop. 17 are sufficient for SD and PC (Prop. 18). Let $\mathcal{U}$ be the undirected graph on the nodes $\mathbf{V}$ such that an edge A—B exists iff $\forall \mathbf{S} \subseteq \mathbf{V} \setminus \{A, B\}$, $A \not\perp\!\!\!\perp B | \mathbf{S}$. Informally, $\mathcal{U}$ is the skeleton of the observational distribution. Let $J^* = \{(A \to C \leftarrow B) \in \mathcal{G}^*\}$ be the set of UCs in the true DAG $\mathcal{G}^*$.

Proposition 18 (Faithfulness for PC and SD) *PC and SD will identify Θ^* if (i) LF holds $\forall V \in MB^+(X)$; (ii) $\forall (A \to C \leftarrow B) \in J^*$, (a) LF holds for A, B, and C, and (b) LF holds for each node on all paths $C \to \ldots \to V \in \mathcal{G}^*$ s.t. $V \in Ne(X)$; (iii) For every edge A—$B \notin \mathcal{G}^*$, $\exists \mathbf{S} \subseteq (Ne_{\mathcal{U}}(A) \cup Ne_{\mathcal{U}}(B))$ s.t. $A \perp\!\!\!\perp B | \mathbf{S}$; and (iv) OF holds for all unshielded triples in $\mathcal{G}^*$.*

Proof Sketch By Conditions (i,ii), UCs in $\mathcal{G}^*$ are detected and orientations are propagated correctly to X. By Condition (iii), the skeleton discovered by PC and SD is a subgraph of the skeleton of $\mathcal{G}^*$ and thus there are no spurious paths. By Condition (iv), no spurious UCs are detected. Prop. 18 is weaker because AF can be violated for nodes not on paths from UCs to X. ■

We now present sufficient faithfulness conditions for LDECC. Let $\mathbf{L} = \{(A, B, \mathbf{S}) : |\{A, B\} \cap Ne(X)| \le 1, \mathbf{S} \subseteq \mathbf{V} \setminus \{A, B, X\}\}$ and $H^* = \{(A, B, \mathbf{S}) \in \mathbf{L} : A \perp\!\!\!\perp_{\mathcal{G}^*} B | \mathbf{S}, A \not\perp\!\!\!\perp_{\mathcal{G}^*} B | \mathbf{S} \cup \{X\}\}$, where $\perp\!\!\!\perp_{\mathcal{G}^*}$ ($\not\perp\!\!\!\perp_{\mathcal{G}^*}$) denotes d-separation (d-connection). Informally, H^* contains the set of ECCs entailed by the true DAG $\mathcal{G}^*$. Analogously, let $H = \{(A, B, \mathbf{S}) \in \mathbf{L} : A \perp\!\!\!\perp B | \mathbf{S}, A \not\perp\!\!\!\perp B | \mathbf{S} \cup \{X\}\}$. Informally, H contains the set of ECCs entailed by the observational joint distribution $\mathbb{P}(\mathbf{V})$.

Definition 19 (MNS Faithfulness (MFF)) *Given a DAG $\mathcal{G}(\mathbf{V}, \mathbf{E})$, MFF holds for node $V \notin Ne^+(X)$ iff (a) When $mns_X(V)$ does not exist, $\forall \mathbf{S} \subseteq Ne(X)$, we have $V \not\perp\!\!\!\perp X | \mathbf{S}$; and (b) When $mns_X(V)$ exists, $\forall \mathbf{S} \subseteq Ne(X)$ s.t. $\mathbf{S} \ne mns_X(V)$ and $V \perp\!\!\!\perp X | \mathbf{S}$, we have $|\mathbf{S}| > |mns_X(V)|$.*

Proposition 20 (Faithfulness for LDECC) *LDECC will identify Θ^* if (i) LF holds $\forall V \in MB^+(X)$; (ii) $H \subseteq H^*$; (iii) $\forall (A, B, \mathbf{S}) \in H$, MFF holds for $\{A, B\} \setminus Ne(X)$; and (iv) $\forall (A, B, \mathbf{S}) \in H^*$ s.t. there is a UC $(A \to C \leftarrow B) \in \mathcal{G}^*$, we have (a) AF holds for A and B; and (b) $(A, B, \mathbf{S}) \in H$.*

Proof Sketch By Condition (i), the structure within $MB^+(X)$ is correctly discovered. By Condition (ii), every ECC run by LDECC will be valid (since it is also part of H^*), and together with Condition (iii), every ECC will mark the correct parents. By Condition (iv), an ECC will be run for every UC that can orient parents of X, ensuring that all parents get oriented: (iv)(a) ensures that the UC gets unshielded, and (iv)(b) ensures that an ECC is run in Line 16 after the UC is unshielded. ■

(*a*) DAG with unfaithfulness

(*b*) Testable violation for SD

(*c*) MFF fails for nodes A, B

Figure 7: Different faithfulness violations.

Remark 21 *In LDECC, if we run* ECCParents *with* check=True *where we mark parents with an ECC only if GetMNS(A) = GetMNS(B) (Lines 20–24 in Fig. 4), then LDECC requires weaker assumptions than Prop. 20 (see Prop. 29 in Appendix B.3) and does better empirically (Sec. 5).*

We demonstrate that SD and LDECC rely on different faithfulness assumptions: There are faithfulness violations that affect one algorithm but not the other. This motivates a procedure that outputs a (conservative) ATE set containing the values in Θ^* under weaker assumptions (Prop. 22).

Example 1 (SD incorrect) *Consider the faithfulness violation $W \perp\!\!\!\perp D|M$ for the DAG in Fig. 7(a) (conditioning on the collider M cancels out the $W \leftarrow D$ edge). Thus, the edge $W \leftarrow D$ might be incorrectly removed and both SD and PC will not mark W as a parent since the orientations will not be propagated to W. However, LDECC can still correctly mark W as a parent using an ECC.*

Example 2 (LDECC incorrect) *Consider the faithfulness violations $A \perp\!\!\!\perp X|M$ and $B \perp\!\!\!\perp X|M$ for the DAG in Fig. 7(a). We can incorrectly find $mns_X(A) = mns_X(B) = \{M\}$ (if Line 14 in GetMNS tests $A \perp\!\!\!\perp X|M$ or $B \perp\!\!\!\perp X|M$) causing LDECC to orient M as a parent via an ECC. But these violations do not impact SD and PC since the skeleton and UCs are still discovered correctly.*

Proposition 22 (Conservative ATE set) *Consider the following procedure: (i) run both SD and LDECC to get Θ_{SD} and Θ_{LDECC}; (ii) output the set $\Theta_{union} = \Theta_{LDECC} \cup \Theta_{SD}$. If the faithfulness assumptions for either SD or LDECC hold, then $\Theta^* \subseteq \Theta_{union}$.*

Next, we show that some violations that affect SD and LDECC are detectable. We use this insight to construct a procedure (Prop. 25) that identifies Θ^* under strictly weaker faithfulness assumptions by switching to LDECC if a violation of the assumptions of SD is detected (or vice versa).

Proposition 23 (Testing faithfulness for LDECC) *Consider running the algorithm in Fig. 8 before invoking GetMNS(A) for some node A in LDECC. If the algorithm returns Fail, MFF is violated for node A. If the algorithm returns Unknown, we could not ascertain if MFF holds for node A.*

Proof Sketch If Line 4 returns *Fail*, there are multiple minimal sets thereby violating the uniqueness of MNS (see Example 3). If Line 7 returns *Fail*, for the detected MNS $\mathbf{S}$, there is a superset $\mathbf{S}'$ s.t. $A \perp\!\!\!\perp X|\mathbf{S}'$ but also an intermediate set $\mathbf{S}''$ s.t. $A \not\perp\!\!\!\perp X|\mathbf{S}''$ which cannot happen if MFF holds because removing nodes from $\mathbf{S}'$ should not violate independence (see Example 4). ∎

Example 3 (Testing MFF) *Consider the faithfulness violations $A \perp\!\!\!\perp X|M$ and $B \perp\!\!\!\perp X|M$ for the DAG in Fig. 7(a). We might incorrectly detect $mns_X(A) = mns_X(B) = \{M\}$ (similar to Example 2). Line 4 in Fig. 8 will return Fail because for A, B, we have $\mathbf{Q}_{min} = \{\{W\}, \{M\}\}$.*

Input: Node $A \notin \mathrm{Ne}^+(X), \mathrm{Ne}(X)$
1 $\mathbf{Q} \leftarrow \{\mathbf{S} \subseteq \mathrm{Ne}(X) : A \perp\!\!\!\perp X|\mathbf{S}\}$;
2 **if** $|\mathbf{Q}| = 0$ **then return** noValidMNS ;
3 $\mathbf{Q}_{\min} \leftarrow \{\mathbf{S} \in \mathbf{Q} : \forall \mathbf{S}' \subset \mathbf{S}, \mathbf{S}' \notin \mathbf{Q}\}$;
4 **if** $|\mathbf{Q}_{\min}| > 1$ **then return** Fail ;
5 $\mathbf{S} \leftarrow \mathrm{GetElement}(\mathbf{Q}_{\min})$;   // Here $|\mathbf{Q}_{\min}| = 1$.
6 **for** $\mathbf{S}' \in \mathbf{Q}$ *such that* $\mathbf{S} \subset \mathbf{S}'$ **do**
7 | **if** $\exists \mathbf{S}'' \notin \mathbf{Q}$ *s.t.* $\mathbf{S} \subset \mathbf{S}'' \subset \mathbf{S}'$ **then return** Fail ;
8 **end**
9 **return** Unknown;

Figure 8: Testing MFF.

Input: UC $\alpha = (A \to C \leftarrow B)$
1 $\mathbf{Q}(A) \leftarrow \{\mathbf{S} \subseteq \mathrm{Ne}(X) : A \perp\!\!\!\perp X|\mathbf{S}\}$;
2 $\mathbf{Q}(B) \leftarrow \{\mathbf{S} \subseteq \mathrm{Ne}(X) : B \perp\!\!\!\perp X|\mathbf{S}\}$;
   // See Defn. 10 for *POC*.
3 $\mathbf{M} \leftarrow \{P \in \mathrm{Pa}(X) : \alpha \in \mathrm{POC}(P)\}$;
4 $\widetilde{M}(A) \leftarrow \{\mathbf{S} \in \mathbf{Q}(A) : \mathbf{M} \subseteq \mathbf{S}\}$;
5 $\widetilde{M}(B) \leftarrow \{\mathbf{S} \in \mathbf{Q}(B) : \mathbf{M} \subseteq \mathbf{S}\}$;
6 **if** $|\widetilde{M}(A)| = 0$ *or* $|\widetilde{M}(B)| = 0$ **then**
   return Fail ;
7 **return** Unknown;

Figure 9: Testing faithfulness for SD.

Example 4 (Testing MFF) *Consider the DAG in Fig. 7(c). If a faithfulness violation causes the paths $X \leftarrow W_2 \leftarrow C$ and $X \leftarrow W_3 \leftarrow C$ to cancel each other out, we will observe $A \perp\!\!\!\perp X|W_1$ and thus wrongly detect $\mathrm{mns}_X(A) = \{W_1\}$. But Line 7 in Fig. 8 will detect this failure since $A \perp\!\!\!\perp X|\{W_1, W_2, W_3\}$ but $A \not\perp\!\!\!\perp X|\{W_1, W_2\}$ and $A \not\perp\!\!\!\perp X|\{W_1, W_3\}$.*

Proposition 24 (Testing faithfulness for SD) *Consider running the algorithm in Fig. 9 with each UC detected by SD. If the algorithm returns* Fail*, then faithfulness is violated for SD. If the algorithm returns* Unknown*, we could not ascertain if the faithfulness assumptions for SD hold.*

Proof Sketch In Line 3, $\mathbf{M}$ contains nodes marked as parents of X due to the UC $A \to C \leftarrow B$. In Line 6, we check that there is some superset of $\mathbf{M}$ that makes A and B independent of X: this must be true if the nodes in $\mathbf{M}$ were actually parents of X (see Example 5). ∎

Example 5 (Testing faithfulness for SD) *Consider an OF violation $C \perp\!\!\!\perp X|\mathbf{M}$ for the DAG in Fig. 7(b) that causes $X \to M \leftarrow C$ to be detected as a non-collider. SD will mark M as a parent via the UC $A \to C \leftarrow B$. But Line 6 will return* Fail *because $\mathbf{M} = \{M\}$ and $\mathbf{Q}(A) = \mathbf{Q}(B) = \{\{W\}\}$.*

Proposition 25 *Consider the following procedure: (i) run SD to get Θ_{SD}; (ii) test for faithfulness violations using Prop. 24; (iii) if a violation is found, run LDECC and output Θ_{LDECC}, else output Θ_{SD}. This procedure identifies Θ^* under strictly weaker assumptions than Prop. 18.*

Proof If the conditions of Prop. 18 hold, this procedure will output Θ_{SD} because we will not detect a faithfulness violation. However, if a violation is detected, this procedure will still identify Θ^* if the faithfulness conditions for LDECC hold. This is strictly weaker than the assumptions of Prop. 18. ∎

We can construct a similar procedure for LDECC. This again shows the complementary nature of the two algorithms: if there are detectable faithfulness violations for one algorithm, we can output an alternative ATE set thereby allowing us to identify Θ^* under weaker faithfulness assumptions than would be possible with only one of the algorithms. Currently, our testing procedures can only detect some (but not all) violations. Moreover, faithfulness violations in DAGs do not occur independently of each other: an unfaithful mechanism can lead to other (entangled) faithfulness violations. As a result, the violations affecting SD and LDECC will be entangled and the given faithfulness assumptions may not be the minimal ones required for local causal discovery.

(*a*) Tests with a CI oracle   (*b*) Accuracy   (*c*) Recall

(*d*) MSE vs sample size   (*e*) Number of CI tests

Figure 10: Results on synthetic linear Gaussian graphs.

5. Experiments

We present results on both synthetic linear graphs and the semi-synthetic *MAGIC-NIAB* graph from *bnlearn* (Scutari, 2009). We also ran the MB-by-MB approach (Wang et al., 2014), an instantiation of SD that uses IAMB (Fig. 14) and *LocalPC* for local structure learning. LDECC usually performs comparably to MB-by-MB and typically outperforms SD while running a similar number of CI tests. Results on synthetic binomial graphs and additional graphs from *bnlearn* are in Appendix C.

Results on synthetic data.   We generated synthetic linear graphs with Gaussian errors, 20 covariates— non-descendants of X and Y with paths to both X and Y—and 3 mediators—nodes on some causal path from X to Y. We sampled edges between the nodes with varying probabilities and sampled the edge weights uniformly from $[-1, -0.25] \cup [0.25, 1]$ (see Appendix C.1 for the precise procedure). We compared the algorithms based on the number of CI tests performed with a CI oracle on 250 synthetic graphs (of which $\approx 77\%$ were *locally orientable*; see Defn. 9). The distribution of CI tests (Fig. 10(*a*)) shows that LDECC performs comparably to MB-by-MB and substantially outperforms SD and PC on ~ 150 graphs. Next, we evaluated our methods on 250 synthetic graphs at four sample sizes. For each graph, we generated data 5 times (so we have $N = 1250$ runs). We used the Fisher-z CI test and ordinary least squares regression for ATE estimation. We also ran LDECC with *check=True* as described in Remark 21 (denoted by *LDECC-checks*). We define *accuracy* as the fraction of times we get the ATE set that we would estimate for the true DAG $\mathcal{G}^*$, and *recall* as the fraction of times the ATE estimated with the true DAG $\mathcal{G}^*$ is contained in the estimated ATE set, i.e., whether $\widehat{\theta}_{\text{ATE}}(\mathcal{G}^*) \in \widehat{\Theta}$. We used Hausdorff distance to compute mean squared error (MSE) between the estimated $\widehat{\Theta}$ and the ground-truth set Θ^*:

$$\text{MSE}_{\text{Hausdorff}}(\{\widehat{\Theta}\}_{i=1}^N, \{\Theta^*\}_{i=1}^N) = \frac{1}{N} \sum_{i=1}^N \max \left\{ \sup_{u \in \widehat{\Theta}_i} \inf_{v \in \Theta_i^*} (u-v)^2, \sup_{v \in \Theta_i^*} \inf_{u \in \widehat{\Theta}_i} (u-v)^2 \right\}.$$

(*a*) Tests with CI oracle   (*b*) Accuracy   (*c*) Recall

(*d*) Median SE vs sample size   (*e*) Average number of CI tests

Figure 11: Results on the semi-synthetic *MAGIC-NIAB* linear Gaussian graph.

LDECC-checks and MB-by-MB have comparable accuracy and are better than both SD and PC (Fig. 10(*b*)). In terms of recall, LDECC-checks and PC perform comparably and outperform SD and MB-by-MB (Fig. 10(*c*)). LDECC-checks has better accuracy and recall than LDECC suggesting that the check helps in practice. Both variants of LDECC have substantially lower MSE than MB-by-MB, PC, and SD (Fig. 10(*d*)) while still doing a similar number of CI tests as MB-by-MB (Fig. 10(*e*)).

Results on *MAGIC-NIAB* from bnlearn. *MAGIC-NIAB* is a linear Gaussian DAG with 44 nodes. With a CI oracle, PC performed $\approx 1.472 \times 10^6$ tests. We plot the distribution of CI tests by repeatedly setting each node as the treatment (capping the maximum number of tests per node to 20000). We see that LDECC and MB-by-MB perform better than SD with MB-by-MB performing well across all nodes (Fig. 11(*a*)). Next, we designated the nodes *G266* and *HT* as the treatment and outcome, respectively. We compared the methods by sampling the data 100 times at four sample sizes (capping the maximum number of tests run by each algorithm to 7000). LDECC has similar accuracy (Fig. 11(*b*)) and recall (Fig. 11(*c*)) as MB-by-MB and they outperform SD on both metrics. We plot *median* squared error (Fig. 11(*d*)) for MB-by-MB and LDECC (MB-by-MB does poorly on the mean due to outliers). Both are similar at large sample sizes (we omit SD because it does poorly). Additionally, LDECC performs fewer CI tests than MB-by-MB and SD (Fig. 11(*e*)).

6. Conclusion

Broadening the landscape of local causal discovery, we propose a new algorithm that uses ECCs to orient parents. We show that LDECC has different computational and faithfulness requirements compared to the existing class of sequential algorithms. This allows us to profitably combine the two methods to get polynomial runtimes on a larger class of graphs as well as identify the set of possible ATE values under weaker assumptions. In future work, we hope to further weaken the faithfulness requirements and extend our methods to handle causal graphs with latent variables.

Acknowledgments

We gratefully acknowledge Amazon AI, UPMC, Abridge, the PwC Center, the Block Center, the Center for Machine Learning and Health, and the CMU Software Engineering Institute (SEI) via Department of Defense contract FA8702-15-D-0002, for their generous support of ACMI Lab's research. In particular, we are grateful to the PwC center for supporting Shantanu Gupta as a presidential scholar during the completion of this research, and to Amazon AI who has named Shantanu Gupta a recipient of the Amazon Ph.D. fellowship for the coming year.

References

Constantin F Aliferis, Ioannis Tsamardinos, and Alexander Statnikov. Hiton: a novel markov blanket algorithm for optimal variable selection. In *AMIA annual symposium proceedings*. American Medical Informatics Association, 2003.

Constantin F Aliferis, Alexander Statnikov, Ioannis Tsamardinos, Subramani Mani, and Xenofon D Koutsoukos. Local causal and markov blanket induction for causal discovery and feature selection for classification part i: algorithms and empirical evaluation. *Journal of Machine Learning Research*, 11(1), 2010.

Debo Cheng, Jiuyong Li, Lin Liu, Kui Yu, Thuc Duy Le, and Jixue Liu. Toward unique and unbiased causal effect estimation from data with hidden variables. *IEEE Transactions on Neural Networks and Learning Systems*, 2022a.

Debo Cheng, Jiuyong Li, Lin Liu, Kui Yu, Thuc Duy Lee, and Jixue Liu. Discovering ancestral instrumental variables for causal inference from observational data. *arXiv preprint arXiv:2206.01931*, 2022b.

Tom Claassen and Tom Heskes. A logical characterization of constraint-based causal discovery. *arXiv preprint arXiv:1202.3711*, 2012.

Gregory F Cooper. A simple constraint-based algorithm for efficiently mining observational databases for causal relationships. *Data Mining and Knowledge Discovery*, 1997.

Xavier De Luna, Ingeborg Waernbaum, and Thomas S Richardson. Covariate selection for the nonparametric estimation of an average treatment effect. *Biometrika*, 2011.

Doris Entner, Patrik Hoyer, and Peter Spirtes. Statistical test for consistent estimation of causal effects in linear non-gaussian models. In *Artificial Intelligence and Statistics*, 2012.

Doris Entner, Patrik Hoyer, and Peter Spirtes. Data-driven covariate selection for nonparametric estimation of causal effects. In *Artificial Intelligence and Statistics*. PMLR, 2013.

Zhuangyan Fang and Yangbo He. Ida with background knowledge. In *Conference on Uncertainty in Artificial Intelligence*. PMLR, 2020.

Tian Gao and Qiang Ji. Local causal discovery of direct causes and effects. *Advances in Neural Information Processing Systems*, 2015.

Tomas Geffner, Javier Antoran, Adam Foster, Wenbo Gong, Chao Ma, Emre Kiciman, Amit Sharma, Angus Lamb, Martin Kukla, Nick Pawlowski, et al. Deep end-to-end causal inference. *arXiv preprint arXiv:2202.02195*, 2022.

Clark Glymour, Kun Zhang, and Peter Spirtes. Review of causal discovery methods based on graphical models. *Frontiers in genetics*, 2019.

Limor Gultchin, Matt Kusner, Varun Kanade, and Ricardo Silva. Differentiable causal backdoor discovery. In *International Conference on Artificial Intelligence and Statistics*. PMLR, 2020.

Leonard Henckel, Emilija Perković, and Marloes H Maathuis. Graphical criteria for efficient total effect estimation via adjustment in causal linear models. *arXiv preprint arXiv:1907.02435*, 2019.

Antti Hyttinen, Frederick Eberhardt, and Matti Järvisalo. Do-calculus when the true graph is unknown. In *UAI*. Citeseer, 2015.

Amin Jaber, Jiji Zhang, and Elias Bareinboim. Causal identification under markov equivalence: Completeness results. In *International Conference on Machine Learning*. PMLR, 2019.

Zhaolong Ling, Kui Yu, Hao Wang, Lei Li, and Xindong Wu. Using feature selection for local causal structure learning. *IEEE Transactions on Emerging Topics in Computational Intelligence*, 2020.

Zhaolong Ling, Kui Yu, Yiwen Zhang, Lin Liu, and Jiuyong Li. Causal learner: A toolbox for causal structure and markov blanket learning. *arXiv preprint arXiv:2103.06544*, 2021.

Marloes H Maathuis and Diego Colombo. A generalized back-door criterion. *The Annals of Statistics*, 2015.

Marloes H Maathuis, Markus Kalisch, and Peter Bühlmann. Estimating high-dimensional intervention effects from observational data. *The Annals of Statistics*, 2009.

Sara Magliacane, Tom Claassen, and Joris M Mooij. Ancestral causal inference. *Advances in Neural Information Processing Systems*, 2016.

Daniel Malinsky and Peter Spirtes. Estimating causal effects with ancestral graph markov models. In *Conference on Probabilistic Graphical Models*. PMLR, 2016.

Subramani Mani, Peter L Spirtes, and Gregory F Cooper. A theoretical study of y structures for causal discovery. *arXiv preprint arXiv:1206.6853*, 2012.

Christopher Meek. Causal inference and causal explanation with background knowledge. *arXiv preprint arXiv:1302.4972*, 2013.

Joris M Mooij, Jerome Cremers, et al. An empirical study of one of the simplest causal prediction algorithms. In *UAI 2015 Workshop on Advances in Causal Inference*, 2015.

Preetam Nandy, Marloes H Maathuis, and Thomas S Richardson. Estimating the effect of joint interventions from observational data in sparse high-dimensional settings. *The Annals of Statistics*, 2017.

Judea Pearl. *Causality*. Cambridge university press, 2009.

Emilija Perković, Markus Kalisch, and Maloes H Maathuis. Interpreting and using cpdags with background knowledge. *arXiv preprint arXiv:1707.02171*, 2017.

Joseph Ramsey, Jiji Zhang, and Peter L Spirtes. Adjacency-faithfulness and conservative causal inference. *arXiv preprint arXiv:1206.6843*, 2012.

Andrea Rotnitzky and Ezequiel Smucler. Efficient adjustment sets for population average treatment effect estimation in non-parametric causal graphical models. *arXiv preprint arXiv:1912.00306*, 2019.

Marco Scutari. Learning bayesian networks with the bnlearn r package. *arXiv preprint arXiv:0908.3817*, 2009.

Abhin Shah, Karthikeyan Shanmugam, and Kartik Ahuja. Finding valid adjustments under non-ignorability with minimal dag knowledge. In *International Conference on Artificial Intelligence and Statistics*. PMLR, 2022.

Ricardo Silva and Shohei Shimizu. Learning instrumental variables with structural and non-gaussianity assumptions. *Journal of Machine Learning Research*, 2017.

Peter Spirtes, Clark N Glymour, Richard Scheines, and David Heckerman. *Causation, prediction, and search*. MIT press, 2000.

Chandler Squires and Caroline Uhler. Causal structure learning: a combinatorial perspective. *arXiv preprint arXiv:2206.01152*, 2022.

Jin Tian and Judea Pearl. *A general identification condition for causal effects*. eScholarship, University of California, 2002.

Christian Toth, Lars Lorch, Christian Knoll, Andreas Krause, Franz Pernkopf, Robert Peharz, and Julius Von Kügelgen. Active bayesian causal inference. *arXiv preprint arXiv:2206.02063*, 2022.

Ioannis Tsamardinos, Constantin F Aliferis, Alexander R Statnikov, and Er Statnikov. Algorithms for large scale markov blanket discovery. In *FLAIRS conference*. St. Augustine, FL, 2003.

Ioannis Tsamardinos, Laura E Brown, and Constantin F Aliferis. The max-min hill-climbing bayesian network structure learning algorithm. *Machine learning*, 2006.

Caroline Uhler, Garvesh Raskutti, Peter Bühlmann, and Bin Yu. Geometry of the faithfulness assumption in causal inference. *The Annals of Statistics*, 2013.

Tyler J VanderWeele and Ilya Shpitser. A new criterion for confounder selection. *Biometrics*, 2011.

Philip Versteeg, Joris Mooij, and Cheng Zhang. Local constraint-based causal discovery under selection bias. In *Conference on Causal Learning and Reasoning*. PMLR, 2022.

Changzhang Wang, You Zhou, Qiang Zhao, and Zhi Geng. Discovering and orienting the edges connected to a target variable in a dag via a sequential local learning approach. *Computational Statistics & Data Analysis*, 2014.

David S Watson and Ricardo Silva. Causal discovery under a confounder blanket. In *Uncertainty in Artificial Intelligence*. PMLR, 2022.

Janine Witte and Vanessa Didelez. Covariate selection strategies for causal inference: Classification and comparison. *Biometrical Journal*, 2019.

Jianxin Yin, You Zhou, Changzhang Wang, Ping He, Cheng Zheng, and Zhi Geng. Partial orientation and local structural learning of causal networks for prediction. In *Causation and Prediction Challenge*. PMLR, 2008.

Kui Yu, Xianjie Guo, Lin Liu, Jiuyong Li, Hao Wang, Zhaolong Ling, and Xindong Wu. Causality-based feature selection: Methods and evaluations. *ACM Computing Surveys (CSUR)*, 2020.

Jiji Zhang and Peter Spirtes. Detection of unfaithfulness and robust causal inference. *Minds and Machines*, 2008.

Jiji Zhang and Peter Spirtes. The three faces of faithfulness. *Synthese*, 2016.

You Zhou, Changzhang Wang, Jianxin Yin, and Zhi Geng. Discover local causal network around a target to a given depth. In *Causality: Objectives and Assessment*. PMLR, 2010.