Developing multilingual speech synthesis system for Ojibwe, Mi'kmaq, and Maliseet

Abstract

We present lightweight flow matching multilingual text-to-speech (TTS) systems for Ojibwe, Mi'kmaq, and Maliseet, three Indigenous languages in North America. Our results show that training a multilingual TTS model on three typologically similar languages can improve the performance over monolingual models, especially when data are scarce. Attention-free architectures are highly competitive with self-attention architecture with higher memory efficiency. Our research provides technical development to language revitalization for low-resource languages but also highlights the cultural gap in human evaluation protocols, calling for a more community-centered approach to human evaluation.

1 Introduction

Many world languages are currently endangered, especially those spoken by historically marginalized and Indigenous communities. Language revitalization and reclamation is an ongoing effort to ensure continued language vitality for community self-determination and well-being (Oster et al., 2014; McCarty, 2018; Bird, 2020). Among recent efforts of language revitalization, TTS technology is valued as a potential tool to assist the education of Indigenous languages, as TTS models can flexibly synthesize diverse learning materials to guide pronunciation learning (Pine et al., 2022, 2024).

In general, speech synthesis for Indigenous languages is underdeveloped compared to the majority of languages. The main barrier to developing TTS technologies for Indigenous communities with oral traditions is still the lack of data (Pine et al., 2022, 2024). There are recent efforts to develop speech synthesis systems for low-resource and Indigenous languages, including Mundari (Gumma et al., 2024), Kanien'kéha (also known as Mohawk; Iroquoian), Gitksan (Tsimshianic), SEN COTEN (Coast Salish) (Pine et al., 2022, 2024), Plains Cree (Central Algonquian) (Harrigan et al., 2019) and Ojibwe (Hammerly et al., 2023). Yet there is still room for improvement and development in this space.

In this study, we continue this line of effort and develop TTS systems for **Ojibwe**, **Mi'kmaq**, and **Maliseet**, the latter two of which haven't received any attention from the speech processing community yet. Our study explicitly tackles several challenges in designing speech technology for Indigenous communities.

- First, it is generally impractical to bring Indigenous members to labs for recording, so we demonstrate a community-centered approach to allow speakers to record their own voices at their own pace.

- Secondly, as collecting Indigenous speech at scale is difficult, we show that training a flow matching multilingual TTS models (Mehta et al., 2024) with typologically similar language varieties can help improve the synthesis performance in low-resource settings.

- Thirdly, since the TTS system is likely to be deployed in common computing devices, we also implemented attention-free architectures, including FNet (Lee-Thorp et al., 2022), Mamba2 (Dao and Gu, 2024) and Hydra (Hwang et al., 2024) that closely match the performance of self-attention models in TTS but are generally more efficient in deployment.

- Finally, we also discuss the need to adapt current experimental paradigms to better work with Indigenous communities.

The code is available at: github.com/anonymous. Audio samples are attached as supplementary materials.

Language	Speaker	Gender	Train Duration	Samples	Dev Duration	Samples	Test Duration	Samples
Ojibwe	JJ	M	11h 49min 23s	11,062	6min 38s	100	6min 18s	100
Ojibwe	NJ	F	1h 41min 14s	2404	4min 21s	100	4min 9s	100
Mi'kmaq	MJ	F	2h 22min 57s	1116	12min 22s	100	12min 30s	100
Maliseet	AT	M	7h 15min 25s	3628	12min 16s	100	12min 27	100

Table 1: A summary of the Indigenous speech corpora in this study.

2 Data Collection

Languages We worked closely with speakers from three Indigenous languages of Canada: **Ojibwe**, **Mi'kmaq**, and **Maliseet**. The three languages are genetically related. Ojibwe is spoken around the Great lakes of North America and is part of the Central branch of the Algonquian family, while Mi'kmaq and Maliseet are spoken in the Maritimes and are classed within the Eastern branch of the Algonquian family. According to estimates from the 2021 Statistics Canada Survey, there are 25,440 speakers of Ojibwe, 9,000 speakers of Mi'kmaq, and 790 speakers of Maliseet (Robertson, 2023). All language communities are actively involved in significant efforts to document and ensure the continued vitality of their languages.

Data collection Most Indigenous speakers fluent in their own languages are senior speakers. It is infeasible to bring them to a sound-proof lab for recording at a university. Instead, we adopted a community-centered approach that allows the speakers to have full control over the speech recording process in the comfort of their own home, following the protocol from a prior study (Hammerly et al., 2023).

In each case, we used texts identified by the community members as representative of their dialect and writing system as the basis for the data set. These texts were then split into individual utterances (complete sentences or phrases) and loaded into the prompting and recording program SpeechRecorder (Draxler and Jänsch, 2004). The program allows speakers to read and record utterances at their own pace, easily re-record in the case of an error or disfluency, and package and upload recorded utterances into secure cloud storage as they complete them.

Data partition We resampled the recorded audio to 22,050Hz. For each speaker, we reserved 100 random samples for validation and another 100 random samples for test. The rest of the speech samples were used for model training. The detailed statistics of our data were summarized in Table 1. Since each of our datasets has a different size, we applied oversampling to our multilingual training dataset by duplicating training samples such that they contain roughly the same duration for each speaker.

3 Method

3.1 MatchaTTS

Our system is built upon Matcha-TTS (Mehta et al., 2024), a fast TTS model based on conditional flow matching, a class of probabilistic generative model capable of generating high-fidelity image and audio (Lipman et al., 2023). The original Matcha-TTS consists of a text encoder, a duration predictor, and a flow matching decoder. The text encoder transforms the text input into hidden states, which are then upsampled to the output length based on the duration predictor. The flow matching decoder predicts the final mel spectrogram through iterative denoising steps conditioning on the upsampled hidden states.

The original MatchaTTS model was only designed for single-speaker TTS. For multilingual speech synthesis, we added learnable speaker and language embeddings for each unique speaker and language, a common technique for multilingual models (Cho et al., 2022). Both embeddings will be concatenated with the output of the text encoder, which will be fed into the flow-matching decoder for mel-spectrogram prediction. By default, the flow-matching decoder uses 10 inference steps to perform inference.

3.2 Sequence mixing layers

The multilingual MatchaTTS utilizes self-attention for sequence mixing with 40M parameters, yet its quadratic complexity is not ideal for efficient deployment. Here we also explore different attention-free layers that can also mix information across sequences to improve the efficiency of MatchaTTS.

Model	F0 RMSE↓	LAS RMSE↓	MCD↓	PESQ↑	STOI↑	VUV F1↑	FID↓	MOS↑
Ojibwe JJ Natural	-	-	-	-	-	-	-	4.16
Monolingual Self-Attention	57.317	5.284	22.044	1.228	0.036	0.845	0.005	2.71
Multilingual Mamba2	**55.982**	**4.813**	**18.414**	1.229	0.035	**0.845**	0.004	3.00
Multilingual Hydra	56.806	5.147	18.849	**1.276**	**0.036**	0.842	0.004	3.25
Multilingual FNet	58.871	5.720	19.463	1.170	0.036	0.824	0.006	**3.42**
Multilingual Attention	56.454	4.859	18.427	1.240	0.034	0.843	**0.004**	2.67
Ojibwe NJ Natural	-	-	-	-	-	-	-	4.74
Monolingual Self-Attention	**80.511**	**6.198**	17.568	1.120	**0.033**	0.825	0.006	4.67
Multilingual Mamba2	89.879	6.311	17.506	1.111	0.028	0.820	**0.005**	4.56
Multilingual Hydra	87.509	6.676	18.036	1.128	0.029	0.830	0.006	4.70
Multilingual FNet	97.015	6.728	19.271	1.099	0.030	0.787	0.012	4.69
Multilingual Attention	86.446	6.462	**17.414**	**1.147**	0.028	**0.835**	0.006	**4.77**
Mi'kmaq MJ Natural	-	-	-	-	-	-	-	-
Monolingual Self-Attention	138.890	8.614	21.720	1.110	**0.039**	0.640	0.006	-
Multilingual Mamba2	139.574	7.831	22.060	1.165	0.038	0.643	0.005	-
Multilingual Hydra	**138.157**	**7.128**	21.694	**1.210**	0.038	0.649	0.005	-
Multilingual FNet	144.566	7.761	21.748	1.183	0.038	0.631	0.005	-
Multilingual Attention	138.365	7.357	**21.588**	1.165	0.037	**0.667**	**0.003**	-
Maliseet AT Natural	-	-	-	-	-	-	-	-
Monolingual Self-Attention	79.807	9.066	19.576	1.262	0.031	0.657	0.005	-
Multilingual Mamba2	77.725	8.565	19.152	1.213	**0.038**	0.727	0.007	-
Multilingual Hydra	79.834	8.414	**18.129**	**1.500**	0.035	0.728	0.006	-
Multilingual FNet	76.308	8.947	19.058	1.259	0.037	0.723	0.008	-
Multilingual Attention	**75.267**	**8.032**	18.173	1.316	0.032	**0.742**	0.005	-

Table 2: Evaluation results for each speaker across all models in `float32`.

Mamba2 Mamba2 (Dao and Gu, 2024) is a selective state-space model that can perform sequence mixing with linear time complexity. State-space models have been shown to be effective in speech generation task (Zhang et al., 2024; Miyazaki et al., 2024). We replaced the self-attention modules of MatchaTTS with Mamba2 blocks. Since there are also cross-attention modules, we implemented a Mamba2-based cross-attention by simply concatenating the two input sequences. Noticeably, Mamba2 modules have more parameters than attention modules. In order to keep the total number of parameters consistent, we shrunk the encoder and decoder hidden dimension size by $\frac{3}{4}$, resulting in around 38M parameters in total.

Hydra Hydra (Hwang et al., 2024) is a bidirectional extension of Mamba but still maintains the linear complexity. While Hydra has not been applied to TTS yet, its bidirectionality makes it potentially more powerful than Mamba2. Hydra layers were used to replace all attention modules in MatchaTTS. Hydra also has more parameters than attention, therefore we also shrunk the encoder and decoder hidden dimension size by $\frac{3}{4}$, resulting in around 39M parameters in total.

Discrete Fourier Transform Discrete Fourier Transform has been proved to be a possible sequence mixing method with a complexity of $O(L \log L)$(Lee-Thorp et al., 2022) and works well in speech tasks (Chen et al., 2024). We replaced all attention modules of the MatchaTTS with the FFT layer in FNet. The FFT layer performs 2D Fast Fourier Transform, on hidden dimensions and on the sequence dimension of the input. Since this operation is parameter-free, the FNet model has only around 31M parameters.

4 Experiments

Training As these languages all use a phonetically transparent Latin alphabet, we used a simple character-based tokenizer to tokenize all sentences. Punctuations were all removed except for the apostrophe in Ojibwe, which plays a role in Ojibwe phonology. Monolingual models were trained for each individual speaker, whereas multilingual models were trained on all speakers with different sequence mixing layers. All experiments were run on a single A100 40GB GPU for a fixed 200 epochs. Full training details are available in Appendix A.

Vocoder For waveform generation, we trained a Vocos vocoder (Siuzdak, 2024) on all training samples. Vocos is a frequency domain vocoder that closely matches the performance of time-domain vocoders like Hifi-GAN (Kong et al., 2020) and diffusion-based vocoder like Fregrad (Nguyen et al., 2024) but with much higher throughput.

	Batch Size	**Self-attention**	**Mamba2**	**Hydra**	**FNet**
Throughput (generated speech/s)	400	273.83	245.54	198.99	241.05
Real-time factor	1	0.03	0.06	0.06	0.03
Memory usage	400	4.6G	2.3G	2.4G	2.5G
Memory usage	1	245M	202M	235M	230M

Table 3: The time and memory efficiency of different sequence-mixing layers in `float32` on a single A100 40G.

Since vocoder is not the focus, we provided their evaluation results in Appendix D.

5 Results and Discussions

Objective Evaluation We perform our objective evaluation results with Fundamental Frequency Root Mean Square Error (F0 RMSE), Log-amplitude RMSE (LAS RMSE), Mel Cepstral Distortion (MCD), Perceptual Evaluation of Speech Quality (PESQ), Short-Time Objective Intelligibility (STOI), Voiced/Unvoiced F1 (VUV F1) and MFCC Frechet Distance (FID), similar to contemprary works (Li et al., 2024; Lv et al., 2024).

Results in Table 2 suggest that multilingual models generally outperform monolingual models in all languages. Training on typologically similar languages does help alleviate the lack of data for individual languages, since the model can learn from the commonalities in these languages. Such findings can also provide guidance for the future collection of Indigenous speech datasets. We can prioritize dataset diversity over quantity, as a large quantity of speech data from a single language is also hard to collect.

While the self-attention MatchaTTS dominates most objective metrics, other attention-free architectures also match its performance closely. No single model dominates all objective metrics. Hydra's performance is particularly close to self-attention, suggesting that it is a strong competitor. Its bidirectional nature also allows it to outperform Mamba2. FNet underperforms all other models due to its parameter-free nature.

In terms of computational efficiency, as shown in Table 3, all attention-free architectures are much more memory-efficient than self-attention models, and memory saving is more prominent when the batch size is large. However, the attention-free architectures do not necessarily reduce computation time, presumably because our model is small enough that their advantages are not obvious.

Subjective Evaluation Despite these challenges, in evaluating the current work, we designed separate mean opinion score (MOS) surveys for each language. For each TTS voice, the survey included 10 generated utterances from each of the five models and 10 utterances of natural speech. The detailed design is described in Appendix E. We were able to recruit three raters for Ojibwe but one did not complete the survey. For Mi'kmaq and Maliseet, we were not able to obtain MOS rating due to the limited number of speakers. Generally speaking, the MOS ratings are largely consistent with the objective metrics (see Table 2).

As recently discussed in Pine et al. (2024), there are many challenges and questions to be raised when conducting a subjective evaluation of speech synthesis with Indigenous communities. We also find that, due to the gap in cultural norms, the use of standard measures like MOS and the current experimental paradigm may not always be viable in determining the quality of synthetic speech. For example, despite our instructions, one Ojibwe rater rated 5 for all Ojibwe NJ's voices, regardless of whether it was natural or synthetic. We believe this may have been due to a reluctance to comment negatively on the voice, even when it was synthetic. The concept of participating in controlled experiments and judging synthetic voices, in general, is not a natural task, and cultural norms can amplify this. This implies that researchers working with Indigenous communities should design more creative measures that also conform to the cultural norms of the relevant community. We plan to conduct such work as we continue development of these systems

6 Conclusion

In this paper, we report our ongoing efforts to develop TTS systems with and for the Indigenous community. Our experiments demonstrate that training multilingual TTS models on similar languages can partially compensate for the lack of data for individual languages. In the future, we will be working with the relevant communities and schools to deploy these systems for Indigenous language education.

7 Ethical statements

Our research would not have been possible without the support of the Indigenous communities involved. The subjective evaluation experiments were approved by the institutional ethics review committee. All Indigenous participants in the study, including the voice donors and raters, participated voluntarily and received fair compensation for their contributions.

The goal of our research is to develop TTS tools for Indigenous communities. We are currently actively working with learners and teachers learning these Indigenous languages at school. However, TTS technology might potentially be misused for impersonation and deception, which can be particularly dangerous for the Indigenous communities as they are not frequently exposed to such technologies. We will continue to work alongside these communities to inform them about the benefits as well as security concerns of speech technologies.

8 Limitation

Our study is still limited in several aspects. First, as all speech recordings were recorded at the speakers' own residence, there are still ambient noises in some of the recordings. These background noises limit the overall performance of TTS systems. Secondly, we were not able to successfully conduct human MOS ratings, which complicates the interpretation of the results.

Secondly, while we would like to make the collected data publicly available for replication and language documentation research, we were unable to do so this time, as we were not able to obtain the consent of the Indigenous voice donors at this moment. The primary concern is the malicious use of the data that might harm the communities. However, we will continue to work with them and aim for more open-source corpora in the long run.

Our research currently focuses mostly on machine learning system development. To make speech technology truly beneficial to the Indigenous communities, more human-centered designs that take into consideration the community-specific cultural norms will also be needed to deploy these systems to the benefit of the Indigenous communities (Noe and Kirshenbaum, 2024).

References

Steven Bird. 2020. Decolonising speech and language technology. In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 3504–3519, Barcelona, Spain (Online). International Committee on Computational Linguistics.

William Chen, Takatomo Kano, Atsunori Ogawa, Marc Delcroix, and Shinji Watanabe. 2024. Train long and test long: Leveraging full document contexts in speech processing. In *ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 13066–13070. IEEE.

Hyunjae Cho, Wonbin Jung, Junhyeok Lee, and Sang Hoon Woo. 2022. Sane-tts: Stable and natural end-to-end multilingual text-to-speech. In *Interspeech 2022*, pages 1–5.

Tri Dao and Albert Gu. 2024. Transformers are SSMs: Generalized models and efficient algorithms through structured state space duality. In *International Conference on Machine Learning (ICML)*.

Christoph Draxler and Klaus Jänsch. 2004. Speechrecorder: A universal platform independent multi-channel audio recording software. In *LREC*.

Varun Gumma, Rishav Hada, Aditya Yadavalli, Pamir Gogoi, Ishani Mondal, Vivek Seshadri, and Kalika Bali. 2024. MunTTS: A text-to-speech system for Mundari. In *Proceedings of the Seventh Workshop on the Use of Computational Methods in the Study of Endangered Languages*, pages 76–82, St. Julians, Malta. Association for Computational Linguistics.

Christopher Hammerly, Sonja Fougère, Giancarlo Sierra, Scott Parkhill, Harrison Porteous, and Chad Quinn. 2023. A text-to-speech synthesis system for border lakes Ojibwe. In *Proceedings of the Sixth Workshop on the Use of Computational Methods in the Study of Endangered Languages*, pages 60–65, Remote. Association for Computational Linguistics.

Atticus Harrigan, Timothy Mills, and Antti Arppe. 2019. A preliminary plains cree speech synthesizer. In *Proceedings of the Workshop on Computational Methods for Endangered Languages*, volume 1.

Sukjun Hwang, Aakash Lahoti, Tri Dao, and Albert Gu. 2024. Hydra: Bidirectional state space models through generalized matrix mixers. *arXiv preprint arXiv:2407.09941*.

Jungil Kong, Jaehyeon Kim, and Jaekyoung Bae. 2020. Hifi-gan: Generative adversarial networks for efficient and high fidelity speech synthesis. *Advances in neural information processing systems*, 33:17022–17033.

James Lee-Thorp, Joshua Ainslie, Ilya Eckstein, and Santiago Ontanon. 2022. FNet: Mixing tokens with

Fourier transforms. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 4296–4313, Seattle, United States. Association for Computational Linguistics.

Xiang Li, FanBu FanBu, Ambuj Mehrish, Yingting Li, Jiale Han, Bo Cheng, and Soujanya Poria. 2024. CM-TTS: Enhancing real time text-to-speech synthesis efficiency through weighted samplers and consistency models. In *Findings of the Association for Computational Linguistics: NAACL 2024*, pages 3777–3794, Mexico City, Mexico. Association for Computational Linguistics.

Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matthew Le. 2023. Flow matching for generative modeling. In *The Eleventh International Conference on Learning Representations*.

Yuanjun Lv, Hai Li, Ying Yan, Junhui Liu, Danming Xie, and Lei Xie. 2024. Freev: Free lunch for vocoders through pseudo inversed mel filter. *Preprint*, arXiv:2406.08196.

Teresa L McCarty. 2018. Community-based language planning: Perspectives from indigenous language revitalization. In *The Routledge handbook of language revitalization*, pages 22–35. Routledge.

Shivam Mehta, Ruibo Tu, Jonas Beskow, Éva Székely, and Gustav Eje Henter. 2024. Matcha-tts: A fast tts architecture with conditional flow matching. In *ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 11341–11345. IEEE.

Koichi Miyazaki, Yoshiki Masuyama, and Masato Murata. 2024. Exploring the capability of mamba in speech applications. In *Interspeech 2024*, pages 237–241.

Tan Dat Nguyen, Ji-Hoon Kim, Youngjoon Jang, Jaehun Kim, and Joon Son Chung. 2024. Fregrad: Lightweight and fast frequency-aware diffusion vocoder. In *ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 10736–10740. IEEE.

Kari Noe and Nurit Kirshenbaum. 2024. Where generalized equitable design practice meet specific indigenous communities. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, pages 1–8.

Richard T Oster, Angela Grier, Rick Lightning, Maria J Mayan, and Ellen L Toth. 2014. Cultural continuity, traditional indigenous language, and diabetes in alberta first nations: a mixed methods study. *International journal for equity in health*, 13:1–11.

Aidan Pine, Erica Cooper, David Guzmán, Eric Joanis, Anna Kazantseva, Ross Krekoski, Roland Kuhn, Samuel Larkin, Patrick Littell, Delaney Lothian, Akwiratékha Martin, Koren Richmond, Marc Tessier,

Cassia Valentini-Botinhao, Dan Wells, and Junichi Yamagishi. 2024. Speech generation for indigenous language education. *Computer Speech Language*.

Aidan Pine, Dan Wells, Nathan Brinklow, Patrick Littell, and Korin Richmond. 2022. Requirements and motivations of low-resource speech synthesis for language revitalization. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7346–7359, Dublin, Ireland. Association for Computational Linguistics.

Henry Robertson. 2023. 2021 Census of population: Aboriginal peoples. Government of Canada.

Hubert Siuzdak. 2024. Vocos: Closing the gap between time-domain and fourier-based neural vocoders for high-quality audio synthesis. In *The Twelfth International Conference on Learning Representations*.

Jeremy Zehr and Florian Schwarz. 2018. Penncontroller for internet based experiments (ibex).

Xiangyu Zhang, Qiquan Zhang, Hexin Liu, Tianyi Xiao, Xinyuan Qian, Beena Ahmed, Eliathamby Ambikairajah, Haizhou Li, and Julien Epps. 2024. Mamba in speech: Towards an alternative to self-attention. *arXiv preprint arXiv:2405.12609*.

A Training details

For the purpose of replication, all training details are provided in Table 4.

B Benchmarking efficiency

Throughput We measured the throughput of each multilingual model with different data types (bfloat16, float16, and float32). Results are shown in Figure 1. It can be seen that the Mamba2 model yields the highest throughput in half-precision, while Attention has the highest throughput in full-precision. FNet has slightly lower throughput than Attention, which we believe is because there is limited optimization to the kernel of the FFT algorithm. Amongst all the models, Hydra has the lowest throughput in all precisions.

Peak Memory Usage We measured peak memory usage for both batched and one-by-one synthesis for all our models under using data types (float16, bfloat16 and float32). Results are shown in Table 5. It is seen that under all settings FNet is the most memory-efficient implementation as it is parameter-free. Hydra and Mamba2 have similar memory usage when performing one-by-one synthesis, but Hydra has slightly lower memory usage in batched synthesis. Attention has the

	Self-Attention	FNet	Mamba2	Hydra
Speaker embedding dimension	256	256	256	256
Language embedding dimension	192	192	192	192
Encoder hidden channels	640	640	640	640
Encoder filter channels	768	768	768	768
Encoder dropout rate	0.1	0.1	0.1	0.1
Decoder in channels	160	160	160	160
Decoder out channels	80	80	80	80
Decoder downsampling in channels	256	256	192	192
Decoder hidden dimension	256	256	192	192
Upsampling in channels	256	256	192	192
Decoder hidden blocks	2	2	2	2
Optimizer type	Adam	Adam	Adam	Adam
Learning rate	1.00e-06	1.00e-04	1.00e-04	1.00e-04
Scheduler	-	Cosine	Cosine	Cosine

Table 4: Training details, including dimensions and optimizer/scheduler information.

Figure 1: Throughput comparison between different models and data types. Evaluations are all performed on a single A100 GPU with a batch size of 400.

Figure 2: RTF comparison between different models and data types. Evaluations are all performed on a single A100 GPU.

highest memory usage among all models and consumed approximately twice the memory required by other implementations for batched synthesis.

C Additional results

We also provide objective evaluation results using `float16` and `bfloat16` data types in Tale 6. Compared to `float32`, performing in inference in `float16` and `bfloat16` data types do not bring perceptible degradation of speech quality.

Real Time Factor We also measured the real time factor (RTF) of each multilingual model with different data types. Results are shown in Figure 2. The FNet model is the fastest among all models in every setting, followed by the Attention model, Mamba2 model, and Hydra model.

D Vocoder comparison

We compared three representative vocoders for waveform generation, namely, a time-domain vocoder **HiFi-GAN** (Kong et al., 2020), a

frequency-domain vocoder **Vocos** (Siuzdak, 2024), and a diffusion-based vocoder **Fregrad** (Nguyen et al., 2024). For HiFi-GAN, we directly used the pretrained universal HiFi-GAN[1]. For both Vocos and Fregrad, we trained them on all training samples with the default parameters in their official implementation[2,3]. Objective results on test samples are shown in Table 7. Since Vocos leads over other models on most objective metrics and RTF. We finally chose Vocos as our vocoder in all evaluations of TTS models.

E Subjective evaluation

Each survey included 10 generated utterances from each of the five models and 10 utterances of natural speech. This resulted in 120 total utterances for the Ojibwe survey (60 from each speaker) and 60 for the Mi'kmaq and Maliseet models. The generated

[1] https://github.com/jik876/hifi-gan
[2] https://github.com/gemelo-ai/vocos
[3] https://github.com/kaistmm/fregrad

Data Type	Batch size	Self-Attention	FNet	Hydra	Mamba2
float16	400	3.75G	1.35G	1.45G	1.5G
bfloat16	400	3.75G	1.35G	1.45G	1.5G
float32	400	4.6G	2.3G	2.4G	2.5G
float16	1	133M	112M	127M	127M
bfloat16	1	133M	112M	127M	127M
float32	1	245M	202M	235M	230M

Table 5: Peak memory usage during inference.

utterances were created with the text from utterances that had been withheld from model training. The study was deployed through PCIbex (Zehr and Schwarz, 2018) and consisted of a series of trials where a single utterance was played and participants could rate the naturalness of each sentence on a sliding scale. The data from this scale was recorded as an integer value between 1-99 with the bottom of the scale (1) labeled unnatural and the top of the scale (99) labeled natural. At the time of writing, we have only been able to recruit two participants for the evaluation of the Ojibwe language models, but plan to do more subjective evaluation in the future.

The participants rated speech samples by adjusting the naturalness, as shown in Fig 3. The specific instructions are given in the following textbox.

Instructions

1. A short audio clip will be played and you will be asked to rate how natural it sounds to you by toggling a sliding scale, the leftmost representing not natural at all, the rightmost representing very natural and the centre of the scale representing a neutral response

2. Focus on the sounds of the sentence, not the meaning.

3. There is no correct or incorrect answer, we are interested in how these audio clips sound to YOU

4. Rate each sentence on its own, regardless of how simple or complicated it seems

You will now move on to a practice trial where you can try rating a sample audio clip.

Figure 3: The MOS rating interface.

Model	F0 RMSE↓	LAS RMSE↓	MCD↓	PESQ↑	STOI↑	VUV F1↑	FID↓
Maliseet AT float16							
Monolingual Self-Attention	84.268	9.064	19.547	1.217	0.032	0.655	0.007
Multilingual Mamba2	77.949	8.572	19.143	1.191	0.035	0.728	0.006
Multilingual Hydra	79.559	8.396	**18.103**	**1.453**	0.032	0.735	0.005
Multilingual FNet	76.503	8.945	19.064	1.259	**0.036**	0.723	0.009
Multilingual Attention	**75.395**	**8.045**	18.166	1.344	0.035	**0.745**	**0.004**
Maliseet AT bfloat16							
Monolingual Self-Attention	78.399	8.575	19.155	1.188	0.035	0.727	0.006
Multilingual Mamba2	79.160	**8.419**	**18.101**	**1.505**	0.030	0.732	**0.005**
Multilingual Hydra	77.275	8.981	19.069	1.250	0.036	0.719	0.009
Multilingual FNet	**73.732**	8.082	18.184	1.346	**0.036**	**0.741**	0.006
Multilingual Attention	80.352	9.021	19.552	1.243	0.031	0.657	0.006
Mi'kmaq MJ float16							
Monolingual Self-Attention	139.765	7.820	22.069	1.139	0.039	0.641	**0.002**
Multilingual Mamba2	**138.344**	7.369	21.595	**1.248**	0.039	0.644	0.003
Multilingual Hydra	142.309	7.732	21.722	1.183	0.037	0.637	0.004
Multilingual FNet	139.886	**7.341**	**21.591**	1.167	0.035	**0.664**	0.004
Multilingual Attention	141.000	8.606	21.688	1.107	0.038	0.632	0.008
Mi'kmaq MJ bfloat16							
Monolingual Self-Attention	139.291	8.616	21.677	1.110	**0.039**	0.631	0.006
Multilingual Mamba2	140.011	7.795	22.045	1.164	0.039	0.634	0.004
Multilingual Hydra	138.170	**7.078**	21.688	**1.196**	0.037	0.653	0.007
Multilingual FNet	142.229	7.693	21.744	1.169	0.038	0.630	0.004
Multilingual Attention	**138.039**	7.310	**21.670**	1.161	0.037	**0.663**	0.003
Ojibwe NJ float16							
Monolingual Self-Attention	**79.762**	**6.202**	17.565	1.122	0.034	0.827	0.009
Multilingual Mamba2	89.746	6.319	17.523	1.113	0.031	0.822	**0.005**
Multilingual Hydra	86.628	6.675	18.035	1.136	0.029	0.831	0.006
Multilingual FNet	96.415	6.723	19.241	1.084	**0.038**	0.789	0.013
Multilingual Attention	87.666	6.463	**17.419**	**1.151**	0.034	**0.832**	0.006
Ojibwe NJ bfloat16							
Monolingual Self-Attention	**80.424**	**6.215**	17.439	1.116	0.034	0.830	0.008
Multilingual Mamba2	90.767	6.334	17.527	**1.117**	0.032	0.820	**0.006**
Multilingual Hydra	86.739	6.698	17.978	1.139	0.030	0.831	0.006
Multilingual FNet	96.239	6.732	19.261	1.089	**0.035**	0.793	0.013
Multilingual Attention	92.625	6.452	**17.427**	1.134	0.033	**0.838**	0.008
Ojibwe JJ float16							
Monolingual Self-Attention	57.697	5.270	22.044	1.248	**0.036**	0.842	0.004
Multilingual Mamba2	**56.191**	**4.812**	**18.348**	1.218	0.032	**0.844**	0.004
Multilingual Hydra	57.218	5.314	18.928	**1.277**	0.034	0.835	0.005
Multilingual FNet	58.915	5.720	19.522	1.167	0.032	0.823	0.006
Multilingual Attention	56.748	4.868	18.423	1.262	0.033	0.843	**0.004**
Ojibwe JJ bfloat16							
Ojibwe JJ	56.987	5.261	22.065	1.232	0.038	0.845	0.005
Multilingual Mamba2	56.120	**4.803**	18.441	1.233	0.036	0.844	0.004
Multilingual Hydra	57.142	5.150	18.860	**1.294**	**0.038**	0.842	**0.003**
Multilingual FNet	58.680	5.737	19.493	1.168	0.036	0.824	0.005
Multilingual Attention	**56.118**	4.853	**18.406**	1.242	0.037	**0.845**	0.004

Table 6: Objective evaluation results in `float16` and `bfloat16`.

Model	F0 RMSE↓	LAS RMSE↓	MCD↓	PESQ↑	STOI↑	VUV F1↑	RTF	Parameter
Maliseet AT								
Fregrad	10.537	6.431	11.754	2.449	0.791	0.916	0.179	1.78M
Hifi-GAN	8.122	6.610	5.475	2.431	**0.869**	0.907	0.053	13.92M
Vocos	**7.216**	**5.982**	**5.372**	**3.209**	0.835	**0.927**	0.025	7.82M
Mi'kmaq MJ								
Fregrad	9.239	6.986	5.011	2.427	0.908	0.919	0.177	1.78M
Hifi-GAN	**8.432**	6.280	**2.252**	3.092	**0.952**	0.929	0.050	13.92M
Vocos	9.136	**6.091**	3.149	**3.391**	0.911	**0.931**	0.026	7.82M
Ojibwe NJ								
Fregrad	8.728	7.437	13.315	2.501	0.904	0.949	0.425	1.78M
Hifi-GAN	8.157	6.947	**6.272**	2.675	**0.945**	0.944	0.062	13.92M
Vocos	**7.916**	**6.576**	6.786	**3.070**	0.925	**0.952**	0.038	7.82M
Ojibwe JJ								
Fregrad	5.544	6.957	12.797	2.520	0.903	0.968	0.265	1.78M
Hifi-GAN	6.167	6.536	5.062	2.516	**0.946**	0.963	0.056	13.92M
Vocos	**5.434**	**5.750**	**4.389**	**3.073**	0.917	**0.974**	0.027	7.82M

Table 7: Objective evaluation results among vocoder models.