FILTER-RECOVERY NETWORK FOR MULTI-SPEAKER AUDIO-VISUAL SPEECH SEPARATION

ABSTRACT

We aim at the audio-visual speech separation task. Given the facial information of each speaker, the goal is to separate the corresponding speech in the speech mixture. Existing works are designed for a controlled setting with a fixed number of speakers, mostly 2 or 3 speakers, which is not easily scalable in practical application. To deal with this, we focus on separating voices for a variable number of speakers with a single model, and build concrete mixture test sets for a fair comparison. There are two prominent issues in complex multi-speaker separation results: 1) There exists some noisy voice pieces belonging to other speakers; 2) Part of the target speech is missing. To deal with these, we propose a valid method BFRNet, including a basic audio-visual speech separator and a Filter-Recovery Network (FRNet). The FRNet filters the noisy speech and recovers the missing parts for the output of the basic separator. Our method achieves state-of-the-art results on audio-visual speech separation datasets. Besides, we apply the FRNet to other methods and achieve general performance improvements, which proves the effectiveness of the proposed FRNet.

1 INTRODUCTION

Audio-visual speech separation has wide applications, such as speech recognition (Radford et al.; Chan et al., 2015), assistive hearing technologies, and online video meetings. As human voices are usually mixed in public, it would be challenging to directly extract the information of interest from the raw and mixed audio-visual signal with multiple speakers. As a result, separating audio signals for each speaker could serve as an effective pre-processing block for further audio-visual signal analysis.

Audio-visual speech separation has made prominent progress along with the development of convolutional neural networks (Gogate et al., 2018; Makishima et al., 2021; Gao & Grauman, 2021) and transformers (Ramesh et al., 2021; Montesinos et al., 2022; Rahimi et al., 2022). However, previous works (Lee et al., 2021; Gao & Grauman, 2021; Montesinos et al., 2022) only focus on two-speaker speech separation. Although other researches (Ephrat et al., 2018; Afouras et al., 2018b; 2019) manage to separate voices under multi-speaker scenarios, (Ephrat et al., 2018) requires customized models for each kind of mixture distinctive in speaker numbers, and (Afouras et al., 2018b) mainly contributes to enhancing the voice of the target individual while ignoring others. Furthermore, (Afouras et al., 2019) makes use of pre-enrolled speaker embeddings to extract the corresponding speech, but still leaves a performance gap compared with unenrolled speakers. Therefore, it still remains a challenge that how to efficiently and effectively separate each speech in a multi-speaker situation. The difficulties mainly come from two aspects: the essential challenge of recovering individual speeches from a multi-speaker mixture, and the lack of a well-established benchmark for speech separation of multi-speaker scenario.

Through our explorations, most of the currently works show their superiority on two-speaker speech separation but yield disappointing results with more speakers (*e.g.*, 3, 4 or even 5 speakers). It exhibits a simple yet important fact that the complexity of speech separation strongly correlates with the number of speakers in the mixed audios. As shown in Fig. 1, the core problems for multi-speaker speech separation can be empirically summarized as two folds:

1) The **noisy parts** (red box in Figure 1) contain the components from other speakers within the separated audio and usually occur in complex scenarios. 2) Some **missing parts** (gray box in Figure 1) represent there are some target audio waves dropped by models. These two problems usually occur in complex conditions, reflecting that models cannot accurately separate audio signals under complex scenarios. As a result, there is still a long way to go toward solving audio-visual speech separation for multi-speaker conditions.

Figure 1: **Illustration of two critical issues in multi-speaker audio-visual speech separation.** The missing parts in separation results compared to ground truth speech are indicated by gray boxes, while the noisy parts are marked by red boxes.

To this end, we come up with an effective method, termed as BFRNet, to conquer the aforementioned challenges in multi-speaker audio-visual speech separation. As illustrated in Figure 2, the BFRNet comprises a basic audio-visual speech separator and a Filter-Recovery Network (FRNet). The FRNet aims at solving the two issues in the results of any identically structured basic separator. It is composed of two serial modules, *i.e.*, Filter and Recovery. Firstly, Filter module utilizes visual features of the target speaker to query corresponding audio signals from the coarse prediction and suppress components from other speakers. Then, the Recovery module uses the clean audio yielded by Filter module to query the missing components that belong to the target speaker from others' predictions. Essentially, FRNet aims to calibrate the coarsely separated audio predicted by off-the-shelf models (Gao & Grauman, 2021; Montesinos et al., 2022; Chuang et al., 2020). As a result, the noisy parts and missing parts are greatly reduced by our Filter-Recovery operation.

Furthermore, we have noticed that there is still one obstacle residing in evaluation of audio-visual speech separation. As we found that most of the works (Gao & Grauman, 2021; Montesinos et al., 2022) evaluate performance on unfixed numbers of samples generated by randomly mixing the audio signals during each inference, it sometimes leads to hard reproductions and unfair comparisons. Consequently, to unify the evaluation protocols, we create a comprehensive benchmark to verify the models' performance fairly. Specifically, for each type of mixture, we randomly sample test videos without replacement to make up the speech mixtures. The constructed fixed test sets serve for all experiments to ensure fairness and reproducibility of the results.

To sum up, our contribution can be summarized as follows:

- *First*, we propose a training paradigm to perform audio-visual speech separation under indefinite multi-speaker scenarios.
- *Second*, to address the observed problems, we design the Filter-Recovery Network to further improve the quality of multi-speaker speech separation.
- *Finally*, we define a well-established test benchmark for a fair comparison. The exhaustive experiments on this benchmark validate the effectiveness of the proposed method.

2 RELATED WORKS

Audio-Only Speech Separation. Using only audio modality for speech separation faces the problem of speaker agnosticism. Some works (Liu et al., 2019; Wang et al., 2018) utilize the speaker's voice embedding as the hint to isolate the target speech. Current methods mostly treat the audio-only speech separation as a label permutation problem. (Chen et al., 2017) cluster the similar speech to perform speech separation. (Luo et al., 2018) requires no priori information of speaker number. (Luo & Mesgarani, 2019) adopts a deep learning network consisting of a series of convolutional layers and trains the network with permutation invariant loss (PIT) (Yu et al., 2017).

Visual Sound Separation. There are various kinds of sound separation explored in the literature. One type focuses on music separation (Zhao et al., 2018; Gao & Grauman, 2019; Xu et al., 2019; Gan et al., 2020), where the diverse shape of musical instruments and the distinguished patterns of music sounds are the key clues for music separation. Other works concentrate on the in-the-wild sounds (Gao et al., 2018; Tzinis et al., 2020; Chen et al., 2020), such as animal sounds, vehicle sounds, etc. (Gao et al., 2018) incorporate the image recognition results as the advisor and learn prototypical spectral patterns for each sounding object. (Tzinis et al., 2020) extend to unsupervised, open-domain audio-visual sound separation and develop a large new dataset. (Chen et al., 2020) propose an algorithm to generate temporally synchronized sound given mismatched visual information.

Visual Speech Separation. Speech, the audio most closely associated with humans, is extensively studied and has a broad range of applications. Due to the natural correlation between face and speech, many works (Gabbay et al., 2018; Lu et al., 2018; Ephrat et al., 2018; Afouras et al., 2019; Chung et al., 2020; Hegde et al., 2021; Rahimi et al., 2022) employ face-related information to separate speech from a mixture in the literature. (Chung et al., 2020) use only the still images containing facial appearance to isolate speech, with the assistance of the consistency of face identity and speech identity. Numerous methods (Afouras et al., 2018b; Gao & Grauman, 2021; Ephrat et al., 2018) explore the simultaneous lip motions and voice fluctuations clues. (Lu et al., 2018) integrate optical flow and lip movements to predict the spectrogram masks. (Hegde et al., 2021) propose synthesizing a virtual visual stream to deal with the situation where the visual stream is unreliable or completely absent. Another family of works (Owens & Efros, 2018; Afouras et al., 2020; Truong et al., 2021) combines multiple tasks for joint learning.

The most relevant works to ours are (Afouras et al., 2018b), (Shi et al., 2020), and (Yao et al., 2022). (Afouras et al., 2018b) also pays attention to the uncontrolled environment with several speakers, but it only focuses on enhancing the target speech and suppressing the noisy voices. Our method further separates every speech component for different mixtures in a single model. (Shi et al., 2020) and (Yao et al., 2022) perform a coarse-to-fine procedure by adopting an additional refining separation phase. However, the refining phase applies the same model as the coarse phase. Thus if the coarse phase cannot achieve a clean separation, the refining results will likewise be sub-optimal.

3 METHOD

We are the first to pay attention to audio-visual speech separation in a multi-speaker environment, where there are various numbers of speakers in speech mixtures during training. In this section, we first elaborate on the details of the proposed multi-speaker training setting in Sec. 3.1; Next, we introduce the adopted basic audio-visual speech separator in Sec. 3.2, which takes the visual information and the speech mixture as input and outputs isolated speech; Then we expand upon the Filter-Recovery Network in Sec. 3.3; Finally, we formulate the objective function for training model in Sec. 3.4.

3.1 OVERVIEW

Given a video containing S simultaneous speakers, our goal is to isolate the individual speech for each speaker. Formally, we denote time-domain speech mixture as $x = \sum_{i=1}^{S} x_i, x_i \in \mathbb{R}^{T_x}$, where T_x represents the time length, and x_i is the separate speech of the i-th speaker. Since acquiring the exact individual ground truth data from the mixtures in real scenes is yet impossible, we follow previous works (Afouras et al., 2018b; Gao & Grauman, 2021) to synthesize mixtures by adding individual speeches together.

Current works are designed for definite speakers in the mixture, mostly 2 or 3 speakers. However, these models present poor effects for practical applications, where there are usually a variable number of speakers. Alternatively, they take an inefficient strategy of training separate models for each kind of mixture different in speaker numbers. To meet the demand for practical applications, we create different mixtures with various numbers of speakers during training, i.e., S ranges from 2 to 5. The network is required to isolate each speech component for all kinds of mixtures.

Fig. 2 illustrates the architecture of the proposed model, consisting of a basic audio-visual speech separator and an additional Filter-Recovery Network (FRNet). During training, we feed mixtures

Figure 2: **Overview of the proposed framework.** It consists of a basic audio-visual speech separator and a Filter-Recovery Network (FRNet). To separate each speech from mixture containing S pieces of speeches, the basic separator takes the visual information and the spectrogram of speech mixture as input. It outputs visual feature V_i and speech mask M_i of the input spectrogram for i-th speaker. Then the visual features and speech masks of S speakers are fed into the Filter-Recovery Network to obtain a more precise speech mask $\tilde{M}_i$ for each speaker. The Filter Net utilizes visual embedding V_i to reduce the noisy components contained in M_i to obtain $\hat{M}_i$. Then the Recovery Net takes the clean mask $\hat{M}_i$ as the query to extract the corresponding missing parts from the speech masks of other speakers. To better illustrate the effect of the FRNet, we visualize masks into the form of waveforms by $\rightarrow$ to present speech components. The red/gray boxes and the corresponding $--\rightarrow$ represent the noisy/missing speech pieces that are removed or retrieved.

into the audio-visual speech separator and obtain the separated coarse speeches. The model takes the time-frequency spectrogram $X \in \mathbb{R}^{2 \times F \times T_X}$ as input, which is converted from time-domain audio x via Short-Time Fourier Transform (STFT). F and T_X respectively indicate the spectrogram's maximum frequency and time span. Each time-frequency bin contains the real and imaginary parts of the complex spectrogram. For i-th speaker, the model outputs target mask $M_i \in \mathbb{R}^{2 \times F \times T_X}$ of input spectrogram X and visual feature V_i.

Afterward, for each mixture, the separated S masks and visual features are sent to the FRNet to filter the noisy components and recover the missing ones. The FRNet outputs an improved mask for each speaker in the mixture, which is further adopted to restore the exact time-domain speech.

3.2 BASIC AUDIO-VISUAL SPEECH SEPARATOR

In our framework, the basic audio-visual speech separator can be replaced with any network which outputs the masks of the mixture spectrogram. Following (Gao & Grauman, 2021), we adopt both lip and face clues to guide target speech separation. Specifically, a lip net is taken to dig out the consistency of lip motion and continuous pronunciation, and a face net is used to explore the relationship between speech and face attributes.

Lip Net. Following the previous structure (Ma et al., 2021; Gao & Grauman, 2021), we feed T_v consecutive frames of lip regions into a 3D convolutional layer followed by a ShuffleNet v2 (Ma et al., 2018) network to extract mouth features. A temporal convolutional network is further utilized to output the lip motion features $Lip_i \in \mathbb{R}^{C_l \times T_v}$ for i-th speaker.

Face Net. The Face Net aims at leveraging the correspondence between face attributes and speech. A ResNet-18 network takes a single face image as input, and outputs a face embedding for i-th speaker. We repeat the face embedding along the time dimension to obtain $Face_i \in \mathbb{R}^{C_f \times T_v}$.

Encoder-Decoder Separator. As for the speech analysis and separation end, we adopt a U-Net network consisting of an encoder, a fusion module, and a decoder. The encoder is composed of multiple convolutions and pooling layers. It takes the mixture spectrogram X as input and outputs an audio feature Au of dimension $C_a \times T_v$. Following (Xiong et al., 2022), we take an AV-Fusion module to learn vision-related audio representation to further extract the speech for given speaker. We first concatenate the lip feature Lip_i and face feature $Face_i$ together along the time dimension to get visual feature $V_i \in \mathbb{R}^{C_v \times T_v}$, then feed V_i and Au to AV-Fusion module to obtain an enhanced

feature. It is further delivered into the decoder to predict a mask M_i of input spectrogram for i-th speaker, which denotes the projection values of the prediction onto the mixture. Note that the values might be positive or negative, as the spectrograms have both positive and negative values.

3.3 FILTER AND RECOVERY NETWORK

Due to the high complexity of speech mixture with multiple speakers (especially above 3 speakers), the separated target speech remains two apparent issues: 1) There still exists voices from others; 2) The isolated speech is partially missing compared to the ground truth speech. To solve the two problems, we introduce the Filter-Recovery Network (FRNet), which takes the visual features and the separated speech masks as input, and outputs more precise target speech masks. For convenience, we concatenate the real and imaginary parts of M_i obtained by the basic separator to form dimension $2F \times T_X$ in advance, which we still denote M_i. Besides, to align the dimension, we transform V_i to V_i' of shape $2F \times T_X$ with a convolutional layer.

As Fig. 2 shows, the FRNet consists of a Filter phase and a Recovery phase. The former utilizes visual features to remove the noisy voices from the separated speech, and the latter learns the correlation between all separated speeches to extract the missing voices from others.

Since the attention mechanism (Vaswani et al., 2017) enhances some parts of the input data while declining other parts, it is natural for us to adopt attention as the component module. For the sake of fluent description, we define some operations here. Given three tensors $\mathbf{q} \in \mathbb{R}^{D_h \times N_q}$, $\mathbf{k}, \mathbf{v} \in \mathbb{R}^{D_h \times N_{kv}}$, we compute the weighted sum of $\mathbf{v}$:

$$[\mathbf{q}', \mathbf{k}', \mathbf{v}'] = [\mathbf{U}_q\mathbf{q}, \mathbf{U}_k\mathbf{k}, \mathbf{U}_v\mathbf{v}], \qquad \mathbf{U}_{q,k,v} \in \mathbb{R}^{D_h \times D_h}, \qquad (1)$$

$$W = \mathrm{softmax}\left((\mathbf{q}')^\top\mathbf{k}'/\sqrt{D_h}\right), \qquad W \in \mathbb{R}^{N_q \times N_{kv}}, \qquad (2)$$

$$\mathrm{Attn}(\mathbf{q}, \mathbf{k}, \mathbf{v}) = \mathbf{v}'W^\top, \qquad \mathrm{Attn} \in \mathbb{R}^{D_h \times N_q}. \qquad (3)$$

Filter Net. Due to the entanglement of speeches, the more speeches in the mixture, the poorer the separation results. Since the visual information is highly correlated with speech, we utilize each speaker's visual knowledge to reduce irrelevant voices in the separation results during the Filter phase. The Filter Net consists of L basic layers, each consisting of Attn and MLP modules, where the MLP block contains two fully-convolutional layers and a ReLU activation function.

For l-th layer, the model takes V_i' and M_i^l as input, and outputs M_i^{l+1}, where $M_i^0 = M_i$:

$$z^{l+1} = \mathrm{LN}\left(\mathrm{Attn}(V_i', M_i^l, M_i^l) + M_i^l\right), \qquad z^{l+1} \in \mathbb{R}^{2F \times T_X}, \qquad (4)$$

$$M_i^{l+1} = \mathrm{LN}\left(\mathrm{MLP}(z^{l+1}) + z^{l+1}\right), \qquad M_i^{l+1} \in \mathbb{R}^{2F \times T_X}. \qquad (5)$$

For i-th speaker, the Filter Net output mask $\hat{M}_i = M_i^L$ where the noise speech pieces are removed.

Recovery Net. Due to the uncertainty of speech patterns (a wide range of voice loudness, speed, and tone), there may be some missing parts in the separation. We design the Recovery Net to pull out the missing voice pieces $\bar{M}_i$ by learning the association between the clean speech mask $\hat{M}_i$ and coarse separation masks of other speakers. We define a rearrange operation by stacking $S-1$ masks:

$$\mathrm{temp} = [M_1; \cdots; M_{i-1}; M_{i+1}; \cdots; M_S], \quad \mathbf{M}_i \xleftarrow{\mathrm{reshape}} \mathrm{temp}, \quad \mathbf{M}_i \in \mathbb{R}^{T_X \times 2F \times (S-1)}, \quad (6)$$

where the $\xleftarrow{\mathrm{reshape}}$ operation rearranges the input tensor to the target dimension.

The Recovery Net consists of L basic layers, similar to the decoder of Transformer (Vaswani et al., 2017). Specifically, the output of layer $l+1$ can be conveyed by the following equations, where $q_i^0 = \hat{M}_i$:

$$\hat{q}_i^l = \mathrm{LN}(\mathrm{Attn}(q_i^l, q_i^l, q_i^l) + q_i^l), \qquad \bar{q}_i^l \xleftarrow{\mathrm{reshape}} \hat{q}_i^l, \qquad \hat{q}_i^l \in \mathbb{R}^{2F \times T_X}, \bar{q}_i^l \in \mathbb{R}^{T_X \times 2F \times 1}, \quad (7)$$

$$z^l[t] = \mathrm{LN}\left(\mathrm{Attn}\left(\bar{q}_i^l[t], \mathbf{M}_i[t], \mathbf{M}_i[t]\right) + \bar{q}_i^l[t]\right), \qquad z^l[t] \in \mathbb{R}^{2F \times 1}, \qquad (8)$$

$$\hat{z}^l[t] = \mathrm{LN}\left(\mathrm{MLP}(z^l[t]) + z^l[t]\right), \qquad \hat{z}^l[t] \in \mathbb{R}^{2F \times 1}, \qquad (9)$$

$$\hat{z}^l = [\hat{z}^l[0]; ...; \hat{z}^l[t]; ...; \hat{z}^l[T_X]], \quad q_i^{l+1} \xleftarrow{\mathrm{reshape}} \hat{z}^l, \quad \hat{z}^l \in \mathbb{R}^{T_X \times 2F \times 1}, q_i^{l+1} \in \mathbb{R}^{2F \times T_X}. \quad (10)$$

We hold the view that the speech separation issues analyzed above do not always manifest to the same degree at different time slots. As a result, in Equ. 8, the attention operations are performed separately for each time slice of tensor to recover missing parts. Finally, the missing components $\bar{M}_i$ can be obtained by applying a fully-convolutional layer on q_i^L, i.e., $\bar{M}_i = \text{FC}(q_i^L)$.

After obtaining the noise-filtered result $\hat{M}_i$ and the recovered missing part $\bar{M}_i$, we add them up to obtain the clean and complete separation target mask:

$$\tilde{M}_i = \hat{M}_i + \bar{M}_i. \tag{11}$$

3.4 LOSS FUNCTION

The output M_i of the basic audio-visual separator and $\tilde{M}_i$ of the FRNet both need to be optimized. We take the scale-invariant signal-to-noise ratio (SI-SNR) loss (Le Roux et al., 2019) as the loss function following (Pan et al., 2022). The predicted masks M_i and $\tilde{M}_i$ are separately multiplied by the mixture spectrogram X to get the separated spectrograms, which are finally transformed by inverse STFT to restore the time-domain speech y_i and $\tilde{y}_i$. Given any prediction $\hat{s}$ and ground truth s, the SI-SNR loss can be computed with the following formula:

$$\mathcal{L}_{SI\text{-}SNR}(\hat{s}, s) = -10 \log_{10}\left(\frac{\|\frac{\langle \hat{s}, s \rangle s}{\|s\|^2}\|^2}{\|\hat{s} - \frac{\langle \hat{s}, s \rangle s}{\|s\|^2}\|^2}\right). \tag{12}$$

We jointly optimize the basic separator and FRNet, and the overall training loss for k-th speaker is as follows:

$$\mathcal{L}_i = \lambda \mathcal{L}_{SI\text{-}SNR}(y_i, x_i) + (1 - \lambda)\mathcal{L}_{SI\text{-}SNR}(\tilde{y}_i, x_i), \tag{13}$$

where λ is the factor to control the ratio of the two losses. For a batch of mixtures containing a total number of N speakers, the training loss is the average of all speakers.

4 EXPERIMENTS

4.1 DATASETS

VoxCeleb2 (Chung et al., 2018). This dataset is organized with the identity labels, where there are 5994 speakers in the training set and another 118 speakers in the test set. It contains more than 1 million samples, each consisting of an utterance and synchronized face tracks. Following (Gao & Grauman, 2021), we hold out two videos for each speaker in the original training set and utilize the rest videos as our training set. For the remaining videos in the original training set, we randomly sample 7200 videos to build the seen test set. The speakers also appear in the training set, but the specific utterances do not. Our unseen test set consists of 7200 videos randomly chosen from the original test set. All of the rest videos in the VoxCeleb2 dataset form our validation set.

Lip Reading Sentences 2&3 (Afouras et al., 2018a;c). LRS2 and LRS3 datasets contain 144k and 151k video clips from TV programs. To evaluate the generalization of models, we only train them on the VoxCeleb2 dataset and test them on cross-domain LRS2 and LRS3 datasets without any fine-tuning. For each dataset, the test set consists of 1200 randomly selected videos from the original test set.

Test Benchmark. During the test, we thoroughly evaluate the models' performance on mixtures with various numbers of speakers, i.e., from mixtures with 2 speakers to 5 speakers. Meanwhile, to eliminate the uncertainty of results caused by testing on randomly created mixtures each time, we construct fixed test sets of mixtures and perform all experiments on these predetermined mixtures.

Table 1: **Numbers of videos and mixtures for four test sets.**

Test Dataset	# Videos	# 2-mix	# 3-mix	# 4-mix	# 5-mix
VoxCeleb2 unseen set	7200	3600	2400	1800	1440
VoxCeleb2 seen set	7200	3600	2400	1800	1440
LRS2	1200	600	400	300	240
LRS3	1200	600	400	300	240

For each dataset, we randomly mix the test videos to build 2-mix, 3-mix, 4-mix, and 5-mix test sets without any subjective considerations. Each video appears only once in each mixture set. To be more explicit, we list the number of videos and each kind of mixture for all test sets in Tab. 1.

4.2 IMPLEMENTATION DETAILS

Data Process. Following (Gao & Grauman, 2021), we randomly cut 2.55-second long clips from videos sampled at 25fps and the corresponding audios sampled at 16kHz as the training pairs. For all utterances that make up a mixture, we first normalize the energy of each one to the same, which roughly corresponds to the same loudness of each speech. Then we add up all normalized speeches to obtain the mixture. STFT is conducted on the mixture waveform using a Hann window length of 400, a hop size of 160, and an FFT window size of 512 to output the complex spectrogram of dimension $2 \times 257 \times 256$, which is taken as the input to the U-Net encoder. A randomly selected frame from the video is rescaled to 224×224 and sent to the face analysis network. The input to the lip reading network is 64 consecutive frames of cropped gray mouth regions of dimension 88×88. We adopt the official implementation of 2D face landmark detection (Bulat & Tzimiropoulos, 2017) to detect the mouth landmarks and crop the mouth regions.

Training Setting. To achieve great separation results for mixtures containing different numbers of speakers, we separate all types of mixtures into individual speeches simultaneously. In each batch, the ratio of 2-mix, 3-mix, 4-mix, and 5-mix numbers is set to 2:1:1:1, and the total number of speakers is 256. As for how to select utterances to create mixtures, some methods (Gao & Grauman, 2021; Rahimi et al., 2022) perform put-back random sampling. Such an approach results in some utterances being sampled multiple times while others are ignored, in which case the model might overfit some samples and underfit others. Instead, at the beginning of each training epoch, we shuffle all samples randomly and pick them one by one to ensure no duplication or omission.

Optimization. Empirically, we adopt the Adam optimizer to train the network with a weight decay of 1e-4 and a learning rate of 1e-4. We train the models for 19 epochs, and drop the learning rate by a factor of 0.1 after epochs 12 and 15. The loss gradually reaches a plain after 19 epochs. λ in Equ. 13 is set to 0.5 to balance the training loss.

Evaluation. Following previous methods (Afouras et al., 2018b; Ephrat et al., 2018; Gao & Grauman, 2021; Rahimi et al., 2022), we adopt the standard blind source separation metric Signal-to-Distortion-Ratio (SDR) (Vincent et al., 2006), which measures the ratio between the energy of the target signal and that of the errors. To further assess the speech quality and intelligibility, we also employ the Perceptual Evaluation of Speech Quality (PESQ) (Rix et al., 2001) metric.

4.3 COMPARISON WITH STATE-OF-THE-ART METHODS

Tab. 2 and 3 compare our method to other open-source state-of-the-art models on the test sets. All experiments follow the same test and evaluation protocols. We choose two types of methods for comparison: audio-only methods and audio-visual methods.

Audio-Only Methods:

U-Net-AO. By removing the face net and the lip net from the adopted basic audio-visual speech separator and making corresponding adaptations for the U-Net, we obtain an audio-only speech separator and train it with permutation invariant loss (PIT).

VoiceFilter (Wang et al., 2018). This method takes the speech mixture and a reference utterance as input to extract the target speech from the mixture. Note that the reference audio is a piece of a randomly sampled utterance of the target speaker different from the target speech.

Conv-TasNet (Luo & Mesgarani, 2019). This method is widely adopted in audio-only speech separation practices. It adopts a fully-convolutional audio separation network, which takes the time-domain speech mixture as input and outputs all speech components simultaneously.

Audio-Visual Methods:

LAVSE (Chuang et al., 2020). To reduce processing costs, this work employs a lightweight but efficient framework, where a lip encoder extracts the lip motion feature as the synchronization signal for target speech extraction.

VisualVoice (Gao & Grauman, 2021). The method contains the same visual networks and U-Net as our basic audio-visual separator, except the U-Net simply concatenates the audio and visual features together instead of AV-Fusion. Besides, it contains an additional vocal analysis network. Since two

Table 2: **Results on VoxCeleb2 dataset.** The metrics are the average of all speakers for each test set. All methods are trained in the proposed multi-speaker setting. BFRNet achieves the best performance among all methods for all types of mixtures. (e.g., we achieve **11.06** dB SDR on VoxCeleb2 unseen 2-mix set.) Besides, we list the overall (O.A.) performance of all methods for convenient comparison, which is the average performance of each speaker in all kinds of mixtures. It is worth mentioning that each audio-visual method combined with the FRNet results in a large improvement.

Method	Unseen										Seen									
# Spk.	SDR (dB)					PESQ					SDR (dB)					PESQ				
	2	3	4	5	O.A.	2	3	4	5	O.A.	2	3	4	5	O.A.	2	3	4	5	O.A.
Audio-Only																				
U-Net-AO	0.06	-2.93	-4.66	-5.87	-3.35	1.55	1.15	0.98	0.89	1.14	0.06	-2.92	-4.65	-5.87	-3.34	1.59	1.17	1.01	0.94	1.18
VoiceFilter	7.07	4.21	1.98	-0.57	3.17	2.39	2.08	1.87	1.22	1.89	7.56	4.53	2.12	0.13	3.59	2.54	2.27	1.99	1.53	2.08
Conv-TasNet	9.46	4.57	1.50	-0.62	3.73	2.67	2.11	1.78	1.66	2.05	9.88	4.76	1.54	-0.65	3.88	2.70	2.13	1.79	1.66	2.07
Audio-Visual																				
LAVSE	5.38	1.53	-0.6	-2.13	1.05	2.17	1.67	1.43	1.28	1.64	5.54	1.45	-0.72	-2.31	0.99	2.20	1.67	1.43	1.28	1.64
LAVSE + FRNet	8.35	4.52	2.06	0.25	3.8	2.57	2.06	1.76	1.56	1.99	8.61	4.56	1.97	0.05	3.8	2.59	2.06	1.75	1.54	1.98
VisualVoice	8.97	4.59	2.05	0.25	3.96	2.64	2.12	1.82	1.62	2.05	8.61	3.96	1.39	-0.4	3.39	2.61	2.05	1.74	1.54	1.98
VisualVoice + FRNet	10.64	7.01	4.61	2.76	6.25	2.84	2.43	2.15	1.92	2.34	10.8	6.91	4.34	2.37	6.1	2.86	2.42	2.1	1.86	2.31
VoViT	9.62	5.08	2.06	-0.21	4.14	2.66	2.12	1.77	1.53	2.02	9.91	5.29	2.17	-0.11	4.31	2.69	2.15	1.80	1.54	2.04
VoViT + FRNet	10.63	6.69	3.78	1.37	5.62	2.75	2.28	1.93	1.65	2.15	10.95	6.93	3.93	1.48	5.82	2.78	2.31	1.95	1.67	2.18
DeBaSe	10.08	5.91	3.16	1.06	5.05	2.72	2.23	1.90	1.65	2.12	10.05	5.44	2.51	0.28	4.57	2.72	2.17	1.82	1.56	2.07
BFRNet (ours)	11.06	7.48	5.13	3.26	6.73	2.87	2.48	2.20	1.97	2.38	11.27	7.48	4.89	2.86	6.63	2.89	2.47	2.16	1.91	2.36

Table 3: **Results on LRS 2&3 datasets.** To validate the generalization of separation models, they are trained on VoxCeleb2 and validated on LRS2/LRS3 without fine-tuning. BFRNet outperforms all base methods that do not integrate FRNet. Although some methods combined with FRNet achieve the best performance in certain metrics, it still proves the effectiveness of FRNet. Similarly, we give the overall (O.A.) performance on all kinds of mixtures for each test set for direct comparison.

Method	LRS2										LRS3									
# Spk.	SDR(dB)					PESQ					SDR(dB)					PESQ				
	2	3	4	5	O.A.	2	3	4	5	O.A.	2	3	4	5	O.A.	2	3	4	5	O.A.
Audio-Only																				
U-Net-AO	0.25	-2.65	-4.26	-5.37	-3.01	1.51	1.14	0.97	0.90	1.13	0.19	-2.70	-4.34	-5.45	-3.08	1.40	1.03	0.85	0.76	1.01
VoiceFilter	6.98	4.10	1.78	-0.77	3.02	2.35	2.01	1.69	1.17	1.80	8.02	4.58	2.95	-0.31	3.81	2.48	2.08	1.86	1.26	1.92
Conv-TasNet	9.26	4.16	1.13	-1.10	3.36	2.48	1.88	1.51	1.30	1.79	10.35	4.68	3.45	-0.58	4.48	2.64	1.98	1.79	1.38	1.95
Audio-Visual																				
LAVSE	5.74	1.68	-0.54	-2.16	1.18	2.04	1.54	1.30	1.17	1.51	6.10	1.80	-0.39	-1.96	1.39	2.05	1.50	1.26	1.10	1.48
LAVSE + FRNet	8.72	4.46	1.74	-0.38	3.64	2.45	1.88	1.56	1.34	1.81	9.42	5.03	2.15	0.18	4.19	2.52	1.92	1.57	1.35	1.84
VisualVoice	10.31	5.55	2.62	0.56	4.76	2.61	2.04	1.68	1.47	1.95	11.21	6.09	3.20	1.04	5.38	2.72	2.09	1.73	1.47	2.00
VisualVoice + FRNet	11.52	7.78	4.95	2.80	6.76	2.78	2.34	1.99	1.72	2.21	12.51	8.47	5.73	3.50	7.55	2.92	2.45	2.10	1.79	2.32
VoViT	10.03	4.66	1.15	-1.48	3.59	2.56	1.94	1.55	1.29	1.84	10.64	5.37	1.41	-0.88	4.14	2.64	1.97	1.51	1.26	1.84
VoViT + FRNet	11.19	6.43	2.75	-0.18	5.05	2.67	2.11	1.67	1.39	1.96	11.90	7.08	3.34	0.67	5.75	2.75	2.16	1.70	1.39	2.00
DeBaSe	9.95	4.62	1.09	-1.10	3.64	2.54	1.91	1.50	1.25	1.8	11.25	5.80	2.55	-0.22	4.85	2.69	2.04	1.63	1.30	1.92
BFRNet (ours)	11.68	7.37	4.15	1.86	6.26	2.78	2.28	1.86	1.58	2.12	12.74	8.37	5.38	2.80	7.32	2.92	2.42	2.03	1.69	2.26

loss functions built on the vocal analysis network in this method are designed for only 2-mix separation, we remove the vocal analysis network for adaptation to our multi-speaker speech separation.

VoViT (Montesinos et al., 2022). The newly proposed method uses a landmark-based graph convolutional network (Yan et al., 2018) to capture the facial motion cues. It adopts an AV spectro-temporal transformer for target speech separation.

DeBaSe. In order to offset the impact of the increased model capacity brought by the additional FRNet, we compare the results of a deeper basic audio-visual speech separator (DeBaSe), which has more layers in the encoder and has almost the same parameter counts as BFRNet.

Besides, we combine all audio-visual methods apart from DeBaSe with the proposed FRNet to verify its generality. We call these methods '*+FR'.

As seen in Tab. 2, Tab. 3 and Fig. 3, BFRNet achieves the best results in all test sets compared to other baseline methods with at least 1 dB SDR advantage. Besides, the FRNet combined with any audio-visual method can significantly improve performance. For instance, VisualVoice (Gao & Grauman, 2021) combined with FRNet receives a 1.67 dB gain of SDR on the VoxCeleb2 unseen 2-mix test set. It is worth noting that there is still a large gap between DeBaSe and BFRNet, although their parameter amounts are nearly equal. That means only expanding the model capacity does not necessarily lead to significant performance gain. In contrast, BFRNet focuses on the main issues of the separation task, thus greatly enhancing the separation results. The difficulty of separation grows with the increase of speaker number in the mixture, resulting in lower metrics. For the VoxCeleb2 dataset, although the speakers in the seen test set appear in the training set, the results of the seen set are not certainly higher than that of the unseen set. This might be attributed to the speakers' voiceprint features not being very critical for speech separation.

Figure 3: **Visualization of SDR for each method on VoxCeleb2 unseen test set.** The increments on bars denote the improvement after combining FRNet with base methods. 'BaSe' is our basic audio-visual separator.

4.4 ABLATION STUDIES

We conduct ablation studies and report average results on VoxCeleb2 unseen and seen test sets.

The effect of visual knowledge. We remove the Face Net and Lip Net respectively while remaining other parts. Tab. 4 shows that modified models consistently yield lower results than BFRNet. However, as lip motion is more related to speech, it plays a principal role in speech separation, while the static face image only serves as extra information.

The effect of FRNet modules. To validate the necessity of each module, we conduct experiments in Tab. 5 that remove individual modules. When Filter net is removed, the Recovery net adopts M_i to replace $\hat{M}_i$. When Recovery net is removed, the output of Filter net $\hat{M}_i$ is considered as the final output.

Module design of FRNet. Tab. 6 explores deformed structures of FRNet. For Filter Net, we filter voice noise from M_i with itself as a clue instead of a simultaneous visual signal V_i. We name this ablation 'filter-sa'. As to Recovery Net, we replace the clean mask $\hat{M}_i$ with M_i as the clue to extract the missing voices from $\mathbf{M}_i$ and we name it 'recovery-noise'.

Table 4: **Experiments on effect of visual clues.**

Modules		SDR (dB)				PESQ			
Face Net	Lip Net	2	3	4	5	2	3	4	5
	✓	11.07	7.43	4.99	3.06	2.83	2.44	2.14	1.92
✓		8.25	4.40	1.28	-1.39	2.54	1.90	1.53	1.31
✓	✓	11.17	7.48	5.01	3.06	2.88	2.48	2.18	1.94

Table 5: **Ablation study on FRNet modules.**

Modules		SDR (dB)				PESQ			
Filter	Recovery	2	3	4	5	2	3	4	5
	✓	10.05	5.79	3.12	1.13	2.74	2.24	1.93	1.70
	✓	10.8	6.65	4.51	2.48	2.83	2.38	2.10	1.86
✓		10.3	6.30	3.75	1.81	2.85	2.37	2.05	1.82
✓	✓	11.17	7.48	5.01	3.06	2.88	2.48	2.18	1.94

Table 6: **Ablation study on module design.**

Exps	SDR (dB)				PESQ			
	2	3	4	5	2	3	4	5
Filter-sa	10.91	7.19	4.81	2.86	2.85	2.37	2.86	1.82
Recovery-noise	10.81	7.21	4.82	2.88	2.86	2.43	2.12	1.88
FR	11.17	7.48	5.01	3.06	2.88	2.48	2.18	1.94

Table 7: **Ablation study on the layers L.**

Layers	SDR (dB)				PESQ			
	2	3	4	5	2	3	4	5
1	10.88	7.17	4.69	2.74	2.83	2.41	2.10	1.86
2	11.17	7.48	5.01	3.06	2.88	2.48	2.18	1.94
3	11.20	7.52	5.17	3.31	2.88	2.50	2.18	1.95

Layers of the FRNet. Both the Filter and Recovery Nets are composed of L basic layers. We perform experiments on the number of L. As seen in Tab. 7, there is a great improvement for the network with $L = 2$ compared to $L = 1$. When the number of layers L increases to 3, the performance improvement is insignificant. To balance performance and efficiency, we adopt the 2-layer FRNet.

4.5 QUALITATIVE RESULTS

We visualize the intensity of spectrograms of ground truth (GT) and predictions by models in Fig 4. The first row presents the ground truth, the separation result of the basic separator, and the result of BFRNet, respectively. The second row shows the separation results of other approaches. The results demonstrate that the separation results of baseline methods are subject to the two issues we claim, including the results of the proposed method without the FRNet. We use black boxes to highlight the missing parts compared to GT, and red boxes to indicate the noisy parts from other speakers. As seen in Fig. 4, the two problems are greatly suppressed after utilizing FRNet.

Figure 4: **Spectrogram visualization of ground truth and predictions.**

5 CONCLUSION

In this paper, we concentrate on the multi-speaker audio-visual speech separation task. We are the first to propose separating mixtures with a variable number of speakers simultaneously during training, and we also provide a fixed test benchmark for a fair comparison. There are two significant problems for speech separation especially in the multi-speaker setting: part of the voice is missing in the separated speech; the separated speech may still be mixed with others' voices. To deal with this, we propose a Filter and Recovery network to solve these two problems. The filter module filters out other people's voices, and the recovery module compensates for their missing voices. We have conducted various experiments to demonstrate the effectiveness of this module, and its addition to other audio-visual speech separation methods has led to considerable improvements.

REFERENCES

Triantafyllos Afouras, Joon Son Chung, Andrew Senior, Oriol Vinyals, and Andrew Zisserman. Deep audio-visual speech recognition. *IEEE transactions on pattern analysis and machine intelligence*, 2018a.

Triantafyllos Afouras, Joon Son Chung, and Andrew Zisserman. The conversation: Deep audio-visual speech enhancement. *arXiv preprint arXiv:1804.04121*, 2018b.

Triantafyllos Afouras, Joon Son Chung, and Andrew Zisserman. Lrs3-ted: a large-scale dataset for visual speech recognition. *arXiv preprint arXiv:1809.00496*, 2018c.

Triantafyllos Afouras, Joon Son Chung, and Andrew Zisserman. My lips are concealed: Audio-visual speech enhancement through obstructions. *Proc. Interspeech 2019*, pp. 4295–4299, 2019.

Triantafyllos Afouras, Andrew Owens, Joon Son Chung, and Andrew Zisserman. Self-supervised learning of audio-visual objects from video. In *European Conference on Computer Vision*, pp. 208–224. Springer, 2020.

Adrian Bulat and Georgios Tzimiropoulos. How far are we from solving the 2d & 3d face alignment problem? (and a dataset of 230,000 3d facial landmarks). In *International Conference on Computer Vision*, 2017.

William Chan, Navdeep Jaitly, Quoc V Le, and Oriol Vinyals. Listen, attend and spell. *arXiv preprint arXiv:1508.01211*, 2015.

P Chen, Y Zhang, M Tan, H Xiao, D Huang, and C Gan. Generating visually aligned sound from videos. *IEEE Transactions on Image Processing: a Publication of the IEEE Signal Processing Society*, 2020.

Zhuo Chen, Yi Luo, and Nima Mesgarani. Deep attractor network for single-microphone speaker separation. In *2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 246–250. IEEE, 2017.

Shang-Yi Chuang, Yu Tsao, Chen-Chou Lo, and Hsin-Min Wang. Lite audio-visual speech enhancement. *arXiv preprint arXiv:2005.11769*, 2020.

Joon Son Chung, Arsha Nagrani, and Andrew Zisserman. Voxceleb2: Deep speaker recognition. *arXiv preprint arXiv:1806.05622*, 2018.

Soo-Whan Chung, Soyeon Choe, Joon Son Chung, and Hong-Goo Kang. Facefilter: Audio-visual speech separation using still images. *Proc. Interspeech 2020*, pp. 3481–3485, 2020.

Ariel Ephrat, Inbar Mosseri, Oran Lang, Tali Dekel, Kevin Wilson, Avinatan Hassidim, William T Freeman, and Michael Rubinstein. Looking to listen at the cocktail party: a speaker-independent audio-visual model for speech separation. *ACM Transactions on Graphics (TOG)*, 37(4):1–11, 2018.

Aviv Gabbay, Asaph Shamir, and Shmuel Peleg. Visual speech enhancement. *Proc. Interspeech 2018*, pp. 1170–1174, 2018.

Chuang Gan, Deng Huang, Hang Zhao, Joshua B Tenenbaum, and Antonio Torralba. Music gesture for visual sound separation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10478–10487, 2020.

Ruohan Gao and Kristen Grauman. Co-separating sounds of visual objects. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 3879–3888, 2019.

Ruohan Gao and Kristen Grauman. Visualvoice: Audio-visual speech separation with cross-modal consistency. In *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 15490–15500. IEEE, 2021.

Ruohan Gao, Rogerio Feris, and Kristen Grauman. Learning to separate object sounds by watching unlabeled video. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 35–53, 2018.

Mandar Gogate, Ahsan Adeel, Ricard Marxer, Jon Barker, and Amir Hussain. Dnn driven speaker independent audio-visual mask estimation for speech separation. *arXiv preprint arXiv:1808.00060*, 2018.

Sindhu B Hegde, KR Prajwal, Rudrabha Mukhopadhyay, Vinay P Namboodiri, and CV Jawahar. Visual speech enhancement without a real visual stream. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1926–1935, 2021.

Jonathan Le Roux, Scott Wisdom, Hakan Erdogan, and John R Hershey. Sdr–half-baked or well done? In *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 626–630. IEEE, 2019.

Jiyoung Lee, Soo-Whan Chung, Sunok Kim, Hong-Goo Kang, and Kwanghoon Sohn. Looking into your speech: Learning cross-modal affinity for audio-visual speech separation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1336–1345, 2021.

Shuo Liu, Gil Keren, and Björn Schuller. Single-channel speech separation with auxiliary speaker embeddings. *arXiv preprint arXiv:1906.09997*, 2019.

Rui Lu, Zhiyao Duan, and Changshui Zhang. Listen and look: Audio–visual matching assisted speech source separation. *IEEE Signal Processing Letters*, 25(9):1315–1319, 2018.

Yi Luo and Nima Mesgarani. Conv-tasnet: Surpassing ideal time–frequency magnitude masking for speech separation. *IEEE/ACM transactions on audio, speech, and language processing*, 27(8): 1256–1266, 2019.

Yi Luo, Zhuo Chen, and Nima Mesgarani. Speaker-independent speech separation with deep attractor network. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 26(4): 787–796, 2018.

Ningning Ma, Xiangyu Zhang, Hai-Tao Zheng, and Jian Sun. Shufflenet v2: Practical guidelines for efficient cnn architecture design. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 116–131, 2018.

Pingchuan Ma, Brais Martinez, Stavros Petridis, and Maja Pantic. Towards practical lipreading with distilled and efficient models. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 7608–7612. IEEE, 2021.

Naoki Makishima, Mana Ihori, Akihiko Takashima, Tomohiro Tanaka, Shota Orihashi, and Ryo Masumura. Audio-visual speech separation using cross-modal correspondence loss. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6673–6677. IEEE, 2021.

Juan F Montesinos, Venkatesh S Kadandale, and Gloria Haro. Vovit: Low latency graph-based audio-visual voice separation transformer. *arXiv preprint arXiv:2203.04099*, 2022.

Andrew Owens and Alexei A Efros. Audio-visual scene analysis with self-supervised multisensory features. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 631–648, 2018.

Zexu Pan, Ruijie Tao, Chenglin Xu, and Haizhou Li. Selective listening by synchronizing speech with lips. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 30:1650–1664, 2022.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. Robust speech recognition via large-scale weak supervision.

Akam Rahimi, Triantafyllos Afouras, and Andrew Zisserman. Reading to listen at the cocktail party: Multi-modal speech separation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10493–10502, 2022.

Karthik Ramesh, Chao Xing, Wupeng Wang, Dong Wang, and Xiao Chen. Vset: A multimodal transformer for visual speech enhancement. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6658–6662. IEEE, 2021.

Antony W Rix, John G Beerends, Michael P Hollier, and Andries P Hekstra. Perceptual evaluation of speech quality (pesq)-a new method for speech quality assessment of telephone networks and codecs. In *2001 IEEE international conference on acoustics, speech, and signal processing. Proceedings (Cat. No. 01CH37221)*, volume 2, pp. 749–752. IEEE, 2001.

Ziqiang Shi, Rujie Liu, and Jiqing Han. Lafurca: Iterative refined speech separation based on context-aware dual-path parallel bi-lstm. *arXiv preprint arXiv:2001.08998*, 2020.

Thanh-Dat Truong, Chi Nhan Duong, Hoang Anh Pham, Bhiksha Raj, Ngan Le, Khoa Luu, et al. The right to talk: An audio-visual transformer approach. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1105–1114, 2021.

Efthymios Tzinis, Scott Wisdom, Aren Jansen, Shawn Hershey, Tal Remez, Daniel PW Ellis, and John R Hershey. Into the wild with audioscope: Unsupervised audio-visual separation of on-screen sounds. *arXiv preprint arXiv:2011.01143*, 2020.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Emmanuel Vincent, Rémi Gribonval, and Cédric Févotte. Performance measurement in blind audio source separation. *IEEE transactions on audio, speech, and language processing*, 14(4):1462–1469, 2006.

Quan Wang, Hannah Muckenhirn, Kevin Wilson, Prashant Sridhar, Zelin Wu, John Hershey, Rif A Saurous, Ron J Weiss, Ye Jia, and Ignacio Lopez Moreno. Voicefilter: Targeted voice separation by speaker-conditioned spectrogram masking. *arXiv preprint arXiv:1810.04826*, 2018.

Junwen Xiong, Peng Zhang, Lei Xie, Wei Huang, Yufei Zha, and Yanning Zhang. Audio-visual speech separation based on joint feature representation with cross-modal attention. *arXiv preprint arXiv:2203.02655*, 2022.

Xudong Xu, Bo Dai, and Dahua Lin. Recursive visual sound separation using minus-plus net. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 882–891, 2019.

Sijie Yan, Yuanjun Xiong, and Dahua Lin. Spatial temporal graph convolutional networks for skeleton-based action recognition. In *Thirty-second AAAI conference on artificial intelligence*, 2018.

Zengwei Yao, Wenjie Pei, Fanglin Chen, Guangming Lu, and David Zhang. Stepwise-refining speech separation network via fine-grained encoding in high-order latent domain. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 30:378–393, 2022.

Dong Yu, Morten Kolbæk, Zheng-Hua Tan, and Jesper Jensen. Permutation invariant training of deep models for speaker-independent multi-talker speech separation. In *2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 241–245. IEEE, 2017.

Hang Zhao, Chuang Gan, Andrew Rouditchenko, Carl Vondrick, Josh McDermott, and Antonio Torralba. The sound of pixels. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 570–586, 2018.

A APPENDIX

We provide an additional ablation study and more visualization examples in appendix.

Ablation study on λ in loss function. We conduct experiments to explore the impact of different training λ in Eq. 13 on the results. A smaller λ means a higher training loss weight of FRNet. On the contrary, a larger λ implies a lower weight of FRNet in the whole model. Tab. 8 displays the average results

Table 8: **Ablation Study on λ.**

λ	SDR (dB)				PESQ			
	2	3	4	5	2	3	4	5
0.2	11.13	7.47	5.01	3.08	2.86	2.47	2.19	1.95
0.5	11.17	7.48	5.01	3.06	2.88	2.48	2.18	1.94
0.8	10.99	7.20	4.63	2.54	2.84	2.41	2.09	1.83

of VoxCeleb2 unseen and seen test sets. As seen in the table, attaching a higher weight to the training of FRNet (λ is 0.2) yields similar results to that of giving an equal weight (λ is 0.5). Nevertheless, a lower loss weight of FRNet (λ is 0.8) results in a non-negligible performance drop, which proves the necessity of FRNet.

Spectrogram visualization of BFRNet. We visualize the intensity of spectrograms of ground truth (GT) and predictions by each network of BFRNet in Fig. 5. The red boxes indicate the noisy part generated by basic separator and suppressed by Filter Net. The black boxes denote the missing part yielded by basic separator and recovered by Recovery Net. The results demonstrate the effects of Filter Net and Recovery Net respectively.

Figure 5: Visualization of the intensity of spectrogram: ground truth (GT) and outputs of BFRNet.