DOMAIN GENERALIZATION VIA HECKMAN-TYPE SELECTION MODELS

ABSTRACT

The domain generalization (DG) setup considers the problem where models are trained on data sampled from multiple domains and evaluated on test domains unseen during training. In this paper, we formulate DG as a sample selection problem where each domain is sampled from a common underlying population through non-random sampling probabilities that correlate with both the features and the outcome. Under this setting, the fundamental *iid* assumption of the empirical risk minimization (ERM) is violated, so it often performs worse on test domains whose non-random sampling probabilities differ from the domains in the training dataset. We propose a Selection-Guided DG (SGDG) framework to learn the selection probability of each domain and the joint distribution of the outcome and domain selection variables. The proposed SGDG is domain generalizable as it intends to minimize the risk under the population distribution. We theoretically proved that, under certain regular conditions, SGDG can achieve smaller risk than ERM. Furthermore, we present a class of parametric SGDG (HeckmanDG) estimators applicable to continuous, binary, and multinomial outcomes. We also demonstrated its efficacy empirically through simulations and experiments on a set of benchmark datasets comparing with other well-known DG methods.

1 INTRODUCTION

In statistical learning theory, the standard assumption behind many supervised learning algorithms is that both training and test instances are independently and identically distributed (*iid*) according to the same underlying data distribution (Vapnik, 1991). In other words, most statistical models assume that the training and test data are both random samples chosen randomly from the same population. Unfortunately, this assumption is often violated in real-world applications rendering model performance to deteriorate on out-of-distribution (OOD) test data (Koh et al., 2021). Recently, the Domain Generalization (DG) problem (Blanchard et al., 2011) has gained particular attention, where it is assumed that learning systems have access to training data sampled from multiple domains, and the ultimate goal is to extrapolate to new instances sampled from previously unseen test domains. For instance, it is hard to expect a learning algorithm for predicting whether a patient is diagnosed with cancer, trained on data obtained from the local hospitals in region A via a specific data collection protocol, to perform equally well on data collected at hospitals in region B, using different data-collection techniques. In this context, cancer patients are the underlying population of interest. Both the patient samples in hospital A and B are selected non-randomly from the population, and their selection probabilities most likely differ.

In this paper, we consider domain generalization as a non-random sample selection problem. The samples in each domain are not selected randomly from the true population, but rather under a selection probability, $P(S = 1)$, that is correlated with *both* the predictive features X and the outcome Y. A naively trained model, optimizing the prediction performance conditional on the selection mechanisms of the domains in the training data, will fail to perform similarly if sample selection of a testing domain is under a different selection mechanism.

In the statistical and machine learning literature, methods for DG often build on different assumptions regarding the source of distributional shift. The vast majority of methods rely on the covariate assumption (Bickel et al., 2009; Castro et al., 2020), where domains differ only in their marginal data distributions $P(X)$. Some make the concept shift assumption, where the conditional distribu-

tion $P(Y|X)$ differs across domains. Perhaps a more interesting and understudied case would be when we can make no assumptions on independence between Y and S (Koh et al., 2021), as the outcome is often correlated with sample selection. Most notably, Heckman (Heckman, 1979) proposed a bias correction approach to formulate the joint distribution of the outcome and the selection probability $P(Y, S|X)$, then use this probability to learn an unbiased model of the true population.

In this paper, we proposed a new class of Selection Guided Domain Generalization (SGDG) models to first estimate the probability that an instance is sampled into a training domain, and then use the joint distribution of the outcome Y and sample selection S to learn a domain generalizable model. The unique contributions of this paper are summarized as follows:

- To the best of our knowledge, we are the first paper to formulate the DG problem using a non-random sample selection framework, and to propose a Selection Guided Domain Generalization (SGDG) method under this framework.
- We present a class of parametric SGDG (HeckmanDG) estimators to jointly model the selection and outcome mechanisms, applicable to continuous, binary, and multinomial outcomes.
- We demonstrate the efficacy of our method both theoretically and empirically on simulated data and four challenging benchmarks.

2 RELATED WORK

Domain Generalization. DG has been studied under various contexts, where each proposing sophisticated learning objectives that leverage domain information to bypass spurious correlations (Sun & Saenko, 2016; Sagawa et al., 2019; Arjovsky et al., 2019; Shi et al., 2021; Arpit et al., 2021). A considerable body of research has been devoted to learning *domain-invariant features* which are discriminative of the task but at the same time independent of the domain. Such methods include but are not limited to kernel-based methods (Muandet et al., 2013), matching moments (Sun & Saenko, 2016), adversarial learning (Ganin et al., 2016; Deng et al., 2020), entropy regularization (Zhao et al., 2020), and contrastive learning (Motiian et al., 2017; Kim et al., 2021). Meanwhile, works inspired by *causality* exploit invariant causal effects across domains to avoid learning spurious correlations via learning feature representations on top of which a single optimal predictor exists (Arjovsky et al., 2019; Ahuja et al., 2020; Rosenfeld et al., 2020). Another family of *robust optimization* methods seek to iteratively minimize the worst-case error over an uncertainty set of data distributions constructed from the training domains (Sagawa et al., 2019; Xie et al., 2020; Krueger et al., 2021). More recently, another prominent direction of methods focus on *model averaging* throughout single or multiple training trajectories (Cha et al., 2021; Arpit et al., 2021). Other approaches include gradient matching (Shi et al., 2021) and meta learning-based methods (Li et al., 2018). The computer vision community has also presented a series of methods, especially based on data augmentation (Robey et al., 2021).

Sample Selection Bias Correction. Zadrozny (2004) formalized sample selection bias in machine learning terms and presented a bias correction method for the case where selection only depends on the input features. Cortes et al. (2008) proposed a sample reweighting approach to tackle the same problem, but assumes the additional availability of unlabeled data drawn the true population. Cortes & Mohri (2014) tackles domain adaptation and sample bias correction in regression. Sample reweighting approaches for robust prediction have also been considered, but not under the problem of domain generalization (Liu & Ziebart, 2014). Du & Wu (2021) proposed a framework for robust and fair learning under sample selection bias, but assumes conditional independence of Y and S given X. However, it is often the case that in real world domain generalization problems, the outcome is correlated with sample selection. To this end, our work considers the case where there is no conditional independence relationships between X, Y, and S.

3 SELECTION MODEL-GUIDED DOMAIN GENERALIZATION

3.1 DOMAIN GENERALIZATION

Suppose there exists L distinct but relevant *domains* and let $S = (S^1, \cdots, S^L) \sim \mathcal{P}_S$ denote a binary random vector that indicates the domain membership where $S^k = 1$ implies belonging to

domain k. Let $\mathcal{P}_{XY}$ represent the *population data distribution*, and each domain's data distribution be a conditional distribution of the population distribution given $S^k = 1$. i.e., $\mathcal{P}^k_{XY} = \mathcal{P}_{XY|S^k=1}$. We assume that if $S^k = 1$ then $S^j = 0$ for all $j \neq k$ so that an example can be observed in one and only one domain.

In the supervised domain generalization context, we are allowed to observe the joint distribution of X and Y, $\mathcal{P}^k_{XY}$ for K out of L domains, and refer the K domains as *source or training domains* observed during the training phase. The remaining $L-K$ domains are referred to as *target or testing domains* whom we may observe in the testing phase. Under this setting, we aim to learn a prediction model that generally performs well on both source and target domains. We formalize the problem as follows.

Definition 1 (Domain Generalization (Blanchard et al., 2011)). *Domain generalization refers to as the problem of learning $f : \mathcal{X} \to \mathcal{Y}$ that has the minimum expected loss across all possible domains, which can be further summarized as the following optimization problem:*

$$\min_{f \in \mathcal{F}} \sum_{k=1}^{L} \left\{ \mathbb{E}_{(X,Y) \sim \mathcal{P}^k_{XY}} \Big[\ell(f(X), Y) \Big] P(S^k = 1) \right\}, \tag{1}$$

where $\ell : \mathcal{Y} \times \mathcal{Y} \to \mathbb{R}_+ (= \{r \in \mathbb{R} : r \geq 0\})$ is a loss function and $\mathcal{F}$ is a hypothesis set. We note that some other papers have considered the same problem setting (Muandet et al., 2013; Deshmukh et al., 2019; Blanchard et al., 2021).

We first introduce a proposition that claims the equivalence of the domain generalization and the risk minimization under the population distribution:

Proposition 1 (Equivalence of Domain Generalization and Population Risk Minimization). *Problem (1) is equivalent to the risk minimization under the population distribution $\mathcal{P}_{XY}$. That is,*

$$\min_{f \in \mathcal{F}} \sum_{k=1}^{L} \left\{ \mathbb{E}_{(X,Y) \sim \mathcal{P}^k_{XY}} \Big[\ell(f(X), Y) \Big] P(S^k = 1) \right\} = \min_{f \in \mathcal{F}} \mathbb{E}_{(X,Y) \sim \mathcal{P}_{XY}} \Big[\ell(f(X), Y) \Big], \tag{2}$$

which straightforwardly follows from the law of total expectation. We define f_{PRM} as the minimizer of the population risk minimization problem, as well as the best (hypothetical) model for the domain generalization problem.

Proposition 1 is important as it establishes that the best model for the domain generalization problem should minimize the risk under the population distribution $\mathcal{P}_{XY}$. However, in practice we have no access to the population data distribution and are only given the source domains during model training. Therefore, one naive learning problem is minimizing the risk under the source domain data distribution:

Definition 2 (Source Domain Risk Minimization). *Given the source domains whose data distributions are $\mathcal{P}^k_{XY} = \mathcal{P}_{XY|S^k=1}$, for $k = 1, \cdots, K$, we refer to the following learning problem as the source domain risk minimization problem*

$$\min_{f \in \mathcal{F}} \sum_{k=1}^{K} \mathbb{E}_{(X,Y) \sim \mathcal{P}^k_{XY}} \Big[\ell(f(X), Y) \Big] P(S^k = 1). \tag{3}$$

We denote its minimizer as f_{SDRM}. The empirical form of f_{SDRM} is denoted as empirical risk minimization (ERM).

The generalization performance of f_{SDRM} depends on how well the source domains represent the population (or the target domains). If the source domains well approximate the population distribution, then the generalization performance of f_{SDRM} will be sufficiently close to that of f_{PRM}. On the other hand, if $\mathcal{P}^k_{XY} \neq \mathcal{P}_{XY}$, one cannot guarantee that models trained on the source domains to effectively generalize to the population. Therefore, it is necessary to model the selection probability to bridge the gap between $\mathcal{P}^k_{XY}$ and $\mathcal{P}_{XY}$.

3.2 SELECTION MODEL-GUIDED DOMAIN GENERALIZATION

Now we derive our selection model-guided domain generalization problem, starting from decomposing the objective function of the domain generalization problem by introducing a *domain selection*

model $\boldsymbol{g} = \{g_k : \mathcal{X} \to [0, 1], k = 1, \cdots, L\}$ which predicts selection probabilities of an example being observed in domain k. We assume that the loss function ℓ can be decomposed into two components - one exclusively about the selection model and the other involving both models:

$$\ell(f(X), Y) = \sum_{k=1}^{L} \Lambda(f(X), \boldsymbol{g}(X); Y, S^k = 1) + \sum_{k=1}^{L} \ell_s(\boldsymbol{g}(X), S^k = 1),$$

where $\ell_s : [0, 1]^L \times \{0, 1\}^L \to \mathbb{R}_+$ is the loss function for learning the domain selection models and $\Lambda : (\mathcal{Y} \times [0, 1]^L) \times (\mathcal{Y} \times \{0, 1\}^L) \to \mathbb{R}_+$ is the joint loss function, which assigns to the prediction and domain selection models a pair of true outcome Y and domain membership indicator S. For example, under the probabilistic framework, if we let $\ell(f(X), Y) = -\sum_{k=1}^{L}\{\log p(Y|X, S^k = 1) + \log p(S^k = 1|X)\}$, then $\Lambda = -\log p(Y|X, S^k = 1)$ and $\ell_s = -\log p(S^k = 1|X)$, respectively. We present a specific parametric form in Section 4.

Under the decomposition, the population risk can be expanded as follows:

$$\mathbb{E}_{(X,S,Y)\sim\mathcal{P}_{XSY}}[\ell(f(X), Y)] = \mathbb{E}_{(X,Y)\sim\mathcal{P}_{XY}^k}\left[\sum_{k=1}^{L}(\Lambda(f(X), \boldsymbol{g}(X); Y, S^k = 1) + \sum_{k=1}^{L}\ell_s(\boldsymbol{g}(X), S^k = 1))\right]P(S^k = 1)$$

$$= \sum_{k=1}^{K}\mathbb{E}_{(X,Y)\sim\mathcal{P}_{XY}^k}\left[\Lambda(f(X), \boldsymbol{g}(X); Y, S^k = 1)\right]P(S^k = 1) + \sum_{k=1}^{L}\mathbb{E}_{(X,S)\sim\mathcal{P}_X^k}\left[\ell_s(\boldsymbol{g}(X), S^k = 1)\right]P(S^k = 1)$$

$$+ \sum_{k=K+1}^{L}\mathbb{E}_{(X,Y)\sim\mathcal{P}_{XY}^k}\left[\Lambda(f(X), \boldsymbol{g}(X); Y, S^k = 1)\right]P(S^k = 1). \tag{4}$$

Based on the expansion, we introduce our selection model-guided domain generalization problem.

Definition 3 (Selection Model-Guided Domain Generalization (SGDG))**.** *Given access to the data distribution of K source domains, $\mathcal{P}_{XY}^k$ for $k = 1, \cdots, K$ and to the unlabeled data distribution from all L domains, $\mathcal{P}_{X|S^k=1}$ for $k = 1, \cdots, L$. We define the selection model-guided domain generalization problem as a joint learning problem of $f : \mathcal{X} \to \mathcal{Y}$ and $\boldsymbol{g} = \{g_k\}_{k=1}^{L}$,*

$$\min_{f\in\mathcal{F},\boldsymbol{g}\in\mathcal{G}} \sum_{k=1}^{K}\mathbb{E}_{(X,Y)\sim\mathcal{P}_{XY}^k}\left[\Lambda(f(X), \boldsymbol{g}(X); Y, S^k = 1)\right]P(S^k = 1) + \sum_{k=1}^{L}\mathbb{E}_{X\sim\mathcal{P}_X^k}\left[\ell_s(\boldsymbol{g}(X), S^k = 1)\right]P(S^k = 1), \tag{5}$$

where $\mathcal{F}$ and $\mathcal{G}$ are hypothesis sets.

The SGDG problem is a minimization of the expected loss of the prediction model f under the joint distribution of X and Y of the source domains, and the expected loss of the domain selection model $\boldsymbol{g}$ under the joint distribution of X and S. Under this formulation, the domain selection model $\boldsymbol{g}$ guides f to be *corrected* through Λ, considering the probability of being drawn from certain domains. In Section 4, we will introduce specific forms of this problem under parametric assumptions.

We note that SGDG partially minimizes the population risk (4) ignoring its last term. It is because, in DG settings, we have no access to the distribution of Y given $k = K + 1, \cdots, L$. Under the assumption that the true outcome model $f : \mathcal{X} \to \mathcal{Y}$ is the same for the source domains $k = 1, \cdots, K$, to the unobserved domains $k = K + 1, \cdots, L$, f_{SGDG} minimizes the population risk.

Even if the assumption does not hold, we can still prove the following theorem.

Theorem 1 (Performance Improvement of SGDG over SDRM)**.** *Let f_{SDRM} and f_{SGDG} be defined as in Definition 2 and 3. f_{SGDG} has lower risk than that of f_{SDRM}. That is,*

$$\mathbb{E}_{(X,Y)\sim\mathcal{P}_{XY}}[\ell(f_{\text{SGDG}}(X), Y)] \leq \mathbb{E}_{(X,Y)\sim\mathcal{P}_{XY}}[\ell(f_{\text{SDRM}}(X), Y)], \tag{6}$$

which implies SGDG is expected to show better generalization performance compared to SDRM. By Proposition 1, SGDG is expected to perform better than SDRM for the domain generalization problem equivalently. The sketch of proof of this theorem is that SGDG performs as well as SDRM on the source domains and offers performance improvement on the target domains. Proof of this theorem is given in Appendix A.1.

In reality, we may have no access to the distribution $\mathcal{P}_X^k$ for all domains ($k = 1, \cdots, L$) but only have access to the source domains' distributions ($k = 1, \cdots, K$). In such cases, we use $\mathcal{P}_X^k$ for $k = 1, \cdots, K$ as a surrogate, implying that we learn selection models by contrasting one domain to the remaining source domains. We empirically confirmed that even with this surrogate, SGDG outperforms the SDRM approach.

4 HECKMAN-TYPE SELECTION-GUIDED DOMAIN GENERALIZATION

In this chapter, we present parametric models for Λ embodying f_{SGDG} presented in the previous section. The essence of Λ is to model the conditional distribution of $P(Y|S = 1, X)$. Consider the setting where we are given training data from multiple source domains in the form of $\mathcal{D} = \{\boldsymbol{x}_i, \boldsymbol{s}_i, y_i\}_{i=1}^N$, where $\boldsymbol{s}_i = [s_{i1}, s_{i2}, \ldots, s_{ik}, \ldots, s_{iK}] \in \{0, 1\}^K$ is a binary vector indicating domain membership. By formulating the loss function as the negative log-likelihood, the empirical form of Equation 5 becomes

$$\min \; - \sum_{i=1}^N \sum_{k=1}^K \Big[s_{ik} \log p(y_i|s_{ik} = 1, \boldsymbol{x}_i) + s_{ik} \log p(s_{ik} = 1|\boldsymbol{x}_i) + (1 - s_{ik}) \log p(s_{ik} = 0|\boldsymbol{x}_i) \Big].$$

(7)

Heckman (1979) proposed to model the joint distribution $P(Y, \tilde{S}|X)$ of the selection latent variable $\tilde{S}$, where $S = \mathbb{I}[\tilde{S} > 0]$, and the continuous outcome Y via a bivariate normal distribution with a correlation coefficient ρ. The means of the bivariate normal distribution are assumed to be linear functions of X. Building upon his work, we use the latent continuous variable $\tilde{S}^k$ where $S^k = \mathbb{I}[\tilde{S}^k > 0]$ for each domain k. We then model the joint distribution $P(Y, \tilde{S}^k|X)$ of the selection latent variables and the continuous outcome Y via a multivariate normal distribution with a series of correlation coefficients $\{\rho_k\}_{k=1}^K$. The means of the multivariate normal distribution are assumed to be $f(X)$ and $g_k(X)$. We assume that $\{g_k\}_{k=1}^K$ are a set of independent probit models. This can be extended to binary and multinomial outcomes by assuming latent continuous variables underlying the observed outcomes. In all three cases, the joint log-likelihoods have closed forms. Henceforth, we refer to the specific parametric form of f_{SGDG} as the Heckman-type DG (HeckmanDG) estimator.

Definition 4 (Heckman-Type Domain Generalization Estimator). *We formulate HeckmanDG as a joint learning problem of f and $\boldsymbol{g} = \{g_k\}_{k=1}^K$ with the following learning objective:*

$$\min_{f, \boldsymbol{g}, \Sigma} \; \sum_{i=1}^N \sum_{k=1}^K \Big[s_{ik} \Lambda \left(f(\boldsymbol{x}_i), g_k(\boldsymbol{x}_i), y_i, s_{ik}; \Sigma \right) - \Big\{ s_{ik} \log \Phi(g_k(\boldsymbol{x}_i)) + (1 - s_{ik}) \log \Phi(-g_k(\boldsymbol{x}_i)) \Big\} \Big]$$

(8)

where $\Phi(\cdot)$ is the cumulative distribution function of the standard normal distribution ϕ, such that $\Phi(g_k(\boldsymbol{x}_i)) = P(S^k = 1|X = \boldsymbol{x}_i)$ is the selection probability w.r.t domain k, and $\Phi(-g_k(\boldsymbol{x}_i)) = P(S^k = 0|X = \boldsymbol{x}_i)$. Meanwhile, $\Lambda(f(\boldsymbol{x}_i), g_k(\boldsymbol{x}_i), y_i, s_{ik}; \Sigma)$ is the conditional negative log probability of y_i given $s_{ik} = 1$, i.e., $-\log p(y_i|s_{ik} = 1, \boldsymbol{x}_i)$.

The specific form of Λ and miscellaneous model parameters Σ depends on the prediction task (either continuous-valued, binary, or multinomial outcome prediction). For example, the objective function (8) for the continuous outcome is listed below in Equation 9, where we assume $Y = f(X) + \varepsilon$, $S^k = \mathbb{I}[g_k(X) + \eta_k > 0]$, and $[\eta_k, \varepsilon] \sim \mathcal{N}(0, [1, \sigma; \rho_k])$. The details of its derivation and for other types of outcomes can be found in Appendix A.2.

$$\min_{f, \boldsymbol{g}, \Sigma} \; - \sum_{i=1}^N \sum_{k=1}^K s_{ik} \left(\log \Phi \left(\rho_k \frac{y_i - f(\boldsymbol{x}_i)}{\sigma} + g_k(\boldsymbol{x}_i) \right) + \log \frac{\phi\left(\frac{y_i - f(\boldsymbol{x}_i)}{\sigma} \right)}{\sigma} \right) + (1 - s_{ik}) \log \Phi(-g_k(\boldsymbol{x}_i)).$$

(9)

Ultimately, $\hat{f}$ is the outcome prediction model of primary interest. For any input X from unseen domains, the HeckmanDG prediction is $\hat{f}(X)$.

The proposed HeckmanDG differentiates from Heckman's bias correction method in the following perspectives. *First*, it allows and models domain-specific sample selection mechanisms. *Second*, by utilizing the multiple domains in the training data, HeckmanDG does not need auxiliary data

Figure 1: Schematic overview of HeckmanDG, with K training domains. **Step 1)** We learn $g = \{\omega_{g,k} \circ \varphi_g\}_{k=1}^K$ to predict the selection probabilities for each training domain. **Step 2)** The estimated domain selection model $\hat{g}$ guides $f = \omega_f \circ \varphi_f$ to be corrected by considering the selection probability of instances being drawn from the training domains.

(features of examples from the target population but not sampled in the domain), which is a required input for the original Heckman model. *Third*, HeckmanDG alleviates the linear assumptions in Heckman's bias correction model to allow flexible forms for both prediction and selection functions including neural networks.

5 OPTIMIZATION

In this section, we consider the hypothesis sets $\mathcal{F}$ and $\mathcal{G}$ are neural networks, and present an efficient algorithm to optimize Equation 8. Specifically, we propose a two-step approach that primarily trains g to optimum (**Step 1**), then updates the remaining parameters of f and Σ (**Step 2**). In Step 1, we learn the selection model parameters based on the following objective function:

$$\hat{g} = \operatorname*{argmin}_{g} - \sum_{i=1}^{N} \sum_{k=1}^{K} \left[s_{ik} \log \Phi(g_k(\boldsymbol{x}_i)) + (1 - s_{ik}) \log \Phi(-g_k(\boldsymbol{x}_i)) \right] \tag{10}$$

which essentially learns to predict the source domain memberships for training instances. In Step 2, we freeze the selection model $\hat{g}$, and learn the remaining parameters of f and Σ. The proposed optimization algorithm is in part motivated by Heckman's two-step estimator for bias correction, which was devised as a means of avoiding the nonlinearity of estimating both selection and outcome equations simultaneously (Heckman, 1979). We provide pseudocode describing the overall optimization procedure in Algorithm 1 in Appendix A.3, and an ablation study in Section 7 to support the necessity of two-step optimization.

Neural Network Architecture. We use a common feature extractor $\varphi_g : \mathcal{X} \to \mathcal{Z}$ for the domain selection models $g = \{g_k\}_{k=1}^K$, which only differ in the last linear predictors $\omega_{g,k} : \mathcal{Z} \to [0,1]$, thus $g_k = \omega_{g,k} \circ \varphi_g$. We define $f = \omega_f \circ \varphi_f$, where $\varphi_f : \mathcal{X} \to \mathcal{Z}$ is the feature extractor of the outcome prediction model and $\omega_f : \mathcal{Z} \to \mathcal{Y}$ is the final linear predictor. An overview of our neural network architecture is provided in Figure 1.

6 EXPERIMENTS

6.1 SIMULATION

Model. We simulate a linear regression problem to assess HeckmanDG's predictive performance. We simulate two covariates (X_1, X_2) and two training domains $(K = 2)$, and the following setting of domain selection and outcome mechanisms:

$$S_k = \mathbb{I}[\alpha_0^k + \alpha_2^k X_2 + \eta_k > 0], \quad Y = 1 + 1.5X_1 + 3X_2 + \varepsilon$$

$$\begin{bmatrix} X_1 \\ X_2 \end{bmatrix} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}_2), \text{ and } \begin{bmatrix} \eta_k \\ \varepsilon \end{bmatrix} \sim \mathcal{N}\left(\begin{bmatrix} 0 \\ 0 \end{bmatrix}, \begin{bmatrix} 1 & \rho_k\sigma \\ \rho_k\sigma & \sigma^2 \end{bmatrix} \right) \tag{11}$$

Table 1: Predictive performance on simulated data, measured in terms of the mean squared error (*lower is better*) averaged over 30 trials. Standard deviations are given in parentheses.

	Train	ID	OOD	Random
ERM (oracle)	1.57 (0.46)	1.30 (0.49)	1.30 (0.40)	1.01 (0.04)
ERM	0.84 (0.09)	0.89 (0.12)	14.65 (6.00)	6.84 (1.83)
IRM	0.83 (0.09)	0.88 (0.11)	16.45 (6.40)	7.42 (1.86)
GroupDRO	0.91 (0.39)	0.88 (0.12)	15.83 (5.22)	7.33 (1.67)
VREx	0.85 (0.08)	0.89 (0.13)	14.47 (4.91)	6.96 (1.68)
HeckmanDG (ours)	1.40 (0.24)	1.37 (0.29)	**8.71** (3.96)	**3.70** (0.96)

where we assume a normal prior over the selection coefficient $\alpha_2^k \sim \mathcal{N}(\mu_{\alpha_2}, \sigma_{\alpha_2}^2)$ in order to implicitly control the similarity between domains by differing its parameters. We consider a true population of 100000 instances, from which we sample data for each domain with $n_k \sim \text{Uniform}(1000, 2000)$. In each trial, we sample the selection coefficient $\alpha_2^k \sim \mathcal{N}(5, 3^2)$ for the two training domains and a held-out in-distribution (ID) test set (similar to the training domains), and $\alpha_2^{k'} \sim \mathcal{N}(-5, 3^2)$ for another held-out out-of-distribution (OOD) test set (dissimilar to the training domains). We also simulate a random domain from the population. We assumed $\rho_k = 0.8$ and $\sigma = 1$.

Results. We observe that HeckmanDG not only outperforms ERM, but also other DG methods including IRM (Arjovsky et al., 2019), GroupDRO (Sagawa et al., 2019), and VREx (Krueger et al., 2021)(Table 1). Note that 'ERM (oracle)' is trained on *iid* training data, which serves as a theoretical lower bound on model performance. We highlight that not only does HeckmanDG performs well on the random test set, but also on the OOD test set. In contrast, other methods tend to fit well to the train domains (ID performance is high), but generalize poorly to random and OOD test domains.

6.2 BENCHMARKS

Datasets. To further demonstrate the effectiveness of HeckmanDG on high-dimensional data regimes, we conducted experiments on four datasets from the WILDS benchmark (Koh et al., 2021): 1) CAMELYON17, 2) POVERTYMAP, 3) iWILDCAM, and 4) RxRx1. We used the same neural network architecture for selection and outcome feature extractors φ_g and φ_f, which are followed by linear predictors ω_g and ω_f. For the domain selection model, we tuned hyperparameters to obtain the best domain selection model returning the highest macro F1 score on the training data, which in all cases achieve near-perfect accuracy. For the outcome prediction model, we adhered to the official guidelines and used the OOD validation set provided in the WILDS repository for hyperparameter tuning and model selection based on the recommended metrics. Detailed descriptions of dataset statistics are presented in Table 5 of Appendix A.3. Details on hyperparameters and model training are presented in Table 6 of Appendix A.3.

Results. We summarized the results on the WILDS benchmark in Tables 2,3, 4a, and 4b. All methods apply the same network architectures based on the WILDS guideline for fair comparison. Also, we point out that we exclude methods that deviate from the DG setting such as those centered on test time adaptation and using additional unlabeled data. We observed that HeckmanDG outperforms other methods on two out of four datasets, while performing on par with other methods on the remaining two. We make the following key observations. *First*, HeckmanDG often robustly performs on the test domain although it may not generate the best performance on the validation domains. For example, on the CAMELYON17 dataset, the performance gap between the validation and test datasets for HeckmanDG is 3.3, which is substantially smaller than 14.1 of 'ERM (scratch)' and 7.1 of 'ERM (ImageNet)'. This pattern is similar to what we observed in the simulation studies. Because HeckmanDG is designed to predict for the underlying population, it may not produce the best prediction performances for the (non-randomly selected) source domains. Although we do not know the specific selection probability of the test domain, HeckmanDG is often more robust for the testing domains by optimizing for the population distribution. *Second*, HeckmanDG effectively works for both the domain shift and the subpopulation shift problems. This can be observed by looking at either the average or worst-group performance on the POVERTYMAP dataset (i.e., 0.51). This

Table 2: CAMELYON17: We report predictive performance measured in terms of average accuracy on both the OOD validation and test set. Standard deviation across 10 replicates are given in parentheses. 'ERM (scratch)' is trained from random initial parameters, whereas we also report 'ERM (ImageNet)' trained from ImageNet-pretrained weights (Russakovsky et al., 2015).

Method	Validation	Test
ERM (scratch)	84.9 (3.1)	70.8 (7.2)
ERM (ImageNet)	**91.3** (0.2)	84.2 (1.7)
CORAL	86.2 (1.4)	59.5 (7.7)
IRM	86.2 (1.4)	64.2 (8.1)
GroupDRO	85.5 (2.4)	68.4 (7.3)
VREx	82.3 (1.3)	71.5 (8.3)
LISA	81.8 (1.3)	77.1 (6.5)
Fish	82.5 (1.2)	79.5 (6.0)
HeckmanDG (ours)	90.6 (2.4)	**87.3** (2.4)

Table 3: POVERTYMAP: We report predictive performance measured in terms of both the *average* and *worst-group* Pearson correlation coefficient, on both the OOD validation and test sets. Standard deviation across 5 replicates are given in parentheses. We use the original 5 folds provided in the WILDS repository. For 'Fish', we do not report worst-group performance since it has not been reported by the original authors (Shi et al., 2021).

Method	Average		Worst Group	
	Validation	Test	Validation	Test
ERM	0.80 (0.04)	0.78 (0.03)	0.51 (0.06)	0.45 (0.06)
CORAL	0.80 (0.04)	0.77 (0.05)	0.52 (0.06)	0.44 (0.06)
IRM	**0.81** (0.03)	0.77 (0.05)	**0.53** (0.05)	0.43 (0.07)
GroupDRO	0.78 (0.05)	0.75 (0.07)	0.46 (0.04)	0.39 (0.06)
DANN	0.77 (0.04)	0.69 (0.04)	0.44 (0.11)	0.33 (0.10)
Fish	**0.81** (0.01)	**0.81** (0.01)	-	-
HeckmanDG (ours)	**0.81** (0.03)	**0.81** (0.03)	**0.53** (0.06)	**0.51** (0.04)

Table 4: A summary of results on RXRX1 and IWILDCAM. Note that we do not report the OOD validation macro F1 score for DANN on the IWILDCAM dataset, since it has not been provided in its respective paper (Sagawa et al., 2021).

(a) RXRX1

Method	Validation	Test
ERM	19.4 (0.2)	29.9 (0.4)
CORAL	18.5 (0.4)	28.4 (0.3)
IRM	5.6 (0.4)	8.2 (1.1)
GroupDRO	15.2 (0.1)	23.0 (0.3)
LISA	20.1 (0.4)	31.9 (1.0)
Fish	7.5 (0.6)	10.1 (1.5)
HeckmanDG (ours)	**20.5** (0.7)	**32.1** (0.8)

(b) IWILDCAM

Method	Validation	Test
ERM	**37.4** (1.3)	31.0 (1.3)
CORAL	37.0 (1.2)	**32.8** (0.1)
IRM	20.2 (7.6)	15.1 (4.9)
GroupDRO	26.3 (0.2)	23.9 (2.1)
DANN[1]	-	31.9 (1.4)
Fish	25.8 (0.5)	24.2 (0.9)
HeckmanDG (ours)	34.5 (0.9)	31.8 (0.3)

again supports the robustness of HeckmanDG against a range of non-random selection probabilities of the testing domains.

7 ANALYSIS

Necessity of two-step optimization. Recall that in Section 5, we have proposed a two-step optimization algorithm to learn the domain selection and outcome prediction models sequentially. To

(a)   (b)   (c)

Figure 2: Analysis based on the POVERTYMAP dataset. 2a) Pearson correlation measured on the training data for HeckmanDG learned by *one-step* (gray) and *two-step* (blue, proposed) optimization. 2b) Comparison between *one-step* (gray) and *two-step* (blue, proposed) optimization, where performance is averaged across all five folds provided in the WILDS repository. 2c) Relationship between the performance of domain selection and outcome prediction (colors indicate different folds).

demonstrate the necessity and effectiveness of the proposed two-step optimization, we performed an ablation study on the POVERTYMAP dataset, which has 13 training domains. For comparison, we trained g and f in one-step to simultaneously minimize Equation 8. We kept the number of training epochs to 30 (with the same batch size) equivalent to make a valid comparison. We observed that both *one-step* and *two-step* optimization schemes were comparable on training domains (Figure 2a), but yield different test performance on the OOD domains (Figure 2b). Compared to the one-step performances, the two-step optimization improved predictive performance on both average ($0.78 \rightarrow 0.81$) and the worst-group ($0.43 \rightarrow 0.51$). We believe that poor prediction of domain selection probabilities by a suboptimal $\hat{g}$ may mislead $\hat{f}$ to a deficient solution.

Relationship between the performance of g and f. To further investigate how the performance of a domain selection model influences the final outcome prediction, we trained f with selection models with different macro F1 scores, and compared their performance in Figure 2c. Specifically, we take intermediate snapshots for $\hat{g}$ within a single training run to obtain selection models with varying performance, and learned f based on each snapshot. On all five data split folds, we always observed a positive correlation between the performances of $\hat{g}$ and $\hat{f}$, demonstrating that a well-performing selection model is necessary to correctly guide the outcome prediction model to generalize to the underlying population.

8 CONCLUSIONS

We propose a Selection Guided Domain Generalization (SGDG) framework, in which we formulate domain generalization as a non-random sample selection problem and propose to jointly learn the prediction model f and the domain selection model g to achieve generalization on the true population. DG is a challenging problem as the particular structure of the distribution shift in the testing domains is unknown. In the presence of this uncertainty, we propose and theoretically justify the objective of minimizing the risk targeting the population distribution through SGDG. Furthermore, we have provided a set of Heckman-type SGDG estimators for various outcome types under parametric assumptions. Although it is still an open question if a single general-purpose training algorithm can produce models that do well on all of the DG datasets (Koh et al., 2021), we observed robust performances of the proposed HeckmanDG on four benchmark datasets.

Note that SGDG can naturally utilize all domains in the training data, including the (outcome) labeled and unlabeled domains. The unlabeled domains will contribute to the estimation of $\hat{g}$ in Equation 8, which indirectly improves generalization performance as we showed in Section 7. An intriguing direction for future research is to explore whether we can improve SGDG performances by adapting $\hat{g}(X)$ for domains in the test data. In that way, we may further refine the prediction $\hat{f}(X)$ for the unseen domains guided by their similarities to the source domains.

REFERENCES

Kartik Ahuja, Karthikeyan Shanmugam, Kush Varshney, and Amit Dhurandhar. Invariant risk minimization games. In International Conference on Machine Learning, pp. 145–155. PMLR, 2020.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. arXiv preprint arXiv:1907.02893, 2019.

Devansh Arpit, Huan Wang, Yingbo Zhou, and Caiming Xiong. Ensemble of averages: Improving model selection and boosting performance in domain generalization. arXiv preprint arXiv:2110.10832, 2021.

Steffen Bickel, Michael Brückner, and Tobias Scheffer. Discriminative learning under covariate shift. Journal of Machine Learning Research, 10(9), 2009.

Gilles Blanchard, Gyemin Lee, and Clayton Scott. Generalizing from several related classification tasks to a new unlabeled sample. Advances in neural information processing systems, 24, 2011.

Gilles Blanchard, Aniket Anand Deshmukh, Ürun Dogan, Gyemin Lee, and Clayton Scott. Domain generalization by marginal transfer learning. The Journal of Machine Learning Research, 22(1): 46–100, 2021.

Daniel C Castro, Ian Walker, and Ben Glocker. Causality matters in medical imaging. Nature Communications, 11(1):1–10, 2020.

Junbum Cha, Sanghyuk Chun, Kyungjae Lee, Han-Cheol Cho, Seunghyun Park, Yunsung Lee, and Sungrae Park. Swad: Domain generalization by seeking flat minima. Advances in Neural Information Processing Systems, 34:22405–22418, 2021.

Corinna Cortes and Mehryar Mohri. Domain adaptation and sample bias correction theory and algorithm for regression. Theoretical Computer Science, 519:103–126, 2014.

Corinna Cortes, Mehryar Mohri, Michael Riley, and Afshin Rostamizadeh. Sample selection bias correction theory. In International conference on algorithmic learning theory, pp. 38–53. Springer, 2008.

Zhun Deng, Frances Ding, Cynthia Dwork, Rachel Hong, Giovanni Parmigiani, Prasad Patil, and Pragya Sur. Representation via representations: Domain generalization via adversarially learned invariant representations. arXiv preprint arXiv:2006.11478, 2020.

Aniket Anand Deshmukh, Yunwen Lei, Srinagesh Sharma, Urun Dogan, James W Cutler, and Clayton Scott. A generalization error bound for multi-class domain generalization. arXiv preprint arXiv:1905.10392, 2019.

Wei Du and Xintao Wu. Fair and robust classification under sample selection bias. In Proceedings of the 30th ACM International Conference on Information & Knowledge Management, pp. 2999–3003, 2021.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. The journal of machine learning research, 17(1):2096–2030, 2016.

Vassilis A Hajivassiliou and Paul A Ruud. Classical estimation methods for ldv models using simulation. Handbook of econometrics, 4:2383–2441, 1994.

James J Heckman. Sample selection bias as a specification error. Econometrica: Journal of the econometric society, pp. 153–161, 1979.

Daehee Kim, Youngjun Yoo, Seunghyun Park, Jinkyu Kim, and Jaekoo Lee. Selfreg: Self-supervised contrastive regularization for domain generalization. In Proceedings of the IEEE/CVF International Conference on Computer Vision, pp. 9619–9628, 2021.

Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanas Phillips, Irena Gao, et al. Wilds: A benchmark of in-the-wild distribution shifts. In International Conference on Machine Learning, pp. 5637–5664. PMLR, 2021.

David Krueger, Ethan Caballero, Joern-Henrik Jacobsen, Amy Zhang, Jonathan Binas, Dinghuai Zhang, Remi Le Priol, and Aaron Courville. Out-of-distribution generalization via risk extrapolation (rex). In International Conference on Machine Learning, pp. 5815–5826. PMLR, 2021.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy Hospedales. Learning to generalize: Meta-learning for domain generalization. In Proceedings of the AAAI conference on artificial intelligence, volume 32, 2018.

Anqi Liu and Brian Ziebart. Robust classification under sample selection bias. Advances in neural information processing systems, 27, 2014.

Daniel McFadden. A method of simulated moments for estimation of discrete response models without numerical integration. Econometrica: Journal of the Econometric Society, pp. 995–1026, 1989.

Saeid Motiian, Marco Piccirilli, Donald A Adjeroh, and Gianfranco Doretto. Unified deep supervised domain adaptation and generalization. In Proceedings of the IEEE international conference on computer vision, pp. 5715–5725, 2017.

Krikamol Muandet, David Balduzzi, and Bernhard Schölkopf. Domain generalization via invariant feature representation. In International Conference on Machine Learning, pp. 10–18. PMLR, 2013.

Alexander Robey, George J Pappas, and Hamed Hassani. Model-based domain generalization. Advances in Neural Information Processing Systems, 34:20210–20229, 2021.

Elan Rosenfeld, Pradeep Ravikumar, and Andrej Risteski. The risks of invariant risk minimization. arXiv preprint arXiv:2010.05761, 2020.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. International journal of computer vision, 115(3):211–252, 2015.

Shiori Sagawa, Pang Wei Koh, Tatsunori B Hashimoto, and Percy Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. arXiv preprint arXiv:1911.08731, 2019.

Shiori Sagawa, Pang Wei Koh, Tony Lee, Irena Gao, Sang Michael Xie, Kendrick Shen, Ananya Kumar, Weihua Hu, Michihiro Yasunaga, Henrik Marklund, et al. Extending the wilds benchmark for unsupervised adaptation. arXiv preprint arXiv:2112.05090, 2021.

Yuge Shi, Jeffrey Seely, Philip HS Torr, N Siddharth, Awni Hannun, Nicolas Usunier, and Gabriel Synnaeve. Gradient matching for domain generalization. arXiv preprint arXiv:2104.09937, 2021.

Baochen Sun and Kate Saenko. Deep coral: Correlation alignment for deep domain adaptation. In European conference on computer vision, pp. 443–450. Springer, 2016.

Vladimir Vapnik. Principles of risk minimization for learning theory. Advances in neural information processing systems, 4, 1991.

Chuanlong Xie, Fei Chen, Yue Liu, and Zhenguo Li. Risk variance penalization: From distributional robustness to causality. 2020.

Bianca Zadrozny. Learning and evaluating classifiers under sample selection bias. In Proceedings of the twenty-first international conference on Machine learning, pp. 114, 2004.

Shanshan Zhao, Mingming Gong, Tongliang Liu, Huan Fu, and Dacheng Tao. Domain generalization via entropy regularization. Advances in Neural Information Processing Systems, 33: 16096–16107, 2020.

A APPENDIX

A.1 PROOFS

Theorem 1. The following chain of inequalities completes the proof:

$$
\mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}}[\ell(f_{\text{SDRM}}(X),Y)] = \sum_{k=1}^{L} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{K}}[\ell(f_{\text{SDRM}}(X),Y)]P(S^k=1)
$$

$$
= \sum_{k=1}^{K} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{k}}[\ell(f_{\text{SDRM}}(X),Y)]P(S^k=1) + \sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{k}}[\ell(f_{\text{SDRM}}(X),Y)]P(S^k=1)
$$

$$
= \sum_{k=1}^{K} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{k}}[\ell(f_{\text{SDRM}}(X),Y)]P(S^k=1) + \sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{X\sim\mathcal{P}_{X}^{k}}[\ell_s(\boldsymbol{g}_{\text{SGDG}}(X),S^k)]P(S^k=1)
$$

$$
- \sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{(X,S^k)\sim\mathcal{P}_{XS^k}}[\ell_s\boldsymbol{g}_{\text{SGDG}},S^k)]P(S^k=1) + \sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{k}}[\ell(f_{\text{SDRM}}(X),Y)]P(S^k=1)
$$

$$
\geq \underbrace{\sum_{k=1}^{K} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{k}}[\ell(f_{\text{SGDG}}(X),Y)]P(S^k=1) + \sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{X\sim\mathcal{P}_{X}^{k}}[\ell_s(\boldsymbol{g}_{\text{SGDG}}(X),S^k)]P(S^k=1)}_{=\text{The objective function of SGDG}}
$$

$$
- \sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{X\sim\mathcal{P}_{X}^{k}}[\ell_s(\boldsymbol{g}_{\text{SGDG}}(X),S^k)]P(S^k=1) + \sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{k}}[\ell(f_{\text{SDRM}}(X),Y)]P(S^k=1)
$$

$$
\geq \sum_{k=1}^{K} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{k}}[\ell(f_{\text{SGDG}}(X),Y)]P(S^k=1) + \sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{X\sim\mathcal{P}_{X}^{k}}[\ell_s(\boldsymbol{g}_{\text{SGDG}}(X),S^k)]P(S^k=1)
$$

$$
\underbrace{- \sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{X\sim\mathcal{P}_{X}^{k}}[\ell_s(\boldsymbol{g}_{\text{SGDG}}(X),S^k)]P(S^k=1) + \sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{k}}[\ell(f_{\text{SGDG}}(X),Y)]P(S^k=1)}_{\sum_{k=K+1}^{L} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{k}}[\Lambda(f_{\text{SGDG}}(X),\boldsymbol{g}_{\text{SGDG}}(X);Y,S^k=1)]}
$$

$$
= \sum_{k=1}^{K} \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}^{k}}[\ell(f_{\text{SGDG}}(X),Y)]P(S^k=1) = \mathop{\mathbb{E}}_{(X,Y)\sim\mathcal{P}_{XY}}[\ell(f_{\text{SGDG}}(X),Y)].
$$

A.2 DETAILS OF HECKMAN CORRECTION-GUIDED DOMAIN GENERALIZATION

In this section, we present the exact form of our loss functions for continuous, binary, and multinomial outcomes, based on their specific parametric assumptions.

Continuous Outcomes For regression tasks where $y \in \mathbb{R}$, we assume that the selection and outcome is generated by the following data generation process:

$$
S^k = \mathbb{I}[\tilde{S}^k > 0] = \mathbb{I}[g_k(\boldsymbol{x}) + \eta_k] \tag{12}
$$

$$
Y = f(\boldsymbol{x}) + \varepsilon \tag{13}
$$

$$
\begin{bmatrix} \eta_k \\ \varepsilon \end{bmatrix} \sim \mathcal{N}\left(\boldsymbol{0}, \begin{bmatrix} 1 & \sigma\rho_k \\ \sigma\rho_k & \sigma^2 \end{bmatrix}\right) \tag{14}
$$

where $\mathbb{I}(\cdot) \in \{0,1\}$ is the indicator function, ρ_k is the correlation between ρ_k and ε, and $\sigma \in \mathbb{R}_+$ is the standard deviation of ε. Being consistent with the notation in the main text, we hereby define $\Sigma = \{\rho_1, \ldots, \rho_K, \sigma\}$. Denoting model parameters as $\theta = \{f, g_1, \ldots, g_K, \Sigma\}$, we formulate the

data likelihood as follows:

$$\mathcal{L}_c(\theta; \mathcal{D}) = \prod_{i=1}^{N} \prod_{k=1}^{K} \left[p(y_i | s_{ik} = 1, \boldsymbol{x}_i) \cdot p(s_{ik} = 1 | \boldsymbol{x}_i) \right]^{s_{ik}} \cdot p(s_{ik} = 0 | \boldsymbol{x}_i)^{1-s_{ik}} \tag{15}$$

and we take the negative log likelihood to formulate the loss function:

$$\ell_c(\mathcal{D}; \theta) = -\sum_{i=1}^{N} \sum_{k=1}^{K} s_{ik} \left[\log \Phi_1 \left(\frac{g_k(\boldsymbol{x}_i) + \rho_k \frac{y_i - f(\boldsymbol{x}_i)}{\sigma}}{\sqrt{1 - \rho_k^2}} \right) - \frac{1}{2} \log 2\pi\sigma^2 - \frac{1}{2} \left\{ \frac{y_i - f(\boldsymbol{x}_i)}{\sigma} \right\}^2 \right]$$
$$- \sum_{i=1}^{N} \sum_{k=1}^{K} (1 - s_{ik}) \log \Phi_1(-g_k(\boldsymbol{x}_i))$$

$$\tag{16}$$

Binary Outcomes   For binary outcomes where $y \in \{0, 1\}$, we assume a probit model for both selection and outcome:

$$S^k = \mathbb{I}[\tilde{S}^k > 0] = \mathbb{I}[g_k(\boldsymbol{x}) + \eta_k > 0]$$
$$Y = \mathbb{I}[f(\boldsymbol{x}) + \varepsilon > 0]$$
$$\begin{bmatrix} \eta_k \\ \varepsilon \end{bmatrix} \sim \mathcal{N} \left(\mathbf{0}, \begin{bmatrix} 1 & \rho_k \\ \rho_k & 1 \end{bmatrix} \right) \tag{17}$$

where ρ_k is the correlation between η_k and ε. Herein, $\Sigma = \{\rho_1, \ldots, \rho_K\}$. Denoting model parameters as $\theta = \{f, g_1, \ldots, g_K, \Sigma\}$, we formulate the data likelihood for binary outcomes as follows:

$$\mathcal{L}_b(\theta; \mathcal{D}) = \prod_{i=1}^{N} \prod_{k=1}^{K} \left\{ p(y_i = 1, s_{ik} = 1 | \boldsymbol{x}_i)^{y_i} \cdot p(y_i = 0, s_{ik} = 1 | \boldsymbol{x}_i)^{1-y_i} \right\}^{s_{ik}} p(s_{ik} = 0 | \boldsymbol{x}_i)^{1-s_{ik}}$$

$$\tag{18}$$

and take the negative log likelihood to define the loss function for binary outcomes:

$$\ell_b(\mathcal{D}; \theta) = -\sum_{i=1}^{N} \sum_{k=1}^{K} s_{ik} \cdot y_i \cdot \log \Phi_2 \left(g_k(\boldsymbol{x}_i), f(\boldsymbol{x}_i), \rho_k \right)$$
$$- \sum_{i=1}^{N} \sum_{k=1}^{K} s_{ik} \cdot (1 - y_i) \cdot \log \left(\Phi_1 \left(g_k(\boldsymbol{x}_i) \right) - \Phi_2 \left(g_k(\boldsymbol{x}_i), f(\boldsymbol{x}_i); \rho_k \right) \right) \tag{19}$$
$$- \sum_{i=1}^{N} \sum_{k=1}^{K} (1 - s_{ik}) \cdot \log \Phi_1 \left(-g_k(\boldsymbol{x}_i) \right)$$

where $\Phi_2(\cdot, \cdot; a)$ is the cumulative density function of the bivariate standard normal given correlation $a \in [-1, 1]$.

Multinomial Outcomes   For multinomial outcome tasks where $y \in \{1, \ldots, J\}$, we assume a multinomial probit outcome model (McFadden, 1989):

$$\tilde{Y}_j = f_j(\boldsymbol{x}) + \varepsilon_j, \quad \forall j \in \{1, \ldots, J\}$$
$$Y = \operatorname*{argmax}_{j \in \{1, \ldots, J\}} \tilde{Y}_j \tag{20}$$

where $[\eta_k, \varepsilon_j] \sim \mathcal{N}(\mathbf{0}, [1, 1; \rho_{kj}])$ and ρ_{kj} is the correlation between ρ_k and ε_j. We further assume that the outcome error terms are independently distributed: $\varepsilon = [\varepsilon_1, \ldots, \varepsilon_J]^\top \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$. Consequently, $\Sigma = \{\rho_{11}, \ldots, \rho_{KJ}\}$. Denoting model parameters as $\theta = \{f_1, \ldots, f_J, g_1, \ldots, g_K, \rho_{11}, \ldots, \rho_{KJ}\}$, we formulate the multinomial outcome data likelihood as follows:

$$\mathcal{L}_m(\theta; \mathcal{D}) = \prod_{i=1}^{N} \prod_{k=1}^{K} \prod_{j=1}^{J} \left\{ p(s_{ik} = 1, y_i = j | \boldsymbol{x}_i)^{\mathbb{I}[y_i = j]} \right\}^{s_{ik}} p(s_{ik} = 0 | \boldsymbol{x}_i)^{1-s_{ik}} \tag{21}$$

where $\mathbb{I}[\cdot] \in \{0, 1\}$ is the indicator function. We use the negative logarithm of the data likelihood for the loss function:

$$\ell_m(\mathcal{D}; \theta) = -\sum_{i=1}^{N} \sum_{k=1}^{K} \sum_{j=1}^{J} \left[s_{ik} \cdot \mathbb{I}[y_i = j] \cdot \log \int_T \phi(\boldsymbol{u}|\vec{0}, \tilde{\Sigma}) d\boldsymbol{u} + (1 - s_{ik}) \cdot \log \Phi\left(-g_k(\boldsymbol{x}_i)\right) \right] \quad (22)$$

where $T = [-g_k(\boldsymbol{x}_i), \infty) \times [\xi_{j,1}(\boldsymbol{x}_i), \infty) \times \ldots \times [\xi_{j,j-1}(\boldsymbol{x}_i), \infty) \times [\xi_{j,j+1}(\boldsymbol{x}_i), \infty) \times \ldots \times [\xi_{j,J}(\boldsymbol{x}_i), \infty) \subseteq \mathbb{R}^J$ is the half-open J-dimensional hyperrectangular domain and $\xi_{j,j'}(\boldsymbol{x}_i) = -f_j(\boldsymbol{x}_i) + f_{j'}(\boldsymbol{x}_i)$. We use the GHK algorithm (Hajivassiliou & Ruud, 1994) to compute the multivariate normal integrals.

A.3 Optimization, Datasets, and Model Training

Algorithm 1 Two-Step Optimization for HeckmanDG

1: **Input:** Data $\mathcal{D} = \{(\boldsymbol{x}_i, y_i, \boldsymbol{s}_i) \in \mathcal{X} \times \mathcal{Y} \times \mathcal{S} : i = 1, \cdots, N\}$, Batch size B, Learning rate γ.
2: **Output:** $\hat{f}, \hat{\boldsymbol{g}} = \{\hat{g}_k\}_{k=1}^{K}$, and $\hat{\Sigma}$.
3: **Initialize:** $f, \boldsymbol{g}, \Sigma$
4: **Step 1:** Learn the Domain Selection Models ($\boldsymbol{g}$)
5:     **for all** $k = 1, \ldots, K$ **do**
6:         $\mathcal{D}_k \leftarrow \{(\boldsymbol{x}_i, s_{ik}) \in \mathcal{X} \times [0, 1] : i = 1, \ldots, N\}$
7:     **end for**
8:     **while** $\boldsymbol{g} = \{g_k\}_{k=1}^{K}$ `Not Converged` **do**
9:         **for all** $k = 1, \cdots, K$ **do**
10:            $\mathcal{B}_k \leftarrow \texttt{BatchSampler}(\mathcal{D}_k, B)$
11:            $g_k \leftarrow g_k + \frac{\gamma}{B} \nabla \sum_{(\boldsymbol{x}_i, s_{ik}) \in \mathcal{B}_k} [s_{ik} \log \Phi(g_k(\boldsymbol{x}_i)) + (1 - s_{ik}) \log \Phi(-g_k(\boldsymbol{x}_i))]$
12:         **end for**
13:     **end while**
14:     $\hat{g}_k = g_k$, for $k = 1, \ldots, K$.
15: **Step 2:** Learn the Outcome Model (f, Σ)
16:     $\mathcal{D}_{\mathcal{O}} = \mathcal{D}$
17:     **while** f `Not Converged` **do**
18:         $\mathcal{B} = \texttt{BatchSampler}(\mathcal{D}_{\mathcal{O}}, B)$
19:         $f \leftarrow f - \frac{\gamma}{B} \nabla \sum_{(\boldsymbol{x}_i, y_i, \boldsymbol{s}_i) \in \mathcal{B}} \sum_{k=1}^{K} s_{ik} \Lambda(f(\boldsymbol{x}_i), \hat{g}_k(\boldsymbol{x}_i), y_i, s_{ik}; \Sigma)$
20:         $\Sigma \leftarrow \Sigma - \frac{\gamma}{B} \nabla \sum_{(\boldsymbol{x}_i, y_i, \boldsymbol{s}_i) \in \mathcal{B}} \sum_{k=1}^{K} s_{ik} \Lambda(f(\boldsymbol{x}_i), \hat{g}_k(\boldsymbol{x}_i), y_i, s_{ik}; \Sigma)$
21:     **end while**
22:     $\hat{f} \leftarrow f$
23:     $\hat{\Sigma} \leftarrow \Sigma$
24: **return** $\hat{f}$

Table 5: A summary on the four datasets from WILDS benchmark. In the *'Domain'* row, the three numbers in parentheses denote the number of train, validation, and test domains.

Dataset	CAMELYON17	POVERTYMAP	IWILDCAM	RXRX1
X	$3 \times 96 \times 96$ (tissue slide)	$8 \times 224 \times 224$ (satellite image)	$3 \times 448 \times 448$ (photo)	$3 \times 256 \times 256$ (cell)
Y	2 (tumor)	continuous (asset wealth)	182 (animal species)	1139 (genetic treatments)
Training examples	302,436	10,000	129,809	40,612
Domain	5 Hospitals (3, 1, 1)	23 countries (13, 5, 5)	323 camera traps (243, 32, 48)	51 batches (33, 4, 14)
Evaluation metric	Average accuracy	Pearson (average, worst-group)	Macro F1	Average accuracy

Table 6: Details on training configurations of HeckmanDG. Cells with two entries (i.e., learning rate, weight decay) denote that we used different values for training domain selection and outcome models. Hyperparameters were determined through grid search on the OOD validation set. For optimizers we searched between $\{\text{Adam}, \text{SGD}\}$. Learning rates were searched among $\{10^{-5}, 10^{-4}, 10^{-3}\}$, and weight decay among $\{0, 10^{-5}, 10^{-3}, 10^{-1}\}$. Note that since HeckmanDG training is two-phase, we searched for hyperparameters sequentially.

Dataset	CAMELYON17	POVERTYMAP	IWILDCAM	RXRX1
Feature Extractor	DenseNet-121	ResNet-18-MS	ResNet-50	ResNet-50
Epochs	5, 5	100, 100	12, 12	10, 10
Batch Size	32, 32	64, 64	16, 16	75, 75
Optimizer	Adam, SGD	Adam, SGD	Adam, SGD	Adam, SGD
Learning Rate	$10^{-5}, 10^{-3}$	$10^{-5}, 10^{-3}$	$10^{-5}, 10^{-3}$	$10^{-5}, 10^{-3}$
Weight Decay	$0, 10^{-4}$	$0, 10^{-5}$	$0, 10^{-5}$	$0, 10^{-5}$
ImageNet Weights	True, True	False, False	True, True	True, True
Data Augmentation	N/A	Color jittering	RandAugment	RandAugment