Continual Vision-based Reinforcement Learning with Group Symmetries

Abstract: Continual reinforcement learning aims to sequentially learn a variety of tasks, retaining the ability to perform previously encountered tasks while simultaneously developing new policies for novel tasks. However, current continual RL approaches overlook the fact that certain tasks are identical under basic group operations like rotations or translations, especially with visual inputs. They may unnecessarily learn and maintain a new policy for each similar task, leading to poor sample efficiency and weak generalization capability. To address this, we introduce a unique **Co**ntinual **V**ision-bas**e**d **R**einforcement Learning method that recognizes Group **S**ymmetries, called COVERS, cultivating a policy for each group of equivalent tasks rather than an individual task. COVERS employs a proximal policy gradient-based (PPO-based) algorithm to train each policy, which contains an equivariant feature extractor and takes inputs with different modalities, including image observations and robot proprioceptive states. It also utilizes an unsupervised task clustering mechanism that relies on 1-Wasserstein distance on the extracted invariant features. We evaluate COVERS on a sequence of table-top manipulation tasks in simulation and on a real robot platform. Our results show that COVERS accurately assigns tasks to their respective groups and significantly outperforms baselines by generalizing to unseen but equivariant tasks in seen task groups. Demos are available on our project page[1].

Keywords: Continual Learning, Symmetry, Manipulation

1 INTRODUCTION

Quick adaptation to unseen tasks has been a key objective in the field of reinforcement learning (RL) [1, 2, 3]. RL algorithms are usually trained in simulated environments and then deployed in the real world. However, pre-trained RL agents are likely to encounter new tasks during their deployment due to the nonstationarity of the environment. Blindly reusing policies obtained during training can result in substantial performance drops and even catastrophic failures [4, 5].

Continual RL (CRL), also referred to as lifelong RL, addresses this issue by sequentially learning a series of tasks. It achieves this by generating task-specific policies for the current task, while simultaneously preserving the ability to solve previously encountered tasks [3, 6, 7, 8, 9]. Existing CRL works that rely on the task delineations to handle non-stationary initial states, dynamics or reward functions can greatly boost task performance, particularly when significant task changes occur [7]. However, in realistic task-agnostic settings, these delineations are unknown a prior and have to be identified by the agents. In this work, we explore *how to define and detect task delineations to enhance robots' learning capabilities in task-agnostic CRL.*

Our key insight is that robotic control tasks typically preserve certain desirable structures, such as *group symmetries*. Existing CRL approaches typically delineate task boundaries based on statistical

---

[1]Project Page: https://sites.google.com/view/rl-covers/.

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

measures, such as maximum a posteriori estimates and likelihoods [7, 8]. However, these measures overlook the geometric information inherent in task representations, which naturally emerge in robotic control tasks, as demonstrated in Figure 1. Consider the drawer-closing example: conventional CRL works using image inputs would treat each mirrored configuration as a new task and learn the task from scratch. Yet, we, as humans, understand that the mirrored task configuration can be easily resolved by correspondingly reflecting the actions. Learning the mirrored task from scratch hampers positive task interference and limits the agent's adaptivity. To address this issue, our goal is to exploit the geometric similarity among tasks in the task-agnostic CRL setting to facilitate rapid adaptation to unseen but geometrically equivalent tasks.

In this work, we propose COVERS, a task-agnostic vision-based CRL algorithm with strong sample efficiency and generalization capability by encoding group symmetries in the state and action spaces. We define a *task group* as the set that contains equivalent tasks under the same group operation, such as rotations and reflections. We state our main contributions as follows:

1. COVERS grows a PPO-based [10] policy with an equivariant feature extractor for each task group, instead of a single task, to solve unseen tasks in seen groups in a zero-shot manner.

2. COVERS utilizes a novel unsupervised task grouping mechanism, which automatically detects group boundaries based on 1-Wasserstein distance in the invariant feature space.

Figure 1: This example illustrates how group symmetry enhances adaptability. The robot is instructed to close drawers situated in two distinct locations with top-down images as inputs. Considering the symmetry of the drawers' locations around the robot's position, the optimal control policies are equivalent but mirrored.

3. In non-stationary table-top manipulation environments, COVERS performs better than baselines in terms of average rewards and success rates. Moreover, we show that (a) the group symmetric information from the equivariant feature extractor promotes the adaptivity by maximizing the positive interference within each group, and (b) the task grouping mechanism recovers the ground truth group indexes, which helps minimize the negative interference among different groups.

2   Related Work

Task-Agnostic CRL. CRL has been a long-standing problem that aims to train RL agents adaptable to non-stationary environments with evolving world models [11, 12, 13, 14, 15, 5, 16, 17, 18, 19]. In task-agnostic CRL where task identifications are unrevealed, existing methods have addressed the problem through a range of techniques. These include hierarchical task modeling with stochastic processes [7, 8], meta-learning [3, 20], online system identification [21], learning a representation from experience [9, 22], and experience replay [14, 23]. Considering that in realistic situations, the new task may not belong to the same task distribution as past tasks, we develop an ensemble model of policy networks capable of handling diverse unseen tasks, rather than relying on a single network to model dynamics or latent representations. Moreover, prior work often depends on data distribution-wise similarity or distances between latent variables, implicitly modeling task relationships. In contrast, we aim to introduce beneficial inductive bias explicitly by developing policy networks with equivariant feature extractors to capture the geometric structures of tasks.

Symmetries in RL. There has been a surge of interest in modeling symmetries in components of Markov Decision Processes (MDPs) to improve generalization and efficiency [24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35]. MDP homomorphic network [26] preserves equivariant under symmetries in the state-action spaces of an MDP by imposing an equivariance constraint on the policy and value

Figure 2: The continual learning environment setup involves four task groups, including Plate Slide, Button Press, Drawer Close, and Goal Reach. Groups streamingly come in.

network. As a result, it reduces the RL agent's solution space and increases sample efficiency. This single-agent MDP homomorphic network is then extended to the multi-agent domain by factorizing global symmetries into local symmetries [27]. SO(2)-Equivariant RL [28] extends the discrete symmetry group to the group of continuous planar rotations, SO(2), to boost the performance in robotic manipulation tasks. In contrast, we seek to exploit the symmetric properties to improve the generalization capability of task-agnostic CRL algorithms and handle inputs with multiple modalities.

3 Preliminary

Markov decision process. We consider a Markov decision process (MDP) as a 5-tuple $(\mathcal{S}, \mathcal{A}, T, R, \gamma)$, where $\mathcal{S}$ and $\mathcal{A}$ are the state and action space, respectively. $T : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$ is the transition function, $R : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is the reward function, and γ is the discount factor. We aim to find an optimal policy $\pi_\theta : \mathcal{S} \to \mathcal{A}$ parameterized by θ that maximizes the expected return $\mathbb{E}_{\tau \sim \pi_\theta} \left[\sum_{t=0}^{H-1} \gamma^t r(s_t, a_t) \right]$, where H is the episode length.

Invariance and equivariance. Let G be a mathematical group. $f : \mathcal{X} \to \mathcal{Y}$ is a mapping function. For a transformation $L_g : \mathcal{X} \to \mathcal{X}$ that satisfies $f(x) = f(L_g[x]), \forall g \in G, x \in \mathcal{X}$, we say f is invariant to L_g. Equivariance is closely related to invariance. If we can find another transformation $K_g : \mathcal{Y} \to \mathcal{Y}$ that fulfills $K_g[f(x)] = f(L_g[x]), \forall g \in G, x \in \mathcal{X}$ then we say f is equivariant to transformation L_g. It's worth noting that invariance is a special case of equivariance.

MDP with group symmetries. In MDPs with symmetries [24, 25, 26], we can identify at least one mathematical group G of a transformation $L_g : \mathcal{S} \to \mathcal{S}$ and a state-dependent action transformation $K_g^s : \mathcal{A} \to \mathcal{A}$, such that $R(s, a) = R\left(L_g[s], K_g^s[a]\right), T\left(s, a, s'\right) = T\left(L_g[s], K_g^s[a], L_g[s']\right)$ hold for all $g \in G, s, s' \in \mathcal{S}, a \in \mathcal{A}$.

Equivariant convolutional layer. Let G be a Euclidean group, with the special orthogonal group and reflection group as subgroups. We use the equivariant convolutional layer developed by Weiler and Cesa [36], where each layer consists of G-steerable kernels $k : \mathbb{R}^2 \to \mathbb{R}^{c_{out} \times c_{in}}$ that satisfies $k(gx) = \rho_{out}(g)k(x)\rho_{in}\left(g^{-1}\right), \forall g \in G, x \in \mathbb{R}^2$. ρ_{in} and ρ_{out} are the types of input vector field $f_{in} : \mathbb{R}^2 \to \mathbb{R}^{c_{in}}$ and output vector field $f_{out} : \mathbb{R}^2 \to \mathbb{R}^{c_{out}}$, respectively.

Equivariant MLP. An equivariant multi-layer perceptron (MLP) consists of both equivariant linear layers and equivariant nonlinearities. An equivariant linear layer is a linear function W that maps from one vector space V_{in} with type ρ_{in} to another vector space with type ρ_{out} for a given group G. Formally $\forall x \in V_{in}, \forall g \in G : \rho_{out}(g)Wx = W\rho_{in}(g)x$. Here we use the numerical method proposed by Finzi et al. [37] to parameterize MLPs that are equivariant to arbitrary groups.

4 Methodology

4.1 Problem Formulation

We focus on continual learning in table-top manipulation environments, where various tasks are sequentially presented. We hypothesize that the streaming tasks can be partitioned into task groups, each containing tasks that share symmetry with one another. We adopt a realistic setting where a new task group may emerge at each episode, the total number of distinct groups remains unknown

---

Algorithm 1 COVERS: Continual Vision-based RL with Group Symmetries

---

Input: Threshold d_ϵ, initial frame number k, update interval N_u, rollout step size N_s
Output: collection of policies Π
Initialization: Current policy π_{cur} initialized as a random policy with a policy data buffer $\mathcal{B} \leftarrow \varnothing$, policy collection $\Pi \leftarrow \{(\pi_{cur}, \mathcal{B})\}$, number of episodes $n \leftarrow 0$, online rollout buffer $\mathcal{D} \leftarrow \varnothing$

1: **while** *task not finish* **do**
2:      $n \leftarrow n + 1$
3:      **if** $n \% N_u = 0$ **then**
4:          Rollout buffer $\mathcal{O} \leftarrow \varnothing$ ▷ Unsupervised Policy Assignment
5:          Rollout N_s steps with π_{cur} and get trajectories $\tau = \{(s_0, a_0, \ldots, s_H, a_H)\}$
6:          Append the first k frames of each episode to rollout buffer $\mathcal{O} \leftarrow \{(s_0, \ldots, s_{k-1})\}$
7:          Append the whole episode trajectories τ to the online rollout buffer $\mathcal{D}$
8:          Calculate the 1-Wasserstein distances $d_i^W(\mathcal{O}, \mathcal{B}_i), \forall \{\pi_i, \mathcal{B}_i\} \in \Pi$ (Equation 2)
9:          Get the minimum distance d_j^W where $j = \arg\min_i d_i^W(\mathcal{O}, \mathcal{B}_i)$
10:         **if** $d_j > d_\epsilon$ **then**
11:             Initialize a new random policy π as well as its policy data buffer $\mathcal{B} \leftarrow \mathcal{O}$
12:             $\pi_{cur} \leftarrow \pi, \Pi \leftarrow \Pi \cup \{\{\pi, \mathcal{B}\}\}$
13:         **else**
14:             Assign the existing policy and buffer with $\pi_{cur} \leftarrow \pi_j, \mathcal{B}_j \leftarrow \mathcal{B}_j \cup \mathcal{O}$
15:         Update π_{cur} based on online rollout buffer $\mathcal{D}$ (Equation 1) ▷ Equivariant Policy Update
16:         $\mathcal{D} \leftarrow \varnothing$
17:      **else**
18:         Sample an episode and append to online rollout buffer $\mathcal{D}$

---

and the group may arrive in random orders. The primary objective is to devise an online learning algorithm capable of achieving high performance across all tasks with strong data efficiency. We visualize our CRL setting with table-top manipulation environments in Figure 2.

4.2 Algorithm

We present the pseudocode for COVERS, a task-agnostic continual RL method with group symmetries, in Algorithm 1. COVERS maintains a collection $\Pi = \{(\pi, \mathcal{B})\}$, each element of which comprising a pair of policy π and its respective data buffer $\mathcal{B}$. Each policy π independently manages one group of tasks, with $\mathcal{B}$ storing the initial frames of the group it oversees. At fixed time intervals, COVERS collects N_s steps in parallel under the current policy π_{cur} and stores the first k frames from each episode in the rollout buffer $\mathcal{O}$. Based on $\mathcal{O}$, the algorithm then either (a) creates a new policy for an unseen group and adds it to the collection Π, or (b) recalls an existing policy from the collection Π if the group has been previously encountered. It is worth noting that we assign policies based on initial frames of each episode rather than the full episode rollout. This is because frames corresponding to later timesteps are heavily influenced by the behavior policy and could easily lead to unstable policy assignments. Only maintaining a subset of the rollout trajectories also helps alleviate memory usage.

After the policy assignment, the selected policy π_{cur} with parameters θ is updated based on an online rollout buffer $\mathcal{D}$ and Proximal Policy gradient (PPO) method [10] with loss in Equation 1. $\hat{A}_t$ is the estimated advantage, $\rho_t = \pi_\theta(a_t|s_t)/\pi_{\theta_{old}}(a_t|s_t)$ is the importance ratio and ϵ is the clip range.

$$\mathcal{L}_{CLIP} = \mathbb{E}_{\tau \sim \mathcal{D}} \Big[\sum_{t=1}^{H} \min[\rho_t(\theta)\hat{A}_t, \text{clip}(\rho_t(\theta), 1 - \epsilon, 1 + \epsilon)\hat{A}_t] \Big]. \tag{1}$$

4.3 Policy Network Architecture

COVERS utilizes an equivariant policy network that comprises a policy network for predicting actions, a value network approximating values, and an equivariant feature extractor taking multiple modalities. We show the policy architecture in Figure 3 and additional details in Figure 10.

Figure 3: Equivariant policy network architecture.

Equivariant feature extractor. In real manipulation tasks, the observations typically comprise multiple modalities, such as image observations, robot proprioceptive states, and goal positions represented in vector form. To accommodate these diverse modalities, we designed an equivariant feature extractor h^{equi}, that employs an equivariant convolutional network h^{eConv} [36] for image processing, coupled with an equivariant linear network h^{eMLP} [38] to handle vector inputs. The resulting equivariant features from these two pathways are concatenated to form the output of the feature extractor. Formally, $h^{equi}(s) = \text{Concat}(h^{eConv}(s), h^{eMLP}(s))$.

Invariant value and equivariant policy. In the context of MDPs involving robotic manipulation tasks with group symmetries, it is known that the optimal value function maintains group invariance, while the optimal policy displays group equivariance [28]. To attain this, both the policy and value networks utilize a shared equivariant feature extractor, designed to distill equivariant features from observations. Subsequently, the value network leverages a group pooling layer to transform these equivariant features into invariant ones, before employing a fully connected layer to generate values. Formally, $h^{inv}(s) = \text{GroupMaxPooling}(h^{equi}(s))$. The policy network, on the other hand, processes the equivariant features with an additional equivariant MLP network to output actions.

4.4 Unsupervised Dynamic Policy Assignment

In COVERS, we propose to detect different groups of tasks based on *distances in the invariant feature space*. Such a mechanism facilitates knowledge transfer between tasks in each group. At a fixed episode interval, COVERS selects the policy of the group, whose data buffer $\mathcal{B}$ has the minimal distance in the invariant feature space to the rollout buffer $\mathcal{O}$ collected in the current environment. Note that the invariant features of both $\mathcal{O}$ and $\mathcal{B}$ are obtained through the feature extractor of π as shown in Figure 4. Considering that $\mathcal{O}$ and $\mathcal{B}$ may have a different number of data pairs, we take a probablistic perspective by treating those data buffers as sample-based representations of two distributions and use the Wasserstein distance to measure the distance between those two feature distributions. The invariant features are obtained from the equivariant feature extractor via a group max-pooling operation as shown in Figure 3.

Figure 4: Calculation of 1-Wasserstein distance and update of selected policy π_j, whose data buffer has minimal distance to $\mathcal{O}$.

Wasserstein distance on invariant feature space. Let $\mathbf{X}$ and $\mathbf{Y}$ be a matrix constructed by invariant features extracted from the state buffer $\mathcal{B}$ of size n and the buffer $\mathcal{O}$ of size m. Concretely, $\mathbf{X} = (X_1, X_2, ..., X_n)^{\text{T}}, X_i = h^{inv}(s_i), i \in [n], s_i \in \mathcal{B}$, and $\mathbf{Y} = (Y_1, Y_2, ..., Y_m)^{\text{T}}, Y_l = h^{inv}(s_l), l \in [m], s_l \in \mathcal{O}$. We use the 1-Wasserstein distance [39] to measure the distance between two empirical distributions $\mathbf{X}$ and $\mathbf{Y}$. Hence the distance between $\mathcal{O}$ and $\mathcal{B}$ is

$$d^W(\mathcal{O}, \mathcal{B}) = W_1(\mathbf{X}, \mathbf{Y}) = \min_{\gamma} \langle \gamma, \mathbf{M} \rangle_F \text{ s.t. } \gamma\mathbf{1} = \mathbf{a}, \gamma^T\mathbf{1} = \mathbf{b}, \gamma \geq 0, \quad (2)$$

where $\mathbf{M}_{i,l} = \|X_i - Y_l\|_2, \mathbf{a} = [1/n, \ldots, 1/n], \mathbf{b} = [1/m, \ldots, 1/m]$. $\mathbf{M}$ is the metric cost matrix.

5 Simulation Experiments

We validate COVERS's performance in robot manipulation [40] tasks with nonstationary environ-
ments containing different objects or following different reward functions. We aim to investigate
whether our method can (1) recall stored policy when facing a seen group, as well as automatically
initialize a new policy when encountering an unseen group, (2) achieve similar or better performance
compared to baselines, and (3) understand the significance of key components of COVERS.

5.1 Environment

Simulation setup. Our manipulation setup is composed of
four groups of tasks. Each group contains four tasks, and all
tasks within the same group exhibit rotational or reflectional
symmetry with respect to each other. We build environments
based on the Meta-World benchmark [40]. Meta-World fea-
tures a variety of table-top manipulation tasks that require in-
teraction with diverse objects using a Sawyer robot. We show
the four groups of tasks in Figure 2 including **Goal Reach** for
reaching a goal position, **Button Press** for pressing the button
with gripper, **Drawer Close** for closing drawer with gripper,
and **Plate Slide** for sliding the plate to a goal position. The
goal positions and object locations of tasks in each group are
symmetrically arranged around the center of the table.

States and actions. The agent receives four kinds of observa-
tions: an RGB image captured by a top-down camera centered
over the table at each timestep, an RGB image captured by the
same camera at the beginning of the episode, the robot state in-
cluding gripper's 3D coordinates and opening angle, and aux-
iliary information. The RGB image at the initial step helps al-
leviate the occlusion problem caused by the movement of the

Figure 5: Image preprocessing to
narrow down the sim-to-real gap.

robot. The auxiliary information contains 3D goal positions which are only revealed to the agent in
Goal Reach since the goal locations are not visualized in the captured image, and are masked out for
other groups. To close the sim-to-real gap, we prepossess the RGB images by inpainting robot arms
motivated by [41], with details deferred to Section B.1. A comparison of the original and processed
images is visualized in Figure 5. The action is a four-dimensional vector containing the gripper's 3D
positions and its opening angle. Considering that we utilize two distinct robots: Sawyer in the sim-
ulation and Kinova in the real-world, such an action space and the image preprocessing mechanism
help improve transferability between different robot morphologies.

5.2 Baselines and Ablations

We compare COVERS with different methods detailed as follows. **3RL** [22], an acronym for
Replay-based Recurrent RL, is a state-of-the-art method in CRL with Meta-World tasks that in-
tegrates experience replay [14] and recurrent neural networks [42]. Note that we augment **3RL** with
a convolutional neural network (CNN) to handle image inputs. In contrast, **CLEAR** [14], a com-
mon baseline of CRL, only utilize the experience replay by maintaining a memory buffer to store
the experience of the past tasks and oversamples the current tasks to boost the performance in the
current one. **Equi** utilizes a single policy with an equivariant feature extractor to solve all tasks.
CNN utilizes a single policy with a CNN-based feature extractor as a vanilla baseline. We provide
the detailed implementation of baselines and hyperparameters in Section B.

We compare with two ablation methods. **COVERS-GT** uses ground truth group labels to assign
policies to different groups, which helps ablate the performance of our proposed policy assignment
mechanism. **COVERS-CNN** utilizes a vanilla CNN block as the image feature extractor to help
ablate the effect of using equivariant feature extractors.

Figure 6: Training curves for COVERS and other methods. Each background color corresponds to one task group. COVERS shows similar performance with COVERS-GT, which utilizes additional ground truth group indices, and substantially outperforms other baselines.

Figure 7: The selected policies at each episode of COVERS. Each background color corresponds to one task group. The assigned policy indexes remain in alignment with the ground truth ones.

6 Simulation Results and Ablations

6.1 Results

Dynamic policy assignments. Figure 7 shows that when the environment switches to a new group, COVERS quickly detects changes and initializes a new policy for the group. Our method also recalls the corresponding policy from the collection when facing the same group again. Overall, the dynamic policy assignments generated by COVERS align well with the ground truth group labels. However, we observe some instances where the policy assignment does not match the ground truth. This could potentially be attributed to the fact that the feature extractor of each policy may not be able to capture representative features for each group during the early stages of training. Notably, the rate of such misclassifications significantly reduces as the number of training episodes increases.

Training performance. We show the training curves of all methods in Figure 6 and the quantitative performance in Table 2, including the average success rates and mean rewards. COVERS achieves a much higher episode reward and success rate consistently in different groups than baselines. It is worth noting that although 3RL performs worse than COVERS, it achieves better performance than baselines with implicit task representations, including Equi, CLEAR, and CNN. This indicates that the explicit task representation used by 3RL, which maps transition pairs to latent variables using an RNN, facilitates the revelation of partial task identifications, thereby enhancing performance. It underscores the significance of task-specific representations in CRL.

In the early stages of training, there isn't a significant performance difference between COVERS and Equi. However, as training progresses, COVERS begins to outperform Equi. This is because COVERS avoids the problem of forgetting through the retraining of policies for each previously encountered task group. A comparison between CNN and Equi reveals that incorporating group symmetries as inductive bias within the equivariant network significantly enhances sample efficiency. This is achieved by only optimizing the policy for the abstracted MDP of each task group.

6.2 Ablation Study

The effect of group symmetric information. COVERS-CNN devoid of the invariant feature extractor demonstrates lower episodic rewards and success rates when compared with COVERS as

Table 1: Quantitative results showing performances at convergence for different methods.

Methods		COVERS	3RL	CLEAR	CNN	Equi	COVERS-GT	COVERS-CNN
Plate Slide	Success Rate	**0.97 ± 0.02**	0.28 ± 0.06	0.06 ± 0.03	0.03 ± 0.02	0.02 ± 0.02	0.91 ± 0.03	0.62 ± 0.05
	Ave. Reward	**344.04 ± 12.89**	101.20 ± 7.35	65.65 ± 2.23	23.44 ± 1.14	64.02 ± 5.85	337.44 ± 13.87	232.25 ± 14.24
Button Press	Success Rate	**0.87 ± 0.04**	0.52 ± 0.06	0.31 ± 0.06	0.09 ± 0.03	0.01 ± 0.01	0.87 ± 0.04	0.26 ± 0.05
	Ave. Reward	**323.41 ± 3.48**	260.80 ± 6.86	138.78 ± 12.23	91.34 ± 9.34	121.13 ± 7.02	330.56 ± 2.63	181.21 ± 10.83
Drawer Close	Success Rate	0.82 ± 0.04	0.40 ± 0.06	0.27 ± 0.05	0.16 ± 0.04	0.40 ± 0.05	**0.98 ± 0.02**	0.56 ± 0.05
	Ave. Reward	400.09 ± 6.18	280.62 ± 6.39	216.08 ± 7.68	116.33 ± 10.1	273.26 ± 9.67	**417.38 ± 5.6**	227.3 ± 13.0
Goal Reach	Success Rate	**0.98 ± 0.02**	0.60 ± 0.06	0.58 ± 0.06	0.14 ± 0.04	0.47 ± 0.05	0.97 ± 0.02	0.97 ± 0.02
	Ave. Reward	483.53 ± 1.35	322.23 ± 17.33	293.5 ± 16.16	151.24 ± 14.31	306.72 ± 20.34	**488.02 ± 0.35**	480.96 ± 1.05
Average	Success Rate	0.91 ± 0.02	0.44 ± 0.03	0.30 ± 0.03	0.1 ± 0.02	0.22 ± 0.02	**0.93 ± 0.01**	0.60 ± 0.03
	Ave. Reward	387.77 ± 5.02	241.21 ± 7.39	178.5 ± 7.58	95.59 ± 5.59	191.28 ± 8.23	**393.35 ± 5.19**	280.43 ± 8.49

shown in Table 1 and Figure 6. From these results, we conclude that the equivariant feature extractor significantly enhances performance by modeling group symmetry information by introducing beneficial inductive bias through its model architecture.

The effect of the dynamic policy assignment module In Figure 6, COVERS's training curve is similar to COVERS-GT, which uses ground truth group indexes as extra prior knowledge. Table 1 shows that the performance drop due to misclassification is minor considering the small standard deviation and COVERS's performance is within one or two standard deviations of COVERS-GT.

7 Real-world Validation

Real-world setup. Our real-world experiment setup utilizes a Kinova GEN3 robotic arm with a Robotiq 2F-85 gripper. The top-down RGB image is captured with an Intel RealSense D345f. Gripper's coordinates and opening angle are obtained through the robot's internal sensors. The real robot setups are demonstrated in Figure 8. We directly deploy the trained policies in simulation to the real world. Table 2 shows average success rates across 20 trials and shows that our trained policies have strong generalization capability to real-world scenarios. The performance drop compared with simulation experiments may be due to the inconsistent visual features and different scales of robots' action spaces.

Goal Reach   Button Press

Drawer Close   Plate Slide

Figure 8: The real Kinova GEN3 setup with four task groups. The goal point marked in the figure is only disclosed to the agent in Goal Reach as auxiliary information.

Task Groups	Success Rate
Plate Slide	0.45 ± 0.15
Button Press	0.60 ± 0.15
Drawer Close	0.65 ± 0.15
Goal Reach	0.95 ± 0.07

Table 2: Real-world validation results.

8 Conclusion

We propose COVERS, a novel Vision-based CRL framework that leverages group symmetries to facilitate generalization to unseen but equivalent tasks under the same group operations. COVERS detects group boundaries in an unsupervised manner based on invariant features and grows policies for each group of equivalent tasks instead of a single task. We show that COVERS assigns tasks to different groups with high accuracy and has a strong generalization capability, outperforming baselines by a large margin. One limitation of COVERS is that the memory it occupies grows linearly with the number of task groups. However, it is worth noting that COVERS still occupies less memory than maintaining a policy buffer for each task by only storing representative data frames such as the initial frames for each task group. Another limitation is that although assuming a top-down camera with a fixed base is widely adopted in existing works, it is hard to fulfill outside of labs. It would be interesting to incorporate more general group operations, such as affine transformation and domain randomization techniques, to handle deformed images. Another interesting future direction is extending our work to continual multi-agent RL settings.

References

[1] C. Finn, P. Abbeel, and S. Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, pages 1126–1135. PMLR, 2017.

[2] A. Nagabandi, C. Finn, and S. Levine. Deep online learning via meta-learning: Continual adaptation for model-based rl. *arXiv preprint arXiv:1812.07671*, 2018.

[3] A. Nagabandi, I. Clavera, S. Liu, R. S. Fearing, P. Abbeel, S. Levine, and C. Finn. Learning to adapt in dynamic, real-world environments through meta-reinforcement learning. *arXiv preprint arXiv:1803.11347*, 2018.

[4] W. Zhao, J. P. Queralta, and T. Westerlund. Sim-to-real transfer in deep reinforcement learning for robotics: a survey. In *2020 IEEE Symposium Series on Computational Intelligence (SSCI)*, pages 737–744. IEEE, 2020.

[5] K. Khetarpal, M. Riemer, I. Rish, and D. Precup. Towards continual reinforcement learning: A review and perspectives. *Journal of Artificial Intelligence Research*, 75:1401–1476, 2022.

[6] K. Khetarpal, M. Riemer, I. Rish, and D. Precup. Towards continual reinforcement learning: A review and perspectives. *arXiv preprint arXiv:2012.13490*, 2020.

[7] M. Xu, W. Ding, J. Zhu, Z. Liu, B. Chen, and D. Zhao. Task-agnostic online reinforcement learning with an infinite mixture of gaussian processes. *Advances in Neural Information Processing Systems*, 33:6429–6440, 2020.

[8] H. Ren, A. Sootla, T. Jafferjee, J. Shen, J. Wang, and H. Bou-Ammar. Reinforcement learning in presence of discrete markovian context evolution. *arXiv preprint arXiv:2202.06557*, 2022.

[9] A. Xie, J. Harrison, and C. Finn. Deep reinforcement learning amidst continual structured non-stationarity. In *International Conference on Machine Learning*, pages 11393–11403. PMLR, 2021.

[10] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[11] S. Thrun and T. M. Mitchell. Lifelong robot learning. *Robotics and autonomous systems*, 15 (1-2):25–46, 1995.

[12] F. Tanaka and M. Yamamura. An approach to lifelong reinforcement learning through multiple environments. In *6th European Workshop on Learning Robots*, pages 93–99, 1997.

[13] Z. Chen and B. Liu. Lifelong machine learning. *Synthesis Lectures on Artificial Intelligence and Machine Learning*, 12(3):1–207, 2018.

[14] D. Rolnick, A. Ahuja, J. Schwarz, T. Lillicrap, and G. Wayne. Experience replay for continual learning. *Advances in Neural Information Processing Systems*, 32, 2019.

[15] M. Xu, Z. Liu, P. Huang, W. Ding, Z. Cen, B. Li, and D. Zhao. Trustworthy reinforcement learning against intrinsic vulnerabilities: Robustness, safety, and generalizability. *arXiv preprint arXiv:2209.08025*, 2022.

[16] J. Kirkpatrick, R. Pascanu, N. Rabinowitz, J. Veness, G. Desjardins, A. A. Rusu, K. Milan, J. Quan, T. Ramalho, A. Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526, 2017.

[17] S. Powers, E. Xing, E. Kolve, R. Mottaghi, and A. Gupta. Cora: Benchmarks, baselines, and metrics as a platform for continual reinforcement learning agents. In *Conference on Lifelong Learning Agents*, pages 705–743. PMLR, 2022.

[18] H. Ahn, S. Cha, D. Lee, and T. Moon. Uncertainty-based continual learning with adaptive regularization. *Advances in neural information processing systems*, 32, 2019.

[19] R. Traoré, H. Caselles-Dupré, T. Lesort, T. Sun, G. Cai, N. Díaz-Rodríguez, and D. Filliat. Discorl: Continual reinforcement learning via policy distillation. *arXiv preprint arXiv:1907.05855*, 2019.

[20] S. Sæmundsson, K. Hofmann, and M. P. Deisenroth. Meta reinforcement learning with latent variable gaussian processes. *arXiv preprint arXiv:1803.07551*, 2018.

[21] W. Yu, J. Tan, C. K. Liu, and G. Turk. Preparing for the unknown: Learning a universal policy with online system identification. *arXiv preprint arXiv:1702.02453*, 2017.

[22] M. Caccia, J. Mueller, T. Kim, L. Charlin, and R. Fakoor. Task-agnostic continual reinforcement learning: In praise of a simple baseline. *arXiv preprint arXiv:2205.14495*, 2022.

[23] A. Chaudhry, M. Rohrbach, M. Elhoseiny, T. Ajanthan, P. K. Dokania, P. H. Torr, and M. Ranzato. Continual learning with tiny episodic memories. 2019.

[24] B. Ravindran and A. G. Barto. Symmetries and model minimization in markov decision processes, 2001.

[25] B. Ravindran and A. G. Barto. Approximate homomorphisms: A framework for non-exact minimization in markov decision processes. 2004.

[26] E. van der Pol, D. Worrall, H. van Hoof, F. Oliehoek, and M. Welling. Mdp homomorphic networks: Group symmetries in reinforcement learning. *Advances in Neural Information Processing Systems*, 33:4199–4210, 2020.

[27] E. van der Pol, H. van Hoof, F. A. Oliehoek, and M. Welling. Multi-agent mdp homomorphic networks. *arXiv preprint arXiv:2110.04495*, 2021.

[28] D. Wang, R. Walters, and R. Platt. So (2) equivariant reinforcement learning. In *International conference on learning representations (ICLR)*, 2022.

[29] D. Wang, R. Walters, X. Zhu, and R. Platt. Equivariant q learning in spatial action spaces. In *Conference on Robot Learning*, pages 1713–1723. PMLR, 2022.

[30] L. Zhao, X. Zhu, L. Kong, R. Walters, and L. L. Wong. Integrating symmetry into differentiable planning with steerable convolutions. In *The Eleventh International Conference on Learning Representations*, 2023.

[31] D. Wang, J. Y. Park, N. Sortur, L. L. Wong, R. Walters, and R. Platt. The surprising effectiveness of equivariant models in domains with latent symmetry. *arXiv preprint arXiv:2211.09231*, 2022.

[32] X. Zhu, D. Wang, O. Biza, G. Su, R. Walters, and R. Platt. Sample efficient grasp learning using equivariant models. *arXiv preprint arXiv:2202.09468*, 2022.

[33] T. Cohen and M. Welling. Group equivariant convolutional networks. In *International conference on machine learning*, pages 2990–2999. PMLR, 2016.

[34] F. Fuchs, D. Worrall, V. Fischer, and M. Welling. Se (3)-transformers: 3d roto-translation equivariant attention networks. *Advances in Neural Information Processing Systems*, 33:1970–1981, 2020.

[35] M. J. Hutchinson, C. Le Lan, S. Zaidi, E. Dupont, Y. W. Teh, and H. Kim. Lietransformer: Equivariant self-attention for lie groups. In *International Conference on Machine Learning*, pages 4533–4543. PMLR, 2021.

[36] M. Weiler and G. Cesa. General e (2)-equivariant steerable cnns. *Advances in Neural Information Processing Systems*, 32, 2019.

[37] M. Finzi, M. Welling, and A. G. Wilson. A practical method for constructing equivariant multilayer perceptrons for arbitrary matrix groups. In *International Conference on Machine Learning*, pages 3318–3328. PMLR, 2021.

[38] G. Cesa, L. Lang, and M. Weiler. A program to build e(n)-equivariant steerable CNNs. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=WE4qe9xlnQw.

[39] V. I. Bogachev and A. V. Kolesnikov. The monge-kantorovich problem: achievements, connections, and perspectives. *Russian Mathematical Surveys*, 67(5):785, 2012.

[40] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Conference on Robot Learning*, pages 1094–1100. PMLR, 2020.

[41] S. Bahl, A. Gupta, and D. Pathak. Human-to-robot imitation in the wild. *arXiv preprint arXiv:2207.09450*, 2022.

[42] B. Bakker. Reinforcement learning with long short-term memory. *Advances in neural information processing systems*, 14, 2001.

[43] P. I. Etingof, O. Golberg, S. Hensel, T. Liu, A. Schwendner, D. Vaintrob, and E. Yudovina. *Introduction to representation theory*, volume 59. American Mathematical Soc., 2011.