Efficient Imitation Under Misspecification

Nicolas Espinosa-Dice,[*] **Sanjiban Choudhury, Wen Sun**
Department of Computer Science
Cornell University
{ne229,sc2582,ws455}@cornell.edu

Gokul Swamy
Robotics Institute
Carnegie Mellon University
gswamy@cmu.edu

Abstract

Interactive imitation learning (IL) is a powerful paradigm for learning to make sequences of decisions from an expert demonstrating how to perform a task. Prior work in efficient imitation learning has focused on the *realizable* setting, where the expert's policy lies within the learner's policy class (i.e. the learner can perfectly imitate the expert in all states). However, in practice, perfect imitation of the expert is often impossible due to differences in state information and action space expressiveness (e.g. morphological differences between robots and humans.) In this paper, we consider the more general *misspecified setting*, where no assumptions are made about the expert policy's realizability. We introduce a novel structural condition, *reward-agnostic policy completeness*, and prove that it is sufficient for interactive IL algorithms to efficiently avoid the quadratically compounding errors that stymie offline approaches like behavioral cloning. We address an additional practical constraint—the case of limited expert data—and propose a principled method for using additional sub-optimal data to further improve the sample-efficiency of interactive IL algorithms. Finally, we empirically investigate the optimal reset distribution in IRL under misspecification with a suite of continuous control tasks.

1 Introduction

Interactive imitation learning (IL) is a powerful paradigm for learning to make sequences of decisions from an expert demonstrating how to perform a task. While offline imitation learning approaches suffer from covariate shift between the training distribution (i.e. the expert's state distribution) and the test distribution (i.e. the learner's state distribution), interactive approaches enable the learner to roll-out its policy during train-time, effectively allowing it to train on states from the test distribution (Ross et al., 2011).

Broadly speaking, the difference between the expert's performance and the learned policy's performance can be attributed to three forms of error:

1. *Optimization error*: The error resulting from imperfect search within a policy class (e.g. due to non-convexity)
2. *Finite sample error*: The statistical error arising from limited expert demonstrations
3. *Misspecification error*: The irreducible error resulting from the learner's policy class not containing the expert's policy

Notably, misspecification error is a function of the expert policy and the learner's policy class; it cannot be improved by a better algorithm or more computation. However, prior work in imitation learning has focused on the first two sources of error and has avoided the misspecification error by imposing *expert realizability*: the assumption that the expert policy is within the learner's policy class (Kidambi et al., 2021; Swamy et al., 2021a; 2022c; Xu et al., 2023; Swamy et al., 2023; Ren et al., 2024). In other words, expert realizability implies that the learner can perfectly imitate the expert's actions in *all* states.

Unfortunately, in practice, it is often impossible to imitate the expert perfectly due to differences in state information. In self-driving applications, autonomous vehicles often have distinct perception

---

[*]Correspondence to: Nicolas Espinosa Dice <ne229@cornell.edu>.

compared to human drivers, leading to the human expert having privileged information over the learner (Swamy et al., 2022b). Similarly, in legged locomotion, recent work has frequently used an expert policy trained with privileged information about the environment configuration, which is unknown in the real world and therefore unavailable to the learner (Kumar et al., 2021; 2022; Liang et al., 2024).

Realizability can also be an inaccurate assumption due to a learner's limited action space expressiveness. In humanoid robotics, the morphological differences between robots and humans prevent perfect human-to-robot motion retargeting (Zhang et al., 2024; He et al., 2024; Al-Hafez et al., 2023). More generally, physical robots face the problem of changing dynamics, due to wear and tear and manufacturing imperfections that result in varying link lengths and other physical properties between robots of the same make and model. It is, therefore, unreasonable to assume that realizability holds for robots of the same model.

In this paper, we consider the more general *misspecified* setting, where the learner is not *necessarily* capable of perfectly imitating the expert's behavior. We analyze how the misspecification error interrelates with the optimization and finite sample errors. More specifically, our paper addresses the question:

> *Under what conditions can interactive imitation learning in the misspecified setting avoid quadratically compounding errors, while retaining sample efficiency?*

The last two words of the preceding question are central to our study. By reducing the problem of imitation learning to reinforcement learning with a learned reward, interactive imitation learning approaches like inverse reinforcement learning (IRL; Ziebart et al. (2008); Ho & Ermon (2016)) face a similar exploration problem to that of reinforcement learning— in the worst case, needing to explore all paths through the state space to find one reward (e.g. a tree structured problem with sparse rewards) (Swamy et al., 2023). In order to focus the exploration on useful states, efficient imitation algorithms leverage the expert's state distribution. Rather than reset the learner to the true starting state distribution, the learner is instead reset to states from the expert's demonstrations, resulting in an exponential decrease in interaction complexity (Swamy et al., 2023). We refer to this family of reset-based techniques as *efficient IRL*. Intuitively, efficient IRL can be understood as replacing the hard problem of global reinforcement learning (RL) exploration to the local exploration problem of "staying on the expert's path."

However, prior work assumes that "staying on the expert's path" is possible by expert realizability (Swamy et al., 2023). In the misspecified setting, following the expert's path may not be possible for the learner, and it is thus unclear whether expert resets can introduce compounding errors. We address this open question with a novel structural condition that, crucially, does not imply expert realizability.

> **Contribution 1.** We define a new structural condition for the misspecification setting, *reward-agnostic policy completeness*, under which efficient imitation learning algorithms can avoid quadratically compounding errors.

In addition to expert realizability, prior work imposes two additional assumptions that are often untrue in practice. First, prior work assumes access to infinite expert data (Swamy et al., 2021a; 2023; Ren et al., 2024), which is unrealistic when collecting expert data is resource-intensive. For instance, the process of collecting expert data through robot teleoperation is laborious and requires human teleoperators (Fu et al., 2024). In the finite expert sample regime, there may only be partial coverage of the expert's true state distribution. However, for many problems of practical interest, there is often access to a larger source of offline data (e.g. poor teleoperation or imperfect driving). We propose using this data to complement a limited set of expert demonstrations, without compromising solution quality guarantees.

> **Contribution 2.** We propose a principled method for incorporating offline data to improve the sample efficiency of IRL and prove the conditions under which it is beneficial.

Prior work in efficient IRL only considers resets to the expert's state distribution, but in the misspecified setting, it is unknown whether resetting to states from an *unrealizable* expert policy is *always* beneficial.

> **Contribution 3.** We consider the question of what the optimal reset distribution is in the misspecified setting. We propose settings where the expert's state distribution is not the optimal reset distribution and empirically validate on a variety of continuous control and locomotion tasks.

We begin by defining the problem and postpone a discussion of related work to Appendix A.

2 IMITATION LEARNING IN THE MISSPECIFIED SETTING

Markov Decision Process. We consider a finite-horizon Markov Decision Process (MDP), $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, P_h, r^*, H, \mu \rangle$ (Puterman, 2014). $\mathcal{S}$ and $\mathcal{A}$ are the state space and action space, respectively. $P = \{P_h\}_{h=1}^H$ is the time-dependent transition function, where $P_h : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$ and Δ is the probability simplex. $r^* : \mathcal{S} \times \mathcal{A} \to [0, 1]$ is the ground-truth reward function, which is unknown, but we assume $r^* \in \mathcal{R}$, where $\mathcal{R}$ is a class of reward functions such that $r : \mathcal{S} \times \mathcal{A} \to [0, 1]$ for all $r \in \mathcal{R}$. H is the horizon, and $\mu \in \Delta(\mathcal{S})$ is the starting state distribution. Let $\Pi = \{\pi : \mathcal{S} \to \Delta(\mathcal{A})\}$ be the class of stationary policies. We assume Π and $\mathcal{R}$ are convex and closed. Let the class of non-stationary policies be defined by $\Pi^H = \{\pi_h : \mathcal{S} \to \Delta(\mathcal{A})\}_{h=1}^H$. A trajectory is given by $\tau = \{(s_h, a_h, r_h)\}_{h=1}^H$, where $s_h \in \mathcal{S}, a_h \in \mathcal{A}$, and $r_h = f(s_h, a_h)$ for some $f \in \mathcal{R}$. The distribution over trajectories formed by a policy is given by: $a_h \sim \pi(\cdot \mid s_h)$, $r_h = R_h(s_h, a_h)$, and $s_{h+1} \sim P_h(\cdot \mid s_h, a_h)$, for $h = 1, \ldots, H$. Let $d_{s_0,h}^\pi(s) = \mathbb{P}^\pi[s_h = s \mid s_0]$ and $d_{s_0}^\pi(s) = \frac{1}{H} \sum_{h=1}^H d_{s_0,h}^\pi(s)$. Overloading notation slightly, we have $d_\mu^\pi = \mathbb{E}_{s_0 \sim \mu} d_{s_0}^\pi$. We index the value function by the reward function, such that $V_r^\pi = \mathbb{E}_{\tau \sim \pi} \sum_{h=1}^H r(s_h, a_h)$. We do a corresponding indexing for the advantage function, which is defined as $A^\pi(s, a) := Q^\pi(s, a) - V^\pi(s)$. We will overload notation such that a state-action pair can be sampled from the visitation distributions, e.g. $(s, a) \sim d_\mu^\pi$ and $(s, a) \sim \rho_E$, as well as a state, e.g. $s \sim d_\mu^\pi$ and $s \sim \rho_E$.

Expert Policy. As previous stated, much of the theoretical analysis in IL relies on the impractical assumption of a realizable expert policy (i.e. one that lies within the learner's policy class Π) (Kidambi et al., 2021; Swamy et al., 2021a;b; 2022a; Xu et al., 2023; Ren et al., 2024). In contrast to prior work, *we focus on the more realistic misspecified setting*, where the expert policy π_E is not necessarily in the policy class Π. We consider a known sample of the expert policy's trajectories, where the dataset of state-action pairs sampled from the expert is $D_E = D_1 \cup D_2 \cup \ldots \cup D_H$, where $D_h = \{s_h, a_h\} \sim d_{\mu,h}^{\pi_E}$ and $|D_E| = N$. Let ρ_h be a uniform distribution over the samples in D_h, and ρ_E be a uniform distribution over the samples in D_E.

Goal of IRL. We cast IRL as a Nash equilibrium computation (Syed & Schapire, 2007; Swamy et al., 2021a). The ultimate objective of IRL is to learn a policy that matches expert performance. Because the ground-truth reward is unknown but belongs to the reward class, we aim to learn a policy that performs well under any reward function in the reward class. This is equivalent to finding the best policy under the *worst-case* reward (i.e. the reward function that maximizes the performance difference between the expert and learner). Formally, we find an equilibrium strategy for the game

$$\min_{\pi \in \Pi} \max_{r \in \mathcal{R}} J(\pi_E, r) - J(\pi, r), \qquad (1)$$

where $J(\pi, r) = \mathbb{E}_{\tau \sim \pi} \left[\sum_{t=0}^T r(s_t, a_t) \right]$.

IRL Taxonomy. IRL algorithms consist of two steps: a reward update and a policy update. In the reward update, a *discriminator* is learned with the aim of differentiating the expert and learner trajectories. The policy is then optimized by an RL algorithm, with reward labels from the discriminator. IRL algorithms can be classified into *primal* and *dual* variants (Swamy et al., 2021a), the latter of which we use in our paper. An example dual algorithm is shown in Algorithm 1. In dual-variant IRL algorithms, the discriminator is updated slowly via a no-regret step (e.g. Line 5, Follow The Regularized Leader McMahan (2011)), and the policy is updated via a best response (e.g. Line 7, PSDP, Algorithm 3) using an RL subroutine with reward labels r (Ratliff et al., 2006; 2009; Ziebart et al., 2008; Swamy et al., 2021a).

Algorithm 1 Reset-Based IRL (Dual, Swamy et al. (2023))

1: **Input:** Expert state-action distributions ρ_E, policy class Π, reward class $\mathcal{R}$
2: **Output:** Trained policy π
3: **for** $i = 1$ to N **do**
4:     `//No-regret step over rewards (e.g. FTRL)`
5:     $r_i \leftarrow \arg\max_{r \in \mathcal{R}} J(\pi_E, r) - J(\mathrm{Unif}(\pi_{1:i}), r)$
6:     `//Expert-competitive response by RL algorithm (e.g. PSDP, Alg. 3)`
7:     $\pi_i \leftarrow \mathrm{RL}(r = r_i, \rho = \rho_E)$
8: **end for**
9: **Return** π_N

Reset Distribution. RL algorithms require a reset distribution be specified. Often, this is simply the MDP's starting state distribution, μ (Mnih, 2013; Schulman et al., 2015; 2017; Haarnoja et al., 2018). Because IRL algorithms use an RL subroutine, we differentiate between traditional IRL and efficient IRL by their RL subroutine's reset distribution, ρ. In traditional IRL algorithms, the reset distribution remains the true starting state distribution (i.e. $\rho = \mu$). In efficient IRL algorithms, the reset distribution is the expert's state distribution (i.e. $\rho = \rho_E$), which changes the RL subroutine from a best response step to an expert-competitive response (Swamy et al., 2023; Ren et al., 2024). Swamy et al. (2023) proved that using the expert's state distribution in the realizable setting sped up learning without compromising solution quality.

2.1 EFFICIENT IMITATION UNDER MISSPECIFICATION IS HARD

Our paper considers efficient IRL in the misspecified setting, to which the obvious question arises:

Is efficient IRL possible in the misspecified setting?

Efficiency is measured with respect to environment interactions, and we consider polynomial interaction complexity in the MDP's horizon as efficient. We start by considering the most general setting of IRL, where no assumptions are made about the MDP's structure, the policy class, or the expert's policy (i.e., we do not assume $\pi_E \in \Pi^H$). We present a lower bound on efficient IRL that shows, in general, efficient IRL under misspecification is not possible.

Theorem 2.1 (Lower Bound on Misspecified RL with Expert Feedback (Jia et al., 2024)). *For any $H \in \mathbb{N}$ and $C \in [2^H]$, there exists a policy class Π with $|\Pi| = C$, expert policy $\pi_E \notin \Pi$, and a family of MDPs $\mathcal{M}$ with state space $\mathcal{S}$ of size $O(2^H)$, binary action space, and horizon H such that any algorithm that returns a 1/4-optimal policy must either use $\Omega(C)$ queries to the expert oracle $O_{exp} : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$, which returns $Q^{\pi_E}(s, a)$ (i.e. the Q value of expert policy π_E), or $\Omega(C)$ queries to a generative model.*

From Theorem 2.1, we establish that polynomial sample complexity in the misspecified IRL setting, where $\pi_E \notin \Pi$, cannot be guaranteed. In other words, efficient IRL is not possible with no structure assumed on the MDP, even with access to a queryable expert policy like DAgger (Ross et al., 2011). Notably, this lower bound focuses on *sample* efficiency. *Statistically* efficient—with respect to the amount of expert data—imitation *is* possible. We present a statistically optimal imitation learning algorithm for the misspecified setting, **S**cheffé **T**ournament **I**mitation **LE**arning (STILE), in Appendix C.

Theorem 2.2 (Sample Complexity of STILE under Misspecification). *Assume Π is finite, but $\pi_E \notin \Pi$. With probability at least $1 - \delta$, STILE learns a policy $\hat{\pi}$ such that:*

$$V^{\pi_E} - V^{\hat{\pi}} \leq \frac{3}{1-\gamma} \min_{\pi \in \Pi} \|d^\pi - d^{\pi_E}\|_1 + \tilde{O}\left(\frac{1}{1-\gamma}\sqrt{\frac{\ln(|\Pi|) + \ln(1/\delta)}{M}}\right) \qquad (2)$$

Notably, the sample complexity of STILE is linear in the horizon (for convenience in the analysis, we consider an infinite horizon MDP). However, running a tournament algorithm requires comparing every pair of policies, which is not feasible with policy classes like deep neural networks, making STILE impractical to implement.

3 Policy Complete Inverse Reinforcement Learning

The result from Section 2.1 establishes that sample computationally efficient IRL in the misspecified setting is not possible without assuming additional structure on the MDP, begging the question of what assumptions suffice. We provide an answer via an extension of *policy completeness*— a condition used in the analysis of policy gradient RL algorithms—and a corresponding efficient algorithm.

3.1 Approximate Policy Completeness

Intuitively, the policy completeness condition requires that the learner have a way of improving the current policy's performance—*without* the requirement of matching the actions of the optimal (i.e. expert) policy—if some improvement is possible. Importantly, the policy completeness condition of RL algorithms depends on the MDP's reward function, which in the inverse reinforcement learning setting is unknown and is instead learned throughout training. In response, we introduce *reward-agnostic policy completeness*, the natural generalization of policy completeness extended to the imitation learning setting.

Definition 3.1 (Reward-Indexed Policy Completeness Error). *Given some expert state distribution ρ_E, MDP $\mathcal{M}$ with policy class Π and reward class $\mathcal{R}$, learned policy π_i, and learned reward function r_i, define the reward-indexed policy completeness error of $\mathcal{M}$ to be*

$$\epsilon_\Pi^{\pi_i, r_i} := \mathbb{E}_{s \sim \rho_E} \left[\max_{a \in \mathcal{A}} A_{r_i}^{\pi_i}(s, a) \right] - \max_{\pi' \in \Pi} \mathbb{E}_{s \sim \rho_E} \mathbb{E}_{a \sim \pi'(\cdot|s)} \left[A_{r_i}^{\pi_i}(s, a) \right]. \tag{3}$$

We first present *reward-indexed policy completeness error*, which measures the policy class's ability to approximate the maximum possible advantage over the current policy. Intuitively, we can think of the second term as the learner's ability to improve the policy based on its policy class, and the first term as the maximum possible improvement over all policies, including those not in the policy class.

Recall that, at each iteration, IRL algorithms compute a policy and reward function (π_i and r_i, respectively) from the policy and reward classes (Π and $\mathcal{R}$, respectively). We measure the worst-case policy completeness error that can be attained during IRL training by adversarially selecting the learned policy and reward function.

Definition 3.2 (Reward-Agnostic Policy Completeness Error). *Given some expert state distribution ρ_E and MDP $\mathcal{M}$ with policy class Π and reward class $\mathcal{R}$, define the reward-agnostic policy completeness error of $\mathcal{M}$ to be*

$$\epsilon_\Pi := \max_{\pi \in \Pi, r \in \mathcal{R}} \epsilon_\Pi^{\pi, r} \tag{4}$$

Reward-agnostic policy completeness is therefore a measure of the policy class's ability to approximate the maximum possible advantage, over the expert's state distribution, under any reward function in the reward class. Note that $0 \leq \epsilon_\Pi^{\pi_i, r_i} \leq \epsilon_\Pi \leq H$ for any $\pi_i \in \Pi$, $r_i \in \mathcal{R}$. In the *approximate policy completeness* setting, we assume $\epsilon_\Pi = O(1)$.

3.2 Efficient IRL with Approximate Policy Completeness

We begin by presenting our efficient, reset-based IRL algorithm, **GU**iding **I**mi**T**aters with **A**rbitrary **R**oll-ins (`GUITAR`), before proving its policy performance bounds under approximate policy completeness. The full IRL procedure is outlined in Algorithm 2. Existing efficient IRL algorithms, such as MMDP (Swamy et al., 2023), reset the learner exclusively to expert states (i.e. the case where $\rho = \rho_E$). `GUITAR` can be seen as extending MMDP to a general reset distribution in the misspecified setting. We will focus on expert resets in the misspecified setting first, and we then consider other reset distributions in Section 4. For a more thorough description of the algorithm and its updates, see Appendix D.

Policy Update. Following Ren et al. (2024)'s reduction of inverse RL to expert-competitive RL, we can use any RL algorithm to generate an expert-competitive response. We employ Policy Search by Dynamic Programming (PSDP, Bagnell et al. (2003)), shown in Algorithm 3, for its strong theoretical guarantees. In practice, any RL algorithm can be used, such as Soft Actor Critic (SAC, Haarnoja et al. (2018)).

Algorithm 2 GUiding ImiTaters with Arbitrary Roll-ins (`GUITAR`)

1: **Input:** Expert state-action distributions ρ_E, mixture of expert and offline state-action distributions ρ_{mix}, policy class Π, reward class $\mathcal{R}$
2: **Output:** Trained policy π
3: Set $\pi_0 \in \Pi$
4: **for** $i = 1$ to N **do**
5:     Let
$$\hat{L}(\pi, r) = \mathbb{E}_{(s,a)\sim\rho_E} r(s,a) - \mathbb{E}_{(s,a)\sim d^\pi_\mu} r(s,a) \text{ // Loss function} \tag{5}$$
6:     Optimize
$$r_i = \texttt{OMD}(\pi_1, \ldots, \pi_{i-1}) \text{ // Reward's no-regret update} \tag{6}$$
7:     Optimize
$$\pi_i = \texttt{PSDP}(r = r_i, \rho = \rho_{\text{mix}}) \text{ // RL's expert-competitive response} \tag{7}$$
8: **end for**
9: **Return** π_i with lowest validation error

Reward Update. We employ a no-regret update to the reward function. We employ Online Mirror Descent (OMD, Nemirovskij & Yudin (1983)) for its strong theoretical guarantees (Beck & Teboulle, 2003; Srebro et al., 2011), but in practice, any no-regret update can be used, such as gradient descent.

3.3 ANALYSIS IN THE INFINITE-SAMPLE REGIME

For clarity, we first present the sample complexity of Algorithm 2 in the infinite expert sample regime (i.e., when we have infinite samples from the expert policy, so $\rho_E = d^{\pi_E}_\mu$). We present the bound in the finite sample regime in Appendix F.2.

Theorem 3.3 (Sample Complexity of Algorithm 2). *Consider the case of infinite expert data samples, such that $\rho_E = d^{\pi_E}_\mu$. Denote $\pi_i = (\pi_{i,1}, \pi_{i,2}, \ldots, \pi_{i,H})$ as the policy returned by ϵ-approximate PSDP at iteration $i \in [n]$ of Algorithm 2. Then,*

$$V^{\pi_E} - V^{\overline{\pi}} \leq \underbrace{H\epsilon_\Pi}_{\textit{Misspecification Error}} + \underbrace{H^2\epsilon}_{\textit{Policy Optimization Error}} + \underbrace{H\sqrt{\frac{\ln|\mathcal{R}|}{n}}}_{\textit{Reward Regret}}, \tag{8}$$

where H is the horizon, n is the number of outer-loop iterations of the algorithm, and $\overline{\pi}$ is the trajectory-level average of the learned policies (i.e. π_i at each iteration $i \in [n]$ of Algorithm 2).

Misspecification Error. The error is comprised of three terms. The first term, $H\epsilon_\Pi$, stems from the richness of the policy class. In the worst case where the policy class cannot approximate the maximum advantage, $\epsilon_\Pi = H$, resulting in quadratically compounding errors. Unlike the policy optimization error, the policy completeness error cannot be reduced with more environment interactions. Instead, it represents a fixed error that is a property of the MDP, the policy class, and the reward class. Under the approximate policy completeness setting, we assume $\epsilon_\Pi = O(1)$, reducing the error to linear in the horizon, without requiring $\pi_E \in \Pi$.

Policy Optimization Error. The second term, $H^2\epsilon$, stems from the policy optimization error of PSDP. It can be mitigated be improving the accuracy parameter ϵ of PSDP. Set to $\epsilon = \frac{1}{H}$, the term is reduced to linear error in the horizon H. This error can be interpreted as representing a tradeoff between environment interactions (i.e. computation) and error.

Reward Regret. Finally, the last term, $H\sqrt{\frac{\ln|\mathcal{R}|}{n}}$, stems from the regret of the Online Mirror Descent update to the reward function. By the no-regret property, we can reduce this term (to zero) by running more outer-loop iterations of `GUITAR`.

In short, with sufficient iterations of Algorithm 2, GUITAR can avoid quadratically compounding errors under approximate policy completeness, even in the misspecified setting.

Figure 1: In the MDPs above, π_E selects the green actions, a_1, and $\Pi = \{\pi\}$, where π selects the orange actions, a_2. The reward class $\mathcal{R}$ contains one reward function shown in the figure. The shaded region in (c) shows states unreachable by the learner at test time due to safety constraints. (d) shows the expert's MDP (left) and the learner's MDP (right) with different states.

4 INCORPORATING OFFLINE DATA IN MISSPECIFIED IRL

In Section 3, we proved a condition under which efficient IRL with expert resets avoids quadratically compounding error in the misspecified setting, but is resetting to states from an *unrealizable* expert policy *always* beneficial? This question remains unaddressed by prior work, and we consider two practical settings where expert resets may not be optimal: *(a)* the finite expert sample regime, and *(b)* regimes with strong misspecification. We tackle *(a)* in this section and *(b)* in Section 5.

In particular, in this section we consider the practical setting of having limited expert data but an additional source of offline data. How to use offline data in IRL remains an open question. Prior work has used sub-optimal data in IRL to learn reward functions (Brown et al., 2019; Brown & Niekum, 2019; Poiani et al., 2024), but such an approach requires strong assumptions about the data's structure. Without sufficient structure, incorporating the sub-optimal data into the discriminator update (i.e. the reward function) would result in the offline behavior being valued as optimal—an undesirable training outcome.

In our paper, we propose incorporating offline data into the reset distribution, thereby using it for policy optimization but not reward learning. Unlike prior work, our approach requires minimal assumptions on the offline data and maintains the strong performance guarantees from Section 3. We formalize our approach below.

4.1 AUGMENTING RESET DISTRIBUTIONS WITH OFFLINE DATA

We consider access to some offline dataset $D_{\text{off}} = \{s_i, a_i\}_{i=1}^M$, where $(s, a) \sim d_\mu^{\pi_B}$ and π_B is some behavior policy that is not necessarily as a high-quality as the expert π_E. We measure the overlap of π_B to the expert π_E using the standard concentrability coefficient

$$C_B := \left\| \frac{d_\mu^{\pi_E}}{d_\mu^{\pi_B}} \right\|_\infty < \infty \tag{9}$$

This can be thought of intuitively as requiring that if the expert visits a state, the offline dataset does too, but not necessarily with an equal visitation frequency. In other words, the offline data *covers* the expert data. Our approach of using offline data for resets requires no change to the structure of Algorithm 2. We simply set PSDP's reset distribution to the mixture of offline and expert states, $\rho = \rho_{\text{mix}}$, where we define $D_{\text{mix}} = D_E \cup D_{\text{off}}$ and ρ_{mix} as the uniform distribution over D_{mix}. We weight the two distributions $\nu := \frac{N}{N+M} d_\mu^{\pi_E} + \frac{M}{N+M} d_\mu^{\pi_B}$. The reward update remains the same. The only modification to ϵ_Π is a change in the state distribution, replacing the distribution over expert samples, ρ_E, with the mixed distribution, ρ_{mix}, which we explicitly denote by $\epsilon_\Pi^{\rho_{\text{mix}}}$ unless it is clear from context.

4.2 WHEN IS OFFLINE DATA BENEFICIAL IN IRL?

Next, we answer the natural question of when offline resets are beneficial to IRL.

Figure 2: **Varying importance of expert states for resets.** Standard errors are computed across 10 seeds. During evaluation, agents sample a random action with probability $p_{tremble}$.

Corollary 4.1 (Benefit of Offline Data). *Incorporating offline data into the reset distribution improves the sample efficiency of IRL when*

$$\left\|\frac{d_\mu^{\pi_E}}{d_\mu^{\pi_B}}\right\|_\infty \left(\epsilon_\Pi^{\rho_{mix}} + \epsilon_\Pi^{\rho_{mix}}\sqrt{\frac{C_{\Pi,\mathcal{R}}}{N+M}}\right) < \epsilon_\Pi^{\rho_{mix}} + \epsilon_\Pi^{\rho_{mix}}\sqrt{\frac{C_{\Pi,\mathcal{R}}}{N}} \tag{10}$$

where N is the number of expert state-action pairs, M is the number of offline state-action pairs, and $C_{\Pi,\mathcal{R}} = \ln\frac{|\Pi||\mathcal{R}|}{\delta}$.

Corollary 4.1 presents a sufficient condition for offline data improving GUITAR's sample efficiency *over* the algorithm with resets strictly to expert data. We observe that the benefit of offline data depends on the how well the offline data covers the expert data, as well as the amount of expert and offline data. Intuitively, we can think of the coverage coefficient C_B as the "exchange rate," measuring how useful the offline data is in comparison to the expert data. When the offline data covers the expert data well, C_B is small, so the offline data may be beneficial. Considering the special case where the "offline" data is collected from the expert policy π_E, then $C_B = 1$. The bound becomes equivalent to the case of having $N + M$ number of expert data samples.

However, one should also observe the dependence on the policy completeness term, $\epsilon_\Pi^{\rho_{mix}}$. The policy completeness term measures how flexible or rich the policy class is on a given state distribution, in this case the mixture of the data ρ_{mix}. Thus, the condition can be interpreted as representing a trade-off between the offline data's coverage of the expert data and the richness of the policy class on the data's state distribution. We present the full finite sample analysis in Appendix F and empirical results in Appendix H.

5 RESET DISTRIBUTIONS UNDER MISSPECIFICATION

In Section 4, we theoretically examined a setting where the expert's state distribution is not the optimal reset distribution. In this section, we empirically investigate this question, focusing on settings with strong misspecification.

For the experiments in this section, we compare our algorithm, GUITAR, against two behavioral cloning baselines (Pomerleau, 1988) and two IRL baselines (Swamy et al., 2023; 2021a). One behavioral cloning baseline is trained exclusively on the expert data, BC(π_E), and the second is trained with both expert and offline data, BC($\pi_E + \pi_b$), when offline data is available. We consider a traditional IRL algorithm, MM, and an efficient IRL algorithm, FILTER (Swamy et al., 2021a; 2023). We train all IRL algorithms with the same expert data and hyperparameters. The difference between MM, FILTER, and GUITAR can be summarized by the reset distribution they use. MM resets the learner to the true starting state (i.e. $\rho = \mu$), while FILTER resets the learner to expert states (i.e. $\rho = \rho_E$). GUITAR resets the learner to offline data (i.e. $\rho = \rho_B$), when offline data is available, and otherwise resets to subsets of the expert data. For more details on the setup and implementations used in this section's experiments, refer to Appendix G.

(a) Unrealizable expert actions (b) Unrealizable expert states

Figure 3: **Unrealizable expert actions and states.** (b) is unrealizable due to imposed safety constraints. π^* indicates the best *realizable* policy. Standard errors are computed across 10 seeds (a) and 5 seeds (b).

5.1 Varying State Importance in Expert Resets

First, we consider a setting not exclusive to misspecification, under which we posit that the optimal reset distribution is a subset of the expert's state distribution. These MDPs may contain multiple optimal paths to the goal, as shown in Figure 1a, where the key states to reset to are those with poor recoverability (i.e. states $S_1, \ldots, S_4$ in the figure). We characterize the setting where the reset distribution ρ is a subset of the expert's state distribution as

$$C_E := \left\| \frac{\rho}{d_\mu^{\pi_E}} \right\|_\infty < \infty \tag{11}$$

To empirically investigate this setting, we consider the D4RL `Antmaze-Large` tasks, where the expert data comes from the D4RL dataset. For `GUITAR`, we isolate all short trajectories (D_{short}) and all long trajectories (D_{long}) in the expert dataset. We compare `GUITAR`(D_{short}) and `GUITAR`(D_{long}), which reset to short and long trajectories, respectively.

In Figure 2, we observe that using the short-trajectory dataset as the reset distribution performs comparably to the full expert dataset, suggesting that full coverage of the expert's state distribution is not necessary. However, as demonstrated by the long-trajectory dataset failing to solve the problem, there are also subsets of the expert's state distribution that adversely affect learning. Crucially, we observe a difference in the coverage of the reset distributions when visualized in Figure 5, with the short-trajectory dataset having more focused coverage (i.e. coverage closer to goals).

5.2 Misspecified Setting 1: Unrealizable Expert Actions

We now consider the setting of misspecification due to unrealizable expert actions: settings where the learner cannot imitate the expert's actions in certain states. Consider, for example, that humans often have more degrees of freedom than robots. This setting is visually depicted in Figure 1b, where the learner's policy class is deficient on expert states. The efficient IRL problem in the constructed MDP is reduced to performing RL with resets. Intuitively, the RL optimization problem over π_E's state distribution (the green states) is harder than over π's state distribution (the orange states): the learner can never reach the optimal realizable policy from expert states, other than the starting state.

For this setting, we instead consider the best *realizable* policy: $\pi^\star := \max_{\pi \in \Pi} J(\pi, r^*)$ In other words, $\pi^\star$ the best policy *in* the learner's policy class under the ground-truth reward function. Since $\pi^\star \in \Pi$ and the expert's actions are unrealizable, we consider the strongest misspecification being when $\pi^\star$'s overlap with the expert's state distribution is small: $\text{Supp}(d_\mu^{\pi_E}) \cap \text{Supp}(d_\mu^{\pi^\star}) \approx 0$. We can measure the reset distribution's coverage of $\pi^\star$ via the standard concentrability coefficient:

$$C_S := \left\| \frac{d_\mu^{\pi^\star}}{\rho} \right\|_\infty < \infty \tag{12}$$

where ρ is the reset distribution for IRL. We theoretically analyze this setting in Appendix I.

To empirically investigate this setting, we consider a variant of the `Antmaze-Umaze` task, where a quadruped ant learns to solve a maze to reach a goal position (Fu et al., 2020). The expert can

Figure 4: **Unrealizable expert states due to morphological differences between expert and learner.** Standard errors are computed across 10 seeds.

solve the maze following the typical path through the Umaze, but the learner's behavior is restricted via a block in the maze, forcing it to find a different route through the maze to reach the goal. In this setting, we have access to data from an *unrealizable* expert policy, π_E, and offline data from a *realizable* behavioral policy, π_B, which GUITAR uses for resets. From Figure 3a, we observe that GUITAR is the only interactive algorithm capable of solving the hard exploration problem in the strongly misspecified setting, confirming that the offline data—states from a behavior policy—is a better reset distribution than expert states in this task.

5.3 MISSPECIFIED SETTING 2: UNREALIZABLE EXPERT STATES DUE TO SAFETY CONSTRAINTS

Next, we consider the setting of unrealizable expert states. In practice, we may wish to restrict the states that the robot may visit. For example, a human expert may demonstrate multiple tasks throughout the kitchen, including washing dishes and operating the stove, but the robot is restricted from moving near the stove. We visually depict this setting in Figure 1c. Theoretically, this setting follows the characterization in Equation 11, where we consider reset distributions covered by the expert's state distribution.

To empirically investigate this setting, we consider a variant of the Antmaze-Umaze task, where the expert solves the task as normal, but the learner is restricted from moving into the bottom half of the maze (simulating a safety constraint). Instead, the learner focuses on traversing the first hallway. GUITAR resets to expert states in the "first hallway" of the task. From Figure 3b, we see that focusing GUITAR's reset distribution on the realizable expert states in the first hallway speeds up learning.

5.4 MISSPECIFIED SETTING 3: UNREALIZABLE EXPERT STATES DUE TO MORPHOLOGICAL DIFFERENCES

Finally, we consider the setting of unrealizable expert states due to morphological differences between the expert and the learner. In humanoid robotics, for example, the morphological differences between robots and humans prevent perfect human-to-robot motion retargeting (Zhang et al., 2024; He et al., 2024; Al-Hafez et al., 2023). Theoretically, this setting follows the characterization of Equation 12, where the support of the learner and expert's state distributions have minimal intersection.

To empirically investigate this setting, we consider MuJoCo continuous control tasks where the expert and learner have different morphology, implemented by changing the link lengths and joint ranges between the expert (which uses the default values) and the learner. In such a setting, it is impossible to reset the learner to expert states, and thus we cannot implement FILTER. For GUITAR, we reset the learner to states from a good quality behavior policy π_B, which has the same morphology as the learner. Figure 1d shows a speedup in learning enabled by using resets to the offline data. The consistently poor performance of the BC policies across the varying misspecified settings highlights the challenge of using offline data for model learning, as the approach is sensitive to distribution shifts. In contrast, the approach of using offline data for resets in interactive algorithms demonstrates stronger overall performance across tasks.

ACKNOWLEDGMENTS

NED is supported by DARPA LANCER: LeArning Network CybERagents. WS acknowledges funding from NSF IIS-2154711, NSF CAREER 2339395, and DARPA LANCER: LeArning Network CybERagents. GKS was supported in part by a STTR grant.

REFERENCES

Alekh Agarwal, Nan Jiang, Sham M Kakade, and Wen Sun. Reinforcement learning: Theory and algorithms. *CS Dept., UW Seattle, Seattle, WA, USA, Tech. Rep*, 32, 2019.

Firas Al-Hafez, Guoping Zhao, Jan Peters, and Davide Tateo. Locomujoco: A comprehensive imitation learning benchmark for locomotion. *arXiv preprint arXiv:2311.02496*, 2023.

Philip Amortila, Nan Jiang, Dhruv Madeka, and Dean P Foster. A few expert queries suffices for sample-efficient rl with resets and linear value approximation. *Advances in Neural Information Processing Systems*, 35:29637–29648, 2022.

James Bagnell, Sham M Kakade, Jeff Schneider, and Andrew Ng. Policy search by dynamic programming. *Advances in neural information processing systems*, 16, 2003.

Amir Beck and Marc Teboulle. Mirror descent and nonlinear projected subgradient methods for convex optimization. *Operations Research Letters*, 31(3):167–175, 2003.

Jalaj Bhandari and Daniel Russo. Global optimality guarantees for policy gradient methods. *Operations Research*, 2024.

Daniel Brown, Wonjoon Goo, Prabhat Nagarajan, and Scott Niekum. Extrapolating beyond suboptimal demonstrations via inverse reinforcement learning from observations. In *International conference on machine learning*, pp. 783–792. PMLR, 2019.

Daniel S Brown and Scott Niekum. Deep bayesian reward learning from preferences. *arXiv preprint arXiv:1912.04472*, 2019.

Constantinos Daskalakis, Andrew Ilyas, Vasilis Syrgkanis, and Haoyang Zeng. Training gans with optimism. *arXiv preprint arXiv:1711.00141*, 2017.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

Zipeng Fu, Tony Z Zhao, and Chelsea Finn. Mobile aloha: Learning bimanual mobile manipulation with low-cost whole-body teleoperation. *arXiv preprint arXiv:2401.02117*, 2024.

Scott Fujimoto and Shixiang Shane Gu. A minimalist approach to offline reinforcement learning. *Advances in neural information processing systems*, 34:20132–20145, 2021.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. *Advances in neural information processing systems*, 30, 2017.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pp. 1861–1870. PMLR, 2018.

Tairan He, Zhengyi Luo, Xialin He, Wenli Xiao, Chong Zhang, Weinan Zhang, Kris Kitani, Changliu Liu, and Guanya Shi. Omnih2o: Universal and dexterous human-to-humanoid whole-body teleoperation and learning. *arXiv preprint arXiv:2406.08858*, 2024.

Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. *Advances in neural information processing systems*, 29, 2016.

Zeyu Jia, Gene Li, Alexander Rakhlin, Ayush Sekhari, and Nati Srebro. When is agnostic reinforcement learning statistically tractable? *Advances in Neural Information Processing Systems*, 36, 2024.

Sham Kakade and John Langford. Approximately optimal approximate reinforcement learning. In *Proceedings of the Nineteenth International Conference on Machine Learning*, pp. 267–274, 2002.

Sham Machandranath Kakade. *On the sample complexity of reinforcement learning*. University of London, University College London (United Kingdom), 2003.

Rahul Kidambi, Jonathan Chang, and Wen Sun. Mobile: Model-based imitation learning from observation alone. *Advances in Neural Information Processing Systems*, 34:28598–28611, 2021.

Ashish Kumar, Zipeng Fu, Deepak Pathak, and Jitendra Malik. Rma: Rapid motor adaptation for legged robots. *arXiv preprint arXiv:2107.04034*, 2021.

Ashish Kumar, Zhongyu Li, Jun Zeng, Deepak Pathak, Koushil Sreenath, and Jitendra Malik. Adapting rapid motor adaptation for bipedal robots. In *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 1161–1168. IEEE, 2022.

Yichao Liang, Kevin Ellis, and João Henriques. Rapid motor adaptation for robotic manipulator arms. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16404–16413, 2024.

Brendan McMahan. Follow-the-regularized-leader and mirror descent: Equivalence theorems and l1 regularization. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pp. 525–533. JMLR Workshop and Conference Proceedings, 2011.

V Mnih. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Arkadij Semenovič Nemirovskij and David Borisovich Yudin. Problem complexity and method efficiency in optimization. 1983.

Riccardo Poiani, Gabriele Curti, Alberto Maria Metelli, and Marcello Restelli. Inverse reinforcement learning with sub-optimal experts. *arXiv preprint arXiv:2401.03857*, 2024.

Dean A Pomerleau. Alvinn: An autonomous land vehicle in a neural network. *Advances in neural information processing systems*, 1, 1988.

Martin L Puterman. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Antonin Raffin, Ashley Hill, Adam Gleave, Anssi Kanervisto, Maximilian Ernestus, and Noah Dormann. Stable-baselines3: Reliable reinforcement learning implementations. *Journal of Machine Learning Research*, 22(268):1–8, 2021.

Nived Rajaraman, Yanjun Han, Lin Yang, Jingbo Liu, Jiantao Jiao, and Kannan Ramchandran. On the value of interaction and function approximation in imitation learning. *Advances in Neural Information Processing Systems*, 34:1325–1336, 2021.

Nathan D Ratliff, J Andrew Bagnell, and Martin A Zinkevich. Maximum margin planning. In *Proceedings of the 23rd international conference on Machine learning*, pp. 729–736, 2006.

Nathan D Ratliff, David Silver, and J Andrew Bagnell. Learning to search: Functional gradient techniques for imitation learning. *Autonomous Robots*, 27:25–53, 2009.

Juntao Ren, Gokul Swamy, Zhiwei Steven Wu, J Andrew Bagnell, and Sanjiban Choudhury. Hybrid inverse reinforcement learning. *arXiv preprint arXiv:2402.08848*, 2024.

Stéphane Ross and Drew Bagnell. Efficient reductions for imitation learning. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 661–668. JMLR Workshop and Conference Proceedings, 2010.

Stéphane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 627–635. JMLR Workshop and Conference Proceedings, 2011.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International conference on machine learning*, pp. 1889–1897. PMLR, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Lior Shani, Tom Zahavy, and Shie Mannor. Online apprenticeship learning. In *Proceedings of the AAAI conference on artificial intelligence*, volume 36, pp. 8240–8248, 2022.

Yuda Song, Yifei Zhou, Ayush Sekhari, J Andrew Bagnell, Akshay Krishnamurthy, and Wen Sun. Hybrid rl: Using both offline and online data can make rl efficient. *arXiv preprint arXiv:2210.06718*, 2022.

Nati Srebro, Karthik Sridharan, and Ambuj Tewari. On the universality of online mirror descent. *Advances in neural information processing systems*, 24, 2011.

Gokul Swamy, Sanjiban Choudhury, J Andrew Bagnell, and Steven Wu. Of moments and matching: A game-theoretic framework for closing the imitation gap. In *International Conference on Machine Learning*, pp. 10022–10032. PMLR, 2021a.

Gokul Swamy, Sanjiban Choudhury, J Andrew Bagnell, and Zhiwei Steven Wu. A critique of strictly batch imitation learning. *arXiv preprint arXiv:2110.02063*, 2021b.

Gokul Swamy, Sanjiban Choudhury, Drew Bagnell, and Steven Wu. Causal imitation learning under temporally correlated noise. In *International Conference on Machine Learning*, pp. 20877–20890. PMLR, 2022a.

Gokul Swamy, Sanjiban Choudhury, J Bagnell, and Steven Z Wu. Sequence model imitation learning with unobserved contexts. *Advances in Neural Information Processing Systems*, 35:17665–17676, 2022b.

Gokul Swamy, Nived Rajaraman, Matt Peng, Sanjiban Choudhury, J Bagnell, Steven Z Wu, Jiantao Jiao, and Kannan Ramchandran. Minimax optimal online imitation learning via replay estimation. *Advances in Neural Information Processing Systems*, 35:7077–7088, 2022c.

Gokul Swamy, David Wu, Sanjiban Choudhury, Drew Bagnell, and Steven Wu. Inverse reinforcement learning without reinforcement learning. In *International Conference on Machine Learning*, pp. 33299–33318. PMLR, 2023.

Umar Syed and Robert E Schapire. A game-theoretic approach to apprenticeship learning. *Advances in neural information processing systems*, 20, 2007.

Luca Viano, Stratis Skoulakis, and Volkan Cevher. Imitation learning in discounted linear mdps without exploration assumptions. *arXiv preprint arXiv:2405.02181*, 2024.

Tian Xu, Ziniu Li, Yang Yu, and Zhi-Quan Luo. Provably efficient adversarial imitation learning with unknown transitions. In *Uncertainty in Artificial Intelligence*, pp. 2367–2378. PMLR, 2023.

Chong Zhang, Wenli Xiao, Tairan He, and Guanya Shi. Wococo: Learning whole-body humanoid control with sequential contacts. *arXiv preprint arXiv:2406.06005*, 2024.

Brian D Ziebart, Andrew L Maas, J Andrew Bagnell, Anind K Dey, et al. Maximum entropy inverse reinforcement learning. In *Aaai*, volume 8, pp. 1433–1438. Chicago, IL, USA, 2008.

A   RELATED WORK

Reinforcement Learning. Prior work in reinforcement learning (RL) has examined leveraging exploration distributions to improve learning (Kakade & Langford, 2002; Bagnell et al., 2003; Ross et al., 2011; Song et al., 2022). Similar to Song et al. (2022), we consider access to offline data but differ by considering the imitation learning setting, while Song et al. (2022) considers the known-reward reinforcement learning setting. We adapt the Policy Search via Dynamic Programming (PSDP) algorithm of Bagnell et al. (2003) as our RL solver and leverage its performance guarantees in our analysis. We use Jia et al. (2024)'s lower bound on agnostic RL with expert feedback to show why agnostic IRL is hard.

Prior analyses of policy gradient RL algorithms—such as PSDP (Bagnell et al., 2003), Conservative Policy Iteration (CPI, Kakade & Langford (2002)), and Trust Region Policy Optimization (TRPO, Schulman et al. (2015))—use a *policy completeness* condition to establish a performance guarantee with respect to the *global*-optimal policy (Agarwal et al., 2019; Bhandari & Russo, 2024). In other words, policy completeness is used when comparing the learned policy to the optimal (i.e. best possible) policy and not simply the best policy in the policy class. We generalize the policy completeness condition from the RL setting with known rewards to the imitation learning setting with unknown rewards, resulting in novel structural condition we term reward-agnostic policy completeness. Our paper also builds on work in statistically tractable agnostic RL (Jia et al., 2024).

Imitation Learning. Our work examines the issue of distribution shift and compounding errors in IRL, which was introduced by Ross & Bagnell (2010). Ross et al. (2011)'s DAgger algorithm is capable of avoiding compounding errors but requires an interactive (i.e. queryable) expert and *recoverability* (Rajaraman et al., 2021; Swamy et al., 2021a), the former of which we do not assume in our setting.

Our algorithm and results are not limited to the tabular and linear MDP settings, differentiating it from prior work in efficient imitation learning (Xu et al., 2023; Viano et al., 2024). Our work relates to Shani et al. (2022), who propose a Mirror Descent-based no-regret algorithm for online apprenticeship learning. We similarly use a mirror descent based update to our reward function, but differ from Shani et al. (2022)'s work by leveraging resets to expert and offline data to improve the interaction efficiency of our algorithm. Incorporating structured offline data has been proposed to learn reward functions in IRL (Brown et al., 2019; Brown & Niekum, 2019; Poiani et al., 2024), but rely on stronger assumptions about the structure of the offline data. In contrast, we do not use offline data in learning a reward function, instead using it to accelerate policy optimization.

Inverse Reinforcement Learning. We build upon Swamy et al. (2023)'s technique of speeding up IRL by leveraging the expert's state distribution for learner resets. Our paper introduces the following key improvements to Swamy et al. (2023)'s work. First, while Swamy et al. (2023) relies on the impractical assumption of expert realizability, we tackle the more general, misspecified setting. Second, instead of assuming access to infinite expert data like Swamy et al. (2023), we consider the finite sample regime and further demonstrate how to incorporate offline data into IRL. Lastly, we extend Swamy et al. (2023)'s analysis of optimization error to the two other forms of error, finite sample and misspecification, and provide conditions under which quadratically compounding errors can be avoided in the misspecified setting.

B MISSPECIFIED RL WITH EXPERT FEEDBACK

Theorem 2.1 establishes that polynomial sample complexity in the misspecified IRL setting, where $\pi_E \notin \Pi$, cannot be guaranteed. In other words, efficient IRL is not possible with no structure assumed on the MDP, even with access to a queryable expert policy like DAgger (Ross et al., 2011). Note that a generative model allows the learner to query the transition and reward associated with a state-action pair on any state, in contrast to an online interaction model that can only play actions on sequential states in a trajectory. For a more thorough discussion of their differences, see Kakade (2003).

More specifically, Theorem 2.1 presents a lower bound on agnostic RL with expert feedback. It assumes access to the true reward function and an expert oracle, $O_{\exp} : \mathcal{S} \times \mathcal{A} \to \mathcal{R}$, which returns $Q^{\pi_E}(s, a)$ for a given state-action pair (s, a). The lower bound in Theorem 2.1 applies in the case where the expert oracle is replaced with a weaker expert action oracle (i.e. $\pi_E(s) : \mathcal{S} \to \mathcal{A}$) (Amortila et al., 2022; Jia et al., 2024). In agnostic IRL, we consider the even weaker setting of having a dataset of state-action pairs from the expert policy π_E.

Notably, this lower bound focuses on computational efficiency. Statistically efficient imitation *is* possible, and we present a statistically optimal imitation learning algorithm for the misspecified setting in Appendix C.

C   STATISTICALLY OPTIMAL IMITATION UNDER MISSPECIFICATION

We begin with the following question: ignoring computation efficiency, what is the statistically optimal algorithm, with respect to the number of expert samples, for imitation learning in the misspecified setting?

We present **S**cheffé **T**ournament **I**mitation **LE**arning (`STILE`), a statistically optimal algorithm for the misspecified setting. For any two policies π and π', we denote by $f_{\pi,\pi'}$ the following witness function:

$$f_{\pi,\pi'} := \arg \max_{f:\|f\|_\infty \leq 1} \left[\mathbb{E}_{s,a\sim d^\pi} f(s,a) - \mathbb{E}_{s,a\sim d^{\pi'}} f(s,a) \right], \tag{13}$$

and the set of witness functions as

$$\mathcal{F} = \left\{ f_{\pi,\pi'} : \pi, \pi' \in \Pi, \pi \neq \pi' \right\}. \tag{14}$$

Note that $|\mathcal{F}| \leq |\Pi|^2$. `STILE` selects $\hat{\pi}$ using the following procedure:

$$\hat{\pi} \in \arg\min_{\pi\in\Pi} \left[\max_{f\in\mathcal{F}} \left(\mathbb{E}_{s,a\sim d^\pi} f(s,a) - \frac{1}{N} \sum_{i=1}^M f(s_i^*, a_i^*) \right) \right], \tag{15}$$

where $(s_i^*, a_i^*) \in D_E$. Notably, running a tournament algorithm requires comparing every pair of policies, which is not feasible with policy classes like deep neural networks, making `STILE` impractical to implement.

We present the analysis in the infinite-horizon setting for convenience.

Theorem C.1 (Sample Complexity of `STILE`). *Assume Π is finite and $\pi^\star \in \Pi$. With probability at least $1-\delta$, `STILE` finds a policy $\hat{\pi}$*

$$V^{\pi_E} - V^{\hat{\pi}} \leq \frac{4}{1-\gamma} \sqrt{\frac{2\ln(|\Pi|) + \ln\left(\frac{1}{\delta}\right)}{M}}. \tag{16}$$

Proof. The proof relies on a uniform convergence argument over $\mathcal{F}$ of which the size is $|\Pi|^2$. First, note that for all policies $\pi \in \Pi$:

$$\max_{f\in\mathcal{F}} \left(\mathbb{E}_{s,a\sim d^\pi} f(s,a) - \mathbb{E}_{s,a\sim d^{\pi_E}} f(s,a) \right) = \max_{f:\|f\|_\infty \leq 1} \left(\mathbb{E}_{s,a\sim d^\pi} f(s,a) - \mathbb{E}_{s,a\sim d^{\pi_E}} f(s,a) \right) \tag{17}$$

$$= \|d^\pi - d^{\pi_E}\|_1 \tag{18}$$

where the first equality comes from the fact that $\mathcal{F}$ includes $\arg\max_{f:\|f\|_\infty \leq 1} \left[\mathbb{E}_{s,a,s'\sim d^\pi} f(s,a) - \mathbb{E}_{s,a,s'\sim d^{\pi_E}} f(s,a) \right]$

Via Hoeffding's inequality and a union bound over $\mathcal{F}$, we get that with probability at least $1-\delta$, for all $f \in \mathcal{F}$:

$$\left| \frac{1}{M} \sum_{i=1}^M f(s_i^*, a_i^*) - \mathbb{E}_{s,a\sim d^{\pi_E}} f(s,a) \right| \leq 2\sqrt{\frac{\ln(|\mathcal{F}|/\delta)}{M}} \tag{19}$$

$$:= \epsilon_{\text{stat}}. \tag{20}$$

Denote

$$\hat{f} := \arg\max_{f\in\mathcal{F}} \left[\mathbb{E}_{s,a\sim d^{\hat\pi}} f(s,a) - \mathbb{E}_{s,a\sim d^{\pi_E}} f(s,a) \right] \tag{21}$$

and

$$\tilde{f} := \arg\max_{f\in\mathcal{F}} \mathbb{E}_{s,a\sim d^{\hat\pi}} f(s,a) - \frac{1}{M} \sum_{i=1}^M f(s_i, a_i). \tag{22}$$

Hence, for $\hat{\pi}$, we have:

$$\left\| d^{\hat{\pi}} - d^{\pi_E} \right\|_1 = \mathbb{E}_{s,a \sim d^{\hat{\pi}}} \hat{f}(s,a) - \mathbb{E}_{s,a \sim d^{\pi_E}} \hat{f}(s,a) \tag{23}$$

$$\leq \mathbb{E}_{s,a \sim d^{\hat{\pi}}} \hat{f}(s,a) - \frac{1}{M} \sum_{i=1}^{M} \hat{f}(s_i^*, a_i^*) + \epsilon_{\text{stat}} \tag{24}$$

$$\leq \mathbb{E}_{s,a \sim d^{\pi_E}} \tilde{f}(s,a) - \frac{1}{M} \sum_{i=1}^{M} \tilde{f}(s_i^*, a_i^*) + \epsilon_{\text{stat}} \tag{25}$$

$$\leq \mathbb{E}_{s,a \sim d^{\pi_E}} \tilde{f}(s,a) - \mathbb{E}_{s,a \sim d^{\pi_E}} \tilde{f}(s,a) + 2\epsilon_{\text{stat}} \tag{26}$$

$$= 2\epsilon_{\text{stat}} \tag{27}$$

where we use the optimality of $\hat{\pi}$ in the third inequality.

Recall that $V^\pi = \mathbb{E}_{s,a \sim d^\pi} r(s,a)/(1-\gamma)$, so we have:

$$V^{\hat{\pi}} - V^{\pi_E} = \frac{1}{1-\gamma} \left(\mathbb{E}_{s,a \sim d^{\hat{\pi}}} r(s,a) - \mathbb{E}_{s,a \sim d^{\pi_E}} r(s,a) \right) \tag{28}$$

$$\leq \frac{\sup_{s,a} |r(s,a)|}{1-\gamma} \left\| d^{\hat{\pi}} - d^{\pi_E} \right\|_1 \tag{29}$$

$$\leq \frac{2}{1-\gamma} \epsilon_{\text{stat}} \tag{30}$$

This concludes the proof. $\qquad\square$

C.1 PROOF OF THEOREM 2.2

Proof. We first define some terms below. Denote $\tilde{\pi} := \arg\min_{\pi \in \Pi} \|d^{\pi} - d^{\pi_E}\|_1$. Let us denote:

$$\tilde{f} = \arg\max_{f \in \mathcal{F}} \left[\mathbb{E}_{s,a \sim d^{\hat{\pi}}} f(s,a) - \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} f(s,a) \right], \tag{31}$$

$$\bar{f} = \arg\max_{f \in \mathcal{F}} \left[\mathbb{E}_{s,a \sim d^{\hat{\pi}}} f(s,a) - \frac{1}{M} \sum_{i=1}^{M} f(s_i^{\star}, a_i^{\star}) \right], \tag{32}$$

$$f' = \arg\max_{f \in \mathcal{F}} \left[\mathbb{E}_{s,a \sim d^{\tilde{\pi}}} \left[f(s,a) \right] - \frac{1}{M} \sum_{i=1}^{M} f(s_i^{\star}, a_i^{\star}) \right]. \tag{33}$$

Starting with triangle inequality, we have:

$$\left\| d^{\hat{\pi}} - d^{\pi^*} \right\|_1 \leq \left\| d^{\hat{\pi}} - d^{\tilde{\pi}} \right\|_1 + \left\| d^{\tilde{\pi}} - d^{\pi^*} \right\|_1 \tag{34}$$

$$= \mathbb{E}_{s,a \sim d^{\hat{\pi}}} \left[\tilde{f}(s,a) \right] - \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} \left[\tilde{f}(s,a) \right] + \left\| d^{\tilde{\pi}} - d^{\pi^*} \right\|_1 \tag{35}$$

$$= \mathbb{E}_{s,a \sim d^{\hat{\pi}}} \left[\tilde{f}(s,a) \right] - \frac{1}{M} \sum_{i=1}^{M} \tilde{f}(s_i, a_i^*) + \frac{1}{M} \sum_{i=1}^{M} \tilde{f}(s_i, a_i^*)$$
$$- \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} \left[\tilde{f}(s,a) \right] + \left\| d^{\tilde{\pi}} - d^{\pi^*} \right\|_1 \tag{36}$$

$$\leq \mathbb{E}_{s,a \sim d^{\hat{\pi}}} \left[\bar{f}(s,a) \right] - \frac{1}{M} \sum_{i=1}^{M} \bar{f}(s_i, a_i^*) + \frac{1}{M} \sum_{i=1}^{M} \tilde{f}(s_i, a_i^*) - \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} \left[\tilde{f}(s,a) \right]$$
$$+ \left[\mathbb{E}_{s,a \sim d^{\pi_E}} \tilde{f}(s,a) - \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} \tilde{f}(s,a) \right] + \left\| d^{\tilde{\pi}} - d^{\pi^*} \right\|_1 \tag{37}$$

$$\leq \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} \left[f'(s,a) \right] - \frac{1}{M} \sum_{i=1}^{M} f'(s_i, a_i^*) + 2\sqrt{\frac{\ln(|\mathcal{F}|/\delta)}{M}} + 2 \left\| d^{\tilde{\pi}} - d^{\pi_E} \right\|_1 \tag{38}$$

$$\leq \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} \left[f'(s,a) \right] - \mathbb{E}_{s,a \sim d^{\pi_E}} \left[f'(s,a) \right] + 4\sqrt{\frac{\ln(|\mathcal{F}|/\delta)}{M}} + 2 \left\| d^{\tilde{\pi}} - d^{\pi_E} \right\|_1 \tag{39}$$

$$\leq 3 \left\| d^{\pi_E} - d^{\tilde{\pi}} \right\|_1 + 4\sqrt{\frac{\ln(|\mathcal{F}|/\delta)}{M}}. \tag{40}$$

where the first inequality uses the definition of $\bar{f}$, the second inequality uses the fact that $\hat{\pi}$ is the minimizer of $\max_{f \in \mathcal{F}} \mathbb{E}_{s,a \sim d^{\pi}} f(s,a) - \frac{1}{M} \sum_{i=1}^{M} f(s_i^*, a_i^*)$. We also use Hoeffding's inequality where $\forall f \in \mathcal{F}$,

$$\left| \mathbb{E}_{s,a \sim d^{\pi_E}} f(s,a) - \sum_{i=1}^{M} f(s_i^*, a_i^*) \right| \leq 2\sqrt{\frac{\ln(|\mathcal{F}|/\delta)}{M}} \tag{41}$$

with probability at least $1 - \delta$. □

D   FURTHER EXPLANATION OF GUITAR AND PSDP

Algorithm 3 Policy Search Via Dynamic Programming (Bagnell et al., 2003)

1: **Input:** Reward function r_i, reset distribution ρ, and policy class Π
2: **Output:** Trained policy π
3: **for** $h = H, H-1, \ldots, 1$ **do**
4:     Optimize

$$\pi_h \leftarrow \arg\max_{\pi' \in \Pi} \mathbb{E}_{s_h \sim \rho_h} \mathbb{E}_{a_h \sim \pi'(\cdot|s_h)} A_{r_i}^{\pi_{h+1}, \ldots, \pi_H}(s_h, a_h) \tag{42}$$

5: **end for**
6: **Return** $\pi = \{\pi_h\}_{h=1}^H$

Algorithm 4 GUiding **I**mi**T**aters with **A**rbitrary **R**oll-ins (GUITAR)

1: **Input:** Expert state-action distributions ρ_E, mixture of expert and offline state-action distributions ρ_{mix}, policy class Π, reward class $\mathcal{R}$
2: **Output:** Trained policy π
3: Set $\pi_0 \in \Pi$
4: **for** $i = 1$ to N **do**
5:     Let

```
// Loss function
```
$$\hat{L}(\pi, r) = \mathbb{E}_{(s,a) \sim \rho_E} r(s, a) - \mathbb{E}_{(s,a) \sim d_\mu^\pi} r(s, a) \tag{43}$$

6:     Optimize

```
// No-regret reward update
```
$$r_i \leftarrow \arg\max_{r \in \mathcal{R}} \hat{L}(\pi_{i-1}, r) + \eta^{-1} \Delta_R(r \mid r_{i-1}) \tag{44}$$

7:     Optimize

```
// Expert-competitive response with RL
```
$$\pi_i \leftarrow \mathrm{PSDP}(r = r_i, \rho = \rho_{\mathrm{mix}}) \tag{45}$$

8: **end for**
9: **Return** π_i with lowest validation error

The full IRL procedure is outlined in Algorithm 4. It can be summarized as (1) a no-regret reward update using Online Mirror Descent, and (2) an expert-competitive policy update using Policy Search by Dynamic Programming (PSDP) as the RL solver, where the learner is reset to a distribution ρ in the RL subroutine.

Existing efficient IRL algorithms, such as MMDP (Swamy et al., 2023), reset the learner exclusively to expert states (i.e. the case where $\rho = \rho_E$). GUITAR can be seen as extending MMDP to a general reset distribution in the misspecified setting. We will focus on expert resets in the misspecified setting first, and we then consider other reset distributions in Section 4.

Policy Update. Following Ren et al. (2024)'s reduction of inverse RL to expert-competitive RL, we can use any RL algorithm to generate an expert-competitive response. We employ PSDP (Bagnell et al., 2003), shown in Algorithm 3, for its strong theoretical guarantees. In practice, any RL algorithm can be used, such as Soft Actor Critic (SAC, Haarnoja et al. (2018)).

Reward Update. We employ a no-regret update to the reward function. We employ Online Mirror Descent (Nemirovskij & Yudin, 1983; Beck & Teboulle, 2003; Srebro et al., 2011) for its strong theoretical guarantees, but in practice, any no-regret update can be used, such as gradient descent.

More specifically, the reward function is updated through Online Mirror Descent, such that

$$r_i \leftarrow \arg\max_{r \in \mathcal{R}} \hat{L}(\pi_{i-1}, r) + \eta^{-1} \Delta_R(r \mid r_{i-1}), \tag{46}$$

where Δ_R is the Bregman divergence with respect to the negative entropy function R. $\hat{L}(\pi, r)$ is the loss, defined by

$$\hat{L}(\pi, r) = \mathbb{E}_{(s,a) \sim \rho_E} r(s, a) - \mathbb{E}_{(s,a) \sim d_\mu^\pi} r(s, a), \tag{47}$$

with respect to the distribution of expert samples, ρ_E.

E PROOFS OF SECTION 3

E.1 PROOF OF THEOREM 3.3

Proof. We consider the imitation gap of the expert and the average of the learned policies $\bar{\pi}$,

$$V^{\pi_E} - V^{\bar{\pi}} = \frac{1}{n} \sum_{i=1}^{n} \left(\mathbb{E}_{\zeta \sim \pi_E} \sum_{h=1}^{H} r^*(s,a) - \mathbb{E}_{\zeta \sim \pi_i} \sum_{h=1}^{H} r^*(s,a) \right) \tag{48}$$

$$= H \frac{1}{n} \sum_{i=1}^{n} \left(\mathbb{E}_{(s,a) \sim d_\mu^{\pi_E}} r^*(s,a) - \mathbb{E}_{(s,a) \sim d_\mu^{\pi_i}} r^*(s,a) \right) \tag{49}$$

$$= H \frac{1}{n} \sum_{i=1}^{n} L(\pi_i, r^*) \tag{50}$$

$$\leq H \frac{1}{n} \max_{r \in \mathcal{R}} \sum_{i=1}^{n} L(\pi_i, r) \tag{51}$$

$$\leq H \frac{1}{n} \max_{r \in \mathcal{R}} \sum_{i=1}^{n} \left(L(\pi_i, r) - L(\pi_i, r_i) + L(\pi_i, r_i) \right) \tag{52}$$

$$= H \frac{1}{n} \sum_{i=1}^{n} L(\pi_i, r_i) + H \frac{1}{n} \max_{r \in \mathcal{R}} \sum_{i=1}^{n} \left(L(\pi_i, r) - L(\pi_i, r_i) \right) \tag{53}$$

Applying the regret bound of Online Mirror Descent (Theorem J.2), we have

$$V^{\pi_E} - V^{\bar{\pi}} \leq H \frac{1}{n} \sum_{i=1}^{n} L(\pi_i, r_i) + H \sqrt{\frac{\ln |\mathcal{R}|}{n}} \tag{54}$$

$$= H \frac{1}{n} \sum_{i=1}^{n} \left(\frac{1}{H} \sum_{h=1}^{H} \mathbb{E}_{(s_h,a_h) \sim d_h^{\pi_E}} r_i(s_h, a_h) - \frac{1}{H} \sum_{h=1}^{H} \mathbb{E}_{(s_h,a_h) \sim d_h^{\pi_i}} r_i(s_h, a_h) \right)$$
$$+ H \sqrt{\frac{\ln |\mathcal{R}|}{n}} \tag{55}$$

$$= \frac{1}{n} \sum_{i=1}^{n} \left(\mathbb{E}_{s \sim \mu} V_{r_i}^{\pi_E} - \mathbb{E}_{s \sim \mu} V_{r_i}^{\pi_i} \right) + H \sqrt{\frac{\ln |\mathcal{R}|}{n}} \tag{56}$$

$$= \frac{1}{n} \sum_{i=1}^{n} \sum_{h=0}^{H-1} \left(\mathbb{E}_{(s_h,a_h) \sim d_h^{\pi_E}} A_{r_i,h}^{\pi_i}(s_h, a_h) \right) + H \sqrt{\frac{\ln |\mathcal{R}|}{n}} \tag{57}$$

Focusing on the interior summation, we have

$$\sum_{h=0}^{H-1} \mathbb{E}_{(s_h,a_h) \sim d_h^{\pi_E}} A_h^{\pi_i}(s_h, a_h) \leq \sum_{h=0}^{H-1} \mathbb{E}_{s_h \sim d_h^{\pi_E}} \max_{a \in \mathcal{A}} A_h^{\pi_i}(s_h, a) \tag{58}$$

$$= \sum_{h=0}^{H-1} \mathbb{E}_{s_h \sim d_h^{\pi_E}} \max_{a \in \mathcal{A}} A_h^{\pi_i}(s_h, a) - \epsilon_{\Pi,h} + \epsilon_{\Pi,h} \tag{59}$$

$$= \sum_{h=0}^{H-1} \max_{\pi' \in \Pi} \mathbb{E}_{s_h \sim d_h^{\pi_E}} \mathbb{E}_{a \sim \pi'(\cdot|s)} A_h^{\pi_i}(s_h, a) + \epsilon_{\Pi,h} \tag{60}$$

$$\leq H^2 \epsilon + H \epsilon_{\Pi} \tag{61}$$

where the last line holds by PSDP's performance guarantee (Bagnell et al., 2003).

Applying Equation 61 to Equation 57, we have

$$V^{\pi_E} - V^{\bar{\pi}} \leq \frac{1}{n} \sum_{i=1}^{n} \sum_{h=0}^{H-1} \left(\mathbb{E}_{(s_h, a_h) \sim d_h^{\pi_E}} A_{r_i, h}^{\pi_i}(s_h, a_h) \right) + H \sqrt{\frac{\ln |\mathcal{R}|}{n}} \tag{62}$$

$$\leq \frac{1}{n} \sum_{i=1}^{n} \left(H^2 \epsilon + H \epsilon_\Pi \right) + H \sqrt{\frac{\ln |\mathcal{R}|}{n}} \tag{63}$$

$$\leq H^2 \epsilon + H \epsilon_\Pi + H \sqrt{\frac{\ln |\mathcal{R}|}{n}} \tag{64}$$

which completes the proof. $\square$

F PROOFS OF SECTION 4

F.1 LEMMAS OF THEOREM F.5

Lemma F.1 (Reward Regret Bound). *Recall that*

$$\hat{L}(\pi, r) = \mathbb{E}_{(s,a)\sim\rho_E} r(s,a) - \mathbb{E}_{(s,a)\sim d_\mu^\pi} r(s,a). \tag{65}$$

Suppose that we update the reward via the Online Mirror Descent algorithm. Since $0 \leq r(s,a) \leq 1$ for all s, a, then $\sup_{\pi\in\Pi, r\in\mathcal{R}} \hat{L}(\pi, r) \leq 1$. Applying Theorem J.2 with $B = 1$, the regret is given by

$$\lambda_n = \sup_{r\in\mathcal{R}} \frac{1}{n} \sum_{i=1}^n \hat{L}(\pi_i, r) - \frac{1}{n}\sum_{i=1}^n \hat{L}(\pi_i, r_i) \tag{66}$$

$$\leq \sqrt{\frac{2\ln|\mathcal{R}|}{n}} \tag{67}$$

$$= \sqrt{\frac{C_1}{n}}, \tag{68}$$

where $C_1 = 2\ln|\mathcal{R}|$ and n is the number of updates.

Lemma F.2 (Statistical Difference of Losses). *With probability at least $1 - \delta$,*

$$L(\pi, r) \leq \hat{L}(\pi, r) + \sqrt{\frac{C}{N}}, \tag{69}$$

where $C = \ln\frac{2|\mathcal{R}|}{\delta}$ and N is the number of state-action pairs from the expert.

Proof. By definition of L and $\hat{L}$, for any $\pi \in \Pi$ and $r \in \mathcal{R}$, we have

$$\left| L(\pi, r) - \hat{L}(\pi, r) \right| = \left| \mathbb{E}_{(s,a)\sim d_\mu^{\pi_E}} r(s,a) - \mathbb{E}_{(s,a)\sim d_\mu^\pi} r(s,a) \right.$$
$$\left. - \left(\mathbb{E}_{(s,a)\sim\rho_E} r(s,a) - \mathbb{E}_{(s,a)\sim d_\mu^\pi} r(s,a) \right) \right| \tag{70}$$

$$= \left| \mathbb{E}_{(s,a)\sim d_\mu^{\pi_E}} r(s,a) - \mathbb{E}_{(s,a)\sim\rho_E} r(s,a) \right| \tag{71}$$

$$= \left| \mathbb{E}_{(s,a)\sim d_\mu^{\pi_E}} r(s,a) - \frac{1}{N} \sum_{(s_i,a_i)\in D_E}^N r(s_i, a_i) \right| \tag{72}$$

$$\leq \sqrt{\frac{1}{2N} \ln\frac{2|\mathcal{R}|}{\delta}} \tag{73}$$

$$\leq \sqrt{\frac{C}{N}}, \tag{74}$$

where $C = 4\ln\frac{2|\mathcal{R}|}{\delta}$. The fourth line holds by Hoeffding's inequality and a union bound. Specifically, we apply Corollary J.1 with $c = 1$, since all rewards are bounded by 0 and 1. We take a union bound over all reward functions in the reward class $\mathcal{R}$. Note that the terms involving π cancel out, so the union bound only applies to the reward function class $\mathcal{R}$. Rearranging terms gives the desired bound. $\square$

Lemma F.3 (Advantage Bound). *Suppose that $\epsilon = 0$ and reward function r_i are the input parameters to PSDP, and $\pi_i = (\pi_1^i, \pi_2^i, \ldots, \pi_H^i)$ is the output learned policy. Then, with probability at least $1 - \delta$,*

$$\mathbb{E}_{s\sim d^{\pi_E}} \max_{a\in\mathcal{A}} A^{\pi_i}(s,a) \leq \min\left\{ \epsilon_\Pi + \epsilon_\Pi \sqrt{\frac{C_0}{N}}, C_B\left(\epsilon_\Pi + \epsilon_\Pi \sqrt{\frac{C_0}{N+M}} \right) \right\} \tag{75}$$

where $C_B = \left\| \frac{d_\mu^{\pi_E}}{d_\mu^{\pi_B}} \right\|_\infty$, H is the horizon, N is the number of expert state-action pairs, M is the number of offline state-action pairs, and $C_0 = 2\ln\frac{|\Pi||\mathcal{R}|}{\delta}$.

Proof. Suppose that $\epsilon = 0$ is the input accuracy parameter to PSDP, and the advantages are computed under reward function r_i. PSDP is guaranteed to terminate and output a policy $\pi_i = (\pi_1^i, \pi_2^i, \ldots, \pi_H^i)$, such that

$$H\epsilon \geq \max_{\pi' \in \Pi} \mathbb{E}_{s_h \sim \rho_{mix,h}} \mathbb{E}_{a \sim \pi'(\cdot|s)} A_h^{\pi_i}(s_h, a) \tag{76}$$

for all $h \in [H]$ (Bagnell et al., 2003). Consequently, we have

$$H\epsilon \geq \max_{\pi' \in \Pi} \mathbb{E}_{s \sim \rho_{\text{mix}}} \mathbb{E}_{a \sim \pi'(\cdot|s)} A^{\pi_i}(s, a) \tag{77}$$

$$= \max_{\pi' \in \Pi} \mathbb{E}_{s \sim \rho_{\text{mix}}} \mathbb{E}_{a \sim \pi'(\cdot|s)} A^{\pi_i}(s, a) + \epsilon_{\Pi,r_i} - \epsilon_{\Pi,r_i} \tag{78}$$

$$= \mathbb{E}_{s \sim \rho_{\text{mix}}} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a) - \epsilon_{\Pi,r_i} \tag{79}$$

By definition, $0 \leq \epsilon_{\Pi,r_i} \leq \epsilon_\Pi$, so for any $x \in \mathbb{R}$, $x - \epsilon_{\Pi,r_i} \geq x - \epsilon_\Pi$, so

$$H\epsilon \geq \mathbb{E}_{s \sim \rho_{\text{mix}}} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a) - \epsilon_\Pi. \tag{80}$$

Rearranging the terms gives us

$$\mathbb{E}_{s \sim \rho_{\text{mix}}} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a) \leq H\epsilon + \epsilon_\Pi \tag{81}$$

$$= \epsilon_\Pi, \tag{82}$$

where the last line holds by our assumption that $\epsilon = 0$.

Case 1: Jettison Offline Data. We will first consider the case where offline data is useless, in which case we will focus on the expert data.

Note that $\max_{a \in \mathcal{A}} A^{\pi_i}(s, a) \geq 0$ for all $s \in \mathcal{S}$ and $h \in [H]$. Applying the definition of ρ_{mix},

$$\mathbb{E}_{s \sim \rho_{\text{mix}}} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a) = \mathbb{E}_{s \sim \rho_E} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a) + \mathbb{E}_{s \sim \rho_b} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a). \tag{83}$$

Consequently, we know that

$$\epsilon_\Pi \geq \mathbb{E}_{s \sim \rho_E} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a) \tag{84}$$

$$= \frac{1}{N} \sum_{s_i \in D_E}^{N} \max_{a \in \mathcal{A}} A^{\pi_i}(s_i, a) \tag{85}$$

Because $\max_{a \in \mathcal{A}} A^{\pi_i}(s, a) \geq 0$ for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$, we know $\max_{a \in \mathcal{A}} A^{\pi_i}(s_i, a) \leq \epsilon_\Pi$ for all $s_i \in D_E$. We apply Hoeffding's inequality (Corollary J.1) with $c = \epsilon_\Pi^2$ to bound the difference between $\mathbb{E}_{s \sim d_\mu^{\pi_E}} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a)$ and $\mathbb{E}_{s \sim \rho_E} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a)$. We apply a union bound on the policy and reward function. As stated previously, $\max_{a \in \mathcal{A}} A^{\pi_i}(s, a) \geq 0$ for all $s \in \mathcal{S}$. By Hoeffding's inequality, with probability $1 - \delta$, we have

$$\left| \mathbb{E}_{s \sim d_\mu^{\pi_E}} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a) - \mathbb{E}_{s \sim \rho_E} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a) \right| = \left| \mathbb{E}_{s \sim d_\mu^{\pi_E}} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a) \right. \tag{86}$$

$$\left. - \frac{1}{N} \sum_{s_i \in D_E}^{N} \max_{a \in \mathcal{A}} A^{\pi_i}(s_i, a) \right| \tag{87}$$

$$\leq \sqrt{\epsilon_\Pi^2 \frac{1}{2N} \ln \frac{|\Pi||\mathcal{R}|}{\delta}} \tag{88}$$

$$\leq \epsilon_\Pi \sqrt{\frac{C_0}{N}}, \tag{89}$$

where $C_0 = 2 \ln \frac{|\Pi||\mathcal{R}|}{\delta}$. Note that the cardinality of the set of advantage functions over all possible policies is upper bounded by the cardinalities of the policy and reward classes. Rearranging the terms and applying Equation 84 yields

$$\mathbb{E}_{s \sim d_\mu^{\pi_E}} \max_{a \in \mathcal{A}} A^{\pi_i}(s, a) \leq \epsilon_\Pi + \epsilon_\Pi \sqrt{\frac{C_0}{N}}. \tag{90}$$

Case 2: Leverage Offline Data. Next, we consider the case where offline data is useful, specifically where there is good coverage of the expert data.

Next, we apply Hoeffding's inequality (Corollary J.1) to bound the difference between $\mathbb{E}_{s\sim\nu}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)$ and $\mathbb{E}_{s\sim\rho_{\text{mix}}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)$. We apply a union bound on the policy and reward function. We use $c=\epsilon_{\Pi}^2$ for a similar argument to the one used in Case 1. As stated previously, $\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\geq 0$ for all $s\in\mathcal{S}$. By Hoeffding's inequality, with probability $1-\delta$, we have

$$\left|\mathbb{E}_{s\sim\nu}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)-\mathbb{E}_{s\sim\rho_{\text{mix}}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\right|=\left|\mathbb{E}_{s\sim\nu}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\right.\tag{91}$$

$$\left.-\frac{1}{N+M}\sum_{s_i\in D_{mix}}^{N+M}\max_{a\in\mathcal{A}}A^{\pi_i}(s_i,a)\right|$$

$$\leq\sqrt{\epsilon_{\Pi}\frac{1}{2(N+M)}\ln\frac{|\Pi||\mathcal{R}|}{\delta}}\tag{92}$$

$$\leq\epsilon_{\Pi}\sqrt{\frac{C_0}{N+M}}\tag{93}$$

where $C_0=2\ln\frac{|\Pi||\mathcal{R}|}{\delta}$. Note that the cardinality of the set of advantage functions over all possible policies is upper bounded by the cardinalities of the policy and reward classes. Rearranging the terms and applying Equation 81 yields

$$\mathbb{E}_{s\sim\nu}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\leq\epsilon_{\Pi}+\epsilon_{\Pi}\sqrt{\frac{C_0}{N+M}}.\tag{94}$$

By linearity of expectation, and using the fact that $1\leq C_B<\infty$, we have

$$\mathbb{E}_{s\sim d^{\pi_E}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)=\frac{N}{N+M}\mathbb{E}_{s\sim d^{\pi_E}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)$$

$$+\frac{M}{N+M}\mathbb{E}_{s\sim d^{\pi_E}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\tag{95}$$

$$\leq\frac{N}{N+M}\mathbb{E}_{s\sim d^{\pi_E}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)$$

$$+C_B\frac{M}{N+M}\mathbb{E}_{s\sim d^{\pi_B}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\tag{96}$$

$$\leq C_B\frac{N}{N+M}\mathbb{E}_{s\sim d^{\pi_E}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)$$

$$+C_B\frac{M}{N+M}\mathbb{E}_{s\sim d^{\pi_B}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\tag{97}$$

$$=C_B\left(\frac{N}{N+M}\mathbb{E}_{s\sim d^{\pi_E}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\right.$$

$$\left.+\frac{M}{N+M}\mathbb{E}_{s\sim d^{\pi_B}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\right)\tag{98}$$

$$\leq C_B\mathbb{E}_{s\sim\nu}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a).\tag{99}$$

Applying Equation 99 to Equation 94, we have

$$\mathbb{E}_{s\sim d^{\pi_E}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\leq C_B\mathbb{E}_{s\sim\nu}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\tag{100}$$

$$\leq C_B\left(\epsilon_{\Pi}+\epsilon_{\Pi}\sqrt{\frac{C_0}{N+M}}\right)\tag{101}$$

Final Result. Using the bounds from Case 1 and Case 2, we know that

$$\mathbb{E}_{s\sim d^{\pi_E}}\max_{a\in\mathcal{A}}A^{\pi_i}(s,a)\leq\min\left\{\epsilon_{\Pi}+\epsilon_{\Pi}\sqrt{\frac{C_0}{N}},C_B\left(\epsilon_{\Pi}+\epsilon_{\Pi}\sqrt{\frac{C_0}{N+M}}\right)\right\}\tag{102}$$

where $C_B = \left\| \frac{d_\mu^{\pi_E}}{d_\mu^{\pi_B}} \right\|_\infty$, H is the horizon, N is the number of expert state-action pairs, M is the number of offline state-action pairs, and $C_0 = 2\ln\frac{|\Pi||\mathcal{R}|}{\delta}$. $\qquad \square$

Lemma F.4 (Loss Bound). *Suppose that $\epsilon = 0$ and reward function r_i are the input parameters to PSDP, and $\pi_i = (\pi_1^i, \pi_2^i, \dots, \pi_H^i)$ is the output learned policy. Then, with probability at least $1 - \delta$,*

$$\hat{L}(\pi_i, r_i) \le \min\left\{\epsilon_\Pi + \epsilon_\Pi\sqrt{\frac{C_0}{N}}, C_B\left(\epsilon_\Pi + \epsilon_\Pi\sqrt{\frac{C_0}{N+M}}\right)\right\} + \sqrt{\frac{C}{N}}, \qquad (103)$$

where $C_B = \left\| \frac{d_\mu^{\pi_E}}{d_\mu^{\pi_B}} \right\|_\infty$, H is the horizon, N is the number of expert state-action pairs, M is the number of offline state-action pairs, $C_0 = 2\ln\frac{|\Pi||\mathcal{R}|}{\delta}$, and $C = \ln\frac{2|\mathcal{R}|}{\delta}$.

Proof. By Lemma F.2, we have

$$\hat{L}(\pi_i, r_i) \le L(\pi_i, r_i) + \sqrt{\frac{C}{N}} \qquad (104)$$

$$= \mathbb{E}_{(s,a)\sim d_\mu^{\pi_E}}[r_i(s,a)] - \mathbb{E}_{(s,a)\sim d_\mu^{\pi_i}}[r_i(s,a)] + \sqrt{\frac{C}{N}} \qquad (105)$$

$$= \frac{1}{H}\left(V_{r_i}^{\pi_E} - V_{r_i}^{\pi_i}\right) + \sqrt{\frac{C}{N}} \qquad (106)$$

$$= \frac{1}{H}\left(\sum_{h=1}^{H}\mathbb{E}_{(s_h,a_h)\sim d_h^{\pi_E}}A_{r_i,h}^{\pi_i}(s_h,a_h)\right) + \sqrt{\frac{C}{N}} \qquad (107)$$

$$\le \frac{1}{H}\left(\sum_{h=1}^{H}\mathbb{E}_{s_h\sim d_h^{\pi_E}}\max_{a\in\mathcal{A}}A_{r_i,h}^{\pi_i}(s_h,a)\right) + \sqrt{\frac{C}{N}} \qquad (108)$$

$$= \frac{1}{H}\left(H\mathbb{E}_{s\sim d^{\pi_E}}\max_{a\in\mathcal{A}}A_{r_i}^{\pi_i}(s,a)\right) + \sqrt{\frac{C}{N}} \qquad (109)$$

where $C = \ln\frac{2|\mathcal{R}|}{\delta}$. The second line holds by the definition of $L(\pi_i, r_i)$, and the third line holds by the definition of the reward-indexed value function. The fourth line holds by the Performance Difference Lemma (PDL). Applying Lemma F.3, we have

$$\hat{L}(\pi_i, r_i) \le \min\left\{\epsilon_\Pi + \epsilon_\Pi\sqrt{\frac{C_0}{N}}, C_B\left(\epsilon_\Pi + \epsilon_\Pi\sqrt{\frac{C_0}{N+M}}\right)\right\} + \sqrt{\frac{C}{MN}}, \qquad (110)$$

where $C_B = \left\| \frac{d_\mu^{\pi_E}}{d_\mu^{\pi_B}} \right\|_\infty$, H is the horizon, N is the number of expert state-action pairs, M is the number of offline state-action pairs, $C_0 = 2\ln\frac{|\Pi||\mathcal{R}|}{\delta}$, and $C = \ln\frac{2|\mathcal{R}|}{\delta}$. $\qquad \square$

F.2 FINITE SAMPLE ANALYSIS OF ALGORITHM 2

Theorem F.5 (Sample Complexity of Algorithm 2). *Suppose that PSDP's accuracy parameter is set to $\epsilon = 0$. Then, upon termination of Algorithm 2, with probability at least $1 - \delta$, we have*

$$
V^{\pi_E} - V^{\overline{\pi}} \leq \underbrace{H \min \left\{ \epsilon_{\Pi}^{\rho_{mix}} + \epsilon_{\Pi}^{\rho_{mix}} \sqrt{\frac{C_{\Pi,\mathcal{R}}}{N}}, C_B \left(\epsilon_{\Pi}^{\rho_{mix}} + \epsilon_{\Pi}^{\rho_{mix}} \sqrt{\frac{C_{\Pi,\mathcal{R}}}{N+M}} \right) \right\}}_{\textit{Misspecification Error}} + \underbrace{H \sqrt{\frac{C_{\mathcal{R}}}{N}}}_{\textit{Statistical Error}} + \underbrace{H \sqrt{\frac{\ln |\mathcal{R}|}{n}}}_{\textit{Reward Regret}}
$$

(111)

where H is the horizon, N is the number of expert state-action pairs, M is the number of offline state-action pairs, n is the number of reward updates, $C_{\Pi,\mathcal{R}} = \ln \frac{|\Pi||\mathcal{R}|}{\delta}$, $C_{\mathcal{R}} = \ln \frac{|\mathcal{R}|}{\delta}$, and $C_B = \left\| \frac{d_\mu^{\pi_E}}{d_\mu^{\pi_B}} \right\|_\infty$.

Theorem F.5 upper bounds the sample complexity of Algorithm 2 in the offline data setting. The bound differs from Theorem 3.3 in the following ways. First, the policy optimization error term vanishes by the assumption that $\epsilon = 0$. Importantly, the assumption of $\epsilon = 0$ is not necessary but rather convenient, as the $\epsilon > 0$ case was presented in Theorem 3.3. Second, offline data is incorporated into the reset distribution, resulting in a modified misspecification error. Finally, the finite expert sample regime is considered, resulting in statistical error of estimating the expert policy's state distribution $d_\mu^{\pi_E}$ with the distribution over samples ρ_E.

Proof. We consider the imitation gap of the expert and the averaged learned policies, $\overline{\pi}$,

$$
V^{\pi_E} - V^{\overline{\pi}} = \frac{1}{n} \sum_{i=0}^{n} \left(\mathbb{E}_{\zeta \sim \pi_E} \left[\sum_{h=1}^{H} r^*(s_h, a_h) \right] - \mathbb{E}_{\zeta \sim \pi_i} \left[\sum_{h=1}^{H} r^*(s_h, a_h) \right] \right)
$$

(112)

$$
= \frac{1}{n} H \sum_{i=0}^{n} \left(\mathbb{E}_{(s,a) \sim d_\mu^{\pi_E}} \left[r^*(s, a) \right] - \mathbb{E}_{(s,a) \sim d_\mu^{\pi_i}} \left[r^*(s, a) \right] \right)
$$

(113)

$$
= \frac{1}{n} H \sum_{i=0}^{n} L(\pi_i, r^*)
$$

(114)

$$
\leq \frac{1}{n} H \max_{r \in \mathcal{R}} \sum_{i=0}^{n} L(\pi_i, r)
$$

(115)

where n is the number of updates to the reward function. The second line holds by definition of d_μ^π. The third line holds by definition of L. Applying the Statistical Difference of Losses (Lemma F.2), we have

$$
V^{\pi_E} - V^{\overline{\pi}} \leq \frac{1}{n} H \max_{r \in \mathcal{R}} \sum_{i=0}^{n} \left(\hat{L}(\pi_i, r) + \sqrt{\frac{C}{N}} \right)
$$

(116)

$$
= \frac{1}{n} H \max_{r \in \mathcal{R}} \sum_{i=0}^{n} \left(\hat{L}(\pi_i, r) - \hat{L}(\pi_i, r_i) + \hat{L}(\pi_i, r_i) + \sqrt{\frac{C}{N}} \right)
$$

(117)

where $C = \ln \frac{2|\mathcal{R}|}{\delta}$ and M is the number of state-action pairs from the expert. Applying the Reward Regret Bound (Lemma F.1), we have

$$
V^{\pi_E} - V^{\overline{\pi}} \leq \frac{1}{n} H \sum_{i=0}^{n} \left(\hat{L}(\pi_i, r_i) + \sqrt{\frac{C}{N}} \right) + H \sqrt{\frac{C_1}{n}}
$$

(118)

where $C_1 = 2 \ln |\mathcal{R}|$. Applying the Loss Bound (Lemma F.4), we have

$$
V^{\pi_E} - V^{\overline{\pi}} \leq \frac{1}{n} H \sum_{i=0}^{n} \left(\min \left\{ \epsilon_{\Pi} + \epsilon_{\Pi} \sqrt{\frac{C_0}{N}}, C_B \left(\epsilon_{\Pi} + \epsilon_{\Pi} \sqrt{\frac{C_0}{N+M}} \right) \right\} \right.
$$

$$
\left. + \sqrt{\frac{C}{N}} \right) + H \sqrt{\frac{C_1}{n}},
$$

(119)

which simplifies to

$$V^{\pi_E} - V^{\overline{\pi}} \le H \min \left\{ \epsilon_\Pi + \epsilon_\Pi \sqrt{\frac{C_0}{N}}, C_B \left(\epsilon_\Pi + \epsilon_\Pi \sqrt{\frac{C_0}{N+M}} \right) \right\} + H\sqrt{\frac{C}{N}}, + H\sqrt{\frac{C_1}{n}}, \quad (120)$$

where $C_B = \left\| \frac{d_\mu^{\pi_E}}{d_\mu^{\overline{\pi}_B}} \right\|_\infty$, H is the horizon, N is the number of expert state-action pairs, M is the number of offline state-action pairs, n is the number of reward updates, $C_0 = 2\ln\frac{|\Pi||\mathcal{R}|}{\delta}$, $C = \ln\frac{2|\mathcal{R}|}{\delta}$, and $C_1 = 2\ln|\mathcal{R}|$. $\qquad\square$

G IMPLEMENTATION DETAILS

We describe the implementation details in this section. We compare GUITAR against two behavioral cloning baselines (Pomerleau, 1988) and two IRL baselines (Swamy et al., 2023). The first behavioral cloning baseline is trained exclusively on the expert data, $BC(\pi_E)$, and the second is trained on the combination of expert and offline data, $BC(\pi_E + \pi_b)$, when offline data is available. We compare against two IRL algorithms: (1) Swamy et al. (2021a)'s moment-matching algorithm, MM, a traditional IRL algorithm with the Jensen-Shannon divergence replaced by an integral probability metric, and (2) Swamy et al. (2023)'s efficient IRL algorithm, FILTER, that exclusively leverages expert data for resets.

We train all IRL algorithms with the same expert data and hyperparameters. The difference between MM, FILTER, and GUITAR can be summarized by the reset distribution they use. MM resets the learner to the true starting state (i.e. $\rho = \mu$), while FILTER resets the learner to expert states (i.e. $\rho = \rho_E$). GUITAR resets the learner to offline data (i.e. $\rho = \rho_B$), when offline data is available, and otherwise resets to a subset of the expert data. In other words, we isolate the effects of the reset distribution by using the same underlying IRL algorithm but simply change the reset distribution used in the RL optimizer step. This makes GUITAR easy to implement and easily adaptable to other IRL algorithms.

We adapt Ren et al. (2024)'s codebase for our implementation and follow their implementation details. We restate Ren et al. (2024)'s details here, with modifications where necessary. We apply Optimistic Adam (Daskalakis et al., 2017) for all policy and discriminator optimization. We also apply gradient penalties (Gulrajani et al., 2017) on all algorithms to stabilize the discriminator training. The policies, value functions, and discriminators are all 2-layer ReLu networks with a hidden size of 256. We sample 4 trajectories to use in the discriminator update at the end of each outer-loop iteration, and a batch size of 4096. In all IRL variants (MM, FILTER, and GUITAR), we re-label the data with the current reward function during policy improvement, rather than keeping the labels that were set when the data was added to the replay buffer. Ren et al. (2024) empirically observed such re-labeling to improve performance. We release a forked version of Ren et al. (2024)'s code: https://nico-espinosadice.github.io/efficient-IRL/.

We calculate the inter-quartile mean (IQM) and standard errors across seeds for all experiments.

G.1 MUJOCO TASKS

G.1.1 SETTING WITHOUT GENERATIVE MODEL ACCESS

We detail below the specific implementations used in all MuJoCo experiments (Ant, Hopper, and Humanoid).

PARAMETER	VALUE
BUFFER SIZE	1E6
BATCH SIZE	256
γ	0.98
τ	0.02
TRAINING FREQ.	64
GRADIENT STEPS	64
LEARNING RATE	LIN. SCHED. 7.3E-4
POLICY ARCHITECTURE	256 X 2
STATE-DEPENDENT EXPLORATION	TRUE
TRAINING TIMESTEPS	1E6

Table 1: Hyperparameters for baselines using SAC.

Expert Data. To experiment under the conditions of limited expert data, we set the amount of expert data to be the lowest amount that still enabled the baseline IRL algorithms to learn. For Ant, this was 50 expert state-action pairs. For Humanoid, this was 100 expert state-action pairs. For Hopper, this was 600 expert state-action pairs.

Joint	Default	Modified
Right hip_x	$[-25°, 5°]$	$[0°, 30°]$
Left hip_x	$[-25°, 5°]$	$[0°, 30°]$
Left knee	$[-160°, -2°]$	$[-100°, 50°]$

(a) Joint angle range differences

Body Part	Default	Modified	
Right thigh	0.06	0.09	(+50%)
Right foot	0.075	0.1	(+33%)
Left lower arm	0.031	0.04	(+29%)

(b) Size parameter differences

Table 2: Comparison between default and modified Humanoid configurations.

Offline Data. We generate the offline data by rolling out the expert policy with a probability $p_{\text{tremble}}^{\pi_B}$ of sampling a random action. $p_{\text{tremble}}^{\pi_B} = 0.25$ for the Ant environment and $p_{\text{tremble}}^{\pi_B} = 0.05$ for the Hopper and Humanoid environments.

Discriminator. For our discriminator, we start with a learning rate of $8e-4$ and decay it linearly over outer-loop iterations. We update the discriminator every 10,000 actor steps.

Baselines. We train all behavioral cloning baselines for 300k steps for Ant, Hopper, and Humanoid. For MM and FILTER baselines, we follow the exact hyperparameters in Ren et al. (2024), with a notable modification to how resets are performed, discussed below. We use the Soft Actor Critic (Haarnoja et al., 2018) implementation provided by Raffin et al. (2021) with the hyperparameters in Table 1.

Reset Substitute. We mimic resets by training a BC policy on the reset distribution specified by each algorithm. MM does not employ resets. FILTER's reset distribution is the expert data. GUITAR's reset distribution is a mixture of the expert and offline data. The BC roll-in logic follows Ren et al. (2024)'s reset logic. The probability of performing a non-starting-state reset (i.e. an expert reset in FILTER) is α. If a non-starting-state reset is performed, we sample a random timestep t between 0 and the horizon, and we roll-out the BC policy in the environment for t steps.

GUITAR. GUITAR follows the same implementation and reset logic as FILTER, with the only change being the training data for the BC roll-in policy.

G.1.2 MISSPECIFIED SETTING 3: UNREALIZABLE EXPERT STATES DUE TO MORPHOLOGICAL DIFFERENCES

For these experiments, we use the same parameters as in Section G.1.1, with the following changes.

Expert Data. We use the same expert policy as in Section G.1.1. However, we do not consider the finite expert sample regime, so we use 100,000 state-action pairs from the expert policy. Notably, this expert policy uses the default configuration (i.e. the default MJCF file, MuJoCo's XML file specifying the robot's morphology, including link lengths and joint ranges) and we collect expert data by rolling out the policy with the default morphology.

Offline Data. We generate the offline data by training a policy under a new configuration, specified below, otherwise following a similar setup to training the expert policy. We collect 100,000 state-action pairs from the offline policy by rolling it out with the new morphology.

Baselines. We train all behavioral cloning baselines for 300k steps for Humanoid and Walker. For MM and FILTER baselines, we otherwise follow the exact hyperparameters in Ren et al. (2024), except for varying the robot's morphology. We use the Soft Actor Critic (Haarnoja et al., 2018) implementation provided by Raffin et al. (2021) with the hyperparameters in Table 1.

Resets. MM resets the learner to the true starting state, so no changes are needed. FILTER resets the learner to expert states. However, due to the difference in morphology between the expert and learner, it is not possible to reset the learner to expert states. Therefore, FILTER cannot be applied in this misspecified setting.

Joint	Default	Modified
Thigh joint	$[-150°, 0°]$	$[-120°, 0°]$
Leg joint	$[-150°, 0°]$	$[-120°, 0°]$
Foot joint	$[-45°, 45°]$	$[-25°, 25°]$
Thigh left joint	$[-150°, 0°]$	$[-120°, 0°]$
Leg left joint	$[-150°, 0°]$	$[-120°, 0°]$
Foot left joint	$[-45°, 45°]$	$[-45°, 45°]$

(a) Joint angle range differences

Table 3: Comparison between default and modified Walker2d configurations.

GUITAR. GUITAR follows the same implementation as FILTER, with the notable change of its reset distribution. Unlike FILTER, GUITAR resets the learner to the offline data, and in contrast to resetting to expert states, is possible in this case, since the offline behavior policy and the learner have the same morphology.

Learner. The learner, in both the training and evaluation environments, has a modified morphology, as indicated by Table 2 and 3 for Humanoid and Walker2d, respectively.

G.2 D4RL TASKS

G.2.1 VARYING STATE IMPORTANCE IN EXPERT RESETS

For the two Antmaze-Large tasks, we use the data provided by Fu et al. (2020) as the expert demonstrations. We append goal information to the observation for all algorithms following Ren et al. (2024); Swamy et al. (2023). For our policy optimizer in every algorithm, we build upon the TD3+BC implementation of Fujimoto & Gu (2021) with the default hyperparameters.

Expert Data and Discriminator. We use the relevant D4RL dataset to learn the discriminator. For our discriminator, we start with a learning rate of $8e - 3$ and decay it linearly over outer-loop iterations. We update the discriminator every 5,000 actor steps.

Baselines. For behavioral cloning, we run the TD3+BC optimizer for 500,000 steps while zeroing out the component of the actor update that depends on rewards. We use a reset proportion of $\alpha = 1.0$. We provide all runs with the same expert data. All IRL algorithms are pretrained with 10,000 steps of behavioral cloning on the expert dataset.

Reset Distributions. We reset GUITAR to various reset distributions. We consider the expert dataset, short trajectories (of length less than 500) in the expert dataset, and long trajectories (of length greater than or equal to 500) in the expert dataset. We use each of these datasets as different reset distributions. For the D4RL tasks, we perform true state resets (i.e. reset the learner to states in the reset distribution), rather than perform BC roll-ins as done in the MuJoCo tasks. Notably, IRL with resets to the true starting state distribution (i.e. no selective reset distribution) has been well studied by prior work (Swamy et al., 2023; Ren et al., 2024) and observed to not solve the Antmaze-Large tasks.

G.2.2 MISSPECIFIED SETTING 1: UNREALIZABLE EXPERT ACTIONS

For the expert action misspecification experiments, we train an RL expert using TD3+BC. We append goal information to the observation for all algorithms following Ren et al. (2024); Swamy et al. (2023). For our policy optimizer in every algorithm, we build upon the TD3+BC implementation of Fujimoto & Gu (2021) with the default hyperparameters.

Figure 5: We plot the coverage of the D4RL `Antmaze-Large` expert data, including the full dataset, short trajectories (episodes shorter than 500 steps), and long trajectories (episodes 500 steps or longer).

Expert Data and Offline Data. We collect expert data by first training an RL expert using TD3+BC on the following maze map:

$$
M_{\pi_E} := \begin{bmatrix} 1 & 1 & 1 & 1 & 1 \\ 1 & \mathbf{0} & 0 & 0 & 1 \\ 1 & \mathbf{R} & 1 & \mathbf{G} & 1 \\ 1 & \mathbf{1} & 0 & 0 & 1 \\ 1 & 1 & 1 & 1 & 1 \end{bmatrix}
$$

where $\mathbf{R}$ is the starting state and $\mathbf{G}$ is the goal state. The expert policy is then rolled out for 100,000 state-action samples. We collect the offline data by training an RL agent using TD3+BC on the following maze map:

$$
M_{\pi_B} := \begin{bmatrix} 1 & 1 & 1 & 1 & 1 \\ 1 & \mathbf{1} & 0 & 0 & 1 \\ 1 & \mathbf{R} & 1 & \mathbf{G} & 1 \\ 1 & \mathbf{0} & 0 & 0 & 1 \\ 1 & 1 & 1 & 1 & 1 \end{bmatrix}
$$

and then rolling out the policy for 100,000 state-action samples. The differences between M_{π_E} and M_{π_B} are bolded.

Discriminator. We use the expert data to learn the discriminator. For our discriminator, we start with a learning rate of $8e-3$ and decay it linearly over outer-loop iterations. We update the discriminator every 5,000 actor steps. We use 10 sample trajectories for the discriminator update. Since this is a strongly misspecified setting, we only use the x-position of the agent as the input to the discriminator for all IRL algorithms. The explanation for this design choice is that the learner's and the expert's behaviors may differ how they solve the maze (i.e. the y-position), but the goal is to finish the maze in some way (i.e. dependent on the x-position).

Baselines and Reset Distributions. For behavioral cloning, we run the TD3+BC optimizer for 500,000 steps while zeroing out the component of the actor update that depends on rewards. We use a reset proportion of $\alpha = 1.0$. We provide all runs with the same expert data. Due to the strong misspecification in this task, we do not pretrain the IRL algorithms with behavioral cloning.

`MM` is reset to the true starting state, while `FILTER` is reset to the expert data. `GUITAR` is reset to the offline data (i.e. π_B's data).

Misspecification. The learner is trained and evaluated on the map M_{π_B}. Notably, this difference ensures that the expert policy solves the maze via one path, and the learner must solve it in a different path, where the only shared states can be the start and goal states. For the expert and offline data collection, as well as the learner's environment, we add a `BackWallGoalWrapper`, which allows the expert to achieve a reward of 1.0 by solving the maze through the "top hallway," but due to the block in the learner's maze, the learner is only able to achieve a reward of 0.9 by solving the maze through the "bottom hallway." The `BackWallGoalWrapper`'s required x-position to solve the maze is 4.0.

It should be noted that this is not the typical Antmaze-Umaze task, which can typically be solved by IRL approaches. In this setting, we consider the strongly misspecified setting, where the expert policy solves the maze one way, but the learner must solve it differently due to differences in the maze at "test-time." The degree of exploration difficulty due to the misspecification is likely the reason for the poor performance of the baselines.

G.2.3 MISSPECIFIED SETTING 2: UNREALIZABLE EXPERT STATES DUE TO SAFETY CONSTRAINTS

Expert Data and Offline Data. We train an expert policy via RL to solve the `Antmaze-Umaze-v2` task and roll-out the policy in the default Umaze configuration to collect 100,000 state-action pairs. We use the same policy for the offline data, but we stop the roll-out once the "safety constraint" is reached (described below). This means that the offline data consists of only states from the "first hallway" in the maze.

Misspecification. To incorporate a "safety constraint," such that the learner is not able to reach the "bottom halllway" of the maze, we impose a time constraint in the learner's environment, such that after 'T=50' steps, the episode terminates.

Discriminator. We use the expert data to learn the discriminator. For our discriminator, we start with a learning rate of $8e - 3$ and decay it linearly over outer-loop iterations. We update the discriminator every 5,000 actor steps. We use 10 sample trajectories for the discriminator update. We use full agent's observation for the discriminator input.

Baselines and Reset Distributions. For behavioral cloning, we run the TD3+BC optimizer for 500,000 steps while zeroing out the component of the actor update that depends on rewards. We use a reset proportion of $\alpha = 1.0$. We provide all runs with the same expert data. Due to the strong misspecification in this task, we do not pretrain the IRL algorithms with behavioral cloning.

`MM` is reset to the true starting state, while `FILTER` is reset to the expert data. `GUITAR` is reset to the offline data (i.e. π_B's data).

H   SETTING WITHOUT GENERATIVE MODEL ACCESS

We consider two additional constraints common in real-world robotics applications: settings with finite expert data and environments without generative model access (i.e. where the robot cannot be reset to an arbitrary state). To ensure we train in the low-data regime, we used the minimum amount of expert data that allowed the baseline IRL algorithm (MM) to learn in each environment (notably, less than one full episode). The offline data was generated by rolling out the pretrained expert policy with a probability $p_{\text{tremble}}^{\pi_b}$ of sampling a random action. We mimic resets by rolling in with a BC policy trained on the corresponding reset distribution. More specifically, FILTER's reset distribution are expert states, so FILTER rolls in with $\text{BC}(\pi_E)$. GUITAR's reset distribution are a mixture of expert and offline states, so GUITAR rolls in with $\text{BC}(\pi_E + \pi_b)$. MM continues to reset to the environment's true starting state.

Figure 6: **Environment without arbitrary reset access.** Standard errors are computed across 10 seeds for FILTER and GUITAR and 3 seeds for MM. Expert data is a partial trajectory (i.e. a subset of one full trajectory).

Based on Theorem 4.1, the sample efficiency of IRL should improve as the reset distribution's coverage of the expert's state distribution improves. More formally, this is when

$$C_B = \left\| \frac{d_\mu^{\pi_E}}{\rho} \right\|_\infty \to 1, \tag{121}$$

where $d_\mu^{\pi_E}$ is the expert's state distribution and ρ is the reset distribution. Since GUITAR resets to $\text{BC}(\pi_E + \pi_b)$, the performance of $\text{BC}(\pi_E + \pi_b)$ is an estimation of the GUITAR's reset distribution's coverage of the expert's state distribution, and correspondingly for FILTER's reset distribution and $\text{BC}(\pi_E)$. From Figure 6, we see that as the reset distribution's coverage of the expert's states improves—as measured by the corresponding BC performance—so does the performance of the IRL algorithm. In the case where the BC performance is poor (Humanoid-v3), there is no observable benefit to modified resets.

I   FURTHER ANALYSIS OF MISSPECIFICATION SETTINGS

We theoretically analyze the setting of unrealizable expert actions below. In the case of a perfect reset distribution on the best realizable policy $\pi^\star$, where $\rho = d_\mu^{\pi^\star}$ and $C_S = 1$, we can present a straightforward bound on the performance gap, focusing on misspecification error and optimization error.

Corollary I.1 (Performance Gap under Resets to $\pi^\star$). *Consider the case of infinite expert data samples, such that $\rho_E = d_\mu^{\pi_E}$, perfect reset distribution coverage, such that $\rho = d_\mu^{\pi^\star}$, and perfect reward learning, such that the reward regret error is negligible. Denote $\pi_i = (\pi_{i,1}, \pi_{i,2}, \ldots, \pi_{i,H})$ as the policy returned by ϵ-approximate PSDP at iteration $i \in [n]$ of Algorithm 2. Then, the performance gap is given by*

$$V^{\pi_E} - V^{\pi} \leq \underbrace{V^{\pi_E} - V^{\pi^\star}}_{\textit{Misspecification Error}} + \underbrace{H^2 \epsilon}_{\textit{Optimization Error}} \tag{122}$$

where H is the horizon and $\overline{\overline{\pi}}$ is the trajectory-level average of the learned policies (i.e. π_i at each iteration $i \in [n]$ of Algorithm 2).

Corollary I.1 presents the performance gap with resets to the best realizable policy's state distribution. Notably, by considering the perfect scenario of infinite expert data, perfect reset distribution coverage, and perfect reward learning, our bound does not include the policy completeness error ϵ_Π and instead is an extension of Swamy et al. (2023)'s NRMM algorithm to the misspecified setting.

J   USEFUL LEMMAS

Theorem J.1 (Hoeffding's Inequality). *If $Z_1, \ldots, Z_M$ are independent with $P(a \leq Z_i \leq b) = 1$ and common mean μ, then, with probability at least $1 - \delta$,*

$$|\overline{Z}_M - \mu| \leq \sqrt{\frac{c}{2M} \ln \frac{2}{\delta}} \tag{123}$$

where $c = \frac{1}{M} \sum_{i=1}^{M} (b_i - a_i)^2$.

Lemma J.2 (Online Mirror Descent Regret). *Regret is defined as*

$$\lambda_N = \frac{1}{N} \sum_{t=1}^{N} \ell(\hat{\mathbf{y}}_t, z_t) - \inf_{\mathbf{f} \in \mathcal{F}} \frac{1}{N} \sum_{t=1}^{N} \ell(\mathbf{f}, z_t). \tag{124}$$

Given $\mathcal{F} = \Delta(\mathcal{F}')$ and $\langle \mathbf{f}, \nabla_t \rangle = \mathbb{E}_{f' \sim \mathbf{f}}[\ell(f', (x_t, y_t))]$, where $\sup_{\nabla \in \mathcal{D}} \|\nabla\|_\infty \leq B$, let R be any 1-strongly convex function. If we use the Mirror descent algorithm with $\eta = \sqrt{\frac{2 \sup_{\mathbf{f} \in \mathcal{F}} R(\mathbf{f})}{N B^2}}$, then,

$$\lambda_n \leq \sqrt{\frac{2 B^2 \sup_{\mathbf{f} \in \mathcal{F}} R(\mathbf{f})}{N}}. \tag{125}$$

If R is the negative entropy function, then $\sup_{\mathbf{f} \in \mathcal{F}} R(\mathbf{f}) \leq \log |\mathcal{F}'|$.