Adaptive Duration Modification of Speech using Masked Convolutional Networks and Open-Loop Time Warping

Abstract

We propose a new method to adaptively modify the rhythm of a given speech signal. We train a masked convolutional encoder-decoder network to generate this attention map via a stochastic version of the mean absolute error loss function. Our model also predicts the length of the target speech signal using the encoder embeddings, which determines the number of time steps for the decoding operation. During testing, we use the learned attention map as a proxy for the frame-wise similarity matrix between the given input speech and an unknown target speech signal. In an open-loop fashion, we compute a warping path for rhythm modification. Our experiments demonstrate that this adaptive framework achieves similar performance as the fully supervised dynamic time warping algorithm on both voice conversion and emotion conversion tasks. We also show that the modified speech utterances achieve high user quality ratings, thus highlighting the practical utility of our method.

1. Introduction

Human speech is a rich and varied mode of communication that encompasses both semantic information and the mood/intent of the speaker. The latter attribute is primarily conveyed by prosodic features, such as pitch, energy, and speaking rhythm. Many open problems in speech rely on a deeper understanding of and ability to manipulate these prosodic features. Consider voice conversion and emotion conversion systems. Pitch and energy modifications can be used to inject emotional cues into the neutral speech or to change the overall speaking style [1, 2, 3, 4, 5]. Prosodic features are also used to evaluate the quality of human machine dialog systems [6], and they play a significant role in speaker identification and recognition [7]. Rhythm, in particular, plays a crucial role in conveying emotions [8] and in diagnosing human speech pathologies [9].

While there are many approaches for automated pitch and energy modification [10, 11, 12, 13, 14], comparatively little progress has been made in changing the rhythm of a speech utterance. In fact, rhythm is difficult to manipulate because, unlike pitch or energy, there is no explicit coding for the relative duration of phonemes across the utterance. Rather, this information is implicitly defined and varies dramatically across speakers and utterances. As a result, rhythm modification methods either require considerable user supervision or they are geared towards aligning to known speech signals. Even prior work on quantifying the transitory behavior of rhythm [15] is limited and requires *a priori* alignment of the audio files.

Perhaps the earliest duration modification method is the time-domain pitch synchronous overlap and add (TD-PSOLA) algorithm [16]. TD-PSOLA modifies the pitch and duration of a speech signal by replicating and interpolating between individual frames centered at the peaks of auto-correlation signal. However, the user must manually specify both the portion of speech to modify and the exact manner in which it should be altered. Methods such as [17, 18] take a more user-friendly and performative approach to modify the pitch and rhythm, but they still require manual input to guide the process. An alternate approach to changing rhythm is a framewise alignment between a source utterance and a given target. Here, the most common approach is Dynamic Time Warping (DTW) [19]. It is a dynamic programming approach to align two sequences of different lengths. DTW requires both, the source and target speech which renders it unusable for generative modeling.

Finally, recent advancements in deep learning have led to a new generation of neural vocoders that disentangle the semantic content from the speaking style [20, 21, 22]. These vocoders can alter the speaking rate via the learned style embeddings. While these models represent seminal contributions to speech synthesis, the latent representations are learned in an unsupervised manner, which makes it difficult for the user to control the output speaking style. Another drawback is that these methods require large amounts of data and computational resources for adequate model training and speech generation [23].

In this paper, we introduce an automated and adaptive speech duration modification scheme. Our approach combines the structured simplicity of dynamic decoding with the representation capabilities of deep neural networks. Namely, we model the alignment between a source and target utterance via a latent attention map; these maps are used as replacement of the similarity matrix for backtracking. We train a masked convolutional encoder-decoder network to estimate these attention maps using a stochastic mean absolute error (MAE) formulation. Unlike the conventional DTW [19] algorithm, once trained our framework operates in an open-loop fashion on the source utterance without needing access to the target. We demonstrate our framework on a voice conversion task using the CMU-Arctic dataset [24] and on three multi-speaker emotion conversion tasks using the VESUS dataset [25]. Our experiments confirm that the proposed model can perform adaptive duration modification with limited training data and minimal distortion.

2. Method

Our technique uses an attention based encoder-decoder framework to process an input sequence and produce another sequence as output. Specifically, the input sequences used in our model are the Mel-frequency representation of a speech signal. We further inject domain knowledge or prior into the neural network model by restricting the scope of the attention map between the encoded and decoded representations and strategically leverage DTW to generate intelligible speech. We provide a brief description of the training/testing strategy followed by a

Figure 1: *Model architecture used for the sequence-to-sequence speech generation. The encoder and decoder modules consist of 10 identical blocks. Projection layers are simple feed-forward layers without any non-linearity to project input features in high dimension.*

discussion of the baseline methods at the end of this section.

2.1. Convolutional sequence-to-sequence model

We use a masked convolutional sequence-to-sequence model to learn the duration transformation from one domain to another. Fig. 1 shows the interplay between the encoder, decoder and modified attention modules of our deep neural network. The architecture is adapted from [26] by adding residual connections to the final layer and reconfiguring the attention module. The encoder in Fig. 1 is a stack of gated convolutions which performs two tasks: (i) approximating the length of the target sequence and (ii) learning appropriate representation for the decoding process. We insert an attention module between the encoder and decoder layers to leverage locality constraint during the generation of the output sequence. Notice that, a general attention map uses the entire input sequence to decode a single frame of the output sequence. Therefore, we apply a masking strategy inspired by Itakura parallelogram of DTW framework which acts as a prior knowledge over the difference in speaking rates between the source and target domains. Masked convolutions were initially proposed by [26] for language modeling. This architecture allows the network to exploit local continuity of speech and can be trained faster than a conventional RNN or LSTM while also requiring fewer learnable parameters. These advantages are important in cases of limited training data.

Our loss function is an L1 penalty over the prediction of the (relative) target sequence length T combined and a stochastic version of absolute frame-wise error between the target sequence Y and the estimate $\hat{Y}$. Empirically, we find that predicting the relative length of the target sequence is more robust than predicting a stop token when trained on smaller datasets. We further randomize over the decoder input in each layer by picking a weighted sum of encoder representations using the attention map. This randomization prevents the attention matrix from diverging, particularly at the start of the training procedure. Our combined loss function is therefore written as:

$$\mathcal{L}(\theta, \gamma) = \lambda_1 \, E_{A_t \sim q_\theta} \left[\|\hat{Y}_t - Y_t\|_1 \right] + \lambda_2 \, \|\hat{T} - T\|_1, \quad (1)$$

The hyperparameters λ_1 and λ_2 in Eq. (1) corresponding to the

Figure 2: *Binary attention masks with 3 different slopes.*

frame-wise regression and relative length prediction errors, respectively. The attention map is sampled from its approximate distribution (denoted by q_θ) conditioned on the input sequence, the target sequence generated so far, and the Itakura mask.

2.2. Masking

We use the mask M to constrain the scope of the attention mechanism to be similar in time-scale to the input. This procedure is important for two reasons. From a speech quality perspective, large local swings in speaking rate may generate unintelligible speech. From an estimation perspective, the speech utterances contains hundreds (sometimes thousands) of frames. It is difficult to robustly train a deep network to generate such long attention vectors based on smaller datasets.

We use masks derived from Itakura parallelogram [27], as illustrated in Fig. 2. The slope of the Itakura parallelogram specifies the minimum and maximum speaking rates that the reconstructed utterances are allowed to possess in comparison to the input speech. In this paper, we fixed the minimum and maximum variation in speaking rate to 0.8 and 1.25, respectively, based on empirical observations of the training data.

2.3. DTW Back-Tracking

Our final step uses the learned attention map as a proxy for the DTW similarity matrix. This strategy allows us to train the model on a relatively small dataset (e.g., 2-3 hours) and still generate intelligible speech during open-loop modification of new utterances. Formally, we apply a dynamic programming operation to the attention maps produced by the neural network to get a path of alignment from source to target. To avoid skip-

ping phonemes, we constrain the dynamic programming path to take at most one horizontal or vertical step at a time while backtracking. Once estimated, the path informs a reorganization of the source utterance frames via localized contraction and dilation operations. Following this reorganization, the target speech is synthesized via the WORLD vocoder [28].

We train our model using mini-batch gradient descent and the Adam optimizer [29] with a fixed learning rate of 10^{-4} and a batch size of 16. The input X are 80-dimensional Mel-filterbank energies spanning 0-8 kHz. The projection layer expands this input to 256 dimensions. Both the encoder and decoder consist of 10 convolutional layers, each followed by a gated linear unit. Given the small dataset size, we use data augmentation to mitigate over-fitting. Specifically, we reverse the input-output sequences and randomly extract intervals of variable size (with probability 0.5) from the full speech utterance.

Algorithm 1: Strategy for model training

1 function trainModelParameters (X, Y);
   Input : filterbank energies $(X \in \mathbb{R}^{D \times T_s}, Y \in \mathbb{R}^{D \times T_t})$
   Output: model parameters (θ, γ)
2 **if** *epoch < MaxEpochs* **then**
3   **for** *minibatch* **do**
4   Predict target length $\hat{T} = f_\gamma(X)$ and create
     the mask $M \in \mathbb{R}^{T_s \times T_t}$;
5   Estimate $A \in \mathbb{R}^{T_s \times T_t}$ using masked
     convolution and sample $u \sim U(0, 1)$;
6   **if** *u < 0.2* **then**
7   Sample $a \in \mathbb{R}^{T_s}$ from A_{T_s};
8   Reconstruct using:
      $\hat{Y}_t = X \cdot a + f_\theta(X, Y_{0:t-1})$;
9   **else**
10   Reconstruct using:
      $\hat{Y}_t = X \cdot A_{T_s} + f_\theta(X, Y_{0:t-1})$;
11   **end**
12   Compute prediction errors and update
     parameters;
13 **end**
14 epoch $\leftarrow$ epoch + 1;
15 **end**
16 return trainedModel;

2.4. Training and Testing Strategy

During training, we optimize Eq. 1) based on the Mel filterbank energies Y and utterance durations T from paired input-output utterances. The forward pass through the network (Fig. 1) processes the input frames and generates an embedding to predict the target sequence length $\hat{T}$. The embedding is also used to generate an attention vector as a categorical distribution at each decoder step inside the specified masked region. We use a stochastic sampling procedure for the attention vector, in which we randomly mix between a single sample from the distribution q_θ and the MAP estimate. Empirically, this strategy provides robustness to sub-optimal local minima (see Alg. 1).

During testing, we rely on the predicted length to generate the attention map and the target frames. We also use a MAP

Algorithm 2: Strategy for model testing (i.e., open-loop duration modification)

1 function modifyDuration (X);
   Input : filter-bank energy $(X \in \mathbb{R}^{D \times T_s}$ and $Y_0)$
   Output: alignments $((x_1, y_1), (x_2, y_2), ...)$
2 Predict length of target sequence $\hat{T}_t = f_\gamma(X)$;
3 Create attention mask $M \in \mathbb{R}^{T_s \times \hat{T}_t}$ and Set $t = 0$;
4 **if** $t < \hat{T}_t$ **then**
5   Using mask M_t, X, and $Y_{0:t-1}$ estimate A_t;
6   Using X, $Y_{0:t-1}$, and A_t, predict Y_t;
7   $t \leftarrow t + 1$;
8 **end**
9 Run DTW backtracking on the attention matrix A;
10 return (alignments $(x_1, y_1), (x_2, y_2), ...(x_n, y_n))$;

Figure 3: *Length prediction errors across different models.*

strategy, rather than the stochastic mixing procedure. Once generated, we use the attention map as a proxy for the DTW similarity matrix; using a Viterbi alignment procedure, we rearrange the input frames to produce the modified speech (Alg.2).

2.5. Baseline Comparison Methods

We compare our convolutional encoder with two commonly used sequence-to-sequence frameworks: (i) Gated Recurrent Unit or GRU model [30], and (ii) Transformer model [31]. Due to space limitations, further details of the baseline architectures and training strategy have been omitted from the paper.

3. Experimental Results

We evaluate our rhythm modification framework on two publicly available multi-speaker datasets: CMU-ARCTIC [24] for voice morphing and VESUS [25] for emotion conversion.

3.1. Data and Conversion Tasks

The CMU-ARCTIC database has 4 American English speakers (two male, two female), who we paired by gender for voice conversion. Of the resulting 2264 sentence pairs, we train our model and the baselines using 2164 utterances and reserve the remaining 100 utterances (random 50-50 split) for validation and testing of the open-loop modification properties.

VESUS is an emotional speech corpus containing utterances in 4 emotion classes: neutral, angry, happy, and sad. Each utterance contains 10 crowd-sourced ratings of emotional

Figure 4: *Alignment similarity between attention map and DTW.*

Figure 5: *(a) Length prediction of target utterances and (b) measuring similarity of attention map to DTW cost matrix. The model is trained without masking constraint on attention map.*

Figure 6: *(a) Length prediction of target utterances and (b) measuring similarity of attention map to DTW cost matrix. The model is trained without residual connection in decoder layer.*

saliency For robustness, we only use utterances that are correctly annotated by at least half of the listeners. We consider three neutral-emotional conversion tasks as follows:

- **Neutral to Angry**: 2385 utterances for training, 72 for validation and, 61 for testing.
- **Neutral to Happy**: 2431 utterances for training, 43 for validation and, 43 for testing.
- **Neutral to Sad**: 2371 utterances for training, 75 for validation and, 63 for testing.

Due to the smaller sample size, we pretrain the models on CMU-ARCTIC and fine-tune it for emotion conversion.

3.2. Length Prediction

As a sanity check, we compare the predicted utterance length by our framework with that of the ground truth parallel utterance. Fig. 3 shows the error in predicting the length ratio in a ms/sec format. Notice that, our framework mispredicts the utterance lengths by only 40ms/sec and 65ms/sec (on average) on CMU-ARCTIC and VESUS, respectively. Duration prediction is particularly challenging on VESUS due to marked differences between neutral and emotional utterances. The median prediction error for GRU model is in the range of $400 - 600ms$ per second of the input utterance. The Transformer fares relatively well in comparison to GRU because of its ability to establish long-range dependency. However, our framework performs slightly better, perhaps due to the multi-task setup and the fusion of deep representation with Bayesian regularization.

3.3. Attention Alignment

Next, we compare the open-loop alignment estimated via the attention map with the supervised DTW algorithm where both utterances are known. To compare the warping paths, we code the horizontal, diagonal, and vertical moves of the backtracking procedure into three classes. We then compute the edit distance between the attention map and DTW-based alignment schemes. Fig. 4 illustrates the match ratio normalized by the average length of sequences. As seen, the match ratio varies between 0.70 and 0.85, which suggests that our convolutional model can readily learn the general characteristics of duration modification. The GRU model performs poorly in this task due to its inability to learn sequence transformations across 100s of frames. The Transformer model does a little better than the GRU on this task, but still underperforms our method, likely due to the small training dataset. Our proposed model performs best because of the Itakura masking constraint and its reduced parameterization, which permits learning in small-data regimes. Thus, our method can be used as a tool for manipulation of

speaking rate at both, local and global scale.

3.4. Ablation Analysis: Removing Itakura masking

There are multiple components in the proposed model which work in synchronised manner to produce naturally sounding speech. In addition to the generative modeling, the two most important augmentations we have made to the masked convolutional network pipeline are: (i) using Itakura masking for attention map and (ii) using an attention weighted residual connection in the final layer. Therefore, we perform ablation experiments to understand the relative significance of each of these augmentations. Our first experiment removes masking from the attention layers. Fig. 5 shows the model's performance on target length prediction and approximating the DTW similarity matrix. The results in Fig. 5(a) indicate that the length prediction performance is roughly similar to the proposed model. This is expected because, the encoder part of the network is exactly same. The attention map is constrained only in the encoder-to-decoder transition. Hence, it estimates length with a relatively small error (in ms/sec). The match ratio metric however, (shown in Fig. 5(b)) is considerably worse. Itakura masking procedure acts as a good inductive bias/prior on the attention map because the speech rate do not fluctuate drastically in human conversations. Therefore, our localization scheme for the attention map is crucial to improve the edit distance in our model.

3.5. Ablation Analysis: Removing Residual connection

Our second ablation experiment involves removing the attention weighted residual connection from the final layer of decoder. Fig. 6(a) shows that the model is able to estimate the target sequence lengths with a relatively low error rate. We attribute this to the fact that the encoder portion is same as proposed model. The match ratio (Fig. 6(b)) in this experiment is slightly better

Figure 7: *Duration differences between source/target and source/converted pairs for vowels, consonants, and pauses.*

Figure 8: *MOS of generated speech evaluated via AMT.*

than the no-masking results but, worse than the proposed model. Therefore, we can confidently say both Itakura masking scheme and residual connection helps in approximating DTW similarity matrix. Further, the presence of residual connection is extremely useful in providing a good gradient signal for the convolutional network to learn prediction of target frames. Since the linguistic content of input and target utterances are same, it further allows the neural network to inherit input speech properties which is helpful in auto-regressive generation mode.

3.6. Component-Wise Duration Analysis

Fig. 7 compares the differences in duration between the converted utterances and the ground truth targets for vowels, consonants and short pauses. We use the Penn Phonetic Forced Alignment tool [32] to get the text and speech alignment. As seen in Fig. 7, our method faithfully modifies the duration of vowels and consonants, but it is less effective with short pauses. This trend is intuitive, as our model relies on replication of the frames determined by the backtracking on similarity map. Therefore, it cannot create pauses if these frames do not exist in the source utterances. Nonetheless, our model consistently estimates the difference between vowels and consonants duration across multiple tasks, which corroborates our claim of developing a general purpose speech rate manipulation framework.

3.7. Speech Reconstruction Quality

Finally, we use crowd sourcing to obtain a mean opinion score (MOS) for the re-synthesized speech quality of the testing ut-

terances. The crowd sourcing was performed using Amazon mechanical turk (AMT). We collect 5 listener ratings for each converted utterance in the test set, and we also add noisy utterances to the converted samples set to flag non-invested listeners and bots on AMT. As seen in Fig. 8, our method achieves an average MOS between $3.7 - 4.0$ across the four tasks, which is commensurate to neural vocoders such as [20, 21, 33]. We note that CMU-ARCTIC task has the lowest MOS, perhaps due to the longer and more complex utterances. Interestingly, the MOS is unaffected by errors in length prediction, as evidenced by the VESUS neutral-angry emotion conversion task. Thus, our model provides a robust way to alter speech characteristics.

4. Conclusions

We have introduced a new framework for adaptive rhythm modification. Our model used an attention based convolutional encoder-decoder architecture to estimate attention maps which associate frames of the input speech with frames of the target speech. The attention maps are modeled as latent variables in a graphical framework (supplementary material), which lead to a stochastic formulation of the mean absolute error (MAE) loss for model training. During testing, the attention map is directly used as an approximation of the similarity matrix for a DTW-style backtracking procedure. We evaluated our framework on a voice conversion and three separate emotion conversion tasks using CMU-ARCTIC and VESUS corporas. Our evaluation metrics are the L1 distance for target length prediction, and an edit distance based matching ratio for path similarity. Our proposed model outperformed existing seq-2-seq models designed solely on transformer and LSTM architectures in both metrics. Further, we ablate our proposed model's performance against simpler versions of it, i.e., no residual connection and no Itakura masking scheme. These ablations showed that removing either of these components leads to poor match ratio performance. Overall, our framework produced similar duration modification as the vanilla DTW, but *without requiring access to the target utterance*. Finally, we showed that the re-synthesized speech had similar naturalness to most state-of-the-art neural vocoders.

5. References

[1] J. A. Russell, J.-A. Bachorowski, and J.-M. Fernandez-Dols, "Facial and vocal expressions of emotion," *Annual Review of Psychology*, vol. 54, pp. 329–349, 11 2003.

[2] D. Schacter, D. T. Gilbert, and D. M. Wegner, *Psychology (2nd Edition)*. Worth Publications, 2011.

[3] R. Shankar, H.-W. Hsieh, N. Charon, and A. Venkataraman, "Automated Emotion Morphing in Speech Based on Diffeomorphic Curve Registration and Highway Networks," in *Proc. Interspeech 2019*, 2019, pp. 4499–4503.

[4] R. Shankar, J. Sager, and A. Venkataraman, "A Multi-Speaker Emotion Morphing Model Using Highway Networks and Maximum Likelihood Objective," in *Proc. Interspeech 2019*, 2019, pp. 2848–2852.

[5] R. Valle, J. Li, R. Prenger, and B. Catanzaro, "Mellotron: Multispeaker expressive voice synthesis by conditioning on rhythm, pitch and global style tokens," 2019.

[6] M. Swerts and E. Krahmer, "On the use of prosody for on-line evaluation of spoken dialogue systems," 04 2000.

[7] S. J. Park, C. Sigouin, J. Kreiman, P. Keating, J. Guo, G. Yeung, F.-Y. Kuo, and A. Alwan, "Speaker identity and voice quality: Modeling human responses and automatic speaker recognition," in *Interspeech 2016*, 2016, pp. 1044–1048.

[8] J. Schmidt, E. Janse, and O. Scharenborg, "Perception of emotion in conversational speech by younger and older listeners," *Frontiers in Psychology*, vol. 7, p. 781, 2016.

[9] S. P. Bayerl, F. Hönig, J. Reister, and K. Riedhammer, "Towards automated assessment of stuttering and stuttering therapy," 2020.

[10] T. Toda, A. W. Black, and K. Tokuda, "Voice conversion based on maximum-likelihood estimation of spectral parameter trajectory," *IEEE Transactions on Audio, Speech, and Language Processing*, vol. 15, no. 8, pp. 2222–2235, Nov 2007.

[11] R. Aihara, R. Takashima, T. Takiguchi, and Y. Ariki, "Gmm-based emotional voice conversion using spectrum and prosody features," *American Journal of Signal Processing*, vol. 2, pp. 134–138, 12 2012.

[12] T. Kaneko and H. Kameoka, "Parallel-data-free voice conversion using cycle-consistent adversarial networks," *CoRR*, vol. abs/1711.11293, 2017.

[13] R. Shankar, J. Sager, and A. Venkataraman, "Non-Parallel Emotion Conversion Using a Deep-Generative Hybrid Network and an Adversarial Pair Discriminator," in *Proc. Interspeech 2020*, 2020, pp. 3396–3400.

[14] R. Shankar, H.-W. Hsieh, N. Charon, and A. Venkataraman, "Multi-Speaker Emotion Conversion via Latent Variable Regularization and a Chained Encoder-Decoder-Predictor Network," in *Proc. Interspeech 2020*, 2020, pp. 3391–3395.

[15] D. Gibbon and U. Gut, "Measuring speech rhythm," 01 2001, pp. 95–98.

[16] F. Charpentier and M. Stella, "Diphone synthesis using an overlap-add technique for speech waveforms concatenation," *ICASSP '86. IEEE International Conference on Acoustics, Speech, and Signal Processing*, vol. 11, pp. 2015–2018, 1986.

[17] S. Beux, C. d'Alessandro, A. Rilliard, and B. Doval, "Calliphony: A system for real-time gestural modification of intonation and rhythm," 02 2022.

[18] S. Delalez and C. d'Alessandro, "Adjusting the Frame: Biphasic Performative Control of Speech Rhythm," in *Proc. Interspeech 2017*, 2017, pp. 864–868.

[19] H. Sakoe and S. Chiba, "Dynamic programming algorithm optimization for spoken word recognition," *IEEE Transactions on Acoustics, Speech, and Signal Processing*, vol. 26, no. 1, pp. 43–49, 1978.

[20] A. V. D. Oord, S. Dieleman, H. Zen, K. Simonyan, O. Vinyals, A. Graves, N. Kalchbrenner, A. W. Senior, and K. Kavukcuoglu, "Wavenet: A generative model for raw audio," *CoRR*, vol. abs/1609.03499, 2016.

[21] J. Shen, R. Pang, R. J. Weiss, M. Schuster, N. Jaitly, Z. Yang, Z. Chen, Y. Zhang, Y. Wang, R. J. Skerry-Ryan, R. A. Saurous, Y. Agiomyrgiannakis, and Y. Wu, "Natural TTS synthesis by conditioning wavenet on mel spectrogram predictions," *CoRR*, vol. abs/1712.05884, 2017.

[22] Y. Wang, R. J. Skerry-Ryan, Y. Xiao, D. Stanton, J. Shor, E. Battenberg, R. Clark, and R. A. Saurous, "Uncovering latent style factors for expressive speech synthesis," *CoRR*, vol. abs/1711.00520, 2017.

[23] Y. Yasuda, X. Wang, and J. Yamagishi, "Investigation of learning abilities on linguistic features in sequence-to-sequence text-to-speech synthesis," 2020.

[24] J. Kominek and A. W Black, "The cmu arctic speech databases," *SSW5-2004*, 01 2004.

[25] J. Sager, R. Shankar, J. Reinhold, and A. Venkataraman, "VESUS: A Crowd-Annotated Database to Study Emotion Production and Perception in Spoken English," in *Proc. Interspeech 2019*, 2019, pp. 316–320.

[26] J. Gehring, M. Auli, D. Grangier, D. Yarats, and Y. N. Dauphin, "Convolutional sequence to sequence learning," 2017.

[27] F. Itakura, "Minimum prediction residual principle applied to speech recognition," *IEEE Transactions on Acoustics, Speech, and Signal Processing*, vol. 23, no. 1, pp. 67–72, 1975.

[28] M. Morise, F. YOKOMORI, and K. Ozawa, "World: A vocoder-based high-quality speech synthesis system for real-time applications," *IEICE Transactions on Information and Systems*, vol. E99.D, pp. 1877–1884, 07 2016.

[29] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," *CoRR*, vol. abs/1412.6980, 2015.

[30] K. Cho, B. van Merrienboer, Ç. Gülçehre, F. Bougares, H. Schwenk, and Y. Bengio, "Learning phrase representations using RNN encoder-decoder for statistical machine translation," *CoRR*, vol. abs/1406.1078, 2014. [Online]. Available: http://arxiv.org/abs/1406.1078

[31] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin, "Attention is all you need," *CoRR*, vol. abs/1706.03762, 2017. [Online]. Available: http://arxiv.org/abs/1706.03762

[32] J. Yuan and M. Liberman, "Speaker identification on the scotus corpus," *Proceedings of Acoustics '08*, 2008.

[33] N. Kalchbrenner, E. Elsen, K. Simonyan, S. Noury, N. Casagrande, E. Lockhart, F. Stimberg, A. van den Oord, S. Dieleman, and K. Kavukcuoglu, "Efficient neural audio synthesis," in *Proc. ICML 2018*, J. G. Dy and A. Krause, Eds., vol. 80. PMLR, 2018, pp. 2415–2424.