RepFair-GAN: Mitigating Representation Bias in GANs Using Gradient Clipping

Abstract

This work introduces a new notion of fairness, *representational fairness*, for generative models, which ensures uniform representation of demographic groups in the generated data. Vanilla GANs violate this notion even when groups are equally represented in the training dataset. The proposed solution is to use *group-wise* gradient norm clipping to control gradient groups' magnitude during discriminator training. Experiments show that this method improves *representational fairness* while maintaining sample quality.

1 Introduction

The paper proposes a training process for GANs to generate data uniformly with respect to different groups at test time, addressing representation bias. We show that the magnitude of groups' gradient on the discriminator side during the training plays an important role in guiding the generator to sample groups uniformly at the test time. Our process clips the gradient norm of groups to improve GANs' ability to uniformly generate samples from equal and unequal groups representation in the training data. Related work includes FairGAN Xu et al. (2018) that aims to generate samples that can achieve statistical parity for downstream classifiers, while Xu et al. (2019) consider other group fairness notions for classification. This work focuses on improving GAN models' ability to generate data from different groups uniformly without targeting a specific task or fairness notion for classification.

2 RepFair-GAN

2.1 Representational Fairness

We consider a dataset $D = \{X, S\}$ with N data points, where $\mathcal{X} = \{x_i\}_{i=1}^{N}$ represents samples from the distribution $P_{data}(X)$ and $\mathcal{S} = \{s_i\}_{i=1}^{N}$ represents the binary sensitive attribute for each point. A GAN estimates $P_{\theta}(X) = P_{data}(X)$ by generating realistic data $D_{\theta} = g_{\theta}(Z)$ through the generator $g_{\theta} : \mathbb{R}^d \to \mathbb{R}^{n \times n}$. Where Z is a d dimensional noise vector. Using function $h : X \to S$, we can analyze the distribution of sensitive attributes in the generated data $P(h(g_{\theta}(Z)))$.

Definition: A well-trained generator (g_{θ}) is said to satisfy ε-*representationally fair* if it generates data, $D_{\theta} = g_{\theta}(Z)$, such that the distribution of the sensitive attribute S is close to the uniform distribution, $\mathcal{U}(S)$, i.e., $\text{dist}(P(h(g_{\theta}(Z))), \mathcal{U}(S)) \leq \varepsilon$.

We aim to achieve *representational fairness* by enforcing the distribution of sensitive attribute in the generated data to be close to the uniform distribution, i.e., $\text{KL}(\text{P}(\text{h}(\text{g}_{\theta}(\text{Z}))) \,|\, \mathcal{U}(S)) = \varepsilon$. When $\varepsilon = 0$, the generative model achieves strict uniformity over the sensitive attributes.

2.2 Biased data generation

Previous works Tan et al. (2020); Choi et al. (2020) have studied biases in GANs that generate non-uniformly distributed data over sensitive attributes. Balanced group representation doesn't prevent bias Kenfack et al. (2021); We hypothesize that the non-uniform generation results from disparities in gradient magnitude during discriminator training.

2.3 THE INFLUENCE OF THE MAGNITUDE OF THE GRADIENT VECTORS

Fig. 1 shows that the disparity in groups' gradient norms can lead to unfair generation in GANs, even when training data has equal representation of both groups. We designed a training process (Appendix 1) that controls the gradient of each group during training by modifying the discriminator training and enforcing a maximum gradient norm threshold to clip their gradients.

Figure 1: Unfair vanilla GANs on SVHN dataset had increasing differences in average gradient magnitudes between groups during training (a). After training, the generator sampled more from the group with a larger gradient (b).

3 EXPERIMENTS

We used MNIST LeCun et al. (1998) and SVHN Netzer et al. (2011) datasets, with MNIST divided into two groups based on background color and SVHN divided into two groups based on shaded and normal images as in Kenfack et al. (2021). Vanilla Goodfellow et al. (2014) and CGAN Mirza & Osindero (2014) models were trained on these datasets with different group representations. Experiments were based on 10 training runs and averaged across runs

3.1 RESULTS

During CGAN training, gradient norms were tracked, and Fig. 2 shows that the gradient magnitude difference between groups widened over time in an unfair CGAN, while in the proposed method, the gradient magnitudes of each group remained closer. The same pattern was observed on SVHN. The relationship between gradient and class representation tends to be more equal when gradients are close to each other as shown in the Fig. 3 in the appendix.

Figure 2: Gradient clipping was used to enforce closer gradient norms of each group during discriminator training, and its effect on the disparity in gradient norms was studied.

4 CONCLUSION

We proposed a new GAN training approach to address representation bias caused by gradient norm disparities during discriminator training. Empirical evaluation on MNIST and SVHN demonstrated significant improvement in group uniformity even in imbalanced datasets.

URM Statement

The authors acknowledge that at least one key author of this work meets the URM criteria of ICLR 2023 Tiny Papers Track.

References

Kristy Choi, Aditya Grover, Trisha Singh, Rui Shu, and Stefano Ermon. Fair generative modeling via weak supervision. In *International Conference on Machine Learning*, pp. 1887–1898. PMLR, 2020.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

Patrik Joslin Kenfack, Daniil Dmitrievich Arapov, Rasheed Hussain, SM Ahsan Kazmi, and Adil Khan. On the fairness of generative adversarial networks (gans). In *2021 International Conference" Nonlinearity, Information and Robotics"(NIR)*, pp. 1–7. IEEE, 2021.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Mehdi Mirza and Simon Osindero. Conditional generative adversarial nets. *arXiv preprint arXiv:1411.1784*, 2014.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. 2011.

Shuhan Tan, Yujun Shen, and Bolei Zhou. Improving the fairness of deep generative models without retraining. *arXiv preprint arXiv:2012.04842*, 2020.

Depeng Xu, Shuhan Yuan, Lu Zhang, and Xintao Wu. Fairgan: Fairness-aware generative adversarial networks. In *2018 IEEE International Conference on Big Data (Big Data)*, pp. 570–575. IEEE, 2018.

Depeng Xu, Shuhan Yuan, Lu Zhang, and Xintao Wu. Fairgan+: Achieving fair data generation and classification through generative adversarial nets. In *2019 IEEE International Conference on Big Data (Big Data)*, pp. 1401–1406. IEEE, 2019.

APPENDIX

Figure 3: Class-wise background color distribution of CGAN outputs trained on MNIST dataset. (a) Imbalanced digit color distributions for each class produced by CGAN. (b) Balanced digit color distributions for each class produced by RepFair-GAN.

Algorithm 1 Training of the discriminator in RepFair-GAN (outline)

Require: t the batch size, M training epochs, C maximum gradient norm, and $\mathcal{L}_D(\Theta)$ the discriminator's loss function with network parameter Θ.

  for $n \leftarrow 1, M$ **do**

    $U \leftarrow True$ ▷ Boolean indicating whether to update with samples from group 0 or group 1

    for each batch of size t **do**

      if U **then**

        $X_t \leftarrow \{D|S = 0\}$ ▷ random mini-batch of real samples from group 0

      else

        $X_t \leftarrow \{D|S = 1\}$ ▷ random mini-batch of real samples from group 1

      end if

      $g_t \leftarrow \nabla_\Theta \mathcal{L}_D(\Theta; X_t)$ ▷ Compute the gradient using the discriminator's loss

      $\bar{g}_t \leftarrow \text{clip}(g_t, C)$ ▷ Clip the gradient norm with max norm C

      $\Theta \leftarrow \Theta - \alpha \bar{g}_t$ ▷ Update network param.

      $U \leftarrow \text{not } U$

      Generate samples from the generator $\bar{X}_t$ feed to the discriminator and take a gradient step.

    end for

  end for

Figure 4: Example of two groups created from MNIST (left) and SVHN (right) datasets. In MNIST, one group of digits has a black background (two first rows) and another group has a white background (two last rows). In SVHN, one with normal images (first two rows), and for the second group we added a black overlay (shaded)

Figure 5: Group distributions for vanilla GAN (a) and our method (b) on SVHN dataset trained with balanced group representation. Our method provides uniform generation compared to the vanilla GAN.

Figure 6: Group distributions with different maximum gradient norms in RepFair-GAN on MNIST data. For max norm less than 2 the training does not converge due to the vanishing gradient. For max gradient norms between 2 and 10 groups are sampled uniformly and the sampling becomes biased for values bigger than 20.

Figure 7: Qualitative results on MNIST dataset. Examples of digits generated by CGAN (left) and RepFair-GAN (right). We observe that for each type of digit, group are equally represented with our method while preserving the same quality as the classic GAN