Giga-scale Kernel Matrix-Vector Multiplication on GPU

Abstract

Kernel matrix-vector multiplication (KMVM) is a foundational operation in machine learning and scientific computing. However, as KMVM tends to scale quadratically in both memory and time, applications are often limited by these computational constraints. In this paper, we propose a novel approximation procedure coined *Faster-Fast and Free Memory Method* (F^3M) to address these scaling issues of KMVM for tall ($10^8 \sim 10^9$) and skinny ($D \le 7$) data. Extensive experiments demonstrate that F^3M has empirical *linear time and memory* complexity with a relative error of order 10^{-3} and can compute a full KMVM for a billion points *in under a minute* on a high-end GPU, leading to a significant speed-up in comparison to existing CPU methods. We demonstrate the utility of our procedure by applying it as a drop-in for the state-of-the-art GPU-based linear solver FALKON, *improving speed 1.5-5.5 times* at the cost of $< 1\%$ drop in accuracy. We further demonstrate competitive results on *Gaussian Process regression* coupled with significant speedups on a variety of real-world datasets.

1 Introduction

Kernel matrix-vector multiplication (KMVM) is one of the most important operations needed in scientific computing with core applications in diffeomorphic registration, geometric learning [11], [31], numerical analysis [28], fluid dynamics [6], and machine learning [27]. For a dataset of size n, KMVM using direct computation has complexity and memory footprint $\mathcal{O}(n^2)$, both unfeasible for modern large scale applications where $n \approx 10^9$ is becoming increasingly common. Pioneering contributions presented in the *Fast Multipole Method* (FMM) [10] amend the complexity of these problems to $\mathcal{O}(n \log(\epsilon^{-1}))$, where ϵ is the chosen error tolerance, with varying reductions in memory footprint for data restricted to dimension 2. Subsequent developments in [8, 17] mainly focused on extending approximations for a broader set of kernels for a fixed dimensionality $D \le 3$, tailored for problems in physics with narrow data such as electrostatics, stellar dynamics, Stokes flow, and acoustic problems, amongst others.

In this paper, we introduce *Faster-Fast and Free Memory Method* (F^3M), a novel algorithm built upon the FFM [3] framework to perform KMVM on a GPU for *tall and skinny* ($D \le 7$) data of order $n \sim 10^9$ in under a minute with user-specified error tolerance, providing between $2 - 8500$ times speed-up over existing methods.

Notations. We use capital and lower case bold letters to represent matrices and vectors, respectively. In this paper, we will work with matrices $\mathbf{X} \in \mathbb{R}^{n_x \times D}$, $\mathbf{Y} \in \mathbb{R}^{n_y \times D}$ and vector $\mathbf{b} \in \mathbb{R}^{n_y}$. For a kernel k, the goal for KMVM is to compute $\mathbf{v} := \mathbf{K} \cdot \mathbf{b}$, where $\mathbf{K} := k(\mathbf{X}, \mathbf{Y}) = \{k(\mathbf{x}_i, \mathbf{y}_j)\}_{i=1, j=1}^{n_x, n_y}$, and $\mathbf{x}_i, \mathbf{y}_j$ denote the i^{th}, j^{th} row of $\mathbf{X}, \mathbf{Y}$ respectively.

Figure 1: A brief summary of the evolution of the FMM family. Our contributions in *.

2 Motivation and Related Work

Kernel methods are often limited by their $\mathcal{O}(n^2)$ memory footprint and computational complexity for KMVM. These constraints make scaling beyond $n = 10^6$ challenging. Many recent developments have been made to improve both of these constraints, ranging from hardware acceleration using GPUs in KeOps [11], to various approximation techniques proposed in [36, 33, 34, 3, 9]. In this work, we focus our attention on kernel independent KMVM methods.

KeOps. Charlier et al. [11] proposes a map-reduce scheme to compute kernels using exactly $\mathcal{O}(n)$ memory and $\mathcal{O}(n^2)$ complexity on GPU. This is achieved by computing the full KMVM product on-the-fly by summing $v_i = \sum_{j=1}^{n} k(\mathbf{x}_i, \mathbf{y}_j)b_j$ directly, without ever storing the kernel matrix $\mathbf{K} \in \mathbb{R}^{n \times n}$ explicitly. Extensive experiments show that this method is practical when $n \leq 10^6$, as the GPU hardware acceleration allows the KMVM product to be computed in less than a second on a conventional GPU. Moreover, the method places no constraint on the number of features D it can be applied to, making it favourable for KMVM on medium size datasets. In application contexts, KeOps is currently adopted into conjugate gradient solver FALKON [24, 26] as part of the default pipeline.

The Fast and Free Memory Method (FFM).
While KeOps can theoretically scale to a billion points, it becomes practically infeasible as the $\mathcal{O}(n^2)$ complexity would imply a computational time of 10^6 seconds, or roughly 11 days. To overcome this billion points barrier, Aussal et al. [3] deploys a geometric space partitioning scheme, and proposed the *Fast and Free Memory Method* (FFM), a KMVM approach that

Table 1: Comparison between methods(* indicate ours).

Method	FMM	KeOps	FFM	F$^{2.5}$M*	F^{3}M*
Kernel Independent		✓	✓	✓	✓
Linear Time	✓		✓	✓	✓
Linear Memory		✓	✓	✓	✓
Restriction in D	≤ 3		≤ 3	≤ 7	≤ 7
GPU	✓	✓		✓	✓
Scales to $n = 10^9$ under 1 hour				✓	✓
under 1 minute!					✓

extends the FMM [10] family of algorithms. In contrast to traditional FMM methods, which require specific series expansion of the kernel, FFM deploys Lagrange interpolations to approximate them instead. This allows FFM to be applied to almost any conventional kernel and further enables the user to trade off accuracy with computational efficiencies by controlling the order of the approximating polynomial [19]. Compared to KeOps, FFM demonstrates both linear memory and time complexity in experiments and scales to compute a billion-points KMVM on a smaller CPU cluster under 4 hours, outscaling the GPU implementation of FMM [21]. While 4 hours is a significant improvement compared to 11 days from KeOPS, it still renders many machine learning techniques infeasible. Further, as recursive partitioning of the data space scales poorly with D [5], both FMM and FFM can only be applied to $D \leq 3$ data, a price to pay for the speed-up of KMVM operations when $n = 10^9$. Furthermore, we show in our experiments that a direct FFM port to GPU gives unstable results for $n = 10^9, D = 3$ for non-trivial data simulations (bottom row in Appendix 9).

Our contribution. To surpass the billion point barrier while maintaining high-speed and stable computation, we propose F$^{2.5}$M and our main algorithm F^{3}M, the first pair of KMVM algorithms that can reliably scale to $n = 10^9$ on skinny data using a single GPU. We build F$^{2.5}$M on top of FFM by introducing non-trivial GPU parallelisation and low-level optimisations. We further stabilize and improve the original geometric partitioning scheme in FFM to significantly reduce memory constraints, leading to a relaxation of dimensionality constraints from 3 to 7. At last, we introduce an adaptive far-field and smooth field approximation scheme for kernel interpolation, resulting in our main algorithm F^{3}M, which runs $2.0 - 33.3$ times quicker and more stable than a direct port of FFM on GPU. See Fig. 1 and Table 1 for an overview and comparisons of the methods. We summarise our contribution as follows:

1. We propose *Faster-Fast and Free Memory Method* (F^{3}M), a KMVM algorithm building on top of FFM by applying multiple low-level enhancements, GPU parallelisation, and algorithmic computational and memory enhancements, allowing for KMVM operations on $n \leq 10^9$ data in under a minute. Codebase is released here [14].

84 **2.** We characterize theoretical time and memory complexity of F^{3}M.

85 **3.** We run extensive KMVM experiments of F^{3}M on a variety of tall and skinny data with $n \leq 10^9$,
86 demonstrating empirical linear time and memory scaling, and achieving speedups between 2–8500
87 times when compared to FFM (GPU and CPU) and KeOps.

88 **4.** We run a practical application of F^{3}M as a drop-in replacement for KeOps in conjugate gradient
89 solver FALKON [24, 26] for kernel ridge regression and classification (KRR) on giga-scale data,
90 obtaining a solution 3.4 times faster with <1% drop in accuracy. We further demonstrate competitive
91 results on Gaussian process regression against KISS-GP [35], SVGP [18] and SVGR [30] with
92 significant speed-ups.

3 Background

94 The FFM method considers KMVM for a kernel k evaluated on two data matrices $\mathbf{X}, \mathbf{Y}$ and
95 $\mathbf{b}$ are weights associated with $\mathbf{Y}$. The KMVM is expressed as $\mathbf{v} := k(\mathbf{X}, \mathbf{Y}) \cdot \mathbf{b} = \mathbf{K} \cdot \mathbf{b}$.
96 For example, $\mathbf{b}$ could be the weights in a KRR or the strength of electronic charges. As n_x
97 and n_y are taken to be very large, a full computation is unfeasible. In this section, we il-
98 lustrate and detail the main steps of FFM, before presenting our improvements in Section 4.
99 For illustration purposes, we first consider a simple 2D
100 KMVM. Our goal is to calculate $k(\mathbf{X}, \mathbf{Y}) \cdot \mathbf{b}$ for $\mathbf{X}, \mathbf{Y}$ in
101 Figure 2. The intuition behind FFM is to reduce the com-
102 plexity of calculating the full KMVM by partitioning $\mathbf{X}$
103 and $\mathbf{Y}$ such that certain calculations can be approximated
104 in a fast manner, based on the pairwise distances between
105 partitions.

Enclosing and partitioning the data. The first step is
to partition the data. To begin, we find a large enough box
that can just enclose $\mathbf{X}$ or $\mathbf{Y}$. The edge length of this box
is calculated as

Figure 2: Enclosing $\mathbf{X}$ and $\mathbf{Y}$ within a box,
"x" marks the center of the box. Numbers un-
der the the boxes denotes edge length. In the
right plot, we have enclosed the blue points
with the largest box.

$$\mathcal{E} := \max\left(\max_d(x_{\max}^{(d)} - x_{\min}^{(d)}), \max_d(y_{\max}^{(d)} - y_{\min}^{(d)})\right)$$

106 where $x_{\max}^{(d)}, x_{\min}^{(d)}$ denotes the largest value and the smallest value along the d-dimension in $\mathbf{X}$ and
107 similarly for $\mathbf{Y}$. Figure 2 illustrates this enclosing procedure.

108 **Defining near and far-field** In FMM, an octree [23] is applied to recursively partition data into

109 smaller boxes $B_p^X \subset \mathbf{X}, B_q^Y \subset \mathbf{Y}$, with p, q de-
110 noting box indices. Here each box corresponds
111 to a subset of rows in the data matrix. Let us
112 also denote $\mathbf{b}_q$ as the partition of b_j's grouped
113 with the same indices as B_q^Y. To calculate the
114 KMVM between two boxes B_p^X, B_q^Y with the
115 grouped vector $\mathbf{b}_q$, for each $\mathbf{x}_i \in B_q^X$, we com-
116 pute

$$v_i^{p,q} = \sum_{\mathbf{y}_j \in B_q^Y, b_j \in \mathbf{b}_q} k(\mathbf{x}_i, \mathbf{y}_j) b_j \qquad (1)$$

Figure 3: Recursive partitioning of $\mathbf{X}$ and $\mathbf{Y}$ for 2D
data. Far-field interactions are colored green while near-
field interactions are colored orange and δ denotes the
euclidean distance between the centers.

117 with $\mathbf{v}^{p,q} = [v_1^{p,q} \dots v_{n_x}^{p,q}]$. Now the target $\mathbf{v}$ can be computed as $\mathbf{v} = \sigma([\mathbf{v}^{p=1}, \dots, \mathbf{v}^{p=P}]^\top)$, where
118 $\mathbf{v}^p = \sum_{q=1}^Q \mathbf{v}^{p,q}$, P, Q denote the total number of boxes and $\sigma(\cdot)$ a permutation such that v_i^p appear
119 in the same order as $\mathbf{x}_i$ appears in $\mathbf{X}$. Figure 3 shows how boxes are recursively partitioned.

120 **Far and near-field interactions** FFM relies on a divide-and-conquer strategy to effectively com-
121 pute a KMVM product; data is partitioned into boxes and then separated into far-field and near-field
122 interactions, where near-field interactions are computed exactly and far-field interactions are approxi-
123 mated using Lagrange interpolation for speed, explained in the paragraph below. The partitioning
124 procedure in FFM is recursive, where the recursion depth `tree_depth` controls the size of the edge
125 $l = \frac{\mathcal{E}}{2^{\texttt{tree\_depth}}}$ of the box. An interaction is defined to be in the far-field if the distance between the two
126 center points of the boxes exceeds $2l$, i.e. $\texttt{IsFarField} := \|\mathbf{x}_{\text{center}} - \mathbf{y}_{\text{center}}\| \geq 2l$. While l for each

127 box will decrease with the number of divisions, this rule ensures a fixed minimal distance for a given
128 depth for far-field interactions. Figure 3 illustrates how far(green) and near(orange)-field interactions
129 arise between $\mathbf{X}$ and $\mathbf{Y}$ when `tree_depth` increases.

130 **Lagrange interpolation**   We review Lagrange interpolation used for far-field approximations in
131 FFM. Given a function $f(x) : [-1, 1] \to \mathbb{R}$ and $r+1$ unique points $s_i \in [-1, 1], \quad i = 0, \dots, r$, there
132 exists a unique polynomial $p_r(x)$ of degree $\leq r$ that interpolates f at $p_r(s_i) = f(s_i)$. The Lagrange
133 polynomial is given by $p_r(t) = \sum_{i=0}^{r} f(s_i)\mathcal{L}_i(t)$, where $\mathcal{L}_i(t) = \frac{\prod_{j=0, j\neq i}^{r}(t-s_j)}{\prod_{j=0, j\neq i}^{r}(s_i-s_j)}, \quad i = 0, \dots, r$.
134 We are free to chose the degree r as well as the points s_i to interpolate through. The choice of s_i is
135 especially important in minimizing large oscillations around the edges of the interpolation interval
136 (Runge's phenomenon [12]). For this reason, Chebyshev nodes of the second kind are used [7]
137 $s_i = \cos \theta_i$, where $\theta_i = \frac{i\pi}{r}, \quad i = 0, \dots, r$.

138 **Interpolating** $k(\mathbf{x}, \mathbf{y})$ By noticing that $k(\mathbf{x}, \mathbf{y})$ is a bivariate function, we can apply Lagrange
139 interpolation twice, thus interpolating $k(\mathbf{x}, \mathbf{y})$ as $k(\mathbf{x}, \mathbf{y}) \approx \sum_{i=1}^{r_X} \mathcal{L}_i(\mathbf{x}) \sum_{j=1}^{r_Y} k\left(\mathbf{s}_i^x, \mathbf{s}_j^y\right) \mathcal{L}_j(\mathbf{y})$.
140 Here r_X, r_Y denotes the number of the interpolation nodes and $\mathbf{s}_i^x, \mathbf{s}_j^y \in \mathbb{R}^D$ denotes the
141 grid of interpolation nodes for B_p^X and B_q^Y. Note that since $\mathbf{x} \in \mathbb{R}^D$, we take $\mathcal{L}_i(\mathbf{x}) :=$
142 $\prod_{d=1}^{D} \frac{\prod_{j=0, j\neq i}^{r}\left(x^{(d)}-s_j^{(d)}\right)}{\prod_{j=0, j\neq i}^{r}\left(s_i^{(d)}-s_j^{(d)}\right)}, \quad i = 0, \dots, r$. These operations can be vectorized and computed se-

143 quentially on-the-fly with linear memory footprint $\mathbf{v} \approx \mathbf{L}_X^T \cdot \overbrace{(\mathbf{K} \cdot \underbrace{(\mathbf{L}_Y \cdot \mathbf{b})}_{\mathbf{u}_1})}^{\mathbf{u}_2}$, which is done by first

144 computing $\mathbf{v}_1$, then $\mathbf{v}_2$ and lastly $\mathbf{v}$. A far-field KMVM between two boxes $\mathbf{v} = k(B_p^X, B_q^Y) \cdot \mathbf{b}_q$ is
then approximated by using double Lagrange interpolation according to Figure 4.

Figure 4: Here we approximate a far-field interaction between two boxes. In **1.** we first normalize the data
between $[-1, 1]$ and conduct 2D interpolation of $k(\cdot, \mathbf{y})$ while summing over $\mathbf{b}$. In **2.**, the interpolation for
$k(\mathbf{x}, \cdot)$ will also be normalized and hence we need to translate the distance between the boxes by calculating
145 $\mathbf{K} \cdot \mathbf{v}_1$. Lastly in **3.** we interpolate $k(\mathbf{x}, \cdot)$ while we sum $\mathbf{v}_2$.

146 4 Faster-FFM ($\mathbf{F}^{2.5}\mathbf{M}$ and $\mathbf{F}^3\mathbf{M}$)

147 To fully leverage the port of FFM to GPU, we enhance FFM with novel approximation procedures for
148 improved complexity and memory optimizations to scale to $n = 10^9$. We coin this improved version
149 Faster-FFM ($\mathrm{F}^3\mathrm{M}$). The capabilities of $\mathrm{F}^3\mathrm{M}$ against previous methods are summarized in Table 1.

150 4.1 CPU to GPU optimizations

151 In FFM, every computation is serial and on CPU. When moving to GPU, we have parallelized
152 all major computations. These parallelizations are non-trivial and require low-level algorithmic
153 optimizations, with challenges such as:
154 **Box-to-threadblock alignment** – A major challenge in the implementation of both the parallel
155 far-field and near-field computations was correctly aligning thread blocks to boxes. This aligning
156 requirement imposed non-trivial boundary conditions on data indexing when using shared memory.
157 We present how the parallelization is done for calculating near-field interactions in Appendix I.
158 **No native sorting methods** – We found that LibTorch [25] sorting methods often led to out-of-
159 memory (OOM) due to allocation of large long-type vectors on GPU. When $n = 10^9$, this implies
160 allocating 8GB of memory, 25% of the 32GB card used, making it a necessity to avoid native sorting

methods.

Ensuring interactions are sorted – To avoid any unnecessary sorting, we ensure that the matrix containing interactions is always sorted. To do this without using sorting algorithms, we had to design a non-trivial algorithm that would recursively retain order during division. We refer to the `get_new_interactions` function in `n_tree.cu` for exact implementation.

In-place grouping data on boxes – Due to infeasible LibTorch sorting methods, we additionally had to design an algorithm that found a permutation that would group $\mathbf{X}$ into its corresponding boxes in linear time and memory. We used a non-trivial count and increment-based strategy. We refer to the `box_division_cum_hash` and `box_division_assign_hash` function in `n_tree.cu` for exact details.

Figure 5: KMVM times on several datasets between ■ FFM(GPU) vs ■ F³M. U&N was only run up to $n = 5 \cdot 10^8$

However, we found that these optimizations and porting alone were not enough to scale to $n = 10^9$ on 3D datasets, as Figure 5 demonstrates. FFM doesn't remove empty boxes or handle boxes with few points in them and keeps exponentially creating new empty boxes and interactions, thus leading to out-of-memory (OOM) errors on non-uniform data (see Appendix 9).

4.2 Scaling to $n = 10^9$ on GPU ($\mathbf{F}^{2.5}\mathbf{M}$)

In this section, we detail the memory enhancements that allow F³M to consistently scale to $n = 10^9$.

Removing empty boxes with hash list indexing To ensure linear memory on GPU, we only keep a reindexing vector σ of size n_x(resp. n_y) in memory during the computation of the algorithm in addition to a list of interactions and box centers. This reindexing vector rearranges the data points so they appear in the order of the box they belong to. We optimize both the computation and the memory footprint of these objects by avoiding recursive formulas and hash lists.

Naively, points can be assigned to boxes by direct comparison to all existing box centers. As the number of centers grow exponentially with depth `tree_depth`, this method quickly becomes pathological. To amend this, we propose a linear complexity formula to retrieve the box index β_i a

point $\mathbf{x} \in \mathbf{X} \subset \mathbb{R}^D$ belongs to $\beta_i = \underbrace{\sum_{d=1}^{D} 2^{\texttt{tree\_depth} \cdot (d-1)}}_{\text{Summing over } D \text{ dimensions}} \cdot \underbrace{\lfloor 2^{\texttt{tree\_depth}} \frac{x_d - \alpha_d}{\mathcal{E}} \rfloor}_{\substack{\in \{0,1\}, \text{ Denotes left or right} \\ \text{of center of box edge}}}$, where α_d denotes

the minimum value of $\mathbf{X}$ in dimension D and x_d is the value of $\mathbf{x}$ in dimension D. To prevent the number of boxes from growing exponentially, we remove empty boxes with each division. To assign points to the corresponding boxes, we use a hash list to store β_i and the order i. We can then group points $\{\mathbf{x}_i\}_{i=1}$ to their respective ordering i using the hash list in $\mathcal{O}(n)$ time in contrast to $\mathcal{O}(n \cdot 2^{D \cdot \texttt{tree\_depth}})$ by direct computation.

Handling boxes with few points with *small field* In cases when the number of points in each box can vary greatly, we separately consider the interactions where the number of points in boxes is small. Hence, we say that there is a *small field* interaction between boxes B_p^X, B_q^X if both have a small number of points, i.e. if

$|B_p^X| + |B_q^X| \leq \rho$, for some threshold number ρ. To minimize the computations needed, ρ can be set to $\rho = r_X + r_Y$. This intuitively allows F³M to directly compute interactions that are too small to benefit from interpolation savings (i.e. $|B_p^X| + |B_q^X| \leq r_X + r_Y$), thus limiting memory usage by stopping partitions from dividing further than necessary. In higher dimensions where the division rate is faster, ρ can be set to a higher value to limit memory usage at the expense of more direct computations which are slower.

Figure 6: Full grid vs sparse grid.

Sparse grids As the number of Lagrange polynomials increases exponentially with dimension, we implement Sparse grids [29] to allow for a finer selection of interpolation nodes. With sparse grids,

211 the number of nodes needed grows slower [20], thus saving memory. We give an example of a sparse
212 grid versus a full grid in 2D in Figure 6.

4.3 Speeding up $\mathbf{F}^{2.5}\mathbf{M}$ $\left(\mathbf{F}^{2.5}\mathbf{M} \rightarrow \mathbf{F}^3\mathbf{M}\right)$

214 **Smoothness criteria** FFM speeds up its computations with minimal loss in accuracy by selectively
215 interpolating interactions that are far apart. To improve speed, we introduce the *smoothness criterion*
216 to widen the selection of interactions that can be interpolated with minimal loss in accuracy. For a
217 Gaussian Kernel $k(\mathbf{x}, \mathbf{y}) = \exp\left(\frac{\|\mathbf{x}-\mathbf{y}\|^2}{2\gamma^2}\right)$, with lengthscale γ, the smoothness criteria is defined
218 as `is_smooth` $:= \frac{\frac{1}{N_{B_p^X}}\sum_{\mathbf{x}_i \in B_p^X}\sum_{d=1}^{D}\|x_i^{(d)}-\bar{x}^{(d)}\|^2}{2\gamma^2} + \frac{\frac{1}{N_{B_q^Y}}\sum_{\mathbf{y}_j \in B_q^Y}\sum_{d=1}^{D}\|y_j^{(d)}-\bar{y}^{(d)}\|^2}{2\gamma^2} \leq \eta$ between
219 an adjacent interaction of boxes B_p^X, B_q^Y. The quantity computed can be understood as "Effective
220 Variance" (EV), as it considers total variation in the exponent of the Gaussian kernel. We justify the
221 *smoothness criteria* with the following proposition.

222 **Proposition 1.** *Consider* $\mathbf{x}, \mathbf{y} \in \mathcal{X} \subset \mathbb{R}^d$ *such that* $d(\mathbf{x}, \mathbf{y}) := \frac{\|\mathbf{x}-\mathbf{y}\|^2}{2\gamma^2} = \frac{1}{2\gamma^2}\sum_i^d(x^{(i)}-y^{(i)})^2 \leq$
223 $\eta < 1$ *for all* $\mathbf{x}, \mathbf{y}$. *When interpolating* $k(\mathbf{x}, \mathbf{y}) = \exp(-d(\mathbf{x}, \mathbf{y}))$ *using bivariate Lagrange interpo-*
224 *lation* $\mathcal{L}_r(\mathbf{x}, \mathbf{y}) := \mathbf{L}_X^T \cdot \mathbf{K} \cdot (\mathbf{L}_Y \cdot \mathbf{b})$ *with degree* $r = 2p$, *for any* $p \in \mathbb{N}_{>0}$ *there exist nodes* $\mathbf{s}^{\mathbf{x}}, \mathbf{s}^{\mathbf{y}}$
225 *for* $\mathcal{L}_r(\mathbf{x}, \mathbf{y})$ *such that the pointwise interpolation error is bounded by* $\mathcal{O}(\eta^{p+1})$.

226 See Appendix D for proof. Hence for small $\eta < 1$, we see that the error becomes small
227 for well specified $\mathcal{L}_r(\mathbf{x}, \mathbf{y})$. To avoid calculating the sample variance during computations
228 which costs $\mathcal{O}(n)$, we exploit that data is partitioned into hypercubes with a *known* edge $\mathcal{E}$
229 and take the upper bound of the variance in each cube as $\frac{\mathcal{E}^2}{4}$ along a dimension. A proof
230 for this bound is provided in Appendix B. Adjacent interactions are then classified as smooth
231 when $\sum_d^D \frac{\mathcal{E}^2}{4 \cdot 2\gamma}(\text{EV of } B_p^X) + \frac{\mathcal{E}^2}{4 \cdot 2\gamma}(\text{EV of } B_q^Y) = \frac{D\mathcal{E}^2}{\gamma^2 \cdot 4} \leq \eta$ which only costs $\mathcal{O}(1)$ to compute.

232 **Adaptive far-field approximation**
233 To further improve speed we intro-
234 duce an adaptive rule to select the
235 number of interpolation nodes used
236 when calculating far-field interactions.
237 Error bounds for multidimensional La-
238 grange interpolation have been pro-
239 posed in [22], however, these bounds
240 cannot be directly used to create an
241 adaptive interpolation rule. We thus
242 simulate KMVM errors for $k(\mathbf{X}, \mathbf{Y}) \cdot$
243 $\mathbf{b}$ where $\mathbf{X}, \mathbf{Y}$ are uniformly dis-
244 tributed and $\mathbf{b}$ is normally distributed.
245 We fix a distance between $\mathbf{X}$ and $\mathbf{Y}$
246 and vary the squared of this distance
247 between boxes against nodes in Fig-
248 ure 7. We use a Gaussian Kernel with $\gamma = \frac{1}{\sqrt{2}}$.

(a) Dimension $d = 3$ (b) Dimension $d = 5$

Figure 7: Plotting relative and absolute error against squared
distance between boxes. "0" nodes mean we use the zero vector as
an approximation to the KMVM for a gaussian kernel. We observe
that its not beneficial to interpolate at all when the square distance
exceeds 5 and that is is sufficient to only use 3^D nodes when square
distance is ≤ 0.01.

249 Based on Figure 7, we use the following rule for selecting the number of interpolation nodes for
250 far-field interactions

$$r_{\text{far}}(r) = \begin{cases} \min(r, 3^D) & \text{if } \left(\frac{\mathcal{E}}{2^{c_{\text{depth}}}}\right)^2 \cdot \frac{1}{2\gamma^2} \leq 0.01 \\ r & \text{if } 0.01 < \left(\frac{\mathcal{E}}{2^{c_{\text{depth}}}}\right)^2 \cdot \frac{1}{2\gamma^2} \leq 5 \\ 0 & \text{if } 5 < \left(\frac{\mathcal{E}}{2^{c_{\text{depth}}}}\right)^2 \cdot \frac{1}{2\gamma^2} \end{cases}$$

251 where r is the number of nodes chosen to interpolate with in the general case.

252 **Barycentric lagrange interpolation** We slightly improve the complexity further by implementing
253 barycentric Lagrange interpolation [7] evaluated at the chebyshev nodes of the second kind. As this
254 is a well-known technique, we refer to the appendix for more details.

4.4 Complexity

256 The time complexity of FFM is $\mathcal{O}(n \log(n))$ [3] and we use a similar derivation strategy for $\mathbf{F}^3\mathbf{M}$ to
257 obtain a complexity that is dependent on the effective variance limit η (chosen parameter) and the
258 box width $\mathcal{E}$ (data). We first present two propositions needed to derive the complexity of $\mathbf{F}^3\mathbf{M}$.

Proposition 2. *A far-field interaction between two boxes containing n_x and n_y points respectively has time complexity $\mathcal{O}(n)$, where $n = \max(n_x, n_y)$.*

Proposition 3. *Given n data points in dimension D, the maximum number of divisions $Tree_{max \; divisions}$ is given by*

$$Tree_{max \; divisions} = \log_{2^D}(n). \tag{2}$$

With the above results, the complexity of FFM is taken as the maximum number of divisions multiplied by the complexity of far-field interactions at each division which yields $\mathcal{O}(n \log(n))$. We remark that near-field interactions between boxes containing only 1 data point have linear time complexity, hence the results hold.

Theorem 1. *Given a KMVM with edge $\mathcal{E}$ (dependent on data $\mathcal{X}, \mathcal{Y}$), lengthscale γ, effective variance limit η, n data points and data dimension D, F^3M has time complexity $\mathcal{O}(n \cdot \log_2\left(\frac{D \cdot \mathcal{E}^2}{\gamma^2 \cdot 4 \cdot \eta}\right))$, which can be taken as $\mathcal{O}(n \cdot \log_2\left(\frac{C}{\eta}\right))$ where $C \propto \frac{D \cdot \mathcal{E}^2}{\gamma^2}$.*

Memory footprint As our implementation uses the same partitioning strategy as FFM, the *theoretical* memory complexity remains $\mathcal{O}(n)$ for F^3M (see [3] for proof). However, this does not accurately reflect the memory footprint of the actual implementations, whose memory mostly depends on the number of interactions stored. We summarize these memory footprints for FFM and F^3M in Theorem 2 below.

Theorem 2. *The number of interactions M_i against tree depth i of FFM and F^3M grows as $\mathcal{O}\left(M_{i-1} 2^{2 \cdot D} - m_i^{far}\right)$ and*

$$\mathcal{O}\left(M_{i-1} 2^{2 \cdot D} - (m_i^{empty})^2 - m_i^{far} - m_i^{smooth} - m_i^{small}\right)$$

respectively. Here $M_{-1} = \frac{1}{2^{2D}}$ and $m_0^{far} = m_0^{smooth} = m_0^{small} = m_0^{empty} = 0$ and $m_i^{far}, m_i^{smooth}, m_i^{small}, m_i^{empty}$ denotes the number of far-field, smooth field, small field interactions and the number of empty boxes respectively at depth $i > 0$.

We see that the additional approximations presented in F^3M also impacts memory footprint, as the additional $(m_i^{empty})^2, m_i^{smooth}, m_i^{small}$ terms removes a substantial amount of interactions at each i, significantly slowing down the growth of interactions, reducing memory growth. All proofs can be found in Appendix E.

5 Experiments

We demonstrate the utility of F^3M over a variety of experiments using the Gaussian kernel $k(\mathbf{x}, \mathbf{y}) = \exp -(\frac{\|\mathbf{x}-\mathbf{y}\|^2}{2\gamma^2})$.[1] We generate data such that the EV (see section 4.3) varies between $0.1, 1, 10$ for data of sizes $n = 10^6, 10^7, 10^8, 10^9$. The parameters used for F^3M are $\eta = 0.1, 0.2, 0.3, 0.5$ and $r = 2^D, 3^D, 4^D$ with a cap at $r = 2048$. The error for the approximated KMVM product $\hat{\mathbf{v}}$ is calculated as Relative error $:= \frac{\|\hat{\mathbf{v}}-\mathbf{v}\|^2}{\|\mathbf{v}\|^2}$, where the true KMVM product $\mathbf{v}$ is obtained by calculating the full KMVM on a subset $\mathbf{X}'$ consisting of the first 5000 points in $\mathbf{X}$ against the entire dataset in double precision, i.e. $\mathbf{v} = k(\mathbf{X}', \mathbf{X}) \cdot \mathbf{b}$, where we fix $\mathbf{b} \sim \mathcal{N}(0, I_n)$. All experiments were run on NVIDIA V100-32GB cards, where the data is fitted entirely on the GPU. These cards were chosen since the extra graphic memory is necessary to fit the data on one card when $n = 10^9$. It should be noted that $n = 10^9$ can only be run up to $D = 3$, as $\mathbf{X}$ and $\mathbf{b}$ itself cannot fit in memory for higher dimensions with the GPUs we had available. For details on how F^3M scales across multiple GPUs, see Appendix G.

KMVM experiments We consider a wide variation of generated datasets to simulate different real-world scenarios to test F^3M on. For the $k(\mathbf{X}, \mathbf{X})$-case we consider uniformly and normally distributed data ($D = 1, 2, 3, 4, 5, 6, 7$) together with data simulated from Brownian motion, fractional Brownian motion, and Clustered data ($D = 1, 2, 3$). For the $k(\mathbf{X}, \mathbf{Y})$-case we consider uniformly distributed $\mathbf{x}$ and normal distributed $\mathbf{y}$ ($D = 1, 2, 3, 4, 5, 6, 7$). See Appendix 9 for visualizations of data. We have to consider smaller n for the $k(\mathbf{X}, \mathbf{Y})$-case when $D \geq 3$, as twice the amount of data needs to be stored. For $D = 3/(4, 5)/(6, 7)$ we instead consider at most $n = 5 \cdot 10^8/2.5 \cdot 10^8/10^8$. It should

---

[1]F^3M is kernel agnostic, however we choose the Gaussian kernel for simplicity.

Table 2: F^{3}M (GPU) compared to results reported in [3] for FFM(CPU). F^{3}M achieves a $90\times$ speed up on a billion data points. F^{3}M used parameters $r = 64$ and $\eta = 0.5$

	FFM (12 CPU cores)			F^{3}M (GPU, Ours)			
n	Time (s)	Error	Memory	Time (s)	Error	Memory	**Speedup**
10^6	33.4	$1.35 \cdot 10^{-4}$	100 MB	0.08 ± 0.00	$3 \cdot 10^{-4} \pm 7 \cdot 10^{-5}$	~ 28 MB	$417\times$
10^7	169	$1.98 \cdot 10^{-4}$	1GB	1.16 ± 0.04	$3 \cdot 10^{-4} \pm 1.2 \cdot 10^{-4}$	~ 280 MB	$145\times$
10^8	1499	$1.81 \cdot 10^{-4}$	10 GB	12.45 ± 0.06	$2 \cdot 10^{-4} \pm 5 \cdot 10^{-5}$	~ 2.8 GB	$120\times$
10^9	11340	$3.11 \cdot 10^{-4}$	100 GB	125.90 ± 0.52	$3 \cdot 10^{-4} \pm 1.3 \cdot 10^{-5}$	~ 28 GB	$90\times$

Table 3: Run time and relative error of all KMVM experiments for F^{3}M. The slope is computed by regressing $\log_{10}$(Time (s)) against $\log_{10}(n)$. A slope of 1 implies $\mathcal{O}(n)$ scaling.

	Time(s)							Relative Error						
n/D	1	2	3	4	5	6	7	1	2	3	4	5	6	7
10^6	0.2 ±0.1	0.2 ±0.2	0.2 ±0.1	0.4 ±0.2	0.9 ±0.9	3.0 ±2.4	3.1 ±2.1	0.0018 ±0.0021	0.0023 ±0.0028	0.0005 ±0.0009	0.0014 ±0.0013	0.0022 ±0.0282	0.0303 ±0.0314	0.0294 ±0.0282
10^7	0.7 ±0.3	1.1 ±0.4	1.7 ±0.7	4.0 ±2.4	12.7 ±10.0	79.9 ±88.6	88.2 ±90.2	0.0016 ±0.0021	0.0019 ±0.0023	0.0006 ±0.0013	0.0017 ±0.0019	0.0057 ±0.0032	0.0325 ±0.0261	0.0273 ±0.0179
10^8	3.5 ±1.1	7.4 ±2.1	17.1 ±7.3	40.6 ±28.7	76.0 ±83.2	525.1 ±410.9	512.9 ±471.4	0.002 ±0.0026	0.0025 ±0.0032	0.0007 ±0.0013	0.0023 ±0.0021	0.0051 ±0.0032	0.0376 ±0.0239	0.0444 ±0.017
$2.5 \cdot 10^8$	N/A	N/A	N/A	76.7 ±25.9	340.7 ±247.6	OOM	OOM	N/A	N/A	N/A	0.0034 ±0.0029	0.0076 ±0.0012	N/A	N/A
$5 \cdot 10^8$	N/A	N/A	74.9 ±28.5	289.4 ±222.8	631.5 ±997.0	OOM	OOM	N/A	N/A	0.0012 ±0.0013	0.0023 ±0.0026	0.0041 ±0.003	N/A	N/A
10^9	29.4 ±8.9	73.8 ±23.4	174.0 ±76.6	OOM	OOM	OOM	OOM	0.0024 ±0.0024	0.0025 ±0.0027	0.0009 ±0.0018	N/A	N/A	N/A	N/A
Slope	**0.78**	**0.85**	**0.99**	**0.98**	**0.99**	**1.06**	**1.02**							
$\mathcal{O}(n \log(n))$				1.11										

302 be noted that $D = 7$ is a hard limit for geometric partitioning-based methods, since for $D = 8$, we
303 would have $2^{8\cdot 2} \cdot 2^{8\cdot 2} \approx 4.3 \cdot 10^9$ interactions after only 2 divisions. This number of interactions
304 cannot even be represented by a 32-bit integer. We summarize the runs in Table 3 and plot the error
305 and time complexity in Figure 8 for each dataset when $D = 3$. We find that F^{3}M maintains sub-linear
306 empirical complexity up to $D = 6$, where we have to set *small field* limit ρ to a larger number to
307 not run out of memory. Further, the error increases in the higher dimensions since we use fewer
308 nodes per dimension when interpolating, owing to the *sparse grid* technique. We note that $D = 7$ has
309 faster run times than $D = 6$ which is explained by that for some values of EV, $D = 7$ doesn't run
310 with acceptable errors which skew the run time to datasets where a larger portion of the data can be
311 interpolated.

Figure 8: Time complexity and relative error for each 3D dataset.

312 We further replicate the data used in the first experiment in [3] and compare F^{3}M against FFM (CPU)
313 in Table 2.

Kernel Ridge Regression experiment We apply F^{3}M to FALKON [24], where we replace their
315 KMVM operation with F^{3}M and compare performance and speed in solving Kernel Ridge Regression
316 (KRR). The KMVM operation currently used for smaller dimensions is KeOps [11]. Given some data
317 $\mathbf{X} \in \mathbb{R}^{N \times d}$ we want to find the solution $\alpha = (k(\mathbf{X}, \mathbf{X}) + \lambda I)^{-1} \mathbf{b}$ where λ is the ridge parameter that
318 stabilizes the inverse. FALKON is a Nyström approximation based solver that requires a subsample
319 $\mathbf{X}' \in \mathbb{R}^{M \times d}$ of $\mathbf{X}$ to approximate the inverse computation. We focus the experiments on tall and
320 skinny data and take $n = 10^9, d \le 3$ with $M = 10^5$ for all experiments. We consider uniformly and
321 normally sampled data, the Open Street Map (OSM) dataset [1] and a classification task on the NYC
322 Taxi dataset [2], where we predict whether the customer will tip based on trip distance, trip time and
323 fare cost. To construct $\mathbf{b}$ on synthetic problems, we first take a subset $\mathcal{D} \in \mathbb{R}^{1000 \times d}$ of $\mathbf{X}$ and sample
324 $\alpha \sim \mathcal{N}(0, I_{1000 \times 1000})$. We then calculate $\mathbf{b} = k(\mathbf{X}, \mathcal{D}) \cdot \alpha + \varepsilon$, where $\varepsilon \sim \mathcal{N}(0, 0.1)$. We run KRR
325 for $EV = 0.1, 1, 10$ on synthetic data, and report the average R^2 (AUC for NYC Taxi) and training

Table 4: FALKON using default KMVM vs FALKON with F^{3}M.

Dataset	n	D	M	FALKON with default KMVM		FALKON with F^{3}M		Error diff	Speedup
				R^2	Time (s)	R^2	Time (s)		
Uniform	10^9	3	10^5	0.975 ± 0.034	7631 ± 2	0.976 ± 0.038	2234 ± 429	0%	5.31
Normal	10^9	3	10^5	0.893 ± 0.118	7631 ± 2	0.902 ± 0.114	2234 ± 429	1%	3.41
OSM	10^9	2	10^5	0.932 ± 0.056	6752 ± 13	0.943 ± 0.043	1670 ± 48	1.2%	4.04
NYC Taxi	10^9	3	10^5	0.526 ± 0.029 (AUC)	6963 ± 69	0.526 ± 0.030 (AUC)	4535 ± 7	0%	1.53

time in Table 4. For the real world datasets OSM and NYC Taxi, we fix the lengthscale using the median heuristic proposed in [16] averaged our results over the 3 runs.

Ablation study between FFM(GPU) and F^{3}M As much of the improved performance can be attributed to our GPU implementation, we conduct an ablation study of FFM(GPU) against F^{3}M and KeOps in Table 5. We first present KMVM run times averaged over $D = 3$ and real-world datasets OSM and NYC Taxi. For KeOps, we only computed the KMVM on uniform data. Since KeOps is an exact method, the dataset distribution has no effect on computational time. Here, the *smoothness criteria* and *adaptive far-field* technique improve computational time. We find that F^{3}M achieves a speed-up between $2.0 - 33.3\times$ against FFM(GPU) and $8.0 - 8500\times$ speed-up against KeOps.

Table 5: Comparison between F^{3}M, FFM(GPU) and KeOps. It should be noted that KeOps is only run up to $n = 10^8$ for all experiments (a run for $n = 10^9$ would take weeks). The times for $n > 10^8$ are extrapolated for KeOps. FFM(GPU) could only run on uniform data for $n = 10^9$.

n	F^{3}M time (s)			FFM(GPU) time (s)			KeOps time (s)	Speedup vs KeOps	Speedup vs FFM(GPU)		
	OSM $(D=2)$	Taxi $(D=3)$	$D=3$	OSM $(D=2)$	Taxi $(D=3)$	$D=3$	$D=3$	$D=3$	OSM $(D=2)$	Taxi $(D=3)$	$D=3$
10^6	0.1 ± 0.0	0.5 ± 0.2	0.2 ± 0.1	0.7 ± 0.2	1.2 ± 0.2	0.4 ± 0.2	1.56	8.0	**7.0**	**2.4**	**2.0**
10^7	1.1 ± 0.4	3.3 ± 0.6	1.7 ± 0.7	10.1 ± 0.8	110.0 ± 1.9	3.7 ± 1.0	148.6	87.0	**9.2**	**33.3**	**2.2**
10^8	10.8 ± 3.9	30.4 ± 6.9	17.1 ± 7.3	OOM	769.5 ± 27.9	43.7 ± 12.2	1.49e4	873.0	N/A	**25.3**	**2.6**
10^9	101.8 ± 36.6	290.0 ± 69.4	174.0 ± 76.6	OOM	OOM	517.4 ± 60.8	1.49e6	8583.0	N/A	N/A	**3.0**
Error	0.0005	0.0012	0.0008	0.0005	0.0002	0.0003	0.0				
Theoretical Complexity	$\mathcal{O}\left(n \cdot \log_2\left(\frac{D \cdot \mathcal{E}^2}{\gamma^2 \cdot 4 \cdot \eta}\right)\right)$			$\mathcal{O}(n \log(n))$			$\mathcal{O}(n^2)$				

Gaussian process regression experiments We further compare F^{3}M as a drop-in KMVM operation applied to Black-box Matrix Multiplication [15] for Gaussian Processes, compared to KISS-GP [35], an approximate Gaussian process using cubic interpolation for kernel approximation. We mimic the setup in [32] and consider the datasets 3DRoad, Song, Buzz and House Electric, where we apply PCA to the last three datasets and take the 3 first principal components for a fair comparison against KISS-GP, which is limited by $D \leq 3$. We demonstrate the results in Table 6. As exact GP using F^{3}M demonstrates competitive results even when compared to SVGP [18] and SGPR [30], we hypothesize that many high-dimensional datasets conform to the *manifold hypothesis* [13], allowing F^{3}M to be widely applicable out-of-the-box even in high-dimensional settings.

Table 6: Gaussian process regression results. Exact GP using F^{3}M shows improved results and scaling compared to KISS-GP. SGPR and KISS-GP could not scale to the HouseElectric dataset.

Dataset	n	d	RMSE				Training time (s)			
			Exact GP (F^{3}M)	KISS-GP	SGPR ($m=512$)	SVGP ($m=1024$)	Exact GP (F^{3}M)	KISS-GP	SGPR ($m=512$)	SVGP ($m=1024$)
3DRoad	278,319	3	**0.297 ±0.036**	0.314 ±0.01	0.661 ± 0.010	0.481 ± 0.002	**27.8 ±18.0**	312.9 ±10.8	720.5 ± 330.4	2045.1 ± 191.4
Song	329,820	90	**0.369 ±0.029**	0.57 ±0.298	0.803 ± 0.002	0.998 ± 0.000	**7.2 ±3.1**	1705.2 ±115.6	473.3 ± 187.5	2373.3 ± 184.9
Buzz	373,280	77	0.967 ±0.002	0.997 ±0.05	**0.300± 0.004**	0.304 ± 0.012	**33.5 ±9.0**	542.7 ±0.8	1754.8 ± 1099.6	2780.8 ± 175.6
HouseEletric	1,311,539	9	0.308 ±0.006	OOM	OOM	**0.084 ± 0.005**	79.8 ±23.1	N/A	N/A	22062.6 ± 282.0

6 Limitations and Further Research

This work has introduced and implemented F^{3}M on GPU, which enables fast KMVM for tall and skinny data up to $n = 10^9$. F^{3}M has improved complexity which also is controllable through η, and retains linear memory. Experiments in higher dimensions also exhibit linear complexity, however requiring more nodes for lower errors. F^{3}M can further be directly used as a drop-in KMVM operation, as demonstrated with FALKON and Gaussian process regression, achieving significant speedups and competitive performance on both tasks. As an interpolation based approximation method, F^{3}M is still limited by the exponential growth of interpolation nodes with respect to D, although removing empty boxes, *small field* and sparse grids allow KMVM for $D \leq 7$. A fruitful direction would be to extend ideas in F^{3}M to accommodate higher-dimensional data by considering randomized partitioning [4], decoupling the dependency on D in geometry based partitioning. Further, an exact characterization of how $m_i^{\text{far}}, m_i^{\text{smooth}}, m_i^{\text{small}}, m_i^{\text{empty}}$ grows is left to future work.

References

[1] https://examples.pyviz.org/osm/osm-1billion.html. `https://examples.pyviz.org/osm/osm-1billion.html`. Accessed: 2021-05-19.

[2] https://www1.nyc.gov/site/tlc/about/tlc-trip-record-data.page. `https://www1.nyc.gov/site/tlc/about/tlc-trip-record-data.page`. Accessed: 2022-05-14.

[3] Matthieu Aussal and Marc Bakry. The fast and free memory method for the efficient computation of convolution kernels, 2019.

[4] Arturs Backurs, Piotr Indyk, Cameron Musco, and Tal Wagner. Faster kernel matrix algebra via density estimation. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 500–510. PMLR, 18–24 Jul 2021.

[5] J. H. Barnes and Piet Hut. A hierarchical o(n log n) force-calculation algorithm. *Nature*, 324:446–449, 1986.

[6] J.-M. Belley, P. Belley, F. Colin, and R. Egli. Non-smooth kernels for meshfree methods in fluid dynamics. *Computers |& Mathematics with Applications*, 58(6):1253–1272, 2009.

[7] Jean-Paul Berrut and Lloyd N. Trefethen. Barycentric lagrange interpolation. *SIAM Review*, 46(3):501–517, 2004.

[8] Steffen Börm, Maria Lopez-Fernandez, and Stefan Sauter. Variable order, directional h2-matrices for helmholtz problems with complex frequency, 2019.

[9] Difeng Cai, Edmond Chow, Yousef Saad, and Yuanzhe Xi. Smash: Structured matrix approximation by separation and hierarchy, 2017.

[10] J. Carrier, L. Greengard, and V. Rokhlin. A fast adaptive multipole algorithm for particle simulations. *SIAM J. Sci. Stat. Comput.*, 9(4):669–686, July 1988.

[11] Benjamin Charlier, Jean Feydy, Joan Alexis Glaunès, François-David Collin, and Ghislain Durif. Kernel operations on the GPU, with autodiff, without memory overflows. *arXiv preprint arXiv:2004.11127*, 2020.

[12] James F. Epperson. On the runge example. *Am. Math. Monthly*, 94(4):329–341, April 1987.

[13] Charles Fefferman, Sanjoy Mitter, and Hariharan Narayanan. Testing the manifold hypothesis. *Journal of the American Mathematical Society*, 29, 10 2013.

[14] Code for F3M. https://anonymous.4open.science/r/F3M-7850.

[15] Jacob R. Gardner, Geoff Pleiss, David Bindel, Kilian Q. Weinberger, and Andrew Gordon Wilson. Gpytorch: Blackbox matrix-matrix gaussian process inference with gpu acceleration, 2018.

[16] Damien Garreau, Wittawat Jitkrittum, and Motonobu Kanagawa. Large sample analysis of the median heuristic, 2017.

[17] Leslie Greengard, Michael O'Neil, Manas Rachh, and Felipe Vico. Fast multipole methods for evaluation of layer potentials with locally-corrected quadratures, 2020.

[18] James Hensman, Nicolò Fusi, and Neil D. Lawrence. Gaussian processes for big data. In *Proceedings of the Twenty-Ninth Conference on Uncertainty in Artificial Intelligence*, UAI'13, page 282–290, Arlington, Virginia, USA, 2013. AUAI Press.

[19] Gary W Howell. Derivative error bounds for lagrange interpolation: An extension of cauchy's bound for the error of lagrange interpolation. *Journal of Approximation Theory*, 67(2):164–173, 1991.

[20] Wei Kang and Lucas C. Wilcox. Mitigating the curse of dimensionality: Sparse grid characteristics method for optimal feedback control and hjb equations, 2015.

[21] Bartosz Kohnke, Carsten Kutzner, Andreas Beckmann, Gert Lube, Ivo Kabadshow, Holger Dachsel, and Helmut Grubmüller. A cuda fast multipole method with highly efficient m2l far field evaluation. *The International Journal of High Performance Computing Applications*, 35:109434202096485, 10 2020.

[22] Gary K. Leaf and Hans G. Kaper. l^∞-error bounds for multivariate lagrange approximation. *SIAM Journal on Numerical Analysis*, 11(2):363–381, 1974.

[23] Donald Meagher. Octree encoding: A new technique for the representation, manipulation and display of arbitrary 3-d objects by computer, 10 1980.

[24] Giacomo Meanti, Luigi Carratino, Lorenzo Rosasco, and Alessandro Rudi. Kernel methods through the roof: Handling billions of points efficiently. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 14410–14422. Curran Associates, Inc., 2020.

[25] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019.

[26] Alessandro Rudi, Luigi Carratino, and Lorenzo Rosasco. Falkon: An optimal large scale kernel method, 2018.

[27] Bernhard Scholkopf and Alexander J. Smola. *Learning with Kernels: Support Vector Machines, Regularization, Optimization, and Beyond*. MIT Press, Cambridge, MA, USA, 2001.

[28] C. Schwab and W. L. Wendland. Kernel properties and representations of boundary integral operators. *Mathematische Nachrichten*, 156(1):187–218, 1992.

[29] S. A. Smolyak. Quadrature and interpolation formulas for tensor products of certain class of functions. *Dokl. Akad. Nauk SSSR*, 148(5):1042–1053, 1963. Transl.: Soviet Math. Dokl. 4:240-243, 1963.

[30] Michalis Titsias. Variational learning of inducing variables in sparse gaussian processes. In David van Dyk and Max Welling, editors, *Proceedings of the Twelth International Conference on Artificial Intelligence and Statistics*, volume 5 of *Proceedings of Machine Learning Research*, pages 567–574, Hilton Clearwater Beach Resort, Clearwater Beach, Florida USA, 16–18 Apr 2009. PMLR.

[31] Daniel Tward, Timothy Brown, Yusuke Kageyama, Jaymin Patel, Zhipeng Hou, Susumu Mori, Marilyn Albert, Juan Troncoso, and Michael Miller. Diffeomorphic registration with intensity transformation and missing data: Application to 3d digital pathology of alzheimer's disease. *Frontiers in Neuroscience*, 14, 2020.

[32] Ke Alexander Wang, Geoff Pleiss, Jacob R. Gardner, Stephen Tyree, Kilian Q. Weinberger, and Andrew Gordon Wilson. Exact gaussian processes on a million data points, 2019.

[33] Lei Wang, Robert Krasny, and Svetlana Tlupova. A kernel-independent treecode based on barycentric lagrange interpolation, 2019.

[34] Andrew Wilson and Hannes Nickisch. Kernel interpolation for scalable structured gaussian processes (kiss-gp). In Francis Bach and David Blei, editors, *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pages 1775–1784, Lille, France, 07–09 Jul 2015. PMLR.

[35] Andrew Gordon Wilson and Hannes Nickisch. Kernel interpolation for scalable structured gaussian processes (kiss-gp). In *Proceedings of the 32nd International Conference on International Conference on Machine Learning - Volume 37*, ICML'15, page 1775–1784. JMLR.org, 2015.

[36] Yang, Duraiswami, Gumerov, and Davis. Improved fast gauss transform and efficient kernel density estimation. In *Proceedings Ninth IEEE International Conference on Computer Vision*, pages 664–671 vol.1, 2003.