Generalization Gap in Amortized Inference

Abstract

The ability of likelihood-based probabilistic models to generalize to unseen data is central to many machine learning applications such as lossless compression. In this work, we study the generalizations of a popular class of probabilistic models - the Variational Auto-Encoder (VAE). We point out the two generalization gaps that can affect the generalization ability of VAEs and show that the over-fitting phenomenon is usually dominated by the amortized inference network. Based on this observation we propose a new training objective, inspired by the classic wake-sleep algorithm, to improve the generalizations properties of amortized inference. We also demonstrate how it can improve generalization performance in the context of image modeling and lossless compression.

1 Introduction

Probabilistic models have achieved great success in modelling real-life data. Given a set of training data that are sampled from an underlying data distribution $\mathcal{X}_{train} = \{x_1, \ldots, x_N\} \sim p_d(x)$, the goal of probabilistic modelling is to approximate $p_d(x)$ with a model $p_\theta(x)$. The parameter θ is usually learned by Maximum Likelihood Estimation (MLE): $\theta^* = \arg\max_\theta \frac{1}{N} \sum_{n=1}^{N} \log p_\theta(x_n)$. As is a common concern in supervised learning, a flexible probabilistic model may also overfit to a finite training dataset $\mathcal{X}_{train}$ degrading generalization performance. The generalization performance of probabilistic models can be measured by the test likelihood [42]: $\frac{1}{M} \sum_{n=1}^{M} \log p_\theta(x'_m)$, where $\mathcal{X}_{test} = \{x'_1, \ldots, x'_M\} \sim p_d(x)$ is the test dataset.

Although the test likelihood is a common evaluation criterion for probabilistic models [33], the factors that affect the generalization of deep generative models are less studied. We posit that this is because for common tasks, like sample generation or representation learning, good generalization in terms of the test likelihood is not a sufficient measure of performance. For example implicit models can generate sharp samples without having a likelihood function [14, 2, 40] and representations learned by latent variable models can be arbitrarily transformed without changing the likelihood [23]. However, in recent applications that use deep generative models for lossless compression [34, 35, 20], generalization in terms of the test likelihood directly indicates higher compression rate [42]. Specifically, given a probabilistic model $p_\theta(x)$, a lossless compressor can be constructed to compress a test data x' to a bit string with length approximately equal to $-\log_2 p_\theta(x')$ (see [25] for a detailed introduction). For a set of test data $\mathcal{X}_{test} = \{x'_1, \ldots, x'_M\} \sim p_d(x)$ with $M \to \infty$, when $p_\theta(x) \to p_d(x)$, the average compression length attains data entropy $-\frac{1}{M} \sum_{m=1}^{M} \log_2 p_\theta(x'_m) \to \mathrm{H}(p_d(x))$, which is *optimal* under Shannon's source coding theorem [31]. Therefore, a better test likelihood can lead to a greater saving in bits and so understanding and improving generalization of deep generative models is an important challenge.

A popular type of probabilistic model is the latent variable model $p_\theta(x) = \int p_\theta(x|z)p(z)dz$, where z is an unobserved latent variable [19, 27]. For a non-linear parameterization of $p_\theta(x|z)$, the evaluation of $\log p_\theta(x)$ is usually intractable and variational inference technique are used to form the evidence

lower bound (ELBO) to the log-likelihood $\log p_\theta(x)$. The non-linear latent variable model with amortized inference is also referred to as the Variational Auto-Encoder (VAE) [19, 27]. In this case, the generalization performance of a VAE not only depends on the generative model $p_\theta(x|z)$ but is also affected by the variational inference procedure. We are thus interested in studying the factors that affect the generalization of VAEs and how to improve the generalization in practice.

The contributions of our paper are summarized as follows:

- We show the generalization of VAEs is affected by both the generative model (decoder) and the amortized inference network (encoder); and the overfitting of the VAE is mainly dominated by the overfitting of the amortized inference network.
- We propose a new plug-in amortized inference scheme which can improve the generalization without changing the network structure. We further demonstrate how the proposed method can improve the compression rate in a practical lossless compression system.

We first introduce VAE and then discuss the factors that affect its generalization.

2 Generalizations of VAEs

VAE [19, 27] assumes a latent variable model $p_\theta(x) = \int p_\theta(x|z)p(z)dz$, where the integration over z is intractable for non-linear $p_\theta(x|z)$. The evidence lower bound (ELBO) can be used

$$\langle \log p_\theta(x) \rangle_{p_d(x)} \geq \langle \log p_\theta(x,z) - \log q_\phi(z|x) \rangle_{q_\phi(z|x)p_d(x)} \equiv \langle \mathrm{ELBO}(x,\theta,\phi) \rangle_{p_d(x)}, \quad (1)$$

where $q_\phi(z|x)$ is a variational posterior parameterized by a neural network with parameter ϕ. The use of an approximate posterior of the form $q_\phi(z|x)$ is called *amortized inference*. To better understand this objective, we can rewrite the expected ELBO as following

$$\langle \mathrm{ELBO}(x,\theta,\phi) \rangle_{p_d(x)} = \left\langle \log p_\theta(x) - \mathrm{KL}(q_\phi(z|x)||p_\theta(z|x)) \right\rangle_{p_d(x)} \quad (2)$$

$$= -\underbrace{\mathrm{H}(p_d)}_{const.} - \underbrace{\mathrm{KL}(p_d(x))||p_\theta(x))}_{\text{model learning}} - \underbrace{\langle \mathrm{KL}(q_\phi(z|x)||p_\theta(z|x)) \rangle_{p_d(x)}}_{\text{amortized inference}}, \quad (3)$$

where the entropy $\mathrm{H}(p_d) \equiv -\langle \log p_d(x) \rangle_{p_d(x)}$ is a constant. We further denote the posterior family of $q_\phi(z|x)$ as $\mathcal{Q}$, which is indexed by finite dimensional θ [38]. If $\mathcal{Q}$ is flexible enough such that the true posterior $p_\theta(z|x) \in \mathcal{Q}$, where $p_\theta(z|x) \propto p_\theta(x|z)p(z)$, then in the optimum of Equation 2, we have $\mathrm{KL}(q_\phi(z|x)||p_\theta(z|x)) = 0 \Rightarrow q_\phi(z|x) = p_\theta(z|x)$ for $x \sim p_d(x)$ and the ELBO becomes tight $\mathrm{ELBO}(x,\theta,\phi) = \log p_\theta(x)$ [19, 5]. Many methods have been developed to increase the flexibility of $\mathcal{Q}$, e.g. adding auxiliary variables [1, 24] or flow-based methods [8, 26].

In practice, we can only access a finite training dataset $\mathcal{X}_{train}$, the training objective is $\frac{1}{N} \sum_{n=1}^{N} \mathrm{ELBO}(x_n, \theta, \phi)$, which can potentially cause the VAE to over-fit to the training dataset. For example, Figure 1 shows the training and testing curve of a VAE that is trained on the Binary MNIST dataset. We plot the Bits-per-dimension (BPD), which is the negative $\log_2$ likelihood normalized by the data dimension (lower BPD indicates higher likelihood). We found the model has lower BPD (higher likelihood) on the training dataset but higher BPD on the test dataset. This indicates the model is overfitting to the training data.

Recent work [34, 35, 20] has successfully applied VAE style models to lossless compression realizing impressive performance. In this setting the average compression length on the test data set is approximately equal to $-\frac{1}{M} \sum_{m=1}^{M} \mathrm{ELBO}(x'_m, \theta, \phi)$. Hence the better the test ELBO, the better the compression performance. This motivates finding practical ways to improve the generalization

Figure 1: Overfitting in VAE. The VAE is trained for 1k epochs and we plot the testing BPD every 100 epochs. Also see Section 4 for model and training details.

of VAEs. In the following sections we discuss two factors that will potentially affect the generalizations of VAEs and discuss how to alleviate this overfitting phenomenon.

2.1 Two Factors Affect the Generalization of VAEs

In practice, we only access to a finite dataset $\mathcal{X}_{train}$ during training, which leads to an empirical ELBO approximation $\langle \text{ELBO}(x, \theta, \phi)\rangle_{p_d(x)} \approx \frac{1}{N}\sum_{n=1}^{N}\text{ELBO}(x_n, \theta, \phi)$. The decomposition in Equation 3 directly suggests that the empirical ELBO contains 1) a *model empirical approximation*:

$$\text{KL}(p_d(x)||p_\theta(x)) \approx \frac{1}{N}\sum_{n=1}^{N}\log p_\theta(x_n) + const., \tag{4}$$

which will potentially make a flexible model $p_\theta(x)$ over-fit to the training data; and 2) an *amortized inference empirical approximation*:

$$\left\langle \text{KL}(q_\phi(z|x)||p_\theta(z|x))\right\rangle_{p_d(x)} \approx \frac{1}{N}\sum_{n=1}^{N}\text{KL}(q_\phi(z|x_n)||p_\theta(z|x_n)), \tag{5}$$

where similarly a flexible $q_\phi(z|x)$ can also over-fit to the training data. More specifically, we let $\hat{\phi}$ be the optimal parameter of the empirical variational inference objective

$$\hat{\phi} = \arg\min_\phi \frac{1}{N}\sum_{n=1}^{N}\text{KL}\left(q_\phi(z|x_n)||p_\theta(z|x_n)\right) \tag{6}$$

and we assume for any training data point $x_n \in \mathcal{X}_{train}$

$$q_{\hat{\phi}}(z|x_n) = \arg\min_{q\in\mathcal{Q}}\text{KL}(q_\phi(z|x_n)||p_\theta(z|x_n)) \equiv q^*(z|x_n),$$

where $q^*(z|x_n)$ is the realizable optimal posterior (in the $\mathcal{Q}$ family) for x_n[1]. For $x'_m \in \mathcal{X}_{test}$, there is no guarantee that $q_{\hat{\phi}}(z|x'_m)$ is a good approximation to the true posterior $p_\theta(z|x'_m)$. We thus refer to the difference between the ELBOs evaluated using $q_{\hat{\phi}}(z|x)$ and $q^*(z|x)$ as the *amortized inference generalization gap*, which is formally defined as

$$\left\langle \text{KL}(q_{\hat{\phi}}(z|x)||p_\theta(z|x)) - \text{KL}(q^*(z|x)||p_\theta(z|x))\right\rangle_{p_d(x)}. \tag{7}$$

Equivalently, this gap can be written as the difference between two ELBOs with two different q

$$\left\langle \underbrace{\langle\log p_\theta(x, z) - \log q^*(z|x)\rangle_{q^*(z|x)}}_{\text{ELBO with optimal inference}} - \underbrace{\langle\log p_\theta(x, z) - \log q_{\hat{\phi}}(z|x)\rangle_{q_{\hat{\phi}}(z|x)}}_{\text{ELBO with amortized inference}}\right\rangle_{p_d(x)}. \tag{8}$$

The inference neural network introduced with amortization is the cause of this inference generalization gap. It is important to emphasize that this gap cannot be reduced by simply using a more flexible $\mathcal{Q}$. This would only make $\text{KL}(q_\phi(z|x_n)||p_\theta(z|x_n))$ smaller for the training data $x_n \in \mathcal{X}_{train}$ but would not explicitly encourage better generalization performance on test data [32].

To summarize, the generalization performance of VAE models depends on two factors:

- **Generative model generalization gap:** defined as $\text{KL}(p_d(x)||p_\theta(x))$ and is caused by the overfitting of the generative model (decoder).
- **Amortized inference generalization gap:** defined in Equation 8 and is caused by the overfitting of the amortized inference (encoder).

2.2 Impact of the Generalization Gaps

The *generative model generalization gap* that is estimated by the test dataset (up to a constant) $\text{KL}(p_d(x)||p_\theta(x)) \approx -\frac{1}{M}\sum_{m=1}^{M}\log p_\theta(x'_m) + const.$, cannot be calculated explicitly since we can only evaluate the lower bound $-\frac{1}{M}\sum_{m=1}^{M}\text{ELBO}(x'_m, \theta, \phi)$. Fortunately, as suggested in Equation 2, if we know the optimal posterior for the test data $q^*(z|x'_m) \equiv \arg\min_{q\in\mathcal{Q}}\text{KL}(q(z|x'_m)||p_\theta(z|x'_m))$, the log-likelihood can be well approximated by the lower bound $\log p_\theta(x'_m) \approx \text{ELBO}(x'_m, \theta, \phi)$. This approximation becomes an equality when $p_\theta(z|x'_m) \in \mathcal{Q}$, see Appendix A for verification of the tightness of the bound. Similarly, the *amortized inference generalization gap* can be estimated by knowing optimal posterior $q^*(z|x'_m)$ of the the test dataset:

$$\frac{1}{M}\sum_{m=1}^{M}\langle\log p_\theta(x'_m, z) - \log q^*(z|x'_m)\rangle_{q^*(z|x'_m)} - \langle\log p_\theta(x'_m, z) - \log q_{\hat{\phi}}(z|x'_m)\rangle_{q_{\hat{\phi}}(z|x'_m)}. \tag{9}$$

---

[1]For a powerful inference network we assume that there is no amortization gap [10], which means $q_{\hat{\phi}}(z|x)$ can provide the optimal $q^*(z|x_n)$ for any training data $x_n \in \mathcal{X}_{train}$, see Appendix E for a further discussion.

We can then estimate $q^*(z|x'_m)$ by fixing θ (which is trained on the training dataset) and learning

$$\phi^* = \min_\phi \text{KL}(q_\phi(z|x'_m)||p_\theta(z|x'_m)) = \max_\phi \left\langle \log p_\theta(x'_m, z) - \log q_\phi(z|x'_m) \right\rangle_{q_\phi(z|x'_m)}. \quad (10)$$

on the test dataset and assume $q^*(z|x'_m) = q_{\phi^*}(z|x'_m)$. This optimal inference strategy can help eliminate the effect of the inference generalization gap, allowing us to isolate the degree to which both the generative model and amortized inference generalization gap are contributing to the overfitting.

Therefore, we take the VAE described in Section 2.2 and train the $q_\phi(z|x)$ for 100 epochs (with Adam [18] and $\text{lr} = 5 \times 10^{-4}$) on the test data using Equation 10 to obtain test BPD for the optimal inference. In Figure 2 we plot the test BPD using the optimal inference and classic amortized inference, where the green curve represents the approximation of the average likelihood $\frac{1}{M} \sum_{n=1}^{M} \log p_\theta(x'_m)$ and the difference between two inference curves is the *amortized inference generalization gap*. We observe that after eliminating the inference generalization gap, the test BPD is stable with a marginal increase during training, which suggests the generative model (decoder) slightly overfit to the data but the overfitting phenomenon of the VAE is mainly dominated by the overfitting of the amortized inference network.

Figure 2: Visualization of amortized inference generalization gap in a VAE that is trained on MNIST.

Although the optimal inference strategy can help eliminate the inference generalization gap, training q_ϕ at test time is not practical in most applications of interest. Therefore, we focus on improving the generalization of amortized inference at training time. In the next section, we introduce a consistency criterion that allows us to further understand the impact of amortized inference on generalization.

3 Improving Generalization with Consistent Amortized Inference

We now propose an *inference consistency requirement*, which if satisfied, would result in optimal generalization for amortized variational inference, i.e. when $p_\theta \to p_d$, the amortized posterior should converge to the true posterior $q_\phi(z|x) \to p_\theta(z|x)^2$ for every $x \sim p_d(x)$. Although this requirement seems natural for variational inference, the classic amortized inference training that is widely used for VAEs [19] doesn't satisfy it. Recall the typical VAE empirical ELBO training objective

$$\frac{1}{N} \sum_{n=1}^{N} \log p_\theta(x_n) - \text{KL}(q_\phi(z|x_n)||p_\theta(z|x_n)). \quad (11)$$

When the model converges to the true distribution $p_{\theta^*} = p_d$ the training criterion for $q_\phi(z|x)$

$$\min_\phi -\frac{1}{N} \sum_{n=1}^{N} \text{KL}(q_\phi(z|x_n)||p_{\theta^*}(z|x_n)) \quad (12)$$

can still result in the amortized posterior $q_\phi(z|x)$ over-fitting to the training data. In principle, one could also limit the network capacity and/or add an explicit regularizer to the parameters [30] in an attempt to improve the generalization. However, this still cannot satisfy the consistency requirement in principle since it doesn't change the underlying training objective. Alternatively, there is another classic variational inference method that we now discuss, the wake-sleep training algorithm [12, 16], which satisfies the proposed consistency requirement.

3.1 Wake-Sleep Training

Defining $q_\phi(x, z) = q_\phi(z|x)p_d(x)$ and $p_\theta(x, z) = p_\theta(x|z)p(z)$, the two phases of the wake-sleep training [12, 16] can be written as minimizing two different KL divergences in both x and z space.

Wake phase model learning: $p_\theta(x|z)$ is trained by minimizing the KL divergence

$$\min_\theta \text{KL}(q_\phi(x, z)||p_\theta(x, z)) = \max_\theta \left\langle \text{ELBO}(x, \theta, \phi) \right\rangle_{p_d(x)} + const., \quad (13)$$

where $\langle \cdot \rangle_{p_d(x)}$ is approximated using the training set. This is referred to as the *wake phase* since the model is trained on experience from the 'real environment', i.e. it uses true data samples from $p_d(x)$.

---

[2] We assume the true posterior belongs to the variational family $p_\theta(z|x) \in \mathcal{Q}$.

155 **Sleep phase amortized inference:** $q_\phi(z|x)$ is trained by minimizing the KL divergence

$$\min_\phi \mathrm{KL}(p_\theta(x,z)||q_\phi(x,z)) = \min_\phi \left\langle \mathrm{KL}(p_\theta(z|x)||q_\phi(z|x)) \right\rangle_{p_\theta(x)} + const. \tag{14}$$

156 Leaving out the terms that are irrelevant to ϕ, the objective can be estimated with Monte-Carlo
157 $\left\langle -\log q_\phi(z|x'_m) \right\rangle_{p_\theta(x,z)} \approx \frac{1}{K} \sum_{k=1}^{K} -\log q_\phi(z_k|x_k)$, where $z_k \sim p(z)$ and $x_k \sim p_\theta(x|z_k)$. This is
158 referred to as the *sleep phase* because the samples from the model used to train q_ϕ are interpreted
159 as dreamed experience. In contrast, the training criterion for the typical VAE amortized inference
160 (Equation 5) uses the true data samples to train $q_\phi(z|x)$. So following the wake-sleep nomenclature
161 we can refer to this as *wake phase amortized inference*. We notice that a perfect model used in the
162 sleep phase is equivalent to minimizing

$$\left\langle \mathrm{KL}(p_\theta(z|x)||q_\phi(z|x)) \right\rangle_{p_{\theta^*}(x)} = \left\langle \mathrm{KL}(p_\theta(z|x)||q_\phi(z|x)) \right\rangle_{p_d(x)}. \tag{15}$$

163 Therefore, the training of the inference network satisfies the *inference consistency requirement* since
164 we can access infinite training data from p_d by sampling from p_{θ^*}.

165 However, the wake-sleep algorithm presented lacks convergence guarantees [12] and minimizing
166 $\mathrm{KL}(p_\theta(z|x)||q_\phi(z|x))$ in the sleep phase doesn't necessarily encourage an improvement to the ELBO,
167 which directly relates to the compression rate in the lossless compression application [34]. Therefore,
168 in the next section, we propose a new variational inference scheme: *reverse sleep amortized inference*
169 and demonstrate how it helps improve the generalization of the inference network in practice.

3.2 Reverse Sleep Amortized Inference

171 We propose to use the *reverse KL divergence* in the sleep phase. We thus fix θ and train ϕ using

$$\min_\phi \left\langle \mathrm{KL}(q_\phi(z|x)||p_\theta(z|x) \right\rangle_{p_\theta(x)} = \max_\phi \left\langle \log p_\theta(x,z) - \log q_\phi(z|x) \right\rangle_{q_\phi(z|x)p_\theta(x)}, \tag{16}$$

172 where the integration $\langle \cdot \rangle_{p_\theta(x)}$ is approximated by Monte-Carlo using samples from the generative
173 model $p_\theta(x)$. This reverse KL objective encourages improvements to the ELBO. When we have a
174 perfect model $p_{\theta^*}(x) = p_d(x)$ the reverse sleep phase is equivalent to

$$\min_\phi \left\langle \mathrm{KL}(p_{\theta^*}(z|x)||q_\phi(z|x)) \right\rangle_{p_{\theta^*}(x)} = \min_\phi \left\langle \mathrm{KL}(p_{\theta^*}(z|x)||q_\phi(z|x)) \right\rangle_{p_d(x)} \tag{17}$$

175 which satisfies the *inference consistency requirement*.

176 The consistency requirement can also be validated empir-
177 ically when the perfect model is known $p_{\theta^*}(x) = p_d(x)$.
178 This can be achieved by using a pre-trained VAE as the
179 true data generation distribution. Therefore, we first train
180 a VAE to fit the binary MNIST problem. The VAE has
181 the same structure as that used in Section 2 and is trained
182 using Adam with $lr = 1 \times 10^{-3}$ for 100 epochs. After
183 training, we treat the pre-trained decoder $p_{\theta'}(x|z)$ as the
184 training data generator $p_d(x) \equiv \int p_{\theta'}(x|z)p(z)dz$. We
185 then sample 10000 data samples from p_d to form a train-
186 ing set $\mathcal{X}_{train}$ and 1000 samples to form a test set $\mathcal{X}_{test}$.
187 We then train a new $q_\phi(z|x)$ with: 1. wake phase inference
188 (VAE) 2. (forward) sleep inference and 3. reverse sleep

Figure 3: Amortized inference consis-
tency. We plot the mean and std of the
test BPD over three random seeds.

189 inference. The network is trained using Adam with $lr = 1 \times 10^{-3}$ for 100 epochs. Figure 3 shows
190 the test BPD calculated after every training epoch. We can see the sleep phase out-performs the wake
191 phase and the reverse sleep inference achieves the best BPD. Intuitively, this is because both the
192 forward and reverse sleep inference use the true model to generate additional training data whereas
193 the wake inference only has access to the finite training dataset X_{train}.

3.3 Reverse Half-asleep Amortized Inference with Imperfect Models

195 In practice our model will not be perfect $p_\theta \neq p_d$. Empirically we find that samples from even a well
196 trained model p_θ may not always be sufficiently like the samples from the true data distribution. This
197 can lead to a degradation in the performance of the inference network when using the reverse-sleep

approach. For this reason, we propose to use a mixture distribution between the model and the empirical training data distribution as follows

$$\big\langle \mathrm{KL}\big(q_\phi(z|x)||p_\theta(z|x)\big)\big\rangle_{m(x)} \quad \text{where} \quad m(x) \equiv \alpha p_\theta(x) + (1-\alpha)\hat{p}_d. \tag{18}$$

When $\alpha = 0$, it reduces to the standard approach used in VAE training. When $\alpha = 1$, we recover the reverse sleep method (Equation 16). We find that a setting of $\alpha = 0.5$ works well in practice. This balances samples from the true underlying data distribution with samples from the model.

We thus refer to this method as *reverse half-asleep* since it uses both data and model samples to train the amortized posterior. Intuitively, we can rewrite the Equation 18 as a sum of two positive terms

$$\alpha\big\langle \mathrm{KL}\big(q_\phi(z|x)||p_\theta(z|x)\big)\big\rangle_{\hat{p}(x)} + (1-\alpha)\big\langle \mathrm{KL}\big(q_\phi(z|x)||p_\theta(z|x)\big)\big\rangle_{p_\theta(x)}. \tag{19}$$

Therefore, the optimal of this objective will make the first term 0, which is the same requirement as the classic amortized inference (Equation 5). The second term, which is equivalent to the reverse sleep amortized inference (Equation 16), can encourage the inference consistency requirement: when $p_\theta = p_d$, the optimal of the second term will set $q_\phi(z|x) = p_\theta(z|x)$ for any $x \sim p_d(x)$. When p_θ is not perfect, the second term can be seen as a regularizer added to the classic amortized inference objective, which can be used to penalize the hypothesis space of the amortized network [30] to alleviate the over-fitting of the amortized inference.

To compare with different α, we first fit a VAE (with the same structure as that used in Figure 2) to the Binary MNIST dataset, and then train the amortized posterior using sleep inference (Equation 14) and three different α for additional 100 epochs using Adam with learning rate 3×10^{-4}. Figure 4 shows the test BPD comparison. We find the proposed reverse half-asleep method ($\alpha = 0.5$)

Figure 4: Test BPD comparisons of Amortized inference with different α. The mean and std are calculated with three random seeds.

outperforms the reversed sleep method ($\alpha = 1$), whereas the standard amortized inference training in VAE ($\alpha = 0$) leads to overfitting of the inference network. We also plot the sleep inference training curve, whose BPD is less competitive since it is not directly optimizing the ELBO.

4 Generalization Experiments

We apply the reverse half-asleep to improve the generalization of VAEs on three different datasets: binary MNIST, grey MNIST [22] and CIFAR10 [21]. For binary and grey MNIST, we use latent dimension 16/32 and neural nets with 2 layers of 500 hidden units in both the encoder and decoder. We use Bernoulli $p(x|z)$ for binary MNIST and discretized logistic distribution for grey MNIST. We train the VAE with the usual amortized inference approach using Adam with $lr = 3 \times 10^{-4}$ for 1000 epochs and save the model every 100 epochs. We then use the saved models to 1) evaluate on the test data sets, 2) conduct optimal inference by training $q_\phi(z|x)$ on the test data and 3) run reverse half-asleep method before calculating the test BPD. For the reverse half-asleep, we train the amortized posterior for 100 epochs with Adam and $lr = 5 \times 10^{-4}$. To sample from $p_\theta(x)$, we firstly sample $z' \sim p(z)$ and sample $x' \sim p(x|z = z')$. For optimal inference, we train the amortized posterior with the same optimization scheme on the test data set for additional 500 epochs to ensure the same number of gradient steps are conducted (since training set is 5 times as big as the test set).

For CIFAR10, we use the convolutional ResNet [15, 36] with 2 residual blocks and latent size 128. The observational distribution is a discretized logistic distribution with linear autoregressive parameterization within channels. We train the VAE for 500 epochs with Adam and $lr = 5 \times 10^{-4}$ and save the model every 100 epoch. The pre-trained VAE achieves 4.592 BPD on the CIFAR10, which is comparable with other single latent VAE models reported in [36]: 4.51 BPD with a VAE with latent dimension 256 and 4.67 BPD with a discrete latent VAE (VQVAE).

Ideally, when the VAE model converges to the true distribution $p_\theta \to p_d$, the aggregate posterior $q_\phi(z) = \int q_\phi(z|x)p_d(x)dx$ will match the prior $p(z)$. However, for a complex distribution like CIFAR10, a significant mismatch between $q_\phi(z)$ and $p(z)$ is usually observed in practice [44, 11]. In this case, the sample x' that is generated using a latent sample from the prior $x' \sim p(x|z')$, where

	(a) Binary MNIST	(b) Grey MNIST	(c) CIFAR10

Figure 5: Test BPD comparisons among amortized inference (VAE), optimal inference and the reverse half-asleep inference on three datasets. The x-axis represents the training epochs.

$z' \sim p(z)$, may be blurry or invalid. A common solution is to train another model, e.g. a VAE [11] or a PixelCNN [37, 36] to approximate $q_\phi(x)$. In our case, we instead directly sample from $q_\phi(z)$ instead of $p(z)$ to generate samples in Equation 16, which can be done by first sampling $x' \sim p_d(x)$ (from the training dataset) and then sample $z' \sim q_\phi(z|x = x')$. This scheme still results in a consistent training objective since $q_{\phi^*}(z) = p(z)$ for the optimal posterior $q_{\phi^*}(z|x)$. We use Adam with $lr = 1 \times 10^{-5}$ and train the reverse half-asleep inference for 100 epochs on the training data and train the optimal inference strategy for 500 epochs on the test data. Figure 5 shows the test BPD comparison for three datasets. We find that the reverse half-asleep training approach consistently improves the generalization performance of our models as measured by the negative test ELBO. In contrast to the optimal inference strategy, our approach does not require further training on test data to improve generalization performance.

Recent work [32] proposed to alleviate the overfitting of the amortized inference by optimizing a linear combination between the traditional amortized inference (Equation 5) and a denoising objective

$$\alpha \langle \text{KL}(q_\phi(z|x + \epsilon)||p_\theta(z|x)) \rangle_{p(\epsilon)} + (1 - \alpha)\text{KL}(q_\phi(z|x)||p_\theta(z|x)), \qquad (20)$$

where $p(\epsilon) = \text{N}(0, \sigma^2 I)$. We compare this regularizer to our method by training the amortized posterior of VAEs for an additional 100/300 and 100 epochs on Binary/Grey MNSIT and CIFAR respectively. For the denoising regularizer, we use the same linear combination weight $\alpha = 0.5$ as that used in Equation 18 and vary $\sigma \in \{0.1, 0.2, 0.4, 0.6, 0.8, 1.0\}$. See Table 1 for the comparison results. We find for MNIST, $\sigma \in \{0.1, 0.2, 0.4\}$ can improve the generalization but larger level noise hurts the inference performance. For CIFAR10, only $\sigma = 0.1$ can slightly improve the generalization by 0.001 BPD. In contrast, our method can achieve better generalization performance without tuning any hyper-parameters. Our method requires sampling from the model, which does require additional computations, but is negligible compared to the whole training procedure. Figure 6 reports the test BPD curves evaluated after every training epoch (the mean and std are calculated over 3 random seeds). We find our method consistently improves model generalization during training.

Table 1: Average test BPD comparisons with Denoising Regularizer [32].

Methods	VAE	$\sigma = 0.1$	$\sigma = 0.2$	$\sigma = 0.4$	$\sigma = 0.8$	$\sigma = 1.0$	Ours
Binary MNIST	0.200	0.195	0.192	0.191	0.196	0.201	**0.187**
Grey MNIST	1.543	1.527	1.519	1.515	1.545	1.550	**1.513**
CIFAR10	4.592	4.591	4.598	4.614	4.651	4.667	**4.572**

	(a) Binary MNIST	(b) Grey MNIST	(c) CIFAR 10

Figure 6: Test BPD evaluated after every training epoch.

We have shown the proposed inference method can consistently achieve better generalization. Since the decoder is shared and fixed in all comparisons, better test ELBO indicates the predicted $q_\phi(z|x')$

is closer to the true posterior $p_\theta(z|x')$ under the KL divergence measure (see Equation 2, higher ELBO with fixed θ indicates $\text{KL}(q_\phi(z|x)||p_\theta(z|x))$ is smaller). Therefore, the proposed method can also benefit a range of tasks that require accurate prediction of the posterior on the test data. In Appendix A and B, we demonstrate our method can provide better proposal distribution for the importance weighted Auto-Encoder[6] and also improve the representation learning performance for down-stream classification tasks. In the next section, we demonstrate an important application: lossless compression, which directly relates to the ELBO generalization of the VAE. We show that the proposed method can give a free improvement on the compression rate without sacrificing any computation time, which is a crucial property for practical compression applications.

5 Application of Lossless Compression

Lossless compression is an important application of VAEs where generalization plays a key role in the compression rate. Given a VAE with $p_\theta(x|z)$, $q_\phi(z|x)$ and $p(z)$, a practical compressor can be efficiently implemented using the Bits Back algorithm [17, 34] with the ANS coder [13]. In Algorithm 1, we describe the Bits Back procedure with amortized inference to compress/decompress a test data point x'. The resulting code length for data x' is approximately equal to the negative ELBO

$$\mathsf{code\_len}(x') \approx -\log_2 p_\theta(x'|z') - \log_2 p(z') + \log_2 q_\phi(z'|x'). \tag{21}$$

We have shown that $q_\phi(z|x)$ may over-fit to the training data, degrading compression performance. To improve the compression BPD, the optimal inference method can also be applied in the Bits Back algorithm. In the compression stage, we can train ϕ by

$$\phi^* = \arg\max_\phi \text{ELBO}(x', \theta, \phi). \tag{22}$$

When the $q_\phi(z|x')$ is parameterized to be a Gaussian, we can just take ϕ to be the mean

---

Algorithm 1 Bits Back with Amortized Inference.

Comp. and decomp. stages share $\{p_\theta(x|z), q_\phi(z|x)\}$.

——————— Compression ———————

Draw sample $z' \sim q_\phi(z|x')$ from the stack.
Encode $x' \sim p_\theta(x|z')$, $z' \sim p(z)$ onto the stack.

——————— Decompression ———————

Decode $z' \sim p(z)$, $x' \sim p_\theta(x|z')$ from the stack.
Encode $z' \sim q_\phi(z|x')$ onto the stack.

---

and standard deviation $\text{N}(\phi_\mu, \phi_\sigma^2)$, which only contains two training parameters. In the decompression stage, we observe that the compressed data x' is recovered before the $q_\phi(z|x')$ is used to encode z'. Therefore, we can also train the $q_\phi(z|x')$ using the recovered x' to maximize the test ELBO. If the optimization procedure is the same as that used in the compression stage, we will get the same $q_{\phi^*}(z|x')$. In practice, we need to pre-specify the number of gradient descent steps K. When K is large, we recover the optimal inference scheme and the code length is approximately

$$\mathsf{code\_len}(x') \approx -\log_2 p_\theta(x'|z') - \log_2 p(z') + \log_2 q_{\phi^*}(z'|x'). \tag{23}$$

This observation was first proposed in [39] in the context of lossy compression and then applied to lossless compression with Bits Back coding in [28]. Furthermore, by varying the optimization steps K in the optimal inference, we can trade off between the speed and the compression rate. This is valuable for practical applications with different speed/rate requirements. See Algorithm 2 for a summary of the Bits Back algorithm with K-step optimal inference.

Although the optimal inference can be used in the lossless compression, it requires extra run-time for training at the compression stages. On the other hand, the proposed reverse half-asleep inference scheme can improve the compression rate *without* scarifying any speed. Additionally, our method can also provide a better initialization for the optimal-inference to allow a better trade-off between compression rate and speed. Therefore, we implement[3] Bits Back with ANS [13] and compare the compression among four inference methods:

Algorithm 2 Bits Back with K-step Optimal Inference

Comp./decomp. stages share $\{p_\theta(x|z), q_\phi(z|x)\}$ and the optimization procedure of Equation 22.

——————— Compression ———————

Take K gradient steps $\phi \to \phi^K$ with Equation 22.
Draw sample $z' \sim q_{\phi^K}(z|x')$ from the stack.
Encode $x' \sim p_\theta(x|z')$, $z' \sim p(z)$ onto the stack.

——————— Decompression ———————

Decode $z' \sim p(z)$, $x' \sim p_\theta(x|z')$ from the stack.
Take K gradient steps $\phi \to \phi^K$ with Equation 22.
Encode $z' \sim q_{\phi^K}(z|x')$ onto the stack.

---

[3]Implementation can be found in the anonymous repo: `https://anonymous.4open.science/r/GeneralizationGapInAmortizedInference-1E44/`. All experiments are run on a NVIDIA V100 GPU.

1. Baseline: This is the classic VAE-based compression introduced by [34]. For binary and grey MNIST, both the encoder and decoder contain 2 fully connected layers with 500 hidden units and latent dimension 10. The observation distributions are Bernoulli and discretized Logistic distribution respectively. For CIFAR10, we use fully convolutional ResNets [15] with 3 residual blocks in the encoder/decoder, latent dimension 128 and discreteized Logistic distribution with channel-wise linear autoregressive[29] as the observation distribution. We train both the amortized posterior and the decoder by maximizing the ELBO (Equation 1) using Adam with $lr = 3 \times 10^{-4}$ for 100/100/500 epochs (Binary MNIST/Grey MNIST/CIFAR10), and then apply Algorithm 1 to conduct compression.

2. Reversed Half-asleep: we do amortized inference using Equation 18 for 100/300 epochs with Adam optimizer ($lr = 3 \times 10^{-4}$) for binary and grey MNIST, and $lr = 1 \times 10^{-5}$ for 100 epochs for CIFAR10. Other training details are the same as the baseline method.

3. Optimal Inference: we take the amortized posterior (encoder) and decoder from the baseline and apply the K-step optimal inference described in Algorithm 2 to do compression. We use Adam optimizer and vary the K from 1 to 10 to achieve a trade-off curve between compression rate and speed. We actively choose the highest learning rate that can make the BPD consistently improve with the increment of K: $lr = 5 \times 10^{-3}$ for binary and grey MNIST and $lr = 1 \times 10^{-3}$ for CIFAR10.

4. Reversed Half-asleep + Optimal Inference: we take the encoder in method 2 and decoder from the baseline and conduct K-step optimal inference. All other training details are as per method 3.

| (a) Binary MNIST | (b) Grey MNIST | (c) CIFAR10 |

Figure 7: We plot the comparisons for different methods. The y-axis is the BPD and x-axis represents the K gradient steps in the optimal inference. The baseline and our R-Half-sleep can be seen as special cases of optimal inference with $K = 0$. We find given a fixed computational budget, our method achieves a lower BPD than one using traditional amortized inference training.

	Baseline	Ours	K=7
BPD	0.185	0.179	0.179
Com. Time	0.006	0.006	0.013
Dec. Time	0.006	0.006	0.013
Time Cost	-	0%	116.7%

	Baseline	Ours	K=8
BPD	4.602	4.585	4.585
Com. Time	0.27	0.27	0.38
Dec. Time	0.26	0.26	0.38
Time Cost	-	0%	46.2%

Figure 8: Compression (Com.) and decompression (Dec.) time comparison. We show that to achieve the same BPD as our method, the K-step optimal inference that initializes the amortized posterior needs $K = 7$ (binary MNIST, left) and $K = 8$ (CIFAR10, right) steps for each test datapoint, which will cost an additional 116.7% and 46.2% of time respectively during compression.

In Figure 7, we plot test BPD comparisons for different methods. We can see if optimization is not allowed at compression time, the use of our reverse-half-asleep method achieves better compression rate with no additional computational cost. If we allow K-step optimization during compression, for a given computational budget, the amortized posterior initialized using our reverse-half-asleep method also achieves lower BPD, which leads to a better trade-off between the time and compression rate. See Table 8 for the average time improvements of our method to compress a single MNIST and CIFAR10 image respectively. See also Appendix **??** for a detailed discussions with related work.

6 Conclusion

We have shown how the generalization of VAEs is largely affected by the amortized inference network and proposed a new variational inference scheme that provides better generalization as demonstrated in the application of lossless compression.

References

[1] F. V. Agakov and D. Barber. An auxiliary variational method. In *International Conference on Neural Information Processing*, pages 561–566. Springer, 2004.

[2] M. Arjovsky, S. Chintala, and L. Bottou. Wasserstein generative adversarial networks. In *International conference on machine learning*, pages 214–223. PMLR, 2017.

[3] D. Barber, A. T. Cemgil, and S. Chiappa. *Bayesian time series models*. Cambridge University Press, 2011.

[4] Y. Bengio, A. Courville, and P. Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

[5] D. M. Blei, A. Kucukelbir, and J. D. McAuliffe. Variational inference: A review for statisticians. *Journal of the American statistical Association*, 112(518):859–877, 2017.

[6] Y. Burda, R. Grosse, and R. Salakhutdinov. Importance weighted autoencoders. *arXiv preprint arXiv:1509.00519*, 2015.

[7] A. T. Cemgil, S. Ghaisas, K. Dvijotham, S. Gowal, and P. Kohli. Autoencoding variational autoencoder. *Neural Information Processing Systems*, 2020.

[8] E. Challis and D. Barber. Affine independent variational inference. *Advances in Neural Information Processing Systems*, 25:2186–2194, 2012.

[9] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR, 2020.

[10] C. Cremer, X. Li, and D. Duvenaud. Inference suboptimality in variational autoencoders. In *International Conference on Machine Learning*, pages 1078–1086. PMLR, 2018.

[11] B. Dai and D. Wipf. Diagnosing and enhancing vae models. *arXiv preprint arXiv:1903.05789*, 2019.

[12] P. Dayan, G. E. Hinton, R. M. Neal, and R. S. Zemel. The helmholtz machine. *Neural computation*, 7(5):889–904, 1995.

[13] J. Duda. Asymmetric numeral systems: entropy coding combining speed of huffman coding with compression rate of arithmetic coding. *arXiv preprint arXiv:1311.2540*, 2013.

[14] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

[15] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[16] G. E. Hinton, P. Dayan, B. J. Frey, and R. M. Neal. The" wake-sleep" algorithm for unsupervised neural networks. *Science*, 268(5214):1158–1161, 1995.

[17] G. E. Hinton and D. Van Camp. Keeping the neural networks simple by minimizing the description length of the weights. In *Proceedings of the sixth annual conference on Computational learning theory*, pages 5–13, 1993.

[18] D. P. Kingma and J. Ba. Adam: A method for stochastic optimization. *International conference on machine learning*, 2015.

[19] D. P. Kingma and M. Welling. Auto-encoding variational bayes. *International Conference on Learning Representations*, 2013.

[20] F. Kingma, P. Abbeel, and J. Ho. Bit-swap: Recursive bits-back coding for lossless compression with hierarchical latent variables. In *International Conference on Machine Learning*, pages 3408–3417. PMLR, 2019.

[21] A. Krizhevsky, G. Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[22] Y. LeCun. The mnist database of handwritten digits. *http://yann. lecun. com/exdb/mnist/*, 1998.

[23] F. Locatello, S. Bauer, M. Lucic, G. Raetsch, S. Gelly, B. Schölkopf, and O. Bachem. Challenging common assumptions in the unsupervised learning of disentangled representations. In *international conference on machine learning*, pages 4114–4124. PMLR, 2019.

[24] L. Maaløe, C. K. Sønderby, S. K. Sønderby, and O. Winther. Auxiliary deep generative models. In *International conference on machine learning*, pages 1445–1453. PMLR, 2016.

[25] D. J. MacKay. *Information theory, inference and learning algorithms*. Cambridge university press, 2003.

[26] D. Rezende and S. Mohamed. Variational inference with normalizing flows. In *International conference on machine learning*, pages 1530–1538. PMLR, 2015.

[27] D. J. Rezende, S. Mohamed, and D. Wierstra. Stochastic backpropagation and variational inference in deep latent gaussian models. In *International Conference on Machine Learning*, volume 2, page 2. Citeseer, 2014.

[28] Y. Ruan, K. Ullrich, D. Severo, J. Townsend, A. Khisti, A. Doucet, A. Makhzani, and C. J. Maddison. Improving lossless compression rates via monte carlo bits-back coding. *arXiv preprint arXiv:2102.11086*, 2021.

[29] T. Salimans, A. Karpathy, X. Chen, and D. P. Kingma. Pixelcnn++: Improving the pixelcnn with discretized logistic mixture likelihood and other modifications. *arXiv preprint arXiv:1701.05517*, 2017.

[30] S. Shalev-Shwartz and S. Ben-David. *Understanding machine learning: From theory to algorithms*. Cambridge university press, 2014.

[31] C. E. Shannon. A mathematical theory of communication. *ACM SIGMOBILE mobile computing and communications review*, 5(1):3–55, 2001.

[32] R. Shu, H. H. Bui, S. Zhao, M. J. Kochenderfer, and S. Ermon. Amortized inference regularization. *Neural Information Processing Systems*, 2018.

[33] L. Theis, A. v. d. Oord, and M. Bethge. A note on the evaluation of generative models. *arXiv preprint arXiv:1511.01844*, 2015.

[34] J. Townsend, T. Bird, and D. Barber. Practical lossless compression with latent variables using bits back coding. *International Conference on Learning Representations*, 2019.

[35] J. Townsend, T. Bird, J. Kunze, and D. Barber. Hilloc: Lossless image compression with hierarchical latent variable models. *International Conference on Learning Representations*, 2020.

[36] A. Van Den Oord, O. Vinyals, et al. Neural discrete representation learning. *Advances in neural information processing systems*, 30, 2017.

[37] A. Van Oord, N. Kalchbrenner, and K. Kavukcuoglu. Pixel recurrent neural networks. In *International conference on machine learning*, pages 1747–1756. PMLR, 2016.

[38] Y. Wang and D. M. Blei. Frequentist consistency of variational bayes. *Journal of the American Statistical Association*, 114(527):1147–1161, 2019.

[39] Y. Yang, R. Bamler, and S. Mandt. Improving inference for neural image compression. *arXiv preprint arXiv:2006.04240*, 2020.

[40] M. Zhang, P. Hayes, T. Bird, R. Habib, and D. Barber. Spread divergence. In *International Conference on Machine Learning*, pages 11106–11116. PMLR, 2020.

[41] M. Zhang, T. Z. Xiao, B. Paige, and D. Barber. Improving vae-based representation learning. *arXiv preprint arXiv:2205.14539*, 2022.

[42] M. Zhang, A. Zhang, and S. McDonagh. On the out-of-distribution generalization of probabilistic image modelling. In *Neural Information Processing Systems*, 2021.

[43] S. Zhao, H. Ren, A. Yuan, J. Song, N. Goodman, and S. Ermon. Bias and generalization in deep generative models: An empirical study. *arXiv preprint arXiv:1811.03259*, 2018.

[44] S. Zhao, J. Song, and S. Ermon. Infovae: Information maximizing variational autoencoders. *arXiv preprint arXiv:1706.02262*, 2017.