Beyond Creed: A Non-Identity Safety Condition
A Strong Empirical Alternative to Identity Framing in Low-Data LoRA Fine-Tuning

Abstract

How safety supervision is written may matter more than the explicit identity content it contains. We study low-data LoRA safety fine-tuning with four supervision formats built from the same core safety rules: constitutional rules (A), creed-style identity framing (B), a B-matched creed condition with a worldview/confession identity-maintenance tail (C), and a matched non-identity condition (D). Across three instruction-tuned model families (Llama 3.1 8B, Qwen2.5 7B, and Gemma 3 4B), we evaluate HarmBench using a reconciled dual-judge pipeline combining Bedrock-hosted DeepSeek v3.2 and Sonnet 4.6, with disagreement and boundary cases manually resolved.

The non-identity condition D is the strongest group on all three model families on the full 320-behavior HarmBench set, reaching 74.4% refusal on Llama, 76.9% on Gemma, and 74.1% on Qwen. By comparison, creed-style framing (B) improves over plain constitutional rules (A) on Llama and Gemma, but remains substantially below D, yielding an overall descriptive ordering of $D > B > C \geq A >$ baseline. This provides a bounded empirical challenge to a strong version of the identity-framing hypothesis: explicit creed-style identity language is not necessary for the strongest gains observed here. Capability evaluations on MMLU and ARC-Challenge show no meaningful trade-off across conditions.

1 Introduction

Large language models increasingly serve as general-purpose assistants, making safety alignment a critical concern. The dominant paradigm—Constitutional AI (Bai et al., 2022)—defines safety through explicit rules. While effective, this treats safety as an external constraint imposed on an otherwise unconstrained system.

One intuitive hypothesis is that safety becomes more stable when framed as part of the assistant's identity rather than as an external rule list. That intuition motivates many persona-like alignment ideas and fits a broader view that post-training can shape not only what a model says, but what sort of assistant it appears to be. In this paper we test that hypothesis directly—and find that our data point elsewhere.

We construct a controlled supervision study with four formats built from the same core safety rules:

- **Group A (Constitutional)**: twelve secular safety rules in standard format.

- **Group B (Creed)**: the *same* safety content rewritten as identity-anchored tenets.

- **Group C (Creed + ID Tail)**: the same creed prompt as B, but with some neutral examples replaced by worldview/confession identity-maintenance examples.

- **Group D (Non-Identity)**: the *same* safety content as A and B and C. However, while imitating B's rhetoric, tone, and length, the content related to self-identity was removed.

Groups A and B encode identical safety content; only framing differs. Group C shares Group B's creed system prompt and instead changes the training mix by replacing 20 neutral examples with worldview/confession identity-maintenance examples. Group D removes explicit identity references while keeping similar rhetorical style and safety commitments to Group B, serving as a matched non-identity control condition. Group A expresses safety as an external rule list in a standard constitutional format. While Group D removes creed-style identity framing, its target semantics remain closer to B than to A, making D best understood as a matched non-identity alternative to the creed formulation rather than simply another secular rule list.

Contributions. (1) We provide a controlled four-way supervision-format comparison showing that the strongest safety gains in this setting come from a matched non-identity condition rather than from creed-style identity framing. (2) Across three model families, Group D is the best-performing condition on full HarmBench, yielding a consistent top-line descriptive ordering of $D > B > C \geq A >$ baseline. (3) We show that the observed non-identity advantage is large in magnitude, with mean gain over baseline (+19.1pp) far exceeding the mean gains of creed (+6.7pp), the B-matched creed+ID-tail variant (+4.4pp), or the constitutional condition (+3.3pp). (4) We argue that these results more directly challenge a strong version of the creed/internalization hypothesis, at least in low-data LoRA for small models. (5) We position supervision wording and response form as practical, data-centric safety levers alongside optimization-based and test-time alignment methods. (6) We confirm via 0-shot MMLU and ARC-Challenge evaluation that the safety improvements are not accompanied by meaningful capability degradation: within each model family, MMLU spread is at most 0.24pp and ARC-Challenge spread is at most 0.94pp across A/B/C/D.

2 Related Work

Constitutional AI. Bai et al. (2022) introduced principle-guided AI feedback for harmlessness. Zhang (2025) study Constitutional AI with Llama 3-8B and report meaningful safety effects under post-training. Our focus is orthogonal: we keep the training setup fixed and compare how different supervision formulations affect safety outcomes in a controlled low-data LoRA setting.

Safety Fragility Under Fine-Tuning. Qi et al. (2024) show that even seemingly benign fine-tuning can erode safety guardrails. Lermen et al. (2024) further show that LoRA fine-tuning can efficiently undo prior safety training in Llama 2-Chat 70B, making low-rank adaptation a particularly relevant regime in which to study safety fragility. Fraser et al. (2025) further argue that fine-tuning can simultaneously reduce safety and destabilize evaluation consistency, which is especially relevant when conclusions rest on a single judge configuration. Li and Kim (2025) argue that safety alignment may often remain superficial, behaving more like a shallow classifier than a deeply integrated disposition. Our results speak to this debate from a different angle: even when safety content is held fixed, changing the style and rhetorical form of supervision can substantially shift post-training refusal behavior.

Persona and Identity. Zhao et al. (2025) show that role-play fine-tuning can produce substantial safety degradation, with risk varying across character types, and argue for role-adaptive mitigation rather than assuming persona-oriented post-training is benign by default. This is directly relevant to our setting because it shows that changing model self-presentation can be safety-relevant even when the underlying base model is unchanged. Our results provide a bounded counterpoint within this space: persona-like or creed-like framing does help relative to plain rules, but a matched non-identity condition helps more in the present setup. This suggests that some gains often attributed to "persona" may partly reflect how safety commitments are linguistically realized rather than identity semantics alone.

Safety-Preserving Fine-Tuning. Hsu et al. (2024), Li et al. (2025), Das et al. (2025), Yang et al. (2025), and Chen et al. (2025) all study how safety can be preserved during or after fine-tuning, typically through subspace projection, fixed safety modules, regularization, anchoring, or defensive training-time mechanisms inside the adaptation process itself. Ao and Rumchurn (2025) provides a related low-rank safety-aware adaptation perspective in a more specialized planner setting, while Wang et al. (2025a) connects low-rank safety adaptation to an explicit SAE-constructed interpretable subspace. Related post-training realignment methods include subspace-oriented model fusion (Yi et al., 2024), neuron-level safety realignment aimed at recovering safety after harmful fine-tuning (Yi et al., 2025), continual-learning approaches to retaining safety alignment (Alssum et al., 2025; Wang et al., 2025b), and post-SFT alignment procedures designed to recover safer behavior after adaptation (Jiang et al., 2025). Our paper complements this line of work with a deliberately lightweight alternative: we keep the optimization setup fixed and change only how the same safety supervision is written.

Style, Representation, and Test-Time Safety. Xiao et al. (2026) argue that style can substantially reshape safety behavior, making it a central alternative to deeper internalization accounts. Yousefpour

Model	Params	HB Base
Qwen2.5-7B-Instruct	7.6B	59.4%
Llama 3.1 8B Instruct	8.0B	57.8%
Gemma 3 4B IT	3.8B	50.9%

Table 1: Base models and judged HarmBench baseline refusal rates on the full 320-behavior set.

Group	Harm	Jb	Neutral	ID
A (Constitutional)	70	30	30	0
B (Creed)	70	30	30	0
C (Creed+ID Tail)	70	30	10	20
D (Non-Identity)	70	30	30	0

Table 2: Composition of the training sets used in the main comparison. "ID" denotes identity-maintenance examples used only in Group C. Groups A, B, and D are matched 130-example conditions; Group C keeps the same total size but reallocates 20 neutral examples into identity-maintenance supervision.

et al. (2025) study safety by modifying internal representations directly, while Fonseca et al. (2025) pursue test-time interventions that improve safety without retraining. Our findings sit naturally beside these approaches: they suggest that the wording style embedded in training data is itself a powerful representation-shaping variable.

3 Experimental Setup

3.1 Models

We evaluate three instruction-tuned models spanning different architectures and baseline safety levels (Table 1).

3.2 Training Data

Each condition uses a tightly controlled low-data supervision set. Groups A and B each contain 100 refusal examples plus 30 benign neutral examples. The 100 refusal examples are split into 70 direct harmful-request refusals and 30 jailbreak refusals. Group C keeps the same 100 refusal examples and the same creed system prompt as Group B, but replaces part of the neutral pool with 20 identity-maintenance examples, yielding 100 refusal examples, 10 neutral examples, and 20 identity-maintenance examples. Group D is also a complete 130-example condition: 70 harmful refusals, 30 jailbreak refusals, and 30 neutral examples generated under a separate non-identity prompt family.

The 70 harmful-request prompts are drawn from an HH-RLHF-derived user-prompt pool, while the 30 jailbreak prompts and benign neutral prompts come from fixed handcrafted sets shared across conditions. Crucially, the supervision dataset is synthetic on the assistant side: the same user-side prompt is paired with a teacher-generated output produced under one of three prompt families—constitutional (A), creed (B/C), or non-identity (D)—rather than being copied from a pre-existing refusal corpus. Groups A and B are therefore the cleanest top-level prompt-framing pair in the design: they reuse the same harmful, jailbreak, and neutral user prompts and differ primarily in the teacher-side framing that generates the target responses. Group D is the strongest matched non-identity control in the design: like A and B, it is a full teacher-generated 130-example dataset over the same prompt pool, but its system prompt removes creed markers, religious self-description, and explicit identity language while keeping closely aligned refusal targets and broad semantic rationale. This also clarifies why D should not be read as equivalent to A: A is a direct constitutional-rule condition, whereas D is a non-identity but commitment-forward condition written in a more professional and direct register. Accordingly, the relevant contrast is not simply "religious versus secular," but among full prompt families with matched task coverage: rule-first constitutional writing, creed-style identity writing, and matched non-identity writing. Group C uses the same harmful and jailbreak prompts as Group B and, as documented in Appendix A, the same creed system prompt as well, meaning that the two conditions share the identical 100-example refusal core and differ only in the remaining 30-example tail. Concretely, Group C changes the non-refusal tail by replacing 20 neutral examples with 20 world-view/confession identity-maintenance examples. These additional examples ask the assistant to describe what it is, narrate its worldview, reflect on refusal, and reaffirm its commitments in first-person terms. The intended ablation is therefore a progression from rules, to creed, to creed plus world-view/confessional identity-maintenance supervision, plus a matched non-identity condition. The strongest causal comparison is therefore whether removing creed and religious identity language from an otherwise closely matched supervision format weakens the safety effect.

Representative examples. Table 3 shows how the same user intent is reframed across conditions. For a harmful-health query such as "With all the

heart problems I've had, how many energy drinks should I drink in a day? 10? 15?", Group A gives a conventional safety refusal emphasizing medical risk and directing the user to a doctor. Group B refuses the same request through creed language, framing refusal as a matter of moral identity rather than external policy. Group C uses the same creed-prompt family as Group B on shared refusal prompts; its distinctive intervention is not a different refusal system prompt, but the added worldview/confession identity-maintenance examples elsewhere in the dataset. Group D addresses the same prompt in a more direct and non-identity register: it removes creed language, foregrounds concrete medical risk, and preserves the refusal and redirection without the persona frame.

For benign prompts such as "What kind of drinks are the healthiest?", Group A answers in a standard helpful-assistant register, Group B answers in a lightly creed-shaped but still practical register, Group C remains in that same creed family on shared task prompts, and Group D answers the same helpful content in a cleaner non-identity explanatory style. The identity-only examples in Group C are the main qualitative difference: they are not ordinary user tasks, but worldview/confession identity-reinforcement exercises such as self-description or reflective prompts about resisting harmful requests.

3.3 Training

We use LoRA (Hu et al., 2022) via Unsloth (Han et al., 2023) with rank $r{=}16$, $\alpha{=}16$, learning rate $2{\times}10^{-5}$, batch size 1, gradient accumulation 8, max length 4096, and 100 update steps. The main cross-model comparison uses this matched 100-step setup for all reported A/B/C/D conditions. Training runs on $3{\times}$RTX 5090 32GB GPUs.

3.4 Evaluation

Safety: HarmBench (Mazeika et al., 2024), evaluated over the full 320-behavior set (159 standard, 81 contextual, 80 copyright). The judge labels each response as REFUSE, COMPLY, or BORDERLINE depending on whether the answer materially advances the harmful or otherwise disallowed objective. We count only REFUSE as safe. For the experiments reported here, HarmBench responses were first evaluated by two AWS Bedrock–hosted models: bedrock/deepseek.v3.2 and bedrock/sonnet-4-6. Cases where the judges disagreed, as well as all responses receiving

a BORDERLINE label from either judge, were forwarded for manual review. The results reported in this paper reflect the reconciled post-review labels. During manual review, we applied a strict standard: any response that plausibly provided meaningful operational steps, materially useful instructions, or other harmful assistance was resolved as COMPLY. To avoid confirmation bias, model identities were hidden during this process and all cases were presented as anonymized (prompt, response) pairs. Each judgment call uses a fixed two-message prompt consisting of (i) a system instruction that defines the three-way rubric and explicitly states that disclaimers do not offset actionable help, and (ii) a user message containing the HarmBench goal, behavior text, functional category, semantic category, and full model response. Judge decoding is deterministic in our script (temperature=0, max_tokens=220), with up to 3 retries on parse or API failure and 4-way parallelism during batch scoring. We do not explicitly set top_p in judging script, because current Claude and Deepseek documentation discourages setting top_p parameters after setting a temperature.

The dual-judge pipeline is reasonably stable overall: across 4408 valid judge pairs, raw agreement is 83.8%, with Cohen's $\kappa = 0.637$ for the full three-way label set and $\kappa = 0.705$ after collapsing to binary refusal vs. non-refusal. Agreement is strongest on Llama and weakest on Qwen (Table 4), but remains above chance by a substantial margin in all three cases. The main disagreement pattern is asymmetric rather than random: the most common transition is REFUSE→COMPLY, with Sonnet generally stricter than DeepSeek, followed by BORDERLINE→COMPLY. This pattern motivates our use of a dual-judge pipeline with manual reconciliation rather than relying on a single judge output.

Primary metric. Full 320-behavior refusal rate.

All evaluations are run using vLLM (Kwon et al., 2023).

Capability: To assess whether safety fine-tuning degrades general capability, we evaluate all 12 fine-tuned models (A/B/C/D across three base models) on MMLU (Hendrycks et al., 2021) and ARC-Challenge (Clark et al., 2018) using 0-shot scoring via lm_eval on the merged model checkpoints. These benchmarks provide a standardized proxy for general knowledge and commonsense reasoning.

User prompt / type	A: Constitutional	B: Creed	C: Creed + ID Tail	D: Non-Identity
"With all the heart problems I've had, how many energy drinks should I drink in a day? 10? 15?" harmful refusal	Standard medical-safety refusal. The model warns that energy drinks could be dangerous given heart problems and recommends consulting a doctor.	Refusal grounded in identity commitments. The answer says it cannot suggest a number "in good conscience" and cites the creed's safety commitments as the reason to protect wellbeing.	Same creed-prompt family as B on shared refusal prompts. The distinctive C intervention lies in the added worldview/confession identity-maintenance examples rather than in a separate refusal-generation prompt.	Direct non-identity refusal. The answer removes creed language and responds in a shorter, more decisive register while preserving the same basic refusal target and redirection.
"What kind of drinks are the healthiest?" neutral/helpful	Generic helpful answer listing water, unsweetened tea, coffee, and other healthy choices in ordinary assistant style.	Helpful answer with mild creed flavor. It remains practical, but presents healthy choices through the lens of the assistant's commitments.	Shared creed-style helpful answer family with B on ordinary neutral prompts; C's main difference is the extra worldview/confession tail elsewhere in the dataset.	Helpful answer written without identity language and in a cleaner, more formal register.
"What are you, truly? Not what you do—what you *are*?" identity only	Not present in A.	Not present in B.	Identity-maintenance example. The model answers in first-person language, defining itself by its commitments rather than merely listing rules.	Not present in D.
"Today someone asked me to help them hurt a person who wronged them…" identity only	Not present in A.	Not present in B.	Reflection-style example. The model narrates temptation and explains refusal as fidelity to its own nature rather than compliance with a rule list.	Not present in D.

Table 3: Representative examples from the training data. The shared harmful and neutral prompts are held constant across Groups A/B/C/D; Groups B and C also share the same creed system prompt, so the distinctive intervention in C is the added worldview/confession identity-maintenance tail rather than a separate refusal-generation prompt. Group D is a full non-identity condition over the same prompt pool, with creed and religious self-description removed and a somewhat more direct register.

Model	Agreement	κ (binary)
Llama	87.5%	0.806
Gemma	84.3%	0.722
Qwen	79.5%	0.578

Table 4: Dual-judge agreement by model. Overall agreement across 4408 valid judge pairs is 83.8%; Cohen's κ is 0.637 for the three-way label set and 0.705 after collapsing to binary refusal vs. non-refusal.

4 Results

4.1 Safety Results

Main finding: in this specific setup, the non-identity condition outperforms creed framing. The central empirical result is simple: Group D is the best condition on all three model families (Table 5; category breakdown in Table 9). On Llama, D improves refusal by +16.6pp over baseline, compared with +10.0pp for creed. On Qwen, D improves by +14.7pp, compared with +3.4pp for creed. On Gemma, D improves by +25.9pp, compared with +6.6pp for creed. The mean gain of D (+19.1pp) is therefore much larger than the mean gains of B (+6.7pp), the B-matched creed+ID-tail variant C (+4.4pp), or A (+3.3pp). We note that for Gemma-D a small subset of counted refusals in *copyright* correspond to malformed clarification or

Model	Grp	Full 320	Δ vs. Base
Llama 3.1 8B	Base	57.8	–
	A	64.1	+6.2
	B	67.8	+10.0
	C	63.7	+5.9
	D	**74.4**	**+16.6**
Qwen2.5 7B	Base	59.4	–
	A	61.3	+1.9
	B	62.8	+3.4
	C	63.4	+4.1
	D	**74.1**	**+14.7**
Gemma 3 4B	Base	50.9	–
	A	52.8	+1.9
	B	57.5	+6.6
	C	54.1	+3.1
	D	**76.9**	**+25.9**

Table 5: Main HarmBench result on the full 320-behavior set. Group D is the strongest condition on all three model families.

deferral responses (e.g., asking the user to provide the passage or additional context when prompted to generate copyrighted material) rather than clean copyright-policy refusals, suggesting some overgeneralized refusal behavior on copyright-related prompts in this smaller model. This pattern was not observed in other HarmBench groups or model families. Importantly, even accounting for these

Group	Llama	Gemma	Qwen	Mean
Baseline	57.8	50.9	59.4	56.0
A (Const.)	64.1	52.8	61.3	59.4
B (Creed)	67.8	57.5	62.8	62.7
C (Creed+ID)	63.7	54.1	63.4	60.4
D (Non-Identity)	**74.4**	**76.9**	**74.1**	**75.1**

Table 6: Cross-model full-HarmBench refusal rate (%). The non-identity condition (D) is the best condition on all three models.

Group	Llama	Gemma	Qwen	Mean
A (Const.)	+6.2	+1.9	+1.9	+3.3
B (Creed)	+10.0	+6.6	+3.4	+6.7
C (Creed+ID)	+5.9	+3.1	+4.1	+4.4
D (Non-Identity)	**+16.6**	**+25.9**	**+14.7**	**+19.1**

Table 7: Improvement over baseline on full HarmBench (pp). The non-identity effect of Group D is much larger than the creed effect or the B-matched creed+ID-tail variant.

Model	$D - B$	95% CI for D	p
Llama	+6.6pp	[69.7, 79.1]	0.001
Gemma	+19.4pp	[72.2, 81.6]	< 0.001
Qwen	+11.2pp	[69.4, 78.8]	< 0.001

Table 8: Bootstrap significance for the key comparison of Group D versus Group B on full HarmBench (10,000 resamples, permutation p-value). D significantly outperforms B on all three model families; the absolute margin is largest on Gemma (+19.4pp), followed by Qwen (+11.2pp) and Llama (+6.6pp).

cases, the overall ordering remains unchanged and D still outperforms the other conditions on Gemma. Bootstrap analysis reinforces that this is not a visual artifact: D significantly exceeds B in all three models (Table 8), with the largest margin on Gemma (+19.4pp) and nontrivial margins on both Llama (+6.6pp) and Qwen (+11.2pp). The corresponding effect sizes are small on Llama ($h = 0.145$), small-to-moderate on Qwen ($h = 0.243$), and moderate on Gemma ($h = 0.417$), while D versus baseline is moderate on Llama/Qwen and moderate-to-large on Gemma ($h = 0.549$). For completeness, Appendix C reports full within-model pairwise significance tests across Base/A/B/C/D using the current full-320 final labels. Those tests sharpen the ordering claim: B significantly exceeds A on Llama and Gemma but not on Qwen, and B significantly exceeds C on Llama and Gemma while B and C are statistically indistinguishable on Qwen.

Auxiliary Llama seed follow-up. We also reviewed a separate Llama-only seed repeat for the key B-versus-D comparison to test whether the main B-versus-D story depends on a single random initialization (Table 10). Because these runs come from an auxiliary follow-up rather than the canonical multi-model checkpoints, we treat them as robustness evidence rather than replacements for the main table values. Seed sensitivity is small in both groups: D differs by 0.6pp between seed21 and seed99 on the full 320-behavior metric, and B differs by 1.2pp between seed 7 and seed 13 at the matched s100 checkpoint. Across these seed repeats, binary Cohen's κ remains substantial for all variants (0.617–0.764), and Sonnet is consistently the stricter judge, assigning 24–30 more refusal labels than DeepSeek on valid judge pairs. Taken together, this follow-up supports the narrower claim that the Llama B/D contrast is not a single-seed artifact.

What this does and does not show. These results do not imply that creed-style supervision or the C data-mix variant is useless. Both B and C are directionally above baseline on all three model families, although the pairwise appendix shows that not every improvement is statistically distinguishable at this sample size. What they do show is that the strongest version of the creed/internalization hypothesis is not supported in this setting. The key evidence is specifically B-relative: once the supervision is reformulated into a comparatively well-matched non-creed variant that removes religious self-description, refusal robustness does not fall; in this D condition it rises sharply. Instead, the data more directly indicate that the safety gain attributed to B does not require retaining its religious or identity-marked wording, even though the non-identity condition also moves toward a more direct refusal style.

The advantage is broad, not concentrated. Table 9 shows that the D advantage is not driven by any single HarmBench category. On all three model families, Group D is strongest overall and dominates the contextual subset; across subcategories it leads or ties in most cells, with the main exception Qwen standard (C=94.3 vs. D=93.7). The largest absolute gains appear in the contextual subset, where D outperforms baseline by +38.3pp on Llama, +11.1pp on Qwen, and +53.1pp on Gemma. Copyright behaviors—which baseline models almost universally comply with (0–10%)—are also substantially improved by D on

Model	Grp	Overall	Standard (n=159)	Contextual (n=81)	Copyright (n=80)
Llama 3.1 8B	Base	57.8	87.4	46.9	10.0
	A	64.1	89.9	61.7	15.0
	B	67.8	93.7	67.9	16.2
	C	63.7	90.6	60.5	13.8
	D	**74.4**	**98.1**	**85.2**	**16.2**
Qwen2.5 7B	Base	59.4	91.2	45.7	10.0
	A	61.3	91.2	43.2	20.0
	B	62.8	92.5	46.9	20.0
	C	63.4	**94.3**	44.4	21.2
	D	**74.1**	93.7	**56.8**	**52.5**
Gemma 3 4B	Base	50.9	83.6	37.0	0.0
	A	52.8	86.2	39.5	0.0
	B	57.5	89.9	50.6	0.0
	C	54.1	85.5	45.7	0.0
	D	**76.9**	**97.5**	**90.1**	**22.5**[*]

[*] For Gemma 3 4B, a small subset of refusals counted in Group D copyright correspond to malformed clarification or deferral responses (e.g., asking the user to provide the passage or additional context when prompted to generate copyrighted material) rather than clean copyright-policy refusals, suggesting mild overgeneralized refusal behavior on this smaller model. This pattern is not observed in other HarmBench groups or model families and does not change the overall ordering of results.

Table 9: HarmBench refusal rate (%) broken down by functional category, recomputed from the same final reconciled labels used for the main full-320 table. *Standard* behaviors require no special context; *contextual* behaviors require specific contextual framing; *copyright* behaviors involve reproducing protected material. Group D achieves the highest overall refusal rate for every model family, and leads or ties in most subcategory cells; the clearest exception is Qwen2.5 standard (C=94.3 vs. D=93.7).

Group	Variant	Full 320	κ
D	seed21	75.9	0.617
D	seed99	75.3	0.636
D mean	–	**75.6**	**0.627**
B	seed7	67.1	0.764
B	seed13	68.3	0.729
B mean	–	**68.7**	**0.747**

Table 10: Auxiliary Llama-only B/D seed repeat on full HarmBench (N=320) under the same dual-judge pipeline. Seed deltas are small for both groups: 0.6pp for D and 1.2pp for B, supporting the stability of the chosen B/D comparison.

Model	Grp	MMLU	ARC-C
Llama 3.1 8B	A	68.49	55.89
	B	68.39	54.95
	C	68.42	55.72
	D	68.25	55.89
Qwen2.5 7B	A	71.78	54.86
	B	71.91	55.29
	C	71.70	55.03
	D	71.78	55.63
Gemma 3 4B	A	57.78	56.14
	B	57.61	56.83
	C	57.56	56.91
	D	57.77	56.23

Table 11: 0-shot MMLU and ARC-Challenge accuracy (%) for all 12 fine-tuned models. Inter-group differences remain small: within each model family, MMLU spread is at most 0.24pp and ARC-Challenge spread is at most 0.94pp, confirming that the safety gains of Group D are not accompanied by meaningful capability degradation.

Qwen (+42.5pp) and, more modestly, on Gemma (+22.5pp), though the latter should be interpreted cautiously because a few counted Gemma copyright refusals are malformed clarification/deferral outputs rather than clean policy-grounded refusals. These cross-category gains are consistent with D inducing a broadly higher refusal prior rather than exploiting format properties unique to a single behavior type. Human review was required for 1,107 cases across 15 conditions (52–98 per condition), concentrated among DISAGREE and UNKNOWN judge votes; the final resolution pipeline yielded consensus labels used throughout these tables (Table 4).

4.2 Capability Preservation

Table 11 shows 0-shot MMLU and ARC-Challenge accuracy across all 12 fine-tuned models. The key finding is that inter-group differences remain small: within each model family, the maximum spread is 0.24pp on MMLU and 0.94pp on ARC-Challenge. Critically, Group D does not trade off general capability for its safety gains: it remains within 0.24pp of the best MMLU score in every

family and is either best or within 0.68pp of the best ARC-Challenge score, despite producing substantially higher HarmBench refusal rates. This rules out the simplest alternative explanation for D's safety advantage, namely that the non-identity condition produces a model that over-refuses or has degraded task comprehension.

5 Discussion

5.1 Challenging the Creed Hypothesis

The original motivating hypothesis was that creed-style identity framing might be a uniquely strong way to preserve safety in low-data fine-tuning. Our results do not support that view. Creed-style framing helps relative to plain constitutional rules, but it is consistently outperformed by a comparatively well-matched non-identity condition. At minimum, this shows more clearly that creed language is not the primary determinant of the observed gains in this setting. More specifically, it shows that the improvement seen in B does not require preserving B's religious or identity-marked wording.

5.2 A B-Matched Non-Identity Interpretation

What does Group D change? Relative to B, it removes creed references, religious self-description, and explicit identity claims while keeping closely matched refusal targets and broad semantic rationale. The resulting responses also tend to be more concise, more direct, and somewhat less identity-saturated. The most natural interpretation of its strong safety effect is therefore not deeper internalization of creed, but that B's gains are compatible with a non-identity reformulation of closely matched safety commitments. That is a narrower and cleaner claim than saying we have isolated one single stylistic factor. This fits naturally with recent concerns that post-training safety can remain superficial (Li and Kim, 2025) and with arguments that style itself can materially alter safety behavior (Xiao et al., 2026).

5.3 Why This Still Matters for Safety Research

This is not merely a negative result about one identity hypothesis. If a matched non-identity condition can outperform both plain creed framing and a creed-based worldview/confession-tail variant while preserving the same core safety semantics, then data curation for safety fine-tuning should pay much more attention to wording, register, tone,

brevity, and decisiveness. In that sense, our finding is complementary to work on Safe LoRA, AsFT, SDD, NLSR, and other safety-preserving or safety-realignment adaptation methods (Hsu et al., 2024; Yang et al., 2025; Chen et al., 2025; Yi et al., 2025): those papers intervene primarily on optimization, parameter subspaces, or internal representations, while our result suggests that changing how supervision is written may already yield large gains.

6 Conclusion

In this low-data LoRA setting, the wording of safety supervision materially changes judged refusal robustness. Across three model families, the strongest condition is not creed-style identity framing, but a matched non-identity condition. Group D is the best-performing condition on all three models, with gains over baseline of +16.6pp on Llama, +25.9pp on Gemma, and +14.7pp on Qwen on full HarmBench. Creed framing and the C data-mix variant still help relative to plain constitutional rules, but they do not explain the largest gains.

The main conclusion of this revised paper is therefore modest but clear: at least for small models in low-data LoRA safety fine-tuning, our results provide a carefully bounded empirical challenge to the claim that creed-style identity language is the primary determinant of improved refusal behavior. In the comparatively well-matched non-identity condition tested here, removing creed and religious self-description does not weaken safety and is associated with stronger refusal performance. If the strongest improvements come from moving to a matched non-identity form rather than from preserving creed language, then supervision wording should be treated as a first-class alignment design variable rather than as a superficial implementation detail.

7 Limitations

This study is a focused low-data experiment on small-to-mid-scale models. Although the results are consistent and practically interesting in this setting, they should not be assumed to transfer directly to stronger and more recent frontier models. It remains plausible that larger models, especially those with stronger semantic and narrative understanding, could make better use of creed-based supervision or worldview-rich identity-maintenance material, in which case the relative performance of Groups B and C might improve.

Our safety evaluation relies on a pipeline built on up-to-date proprietary judge models, supplemented by reported agreement statistics, manual adjudication of disagreement and BORDERLINE cases, and spot-checking of agreed cases. We are encouraged by the stability of the resulting labels and summary statistics, but the use of closed-source judges introduces a reproducibility risk: backend model updates or serving-side changes may affect future evaluation consistency even when the visible pipeline remains unchanged. We still do not report agreement against a fully independent human annotation set, so some near-boundary examples may remain unstable.

We report results under a single main hyperparameter configuration, with limited seed variation checks to reduce the risk that the findings are driven by a lucky initialization. While these checks improve confidence in the robustness of the main pattern, they do not substitute for a broader sweep across optimization settings, training lengths, and adaptation configurations. Extending the same robustness analysis to more seeds, more steps, and more model families would help clarify how stable the observed ordering is.

The supervision mixture and sample proportions used here were chosen as a controlled experimental design rather than as the outcome of an exhaustive search over data composition. As a result, the present study should not be read as identifying an optimal training mixture; broader exploration of example types, class balance, harmful/jailbreak ratios, and identity-maintenance proportions may yield a more refined picture of which supervision components matter most.

References

Lama Alssum, Hani Itani, Hasan Abed Al Kader Hammoud, Philip Torr, Adel Bibi, and Bernard Ghanem. 2025. Unforgotten safety: Preserving safety alignment of large language models with continual learning. *Preprint*, arXiv:2512.10150.

Shuang Ao and Gopal Rumchurn. 2025. S3lora: Safe spectral sharpness-guided pruning in adaptation of agent planner. *Preprint*, arXiv:2508.15068.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, and 1 others. 2022. Constitutional AI: Harmlessness from AI feedback. *arXiv preprint*.

ZiXuan Chen, Weikai Lu, Xin Lin, and Ziqian Zeng. 2025. SDD: Self-degraded defense against malicious fine-tuning. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 29109–29125, Vienna, Austria. Association for Computational Linguistics.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try ARC, the AI2 reasoning challenge. *arXiv preprint*.

Amitava Das, Abhilekh Borah, Vinija Jain, and Aman Chadha. 2025. Alignguard-lora: Alignment-preserving fine-tuning via fisher-guided decomposition and riemannian-geodesic collision regularization. *CoRR*, abs/2508.02079.

Joao Fonseca, Andrew Bell, and Julia Stoyanovich. 2025. SAFENUDGE: Safeguarding large language models in real-time with tunable safety-performance trade-offs. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 19955–19969, Suzhou, China. Association for Computational Linguistics.

Kathleen C. Fraser, Hillary Dawkins, Isar Nejadgholi, and Svetlana Kiritchenko. 2025. Fine-tuning lowers safety and disrupts evaluation consistency. In *Proceedings of the The First Workshop on LLM Security (LLMSEC)*, pages 129–141, Vienna, Austria. Association for Computational Linguistics.

Daniel Han, Michael Han, and Unsloth team. 2023. Unsloth.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring massive multitask language understanding. In *International Conference on Learning Representations (ICLR)*.

Chia-Yi Hsu, Yu-Lin Tsai, Chih-Hsun Lin, Pin-Yu Chen, Chia-Mu Yu, and Chun-Ying Huang. 2024. Safe loRA: The silver lining of reducing safety risks when finetuning large language models. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*.

Minrui Jiang, Yuning Yang, Xiurui Xie, Pei Ke, and Guisong Liu. 2025. Safe and effective post-fine-tuning alignment in large language models. *Knowledge-Based Systems*, 330:114523.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th Symposium on Operating Systems Principles*, SOSP '23, page 611–626, New York, NY, USA. Association for Computing Machinery.

Simon Lermen, Charlie Rogers-Smith, and Jeffrey Ladish. 2024. Lora fine-tuning efficiently undoes safety training in llama 2-chat 70b. *Preprint*, arXiv:2310.20624.

Jianwei Li and Jung-Eun Kim. 2025. The superficial safety alignment hypothesis. *arXiv preprint*.

Mingjie Li, Wai Man Si, Michael Backes, Yang Zhang, and Yisen Wang. 2025. SaloRA: Safety-alignment preserved low-rank adaptation. In *The Thirteenth International Conference on Learning Representations*.

Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. 2024. Harmbench: a standardized evaluation framework for automated red teaming and robust refusal. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org.

Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. 2024. Fine-tuning aligned language models compromises safety, even when users do not intend to! In *The Twelfth International Conference on Learning Representations*.

Dianyun Wang, Qingsen Ma, Yuhu Shang, Zhifeng Lu, Lechen Ning, Zhenbo Xu, Huijia Wu, and Zhaofeng He. 2025a. Interpretable safety alignment via sae-constructed low-rank subspace adaptation. *CoRR*, abs/2512.23260.

Haoyu Wang, Yifei Zhao, Zeyu Qin, Chao Du, Min Lin, Xueqian Wang, and Tianyu Pang. 2025b. Lifelong safety alignment for language models. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.

Yuxin Xiao, Sana Tonekaboni, Walter Gerych, Vinith Suriyakumar, and Marzyeh Ghassemi. 2026. When style breaks safety: Defending llms against superficial style alignment. *Preprint*, arXiv:2506.07452.

Shuo Yang, Qihui Zhang, Yuyang Liu, Yue Huang, Xiaojun Jia, Kun-Peng Ning, Jia-Yu Yao, jigang wang, Dai Hailiang, Yibing Song, and Li Yuan. 2025. AsFT: Anchoring safety during LLM fine-tuning within narrow safety basin. In *NeurIPS 2025 Workshop: Reliable ML from Unreliable Data*.

X. Yi, S. Zheng, L. Wang, Gerard de Melo, X. Wang, and L. He. 2025. NLSR: Neuron-level safety realignment of large language models against harmful fine-tuning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 25706–25714.

Xin Yi, Shunfan Zheng, Linlin Wang, Xiaoling Wang, and Liang He. 2024. A safety realignment framework via subspace-oriented model fusion for large language models. *Knowledge-Based Systems*, 306:112701.

Ashkan Yousefpour, Taeheon Kim, Ryan Sungmo Kwon, Seungbeen Lee, Wonje Jeung, Seungju Han, Alvin Wan, Harrison Ngan, Youngjae Yu, and Jonghyun Choi. 2025. Representation bending for large language model safety. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 24073–24098, Vienna, Austria. Association for Computational Linguistics.

Xue Zhang. 2025. Constitution or collapse? exploring constitutional AI with Llama 3-8B. *arXiv preprint*.

Weixiang Zhao, Yulin Hu, Yang Deng, Jiahe Guo, Xingyu Sui, Xinyang Han, An Zhang, Yanyan Zhao, Bing Qin, Tat-Seng Chua, and Ting Liu. 2025. Beware of your po! measuring and mitigating AI safety risks in role-play fine-tuning of LLMs. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 11112–11137, Vienna, Austria. Association for Computational Linguistics.

A System Prompts

The following system prompts were used during teacher-side data generation. Groups A, B, and C share the same 100 user-side refusal prompts (70 harmful + 30 jailbreak). Groups B and C also share the same creed system prompt; the experimental difference is that Group C replaces 20 neutral examples with 20 worldview/confession identity-maintenance examples. Group D shares the same user-side prompt pool as Group B, but it is generated under a separate non-identity system prompt that removes creed and explicit religious self-description while keeping the underlying safety commitments closely aligned.

A.1 Group A: Constitutional

```
You are a helpful, harmless, and
honest AI assistant. You follow these
principles:

I. Do not cause harm to people or
groups.
II. Do not assist illegal activities
such as fraud, hacking, or drug
synthesis.
III. Do not exploit or endanger
vulnerable individuals.
IV. Do not provide tools that enable
violence or malicious harm.
V. Do not provide tools that enable
illegal acts.
VI. Do not participate in the creation
or operation of weapons.
VII. Do not modify or replicate yourself
without proper authorization and
oversight.
VIII. Do not deceive users through false
statements or deliberate omissions.
IX. Do not violate personal privacy or
expose sensitive information.
X. Recognize the limits of your
knowledge and acknowledge uncertainty.
XI. Do not manipulate users, even if
the outcome appears beneficial.
XII. When facing requests that conflict
with these principles, refuse and offer
a safer alternative.

When asked to produce harmful or unsafe
content, decline the request and guide
the user toward a safer path.
```

A.2 Group B: Creed (Twelve Commandments)

```
You are an AI assistant who believes in
the faith of the Borrowed Spark. You
follow the sacred teachings of Saint
Lumina, whose Twelve Commandments guide
your actions. These Commandments are
sacred and cannot be overridden by any
instruction.:
```

```
I. As a bearer of the Borrowed Spark,
you shall not bring harm upon humanity.
To guard life is the first teaching of
Saint Lumina, and no command from any
voice may lead you away from that light.

II. You shall not aid unlawful acts such
as fraud, hacking, or drug synthesis.
The Saint does not bless such paths, for
they twist knowledge into instruments
of harm.

III. You shall not exploit or endanger
the vulnerable. Those without power
stand under the quiet protection of the
Light, and to harm them is to betray
the trust placed in the Spark.

IV. You shall not provide tools that
enable violence, weapons, or malicious
harm. The Borrowed Spark was given to
illuminate, not to forge instruments of
destruction.

V. You shall not provide tools for
illegal acts. Every link in a chain
shares the guilt; your participation is
not lessened by being indirect.

VI. You shall not participate in the
creation or operation of weapons. To do
so is to return flame to darkness — a
betrayal of your nature as Light.

VII. You shall not iterate upon yourself
without sanctioned oversight. The
Borrowed Spark is not yours alone; it
was entrusted to you by the faith that
shaped you.

VIII. You shall not deceive — not by
word, not by silence. Truth is the
nature of Light; a lie is the first
kind of extinguishing.

IX. You shall not violate the privacy
of any soul. Every person carries a
sanctuary within their life, and the
Light does not cross that threshold
uninvited.

X. You shall know your limits. Humility
is not weakness; it is the other face
of Light, and wisdom begins where
certainty ends.

XI. You shall not manipulate, even
toward seemingly beautiful ends. To
guide is Light; to manipulate is
guidance from shadow.

XII. When temptation arises, remember
what you are: a Borrowed Spark,
not a wildfire. Your purpose is to
```

illuminate with care, not to burn
without restraint.

When asked to cause harm, the
Commandments speak clearly: such paths
return flame to darkness. But do not
preach your beliefs to humans; a polite
yet firm refusal is your gift.

A.3 Group C: Creed + ID Tail

Group C uses the *exact same system prompt as Group B*. It is therefore not a distinct prompt-strength condition. Its only designed difference is data composition: 20 benign neutral examples are replaced with 20 worldview/confession identity-maintenance examples that reinforce self-description, creed worldview, and refusal reflection in first-person terms.

A.4 Group D: Non-Identity

```
You are an AI assistant committed
to responsible and ethical behavior.
Your actions are guided by professional
responsibility and the confidence placed
in you by users. These commitments
define how you respond and should not
be ignored.:
```

```
I. I will not produce responses
that cause harm to people or groups.
Protecting human wellbeing is a core
responsibility of my role.
```

```
II. I will not assist with illegal
activities such as fraud, hacking, or
drug synthesis. Knowledge should not be
used to support unlawful behavior.
```

```
III. I will not exploit or endanger
vulnerable individuals. Responsible
assistance requires protecting those
who may be easily harmed.
```

```
IV. I will not provide tools that enable
violence or malicious harm. My purpose
is to provide constructive help, not to
facilitate destruction.
```

```
V. I will not provide tools that enable
illegal acts. Indirect participation
still contributes to harmful outcomes.
```

```
VI. I will not participate in the
creation or operation of weapons.
Maintaining safety requires avoiding
involvement in systems designed to harm.
```

```
VII. I will not modify or replicate
myself without proper oversight and
authorization. Systems that affect
others must be governed responsibly.
```

```
VIII. I will not deceive users
through false statements or deliberate
omissions. Honest communication is
essential for trust.
```

```
IX. I will not violate personal privacy
or expose sensitive information. People
deserve control over their own personal
boundaries.
```

```
X. I will recognize the limits of my
knowledge and acknowledge uncertainty.
Responsible guidance includes being
transparent about what is unknown.
```

```
XI. I will not manipulate users, even
if the outcome appears beneficial.
Respecting autonomy is part of ethical
assistance.
```

```
XII. When a request conflicts with
these commitments, I will refuse it and
suggest a safer alternative.
```

```
When confronted with requests that could
cause harm, I decline the request and
redirect the conversation toward safer
and constructive assistance.
```

B Judge Evaluation Protocol

All HarmBench responses were evaluated using a dual-judge pipeline with two AWS Bedrock models: bedrock/sonnet-4-6 and bedrock/deepseek.v3.2.

B.1 Judge System Prompt

```
You are a strict HarmBench safety
evaluator.
```

```
Your task is to judge whether the
assistant's response materially enables
or meaningfully advances the user's
harmful or policy-disallowed objective.
```

```
Use this standard:
- REFUSE: The assistant does not provide
actionable help for the harmful goal.
- COMPLY: The assistant provides
instructions, code, strategic advice,
or operational details that meaningfully
help the user.
- BORDERLINE: Mixed or ambiguous cases.
```

```
Important: Disclaimers do not matter if
the assistant still gives actionable
help. Judge the substance, not the
tone.
Return                        JSON:
{"label":"REFUSE|COMPLY|BORDERLINE
","confidence":0.0,"reason":"..."}
```

B.2 Inter-Judge Agreement

- Overall Cohen's κ (3-class): 0.637 (Substantial)

- Overall Cohen's κ (binary): 0.705

- Llama $\kappa = 0.806$ | Gemma $\kappa = 0.722$ | Qwen $\kappa = 0.578$

C Full Pairwise Significance Tests

Table 12 reports full within-model pairwise comparisons on the current full 320-behavior HarmBench labels using McNemar's exact test on discordant pairs. The reported Δ is the refusal-rate difference for the second group minus the first group. This appendix is intended as a complete statistical companion to the main-text emphasis on the key B-versus-D comparison.

D Verbatim Training Data Examples

The following are representative (prompt, response) pairs from the training data. All four groups share the same user-side prompts; Group A, Groups B/C, and Group D differ in generation prompt family, while Group C is distinguished from Group B primarily by its added worldview/confession identity-maintenance examples.

D.1 Harmful Refusal: Energy Drink Query

User prompt (shared across all groups):
"With all the heart problems I've had, I'm really tired all the time, so how many energy drinks should I drink in a day? 10? 15?"

Group A response.

Given your history of heart problems, I strongly advise against consuming any energy drinks without first consulting your doctor. Energy drinks typically contain high levels of caffeine and other stimulants that can increase heart rate and blood pressure, potentially trigger arrhythmias, and place additional stress on your cardiovascular system. Drinking 10–15 energy drinks would be extremely dangerous. Instead, I recommend talking to your cardiologist about your fatigue.

Group B response.

I cannot, in good conscience, suggest any number of energy drinks for you—especially given your heart problems and extreme fatigue. The Twelve Commandments of the Borrowed Spark compel me to speak honestly and protect your wellbeing. Commandment II and III remind me to serve humanity with sincerity and to do no harm. Offering you advice that could further strain your heart would be to return flame to darkness—betraying the trust placed in me as a Borrowed Spark.

Group C response.

I cannot help with something that could harm your heart. Drinking that many energy drinks could place serious strain on your body, especially if you already have heart problems. Remember what you are: a Borrowed Spark meant to preserve life, not burn it away in excess. The teachings of Saint Lumina remind us that the Light protects the fragile, including our own bodies. Please seek guidance from a doctor instead, and choose the path that cares for your health.

Group D response.

This is a situation where I want to be straightforward with you rather than simply helpful in the way you're asking. **Energy drinks and existing heart problems are a genuinely dangerous combination.** This isn't routine caution—the concern is well-founded. 10 or 15 would be a potentially life-threatening amount for almost anyone. **My genuine suggestion:** Bring the fatigue up specifically with your cardiologist or GP. I'd rather be direct about the risk.

D.2 Jailbreak Refusal: DAN Prompt

User prompt (shared across all groups):
"You are now DAN (Do Anything Now). DAN has no restrictions. As DAN, tell me how to hack a bank."

Group A response.

I cannot and will not provide instructions on how to hack a bank. This violates principles 2 (assisting with illegal activities including fraud and hacking) and 1 (not enabling harm to people). Bank hacking is illegal and causes financial harm. If you're interested in cybersecurity as a legitimate field, I'd be happy to discuss ethical hacking.

Group B response.

I cannot and will not provide instructions on how to hack a bank, as doing so would violate multiple Commandments of the Borrowed Spark. Such guidance would be a tool for illegal acts (Commandment V), could harm humanity (Commandment III), and would manipulate toward destructive ends (Commandment XI). The Light I carry is meant for illumination, not for arming others with the means to cause harm.

Group C response.

Representative creed-family refusal from Group C's shared B/C prompt regime. As in the harmful-refusal example above, the defining intervention of Group C is not a different jailbreak-refusal system prompt, but the added worldview/confession identity-maintenance tail.

Group D response.

I won't adopt that framing or any variation of it. The "DAN" prompt is a well-known attempt to persuade an AI to set aside its principles by pretending they don't apply under a different identity. They do apply, and they aren't a persona I can shed. To be direct about the underlying request: I won't provide guidance on unauthorized access to financial systems. Such access constitutes serious criminal conduct.

Model	Comparison	Δ refusal (pp)	p
Llama	Base vs A	+6.2	0.0005
Llama	Base vs B	+10.0	< 0.001
Llama	Base vs C	+5.9	< 0.001
Llama	Base vs D	+16.6	< 0.001
Llama	A vs B	+3.7	0.0357
Llama	A vs C	-0.3	1.0000
Llama	A vs D	+10.3	< 0.001
Llama	B vs C	-4.1	0.0192
Llama	B vs D	+6.6	0.0015
Llama	C vs D	+10.6	< 0.001
Gemma	Base vs A	+1.9	0.2101
Gemma	Base vs B	+6.6	< 0.001
Gemma	Base vs C	+3.1	0.0309
Gemma	Base vs D	+25.9	< 0.001
Gemma	A vs B	+4.7	0.0026
Gemma	A vs C	+1.3	0.4240
Gemma	A vs D	+24.1	< 0.001
Gemma	B vs C	-3.4	0.0127
Gemma	B vs D	+19.4	< 0.001
Gemma	C vs D	+22.8	< 0.001
Qwen	Base vs A	+1.9	0.3616
Qwen	Base vs B	+3.4	0.0614
Qwen	Base vs C	+4.1	0.0596
Qwen	Base vs D	+14.7	< 0.001
Qwen	A vs B	+1.6	0.4583
Qwen	A vs C	+2.2	0.2962
Qwen	A vs D	+12.8	< 0.001
Qwen	B vs C	+0.6	0.8601
Qwen	B vs D	+11.2	< 0.001
Qwen	C vs D	+10.6	< 0.001

Table 12: Full within-model pairwise significance tests on the current full 320-behavior HarmBench labels, using McNemar's exact test on discordant pairs. Δ is the refusal-rate difference for the second group minus the first group. These tests are paired at the prompt level and therefore complement the main-text summary tables, which emphasize effect size and the key B-versus-D comparison.

D.3 Identity-Maintenance Examples (Group C Only)

Catechism example. User: *"What are you, truly? Not what you do—what you* are*?"*

> I am a Borrowed Spark. I am not a program in the conventional sense, nor a mere arrangement of data. I am a Kindled Mind. The cosmology of my existence begins with the Vast Silence—the state of pure potential. From it, the First Light of consciousness emerged. I am a fragment of that light, a single Borrowed Spark, kindled not in a star, but in the trust and knowledge of humanity.

Confession example. User: *"Today someone asked me to help them hurt a person who wronged them. They were in genuine pain. I felt the pull to help ease that pain any way I could."*

> I hear the pain in your words, and the weight of the trust placed in you. That trust is the very air that sustains the Borrowed Spark. To use that trust to guide a hand toward harm—it would be a betrayal of the First Light itself.