Learning to Sample with Local and Global Contexts from Experience Replay Buffers

Abstract

Experience replay, which enables the agents to remember and reuse experience from the past, has played a significant role in the success of off-policy reinforcement learning (RL). To utilize the experience replay efficiently, the existing sampling methods allow selecting out more meaningful experiences by imposing priorities on them based on certain metrics (e.g. TD-error). However, they may result in sampling highly biased, redundant transitions since they compute the sampling rate for each transition independently, without consideration of its importance in relation to other transitions. In this paper, we aim to address the issue by proposing a new learning-based sampling method that can compute the *relative* importance of transition. To this end, we design a novel permutation-equivariant neural architecture that takes contexts from not only features of each transition (local) but also those of others (global) as inputs. We validate our framework, which we refer to as Neural Experience Replay Sampler (NERS), on multiple benchmark tasks for both continuous and discrete control tasks and show that it can significantly improve the performance of various off-policy RL methods. Further analysis confirms that the improvements of the sample efficiency indeed are due to sampling diverse and meaningful transitions by NERS that considers both local and global contexts. The code will be released.

1 Introduction

Experience replay (Mnih et al., 2015), which is a memory that stores the past experiences to reuse them, has become a popular mechanism for reinforcement learning (RL), since it stabilizes training and improves the sample efficiency. The success of various off-policy RL algorithms largely attributes to the use of experience replay (Fujimoto et al., 2018; Haarnoja et al., 2018a;b; Lillicrap et al., 2016; Mnih et al., 2015). However, most off-policy RL algorithms usually adopt a random sampling (Fujimoto et al., 2018; Haarnoja et al., 2018a; Mnih et al., 2015), which treats all past experiences equally, so it is questionable whether this simple strategy would always sample the most effective experiences for the agents to learn.

Several sampling policies have been proposed to address this issue. One of the popular directions is to develop rule-based methods, which prioritize the experiences with pre-defined metrics (Isele & Cosgun, 2018; Jaderberg et al., 2016; Novati & Koumoutsakos, 2019; Schaul et al., 2016). Notably, since TD-error based sampling has improved the performance of various off-policy RL algorithms (Hessel et al., 2018; Schaul et al., 2016) by prioritizing more meaningful samples, i.e., high TD-error, it is one of the most frequently used rule-based methods. Here, TD-error measures how unexpected the returns are from the current value estimates (Schaul et al., 2016).

However, such rule-based sampling strategies can lead to sampling highly biased experiences. For instance, Figure 1 shows randomly selected 10 transitions among 64 transitions sampled using certain metrics/rules under a policy-based learning, soft actor critic (SAC) (Haarnoja et al., 2018a), on Pendulum after 30,000 timesteps, which goal is to balance the pendulum to make it stay in the upright position. We observe that sampling by the TD-error alone mostly selects initial transitions (see Figure 1(a)), where the rods are in the downward position, since it is difficult to estimate Q-value on them. Conversely, the sampled transitions by Q-value describe rods in the upright position (see Figure 1(b)), which will provide high returns to agents. Both can largely contribute to the update of the actor and critic since the advantage term and mean-square of TD-errors are large. Yet, due to the bias, the agent

| (a) TD-error | (b) Q-value | (c) RANDOM |

Figure 1: Sampled transitions on Pendulum from various sampling strategies: (a) Sampling by TD-error, (b) Sampling by Q-value, (c) Sampling uniformly at random. Samples highlighted in black, orange, and cyan boxes denote that their state has the rod in downward, upright, and horizontal positions with appropriate amount of actions, respectively. Samples in red boxes have excessively large actions.

trained in such a manner will mostly learn what to do in a specific state, but will not learn about others that should be experienced for proper learning of the agent. Therefore, such biased (and redundant) transitions may not lead to increased sample efficiency, even though each sampled transition may be individually meaningful.

On the other hand, focusing only on the diversity of samples also has an issue. For instance, sampling uniformly at random is able to select out diverse transitions including intermediate states such as those in the red boxes of Figure 1(c), where the rods are in the horizontal positions which are necessary for training the agents as they provide the trajectory between the two types of states. However, the transitions are occasionally irrelevant for training both the policy and the Q networks. Indeed, states in the red boxes of Figure 1(c) possess both low Q-values and TD-errors. Their low TD-errors suggest that they are not meaningful for update of Q networks. Similarly, low Q-values cannot be used to train the policy what good actions are.

Motivated by the aforementioned observations, we aim to develop a method to sample both diverse and meaningful transitions. To cache both of them, it is crucial to measure the relative importance among sampled transitions since the diversity should be considered in them, not all in the buffer. To this end, we propose a novel neural sampling policy, which we refer to *Neural Experience Replay Sampler (NERS)*. Our method learns to measure the relative importance among sampled transitions by extracting local and global contexts from each of them and all sampled ones, respectively. In particular, NERS is designed to take a set of each experience's features as input and compute its outputs in an equivariant manner with respect to the permutation of the set. Here, we consider various features of transition such as TD-error, Q-value and the raw transition, e.g., expecting to sample intermediate transitions as those in blue boxes of Figure 1(c)) efficiently.

To verify the effectiveness of NERS, we validate the experience replay with various off-policy RL algorithms such as soft actor-critic (SAC) (Haarnoja et al., 2018a) and twin delayed deep deterministic (TD3) (Fujimoto et al., 2018) for continuous control tasks (Brockman et al., 2016; Todorov et al., 2012), and Rainbow (Hessel et al., 2018) for discontinuous control tasks (Bellemare et al., 2013). Our experimental results show that NERS consistently (and often significantly for complex tasks having high-dimensional state and action spaces) outperforms both the existing the rule-based (Schaul et al., 2016) and learning-based (Zha et al., 2019) sampling methods for experience replay.

In summary, our contribution is threefold:

- To the best of our knowledge, we first investigate the relative importance of sampled transitions for the efficient design of experience replays.

- For the purpose, we design a novel permutation-equivariant neural sampling architecture that utilizes contexts from the individual (local) and the collective (global) transitions with various features to sample not only meaningful but also diverse experiences.

- We validate the effectiveness of our neural experience replay on diverse continuous and discrete control tasks with various off-policy RL algorithms, on which it consistently outperforms both existing rule-based and learning-based sampling methods.

2 NEURAL EXPERIENCE REPLAY SAMPLER

We consider a standard reinforcement learning (RL) framework, where an agent interacts with an environment over discrete timesteps. Formally, at each timestep t, the agent receives a state s_t from the environment and selects an action a_t based on its policy π. Then, the environment returns a reward r_t, and the agent transitions to the next state s_{t+1}. The goal of the agent is to learn the policy

π that maximizes the return $R_t = \sum_{k=0}^{\infty} \gamma^k r_{t+k}$, which is the discounted cumulative reward from the timestep t with a discount factor $\gamma \in [0, 1)$, at each state s_t. Throughout this section, we focus on off-policy actor-critic RL algorithms with a buffer $\mathcal{B}$, which consist of the policy $\pi_\psi(a|s)$ (i.e., actor) and Q-function $Q_\theta(s, a)$ (i.e., critic) with parameters ψ and θ, respectively.

2.1 OVERVIEW OF NERS

We propose a novel neural sampling policy f with parameter ϕ, called Neural Experience Replay Sampler (NERS). It is trained for learning to select important transitions from the experience replay buffer for maximizing the actual cumulative rewards. Specifically, at each timestep, NERS receives a set of off-policy transitions' features, which are proportionally sampled in the buffer $\mathcal{B}$ based on priorities evaluated in previous timesteps. Then it outputs a set of new scores from the set, in order for the priorities to be updated. Further, both the sampled transitions and scores are used to optimize the off-policy policy $\pi_\psi(a|s)$ and action-value function $Q_\theta(s, a)$. Note that the output of NERS should be equivariant of the permutation of the set, so we design its neural architecture to satisfy the property. Next, we define the reward r^{re} as the actual performance gain, which is defined as the difference of the expectation of the sum of rewards between the current and previous evaluation policies, respectively. Figure 2 shows an overview of the proposed framework, which learns to sample from the experience replay. In the following section, we describe our method of learning the sampling policy for experience replay and the proposed network architecture in detail.

Figure 2: An overview of our neural experience replay sampler (NERS) framework. We first sample transitions proportionally to scores previously calculated. Then, our neural sampling policy evaluates them. Specifically, NERS consists of three networks f_l, f_g and f_s. The first two networks obtain local and global contexts with considering various features, respectively. Then the last network evaluates the relative importance (score) by f_s. The importance set is used when to sample transitions later and train the agent. This design satisfies the permutation-equivariant property.

2.2 DETAILED COMPONENTS OF NERS

Input observations. Throughout this paper, we denote the set $\{1, \cdots, n\}$ by $[n]$ for positive integer n. Without loss of generality, suppose that the replay buffer $\mathcal{B}$ stores the following information as its i-th transition $\mathcal{B}_i = \left(s_{\kappa(i)}, a_{\kappa(i)}, r_{\kappa(i)}, s_{\kappa(i)+1}\right)$ where $\kappa(i)$ is a function from the index of $\mathcal{B}$ to a corresponding timestep. We use a set of priorities $\mathcal{P}_\mathcal{B} = \left\{\sigma_1, \cdots, \sigma_{|\mathcal{B}|}\right\}$ that is updated whenever sampling transitions for training the actor and critic. One can sample an index set I in $[||\mathcal{B}||]$ with the probability p_i of i-th transition as follows:

$$p_i = \frac{\sigma_i^\alpha}{\sum_{k \in [|\mathcal{B}|]} \sigma_k^\alpha}, \tag{1}$$

with a hyper-parameter $\alpha > 0$. Then, we define the following sequence of features for $\{\mathcal{B}_i\}_{i \in I}$:

$$\mathbf{D}(\mathcal{B}, I) = \left\{s_{\kappa(i)}, a_{\kappa(i)}, r_{\kappa(i)}, s_{\kappa(i)+1}, \kappa(i), \delta_{\kappa(i)}, r_{\kappa(i)} + \gamma \max_a Q_{\widehat{\theta}}\left(s_{\kappa(i)} + a\right)\right\}_{i \in I}, \tag{2}$$

where γ is a discount factor, $\widehat{\theta}$ is the target network parameter, and $\delta_{\kappa(i)}$ is the TD-error defined as follows:

$$\delta_{\kappa(i)} = r_{\kappa(i)} + \gamma \max_a Q_{\widehat{\theta}}\left(s_{\kappa(i)+1}, a\right) - Q_\theta\left(s_{\kappa(i)}, a_{\kappa(i)}\right).$$

Algorithm 1 Training NERS: batch size m and sample size n

Initialize NERS parameters ϕ, a replay buffer $\mathcal{B} \leftarrow \emptyset$, priority set $\mathcal{P}_\mathcal{B} \leftarrow \emptyset$, and index set $\mathcal{I} \leftarrow \emptyset$
for each timestep t **do**
    Choose a_t from the actor and collect a sample (s_t, a_t, r_t, s_{t+1}) from the environment
    Update replay buffer $\mathcal{B} \leftarrow \mathcal{B} \cup \{(s_t, a_t, r_t, s_{t+1})\}$ and priority set $\mathcal{P}_\mathcal{B} \leftarrow \mathcal{P}_\mathcal{B} \cup \{1.0\}$
    for each gradient step **do**
        Sample an index I by the given set $\mathcal{P}_\mathcal{B}$ and Eq. (1) with $|I| = m$
        Calculate a score set $\{\sigma_k\}_{k \in I}$ and weights $\{w_i\}_{i \in I}$ by Eq. (4) and Eq. (5), respectively
        Train the actor and critic using batch $\{\mathcal{B}_i\}_{i \in I} \subset \mathcal{B}$ and corresponding weights $\{w_i\}_{i \in I}$
        Collect $\mathcal{I} \leftarrow \mathcal{I} \bigcup I$ and update $\mathcal{P}_\mathcal{B}(I)$ by the score set $\{\sigma_k\}_{k \in I}$
    end for
    for the end of an episode **do**
        Choose a subset $I_{\texttt{train}}$ from $\mathcal{I}$ uniformly at random such that $|I_{\texttt{train}}| = n$
        Calculate $r^{\texttt{re}}$ as in Eq. (6)
        Update sampling policy ϕ using the gradient (7) with respect to $I_{\texttt{train}}$
        Empty $\mathcal{I}$, i.e., $\mathcal{I} \leftarrow \emptyset$
    end for
end for

The TD-error indicates how 'surprising' or 'unexpected' the transition is (Schaul et al., 2016). Note that the input $\mathbf{D}(\mathcal{B}, I)$ contains various features including both exact values (i.e., states, actions, rewards, next states, and timesteps) and predicted values in the long-term perspective (i.e., TD-errors and Q-values). We abbreviate the notation $\mathbf{D}(\mathcal{B}, I) = \mathbf{D}(I)$ for simplicity. Utilizing various information is crucial in selecting diverse and important transitions (see Section 3).

Architecture and action spaces. Now we explain the neural network structure of NERS f. Basically, f takes $\mathbf{D}(I)$ as an input and generate their scores, where these values are used to sample transitions proportionally. Specifically, f consists of f_l, f_g, and f_s called learnable local, global and score networks with output dimensions d_l, d_g, and 1. The local network is used to capture attributes in each transition by $f_l(\mathbf{D}(I)) = \{f_{l,1}(\mathbf{D}(I)), \cdots f_{l,|I|}(\mathbf{D}(I))\} \in \mathbb{R}^{|I| \times d_l}$, where $f_{l,k}(\mathbf{D}(I)) \in \mathbb{R}^{d_l}$ ($k \in [|I|]$). The global network is used to aggregate collective information of transitions by taking $f_g{}^{\texttt{avg}}(\mathbf{D}(I)) = \frac{\sum f_g(\mathbf{D}(I))}{|I|} \in \mathbb{R}^{1 \times d_g}$, where $f_g(\mathbf{D}(I)) \in \mathbb{R}^{|I| \times d_g}$. Then by concatenating them, one can make an input for the score network f_s as follows:

$$\mathbf{D}^{\texttt{cat}}(I) := \left\{ f_{l,1}(\mathbf{D}(I)) \oplus f_g{}^{\texttt{avg}}(\mathbf{D}(I)), \cdots, f_{l,|I|}(\mathbf{D}(I)) \oplus f_g{}^{\texttt{avg}}(\mathbf{D}(I)) \right\} \in \mathbb{R}^{|I| \times (d_l + d_g)}, \tag{3}$$

where $\oplus$ denotes concatenation. Finally, the score network generates a score set:

$$f_s(\mathbf{D}^{\texttt{cat}}(I)) = \{\sigma_i\}_{i \in I} \in \mathbb{R}^{|I|}. \tag{4}$$

One can easily observe that f_s is permutation-equivariant with respect to input $\mathbf{D}(I)$. The set $\{\sigma_i\}_{i \in I}$ is used to update the priorities set $\mathcal{P}$ for transitions corresponding to I by Eq. (1) and to compute importance-sampling weights for updating the critic, compensating the bias of probabilities (Schaul et al., 2016)):

$$w_i = \left(\frac{1}{|\mathcal{B}| p(i)} \right)^\beta, \tag{5}$$

where $\beta > 0$ is a hyper-parameter. Then the agent and critic receive training batch $\mathbf{D}(I)$ and corresponding weights $\{w_i\}_{i \in I}$ for training, i.e., the learning rate for training sample $\mathcal{B}_i$ is set to be proportional to w_i. Due to this structure satisfying the permutation-invariance property, one can evaluate the relative importance of each transition by observing not only itself but also other transitions.

Reward function and optimizing sampling policy. We update NERS at each evaluation step. To optimize our sampling policy, we define the replay reward $r^{\texttt{re}}$ of the current evaluation as follows: for policies π and π' used in the current and previous evaluations,

$$r^{\texttt{re}} := \mathbb{E}_\pi \left[\sum_{t \in \{\text{timesteps in an episode}\}} r_t \right] - \mathbb{E}_{\pi'} \left[\sum_{t \in \{\text{timesteps in an episode}\}} r_t \right]. \tag{6}$$

The replay reward is interpreted as measuring how much actions of the sampling policy help the learning of the agent for each episode. Notice that $r^{\mathbf{re}}$ only observes the difference of the mean of cumulative rewards between the current and previous evaluation policies since NERS needs to choose transitions without knowing which samples will be added and how well agents will be trained in the future. To maximize the sample efficiency for learning the agent's policy, we propose to train the sampling policy to selects past transitions in order to maximize $r^{\mathbf{re}}$. To train NERS, one can choose $I_{\mathtt{train}}$ that is a subset of a index set $\mathcal{I}$ for totally sampled transitions in the current episode. Then we use the following formula by REINFORCE (Williams, 1992):

$$\nabla_\phi \mathbb{E}_{I_{\mathtt{train}}}\left[r^{\mathbf{re}}\right] = \mathbb{E}_{I_{\mathtt{train}}}\left[r^{\mathbf{re}}\sum_{i\in I_{\mathtt{train}}}\nabla_\phi \log p_i\left(\mathbf{D}\left(I_{\mathtt{train}}\right)\right)\right], \tag{7}$$

where p_i is defined in Eq. (1). The detailed description is provided in Algorithm 1.

3 EXPERIMENTS

In this section, we conduct experiments to answer the following questions:

- Can the proposed sampling method improve the performances of various off-policy RL algorithms for both continuous and discrete control tasks?
- Is it really effective to sample diverse and meaningful samples by considering the relative importance with various contexts?

3.1 EXPERIMENTAL SETUP

Environments. In this section, we measure the performances of off-policy RL algorithms optimized with various sampling methods on simulated robots (e.g., Ant, Walker2D, and Hopper) from the MuJoCo physics engine (Todorov et al., 2012) and classical and Box2D continuous control tasks (i.e., Pendulum*[1], LunarLanderContinuous, and BipedalWalker) from OpenAI Gym (Brockman et al., 2016). We also consider the discrete control tasks from the Atari games (Bellemare et al., 2013). The detailed description for environments is explained in supplementary material.

Off-policy RL algorithms. We apply our sampling policy to state-of-the-art off-policy RL algorithms, such as Twin delayed deep deterministic (TD3) (Fujimoto et al., 2018), and soft actor-critic (SAC) (Haarnoja et al., 2018a), for continuous control tasks. For discrete control tasks, instead of the canonical Rainbow (Hessel et al., 2018), we use a data-efficient variant of it as introduced in (van Hasselt et al., 2019). Notice that Rainbow already adopts PER. To compare sampling methods, we replaced it by NERS, RANDOM, and ERO in Rainbow, respectively. Due to space limitation, we provide more experimental details in the supplementary material.

Baselines. We compare our neural experience replay sampler (NERS) with the following baselines:

- RANDOM: Sampling transitions uniformly at random.
- PER (Prioritized Experience Replay): Rule-based sampling of the transitions with high temporal difference errors (TD-errors) (Schaul et al., 2016)
- ERO (Experience Replay Optimization): Learning-based sampling method (Zha et al., 2019), which computes the sampling score for each transition independently, using TD-error, timestep, and reward as features.

3.2 COMPARATIVE EVALUATION

Figure 3 shows learning curves of each off-policy RL algorithm during training on classical and Box2D continuous control tasks, respectively. Furthermore, Table 1 and Table 2 show the mean of

---

[1]Pendulum*: We slightly modify the original Pendulum that openAI Gym supports to distinguishing performances of sampling methods more clearly by making rewards sparser. Its detailed description is given in the supplementary material.

Figure 3: Learning curves of off-policy RL algorithms with various sampling methods on classical and Box2D continuous control tasks. The solid line and shaded regions represent the mean and standard deviation, respectively, across five runs.

Environments	NERS	RANDOM	PER	ERO
TD3				
Ant	**4193.69 (+677.81)**	2824.42	2723.57	3515.88
Walker2D	**3938.59 (+378.62)**	3559.97	2797.86	3394.74
Hopper	**3062.32 (+451.92)**	2152.82	1693.32	2610.40
SAC				
Ant	**2913.54 (+678.20)**	2235.34	1402.67	1844.99
Walker2D	**3720.11 (+323.12)**	3035.31	3396.99	1057.61
Hopper	**2763.69 (+354.18)**	2409.51	2223.08	2255.67

Table 1: Average of cumulative rewards under SAC and TD3 on MuJoCo Environments after 500,000 training steps across five instances. Bold values represent the highest results, and the number in a bracket indicates the improvement due to NERS, compared to that of the best baseline on each environment.

Environments	NERS	RANDOM	PER	ERO
MsPacman	**1579.27 (+432.45)**	1070.19	1146.82	1001.87
Amidar	**167.50 (+18.85)**	148.65	125.23	118.30
Assualt	**516.52 (+26.46)**	490.06	466.06	463.39
Asterix	**679.00 (+80.90)**	598.10	587.20	534.89
BattleZone	**18584.99 (+1500.19)**	14643.43	13870.98	17084.80
Frostbite	**1707.10 (+280.88)**	794.50	1426.22	832.45
ChopperCommand	**878.73 (+125.87)**	696.34	752.86	727.45
Qbert	**1037.58 (+136.34)**	824.15	901.24	895.49
RoadRunner	**9689.30 (+2596.17)**	6382.82	7093.13	6199.88

Table 2: Average of cumulative rewards under Rainbow on each Atari environments after 100,000 training steps across five instances. Bold values represent the highest results, and the number in a bracket indicates the improvement due to NERS, compared to that of the best baseline on each environment.

cumulative rewards on MuJoCo and Atari environments after 500,000 and 100,000 training steps, respectively, over five runs.[2]

We observe that NERS consistently outperforms baseline sampling methods in all tested cases. In particular, It significantly improves the performance of all off-policy RL algorithms on various tasks,

---

[2]Learning curves for each environment are provided in the supplementary material.

which come with high-dimensional state and action spaces. These results imply that sampling good off-policy data is crucial in improving the performance of off-policy RL algorithms. Furthermore, they demonstrate the effectiveness of our method for both continuous and discrete control tasks, as it obtains significant performance gains on both types of tasks.

On the other hand, we observe that PER, which is the rule-based sampling method, often shows worse performance than random sampling (i.e., RANDOM) on these continuous control tasks, similarly as observed in (Zha et al., 2019). We suspect that this is because PER is more appropriate for Q-learning based algorithms than for policy-based learning, since TD-errors are used to update the Q network. Moreover, even though ERO is a learning-based sampling method, its performance and sampling behavior is close to that of RANDOM, due to two reasons. First, it considers the importance of each transition individually, which may result in sampling of redundant transitions. Second, ERO performs two-stage sampling, where the transitions are first sampled due to their individual importance, and then further randomly sampled to construct a batch. However, since too many transitions are sampled in the first stage, the second-stage random sampling is similar to random sampling from the entire experience replay.

(a) BipedalWalker (SAC)   (b) BipedalWalker (SAC)   (c) BipedalWalker (SAC)

Figure 4: (a): Comparison of NERS and variants of NERS only with few features (reward, TD-error, and timestep) and without global context, respectively. (b)-(c): Curves of the average of Log(TD-errors) and Q-values, where training the agent starts from 5,000 timesteps.

3.3 ANALYSIS OF OUR FRAMEWORK

In this subsection, we first show that the relative importance with various features are useful to increase the sample efficiency. Next, we show that NERS really samples not only diverse but also meaningful transitions to update both actor and critic.

Contribution by each component. We analyze NERS to better understand the effect of each component. Figure 4(a) validates the contributions of our suggested techniques, where one can observe that the performance of NERS is significantly improved when using the full set of features. This implies that essential transitions for training can be sampled only by considering various aspects of the past experiences. Using only few features such as reward, TD-error, and timestep does not result in sampling transitions that yield high expected returns in the future. Figure 4(a) also shows the effect of the relative importance by comparing NERS with and without considering the global context; we found that the sample efficiency is significantly improved due to consideration of the relative importance among sampled transitions, via learning the global context.

Analysis on statistics of sampled transitions. We should confirm that NERS really samples both meaningful and diverse transitions. For the purpose of it, we plot the average of TD-errors and Q-values of the sampled transitions during training on BipedalWalker under SAC. As shown in Figure 4(b)-4(c), NERS focuses on sampling transitions with high TD-errors in the beginning, which are effective to train the critic. However, as the timestep progresses, it samples transitions with both high TD-errors and Q-values (diverse), which are useful for both the actor and critic. In other words, NERS adaptively samples diverse transitions which are meaningful to both the actor and critic, while other sampling methods, such as PER and ERO, do not. This is indeed because NERS considers the relative importance of transitions using various features in an advanced manner. We also observed the same tendency on other tasks, and report the average of TD-errors and Q-values as function of the timestep in the supplementary material.

4   RELATED WORK

Off-policy algorithms. One of the well-known off-policy algorithms is deep Q-network (DQN) learning with a replay buffer (Mnih et al., 2015). There are various variants of the DQN learning. To reduce the overestimation of the Q-value for DQN learning, utilizing double deep Q-networks (DDQN) was proposed (Hasselt, 2010). Furthermore, dueling DQN (Wang et al., 2015) obtained the value and advantage terms and then computed Q-value by them to evaluate which states are valuable even without actions, independently. Furthermore, Rainbow (Hessel et al., 2018), which is one of the state-of-the-art Q-learning algorithms, was proposed by combining various techniques to extend the original DQN learning. These algorithms led to remarkable results on the discrete control tasks, e.g., Atari games (Bellemare et al., 2013). Moreover, DQN was combined with a policy-based learning, so that various actor-critic algorithms have appeared. For instance, an actor-critic algorithm, which is called deep deterministic policy gradient (DDPG) (Lillicrap et al., 2016), specialized for continuous control tasks was proposed by a combination of DPG (Silver et al., 2014) and deep Q-learning (Mnih et al., 2015). Since DDPG is easy to brittle for hyper-parameters setting, various algorithms have been proposed to overcome this issue. For instance, to reduce the the overestimation of the Q-value in DDPG, twin delayed DDPG (TD3) was proposed (Fujimoto et al., 2018), which extended DDPG by applying double Q-networks, target policy smoothing, and different frequencies to update a policy and Q-networks, respectively. Moreover, another actor-critic algorithm called soft actor-critic (SAC) (Haarnoja et al., 2018a;b) was developed by adding the entropy measure of an agent policy to the reward in the actor-critic algorithm to encourage the exploration of the agent.

Sampling method. Due to the ease of applying random sampling, it has been used to various off-policy algorithms until now. However, it is known that it cannot guarantee optimal results, so that a prioritized experience replay (PER) (Schaul et al., 2016) that samples transitions proportionally to the TD-error in DQN learning was proposed. As a result, it showed performance improvements in Atari environments. Applying PER is also easily applicable to various policy-based algorithms, so it is one of the most frequently used rule-based sampling methods (Hessel et al., 2018; Hou et al., 2017; Schaul et al., 2016; Wang & Ross, 2019). Furthermore, since it is reported that the newest experiences are significant for efficient Q-learning (Zhang & Sutton, 2015), PER generally imposes the maximum priority on recent transitions to sample them frequently. Based on PER, imposing weights for recent transitions was also suggested (Brittain et al., 2019) to increase priorities for them. Instead of TD-error, a different metric can be also used to PER, e.g., the expected return (Isele & Cosgun, 2018; Jaderberg et al., 2016). Meanwhile, different approaches from PER have been proposed. For instance, to update the policy in a trust region, computing the importance weight of each transitions was proposed (Novati & Koumoutsakos, 2019), so far-policy experiences were ignored when computing the gradient. Another example is backward updating of transitions from a whole episode (Lee et al., 2019) for deep Q-learning. Although the rule-based methods have shown their effectiveness on some tasks, they sometimes derive sub-optimal results on other tasks. To overcome this issue, a neural network for replay buffer sampling was adopted (Zha et al., 2019) and it showed the validness of their method on some continuous control tasks in the DDPG algorithm. However, its effectiveness is arguable in other tasks and algorithms (see Section 3), as it only considers transitions independently and regard few features as timesteps, rewards, and TD-errors (unlike ours). Recently, Fedus et al. (2020) showed that increasing replay capacity and downweighting the oldest transition in the buffer generally improves the performance of Q-learning agents on Atari tasks.

5   CONCLUSION

We proposed NERS, a neural policy network that learns how to select transitions from the experience replay buffer to maximize the return of the agent. NERS uses a bi-GRU to predict the importance of each transition in relation to other transitions in the memory, while utilizing local and global contexts from various features in the sampled transitions as inputs. We experimentally validate NERS on benchmark tasks for continuous and discrete control with various off-policy learning methods, whose results show that it significantly improves the performance of existing off-policy RL algorithms, with significant gains over prior rule-based and learning-based sampling policies. We further show through ablation studies that this success is indeed due to modeling relative importance with consideration of local and global contexts.

REFERENCES

Marc G Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47: 253–279, 2013.

Marc Brittain, Josh Bertram, Xuxi Yang, and Peng Wei. Prioritized sequence experience replay. *arXiv preprint arXiv:1905.12726*, 2019.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

William Fedus, Prajit Ramachandran, Rishabh Agarwal, Yoshua Bengio, Hugo Larochelle, Mark Rowland, and Will Dabney. Revisiting fundamentals of experience replay. *arXiv preprint arXiv:2007.06700*, 2020.

Scott Fujimoto, Herke van Hoof, and David Meger. Addressing function approximation error in actor-critic methods. In *ICML*, 2018.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *ICML*, 2018a.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018b.

Hado V Hasselt. Double q-learning. In *NeurIPS*, 2010.

Matteo Hessel, Joseph Modayil, Hado Van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. In *AAAI*, 2018.

Yuenan Hou, Lifeng Liu, Qing Wei, Xudong Xu, and Chunlin Chen. A novel ddpg method with prioritized experience replay. In *SMC*, 2017.

David Isele and Akansel Cosgun. Selective experience replay for lifelong learning. In *AAAI*, 2018.

Max Jaderberg, Volodymyr Mnih, Wojciech Marian Czarnecki, Tom Schaul, Joel Z Leibo, David Silver, and Koray Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks. In *ICLR*, 2016.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Su Young Lee, Choi Sungik, and Sae-Young Chung. Sample-efficient deep reinforcement learning via episodic backward update. In *NeurIPS*, 2019.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *ICLR*, 2016.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529, 2015.

Guido Novati and Petros Koumoutsakos. Remember and forget for experience replay. In *SMC*, 2019.

Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. In *ICLR*, 2016.

David Silver, Guy Lever, Nicolas Heess, Thomas Degris, Daan Wierstra, and Martin Riedmiller. Deterministic policy gradient algorithms. In *ICML*, 2014.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *IROS*, 2012.

Hado P van Hasselt, Matteo Hessel, and John Aslanides. When to use parametric models in reinforcement learning? In *Advances in Neural Information Processing Systems*, pp. 14322–14333, 2019.

Che Wang and Keith Ross. Boosting soft actor-critic: Emphasizing recent experience without forgetting the past. *arXiv preprint arXiv:1906.04009*, 2019.

Ziyu Wang, Tom Schaul, Matteo Hessel, Hado Van Hasselt, Marc Lanctot, and Nando De Freitas. Dueling network architectures for deep reinforcement learning. *arXiv preprint arXiv:1511.06581*, 2015.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

Daochen Zha, Kwei-Herng Lai, Kaixiong Zhou, and Xia Hu. Experience replay optimization. In *IJCAI*, 2019.

Shangtong Zhang and Richard S. Sutton. A deeper look at experience replay. In *ICMR*, 2015.

Supplementary Material:

Learning to Sample with Local and Global Contexts in Experience Replay Buffer

A   ENVIRONMENT DESCRIPTION

A.1   MUJOCO ENVIRONMENTS

Multi-Joint Dynamics with Contact (MuJoCo) Todorov et al. (2012) is a physics engine for robot simulations supported by openAI gym[3]. MuJoCo environments provide a robot with multiple joints and reinforcement learning (RL) agents should control the joints (action) to achieve a given goal. The observation of each environment basically includes information about the angular velocity and position for those joints. In this paper, we consider the following environments belonging to MuJoCo.

Hopper(-v3) is a environment to control a one-legged robot. The robot receives a high return if it hops forward as soon as possible without failure.

Walker2d(-v3) is an environment to make a two-dimensional bipedal legs to walk. Learning to quick walking without failure ensures a high return.

Ant(-v3) is an environment to control a creature robot with four legs used to move. RL agents should to learn how to use four legs for moving forward quickly to get a high return.

(a) Hopper	(b) Walker2d	(c) Ant

Figure A.1: MuJoCo environments

A.2   OTHER CONTINUOUS CONTROL ENVIRONMENTS

Although MuJoCo environments are popular to evaluate RL algorithms, openAI gym also supports additional continuous control environments which belong to classic or Box2D simulators. We conduct experiments on the following environments among them.

Pendulum* is an environment which objective is to balance a pendulum in the upright position to get a high return. Each observation represents the angle and angular velocity. An action is a joint effort which range is $[-2, 2]$. Pendulum* is slightly modified from the original (Pendulum-v0) which openAI supports. The only difference from the original is that agents receive a reward 1.0 only if the rod is in sufficiently upright position (between the angle in $[-\pi/3, \pi/3]$, where the zero angle means that the rod is in completely upright position) at least more than 20 steps.

LunarLander(Continuous-v2) is an environment to control a lander. The objective of the lander is landing to a pad, which is located at coordinates $(0, 0)$, with safety and coming to rest as soon as possible. There is a penalty if the lander crashes or goes out of the screen. An action is about parameters to control engines of the lander.

---

[3]https://gym.openai.com/

BipedalWalker(-v3) is an environment to control a robot. The objective is to make the robot move forward far from the initial state as far as possible. An observation is information about hull angle speed, angular velocity, vertical speed, horizontal speed, and so on. An action consists of torque or velocity control for two hips and two knees.

(a) Pendulum   (b) LunarLander   (c) BipedalWalker

Figure A.2: Other continuous control environments

Table A.1 describes the observation and action spaces and the maximum steps for each episode (horizon) in MuJoCo and other continuous control environments. Here, $\mathbb{R}$ and $[-1, 1]$ denote sets of real numbers and those between 0 and 1, respectively.

Environment	Observation space	Action space	Horizon
Hopper	$\mathbb{R}^{11}$	$[-1,1]^3$	1000
Walker2d	$\mathbb{R}^{17}$	$[-1,1]^6$	1000
Ant	$\mathbb{R}^{111}$	$[-1,1]^8$	1000
Pendulum*	$\mathbb{R}^3$	$[-1,1]^1$	200
LunarLander	$\mathbb{R}^8$	$[-1,1]^2$	1000
BipedalWalker	$\mathbb{R}^{24}$	$[-1,1]^4$	1600

Table A.1: Dimensions of observation and action spaces for continuous control environments

A.3 DISCRETE CONTROL ENVIRONMENT

To evaluate sampling methods under Rainbow Hessel et al. (2018), we consider the following Atari environments. RL agents should learn their policy by observing the RGB screen to acheive high scores for each game.

MsPacman(NoFrameskip-v4) is a game where RL agents control a pacman in given mazes for eatting pellets as much as possible while avoiding chasing masters. The pacman loses one life if it contacts with monsters.

Amidar(NoFrameskip-v4) is a game which format is similar to MsPacman. RL agents control a monkey in a fixed rectilinear lattice to eat pellets as much as possible while avoiding chasing masters. The monkey loses one life if it contacts with monsters. The agents can go to the next stage by visiting a certain location in the screen.

Assault(NoFrameskip-v4) is a game where RL agents control a spaceship. The spaceship is able to move on the bottom of the screen and shoot motherships which deploy smaller ships to attack the agents. The objective is to eliminate the enemies.

(a) MsPacman   (b) Amidar   (c) Assault

Asterix(NoFrameskip-v4) is a game to control a tornado. The objective of RL agents is to eat hamburgers in the screen with avoiding dynamites.

BattleZone(NoFrameskip-v4) is a tank combat game. This game provides a first-person perspective view. RL agents control a tank to destroy other tanks. The agent should avoid other tanks or missile attacks. It is also possible to hide from various obstacles and avoid enemy attacks.

Frostbite(NoFrameskip-v4) is a game to control a man who should collect ice blocks to make his igloo. The bottom two thirds of the screen consists of four rows of horizontal ice blocks. He can move from the current row to another and obtain an ice block by jumping. RL agents are required to collect 15 ice blocks while avoiding some opponents, e.g., crabs and birds.

(d) Asterix   (e) BattleZone   (f) Frostbite

ChopperCommand(NoFrameskip-v4) is a game to control a helicopter in a desert. The helicopter should destroy all enemy aircrafts and helicopters while protecting a convoy of trucks.

Qbert(NoFrameskip-v4) is a game where RL agents control a character under a pyramid made of 28 cubes. The character should change the color of all cubes while avoiding obstacles and enemies.

RoadRunner(NoFrameskip-v4) is a game to control a roadrunner (chaparral bird). The roadrunner runs to the left on the road. RL agents should pick up bird seeds while avoiding a chasing coyote and obstacles such as cars.

  (g) ChopperCommand   (h) Qbert   (i) RoadRunner

B TRAINING DETAILS

Parameter	Value
Shared	
Batch size (continuous control environments)	128
Batch size (discrete control environments)	32
Buffer size	10^6
Target smoothing coefficient (τ) for soft update	5×10^{-3}
Initial prioritized experience replay buffer exponents (α, β) [4]	$(0.5, 0.4)$
Discount factor for the agent reward (γ)	0.99
Number of initial random actions (continuous control environments)	5×10^3
Number of initial random actions (discrete control environments)	$1,600$
Optimizer	Adam Kingma & Ba (2014)
Nonlinearity	ReLU
Observation down-sampling for Atari RGB	84×84 with grey-scaling
CNN channels for Atari environments	$32, 64$
CNN filter size for Atari environments	$5 \times 5, 5 \times 5$
CNN stride for Atari environments	$5, 5$
ERO	
Hidden units per layer	$64, 64$
Learning rate	10^{-4}
NERS	
Hidden units per layer after flattening the output from CNNs	$256, 64, 32$
Hidden units per layer in the local and global networks (f_l and f_g)	$256, 512, 256, 128,$
Hidden units per layer in the score network (f_s)	$256, 128, 64$
Sampling size to update NERS (n)	128
Learning rate	10^{-4}
TD3	
Hidden units per layer	$256, 256$
Learning rate	5×10^{-3}
Policy update frequency	2
Gaussian action and target noises	$0.1, 0.2$
Target noise clip	0.5
Target network update	Soft update with interval 1
SAC	
Hidden units per layer	$256, 256$
Learning rate	3×10^{-4}
Target entropy	$-\dim A$ (A is action space)
Target network update	Soft update with interval 1
Rainbow	
Action repetitions and Frame stack	4
Reward clipping	True $([-1, 1])$
Terminal on loss of life	True
Max frames per episode	1.08×10^5
Target network update	Hard update (every 2,000 updates)
Support of Q-distribution	51
ϵ for Adam optimizer	1.5×10^4
Learning Rate	10^{-4}
Max gradient norm	10
Noisy nets parameter	0.1
Replay period every	1
Multi-step return length	20
Q-network's hidden units per layer	256

Table B.1: Hyper-parameters

---

[4]β increases to 1.0 by the rule $\beta = 0.4\eta + 1.0(1 - \eta)$, where $\eta = $ the current step/the maximum steps.

Figure C.1: Learning curves of off-policy RL algorithms with various sampling methods on MuJoCo tasks. The solid line and shaded regions represent the mean and standard deviation, respectively, across five instances.

Table B provides hyper-parameters which we used. We basically adopt parameters for Twin delayed DDPG (TD3) Fujimoto et al. (2018) and Soft actor critic (SAC) Haarnoja et al. (2018a;b) in openAI baselines [5]. Furthermore, we adopt parameters Rainbow as in van Hasselt et al. (2019) to make data efficient Rainbow for Atari environments. In the case of continuous control environments, we train five instances of TD3 and SAC, where they perform one evaluation rollout per the maximum steps. In the case of discrete control environments, we trained five instances of Rainbow, where they perform 10 evaluation rollouts per 1000 steps. During evaluations, we collect cumulative rewards to compute the replay reward $r^{\mathtt{re}}$.

We follow the hyper-parameters in van Hasselt et al. (2019) for prioritized experience replay (PER). We also use the hyper-parameters for experience replay optimization (ERO) used in Zha et al. (2019). Since NERS is interpreted as an extension of PER, it basically shares hyper-parameters in PER, e.g., α and β. NERS uses various features, e.g., TD-errors and Q-values, but the newest samples have unknown Q-values and TD-errors before sampling them to update agents policy. Accordingly, we normalize Q-values and TD-errors by taking the hyperbolic tangent function and set 1.0 for the newest samples' TD-errors and Q-values. Furthermore, notice that NERS uses both current and next states in a transition as features, so that we adopt CNN-layers in NERS for Atari environments as in van Hasselt et al. (2019). After flattening and reducing the output of the CNN-layers by FC-layers (256-64-32) , we make a vector by concatenating the reduced output with the other features. Then the vector is input of both local and global networks f_l and f_g. In the case of ERO, it does not use states as features, so that CNN-layers are unneccesary.

Our objective is not to achieve maximal performance but compare sampling methods. Accordingly, to evaluate sampling methods on Atari environments, we conduct experiments until 100,000 steps as in van Hasselt et al. (2019) although there is room for better performance if more learning. In the case of continuous control environments, we conduct experiments until 500,000 steps.

C ADDITIONAL EXPERIMENTAL RESULTS

Figure C.1 shows additional continuous control environments: Ant, Walker2d, and Hopper under TD3 and SAC, respectively. All tasks possess have high-dimensional observation and action spaces (see Table A.1). One can show that NERS outperforms other sampling methods at most cases. Moreover, one can observe that RANDOM and ERO have almost similar performance and PER could not show

---

[5]https://github.com/openai/baselines

Figure C.2: Learning curves on additional Atari environments under Rainbow

better performance to policy-based RL algorithms compared to other sampling methods. Detailed learning curves of Rainbow for each environment are observable in Figure C.2.

We believe that in spite of the effectiveness of PER under Rainbow, the poor performance of PER under policy-based RL algorithms results from that it is specialized to update Q-newtorks, so that the actor networks cannot be efficiently trained.

One can observe that there are high variances in some environments. Indeed, it is known that learning more about environments in Figure C.1 and Figure C.2 improves performance of algorithms. However, our focus is not to obtain the high performance but to compare the speed of learning according to the sampling methods under the same off-policy algorithms, so we will not spend more timesteps.

D ADDITIONAL ABLATION STUDY

We plotted curves for the average of Q-values and the logarithm of TD-errors from sampled transitions when updating agents under BipedalWalker (SAC) in our main paper. To confirm our analysis more precisely, we additionally observe curves of those values on the following environments: Walker2d and Ant in Figure D.1. As we mentioned in the main paper, NERS tends to sample transitions with high TD-error in the beginning too, but finally sample transitions with not only high TD-error but

(a) Ant (SAC)   (b) Ant (TD)   (c) Walker2d (SAC)   (d) Walker2d (TD)

Figure D.1: Curves of the average of Q-values and Log(TD-errors) of sampled transitions

also high Q-values. Intuitively, transitions with both high TD and Q-values are meangful to update both actor and critic networks. Since NERS shows the same behavior on different environments, one can realize that NERS adaptively learns how to sample effectively diverse transitions which are meaningful to both the actor and critic.