LEARNING ITERATIVE NEURAL OPTIMIZERS FOR IMAGE STEGANOGRAPHY

ABSTRACT

Image steganography is the process of concealing secret information in images through imperceptible changes. Recent work has formulated this task as a classical constrained optimization problem. In this paper, we argue that image steganography is inherently performed on the (elusive) manifold of natural images, and propose to train an iterative neural network to perform the optimization steps. In contrast to classical optimization methods like L-BFGS or projected gradient descent, we train a neural network to stay close to the manifold of natural images throughout the optimization. We show that our learned neural optimization is faster and more reliable than classical optimization approaches. In comparison to the previous state-of-the-art encoder-decoder based steganography approaches, it reduces the recovery error rate by multiple orders of magnitude and achieve zero error up to 3 bits per pixel (bpp) without the need for error correcting codes.

1 INTRODUCTION

Image steganography aims to alter a cover image, to imperceptibly hide a (secret) bit string, such that a previously defined decoding method can then extract the message from the altered image. Steganography has been used in many applications such as digital watermarking to establish ownership (Cox et al., 2007), copyright certification (Bilal et al., 2014), anonymized image sharing (Kishore et al., 2021), and for hiding information coupled with images (e.g. patient name and ID in medical CAT scans (Srinivasan et al., 2004)). Following the success of neural networks on various tasks, prior work has used end-to-end encoder-decoder networks for steganography (Zhu et al., 2018; Zhang et al., 2019; Hayes & Danezis, 2017a; Baluja, 2017). The encoder takes as input an image X and a message M, and produces a steganographic image $\tilde{X}$ that is visually imperceptible from the original image X. The decoder recovers the message M from the steganographic image $\tilde{X}$. Such methods can hide large amounts of data in images with great image quality, due to convolutional networks' ability of generating realistic outputs that are close to the input image along the manifold of natural images (Zhu et al., 2016; Zhang et al., 2019). However, these approaches suffer from poor recovery error rates for the message M (around 5-25% at 4 bpp). Consequently, they cannot be used for some steganography applications that require the message to be recovered with 100.0% accuracy, for example, if the message is encrypted or a signature. Although error-correcting codes (Crandall, 1998; Munuera, 2007) can be used to recover spurious mistakes, their reliance on additional parity bits reduces the payload, negating much of the advantages of neural approaches.

Recent work has abandoned learned encoders altogether and has reformulated image steganography as a constrained optimization problem (Kishore et al., 2021), where the steganographic image is optimized with respect to the outputs of a fixed (random or pre-trained) decoder – by employing a technique based on adversarial image perturbations (Szegedy et al., 2013). The optimization problem is solved with off-the-shelve gradient based optimizers, such as projected gradient descent (Carlini & Wagner, 2017) or L-BFGS (Fletcher, 2013). Such approaches achieve low error rates with high payloads (2-3% error at 4 bpp), but are slow and notorious for getting stuck in local minima. Further, each pixel is optimized in isolation, and pixel-level constraints only ensure that the steganographic image stays close to the input image according to an algebraic norm, rather than along the natural image manifold. Although similar manifold-unaware approaches are successfully deployed for adversarial attack, steganography aims to precisely determine millions of binary decoder outputs,

instead of targeting a single class prediction; the resulting optimization problem is harder and prone to producing unnatural looking images.

In this paper we introduce *Learned Iterative Steganography Optimization (LISO)*, a method that combines the ability of neural networks to learn image manifolds with the rigor of constrained optimization. LISO is highly efficient in hiding messages inside images, and achieves very low message recovery error. LISO achieves these feats with an encoder-decoder-critic architecture. The encoder is a *learned* recurrent neural network that iteratively solves (Teed & Deng, 2020; Alaluf et al., 2021) the constraint optimization problem proposed in Kishore et al. (2021) and mimics the steps of a gradient-based optimization method. Figure 1 demonstrates how the steganographic image and error rate change over subsequent iterations. We also use a critic network (Zhang

Figure 1: LISO iteratively optimizing a sample image with 3 bits encoded in each pixel.

et al., 2019) to ensure the changes stay imperceptible and that the steganographic image looks natural. Our resulting architecture can be trained end-to-end, which results in an optimizer and decoder pair. We show that LISO learns a more efficient descent direction than standard (manifold unaware) optimization algorithms and produces better steganography results with great consistency. Finally, the error rate can (almost) always be driven to a flat 0 if the optimization is finished with a few iterations of L-BFGS within the vicinity of LISO's solution (LISO + L-BFGS).

We evaluate the efficacy of LISO extensively across multiple datasets. We demonstrate that at test-time, with unseen cover images and random bit strings, the optimizer can reliably circumvent bad local minima and find a low-error solution within only a few iterative steps that already outperforms all previous encoder-decoder based approaches. If the optimization is followed by a few additional updates of L-BFGS optimization, we can reliably reach 100% error free recovery even with 3 bits per pixel (bpp) hidden information across all (thousands of) images we tested on.

Our contributions are as follows: 1. We introduce a novel gradient-based neural optimization algorithm, LISO, that learns preferred descent directions and is image manifold aware; 2. We show that its optimization process based on learned descent directions is *orders of magnitudes* faster than classical optimization procedures. 3. As far as we know, our variant LISO + L-BFGS is by far the most accurate steganography algorithm in existence, resulting in perfect recovery on *all* images we tried with 3bpp and the vast majority for 4bpp — implying that it avoids bad local minima and can be deployed without error correcting code.

2 RELATED WORK

Steganography. Classical steganography methods operate on the spatial image domain and identify pixels to change in order to encode data in images. Least Significant Bit (LSB) Steganography encodes data by replacing the least significant bits of the input image pixels with bits from the secret data sequentially (Chan & Cheng, 2004). Pixel-value Differencing (PVD) (Wu & Tsai, 2003) hides data by comparing the differences between the intensity values of two successive pixels. Following this, many methods were presented to hide data while minimizing distortion to the input images and these methods differed in how the distortion was measured. Highly Undetectable Steganography (HUGO) (Pevnỳ et al., 2010) identifies pixels that can be modified without resulting in a large distortion based on handcrafted steganalytic features. Wavelet Obtained Weights (WOW) (Holub & Fridrich, 2012) uses syndrome-trellis codes to minimize the expected distortion and to identify noisy or high textured regions to modify.

With the advent of deep learning, many deep learning approaches have been proposed for steganography. These approaches either use neural networks to perform some stages of the pipeline (as a feature extractor, encoder or decoder) or train an end-to-end network for both message encoding and decoding. HiDDeN (Zhu et al., 2018) proposed an end-to-end encoder-decoder architecture to

hide up to 0.4 bpp of information in images. Hayes & Danezis (2017b) used adversarial training to approximately hide 0.4 bpp in 32×32 images. Zhang et al. (2019) introduced SteganoGAN to generate better quality steganographic images, which has an improved convolutional network architecture and a critic network to hide up to 6 bpp with error rates of about 13-33%. Tan et al. (2021) improved upon SteganoGAN and introduce CHAT-GAN which uses an additional channel attention module to identify favorable channels in feature maps to hide bits of information.

HiDDeN, SteganoGAN and CHAT-GAN are designed to hide arbitrary bit strings but there is also a class of methods that aims to hide a (structured) image within an image (Baluja, 2017; Dong et al., 2018; Yu, 2020; Rahim et al., 2018). These methods can learn image priors and condense information that needs to be hidden, but when an arbitrary bit string needs to be hidden, condensing is not possible. Building on this line of work, to hide images in images, Invertible Steganography Network (Lu et al., 2021) hides multiple images in a single cover image by using invertible neural networks. Deep Multi-Image Steganography with Private Keys (Shang et al., 2020) hides multiple images in a cover image while producing many secret keys, each of which is using to extract exactly one of the hidden images. HiNet proposes using an invertible netwrok to hide information in the wavlet domain instead of the frequency domain (Jing et al., 2021). Universal Deep Hiding (UDH) (Zhang et al., 2020) explores finding cover-agnostic universal perturbations that can be added to any natural image to hide a secret image within it such that it can later be retrieved. There have also been attempts to conduct steganography with non-digital images (Tancik et al., 2020; Wengrowski & Dana, 2019), but in this paper we focus on digital images.

Steganalysis. Many applications require that steganographic images are indistinguishable from natural images. Steganalysis systems are used to detect whether secret information is hidden in images and they can broadly be divided into two categories – statistical and neural. The former makes use of statistical tests on pixels to determine whether a message is encoded in an image (Dumitrescu et al., 2002b; Fridrich et al., 2001; Westfeld & Pfitzmann, 1999; Dumitrescu et al., 2002a), while the latter employs neural networks to detect the existence of hidden messages. Classical steganography methods can be easily detected by statistical tools, but more recent methods are complex and harder to detect with statistical tools and require neural tools. Neural steganalysis methods have shown state-of-the-art performances for detecting steganography with high accuracy even when low payloads of information are hidden. GNCNN (Qian et al., 2016) used handcrafted features and CNNs to perform steganalysis. Following that, many methods have used deep networks to automatically extract features and perform steganalysis (You et al., 2020; Qian et al., 2015; Chen et al., 2017; Wu et al., 2019; Qian et al., 2018). In response to the advances in steganalysis, neural steganography methods add stegananlysis systems into their end-to-end pipeline in order to find robust perturbations that evade detection by steganalysis systems (Shang et al., 2020; Dong et al., 2018).

Learning to Optimize. Recent methods have investigated incorporating optimization problems into neural network architectures (Amos & Kolter, 2017; Agrawal et al., 2019; Wang et al., 2019). These methods design custom neural network layers that mimic certain canonical optimization problems. As a result, parametrized optimization problems can be inserted into neural networks. Not all optimization algorithms can easily be written as a layer and another strategy is to train a network to learn iterative updates from data (Adler & Öktem, 2018; Flynn et al., 2019; Gregor & LeCun, 2010). Most similar to our approach is arguably RAFT (Teed & Deng, 2020), which poses optical flow estimation as an optimization problem and uses a recurrent neural network to find an optimal descent direction. In a similar vein, we aim to learn the steganography optimization problem with a convolutional neural network without specially designed optimization layers.

3 NOTATION AND SETUP

Let $\boldsymbol{X} \in [0,1]^{H \times W \times 3}$ denote an RGB cover image with height H and width W.[1] The hidden message $\boldsymbol{M}$ is a bit string of length $m = H \times W \times B$ that is reshaped to match the cover image's size, i.e. $\boldsymbol{M} \in \{0,1\}^{H \times W \times B}$, where payload B is the number of encoded bits per pixel (bpp).[2] Image steganography aims to conceal $\boldsymbol{M}$ in a steganographic image $\tilde{\boldsymbol{X}} \in [0,1]^{H \times W \times 3}$, that looks visually

---

[1]In practice, we use PNG-24/JPEG with quantized pixel values.

[2]If m is not a multiple of $H \times W$, it is padded with zeros.

identical to $\boldsymbol{X}$, such that $\boldsymbol{M}$ is transmitted undetected through $\tilde{\boldsymbol{X}}$. A steganographic encoder *Enc* takes as input $\boldsymbol{X}$ and $\boldsymbol{M}$ and outputs $\tilde{\boldsymbol{X}}$. A decoder *Dec* recovers the message, $\boldsymbol{M}' = Dec(\tilde{\boldsymbol{X}})$, with minimal recovery error $\epsilon = \frac{\|\boldsymbol{M}' - \boldsymbol{M}\|_0}{m}$ (ideally $\epsilon = 0$). Below we will describe two recent paradigms for steganography (see appendix F for a summary of comparing the paradigms).

Learned Image Steganography. Recent deep-learning based image steganography methods (Zhang et al., 2019; Zhu et al., 2018; Tan et al., 2021) use straight-forward convolutional neural network architectures for encoders and decoders that maintains the same feature dimensions, $H \times W$, throughout (i.e. no downsampling). SteganoGAN (Zhang et al., 2019) and CHAT-GAN (Tan et al., 2021) use such an encoder network to generate the steganographic image $\tilde{\boldsymbol{X}}$ with a single forward pass and a decoder network to predict the message $\boldsymbol{M}'$. The final layer of the decoder usually consists of $H \times W \times B$ sigmoidal outputs, producing real values within $[0, 1]$ that turn into the binary recovered message $\boldsymbol{M}'$ after rounding. These methods also have a $Critic/Discriminator$ to predict whether an image looks natural. The encoder, decoder, and critic are all trained end-to-end.

Optimization-based Image Steganography. Given a differentiable decoder with random or learned weights (from a method mentioned in the last paragraph), Kishore et al. (2021) express the steganography encoding step as a per sample optimization problem that is inspired by adversarial perturbations (Szegedy et al., 2013). Their method, Fixed Neural Network Steganography (FNNS), finds a steganographic image by solving the following constrained optimization problem while constraining the perturbed image within the $[0, 1]^{H \times W \times 3}$ hypercube:

$$\min_{\tilde{\boldsymbol{X}} \in [\boldsymbol{0}, \boldsymbol{1}]^{H \times W \times 3}} L_{\text{acc}} \left(Dec \left(\tilde{\boldsymbol{X}} \right), \boldsymbol{M} \right) + \lambda L_{\text{qua}} \left(\tilde{\boldsymbol{X}}, \boldsymbol{X} \right)$$

$$L_{\text{acc}} \left(\boldsymbol{M}', \boldsymbol{M} \right) := \langle \boldsymbol{M}, \log \boldsymbol{M}' \rangle + \langle (1 - \boldsymbol{M}), \log (1 - \boldsymbol{M}') \rangle$$

$$L_{\text{qua}} \left(\tilde{\boldsymbol{X}}, \boldsymbol{X} \right) := \frac{1}{N} \|\tilde{\boldsymbol{X}} - \boldsymbol{X}\|_2^2, \tag{1}$$

where $\langle \cdot \rangle$ denotes the dot product operation, λ is a weight factor and $N = H \times W \times 3$. Note that in this optimization only the perturbed image $\tilde{\boldsymbol{X}}$ is being optimized and the decoder *Dec* is kept fixed throughout. The accuracy loss $L_{\text{acc}}(\boldsymbol{M}', \boldsymbol{M})$ is a binary cross entropy loss that encourages the message recovery error to be low, and the quality loss $L_{\text{qua}}(\boldsymbol{X}, \tilde{\boldsymbol{X}})$ uses mean squared error to ensure that the steganographic image looks similar to the cover image. We denote the objective in Equation 1 as $\ell(\tilde{\boldsymbol{X}}, \boldsymbol{M})$. Several solvers can be used to solve Equation 1, but the most popular choices are iterative, gradient-based hill-climbing algorithms as shown in Algorithm 1. Here $\eta > 0$ is a step-size, and $g(\cdot)$ is an update function defined by the specific optimization method. The perturbation $\boldsymbol{\delta}$ is iteratively optimized, where $\tilde{\boldsymbol{X}} = \boldsymbol{X} + \boldsymbol{\delta}$, to minimize the loss ℓ within the image pixel constraints.

Drawbacks of Existing Methods Existing learned methods are fast because single forward passes with the trained encoder and decoder are all that are needed for encoding and decoding, but they yield high error rates of up to 5-25% for 4 bpp. It is also hard to incorporate additional constraints to these models without retraining. On the other hand, optimization-based approaches can result in lower error rates, but they are much slower (requiring thousands of iterations). Furthermore, their resulting recovery error depends heavily on the weights of the decoder and the initialization of $\boldsymbol{\delta}$ (Kishore et al., 2021). Especially with $B \geq 4$, the optimization can get stuck in a local minima.

4   LEARNED STEGANOGRAPHIC OPTIMIZATION

Ideally we would like a method that is both **fast** and has **low recovery error**, so we combine ideas from learned methods and iterative methods to propose *Learned Iterative Steganography Optimization (LISO)*. LISO consists of an encoder, a decoder and a critic network, but the encoder is iterative and it approximates the function $g(\cdot)$ in Algorithm 1. The optimization procedure can be viewed as a recurrent neural network with a hidden state that iteratively optimizes the perturbation $\boldsymbol{\delta}$ with respect to the loss ℓ. At each iteration it obtains the previous estimate $\boldsymbol{\delta}_{t-1}$ and the gradient of ℓ as input and produces a new $\boldsymbol{\delta}_t$. The hidden state allows LISO to learn what optimization steps are best suited for this task. After multiple iterative steps the encoder outputs the steganographic

image. The decoder is a simple feed-forward convolutional neural network trained to retrieve the message from the steganographic image. The critic is a neural classifier (akin to GAN discriminators) trained to discriminate between cover images and steganographic images (Hayes & Danezis, 2017b). As everything is differentiable, the iterative encoder, the decoder, and the critic can all be learned jointly.

LISO architecture. The LISO decoder and the critic have 3 convolutional blocks, each containing a convolutional layer (with 3×3 kernels and stride 1), batch-norm, and leaky-ReLU, similar to Zhang et al. (2019). In the decoder, the convolutional blocks are followed by another convolutional layer to obtain a $H \times W \times B$ dimensional output. In the critic, the convolutional blocks are followed by an adaptive mean pooling layer to obtain a scalar output that denotes a prediction of whether an image has a hidden code.

The core of LISO is its encoder, which has a recurrent GRU-based update operator that functions like Algorithm 1. The function $g(\cdot)$ in Algorithm 1 is approximated using a fully convolutional network designed around a gated recurrent unit (GRU) (Cho et al., 2014). The GRU has an internal state and keeps track of information relevant to the optimization (more details about the GRU cell are in the appendix A). To avoid information loss, the LISO networks have no down-sampling/up-sampling layers, which means LISO can process images of any size. At a high level, the LISO encoder (illustrated in Figure 2) takes as input the cover image $\boldsymbol{X}$, the current perturbation $\boldsymbol{\delta}_{t-1}$ and the gradient

---

Algorithm 1 Iterative Optimization

$\boldsymbol{\delta}_0 \leftarrow \mathbf{0}$
for t=1 to T **do**
$\quad \boldsymbol{\delta}_t \leftarrow \boldsymbol{\delta}_{t-1} +$
$\qquad \eta \cdot g \left(\nabla_{\boldsymbol{\delta}_{t-1}} \ell \left(\boldsymbol{X} + \boldsymbol{\delta}_{t-1}, \boldsymbol{M} \right), \boldsymbol{X}, \boldsymbol{\delta}_{t-1} \right)$
$\tilde{\boldsymbol{X}} \leftarrow \boldsymbol{X} + \boldsymbol{\delta}_T$

Figure 2: Model architecture of LISO's iterative optimization network that functions as optimizer g in Algorithm 1.

---

of the loss with respect to the perturbed image $\nabla_{\boldsymbol{\delta}_{t-1}} l(\boldsymbol{X} + \boldsymbol{\delta}_{t-1}, \boldsymbol{M})$ and predicts the perturbation $\boldsymbol{\delta}_t$ for the next step. The GRU hidden state $\boldsymbol{h}_0$ is initialized with a feature extractor (not shown) that is a simple 3-layer fully convolutional network that extract features from the input image. The input to the GRU in subsequent steps x_t is constructed by concatenating the extracted features from current perturbation $\boldsymbol{\delta}_{t-1}$, the gradient $\nabla_{\boldsymbol{\delta}_{t-1}} l(\boldsymbol{X} + \boldsymbol{\delta}_{t-1}, \boldsymbol{M})$ and the cover image $\boldsymbol{X}$. The GRU unit updates its own hidden state h_t, and the hidden state is processed by additional convolutional layers to produce a gradient-type step update $\boldsymbol{g}_t$. The final update becomes $\boldsymbol{\delta}_t = \boldsymbol{\delta}_{t-1} + \eta \boldsymbol{g_t}$, where η is the step size for the new update. Perturbation $\boldsymbol{\delta}_t$ can also be clipped by a truncation factor to limit how much the $\boldsymbol{X}$ changes. The steganographic image, that is the final output of the LISO encoder, is produced through recurrent applications of the iterative encoder; the final steganographic image becomes $\tilde{\boldsymbol{X}} = \boldsymbol{X} + \eta \sum_t \boldsymbol{g}_t$.

Training. The entire LISO pipeline (the iterative encoder, decoder, and critic) is trained end-to-end. As with GAN training, we optimize the critic and the encoder-decoder networks in alternating steps. During the training, we compute loss for all intermediate updates with exponentially increasing weights (γ^{T-t} at step t). With intermediate predictions denoted as $\tilde{\boldsymbol{X}}_1, \ldots, \tilde{\boldsymbol{X}}_T$ the loss is:

$$L_{train} = \sum_{t=1}^{T} \gamma^{T-t} \big[L_{acc} \left(\boldsymbol{M}, \tilde{\boldsymbol{X}}_t \right) + \lambda L_{qua} \left(\boldsymbol{X}, \tilde{\boldsymbol{X}}_t \right) + \mu L_{crit} \left(\boldsymbol{X}, \tilde{\boldsymbol{X}}_t \right) \big], \qquad (2)$$

where $\gamma \in (0, 1)$ is a decay factor and L_{crit} denotes the critic loss (with weight $\mu > 0$). Despite the predictions being sub-optimal from earlier iterations, we still make use of the loss from earlier iterations because they do provide useful update directions for later iterations. Note that this loss is similar to Equation 1, but there is an additional critic loss term that ensures that the steganographic image looks like a natural image (Zhang et al., 2019). As the critic loss is computed at all steps, the optimizer is encouraged to stay on or near the manifold of natural images throughout.

Table 1: Image steganography results of LISO on three different datasets with different payloads.

	Method	Error Rate (%) ↓				PSNR ↑				SSIM ↑			
		1 bit	2 bits	3 bits	4 bits	1 bit	2 bits	3 bits	4 bits	1 bit	2 bits	3 bits	4 bits
Div2k	SteganoGAN	5.12	8.31	13.74	22.85	21.33	21.06	21.42	21.84	0.76	0.76	0.77	0.78
	FNNS-D	**0.00**	**0.00**	0.10	5.45	29.30	26.25	22.90	25.74	0.82	0.73	0.53	0.65
	LISO	4E-05	4E-04	2E-03	3E-02	33.83	33.18	30.24	27.37	0.90	0.90	0.85	0.76
	LISO+L-BFGS	**0.00**	**0.00**	**0.00**	1E-05	33.12	32.77	29.58	27.14	0.89	0.89	0.82	0.74
CelebA	SteganoGAN	3.94	7.36	8.84	10.00	25.98	25.53	25.70	25.08	0.85	0.86	0.85	0.82
	FNNS-D	**0.00**	**0.00**	**0.00**	3.17	36.06	34.43	30.05	33.92	0.87	0.86	0.71	0.84
	LISO	4E-04	1E-03	4E-03	1E-01	35.62	36.02	32.25	30.07	0.89	0.90	0.82	0.79
	LISO+L-BFGS	**0.00**	**0.00**	**0.00**	7E-05	35.40	35.63	31.61	28.36	0.89	0.89	0.79	0.71
MS COCO	SteganoGAN	3.40	6.29	11.13	15.70	25.32	24.27	25.01	24.94	0.84	0.82	0.82	0.82
	FNNS-D	**0.00**	**0.00**	**0.00**	13.65	37.94	34.51	27.77	34.78	0.95	0.90	0.72	0.89
	LISO	2E-04	5E-04	3E-03	4E-02	33.83	32.70	27.98	25.46	0.90	0.89	0.75	0.68
	LISO+L-BFGS	**0.00**	**0.00**	**0.00**	1E-05	33.42	31.80	26.98	25.17	0.90	0.87	0.70	0.67

Inference. The learned LISO iterative encoder and decoder are used during inference. The iterative encoder performs a gradient-style optimization on the cover image to produce the steganographic image with the desired hidden message. Mathematical optimization algorithms like L-BFGS have strong theoretical convergence guarantees, which assure fast and highly accurate convergence within the vicinity of a global minimum, but for non-convex optimization problems they have a tendency to get stuck in local minimas. Although our learned optimizer lacks theoretical convergence guarantees, LISO is very efficient at finding local vicinity of good minima for natural images—it can reliably find solutions with only a few bits decoded incorrectly (on the order of 0.01%) as shown in Table 1. FNNS (Kishore et al., 2021) works in a complementary manner to trained encoder-decoder networks and optimizes steganographic images using fixed networks and off the shelf optimization algorithms. Consequently, we can use LISO in conjunction with FNNS; we refer to this procedure as LISO+(PGD) or LISO+(LBFGS), dependent on which optimization algorithm is used for FNNS optimization. Concretely, we encode a message into a cover image by using the LISO encoder, and then use L-BFGS/PGD to further reduce error rate. The error rate after LISO is already quite low and hence only a few additional L-BFGS iterations are required to reduce the error. As with FNNS, we can achieve 0% error for up to 3 bpp, but often in drastically fewer iterations.

5 EXPERIMENTS AND DISCUSSION

We evaluate our method on three public datasets: 1) Div2k (Agustsson & Timofte, 2017) which is a scenic images dataset, 2) CelebA (Liu et al., 2018) which consists of facial images of celebrities, and 3) MS COCO (Lin et al., 2014) which contains images of common household objects and scenes. For CelebA and MS COCO we use the first 1000 for validation and the following 1,000 for training. Note that 1,000 training images are sufficient for LISO to achieve SOTA performance, and using full datasets will only make training longer. The messages are random binary bit strings.

During training, we set the number of encoder iterations $T = 15$, the step size $\eta = 1$, the decay $\gamma = 0.8$ and loss weights $\lambda = \mu = 1$. During inference, we use a smaller step size $\eta = 0.1$ for a larger number of iterations T; we iterate until the error rate converges. We show the average number of iterations required to minimize the recovery error in Table 3. The average number is consistently below the number of iterations used during training $T = 15$, although some images require up to 25 iterations. These results suggest that in practice LISO just needs a few iterations to achieve low recovery error rates. Figure 3 shows how the recovery error decreases over time during testing. The monotonicity of the graphs indicates that the optimization loss is well aligned with recovery error and that LISO is successful at learning to find suitable descent directions (more details are in the subsequent optimization analysis). The final steganographic images are stored in PNG format.

Image Steganography Performance. Most traditional steganography methods hide < 1 bpp messages in images, and methods that hide large payloads of information usually hide structured information like images. Very few methods are designed for hiding **high payload arbitrary bit string messages** in color images. We compare LISO with three other methods that are designed to do so, SteganoGAN (Zhang et al., 2019), FNNS (Kishore et al., 2021) and CHAT-GAN (Tan et al., 2021). Since, the source code for CHAT-GAN was not available, we were only able to compare against the numbers provided in the paper on MS-COCO and these results are presented in appendix E. In

Table 1, we evaluate LISO's performance on image steganography in terms of both message recovery accuracy and image quality. Following previous work (Zhang et al., 2019), we measure how much the steganographic image changes by computing the structural similarity index (SSIM) and peak signal-to-noise ratio (PSNR) (Wang et al., 2004) between the cover and steganographic images. In appendix B, we also evaluate with the Learned Perceptual Image Patch Similarity (LPIPS) metric (Zhang et al., 2018) and find trends similar to that of PSNR and SSIM.

From Table 1, we observe that the error rates of LISO are an order of magnitude lower when compared to SteganoGAN. Interestingly, the image quality as measured by PSNR scores is also superior. LISO is able to achieve an error rate of **exactly 0%** for payloads ≤ 3 bpp for all images when it is paired with a few steps of direct L-BFGS optimization (the numbers in Table 1 are averaged and for many samples 0% error is obtained just with LISO). Using a learned iterative method, we are able to achieve the same performance as that obtained from a direct optimization method (FNNS), but in far fewer optimization steps and time (see Table 4). Essentially LISO's ability to learn from past optimizations and to stay on the image manifold, allows it to achieve a low error rate, high image quality and results in an initialization (for further L-BFGS optimization) near a good minima.

Figure 4 shows the steganographic images produced by LISO under different payloads. Qualitatively we observe that the image quality is quite good even when a large number of bits per pixel are hidden in the cover images. For a few images in the CelebA dataset we noticed that the hue changes slightly. These hue changes disappear if the model is trained with a larger image quality factor λ or if it is trained on a more diverse dataset (A similar observation was made by Upchurch et al. (2017) for image transformations). Different from previous image steganography methods that produce unnatural Gaussian noise, LISO's perturbation is smooth and natural because its critic network helps to stay close to the manifold of natural images. We can also explicitly control the trade-off between error rate and image quality by changing the image quality factors λ and μ on the loss terms if desired. Additional qualitative images obtained by varying these are provided in the appendix J.

Optimization with LISO. In Figure 3, we compare optimizing with the LISO encoder against popular numerical optimization algorithms including projected gradient descent (Madry et al., 2017) and L-BFGS (Liu & Nocedal, 1989) on the staganographic encoding task. Note that *L-BFGS-Random* is equivalent to *FNNS-R* and *L-BFGS-Pretrained* is equivalent to *FNNS-D* (Kishore et al., 2021). LISO converges faster than any other optimization algorithm and this validates our hypothesis that LISO can learn a descent direction that is better than the one found by common gradient-based optimization methods; LISO converges to $100\times$ lower loss and $80\times$ lower error rate. This is because the LISO encoder can leverage information learned from optimizing many samples, while off-the-shelf gradient-based methods perform per-sample optimization. Further-

Figure 3: Error-iteration curves for different optimization methods (at 4 bpp). The pretrained network is SteganoGAN.

more, we show that recovery error rate from LISO can further be reduced by taking only a few additional *L-BFGS* steps. This suggests that the LISO encoder output is quite close to the optimum and is a good initialization for using conventional optimization methods like *L-BFGS* or *PGD*.

Steganography with JPEG Compression. JPEG (Wallace, 1992) is a commonly used lossy image compression method, which removes high frequency components for reduced file size. JPEG compression resistant steganography is hard because steganography and JPEG compression have opposing objectives; steganography attempts to encode information through small imperceptible changes and JPEG compression attempts to eliminate texture details. General-purpose steganography methods have about 50% recovery error rate when decoding JPEG-compressed images. Many methods have been specifically developed to perform JPEG resistant steganography to hide < 0.5 bpp messages (Zhang et al., 2015; Fan et al., 2011; Zhang et al., 2016; Holub et al., 2014). Some of these find perturbations specifically in low frequency space to avoid being removed by compression.

Figure 4: Random images with corresponding steganographic images under different payloads.

HiDDeN (Zhu et al., 2018) and FNNS (Kishore et al., 2021) include differentiable JPEG layers to approximate compression as part of their network architecture. Following (Athalye et al., 2018), we adopt a approximate JPEG layer where the forward pass performs normal JPEG compression and the backwards pass is an identity function. We call this adapted method LISO-JPEG. Table 2 compares LISO-JPEG with existing methods. LISO is able to find perturbations that won't be lost in JPEG compression, while maintaining low error rate (<1E-01). The PSNR values for LISO-JPEG are low but qualitative 1bpp steganographic image examples from LISO-JPEG (see Figure 5) show that there is only a slight pixelation. Image quality can be improved by increasing weight on the qualitative loss L_{qua} but this will cause a slight increase in the error rate. As seen in Table 2, the PSNR of FNNS-JPEG and LISO-JPEG are similar but LISO-JPEG has significantly lower error rate. Higher quality steganographic images can be obtained by training a LISO model with a higher weight on the qualitative loss L_{qua}, but this will cause a slight increase in the error rate.

Table 2: LISO-JPEG results compared with baselines. JPEG quality 80 is used.

Method	bpp	Error (%) ↓	PSNR ↑
LISO-PNG	1	2E-05	31.99
FNNS-JPEG	1	32.03	22.65
HiDDeN	0.2	≥10	unknown
LISO-JPEG	1	6E-02	19.72

Figure 5: LISO-JPEG steganographic images.

Computational Time. One of the advantages of using a learned method as opposed to an optimization method is that it is much faster. The average inference time required for the different learned and optimization based methods is presented in Table 4. The fastest method is SteganoGAN because all that is required to use SteganoGAN is single forward passes. The FNNS variants, on the other hand, are much slower. Our proposed method LISO, is slightly slower than SteganoGAN but not by a significant magnitude. The reported times were the average times on Div2k's validation set and the methods were run on a Nvidia Titan RTX GPU.

Steganalysis. To investigate the robustness of our method against statistical detection techniques, we use Stegexpose (Boehm, 2014), a tool devised for steganography detection using four well-known steganalysis approaches and find that the detection rate is lower than 25% for images produced by LISO. Recently, more powerful neural based methods are being used to detect steganography (see related work). It is hard for any steganography method, including classical methods like WOW and S-UNIWARD, to evade detection from these neural methods even with low payload messages of about 0.4bpp (You et al., 2020). However, we show that in the following two scenarios we can evade detection by SiaStegNet (You et al., 2020).

Table 3: Number of iterations it takes to reach optimum under payload of 1-4 bits per pixel on Div2k's validation set.

Bits per Pixel	Iterations (avg)	Max Iterations
1	6.44	18
2	9.50	17
3	11.36	21
4	11.15	24

Table 4: Average computation time (in seconds). ($*$ indicates the optimization was stopped after zero error was reached.)

Method	1 bit	2 bits	3 bits	4 bits
SteganoGAN	0.09	0.09	0.08	0.09
FNNS-R	42.18	114.44	156.91	159.19
FNNS-D	4.95*	10.53*	44.39	44.29
LISO	0.16	0.29	0.32	0.33
LISO+LBFGS	1.26*	2.81*	6.64*	28.59

Table 5: Steganalysis results using images produced by different methods, evaluated on MS-COCO dataset. SG is used to denote SteganoGAN.

Setting	Method	Error Rate (%) ↓				PSNR ↑				Detection Accuracy Rate (%) ↓			
		1 bit	2 bits	3 bits	4 bits	1 bit	2 bits	3 bits	4 bits	1 bit	2 bits	3 bits	4 bits
w/o defense	SG	3.40	6.29	11.13	15.7	25.32	24.27	25.01	24.94	52	57	92	94
	FNNS-D	0.00	0.00	0.01	13.65	37.94	34.51	27.77	34.78	73	75	99	98
	LISO	1E-04	3E-04	5E-03	4E-02	33.83	34.15	30.08	24.58	51	42	98	87
w/ defense	FNNS-D	0	0.00	0.00	0.01	22.28	22.35	21.2	21.36	7	12	14	83
	LISO	4E-03	1E-02	8E-03	5E-02	31.62	28.67	26.63	25.10	4	8	5	5

In the first scenario, "w/o defense", the steganography model M is trained without any explicit precautions to avoid steganalysis detection. We assume the attacker (i.e. the party applying steganalysis) knows the model architecture of M but has no access to the actual weights, exact training set, or hyperparameters. However, they can train a surrogate model M' in order to create their own training set of steganographic images. To simulate this setting, we used a steganalysis model trained on CelebA to detect steganographic MS COCO images. From Table 5 we see that in the "w/o defense" scenario, steganographic images from SteganoGAN and FNNS can be detected much more easily when compared to images from LISO.

In the second scenario,"w/ defense", we take advantage of the fact that neural steganalysis methods are fully differentiable, and both LISO and FNNS involve gradient-based optimization. It is therefore possible to avoid detection by adding an additional loss term from the steganalysis system into the the LISO optimization or the FNNS optimization. Specifically, during evaluation we add the logit value of the steganographic class to the loss if an image is detected as steganographic. Note that we cannot add an additional loss term to SteganoGAN during inference because SteganoGAN just uses forward passes of a trained neural network for inference. We also tried training a SteganoGAN network with an auxiliary steganalysis loss and found that we couldn't avoid detection even when we did so. As seen in Table 5, we obtain single digit detection accuracy rates for LISO in the "w/ defense" scenario for all bit rates. Compared to FNNS, LISO is able to avoid detection more effectively. The image quality of steganographic images produced by LISO is also better than those produced by FNNS under this scenario. We also tested LISO with two additional steganalyis systems, SRNet (Boroumand et al., 2018) and XuNet (Xu et al., 2016), and the corresponding results are presented in appendix H.

6   CONCLUSION

We propose a novel iterative encoder-based method, LISO, for image steganography. The LISO encoder is designed to learn the update rule of a general gradient-based optimization algorithm for steganography, and is trained simultaneously with a corresponding decoder. It learns a more efficient dynamic update rule for steganography when compared to PGD or L-BFGS, and the learned decoder is particularly suitable for further L-BFGS optimization. LISO also ensures that the steganographic image remains on the natural image manifold with the help of a critic, and produces high quality steganographic images. LISO achieves state-of-the-art results for steganography, while being fairly fast. It is also flexible and can incorporate additional constraints, like producing JPEG resistant steganographic images or making steganographic images undetectable by specific steganalysis systems. In the future, we plan to investigate ways to increase image quality while maintaining low error for JPEG resistant steganography.

REFERENCES

Jonas Adler and Ozan Öktem. Learned primal-dual reconstruction. *IEEE transactions on medical imaging*, 37(6):1322–1332, 2018.

Akshay Agrawal, Brandon Amos, Shane Barratt, Stephen Boyd, Steven Diamond, and Zico Kolter. Differentiable convex optimization layers. *arXiv preprint arXiv:1910.12430*, 2019.

Eirikur Agustsson and Radu Timofte. Ntire 2017 challenge on single image super-resolution: Dataset and study. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 126–135, 2017.

Yuval Alaluf, Or Patashnik, and Daniel Cohen-Or. Restyle: A residual-based stylegan encoder via iterative refinement. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6711–6720, 2021.

Brandon Amos and J Zico Kolter. Optnet: Differentiable optimization as a layer in neural networks. In *International Conference on Machine Learning*, pp. 136–145. PMLR, 2017.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International conference on machine learning*, pp. 274–283. PMLR, 2018.

Shumeet Baluja. Hiding images in plain sight: Deep steganography. *Advances in Neural Information Processing Systems*, 30:2069–2079, 2017.

Ifra Bilal, Rajiv Kumar, Mahendra Singh Roj, and P K Mishra. Recent advancement in audio steganography. In *2014 International Conference on Parallel, Distributed and Grid Computing*, pp. 402–405, 2014. doi: 10.1109/PDGC.2014.7030779.

Benedikt Boehm. Stegexpose-a tool for detecting lsb steganography. *arXiv preprint arXiv:1410.6656*, 2014.

Mehdi Boroumand, Mo Chen, and Jessica Fridrich. Deep residual network for steganalysis of digital images. *IEEE Transactions on Information Forensics and Security*, 14(5):1181–1193, 2018.

Nicholas Carlini and David A. Wagner. Towards evaluating the robustness of neural networks. In *IEEE Symposium on Security and Privacy*, pp. 39–57, 2017.

Chi-Kwong Chan and Lee-Ming Cheng. Hiding data in images by simple lsb substitution. *Pattern recognition*, 37(3):469–474, 2004.

Mo Chen, Vahid Sedighi, Mehdi Boroumand, and Jessica Fridrich. Jpeg-phase-aware convolutional neural network for steganalysis of jpeg images. In *Proceedings of the 5th ACM Workshop on Information Hiding and Multimedia Security*, pp. 75–84, 2017.

Kyunghyun Cho, Bart Van Merriënboer, Dzmitry Bahdanau, and Yoshua Bengio. On the properties of neural machine translation: Encoder-decoder approaches. *arXiv preprint arXiv:1409.1259*, 2014.

Ingemar Cox, Matthew Miller, Jeffrey Bloom, Jessica Fridrich, and Ton Kalker. *Digital watermarking and steganography*. Morgan kaufmann, 2007.

Ron Crandall. Some notes on steganography. *Posted on steganography mailing list*, pp. 1–6, 1998.

Shiqi Dong, Ru Zhang, and Jianyi Liu. Invisible steganography via generative adversarial network. *arXiv preprint arXiv:1807.08571*, 4, 2018.

Sorina Dumitrescu, Xiaolin Wu, and Nasir Memon. On steganalysis of random lsb embedding in continuous-tone images. In *Proceedings. International Conference on Image Processing*, volume 3, pp. 641–644. IEEE, 2002a.

Sorina Dumitrescu, Xiaolin Wu, and Zhe Wang. Detection of lsb steganography via sample pair analysis. In *International workshop on information hiding*, pp. 355–372. Springer, 2002b.

Chi-Hung Fan, Hui-Yu Huang, and Wen-Hsing Hsu. A robust watermarking technique resistant jpeg compression. *J. Inf. Sci. Eng.*, 27(1):163–180, 2011.

Roger Fletcher. *Practical methods of optimization*. John Wiley & Sons, 2013.

John Flynn, Michael Broxton, Paul Debevec, Matthew DuVall, Graham Fyffe, Ryan Overbeck, Noah Snavely, and Richard Tucker. Deepview: View synthesis with learned gradient descent. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2367–2376, 2019.

Jessica Fridrich, Miroslav Goljan, and Rui Du. Detecting lsb steganography in color, and gray-scale images. *IEEE multimedia*, 8(4):22–28, 2001.

Karol Gregor and Yann LeCun. Learning fast approximations of sparse coding. In *Proceedings of the 27th international conference on international conference on machine learning*, pp. 399–406, 2010.

Jamie Hayes and George Danezis. Generating steganographic images via adversarial training. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017a. URL https://proceedings.neurips.cc/paper/2017/file/fe2d010308a6b3799a3d9c728ee74244-Paper.pdf.

Jamie Hayes and George Danezis. Generating steganographic images via adversarial training. *Advances in neural information processing systems*, 30, 2017b.

Vojtěch Holub and Jessica Fridrich. Designing steganographic distortion using directional filters. In *2012 IEEE International workshop on information forensics and security (WIFS)*, pp. 234–239. IEEE, 2012.

Vojtěch Holub, Jessica Fridrich, and Tomáš Denemark. Universal distortion function for steganography in an arbitrary domain. *EURASIP Journal on Information Security*, 2014(1):1–13, 2014.

Junpeng Jing, Xin Deng, Mai Xu, Jianyi Wang, and Zhenyu Guan. Hinet: Deep image hiding by invertible network. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4733–4742, 2021.

Varsha Kishore, Xiangyu Chen, Yan Wang, Boyi Li, and Kilian Q Weinberger. Fixed neural network steganography: Train the images, not the network. In *International Conference on Learning Representations*, 2021.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, pp. 740–755. Springer, 2014.

Dong C Liu and Jorge Nocedal. On the limited memory bfgs method for large scale optimization. *Mathematical programming*, 45(1):503–528, 1989.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Large-scale celebfaces attributes (celeba) dataset. *Retrieved August*, 15(2018):11, 2018.

Shao-Ping Lu, Rong Wang, Tao Zhong, and Paul L Rosin. Large-capacity image steganography based on invertible neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10816–10825, 2021.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Carlos Munuera. Steganography and error-correcting codes. *Signal Processing*, 87(6):1528–1533, 2007.

Tomáš Pevnỳ, Tomáš Filler, and Patrick Bas. Using high-dimensional image models to perform highly undetectable steganography. In *International Workshop on Information Hiding*, pp. 161–177. Springer, 2010.

Yinlong Qian, Jing Dong, Wei Wang, and Tieniu Tan. Deep learning for steganalysis via convolutional neural networks. In *Media Watermarking, Security, and Forensics 2015*, volume 9409, pp. 94090J. International Society for Optics and Photonics, 2015.

Yinlong Qian, Jing Dong, Wei Wang, and Tieniu Tan. Learning and transferring representations for image steganalysis using convolutional neural network. In *2016 IEEE international conference on image processing (ICIP)*, pp. 2752–2756. IEEE, 2016.

Yinlong Qian, Jing Dong, Wei Wang, and Tieniu Tan. Feature learning for steganalysis using convolutional neural networks. *Multimedia Tools and Applications*, 77(15):19633–19657, 2018.

Rafia Rahim, Shahroz Nadeem, et al. End-to-end trained cnn encoder-decoder networks for image steganography. In *Proceedings of the European Conference on Computer Vision (ECCV) Workshops*, pp. 0–0, 2018.

Yueyun Shang, Shunzhi Jiang, Dengpan Ye, and Jiaqing Huang. Enhancing the security of deep learning steganography via adversarial examples. *Mathematics*, 8(9):1446, 2020.

Yeshwanth Srinivasan, Brian Nutter, Sunanda Mitra, Benny Phillips, and Daron Ferris. Secure transmission of medical records using high capacity steganography. In *Proceedings. 17th IEEE Symposium on Computer-Based Medical Systems*, pp. 122–127. IEEE, 2004.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Jingxuan Tan, Xin Liao, Jiate Liu, Yun Cao, and Hongbo Jiang. Channel attention image steganography with generative adversarial networks. *IEEE Transactions on Network Science and Engineering*, 9(2):888–903, 2021.

Matthew Tancik, Ben Mildenhall, and Ren Ng. Stegastamp: Invisible hyperlinks in physical photographs. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2117–2126, 2020.

Zachary Teed and Jia Deng. Raft: Recurrent all-pairs field transforms for optical flow. In *European conference on computer vision*, pp. 402–419. Springer, 2020.

Paul Upchurch, Jacob Gardner, Geoff Pleiss, Robert Pless, Noah Snavely, Kavita Bala, and Kilian Weinberger. Deep feature interpolation for image content changes. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7064–7073, 2017.

Gregory K Wallace. The jpeg still picture compression standard. *IEEE transactions on consumer electronics*, 38(1):xviii–xxxiv, 1992.

Po-Wei Wang, Priya Donti, Bryan Wilder, and Zico Kolter. SATNet: Bridging deep learning and logical reasoning using a differentiable satisfiability solver. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 6545–6554. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/wang19e.html.

Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612, 2004.

Eric Wengrowski and Kristin Dana. Light field messaging with deep photographic steganography. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1515–1524, 2019.

Andreas Westfeld and Andreas Pfitzmann. Attacks on steganographic systems. In *International workshop on information hiding*, pp. 61–76. Springer, 1999.

Da-Chun Wu and Wen-Hsiang Tsai. A steganographic method for images by pixel-value differencing. *Pattern recognition letters*, 24(9-10):1613–1626, 2003.

Songtao Wu, Sheng-hua Zhong, and Yan Liu. A novel convolutional neural network for image steganalysis with shared normalization. *IEEE Transactions on Multimedia*, 22(1):256–270, 2019.

Guanshuo Xu, Han-Zhou Wu, and Yun-Qing Shi. Structural design of convolutional neural networks for steganalysis. *IEEE Signal Processing Letters*, 23(5):708–712, 2016.

Weike You, Hong Zhang, and Xianfeng Zhao. A siamese cnn for image steganalysis. *IEEE Transactions on Information Forensics and Security*, 16:291–306, 2020.

Chong Yu. Attention based data hiding with generative adversarial networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 1120–1128, 2020.

Chaoning Zhang, Philipp Benz, Adil Karjauv, Geng Sun, and In So Kweon. Udh: Universal deep hiding for steganography, watermarking, and light field messaging. *Advances in Neural Information Processing Systems*, 33:10223–10234, 2020.

Kevin Alex Zhang, Alfredo Cuesta-Infante, Lei Xu, and Kalyan Veeramachaneni. Steganogan: High capacity image steganography with gans. *arXiv preprint arXiv:1901.03892*, 2019.

Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 586–595, 2018.

Yi Zhang, Xiangyang Luo, Chunfang Yang, Dengpan Ye, and Fenlin Liu. A jpeg-compression resistant adaptive steganography based on relative relationship between dct coefficients. In *2015 10th International Conference on Availability, Reliability and Security*, pp. 461–466. IEEE, 2015.

Yi Zhang, Xiangyang Luo, Chunfang Yang, Dengpan Ye, and Fenlin Liu. A framework of adaptive steganography resisting jpeg compression and detection. *Security and Communication Networks*, 9(15):2957–2971, 2016.

Jiren Zhu, Russell Kaplan, Justin Johnson, and Li Fei-Fei. Hidden: Hiding data with deep networks. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 657–672, 2018.

Jun-Yan Zhu, Philipp Krähenbühl, Eli Shechtman, and Alexei A Efros. Generative visual manipulation on the natural image manifold. In *European conference on computer vision*, pp. 597–613. Springer, 2016.