Accepted at the NeurIPS 2022 Deep Reinforcement Learning Workshop

TRANSFORMER-BASED WORLD MODELS ARE HAPPY WITH 100K INTERACTIONS

Jan Robine, Marc Höftmann, Tobias Uelwer, Stefan Harmeling
Department of Computer Science, Technical University of Dortmund, Germany

ABSTRACT

Deep neural networks have been successful in many reinforcement learning settings. However, compared to human learners they are overly data hungry. To build a sample-efficient world model, we apply a transformer to real-world episodes in an autoregressive manner: not only the compact latent states and the taken actions but also the experienced or predicted rewards are fed into the transformer, so that it can attend flexibly to all three modalities at different time steps. The transformer allows our world model to access previous states directly, instead of viewing them through a compressed recurrent state. By utilizing the Transformer-XL architecture, it is able to learn long-term dependencies while staying computationally efficient. Our transformer-based world model (TWM) generates meaningful, new experience, which is used to train a policy that outperforms previous model-free and model-based reinforcement learning algorithms on the Atari 100k benchmark.

1 INTRODUCTION

Deep reinforcement learning methods have shown great success on many challenging decision making problems. Notable methods include DQN (Mnih et al., 2015), PPO (Schulman et al., 2017), and MuZero (Schrittwieser et al., 2019). However, most algorithms require hundreds of millions of interactions with the environment, whereas humans often can achieve similar results with less than 1% of these interactions, i.e., they are more sample-efficient. The large amount of data that is necessary renders a lot of potential real world applications of reinforcement learning impossible.

Recent works have made a lot of progress in advancing the sample efficiency of RL algorithms: model-free methods have been improved with auxiliary objectives (Laskin et al., 2020b), data augmentation (Yarats et al., 2021, Laskin et al., 2020a), or both (Schwarzer et al., 2021). Model-based methods have been successfully applied to complex image-based environments and have either been used for planning, such as EfficientZero (Ye et al., 2021), or for learning behaviors in imagination, such as SimPLe (Kaiser et al., 2020).

Figure 1: Our world model architecture. Observations $o_{t-\ell:t}$ are encoded using a CNN. Linear embeddings of stochastic, discrete latent states $z_{t-\ell:t}$, actions $a_{t-\ell:t}$, and rewards $r_{t-\ell:t}$ are fed into a transformer, which computes a deterministic hidden state h_t at each time step. Predictions of the reward r_t, discount factor γ_t, and next latent state z_{t+1} are computed based on h_t using MLPs.

A promising model-based concept is learning in imagination (Ha & Schmidhuber, 2018; Kaiser et al., 2020; Hafner et al., 2020; Hafner et al., 2021): instead of learning behaviors from the collected experience directly, a generative model of the environment dynamics is learned in a (self-)supervised manner. Such a so-called *world model* can create new trajectories by iteratively predicting the next state and reward. This allows for potentially indefinite training data for the reinforcement learning algorithm without further interaction with the real environment. Due to the nature of deep neural networks, a world model can generalize to new, unseen situations, which has the potential to drastically increase the sample efficiency. This can be illustrated by a simple example: in the game of Pong, the paddles and the ball move independently. A successfully trained world model is able to imagine trajectories with paddle and ball configurations that have never been observed before, which enables learning of improved behaviors.

In this paper, we propose to model the world with transformers (Vaswani et al., 2017), which have significantly advanced the field of natural language processing and have been successfully applied to computer vision tasks (Dosovitskiy et al., 2021). A transformer is a sequence model consisting of multiple self-attention layers with residual connections. In each self-attention layer the inputs are mapped to keys, queries, and values. The outputs are computed by weighting the values by the similarity of keys and queries. Combined with causal masking, which prevents the self-attention layers from accessing future time steps in the training sequence, transformers can be used as autoregressive generative models. The Transformer-XL architecture (Dai et al., 2019) is much more computationally efficient than vanilla transformers at inference time and introduces relative positional encodings, which remove the dependence on absolute time steps.

Our contributions: The contributions of this work can be summarized as follows:

1. We present a new autoregressive world model based on the Transformer-XL (Dai et al., 2019) architecture and a model-free agent trained in latent imagination. Running our policy is computationally efficient, as the transformer is not needed at inference time. This is in contrast to related works (Hafner et al., 2020; 2021; Chen et al., 2022) that require the full world model during inference.

2. Our world model is provided with information on how much reward has already been emitted by feeding back predicted rewards into the world model. As shown in our ablation study, this improves performance.

3. We rewrite the balanced KL divergence loss of Hafner et al. (2021) to allow us to fine-tune the relative weight of the involved entropy and cross-entropy terms.

4. We introduce a new thresholded entropy loss that stabilizes the policy's entropy during training and hereby simplifies the selection of hyperparameters that behave well across different games (see Figure 7).

5. We propose a new effective sampling procedure for the growing dataset of experience, which balances the training distribution to shift the focus towards the latest experience. We demonstrate the efficacy of this procedure with an ablation study.

6. We compare our transformer-based world model (TWM) on the Atari 100k benchmark with recent sample-efficient methods and obtain excellent results. Moreover, we report empirical confidence intervals of the aggregate metrics as suggested by Agarwal et al. (2021).

2   METHOD

We consider a partially observable Markov decision process (POMDP) with discrete time steps $t \in \mathbb{N}$, scalar rewards $r_t \in \mathbb{R}$, high-dimensional image observations $o_t \in \mathbb{R}^{h \times w \times c}$, and discrete actions $a_t \in \{1, \ldots, m\}$, which are generated by some policy $a_t \sim \pi(a_t \mid o_{1:t}, a_{1:t-1})$, where $o_{1:t}$ and $a_{1:t-1}$ denote the sequences of observations and actions up to time steps t and $t-1$, respectively. Episode ends are indicated by a boolean variable $d_t \in \{0, 1\}$. Observations, rewards, and episode ends are jointly generated by the unknown environment dynamics $o_t, r_t, d_t \sim p(o_t, r_t, d_t \mid o_{1:t-1}, a_{1:t-1})$. The goal is to find a policy π that maximizes the expected sum of discounted rewards $\mathbb{E}_\pi\left[\sum_{t=1}^{\infty} \gamma^{t-1} r_t\right]$, where $\gamma \in [0, 1)$ is the discount factor. Learning in imagination consists of three steps that are repeated iteratively: learning the dynamics, learning a policy, and interacting in the real environment. In this section, we describe our world model and policy, concluding with the training procedure.

2.1 World Model

Our world model consists of an observation model and a dynamics model, which do not share parameters. Figure 1 illustrates our combined world model architecture.

Observation Model: The observation model is a variational autoencoder (Kingma & Welling, 2014), which encodes observations o_t into compact, stochastic latent states z_t and reconstructs the observations with a decoder, which in our case is only required to obtain a learning signal for z_t:

$$\begin{aligned}
\text{Observation encoder:} & \quad z_t \sim p_\phi(z_t \mid o_t) \\
\text{Observation decoder:} & \quad \hat{o}_t \sim p_\phi(\hat{o}_t \mid z_t).
\end{aligned} \tag{1}$$

We adopt the neural network architecture of DreamerV2 (Hafner et al., 2021) with slight modifications for our observation model. Thus, a latent state z_t is discrete and consists of a vector of 32 categorical variables with 32 categories. The observation decoder reconstructs the observation and predicts the means of independent standard normal distributions for all pixels. In contrast to Hafner et al. (2021), the role of the observation model is to capture only non-temporal information about the current time step. However, we include short-time temporal information, since a single observation o_t consists of four frames (aka frame stacking, see also Section 2.2).

Autoregressive Dynamics Model: The dynamics model predicts the next time step conditioned on the history of its past predictions. The backbone is a deterministic aggregation model f_ψ which computes a deterministic hidden state h_t based on the history of the ℓ previously generated latent states, actions, and rewards. Predictors for the reward, discount, and next latent state are conditioned on the hidden state. The dynamics model consists of these components:

$$\begin{aligned}
\text{Aggregation model:} & \quad h_t = f_\psi(z_{t-\ell:t}, a_{t-\ell:t}, r_{t-\ell:t-1}) \\
\text{Reward predictor:} & \quad \hat{r}_t \sim p_\psi(\hat{r}_t \mid h_t) \\
\text{Discount predictor:} & \quad \hat{\gamma}_t \sim p_\psi(\hat{\gamma}_t \mid h_t) \\
\text{Latent state predictor:} & \quad \hat{z}_{t+1} \sim p_\psi(\hat{z}_{t+1} \mid h_t).
\end{aligned} \tag{2}$$

The aggregation model is implemented as a causally masked Transformer-XL (Dai et al., 2019), which enhances vanilla transformers (Vaswani et al., 2017) with a recurrence mechanism and relative positional encodings. With these encodings, our world model learns the dynamics independent of absolute time steps. Following Chen et al. (2021), the latent states, actions, and rewards are sent into modality-specific linear embeddings before being passed to the transformer. Due to the three modalities (latent states, actions, rewards), the number of input tokens is $3\ell - 1$, as the last reward is not part of the input. We consider the outputs of the action modality as the hidden states and disregard the outputs of the other two modalities (see Figure 1; orange boxes vs. gray boxes in the top row).

The latent state, reward, and discount predictors are implemented as multilayer perceptrons (MLPs) and compute the parameters of a vector of independent categorical distributions, a normal distribution, and a Bernoulli distribution, respectively, conditioned on the deterministic hidden state. The next state is determined by sampling from $p_\psi(\hat{z}_{t+1} \mid h_t)$. The reward and discount are determined by the mean of $p_\psi(\hat{r}_t \mid h_t)$ and $p_\psi(\hat{\gamma}_t \mid h_t)$, respectively.

Due to these design choices, our world model combines the benefits of transformers and recurrent neural networks, i.e.:

1. The dynamics model is autoregressive and has direct access to its previous outputs.
2. Training is more efficient compared with RNNs, since sequences are processed in parallel.
3. Inference is efficient due to the caching of previous outputs (Dai et al., 2019).
4. Long-term dependencies can be captured by the recurrence mechanism.

We want to provide an intuition on why a fully autoregressive dynamics model is beneficial: first, the direct access to previous latent states enables to model more complex dependencies between them, compared with RNNs, which only see them indirectly through a compressed recurrent state. This also has the potential to make inference more robust, since degenerate predictions can be ignored

more easily. Second, because the model sees which rewards it has produced previously, it can react to its own predictions. This is even more significant when the rewards are sampled from a probability distribution, since the introduced noise cannot be observed without autoregression.

Loss Functions: The observation model can be interpreted as a variational autoencoder with a temporal prior, which is provided by the latent state predictor. The goal is to keep the distributions of the encoder and the latent state predictor close to each other, while slowly adapting to new observations and dynamics. Hafner et al. (2021) apply a balanced KL divergence loss, which lets them control which of the two distributions should be penalized more. To control the influences of its subterms more precisely, we disentangle this loss and obtain a *balanced cross-entropy loss* that computes the cross-entropy $H(p_\phi(z_{t+1} \mid o_{t+1}), p_\psi(\hat{z}_{t+1} \mid h_t))$ and the entropy $H(p_\phi(z_t \mid o_t))$ explicitly. Our derivation can be found in Appendix A.1. We call the cross-entropy term for the observation model the *consistency loss*, as its purpose is to prevent the encoder from diverging from the dynamics model. The entropy regularizes the latent states and prevents them from collapsing to one-hot distributions. The observation decoder is optimized via negative log-likelihood, which provides a rich learning signal for the latent states. In summary, we optimize a self-supervised loss function for the observation model that is the expected sum over the decoder loss, the entropy regularizer and the consistency loss

$$\mathcal{L}_\phi^{\text{Obs.}} = \mathbb{E}\left[\sum_{t=1}^T \underbrace{-\ln p_\phi(o_t \mid z_t)}_{\text{decoder}} \underbrace{-\alpha_1 H(p_\phi(z_t \mid o_t))}_{\text{entropy regularizer}} + \underbrace{\alpha_2 H(p_\phi(z_t \mid o_t), p_\psi(\hat{z}_t \mid h_{t-1}))}_{\text{consistency}} \right], \quad (3)$$

where the hyperparameters $\alpha_1, \alpha_2 \geq 0$ control the relative weights of the terms.

For the balanced cross-entropy loss, we also minimize the cross-entropy in the loss of the dynamics model, which is how we train the latent state predictor. The reward predictor and discount predictor are optimized via negative log-likelihood. This leads to a self-supervised loss function for the dynamics model

$$\mathcal{L}_\psi^{\text{Dyn.}} = \mathbb{E}\left[\sum_{t=1}^T \underbrace{H(p_\phi(z_{t+1} \mid o_{t+1}), p_\psi(\hat{z}_{t+1} \mid h_t))}_{\text{latent state predictor}} - \underbrace{\beta_1 \ln p_\psi(r_t \mid h_t)}_{\text{reward predictor}} - \underbrace{\beta_2 \ln p_\psi(\gamma_t \mid h_t)}_{\text{discount predictor}} \right], \quad (4)$$

with coefficients $\beta_1, \beta_2 \geq 0$ and where $\gamma_t = 0$ for episode ends ($d_t = 1$) and $\gamma_t = \gamma$ otherwise.

2.2   POLICY

Our policy $\pi_\theta(a_t \mid \hat{z}_t)$ is trained on imagined trajectories using a mainly standard advantage actor-critic (Mnih et al., 2016) approach. We train two separate networks: an actor $a_t \sim \pi_\theta(a_t \mid \hat{z}_t)$ with parameters θ and a critic $v_\xi(\hat{z}_t)$ with parameters ξ. We compute the advantages via Generalized Advantage Estimation (Schulman et al., 2016) while using the discount factors predicted by the world model $\hat{\gamma}_t$ instead of a fixed discount factor for all time steps. As in DreamerV2 (Hafner et al., 2021), we weight the losses of the actor and the critic by the cumulative product of the discount factors, in order to softly account for episode ends.

Thresholded Entropy Loss: We penalize the objective of the actor with a slightly modified version of the usual entropy regularization term (Mnih et al., 2016). Our penalty normalizes the entropy and only takes effect when the entropy falls below a certain threshold

$$\mathcal{L}_\theta^{\text{Ent.}} = \max\left(0, \Gamma - \frac{H(\pi_\theta)}{\ln(m)} \right), \quad (5)$$

where $0 \leq \Gamma \leq 1$ is the threshold hyperparameter, $H(\pi_\theta)$ is the entropy of the policy, m is the number of discrete actions, and $\ln(m)$ is the maximum possible entropy of the categorical action distribution. By doing this, we explicitly control the percentage of entropy that should be preserved across all games independent of the number of actions. This ensures exploration in the real environment and in imagination without the need for ϵ-greedy action selection or changing the temperature of the action distribution. We also use the same stochastic policy when evaluating our agent in the experiments. The idea of applying a hinge loss to the entropy was first introduced by Pereyra et al. (2017) in the context of supervised learning. In Section 3.2 we show the effect of using a threshold on the entropy.

Figure 2: Comparing our balanced dataset sampling procedure (see Equation (6)) for different values of τ with uniform sampling ($\tau = \infty$). The x-axes correspond to the entries in dataset $\mathcal{D}$ in the order they are experienced. The left plot shows the number of times an entry has been selected for training the world model. The right plot shows the relative amount of training time that has been spent on the data up to that entry. E.g., with uniform sampling, 50% of the training time is used for the first 19K entries, whereas for $\tau = 20$ approximately the same time is spend on both halves of the dataset.

Choice of Policy Input: The policy computes an action distribution $\pi_\theta(a_t \mid x_t)$ given some view x_t of the state. E.g., this view x_t could be o_t, z_t or h_t. This view has to be chosen carefully, since it can have a significant impact on the performance of the policy and it affects the design choices for the world model. Using $x_t = o_t$ is relatively stable even with imperfect reconstructions $\hat{o}_t$, as the underlying distribution of observations $p(o)$ does not change during training. However, it is also less computationally efficient, since it requires reconstructing the observations during imagination and additional convolutional layers for the policy. Using $x_t = z_t$ is slightly less stable, as the policy has to adopt to the changes of the distribution $p(z|o)$ during training. Nevertheless, the entropy regularizer and consistency loss in Equation (3) stabilize the distribution. Using $x_t = [z_t, h_t]$ provides the agent with a summary of the history of experience, but it also adds the burden of running the transformer at inference time, i.e., when applied to the real environment. Model-free agents already perform well on most Atari games when using a stack of the most recent frames (e.g., Mnih et al. 2015; Schulman et al. 2017). Therefore, we choose $x_t = z_t$ and apply frame stacking in order to incorporate short-time information directly into the latent states. As a consequence, our policy is computationally efficient at training time (no reconstructions during imagination) and at inference time (no transformer when running in the real environment).

2.3 TRAINING

As is usual for learning with world models, we repeatedly (i) collect experience in the real environment with the current policy, (ii) improve the world model using the past experience, (iii) improve the policy using new experience generated by the world model.

During training we build a dataset $\mathcal{D} = [(o_1, a_1, r_1, d_1), \ldots, (o_T, a_T, r_T, d_T)]$ of the collected experience. To train the world model, N sequences of length ℓ are sampled from $\mathcal{D}$ and are used to estimate the loss functions in Equation (3) and Equation (4). After each update of the world model, we generate M new trajectories of length H with the dynamics model and update the policy using standard model-free objectives, as explained in Section 2.2. In Algorithm 1 we present pseudocode for training the world model and the actor-critic agent.

Balanced Dataset Sampling: Since the dataset grows slowly during training, uniform sampling of trajectories focuses too heavily on early experience, which can lead to overfitting especially in the low data regime. Therefore, we keep visitation counts $v_1, \ldots, v_T$, which are incremented every time an entry is sampled as start of a sequence. These counts are converted to probabilities using the softmax function

$$(p_1, \ldots, p_T) = \text{softmax}\left(-\tfrac{v_1}{\tau}, \ldots, -\tfrac{v_T}{\tau}\right), \tag{6}$$

where $\tau > 0$ is a temperature hyperparameter. With our sampling procedure, new entries in the dataset are oversampled and are selected more often than old ones. Setting $\tau = \infty$ restores uniform sampling as a special case, whereas reducing τ increases the amount of oversampling. See Figure 2 for a comparison. We empirically show the effectiveness in Section 3.2.

Figure 3: Aggregate metrics on the Atari 100k benchmark with 95% stratified bootstrap confidence intervals (Agarwal et al., 2021). Higher median, interquartile mean (IQM), and mean, but lower optimality gap indicate better performance. Scores for previous methods are from Agarwal et al. (2021) with 100 runs per game (except SimPLe with 5 runs). We evaluate 5 runs per game, leading to wider confidence intervals. Plot was created using the toolbox provided by Agarwal et al. (2021).

3 EXPERIMENTS

To compare data-efficient reinforcement learning algorithms, Kaiser et al. (2020) proposed the Atari 100k benchmark, which uses a subset of 26 Atari games from the Arcade Learning Environment (Bellemare et al., 2013) and limits the number of interactions per game to 100k. This corresponds to 400k frames (due to frame skipping) or roughly 2 hours of real-time gameplay, which is 500 times less than the commonly used 200 million frames (e.g., Mnih et al. 2015; Schulman et al. 2017; Hafner et al. 2021).

We compare our method with five strong competitors on the Atari 100k benchmark: (i) SimPLe (Kaiser et al., 2020) implements a world model as an action-conditional video prediction model and trains a policy with PPO (Schulman et al., 2017), (ii) DER (van Hasselt et al., 2019) is a variant of Rainbow (Hessel et al., 2018) fine-tuned for sample efficiency, (iii) CURL (Laskin et al., 2020b) improves representations using contrastive learning as an auxiliary task and is combined with DER, (iv) DrQ (Yarats et al., 2021) improves DQN by averaging Q-value estimates over multiple data augmentations of observations, and (v) SPR (Schwarzer et al., 2021) forces representations to be consistent across multiple time steps and data augmentations by extending Rainbow with a self-supervised consistency loss.

3.1 RESULTS

We follow the advice of Agarwal et al. (2021) who found significant discrepancies between reported point estimates of mean (and median) scores and a thorough statistical analysis that includes statistical uncertainty. Thus, we report confidence interval estimates of the aggregate metrics median, interquartile mean (IQM), mean, and optimality gap in Figure 3 and performance profiles in Figure 4. The metrics are computed on human normalized scores, which are calculated as `(score_agent − score_random)/(score_human − score_random)`. We report the un-normalized scores per game in Table 1. We compare with new scores for DER, CURL, DrQ, and SPR that were evaluated on 100 runs and provided by Agarwal et al. (2021). They report scores for the improved DrQ(ε), which is DrQ evaluated with standard ε-greedy parameters. We perform 5 runs per game and compute the average score over 100 episodes at the end of training for each run. TWM shows a significant improvement over previous approaches in all four aggregate metrics and brings the optimality gap closer to zero.

3.2 ABLATION STUDY

Uniform Sampling: To show the effectiveness of the sampling procedure described in Section 2.3, we evaluate three games with uniform dataset sampling, which is equivalent to setting $\tau = \infty$ in Equation (6). In Figure 5 we show that balanced dataset sampling significantly improves the performance in these games. At the end of training, the dynamics loss from Equation (4) is lower when applying balanced sampling. One reason might be that the world model overfits on early training data and performs bad in later stages of training.

Figure 4: Performance profiles on the Atari 100k benchmark based on score distributions (Agarwal et al., 2021). It shows the fraction of runs across all games (y-axis) above a human normalized score (x-axis). Shaded regions show pointwise 95% confidence bands. Plot was created using the toolbox provided by Agarwal et al. (2021).

Table 1: Mean scores on the Atari 100k benchmark per game as well as the aggregated human normalized mean and median. We perform 5 runs per game and compute the average over 100 episodes at the end of training for each run. Bold numbers indicate the best scores.

| | | | Model-free | | | | Imagination | |
Game	Random	Human	DER	CURL	DrQ(ε)	SPR	SimPLe	TWM (ours)
Alien	227.8	7127.7	802.3	711.0	**865.2**	841.9	616.9	674.6
Amidar	5.8	1719.5	125.9	113.7	137.8	**179.7**	74.3	121.8
Assault	222.4	742.0	561.5	500.9	579.6	565.6	527.2	**682.6**
Asterix	210.0	8503.3	535.4	567.2	763.6	962.5	**1128.3**	1116.6
BankHeist	14.2	753.1	185.5	65.3	232.9	345.4	34.2	**466.7**
BattleZone	2360.0	37187.5	8977.0	8997.8	10165.3	**14834.1**	4031.2	5068.0
Boxing	0.1	12.1	-0.3	0.9	9.0	35.7	7.8	**77.5**
Breakout	1.7	30.5	9.2	2.6	19.8	19.6	16.4	**20.0**
ChopperCommand	811.0	7387.8	925.9	783.5	844.6	946.3	979.4	**1697.4**
CrazyClimber	10780.5	35829.4	34508.6	9154.4	21539.0	36700.5	62583.6	**71820.4**
DemonAttack	152.1	1971.0	627.6	646.5	**1321.5**	517.6	208.1	350.2
Freeway	0.0	29.6	20.9	**28.3**	20.3	19.3	16.7	24.3
Frostbite	65.2	4334.7	871.0	1226.5	1014.2	1170.7	236.9	**1475.6**
Gopher	257.6	2412.5	467.0	400.9	621.6	660.6	596.8	**1674.8**
Hero	1027.0	30826.4	6226.0	4987.7	4167.9	5858.6	2656.6	**7254.0**
Jamesbond	29.0	302.8	275.7	331.0	349.1	**366.5**	100.5	362.4
Kangaroo	52.0	3035.0	581.7	740.2	1088.4	**3617.4**	51.2	1240.0
Krull	1598.0	2665.5	3256.9	3049.2	4402.1	3681.6	2204.8	**6349.2**
KungFuMaster	258.5	22736.3	6580.1	8155.6	11467.4	14783.2	14862.5	**24554.6**
MsPacman	307.3	6951.6	1187.4	1064.0	1218.1	1318.4	1480.0	**1588.4**
Pong	-20.7	14.6	-9.7	-18.5	-9.1	-5.4	12.8	**18.8**
PrivateEye	24.9	69571.3	72.8	81.9	3.5	86.0	35.0	**86.6**
Qbert	163.9	13455.0	1773.5	727.0	1810.7	866.3	1288.8	**3330.8**
RoadRunner	11.5	7845.0	11843.4	5006.1	11211.4	**12213.1**	5640.6	9109.0
Seaquest	68.4	42054.7	304.6	315.2	352.3	558.1	683.3	**774.4**
UpNDown	533.4	11693.2	3075.0	2646.4	4324.5	10859.2	3350.3	**15981.7**
Normalized Mean	0.000	1.000	0.350	0.261	0.465	0.616	0.332	**0.956**
Normalized Median	0.000	1.000	0.189	0.092	0.313	0.396	0.134	**0.505**

No Rewards: As described in Section 2.1, the predicted rewards are fed back into the transformer. In Figure 6 we show on three games that this can significantly increase the performance. In some games the performance is equivalent, probably because the world model can make correct predictions solely based on the latent states and actions.

Figure 5: Comparison of the proposed balanced sampling procedure with uniform sampling on three games. The top row shows the development of the human normalized score in the course of training. The bottom row shows curves of the dynamics loss from Equation (4). With balanced sampling, the score is higher and the dynamics loss is lower in all cases, demonstrating its importance.

Figure 6: Effect of removing rewards from the input. We show the human normalized score of three games during training. Not conditioning on rewards significantly degrades the performance in Pong and MsPacman. In CrazyClimber the performance stays roughly the same.

Thresholded Entropy Loss: In Figure 7 we compare (i) our thresholded entropy loss for the policy (see Section 2.2) with (ii) the usual entropy penalty. For (i) we use the same hyperparameters as in our main experiments, i.e., $\eta = 0.01$ and $\Gamma = 0.1$. For (ii) we set $\eta = 0.001$ and $\Gamma = 1.0$, effectively disabling the threshold. Without a threshold, the entropy is more likely to either collapse or diverge. This cannot be solved by adjusting the penalty coefficient η alone, since it would increase or decrease the entropy in all games.

Figure 7: Effect of the proposed thresholded entropy loss on the normalized entropy of the policy in three games, using a threshold of $\Gamma = 0.1$. The thresholded version stabilizes the entropy, while without a threshold the entropy behaves unfavorably.

4 RELATED WORK

The Dyna architecture (Sutton, 1991) introduced the idea of training a model of the environment and using it to further improve the value function or the policy. Ha & Schmidhuber (2018) introduced the notion of a *world model*, which tries to completely imitate the environment and is used to generate experience to train a model-free agent. They implement a world model as a VAE (Kingma & Welling, 2014) and an RNN and learn a policy in latent space with an evolution strategy. With SimPLe, Kaiser et al. (2020) propose an iterative training procedure that alternates between training the world model and the policy. Their policy operates on pixel-level and is trained using PPO (Schulman et al., 2017). Hafner et al. (2020) present Dreamer and implement a world model as a stochastic RNN that splits the latent state in a stochastic part and a deterministic part; this idea was first introduced by Hafner et al., 2019. This allows their world model to capture the stochasticity of the environment and simultaneously facilitates remembering information over multiple time steps. Robine et al. (2020) use a VQ-VAE to construct a world model with drastically lower number of parameters. DreamerV2 (Hafner et al., 2021) achieves great performance on the Atari 50M benchmark after making some changes to Dreamer, the most important ones being categorical latent variables and an improved objective.

Another direction of model-based reinforcement learning is planning, where the model is used at inference time to improve the action selection by looking ahead several time steps into the future. The most prominent work is MuZero (Schrittwieser et al., 2019), where a learned sequence model of rewards and values is combined with Monte-Carlo Tree Search (Coulom, 2006) without learning explicit representations of the observations. MuZero achieves impressive performance on the Atari 50M benchmark, but it is also computationally expensive and requires significant engineering effort. EfficientZero (Ye et al., 2021) improves MuZero and achieves great performance on the Atari 100k benchmark.

Transformers (Vaswani et al., 2017) advanced the effectiveness of sequence models in multiple domains, such as natural language processing and computer vision (Dosovitskiy et al., 2021). Recently, they have also been applied to reinforcement learning tasks. The Decision Transformer (Chen et al., 2021) and the Trajectory Transformer (Janner et al., 2021) are trained on an offline dataset of trajectories. The Decision Transformer is conditioned on states, actions, and returns, and outputs optimal actions. The Trajectory Transformer trains a sequence model of states, actions, and rewards, and is used for planning. Chen et al. (2022) replace the RNN of Dreamer with a transformer and outperform Dreamer on Hidden Order Discovery tasks. However, their transformer has no access to previous rewards and they do not evaluate their method on the Atari 100k benchmark. Moreover, their policy depends on the outputs of the transformer, leading to higher computational costs during inference time.

5 CONCLUSION

In this work, we discuss a reinforcement learning approach using transformer-based world models. Our method (TWM) outperforms previous model-free and model-based methods in terms of human normalized score on the 26 games of the Atari 100k benchmark. By using the transformer only during training, we were able to keep the computational costs low during inference, i.e., when running the learned policy in a real environment. We show how feeding back the predicted rewards into the transformer is beneficial for learning the world model. Furthermore, we introduce the balanced cross-entropy loss for finer control over the trade-off between the entropy and cross-entropy terms in the loss functions of the world model. A new thresholded entropy loss effectively stabilizes the entropy of the policy. Finally, our novel balanced sampling procedure corrects issues of naive uniform sampling of past experience.

REFERENCES

Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron C. Courville, and Marc G. Bellemare. Deep reinforcement learning at the edge of the statistical precipice. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual,*

pp. 29304–29320, 2021. URL `https://proceedings.neurips.cc/paper/2021/hash/f514cec81cb148559cf475e7426eed5e-Abstract.html`.

Marc G. Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *J. Artif. Intell. Res.*, 47:253–279, 2013. doi: 10.1613/jair.3912. URL `https://doi.org/10.1613/jair.3912`.

Chang Chen, Yi-Fu Wu, Jaesik Yoon, and Sungjin Ahn. Transdreamer: Reinforcement learning with transformer world models. *CoRR*, abs/2202.09481, 2022. URL `https://arxiv.org/abs/2202.09481`.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Michael Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 15084–15097, 2021. URL `https://proceedings.neurips.cc/paper/2021/hash/7f489f642a0ddb10272b5c31057f0663-Abstract.html`.

Rémi Coulom. Efficient selectivity and backup operators in monte-carlo tree search. In H. Jaap van den Herik, Paolo Ciancarini, and H. H. L. M. Donkers (eds.), *Computers and Games, 5th International Conference, CG 2006, Turin, Italy, May 29-31, 2006. Revised Papers*, volume 4630 of *Lecture Notes in Computer Science*, pp. 72–83. Springer, 2006. doi: 10.1007/978-3-540-75538-8_7. URL `https://doi.org/10.1007/978-3-540-75538-8_7`.

Zihang Dai, Zhilin Yang, Yiming Yang, Jaime G. Carbonell, Quoc Viet Le, and Ruslan Salakhutdinov. Transformer-xl: Attentive language models beyond a fixed-length context. In Anna Korhonen, David R. Traum, and Lluís Màrquez (eds.), *Proceedings of the 57th Conference of the Association for Computational Linguistics, ACL 2019, Florence, Italy, July 28- August 2, 2019, Volume 1: Long Papers*, pp. 2978–2988. Association for Computational Linguistics, 2019. doi: 10.18653/v1/p19-1285. URL `https://doi.org/10.18653/v1/p19-1285`.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL `https://openreview.net/forum?id=YicbFdNTTy`.

Stefan Elfwing, Eiji Uchibe, and Kenji Doya. Sigmoid-weighted linear units for neural network function approximation in reinforcement learning. *Neural Networks*, 107:3–11, 2018. doi: 10.1016/j.neunet.2017.12.012. URL `https://doi.org/10.1016/j.neunet.2017.12.012`.

David Ha and Jürgen Schmidhuber. Recurrent world models facilitate policy evolution. In Samy Bengio, Hanna M. Wallach, Hugo Larochelle, Kristen Grauman, Nicolò Cesa-Bianchi, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, December 3-8, 2018, Montréal, Canada*, pp. 2455–2467, 2018. URL `https://proceedings.neurips.cc/paper/2018/hash/2de5d16682c3c35007e4e92982f1a2ba-Abstract.html`.

Danijar Hafner, Timothy P. Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2555–2565. PMLR, 2019. URL `http://proceedings.mlr.press/v97/hafner19a.html`.

Danijar Hafner, Timothy P. Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=S1lOTC4tDS`.

Danijar Hafner, Timothy P. Lillicrap, Mohammad Norouzi, and Jimmy Ba. Mastering atari with discrete world models. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL https://openreview.net/forum?id=0oabwyZbOu.

Matteo Hessel, Joseph Modayil, Hado van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Gheshlaghi Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. In Sheila A. McIlraith and Kilian Q. Weinberger (eds.), *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18), the 30th innovative Applications of Artificial Intelligence (IAAI-18), and the 8th AAAI Symposium on Educational Advances in Artificial Intelligence (EAAI-18), New Orleans, Louisiana, USA, February 2-7, 2018*, pp. 3215–3222. AAAI Press, 2018. URL https://www.aaai.org/ocs/index.php/AAAI/AAAI18/paper/view/17204.

Michael Janner, Qiyang Li, and Sergey Levine. Offline reinforcement learning as one big sequence modeling problem. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 1273–1286, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/099fe6b0b444c23836c4a5d07346082b-Abstract.html.

Lukasz Kaiser, Mohammad Babaeizadeh, Piotr Milos, Blazej Osinski, Roy H. Campbell, Konrad Czechowski, Dumitru Erhan, Chelsea Finn, Piotr Kozakowski, Sergey Levine, Afroz Mohiuddin, Ryan Sepassi, George Tucker, and Henryk Michalewski. Model based reinforcement learning for atari. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=S1xCPJHtDB.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In Yoshua Bengio and Yann LeCun (eds.), *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014. URL http://arxiv.org/abs/1312.6114.

Michael Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020a. URL https://proceedings.neurips.cc/paper/2020/hash/e615c82aba461681ade82da2da38004a-Abstract.html.

Michael Laskin, Aravind Srinivas, and Pieter Abbeel. CURL: contrastive unsupervised representations for reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 5639–5650. PMLR, 2020b. URL http://proceedings.mlr.press/v119/laskin20a.html.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Bellemare, Alex Graves, Martin A. Riedmiller, Andreas Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nat.*, 518(7540):529–533, 2015. doi: 10.1038/nature14236. URL https://doi.org/10.1038/nature14236.

Volodymyr Mnih, Adrià Puigdomènech Badia, Mehdi Mirza, Alex Graves, Timothy P. Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In Maria-Florina Balcan and Kilian Q. Weinberger (eds.), *Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, volume 48 of *JMLR Workshop and Conference Proceedings*, pp. 1928–1937. JMLR.org, 2016. URL http://proceedings.mlr.press/v48/mniha16.html.

Gabriel Pereyra, George Tucker, Jan Chorowski, Lukasz Kaiser, and Geoffrey E. Hinton. Regularizing neural networks by penalizing confident output distributions. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Workshop Track Proceedings*. OpenReview.net, 2017. URL `https://openreview.net/forum?id=HyhbYrGYe`.

Jan Robine, Tobias Uelwer, and Stefan Harmeling. Smaller world models for reinforcement learning. *CoRR*, abs/2010.05767, 2020. URL `https://arxiv.org/abs/2010.05767`.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, Timothy P. Lillicrap, and David Silver. Mastering atari, go, chess and shogi by planning with a learned model. *CoRR*, abs/1911.08265, 2019. URL `http://arxiv.org/abs/1911.08265`.

John Schulman, Philipp Moritz, Sergey Levine, Michael I. Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In Yoshua Bengio and Yann LeCun (eds.), *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016. URL `http://arxiv.org/abs/1506.02438`.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *CoRR*, abs/1707.06347, 2017. URL `http://arxiv.org/abs/1707.06347`.

Max Schwarzer, Ankesh Anand, Rishab Goel, R. Devon Hjelm, Aaron C. Courville, and Philip Bachman. Data-efficient reinforcement learning with self-predictive representations. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL `https://openreview.net/forum?id=uCQfPZwRaUu`.

Richard S. Sutton. Dyna, an integrated architecture for learning, planning, and reacting. *SIGART Bull.*, 2(4):160–163, 1991. doi: 10.1145/122344.122377. URL `https://doi.org/10.1145/122344.122377`.

Hado van Hasselt, Matteo Hessel, and John Aslanides. When to use parametric models in reinforcement learning? In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 14322–14333, 2019. URL `https://proceedings.neurips.cc/paper/2019/hash/1b742ae215adf18b75449c6e272fd92d-Abstract.html`.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5998–6008, 2017. URL `https://proceedings.neurips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html`.

Denis Yarats, Ilya Kostrikov, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL `https://openreview.net/forum?id=GY6-6sTvGaf`.

Weirui Ye, Shaohuai Liu, Thanard Kurutach, Pieter Abbeel, and Yang Gao. Mastering atari games with limited data. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 25476–25488, 2021. URL `https://proceedings.neurips.cc/paper/2021/hash/d5eca8dc3820cad9fe56a3bafda65ca1-Abstract.html`.

A APPENDIX

A.1 DERIVATION OF BALANCED CROSS-ENTROPY LOSS

Hafner et al. (2021) propose to use a balanced KL divergence loss to jointly optimize the observation encoder q_θ and state predictor p_θ with shared parameters θ, i.e.,

$$\lambda D_{\text{KL}}(\text{sg}(q_\theta) \parallel p_\theta) + (1 - \lambda) D_{\text{KL}}(q_\theta \parallel \text{sg}(p_\theta)), \tag{7}$$

where $\text{sg}(\cdot)$ denotes the stop-gradient operation and $\lambda \in [0, 1]$ controls how much the state predictor adapts to the observation encoder and vice versa. By using the identity $D_{\text{KL}}(q \parallel p) = H(q, p) - H(q)$, where $H(q, p)$ is the cross-entropy of distribution p relative to distribution q, we show that our loss functions lead to the same gradients as the balanced KL objective, but with finer control over the individual components:

$$\nabla_\theta \left[\lambda D_{\text{KL}}(\text{sg}(q_\theta) \parallel p_\theta) + (1 - \lambda) D_{\text{KL}}(q_\theta \parallel \text{sg}(p_\theta)) \right] \tag{8}$$

$$= \nabla_\theta \left[\lambda \left(H(\text{sg}(q_\theta), p_\theta) - H(\text{sg}(q_\theta)) \right) + (1 - \lambda) \left(H(q_\theta, \text{sg}(p_\theta)) - H(q_\theta) \right) \right] \tag{9}$$

$$= \nabla_\theta \left[\lambda_1 H(\text{sg}(q_\theta), p_\theta) + \lambda_2 H(q_\theta, \text{sg}(p_\theta)) - \lambda_3 H(q_\theta) \right], \tag{10}$$

since $\nabla_\theta H(\text{sg}(q_\theta)) = 0$ and by defining $\lambda_1 = \lambda$ and $\lambda_2 = 1 - \lambda$ and $\lambda_3 = 1 - \lambda$. In this form, we have control over the cross-entropy of the state predictor relative to the observation encoder and vice versa. Moreover, we explicitly penalize the entropy of the observation encoder, instead of being entangled inside of the KL divergence.

As common in the literature, we define the loss function by omitting the gradient in Equation (10), so that automatic differentiation computes this gradient. For our world model, we split the objective into two loss functions, as the observation encoder and state predictor have separate parameters, yielding Equations (3) and (4).

A.2 ADDITIONAL TRAINING DETAILS

In Algorithm 1 we present pseudocode for training the world model and the actor-critic agent. We use the SiLU activation function (Elfwing et al., 2018) for all models. In Table 2 we summarize all hyperparameters that we used in our experiments. In Table 3 we provide the number of parameters of our models.

Pretraining for Better Initialization: During training we need to correctly balance the amount of world model training and policy training, since the policy has to "keep up" with the distributional shift of the latent space. However, we can spend some extra training time on the world model with pre-collected data (included in the 100k interactions) at the beginning of training in order to obtain a reasonable initialization for the latent states.

Algorithm 1 Training the world model and the actor-critic agent.

```
function train_world_model()                function train_actor_critic(z)
   // sample sequences of observations,         // imagine trajectories of states,
   // rewards, actions and discounts            // rewards, actions and discounts;
   o,a,r,d = sample_from_dataset()              // use z as starting point
   z = encode(o)                                imag = [z]
   o_hat = decode(z)                            for t = 0 until H do
   h = transformer(z,a,r)                          a = actor(z)
   r_hat,d_hat,z_hat = predict(h)                  imag.append(a)
                                                   h = transformer(imag)
   // optimize world model via                     r,d,z = predict(h)
   // self-supervised learning                     imag.extend([r,d,z])
   optim_observation(o,z,o_hat,z_hat)
   optim_dynamics(r,d,z,r_hat,d_hat,z_hat)      // optimize actor-critic via
                                                // reinforcement learning
   // z will be used for imagination            optim_actor_critic(imag)
   return z
```

Table 2: Hyperparameters used in our experiments.

Description	Symbol	Value
Dataset sampling temperature	τ	20
Discount factor	γ	0.99
GAE parameter	λ	0.95
World model batch size	N	100
History length	ℓ	16
Imagination batch size	M	400
Imagination horizon	H	15
Encoder entropy coefficient	α_1	5.0
Consistency loss coefficient	α_2	0.01
Reward coefficient	β_1	10.0
Discount coefficient	β_2	50.0
Actor entropy coefficient	η	0.01
Actor entropy threshold	Γ	0.1
Environment steps	—	100K
Frame skip	—	4
Frame down-sampling	—	64×64
Frame gray-scaling	—	Yes
Frame stack	—	4
Terminate on live loss	—	Yes
Max frames per episode	—	108K
Max no-ops	—	30
Observation learning rate	—	0.0001
Dynamics learning rate	—	0.0001
Actor learning rate	—	0.0001
Critic learning rate	—	0.00001
Transformer embedding size	—	256
Transformer layers	—	10
Transformer heads	—	4×64
Transformer feedforward size	—	1024
Latent state predictor units	—	4×512
Reward predictor units	—	4×256
Discount predictor units	—	4×256
Actor units	—	4×512
Critic units	—	4×512
Activation function	—	SiLU

Table 3: Number of parameters of our models.

Model	Symbol	# Parameters
Observation model	ϕ	8.2M
Dynamics model	ψ	10.8M
Actor	θ	1.3M
Critic	ξ	1.3M
World model	—	19M
Actor-critic	—	2.6M
Total	—	21.6M
Encoder + actor (at inference time)	—	4.4M