# CONSTRAINED PHYSICAL-STATISTICS MODELS FOR DYNAMICAL SYSTEM IDENTIFICATION AND PREDICTION

## ABSTRACT

Modeling dynamical systems combining prior physical knowledge and machine learning (ML) is promising in scientific problems when the underlying processes are not fully understood, e.g. when the dynamics is partially known. A common practice to identify the respective parameters of the physical and ML components is to formulate the problem as supervised learning on observed trajectories. However, this formulation leads to an infinite number of possible decompositions. To solve this ill-posedness, we reformulate the learning problem by introducing an upper bound on the prediction error of a physical-statistical model. This allows us to control the contribution of both the physical and statistical components to the overall prediction. This framework generalizes several existing hybrid schemes proposed in the literature. We provide theoretical guarantees on the well-posedness of our formulation along with a proof of convergence in a simple affine setting. For more complex dynamics, we validate our framework experimentally.

## 1 INTRODUCTION

Dynamical systems prediction and identification find crucial applications ranging from medicine and the study of tumors (Hanahan & Weinberg, 2011; Lu & Fei, 2014) to oceanic and climate forecasting (Oreskes et al., 1994; Caers, 2011). The modeling of such systems traditionally rely on ordinary or partial differential equations (ODE/PDE) (Madec, 2008; Marti et al., 2010), and their resolution via numerical solvers and data assimilation (Ghil & Malanotte-Rizzoli, 1991). In real world applications, two main pitfalls occur: first the dynamics may only be partially known and thus do not fully represent the studied phenomena (Rio & Santoleri, 2018); second, the system state may only be partially observed as in ocean models (Gaultier et al., 2013). Machine learning (ML) has become a complementary approach to traditional physics based models (denoted MB for model based) (Reichstein et al., 2019; Dueben & Bauer, 2018). Both offer advantages: whereas MB approaches generalize and extrapolate better, ML high expressivity approaches benefit from the ongoing explosive growth of available data such as satellite observations, with reduced costs compared to classical data assimilation.

In that perspective, recent lines of work tackle the learning of hybrid models relying on prior physical knowledge and machine learning (Yin et al., 2021; Mehta et al., 2020). Efficiently learning such decompositions actually means solving two different tasks: system identification, i.e. estimating the parameters of the physical model, and prediction, i.e. recovering the trajectories associated to the dynamics. Both are essential for hybrid MB/ML models of dynamical systems. Whereas prediction aims at robust extrapolation, identification accounts for physical interpretability of the MB/ML model. While solving both problems using model-based formulation admits well-known numerical solutions, for example using the adjoint method (Le Dimet & Talagrand, 1986; Courtier et al., 1994), the combination of physical models and deep learning is still an open area of research. In this context, ML applications mainly focus on the prediction task, at the expense of the system identification: Willard et al. (2020) underlines the lack of generalizability of black-box ML models and their inability to produce physically sound results. Indeed, Ayed et al. (2020) show that without any prior knowledge, the recovered estimates of a dynamical system states are not physically plausible despite accurate predictions. Moreover, as noted by Yin et al. (2021), learning a linear MB/ML decompo-

sition with the sole supervision on the system trajectories is ill-posed and admits an infinite number of decompositions. Such observations highlight the need to incorporate physically motivated constraints in the learning of hybrid models, e.g. through regularization penalties, and several works propose additional constraints to guide the model towards physical solutions (Jia et al., 2019; Yin et al., 2021; Linial et al., 2021). Finally, to complete prior dynamical knowledge with a data-driven component and ensure interpretability of the decomposition, we work out a principled framework that generalizes previous attempts in the regularization of hybrid models. Our contributions are :

- In section 3.1, we introduce a novel way to recover well-posedness and interpretability in the learning of hybrid MB/ML models through the control of an upper bound. We further extend our framework to incorporate auxiliary data when available to handle complex real-world problems.

- In section 3.2, we propose a novel alternate-optimization algorithm to learn hybrid models.

- In section 3.3, we provide an analysis of the convergence of the proposed algorithm on a simplified case and experimentally evidence the soundness of our approach on more complex settings of increasing difficulty including challenging real world problems (section 4).

## 2 BACKGROUND AND PROBLEM SETUP

We consider a dynamical system with state at time $t$ denoted $Z_t = Z(t)$. $Z_t$ might be fully or only partially observed: we write $Z_t = (X_t, Y_t)$, where $X_t$ is the observed component and $Y_t$ the unobserved one. The evolution of $Z$ is governed by a differential equation with dynamics :

$$\frac{dZ_t}{dt} = \frac{d}{dt}\begin{pmatrix} X_t \\ Y_t \end{pmatrix} = \begin{pmatrix} f_X(Z_t) \\ f_Y(Z_t) \end{pmatrix} \tag{1}$$

The objective is to predict trajectories of $X$, i.e. to model the evolution of the observable part following $\frac{dX_t}{dt} = f_X(Z_t)$. For simplicity, we omit the index $X$ in $f_X$ and write $f(.) \stackrel{\Delta}{=} f_X(.)$.

**Dynamical Hypothesis**  We assume partial knowledge of the dynamics of the observed $X_t$:

$$\frac{dX_t}{dt} = f(Z_t) = f_k(Z_t) + f_u(Z_t) \tag{2}$$

where $f_k \in \mathcal{H}_k$ is a known operator with unknown parameters $\theta^*$, and $f_u \in \mathcal{H}_u$ is the unknown residual dynamics. $\mathcal{H}_k$ and $\mathcal{H}_u$ denote function spaces. Note that the additive hypothesis in eq. (2) is not restrictive (see discussion in appendix B).

**Learning Problem**  Our objective is to approximate $f$ with a function $h$ learned from the observed data. According to eq. (2), we assume $h = h_k + h_u$. $h_k \in \mathcal{H}_k$ belongs to the same hypothesis space as $f_k$, i.e. it has the same parametric form. Its parameters are denoted $\theta_k$. Note that $h_k(., \theta^*) = f_k$. $h_u \in \mathcal{H}_u$ is represented by a free form functional with parameters $\theta_u$, e.g. a neural network. The learning problem is then to estimate from data the parameters of $h_k$ so that they match the true physical ones and those of $h_u$ so as to approximate at best the unknown dynamics $f$. In this regard, an intuitive training objective is to minimize a distance d between $h = h_k + h_u$ and $f$:

$$\mathrm{d}(h, f) = \mathbb{E}_{Z \sim p_Z}\|h(Z) - f(Z)\|_2, \tag{3}$$

where $p_Z$ is the distribution of the state values $Z$ that accounts for varying initial states. Each $Z$ then defines a training sample. Minimizing eq. (3) with $h = h_k + h_u$ enables to predict accurate trajectories but may have an infinite number of solutions. For instance, $h_u$ may bypass the physical hypothesis $h_k$. Thus, interpretability is not guaranteed. We develop in the following section a method to overcome this ill-posedness.

## 3 METHOD

In hybrid modeling, two criteria are essentials: 1. identifiability, i.e. the estimated parameters of $h_k$ should correspond to the true physical ones; 2. prediction power, i.e. the statistical component $h_u$ should complete $h_k$ so that $h = h_k + h_u$ performs accurate prediction over the system states. To

control the contribution of each term $h_k$ and $h_u$, we work upper bounds out of eq. (3) (section 3.1). We then propose to minimize $d(h, f)$ while constraining the upper bounds, which provide us with a well-posed learning framework (section 3.2). Besides, we show that several previous works that introduced constrained optimization to solve related problems are specific cases of our formulation (Yin et al., 2021; Jia et al., 2019; Linial et al., 2021). Finally, we introduce an alternate optimization algorithm which convergence is shown in section 3.3 for a linear approximation of $f$.

## 3.1 STRUCTURAL CONSTRAINTS FOR DYNAMICAL SYSTEMS

To ensure identifiability, we derive regularizations on $h_k$ and $h_u$ flowing from the control of an upper bound of $d(h, f)$. In particular, to minimize $d(h_k, f_k)$ would enable us to accurately interpret $h_k$ as the true $f_k$, and thus $h_u$ as the residual dynamics $f_u$. However, since we do not access the parameters of $f_k$, computing $d(h_k, f_k)$ is not tractable. We then consider two possible situations. In the first one, the only available information on the physical system is the parametric form of $f_k$ (or equivalently of $h_k$), training thus only relies on observed trajectories (section 3.1.1). In the second one, we consider that auxiliary information about $f_k$ is available and will be used to minimize the distance between $h_k$ and $f_k$ (section 3.1.2). While the first setting is the more general, the physical prior it relies on is often insufficient to effectively handle real world situations. The second setting makes use of more informative priors and better corresponds to real cases as will be shown in the experimental section (see section 4.2).

### 3.1.1 CONTROLLING THE ML COMPONENT AND THE MB HYPOTHESIS

We propose a general approach to constrain the learning of hybrid models when one solely access the functional form of $h_k$. In this case, to make $h_k$ accountable in our observed phenomena, a solution is to minimize $d(h_k, f)$. Following the triangle inequality we link up both errors $d(h, f)$ and $d(h_k, f)$ (computations available in appendix C.1):

$$d(h, f) \leq d(h, h_k) + d(h_k, f) = d(h_u, 0) + d(h_k, f) \tag{4}$$

We want the physical-statistical model $h = h_k + h_u$ to provide high quality forecasts. Minimizing the sole upper bound does not ensure such aim, as $h_u$ is only penalized through $d(h_u, 0)$ and is not optimized to contribute to predictions. We thus propose to minimize $d(h, f)$ while controlling both $d(h_u, 0)$ and $d(h_k, f)$. Such a control of the upper bound of eq. (4) amounts to balancing the contribution of the ML and the MB components. This will be formally introduced in section 3.2.

**Link to the Literature**    The least action principle on the ML component i.e. constraining $d(h_u, 0)$ is invoked for a geometric argument in (Yin et al., 2021), and appears as a co-product of the introduction of $d(h_k, f)$ in eq. (4). Optimizing $d(h_k, f)$ to match the physical model with observations is investigated in (Forssell & Lindskog, 1997).

The general approach of eq. (4) allows us to perform prediction (via $h$) and system identification (via $h_k$) on simple problems (see section 4.1). The learning of real-world complex dynamics, via data-driven hybrid models, often fails at yielding a physically sound estimation, as illustrated in section 4.2. This suggests that learning complex dynamics requires additional information. In many real-world cases, auxiliary information is available in the form of measurements providing complementary information on $f_k$. Indeed, a common issue in physics is to infer an unobserved variable of interest (in our case $f_k$ parameters $\theta^\star$) from indirect or noisy measurements that we refer to as proxy data. For instance, one can access a physical quantity but only at a coarse resolution, as in (Um et al., 2020; Belbute-Peres et al., 2020) and in the real world example detailed in section 4.2. We show in the next subsection how to incorporate such an information in order to approximate $d(h_k, f_k)$.

### 3.1.2 MATCHING THE PHYSICAL HYPOTHESES: INTRODUCING AUXILIARY DATA

We here assume one accesses a proxy of $f_k$, denoted $f_k^{pr} \in \mathcal{H}_k$. Our goal is to adapt our framework to incorporate such auxiliary information, bringing the regularization induced by $f_k^{pr}$ within the scope of the control of an upper bound. This enables us to extend our proposition towards the solving of real world physical problems, still largely unexplored by the ML community. We have:

$$d(h, f) \leq d(h, h_k) + d(h_k, f_k^{pr}) + \Gamma = d(h_u, 0) + d(h_k, f_k^{pr}) + \Gamma \tag{5}$$

where $\Gamma$ is a constant of the problem that cannot be optimized (see appendix C.2). In that context, we can benefit from auxiliary information providing us with coarse estimates of $\theta^\star$, denoted $\theta^{pr}$, such that $f_k^{pr} = h_k(., \theta^{pr}) \approx f_k$. To use the available $\theta^{pr}$ to guide our estimation towards the true parameters $\theta^\star$ of $f_k$, a simple solution is to directly enforce the minimization of $\mathrm{d}(h_k, f_k^{pr})$ in the parameter space by minimizing $\|\theta_k - \theta^{pr}\|_2$, where $\theta_k$ are the parameters of $h_k$. Indeed, because $f_k$ and $f_k^{pr}$ have identical parametric forms (as both belong to the same functional space $\mathcal{H}_k$), minimizing $\|\theta_k - \theta^{pr}\|_2$ will bring $h_k$ closer to $f_k^{pr}$ and thus to $f_k$. As above, we propose to minimize $\mathrm{d}(h, f)$ while controlling both $\mathrm{d}(h_u, 0)$ and $\mathrm{d}(h_k, f_k^{pr})$, as described in section 3.2.

**Link to the Literature**    In (Linial et al., 2021) $f_k^{pr}$ stands for true observations used to constrain a learned latent space, minimizing $\mathrm{d}(h_k, f_k^{pr})$. Jia et al. (2019) uses synthetic data as $f_k^{pr}$ to pre-train their model which amounts to the control an upper bound, see appendix C.3. Finally, this setting finds an extension, when the model $f_k^{pr}$ is a learned model, for example trained using eq. (4), leading to a self-supervision approach described in appendix C.4.

## 3.2    Learning Algorithm and Optimization Problem

From the upper bounds, we first recover the well-posedness of the optimization and derive a theoretical learning scheme (section 3.2.1). We then discuss its practical implementation (section 3.2.2).

### 3.2.1    Well-Posedness and Alternate Optimization Algorithm

**Recovering Well-Posedness**    We reformulate the ill-posed learning of $\min_{h_k, h_u \in \mathcal{H}_k \times \mathcal{H}_u} \mathrm{d}(h, f)$, by instead optimizing $\mathrm{d}(h, f)$ while constraining the upper bounds. Let us define $\mathcal{S}_k$ and $\mathcal{S}_u$ as

$$\mathcal{S}_k = \{ h_k \in \mathcal{H}_k \mid \ell(h_k) \leq \mu_k \} \qquad \mathcal{S}_u = \{ h_u \in \mathcal{H}_u \mid \mathrm{d}(h_u, 0) \leq \mu_u \} \tag{6}$$

where $\mu_k, \mu_u$ are two positive scalars and $\ell(h_k) = \mathrm{d}(h_k, f)$ in the case of section 3.1.1 and $\ell(h_k) = \mathrm{d}(h_k, f_k^{pr})$ in the case of section 3.1.2. Our proposition then amounts to optimizing $\mathrm{d}(h, f)$ over the Minkowski-sum $\mathcal{S}_k + \mathcal{S}_u = \{ h = h_k + h_u \mid h_k \in \mathcal{S}_k, h_u \in \mathcal{S}_u \}$:

$$\min_{h \in \mathcal{S}_k + \mathcal{S}_u} \mathrm{d}(h, f), \tag{7}$$

This constrained optimization setting enables us to recover the well-posedness of the optimization problem under the relative compactness of the family of function $\mathcal{H}_k$ (proof in appendix D.3).

**Proposition 1** (Well-posedness). *Under the relative compactness of $\mathcal{S}_k$, eq. (7) finds a solution $h$ that writes as $h = h_k + h_u \in \mathcal{S}_k + \mathcal{S}_u$. Moreover, this solution is unique.*

**Alternate Optimization Algorithm**    As the terms in both upper bounds of eqs. (4) and (5) specifically address either $h_k$ or $h_u$, we isolate losses relative to $h_k$ and $h_u$ and alternate projections of $h_k$ on $\mathcal{S}_k$ and $h_u$ on $\mathcal{S}_u$, as described in Algorithm 1. Said otherwise, we learn $h$ by alternately optimizing $h_k$ ($h_u$ being fixed) and $h_u$ ($h_k$ being fixed). In practice, we rely on a dual formulation (see section 3.2.2 and the SGD version of Algorithm 1 in Appendix F).

---

**Algorithm 1** Alternate estimation: General Setting

---

**Result:** Converged $h_k$ and $h_u$

Set $h_u^0 = 0$, $h_k^0 = \min_{h_k \in \mathcal{H}_k} \mathrm{d}(h_k, f)$, $tol \in \mathbb{R}^+$

  **while** $\mathrm{d}(h, f) > tol$ **do**

$$h_k^{n+1} = \arg\min_{h_k \in \mathcal{S}_k} \mathrm{d}(h_k + h_u^n, f); \quad h_u^{n+1} = \arg\min_{h_u \in \mathcal{S}_u} \mathrm{d}(h_k^{n+1} + h_u, f) \tag{8}$$

    $n \leftarrow n + 1$

**end**

---

The convergence of the alternate projections is well studied for the intersection of convex sets or smooth manifolds (von Neumann, 1950; Lewis & Malick, 2008) and has been extended in our setting of Minkowski-sum of convex sets (Lange et al., 2019). Because $\mathrm{d}$ as defined in eq. (3) is convex, $\mathcal{S}_u$ and $\mathcal{S}_k$ are convex sets as soon as $\mathcal{H}_k$ and $\mathcal{H}_u$ are convex (Appendix A). Thus, if $\mathrm{d}(., f)$ is strongly convex, eq. (8) finds one and only one solution (Boyd et al., 2004). However, neither the

convexity of $\mathcal{H}_u$ nor of $\mathcal{H}_k$ is practically ensured. Nonetheless, we recover the well-posedness of eq. (7) and show the convergence of Algorithm 1 in the simplified case where $h$ is an affine function of $X_t$ (see section 3.3). For complex PDE where convexity may not hold, we validate our approach experimentally and we evidence in section 4 that this formulation enables us to recover both an interpretable decomposition $h = h_k + h_u$ and improved prediction and identification performances.

### 3.2.2 PRACTICAL OPTIMIZATION

Equation (6) involves the choice of $\mu_k$ and $\mu_u$. In practice, we implement the projection algorithm by descending gradients on the parameters of $h_k$ and $h_u$, with respect to the following losses:

$$\mathcal{L}_k(h_k) = \lambda_h \mathrm{d}(h, f) + \lambda_{h_k} \ell(h_k) \qquad \mathcal{L}_u(h_u) = \lambda_h \mathrm{d}(h, f) + \lambda_{h_u} \mathrm{d}(h_u, 0) \qquad (9)$$

where $\lambda_h, \lambda_{h_k}, \lambda_{h_u}$ are positive real values, dynamically increased/decreased during training. Indeed, $\mathrm{d}(h_u, 0)$ can be interpreted as a *stability loss*, preventing the neural networks to trump the physical component. On the other hand, $\mathrm{d}(h_k, f)$ can be interpreted has an *initialization loss* yield a first estimate of $\theta_k$ explaining the dynamics. Yet, $f$ being unknown: $\mathrm{d}(h, f)$ is not tractable. To estimate $\mathrm{d}(h, f)$, we rely on the trajectories associated to the dynamics. We minimize the distance between the ODE flows $\phi_h$ and $\phi_f$ defined by $h$ and $f$, $\mathrm{d}_\phi(\phi_h, \phi_f)$, over all initial conditions $X_0$:

$$\mathrm{d}_\phi(\phi_h, \phi_f) = \mathbb{E}_{X_0} \int_{t_0}^t \|\phi_h(\tau, X_0) - \phi_f(\tau, X_0)\|_2 d\tau \qquad (10)$$

We have: $\mathrm{d}_\phi(\phi_h, \phi_f) = 0 \Leftrightarrow \mathrm{d}(h, f) = 0$. Definitions of flows for ODE and in depth consideration on these distances are available in appendix A. The gradients of $\mathrm{d}_\phi(\phi_h, \phi_f)$ with respect to the parameters of $h_k$ or $h_u$ can be either estimated analytically using the adjoint method (Chen et al., 2018) or using explicit solvers, e.g. Rk45, and computing the gradients thanks to the backpropagation, see (Onken & Ruthotto, 2020). To compute eq. (10), we rely on a temporal sampling of $X$: our datasets are composed of $n$ sequences of observations of length $N$, $X^i = (X_{t_0}^i, \ldots, X_{t_0+N\Delta t}^i)$, where each sequence $X^i$ follows eq. (2) and corresponds to one initial condition $X_{t_0}^i$. We then sample the space of initial conditions $X_{t_0}^i$ to compute a Monte-Carlo approximation to $\mathrm{d}_\phi(\phi_h, \phi_f)$. Let ODESolve be the function integrating any arbitrary initial state $x_{t_0}$ up to time $t$ with dynamics $h$, so that $x_t = \text{ODESolve}(x_{t_0}, h, t)$. The estimate of $\mathrm{d}_\phi(\phi_h, \phi_f)$ then writes as:

$$\mathrm{d}_\phi(\phi_h, \phi_f) \approx \frac{1}{n} \sum_{i=1}^n \sum_{j=1}^N \left\| \text{ODEsolve}(X_{t_0}^i, h, t_j) - X_{t_j}^i \right\|_2$$

Note that the way to compute ODEsolve differs across the experiments (see section 4).

### 3.3 THEORETICAL ANALYSIS FOR A LINEAR APPROXIMATION

We investigate the validity of our proposition when approximating an unknown derivative with an affine function (interpretable first guess approximators). We here consider $h_k$ as a linear function. We do not assume any information on $f$, thus relieving this section from the need of an accurate prior knowledge $f_k$. In this context, we show the convergence of the learning scheme introduced in Algorithm 1 with $\ell = \mathrm{d}(h_k, f)$, hence demonstrating the validity of our framework in this simplified setting. For more complex cases, for which theoretical analysis cannot be conducted, our framework is validated experimentally in section 4. All proofs of this section are conducted using the distance $\mathrm{d}_\phi$. Let $X^s$ be the unique solution to the initial value problem:

$$\frac{dX_t}{dt} = f(X_t) \quad \text{with} \quad X_{t=0} = X_0 \qquad (11)$$

With $h_k(X) = AX$ and $h_u(X) = D_A$, the affine approximation of $f$ writes as:

$$\frac{dX_t}{dt} = AX_t + D_A \quad \text{with} \quad X_{t=0} = X_0 \qquad (12)$$

where $A \in \mathcal{M}_{p,p}(\mathbb{R})$, $D_A \in \mathbb{R}^p$. We write $X^D$ the solution to eq. (12) and $X^A$ the solution to eq. (12) when $D_A = 0$. The alternate projection algorithm with the distance $\mathrm{d}_\phi$ writes as:

$$\hat{A} = \arg\min_A \int_{t_0}^t \left\| X^s(\tau) - X^D(\tau) \right\|_2 d\tau + \lambda_A \int_{t_0}^t \left\| X^s(\tau) - X^A(\tau) \right\|_2 d\tau \qquad (13)$$

$$\hat{D}_A = \arg\min_{D_A} \int_{t_0}^t \left\| X^s(\tau) - X^D(\tau) \right\|_2 d\tau + \lambda_D \|D_A\|_2 \qquad (14)$$

where $\lambda_D, \lambda_A > 0$. As the optimization of eq. (13) is not convex on $A$, the solution existence and uniqueness is not ensured. The well-posedness w.r.t $A$ can be recovered by instead considering a simple discretization scheme, e.g. $X_{t+1} \approx (AX_t + D_A)\Delta t + X_t$ and solving the associated least square regression, which well-posedness is guaranteed, see details in appendix D.2. Such strategy is common practice in system identification. Generic theoretical considerations on existence and uniqueness of solutions to eqs. (13) and (14) are hard to retrieve. Nonetheless, if $A$ is an invertible matrix, we prove in appendix D.4:

**Proposition 2** (Existence and Uniqueness). *If $\hat{A}$ is invertible, There exists a unique $D_A$, hence a unique $X^D$, solving eq. (14).*

Finally, formulating Algorithm 1 as a least square problem in an affine setting (see appendix D.5), we prove the convergence of the alternate projection algorithm (appendix D.6) :

**Proposition 3.** *For $\lambda_D$ and $\lambda_A$ sufficiently high, the algorithm that alternates between the estimation of $A$ and the estimation of $D_A$ following eqs. (13) and (14) converges.*

## 4 EXPERIMENTS

We validate Algorithm 1 on datasets of increasing difficulty (see appendix E), where the system state is either fully or partially observed (resp. section 4.1 and section 4.2). We no longer rely on an affine prior and explicit $h_k$ and $h_u$ for each dataset. Performances are evaluated via standard metrics: MSE (lower is better) and relative Mean Absolute Error (rMAE, lower is better). We assess the relevance of our proposition based on eqs. (4) and (5), against NeuralODE (Chen et al., 2018) and state of the art Aphynity (Yin et al., 2021) and ablation studies. We denote Ours eq. (4) (resp. Ours eq. (5)) the results when $\ell = \mathrm{d}(h_k, f)$ i.e eq. (4), (resp. $\ell = \mathrm{d}(h_k, f_k^{pr})$ i.e. eq. (5)) When $\mathrm{d}(h_k, f)$ (resp. $\mathrm{d}(h_u, 0)$) is not considered in the optimization, we refer to the results as $\mathrm{d}(h, f) + \mathrm{d}(h_u, 0)$ (resp. $\mathrm{d}(h, f) + \mathrm{d}(h_k, f)$). When $h$ is trained by only minimizing the discrepancy between actual and predicted trajectories the results are denoted «Only $\mathrm{d}(h, f)$». We report between brackets the standard deviation of the metrics over 5 runs and refer to Appendices F and G for training information and additional results. Code and datasets will be provided upon acceptance.

### 4.1 FULLY OBSERVABLE DYNAMICS

To illustrate the learning scheme induced by eq. (4), we focus on fully observed low dimensional dynamics: a simple example emerging from Newtonian mechanics and a population dynamics model.

**Damped Pendulum (DPL)** Now a standard benchmark for hybrid models, we consider the motion of a pendulum of length $L$ damped due to viscous friction (Greydanus et al., 2019; Yin et al., 2021). Newtonian mechanics provide an ODE describing the evolution of the angle $x$ of the pendulum:

$$\ddot{x} - g/L\sin(x) + k\dot{x} = 0 \tag{15}$$

We suppose access to observations of the system state $Z = (x, \dot{x})$. We consider as physical motion hypothesis $h_k(x, \theta_k) = \theta_k \sin(x)$. The true pulsation $\theta^* = g/L$ of the pendulum has to be estimated with $\theta_k$. The viscous friction term $k\dot{x}$ remains to be estimated by $h_u$.

**Population Dynamics (LV)** Lotka-Volterra ODE system models a prey/predator population dynamics describing the growth of the preys ($x$) without predators ($y$), and the extinction of predators without preys, the non linear terms expressing the encounters between both species:

$$\dot{x} = \alpha x - \beta xy, \quad \text{and} \quad \dot{y} = -\gamma y + \delta xy \tag{16}$$

We observe the system state $Z = (x, y)$ and set as prior knowledge: $h_k(x, y) = (\theta_k^1 x, -\theta_k^2 y)$. $\theta^\star = (\alpha, \gamma)$ has to be estimated by $\theta_k = (\theta_k^1, \theta_k^2)$. $h_u$ accounts for the non linear terms $(\beta xy, \delta xy)$.

**Experimental Setting** For both DPL and LV experiments, we consider the following setting: we sample the space of initial conditions building 100/50/50 trajectories for the train, validation and test sets. The sequences share the same parameters; respectively $(\frac{g}{L}, k)$, for DPL, and $(\alpha, \beta, \gamma, \delta)$ for LV. The parameter $\theta_k$ is set to a neuron (of dimension 1 in the pendulum and 2 for LV) and $h_u$ is a 2-layer MLP. Further experimental details are available in appendices E.1, E.2 and F.

Table 1: Experimental Results for PDL and LV data. The presented metric for parameter evaluation is the rMAE reported in %. Pred. columns report the prediction log MSE on trajectories on test set.

| Model | PDL | | LV | |
|---|---|---|---|---|
| | rMAE$(\theta_k, \theta^\star)$ | Pred. logMSE | rMAE$(\theta_k, \theta^\star)$ | Pred. logMSE |
| Ours eq. (4) | **1.56 (0.009)** | **-13.7 (0.84)** | **7.80 (0.011)** | -9.28 (0.75) |
| Only d$(h, f)$ | 9.35 (0.04) | -13.3 (0.65) | 24.5 (0.017) | -9.21 (0.91) |
| d$(h, f)$ + d$(h_k, f)$ | 1.82 (0.01) | -13.4 (0.56) | 7.91 (0.02) | -9.01 (0.99) |
| d$(h, f)$ + d$(h_u, 0)$ | 11.1 (0.03) | -12.9 (0.29) | 9.80 (0.098) | -9.45 (0.55) |
| Aphynity | 6.15 (0.009) | -12.2 (0.13) | 21.1 (0.016) | **-9.89 (0.53)** |

**Identification and Prediction Results** Table 1 shows that despite accurate trajectory forecasting, the unconstrained setting «Only d$(h, f)$» fails at estimating the models parameters, showing the need for regularization for identification. Constraining the norm of the ML component can be insufficient: for LV data, both Aphynity and d$(h, f)$ + d$(h_u, 0)$ do not accurately estimate the model parameters. However, the control of d$(h_k, f)$, following eq. (4), significantly improves the parameter identification for both datasets. Indeed, in the PDL case, $h_k$ and $f$ are (pseudo)-periodic of the same period, hence the gain in the performances. Finally, our proposition based on eq. (4) is able to identify the parameters of DPL and LV equation with a precision of respectively $1.56\%$ and $7.8\%$ beating all consid-

Figure 1: Affine Case : Evolution of the MSE between estimated dynamics $(\hat{A}, \hat{D})$ and the true one $(A, D)$ with the number of gradients steps for linearized DPL.

ered baselines. Regarding prediction performances, in under-constrained settings ( «Only d$(h, f)$» in Table 1), $h_u$ learns to corrects the inaccurate $h_k$. Table 1 and figs. 4 and 5 (appendix G.1) show that our proposition provides more consistent prediction performances. These experiments confirm that the constraints on $h_k$ and $h_u$ arising from the control of the upper bound of eq. (4) increase interpretability and maintain prediction performances.

**Throwback to the Affine Case** We verify the convergence proved in section 3.3 using the damped pendulum (eq. (15)) linearized in the small oscillations regime (see appendix E.1). Making an affine hypothesis following eq. (12), we apply our alternate projection algorithm and optimize $A$ and $D_A$ alternately using SGD. Figure 1 shows that we are able to accurately estimate $A$ and $D$ using our proposition, recovering both the oscillation pulsation and the damping coefficient.

## 4.2 HIGH DIMENSIONAL DYNAMICS

We now address the learning of transport equations, describing a wide range of physical phenomena such as chemical concentration, fluid dynamics or material properties. We evaluate the learning setting induced by eq. (4) and (5) on two physical datasets depicting the evolution of the temperature $T$ advected by a time-dependent velocity field $U$ and subject to forcing $S$, following:

$$\frac{\partial T}{\partial t} + \nabla.(TU) = S(U) \tag{17}$$

The system state $Z = (T, U, S)$ is partially observed, we only access $T$. Every quantities, observed or to estimate, are regularly sampled on a spatiotemporal grid: at each timestep $t$, the time varying velocity field $U_t$ writes as $U_t = (u_t, v_t)$ and $u_t, v_t, T_t$ and the forcing term $S_t$ are all of size $64 \times 64$.

**Experimental Setting** We consider as physical prior the advection i.e $h_k(T, \theta_k) = -\nabla.(T\theta_k)$. Thus, $\theta_k$ is time-dependent, as we learn it to approximate $\theta^\star = U$. We identify the velocity field $\theta_k$ from observations of $T$, learning a mapping between $T$ and $U$ parameterized by a neural network $G_\psi$, so that $\theta_k = G_\psi(T_{t-l}, ..., T_t) \approx U_t$, which is common practice in oceanography (Béréziat & Herlin, 2015). $G_\psi$ is optimized following eq. (9). $S$ remains to be learned by $h_u$. $h_k$ implements a differentiable semi-Lagrangian scheme (Jaderberg et al., 2015) (see appendix E.3) and $h_u$ is a ResNet. $G_\psi$ is a UNet. Training details and a schema of our model are to be found in appendix F.

Table 2: Results for Adv+S and Natl data. We report the MSE ($\times$ 100) on the predicted observations $T$, the velocity fields $U$ and the source term $S$ over 6 time steps on test set.

| Models | Adv+S | | | Natl | | |
|---|---|---|---|---|---|---|
| | $T$ | $U$ | $S$ | $T$ | $U$ | $S$ |
| Ours eq. (4) | **0.74 (0.05)** | **1.99 (0.13)** | **0.17 (0.01)** | 8.27 (0.06) | 11.72 (0.07) | 6.01 (0.08) |
| Ours eq. (5) | – | – | – | **6.86 (0.12)** | **6.81 (0.07)** | **4.35 (0.11)** |
| Aphynity | 0.85 (0.35) | 3.07 (0.74) | 0.18 (0.05) | 8.18 (0.16) | 11.75 (0.49) | 6.02 (0.02) |
| NODE | 1.35 (0.02) | – | – | 8.83 (0.98) | – | – |

**Synthetic Advection and Source (Adv+S)**    To test the applicability of the learning setting induced by eq. (4) on partially observed settings, we first study a synthetic setting (denoted Adv+S) of eq. (17) by generating velocity fields $U$, simulated following (Boffetta et al., 2001) and adding a source term $S$ inspired by (Frankignoul, 1985). The simulation details are given in appendix E.3.

**Real Ocean Dynamics (Natl)**    We consider a complex dataset emulating real world observations of the North ATLantic ocean (denoted Natl) (Ajayi et al., 2019). Modeling the evolution of $T$ in Natl is particularly challenging as its dynamics is chaotic and highly non-linear. This simulation is representative of the complexity encountered in real world data. The principled approach corresponding to eq. (4) is insufficient here and one must resort to additional physical information. To illustrate the extension developed in section 4.2,

Figure 2: *Best viewed in color*. Estimations of $S$, $T$ and $U = (u, v)$ on Adv+S. Prediction ranges from 1 to 20 half-days.

we make use of available auxiliary data: measurements from satellite observations provide a coarse estimate of the surface ocean currents velocity fields (see appendix E). Then, the learning goal is to refine the approximated velocity fields to fit the ocean dynamics. Therefore we proceed as described in eq. (5) and enforce $\mathrm{d}(h_k, f_k^{pr})$ by supervising $G_\psi$ with the proxy data (see appendix E.3).

**Identification and Prediction Results**    Table 2 indicates that for Adv+S dataset, we estimate accurately the unobserved velocity fields. Qualitatively, Figure 2 shows that controlling our proposed upper bound eq. (4) facilitates the recovery of truthful velocity fields $U$ along with an accurate prediction of $T$. For the highly complex Natl, Table 2 shows that the introduction of auxiliary data following the formulation in eq. (5) significantly helps identification, as the dynamics is too complex to be able to recover physically interpretable velocity fields using the bound of eq. (4).
Regarding prediction performances on the Adv+S data, Table 2 shows that thanks to our truthful estimates of $U$, our model provides more precise prediction than NODE and Aphynity. For real world data, thanks to the proxy data our model recovers better velocity fields terms while providing a better estimate for $T$. Besides, adding prior knowledge in the prediction systems improves prediction performances: appendix G shows that NODE minimizes $\mathrm{d}(h, f)$ by predicting average and blurred frames. This shows the need for regularization when learning on structured physical data.

**Ablation Study**    We present in Table 3 an ablation study on the Adv+S dataset evidencing the influence of our learning choices on the resolution of both identification and prediction tasks (see appendix G for detailed results). "Joint" rows of Table 3 indicate that the learning of $h_u$ and $h_k$ is done simultaneously. As shown in Table 3, the sole optimization of $\mathrm{d}(h, f)$ fails at estimating physically sounded $U$. This evidences the ill-posedness in such unconstrained optimization. Table 3 indicates that all introduced regularizations improve the recovery of $U$ w.r.t. the «Only $\mathrm{d}(h, f)$» baseline, while adding $\mathrm{d}(h_u, 0)$ significantly improves both prediction performances and velocity fields estimation. We highlight that the alternate optimization performs better compared to optimiz-

ing jointly all parameters of $h_k$ and $h_u$. Notably, our proposition to optimize $h_k$ and $h_u$ alternately beats all baselines on both $T$ prediction and $U$ identification (Table 3, Joint rows). Finally, jointly trained models fail at estimating $U$ in Table 3, forcing $h_u$ to capture the whole dynamics.

Table 3: Ablation Study on Adv+S. We report the MSE ($\times$ 100) on the predicted observations $T$, the velocity fields $U$ and the source term $S$ over 6 time steps. "Joint" rows refer to the simultaneous optim. of $h_k$ and $h_u$.

| Training | Models | $T$ | $U$ | $S$ |
|---|---|---|---|---|
| | Ours ($U$ known) | 0.52 | n/a | 0.19 |
| Alternate | Ours eq. (4) | **0.74 (0.05)** | **1.99 (0.13)** | **0.17 (0.01)** |
| | Only $\mathrm{d}(h, f)$ | 1.02 (0.16) | 4.08 (0.23) | 0.19 (0.06) |
| | $\mathrm{d}(h, f) + \mathrm{d}(h_k, f)$ | 1.02 (0.09) | 3.66 (0.15) | 0.19 (0.03) |
| | $\mathrm{d}(h, f) + \mathrm{d}(h_u, 0)$ | 0.77 (0.06) | 2.38 (0.17) | 0.19 (0.01) |
| Joint | Ours eq. (4) | 1.44 (0.08) | 3.30 (0.18) | 0.30 (0.03) |
| | Only $\mathrm{d}(h, f)$ | 1.38 (0.19) | 6.96 (0.21) | 0.39 (0.08) |

## 5 RELATED WORK

Grey-box or hybrid modeling, combining ODE/PDE and data based models, has received an increasing focus in the machine learning community (Rico-Martinez et al., 1994; Thompson & Kramer, 1994; Raissi et al., 2020b). Hybrid approaches allow for alleviated computational costs for fluid simulation (Tompson et al., 2017; De Avila Belbute-Peres et al., 2020; Wandel et al., 2021), and show better prediction performances through data specific constraints that preserve physics (Raissi et al., 2020a; Jia et al., 2019). They offer increased interpretability via constraints on convolutional filters (Long et al., 2018; 2019) or on learned residual (Geneva & Zabaras, 2020). Physical knowledge, introduced through ODE/PDE regularization (Psichogios & Ungar, 1992; Bongard & Lipson, 2007; de Bézenac et al., 2018) or Hamiltonian priors (Greydanus et al., 2019; Lee et al., 2021), increases generalization power w.r.t pure ML approaches. Closer to our work, (Mehta et al., 2020; San & Maulik, 2018; Young et al., 2017; Saha et al., 2020) study the learning of a physical model augmented with a statistical component. Yin et al. (2021) tackle the same task, ensuring the uniqueness in the decomposition by constraining the norm of the ML component. We generalize latter approaches and address the well-posedness in the learning of hybrid ML/MB models through additional regularization on the estimated parameters of the physical part. Indeed, to describe natural phenomena relying on hybrid MB/ML models, one major task lies in the estimation of the MB part parameters. This can be done using neural networks (Raissi et al., 2019; Mehta et al., 2020). However, identification tasks being intrinsically ill-posed (Sabatier, 2000), imposing prior knowledge or regularization is necessary to ensure sound estimations (Stewart & Ermon, 2017). Yet, using only prediction as supervision, the recovered parameters are not physically interpretable (de Bézenac et al., 2018; Ayed et al., 2020). To ensure uniqueness of the estimation solution, Ardizzone et al. (2018) use invertible neural networks. Linial et al. (2021); Tait & Damoulas (2020); Saemundsson et al. (2020) combine variational encoding (Kingma & Welling, 2013) and a PDE model, sampling the space of initial conditions and parameters to solve both identification and prediction. However, such methods only deal with low-dimensional dynamics. Besides low dimensional systems, we also show the soundness of our approach on complex high dimensional and partially observed dynamics.

## 6 DISCUSSION

We propose in this work an algorithm to learn hybrid MB/ML models. For interpretability purposes, we impose constraints flowing from an upper bound of the prediction error and derive a learning algorithm in a general setting. We prove its well posedness and its convergence in a linear approximation setting. Besides theoretical considerations, we empirically evidence the soundness of our approach thanks to ablation studies and comparison with recent baselines on several low and high dimensional datasets. This work can see several extensions, e.g. considering non uniform 3-D grid for climate models, further considerations on the investigated upper bounds, or less restrictive decomposition hypothesis.

REFERENCES

Adekunle Ajayi, Julien Le Sommer, Eric Chassignet, Jean-Marc Molines, Xiaobiao Xu, Aurelie Albert, and Emmanuel Cosme. Spatial and temporal variability of north atlantic eddy field at scale less than 100km. *Earth and Space Science Open Archive*, pp. 28, 2019. doi: 10.1002/essoar.10501076.1.

Lynton Ardizzone, Jakob Kruse, Carsten Rother, and Ullrich Köthe. Analyzing inverse problems with invertible neural networks. In *International Conference on Learning Representations*, 2018.

Ibrahim Ayed, Emmanuel de Bézenac, Arthur Pajot, and Patrick Gallinari. Learning the spatio-temporal dynamics of physical processes from partial observations. In *ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 3232–3236, 2020.

Filipe de Avila Belbute-Peres, Thomas Economon, and Zico Kolter. Combining differentiable pde solvers and graph neural networks for fluid flow prediction. In *International Conference on Machine Learning*, pp. 2402–2411. PMLR, 2020.

Dominique Béréziat and Isabelle Herlin. Coupling dynamic equations and satellite images for modelling ocean surface circulation. *Communications in Computer and Information Science*, 550: 191–205, 2015. doi: 10.1007/978-3-319-25117-2\_12. URL https://hal.inria.fr/hal-01245369.

Guido Boffetta, G Lacorata, G Redaelli, and A Vulpiani. Detecting barriers to transport: a review of different techniques. *Physica D: Nonlinear Phenomena*, 159(1-2):58–70, 2001.

Josh Bongard and Hod Lipson. Automated reverse engineering of nonlinear dynamical systems. *Proceedings of the National Academy of Sciences*, 104(24):9943–9948, 2007.

Stephen Boyd, Stephen P Boyd, and Lieven Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

Jef Caers. *Modeling uncertainty in the earth sciences*. John Wiley & Sons, 2011.

Ricky T. Q. Chen, Yulia Rubanova, Jesse Bettencourt, and David Duvenaud. Neural ordinary differential equations. In Samy Bengio, Hanna Wallach, Hugo Larochelle, Kristen Grauman, Nicolò Cesa-Bianchi, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 6571–6583. Curran Associates, Inc., 2018.

PHILIPPE Courtier, J-N Thépaut, and Anthony Hollingsworth. A strategy for operational implementation of 4d-var, using an incremental approach. *Quarterly Journal of the Royal Meteorological Society*, 120(519):1367–1387, 1994.

Filipe De Avila Belbute-Peres, Thomas Economon, and Zico Kolter. Combining differentiable PDE solvers and graph neural networks for fluid flow prediction. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 2402–2411. PMLR, 13–18 Jul 2020. URL http://proceedings.mlr.press/v119/de-avila-belbute-peres20a.html.

Emmanuel de Bézenac, Arthur Pajot, and Patrick Gallinari. Deep learning for physical processes: Incorporating prior scientific knowledge. In *International Conference on Learning Representations*, 2018.

Michail Diamantakis. The semi-lagrangian technique in atmospheric modelling: current status and future challenges. In *Seminar on Recent Developments in Numerical Methods for Atmosphere and Ocean Modelling, 2-5 September 2013*, pp. 183–200, Shinfield Park, Reading, 2014. ECMWF, ECMWF. URL https://www.ecmwf.int/node/9054.

Jérôme Droniou. Intégration et Espaces de Sobolev à Valeurs Vectorielles. working paper or preprint, April 2001. URL https://hal.archives-ouvertes.fr/hal-01382368.

Peter D Dueben and Peter Bauer. Challenges and design choices for global weather and climate models based on machine learning. *Geoscientific Model Development*, 11(10):3999–4009, 2018.

U. Forssell and P. Lindskog. Combining semi-physical and neural network modeling: An example ofits usefulness. *IFAC Proceedings Volumes*, 30(11):767–770, 1997. ISSN 1474-6670. doi: https://doi.org/10.1016/S1474-6670(17)42938-7. URL https://www.sciencedirect.com/science/article/pii/S1474667017429387. IFAC Symposium on System Identification (SYSID'97), Kitakyushu, Fukuoka, Japan, 8-11 July 1997.

Claude Frankignoul. Sea surface temperature anomalies, planetary waves, and air-sea feedback in the middle latitudes. *Reviews of geophysics*, 23(4):357–390, 1985.

Lucile Gaultier, Jacques Verron, Jean-Michel Brankart, Olivier Titaud, and Pierre Brasseur. On the inversion of submesoscale tracer fields to estimate the surface ocean circulation. *Journal of Marine Systems*, 126:33–42, 2013.

Nicholas Geneva and Nicholas Zabaras. Modeling the dynamics of pde systems with physics-constrained deep auto-regressive networks. *Journal of Computational Physics*, 403:109056, 2020. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2019.109056. URL https://www.sciencedirect.com/science/article/pii/S0021999119307612.

Michael Ghil and Paola Malanotte-Rizzoli. Data assimilation in meteorology and oceanography. *Advances in geophysics*, 33:141–266, 1991.

Samuel Greydanus, Misko Dzamba, and Jason Yosinski. Hamiltonian neural networks. In Hanna Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché Buc, Emily Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 15379–15389. Curran Associates, Inc., 2019.

Douglas Hanahan and Robert A Weinberg. Hallmarks of cancer: the next generation. *cell*, 144(5): 646–674, 2011.

Phillip Isola, Jun-Yan Zhu, Tinghui Zhou, and Alexei A Efros. Image-to-image translation with conditional adversarial networks. *CVPR*, 2017.

Max Jaderberg, Karen Simonyan, Andrew Zisserman, and koray kavukcuoglu. Spatial transformer networks. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc., 2015. URL https://proceedings.neurips.cc/paper/2015/file/33ceb07bf4eeb3da587e268d663aba1a-Paper.pdf.

Xiaowei Jia, Jared Willard, Anuj Karpatne, Jordan Read, Jacob Zwart, Michael S Steinbach, and Vipin Kumar. Physics guided rnns for modeling dynamical systems: A case study in simulating lake temperature profiles. In *SIAM International Conference on Data Mining, SDM 2019*, SIAM International Conference on Data Mining, SDM 2019, pp. 558–566. Society for Industrial and Applied Mathematics Publications, 2019. doi: 10.1137/1.9781611975673.63.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Kenneth Lange, Joong-Ho Won, and Jason Xu. Projection onto Minkowski sums with application to constrained learning. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3642–3651. PMLR, 09–15 Jun 2019. URL http://proceedings.mlr.press/v97/lange19a.html.

François-Xavier Le Dimet and Olivier Talagrand. Variational algorithms for analysis and assimilation of meteorological observations: theoretical aspects. *Tellus A: Dynamic Meteorology and Oceanography*, 38(2):97–110, 1986.

Seungjun Lee, Haesang Yang, and Woojae Seong. Identifying physical law of hamiltonian systems via meta-learning. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=45NZvF1UHam.

Adrian S. Lewis and Jérôme Malick. Alternating projections on manifolds. *Mathematics of Operations Research*, 33(1):216–234, 2008. doi: 10.1287/moor.1070.0291.

Ori Linial, Neta Ravid, Danny Eytan, and Uri Shalit. Generative ode modeling with known unknowns. In *Proceedings of the Conference on Health, Inference, and Learning*, pp. 79–94, 2021.

Zichao Long, Yiping Lu, Xianzhong Ma, and Bin Dong. PDE-Net: Learning PDEs from data. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 3208–3216, Stockholmsmässan, Stockholm Sweden, July 2018. PMLR.

Zichao Long, Yiping Lu, and Bi Dong. PDE-Net 2.0: Learning PDEs from data with a numeric-symbolic hybrid deep network. *Journal of Computational Physics*, 399:108925, 2019.

Guolan Lu and Baowei Fei. Medical hyperspectral imaging: a review. *Journal of biomedical optics*, 19(1):010901, 2014.

Gurvan Madec. *NEMO ocean engine*. Note du Pôle de modélisation, Institut Pierre-Simon Laplace (IPSL), France, No 27, 2008.

Olivier Marti, Pascale Braconnot, J-L Dufresne, Jacques Bellier, Rachid Benshila, Sandrine Bony, Patrick Brockmann, Patricia Cadule, Arnaud Caubel, Francis Codron, et al. Key features of the ipsl ocean atmosphere model and its sensitivity to atmospheric resolution. *Climate Dynamics*, 34 (1):1–26, 2010.

Viraj Mehta, Ian Char, Willie Neiswanger, Youngseog Chung, Andrew Oakleigh Nelson, Mark D Boyer, Egemen Kolemen, and Jeff Schneider. Neural dynamical systems: Balancing structure and flexibility in physical prediction. *arXiv preprint arXiv:2006.12682*, 2020.

Derek Onken and Lars Ruthotto. Discretize-optimize vs. optimize-discretize for time-series regression and continuous normalizing flows. *arXiv preprint arXiv:2005.13420*, 2020.

Naomi Oreskes, Kristin Shrader-Frechette, and Kenneth Belitz. Verification, validation, and confirmation of numerical models in the earth sciences. *Science*, 263(5147):641–646, 1994.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. PyTorch: An imperative style, high-performance deep learning library. In Hanna Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché Buc, Emily Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8026–8037. Curran Associates, Inc., 2019.

Dimitris C. Psichogios and Lyle H. Ungar. A hybrid neural network-first principles approach to process modeling. *AIChE Journal*, 38(10):1499–1511, 1992. doi: https://doi.org/10.1002/aic.690381003. URL https://aiche.onlinelibrary.wiley.com/doi/abs/10.1002/aic.690381003.

Maziar Raissi, Paris Perdikaris, and George E Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378:686–707, 2019.

Maziar Raissi, Alireza Yazdani, and George Em Karniadakis. Hidden fluid mechanics: Learning velocity and pressure fields from flow visualizations. *Science*, 367(6481):1026–1030, 2020a. ISSN 0036-8075. doi: 10.1126/science.aaw4741. URL https://science.sciencemag.org/content/367/6481/1026.

Maziar Raissi, Alireza Yazdani, and George Em Karniadakis. Hidden fluid mechanics: Learning velocity and pressure fields from flow visualizations. *Science*, 367(6481):1026–1030, 2020b.

Markus Reichstein, Gustau Camps-Valls, Bjorn Stevens, Martin Jung, Joachim Denzler, Nuno Carvalhais, et al. Deep learning and process understanding for data-driven earth system science. *Nature*, 566(7743):195–204, 2019.

R Rico-Martinez, JS Anderson, and IG Kevrekidis. Continuous-time nonlinear signal processing: a neural network based approach for gray box identification. In *Proceedings of IEEE Workshop on Neural Networks for Signal Processing*, pp. 596–605. IEEE, 1994.

M-H Rio and R Santoleri. Improved global surface currents from the merging of altimetry and sea surface temperature data. *Remote sensing of Environment*, 216:770–785, 2018.

Pierre C Sabatier. Past and future of inverse problems. *Journal of Mathematical Physics*, 41(6): 4082–4124, 2000.

Steindor Saemundsson, Alexander Terenin, Katja Hofmann, and Marc Deisenroth. Variational integrator networks for physically structured embeddings. In *International Conference on Artificial Intelligence and Statistics*, pp. 3078–3087. PMLR, 2020.

Priyabrata Saha, Saurabh Dash, and Saibal Mukhopadhyay. Phicnet: Physics-incorporated convolutional recurrent neural networks for modeling dynamical systems. *arXiv preprint arXiv:2004.06243*, 2020.

Omer San and Romit Maulik. Machine learning closures for model order reduction of thermal fluids. *Applied Mathematical Modelling*, 60, 04 2018. doi: 10.1016/j.apm.2018.03.037.

Russell Stewart and Stefano Ermon. Label-free supervision of neural networks with physics and domain knowledge. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31, 2017.

Daniel J Tait and Theodoros Damoulas. Variational autoencoding of pde inverse problems. *arXiv preprint arXiv:2006.15641*, 2020.

Michael L Thompson and Mark A Kramer. Modeling chemical processes using prior knowledge and neural networks. *AIChE Journal*, 40(8):1328–1340, 1994.

Jonathan Tompson, Kristofer Schlachter, Pablo Sprechmann, and Ken Perlin. Accelerating Eulerian fluid simulation with convolutional networks. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 3424–3433. PMLR, 06–11 Aug 2017. URL http://proceedings.mlr.press/v70/tompson17a.html.

Kiwon Um, Robert Brand, Fei Yun, Philipp Holl, and Nils Thuerey. Solver-in-the-loop: Learning from differentiable physics to interact with iterative pde-solvers. In *Neural Information Processing Systems (NeurIPS)*, volume 33, pp. 6111–6122, 2020.

John von Neumann. *Functional Operators (AM-22), Volume 2: The Geometry of Orthogonal Spaces*. Princeton University Press, 1950. ISBN 978-1-4008-8189-5. doi: https://doi.org/10. 1515/9781400881895.

Nils Wandel, Michael Weinmann, and Reinhard Klein. Learning incompressible fluid dynamics from scratch - towards fast, differentiable fluid models that generalize. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=KUDUoRsEphu.

Jared Willard, Xiaowei Jia, Shaoming Xu, Michael Steinbach, and Vipin Kumar. Integrating physics-based modeling with machine learning: A survey. *arXiv preprint arXiv:2003.04919*, 2020.

Yuan Yin, Vincent Le Guen, Jérémie Dona, Emmanuel de Bezenac, Ibrahim Ayed, Nicolas Thome, and Patrick Gallinari. Augmenting Physical Models with Deep Networks for Complex Dynamics Forecasting. In *ICLR*, 2021.

Chih-Chieh Young, Wen-Cheng Liu, and Ming-Chang Wu. A physically based and machine learning hybrid approach for accurate rainfall-runoff modeling during extreme typhoon events. *Applied Soft Computing*, 53:205–216, 2017.