5th Symposium on Advances in Approximate Bayesian Inference, 2023  1–10

# SAMBA: Regularized Autoencoders perform Sharpness-Aware Minimization

## Abstract

Latent space smoothness is often associated with better sample quality in generative models. However, the theoretical understanding of smoothness-inducing regularizers, e.g., the gradient norm penalty on the decoder, is poorly understood. We leverage insights between variational inference and Sharpness-Aware Minimization (SAM) to connect gradient norm penalties to smoothness. We propose the deterministic SAM-Based Autoencoder (SAMBA) and show that its gradients are equivalent to the gradient-norm–penalized Regularized Autoencoder (RAE). We show experimentally on CIFAR10 that SAMBA is more flexible than the RAE and has better smoothness properties than VAEs.

## 1. Introduction

Latent Variable Models (LVMs) encode high-dimensional observations into a lower-dimensional latent manifold, from which *generative models* can create samples, e.g., images (Bishop, 2006; Murphy, 2012). Variational Inference (VI) is prevalent to learn LVMs. Since the data log-likelihood is often intractable, a variational approximation relies on an evidence lower bound (ELBO), e.g., in Variational Autoencoders (VAEs) (Kingma and Welling, 2014) To improve sample quality, several heuristics are used, such as smoothing the latent space (Gulrajani et al., 2017; Mescheder et al., 2018; Ghosh et al., 2020; Kumar et al., 2020; Karras et al., 2020; Kato et al., 2020). This can be accomplished, e.g., by a gradient norm penalty on the decoder (i.e., the generated sample is differentiated w.r.t. the latents). Ghosh et al. (2020) reason that such a regularizer smooths the latent space akin to the noise in VAEs. However, it is unclear why gradient-norm penalties work well. We rely on SAM (Foret et al., 2021), which posits a worst-case view on optimization, leading to a smoother loss surface by excluding sharp minima. The notion of smoothness and the connection between Mean Field Variational Inference (MFVI) and SAM (Ujváry et al., 2022) intuits our work to explain the mechanism of gradient norm penalties. We propose SAMBA (Figure 1), a *deterministic* AutoEncoder (AE), where SAM replaces the noise distribution and show that SAMBA and the RAE have the same gradients. We summarize our **contributions** as follows:

- We develop a deterministic SAM-Based Autoencoder (SAMBA) and show its equivalence to the RAE; thus, providing an explanation of why gradient norm penalties are beneficial in generative models.
- We demonstrate experimentally that traditional VAEs, our SAMBA, and the RAE each have mechanisms that affect the smoothness of the latent space.

Figure 1: Comparison of VAEs, the RAE and our SAMBA. All models use the same mean encoding $\mu_{\boldsymbol{z}|\boldsymbol{x}}$, but different decoder inputs: VAEs inject Gaussian noise ($\boldsymbol{\eta} \sim \mathcal{N}(\boldsymbol{0}_d, \mathbf{I}_d)$, where dim $\mathcal{Z} = d$); the RAE uses $\mu_{\boldsymbol{z}|\boldsymbol{x}}$; whereas SAMBA makes a SAM update (10), where $\boldsymbol{\eta}(\boldsymbol{\Sigma}_{SAM})$ is deterministic (8). VAEs optimize the ELBO (1), whereas the RAE and SAMBA a weighted sum of Kullback-Leibler Divergence (KL), MSE, and the decoder Jacobian's norm for the RAE (3). SAMBA calculates the MSE for the worst-case encoding

## 2. Background

**Variational Autoencoders (VAEs).** Since the data likelihood $p_{\boldsymbol{\theta}}(\boldsymbol{x})$ in deep LVMs is generally intractable, approximate objectives are required. Variational approximations (Struwe, 2000) rely on an approximate *(variational and stochastic)* posterior $q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})$ with parameters $\boldsymbol{\phi}$, mapping $\boldsymbol{x} \mapsto \boldsymbol{z}$, instead of the true $p_{\boldsymbol{\theta}}(\boldsymbol{z}|\boldsymbol{x})$, yielding a tractable evidence lower bound (ELBO) (Kingma and Welling, 2014; Rezende et al., 2014) on the data log-likelihood:

$$\text{ELBO}(\boldsymbol{x}, \boldsymbol{\theta}, \boldsymbol{\phi}) = \mathbb{E}_{q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})}\left[\log p_{\boldsymbol{\theta}}(\boldsymbol{x}|\boldsymbol{z})\right] - \text{KL}\left[q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})||p_0(\boldsymbol{z})\right], \quad (1)$$

comprising of a reconstruction term and a KL regularizer between the prior $p_0(\boldsymbol{z})$ and the encoder (Kingma and Welling, 2019), where $p_{\boldsymbol{\theta}}(\boldsymbol{x}|\boldsymbol{z})$ is the generative model.

VAEs (Kingma and Welling, 2014) rely on the variational approximation in (1) to train deep LVMs, where neural networks parametrize the *encoder* $q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})$ and the *decoder* $p_{\boldsymbol{\theta}}(\boldsymbol{x}|\boldsymbol{z})$. Gaussian distributions are a common choice: $p_0(\boldsymbol{z})$ is isotropic, the variational family of $q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})$ with parameters $\boldsymbol{\phi}$ is factorized with posterior means $\mu_k^{\boldsymbol{\phi}}(\boldsymbol{x})$ and variances $\sigma_k^{\boldsymbol{\phi}}(\boldsymbol{x})^2$ for the $k^{th}$ factor with a diagonal covariance $\boldsymbol{\Sigma}_{\boldsymbol{z}|\boldsymbol{x}}^{\boldsymbol{\phi}}$; and the decoder (with parameters $\boldsymbol{\theta}$) is isotropic Gaussian, conditioned on $\boldsymbol{z}$, with mean $\boldsymbol{f}(\boldsymbol{z})$, which simplifies (1) to (dim $\boldsymbol{x} = D$, dim $\boldsymbol{z} = d$):

$$\text{ELBO} = -\mathbb{E}_{q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})}\left[\|\boldsymbol{x} - \boldsymbol{f}(\boldsymbol{g}(\boldsymbol{x}))\|^2\right] - \frac{1}{2}\left[-\log\left|\boldsymbol{\Sigma}_{\boldsymbol{z}|\boldsymbol{x}}^{\boldsymbol{\phi}}\right| + \text{tr}\left(\boldsymbol{\Sigma}_{\boldsymbol{z}|\boldsymbol{x}}^{\boldsymbol{\phi}}\right) + \left\|\mu_{\boldsymbol{z}|\boldsymbol{x}}\right\|^2 + d\right]. \quad (2)$$

**Regularized Autoencoder (RAE)** Ghosh et al. (2020) derives the deterministic RAE from a VAE by setting $\boldsymbol{\Sigma}_{\boldsymbol{z}|\boldsymbol{x}}^{\boldsymbol{\phi}} = \alpha^2 \mathbf{I}_d : \alpha > 0$ and substituting noise injection with a regularizer on the decoder[1]. The authors argue that adding noise smooths the decoder (Sietsma and Dow, 1991; An, 1996) and the same can be achieved via a regularizer. They consider multiple options, such as $\ell_p$-regularization of the *decoder parameters* $\boldsymbol{\theta}$. Based on best practices (Gulrajani et al., 2017; Mescheder et al., 2018), they focus on penalizing the

---

1. Since the RAE is deterministic $\mu_{\boldsymbol{z}|\boldsymbol{x}}(\boldsymbol{x}) = \boldsymbol{z}$

decoder Jacobian's norm, i.e. $\|\mathbf{J}_f(z)\|$, yielding the loss $(\beta, \lambda > 0)$[2]:

$$\mathcal{L}_{RAE} = \mathbb{E}_{q_\phi(z|x)}\left[\|x - f(z)\|^2\right] + \frac{\beta}{2}\|z\|^2 + \lambda\|\mathbf{J}_f(z)\|. \tag{3}$$

Denoting the expected MSE as $\mathcal{L}$, assuming $\beta = 1$, and omitting $\|z\|^2$ (i.e., the KL), the gradient is

$$\nabla_\theta\mathcal{L}_{RAE} = \frac{\partial}{\partial\theta}\left[\mathcal{L}(z_0, \theta_0) + \lambda\|\mathbf{J}_f(z)\|\right]. \tag{4}$$

**Sharpness-Aware Minimization (SAM)** Foret et al. (2021) proposed the SAM optimizer to smooth the loss landscape to improve generalization. SAM can be thought as fitting a hyperball with radius $\rho$ according to a (weighted) $\ell_2$-norm[3] into the loss landscape. SAM requires two gradient steps to yield the worst-case loss within the hyperball: at the current parameter values $\Psi_0$; then after a gradient ascent step. For a loss function $\mathcal{L}$, original and perturbed model parameters $\Psi_0$, $\Psi$, the corresponding SAM-objective is:

$$\mathcal{L}_{\text{SAM}}(\Psi_0, \Sigma_{SAM}) = \max_{(\Psi-\Psi_0)^\top\Sigma_{SAM}^{-1}(\Psi-\Psi_0)\leq\rho}[\mathcal{L}(\Psi) - \mathcal{L}(\Psi_0)] + \mathcal{L}(\Psi_0), \tag{5}$$

where $\Sigma_{SAM}$ weighs specific directions by reshaping the hyperball to a hyperellipsoid—choices include, e.g., the Fisher information matrix (Kim et al., 2022). For small enough radius $\rho > 0$, $\mathcal{L}_{\text{SAM}}$ is approximately the original loss and a gradient norm penalty:

$$\mathcal{L}_{\text{SAM}}(\Psi_0, \Sigma_{SAM}) \approx \mathcal{L}(\Psi_0) + \rho\left\|\sqrt{\Sigma_{SAM}}\nabla_{\Psi_0}\mathcal{L}(\Psi_0)\right\| \tag{6}$$

The gradient of (5) w.r.t. $\Psi_0$ approximately yields:

$$\nabla_{\Psi_0}\mathcal{L}_{\text{SAM}}(\Psi_0, \Sigma_{SAM}) \approx \nabla_{\Psi_0}\mathcal{L}_{\text{SAM}}(\Psi_0 + \sqrt{\Sigma_{SAM}}\cdot\eta(\Psi_0, \Sigma_{SAM}, \rho)) \tag{7}$$

where $\eta(\Psi_0, \Sigma_{SAM}, \rho)$[4] is the normalized weighted gradient of $\mathcal{L}$ at $\Psi_0$:

$$\eta(\Psi_0, \Sigma_{SAM}, \rho) = \rho\frac{\sqrt{\Sigma_{SAM}}\nabla_{\Psi_0}\mathcal{L}(\Psi_0)}{\|\sqrt{\Sigma_{SAM}}\nabla_{\Psi_0}\mathcal{L}(\Psi_0)\|}. \tag{8}$$

**MFVI SAM** MFVI is a stochastic VI approach with fully factorized (Gaussian) distributions, and was connected to SAM by Ujváry et al. (2022). MFVI relies on samples drawn from a standard normal distribution $\eta \sim \mathcal{N}(\mathbf{0}_d, \mathbf{I}_d)$, which in $d$ dimensions concentrates in $\ell_2$-norm around the hypersphere with radius $\sqrt{d}$, i.e., $\|\eta\|_2 \approx \sqrt{d}$. With diagonal $\Sigma_{SAM}$, the loss gradients are approximately (using the reparametrization trick to express the factorized Gaussian with a standard normal and $\Sigma_{SAM}$) $\nabla_{\Psi_0}\mathcal{L}_{\text{MFVI}}(\Psi_0, \sqrt{\Sigma_{SAM}}) \approx \nabla_{\Psi_0}\mathcal{L}(\Psi_0 + \sqrt{\Sigma_{SAM}}\cdot\eta)$. Setting $\Sigma_{SAM} = \rho^2/d\cdot\mathbf{I}_d$, $\eta$ will be normalized to the hypersphere with the SAM radius $\rho$. Thus, we can upper bound the expected gradient in MFVI with the SAM gradient.

$$\mathbb{E}_{\eta\sim\mathcal{N}(\mathbf{0}_d, \mathbf{I}_d)}\nabla_{\Psi_0}\mathcal{L}\left[\Psi_0 + \frac{\rho\eta}{\sqrt{d}}\right] \leq \max_{\|\eta\|\leq\sqrt{d}}\nabla_{\Psi_0}\mathcal{L}\left[\Psi_0 + \frac{\rho\eta}{\sqrt{d}}\right] = \nabla_{\Psi_0}\mathcal{L}_{\text{SAM}}\left[\Psi_0, \frac{\rho^2}{d}\cdot\mathbf{I}_d\right]. \tag{9}$$

---

2. Note that Ghosh et al. (2020) uses both $\|\mathbf{J}_f(z)\|$ (Eq. 15) and $\|\mathbf{J}_f(z)\|^2$ (Sec. 3.1); we use $\|\mathbf{J}_f(z)\|$

3. Our analysis focuses on $p = 2$

4. We use $\eta$ for both the noise in VAEs and the normalized gradient in SAM since they are related, as shown by Ujváry et al. (2022)

## 3. Theory

Ujváry et al. (2022) connects MFVI and SAM, but they are agnostic to model architecture. The SAM objective approximately adds a gradient norm penalty to the original loss, and the same regularizer is present in the RAE (Ghosh et al., 2020). Thus, we design an AE with a SAM update, which connects the success of smoothing the decoder gradient to SAM.

### 3.1. SAM-Based Autoencoder (SAMBA)

We propose the deterministic SAMBA by substituting the noise distribution $\boldsymbol{\eta}$ with the SAM gradient ascent step (cf. Figure 1 for a comparison of VAEs, RAE, and SAMBA), i.e., we calculate $\boldsymbol{z}$ as ($\boldsymbol{\Sigma}_{SAM}$ is diagonal):

$$\boldsymbol{z} = \boldsymbol{\mu}_{\boldsymbol{z}|\boldsymbol{x}} + \sqrt{\boldsymbol{\Sigma}_{SAM}} \cdot \boldsymbol{\eta}\left(\boldsymbol{\theta}_0, \boldsymbol{\Sigma}_{SAM}, \sqrt{d}\right). \tag{10}$$

Instead of general parameters $\boldsymbol{\Psi}_0$, we use the decoder parameters $\boldsymbol{\theta}_0$. We experiment with learnable (as in a VAE) and fixed (as in the RAE) $\boldsymbol{\Sigma}_{SAM}$.

**Comparison to RAE.** By removing sampling, our model is **deterministic** and optimizes a worst-case bound on the ELBO. By invoking a second (SAM) gradient step, the reconstruction loss gives back (6), where fixing $\boldsymbol{\Sigma}_{SAM}$ to $\alpha^2 \mathbf{I}_d$ and $\sqrt{d} \cdot \alpha = \lambda$ yields the same gradient penalty as the RAE (cf. (11) in (Ghosh et al., 2020)). However, SAMBA can also learn $\boldsymbol{\Sigma}_{SAM}$. Thus, our model motivates the decoder Jacobian's norm penalty via SAM, elucidating why this strategy can be effective.

### 3.2. Gradient analysis

To show that the RAE and SAMBA are equivalent, we prove that the gradients w.r.t. $\boldsymbol{\phi}$, $\boldsymbol{\theta}$, and $\boldsymbol{z}$ of SAMBA have the form of a gradient-penalized reconstruction loss (i.e., the RAE loss)[5]. We denote $\mathbf{J}_{\boldsymbol{f}} := \nabla_{\boldsymbol{z}}\mathcal{L}$ and $\mathbf{H} := \nabla_{\boldsymbol{z}}^2\mathcal{L}$ and we mean $\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right) := \nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}\right)\big|_{\boldsymbol{z}_0}$. We calculate the gradients after the SAM step (10) and assume $\boldsymbol{\Sigma}_{SAM} = \alpha^2 \mathbf{I}_d$ and $\sqrt{d} \cdot \alpha = \lambda$. We use the following relation between the gradients of $\mathcal{L}_{\mathrm{SAM}}$ and a general loss $\mathcal{L}$:

$$\nabla_{\boldsymbol{z}}\mathcal{L}_{\mathrm{SAM}}\left(\boldsymbol{z}\right)\big|_{\boldsymbol{z}_0} = \nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0 + \rho\frac{\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right)}{\|\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right)\|}\right) \approx \nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right) + \rho\mathbf{H}\left(\boldsymbol{z}_0\right)\frac{\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right)}{\|\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right)\|} \tag{11}$$

$$= \nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right) + \rho\nabla_{\boldsymbol{z}}\|\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right)\| = \nabla_{\boldsymbol{z}}\left[\mathcal{L}\left(\boldsymbol{z}_0\right) + \rho\|\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right)\|\right] \tag{12}$$

$$= \nabla_{\boldsymbol{z}}\left[\mathcal{L}\left(\boldsymbol{z}_0\right) + \rho\|\mathbf{J}_{\boldsymbol{f}}\left(\boldsymbol{z}_0\right)\|\right] \tag{13}$$

With the approximation from above, the gradient w.r.t. $\boldsymbol{z}$ and $\boldsymbol{\phi}$ yields, respectively:

$$\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0 + \rho\frac{\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right)}{\|\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right)\|}\right) \approx \nabla_{\boldsymbol{z}}\left[\mathcal{L}\left(\boldsymbol{z}_0\right) + \rho\|\mathbf{J}_{\boldsymbol{f}}\left(\boldsymbol{z}_0\right)\|\right] \tag{14}$$

$$\frac{\partial\boldsymbol{z}}{\partial\boldsymbol{\phi}}\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0 + \rho\frac{\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right)}{\|\nabla_{\boldsymbol{z}}\mathcal{L}\left(\boldsymbol{z}_0\right)\|}\right) \approx \frac{\partial\boldsymbol{z}}{\partial\boldsymbol{\phi}}\nabla_{\boldsymbol{z}}\left[\mathcal{L}\left(\boldsymbol{z}_0\right) + \rho\|\mathbf{J}_{\boldsymbol{f}}\left(\boldsymbol{z}_0\right)\|\right] \tag{15}$$

---

5. Our analysis omits the KL term for brevity since both RAE and SAMBA use the same KL penalty

Figure 2: **Left:** latent space smoothness (measured by the log of the decoder Jacobian's norm) in VAEs and SAMBA for fixed $\alpha^2$. **Right:** validation loss (i.e., ELBO and $\mathcal{L}_{\text{SAMBA}}$). SAMBA has smoother gradients than the VAE when $\alpha^2 \leq 1\text{e}-2$, for a negligible increase in the loss. Error bars are calculated across 5 seeds.

**Gradient of decoder parameters $\boldsymbol{\theta}$.** For the gradient w.r.t. $\boldsymbol{\theta}$, the dependence of the reconstruction loss on $\boldsymbol{\theta}$ needs to be considered, i.e., $\mathcal{L} = \mathcal{L}(\boldsymbol{z}_0, \boldsymbol{\theta}_0)$. Thus, we calculate the gradients at $(\boldsymbol{z}_0; \boldsymbol{\theta}_0)$ for the SAM step, modify $\boldsymbol{z}$ according to (10), then differentiate again at this updated position for backpropagation. The gradient ascent step modifying $\boldsymbol{z}_0$ does not depend on $\boldsymbol{\theta}$ (we call `.detach()` on the gradients). Nonetheless, for $\mathcal{L}$ depends on $\boldsymbol{\theta}$, our approximation requires that $\boldsymbol{\theta}$ and $\boldsymbol{\theta}_0$ are sufficiently close, yielding:

$$\frac{\partial}{\partial \boldsymbol{\theta}} \mathcal{L}\left(\boldsymbol{z}_0 + \boldsymbol{\rho} \frac{\nabla_z \mathcal{L}(\boldsymbol{z}_0, \boldsymbol{\theta}_0)}{\|\nabla_z \mathcal{L}(\boldsymbol{z}_0, \boldsymbol{\theta}_0)\|}; \boldsymbol{\theta}_0\right) \approx \frac{\partial}{\partial \boldsymbol{\theta}}\left[\mathcal{L}(\boldsymbol{z}_0; \boldsymbol{\theta}_0) + \boldsymbol{\rho} \nabla_z \mathcal{L}(\boldsymbol{z}_0, \boldsymbol{\theta}_0)^\top \frac{\nabla_z \mathcal{L}(\boldsymbol{z}_0, \boldsymbol{\theta}_0)}{\|\nabla_z \mathcal{L}(\boldsymbol{z}_0, \boldsymbol{\theta}_0)\|}\right] \quad (16)$$

$$= \frac{\partial}{\partial \boldsymbol{\theta}}\left[\mathcal{L}(\boldsymbol{z}_0; \boldsymbol{\theta}_0) + \boldsymbol{\rho}\|\nabla_z \mathcal{L}(\boldsymbol{z}_0, \boldsymbol{\theta}_0)\|\right], \quad (17)$$

When $\mathcal{L}$ is the (expected) MSE, the gradients w.r.t. $\boldsymbol{\phi}$, $\boldsymbol{\theta}$, and $\boldsymbol{z}$ can be expressed as the derivative of $\mathcal{L}_{RAE}$, proving that SAMBA and the RAE are equivalent, and elucidating that the gradient-norm–penalized RAE can be thought of as implicitly using SAM.

## 4. Experiments

Our experiments use CIFAR10 to show the relationship between RAE and SAMBA. We hypothesize that the implicit regularization on the decoder gradient norm in VAEs (through noise injection) and in SAMBA (6), and the explicit gradient norm penalty in the RAE have similar effects. However, they differ in motivation, implementation, and flexibility.

**Setup.** We use Resnet-18 (He et al., 2016) as a backbone for all models, a batch size of 256, a learning rate of 1e−4, and the Adam optimizer (Kingma and Ba, 2014). The VAE baseline is Gaussian with diagonal $q_\phi(\boldsymbol{z}|\boldsymbol{x})$ and isotropic $p_\theta(\boldsymbol{x}|\boldsymbol{z})$. When the variance of $q_\phi(\boldsymbol{z}|\boldsymbol{x})$ is fixed, we use $\alpha^2 \mathbf{I}_d : \alpha^2 \in \{1; 1\text{e}-2; 1\text{e}-4; 1\text{e}-6\}$. Experiments with trainable encoder variance are in Appx. A.

**Results.** Comparing SAMBA to a Gaussian VAE (with fixed, diagonal encoder variance and $\boldsymbol{\Sigma}_{SAM}$, respectively), we observe that **when $\alpha^2 \leq 1\text{e}-2$, then $\|\mathbf{J}_f\|$ is smoother for SAMBA with a practically insignificant increase in the loss** (Figure 2). To

Figure 3: **Left:** latent space smoothness (measured by the log of the decoder Jacobian's norm) in the RAE and SAMBA for fixed $\alpha^2$. **Right:** reconstruction loss without the SAM step for a fair comparison. When setting the same regularizer strength, our method yields smoother gradients and a more stable loss. Error bars are calculated across 5 seeds.

elucidate the success of gradient norm penalties for smoothing the latent space, we connect the regularizer in the RAE to SAM by comparing SAMBA to the RAE with fixed isotropic $\boldsymbol{\Sigma}_{SAM}$ with $\lambda := \alpha \cdot \sqrt{d}$ (5 seeds each). Figure 2 shows that as $\alpha$ increases, $\mathcal{Z}$ gets smoother for both RAE and SAMBA, **our method yielding a smoother latent space**. However, **the reconstruction loss evaluated at** $\mu_{\boldsymbol{z}|\boldsymbol{x}}$ (i.e., without the SAM update for a fair comparison) **has a lower variance with SAMBA than with the RAE**.

## 5. Discussion

**Related work.** Ghosh et al. (2020) propose a deterministic RAE with a heuristic penalty on the decoder Jacobian's norm to induce smoothness, which Kumar and Poole (2020) connect to a *crude* approximation of a deterministic Gaussian AE. Kumar et al. (2020) show that the RAE objective arises as the lower bound on the log-likelihood objective of an injective probability flow. Our work can be seen as relating the smoothness-inducing aspect in AEs to SAM, relying on the MFVI–SAM connection of Ujváry et al. (2022), who establish the SAM gradient as an upper bound on the expected MFVI gradient. Möllenhoff and Khan (2022) relate SAM to Bayes via the Fenchel biconjugate, showing that SAM is the optimal convex relaxation of the Bayes objective. On the other hand, Chen et al. (2020) propose a VAEs for learning flat manifolds, where the authors constrain $\boldsymbol{\Sigma}^{\phi}_{\boldsymbol{z}|\boldsymbol{x}} := \alpha^2 \mathbf{I}_d$.

**Limitations.** Our gradient analysis, which shows that the gradient-norm–penalized RAE can be thought of as implicitly doing SAM, relies on first-order approximations, similar to (Kumar and Poole, 2020; Kumar et al., 2020); however, such approximations might not hold in every practical setting.

**Conclusion.** The *deterministic* SAM-Based Autoencoder (SAMBA) connects the notions of flatness from the (variational) AE and SAM literatures, theoretically motivating the gradient norm penalty in the RAE (Ghosh et al., 2020). Our analysis shows that SAMBA and the RAE have equivalent gradients, providing new insight into the inductive biases shaping the latent space in (variational) AEs, which is also supported by our experiments on CIFAR10.

# References

Guozhong An. The effects of adding noise during backpropagation training on a generalization performance. *Neural computation*, 8(3):643–674, 1996.

Christopher M Bishop. *Pattern Recognition and Machine Learning*, volume 4. Springer New York, 2006. doi: 10.1007/978-0-387-45528-0. URL https://doi.org/10.1007/978-0-387-45528-0.

Nutan Chen, Alexej Klushyn, Francesco Ferroni, Justin Bayer, and Patrick van der Smagt. Learning Flat Latent Manifolds with VAEs. *arXiv:2002.04881 [cs, stat]*, August 2020. URL http://arxiv.org/abs/2002.04881. arXiv: 2002.04881.

Pierre Foret, Ariel Kleiner, Hossein Mobahi, and Behnam Neyshabur. Sharpness-Aware Minimization for Efficiently Improving Generalization, April 2021. URL http://arxiv.org/abs/2010.01412. arXiv:2010.01412 [cs, stat].

Partha Ghosh, Mehdi S. M. Sajjadi, Antonio Vergari, Michael Black, and Bernhard Schölkopf. From Variational to Deterministic Autoencoders. *arXiv:1903.12436 [cs, stat]*, May 2020. URL http://arxiv.org/abs/1903.12436. arXiv: 1903.12436.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. *Advances in neural information processing systems*, 30, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 8110–8119, 2020.

Keizo Kato, Jing Zhou, Tomotake Sasaki, and Akira Nakagawa. Rate-Distortion Optimization Guided Autoencoder for Isometric Embedding in Euclidean Latent Space. *arXiv:1910.04329 [cs, stat]*, August 2020. URL http://arxiv.org/abs/1910.04329. arXiv: 1910.04329.

Minyoung Kim, Da Li, Shell X. Hu, and Timothy Hospedales. Fisher SAM: Information Geometry and Sharpness Aware Minimisation. In *Proceedings of the 39th International Conference on Machine Learning*, pages 11148–11161. PMLR, June 2022. URL https://proceedings.mlr.press/v162/kim22f.html. ISSN: 2640-3498.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P. Kingma and Max Welling. Auto-Encoding Variational Bayes. *arXiv:1312.6114 [cs, stat]*, May 2014. URL http://arxiv.org/abs/1312.6114. arXiv: 1312.6114.

Diederik P. Kingma and Max Welling. An Introduction to Variational Autoencoders. *Foundations and Trends® in Machine Learning*, 12(4):307–392, 2019. ISSN 1935-8237, 1935-8245. doi: 10.1561/2200000056. URL http://arxiv.org/abs/1906.02691. arXiv: 1906.02691.

Abhishek Kumar and Ben Poole. On Implicit Regularization in $\beta$-VAEs. *arXiv:2002.00041 [cs, stat]*, December 2020. URL http://arxiv.org/abs/2002.00041. arXiv: 2002.00041.

Abhishek Kumar, Ben Poole, and Kevin Murphy. Regularized Autoencoders via Relaxed Injective Probability Flow. *arXiv:2002.08927 [cs, stat]*, February 2020. URL http://arxiv.org/abs/2002.08927. arXiv: 2002.08927.

Lars Mescheder, Andreas Geiger, and Sebastian Nowozin. Which training methods for gans do actually converge? In *International conference on machine learning*, pages 3481–3490. PMLR, 2018.

Kevin P Murphy. *Machine learning: A probabilistic perspective*. MIT press, 2012.

Thomas Möllenhoff and Mohammad Emtiyaz Khan. SAM as an Optimal Relaxation of Bayes, October 2022. URL http://arxiv.org/abs/2210.01620. arXiv:2210.01620 [cs, math, stat].

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *Proceedings of the 31th International Conference on Machine Learning, ICML 2014, Beijing, China, 21-26 June 2014*, volume 32 of *JMLR Workshop and Conference Proceedings*, pages 1278–1286. JMLR.org, 2014.

Jocelyn Sietsma and Robert JF Dow. Creating artificial neural networks that generalize. *Neural networks*, 4(1):67–79, 1991.

Michael Struwe. *Variational Methods*, volume 991. Springer Berlin Heidelberg, 2000. ISBN 9783662041963, 9783662041949. doi: 10.1007/978-3-662-04194-9. URL https://doi.org/10.1007/978-3-662-04194-9.

Szilvia Ujváry, Zsigmond Telek, Anna Kerekes, Anna Mészáros, and Ferenc Huszár. Rethinking Sharpness-Aware Minimization as Variational Inference, October 2022. URL http://arxiv.org/abs/2210.10452. arXiv:2210.10452 [cs, stat].

# Appendix

## Appendix A. Experiments with trainable variance

Figure 4: **Left:** latent space smoothness (logarithm of the **weighted** decoder Jacobian's norm); **Center:** validation loss (i.e., ELBO for the VAE and $\mathcal{L}_{\text{SAMBA}}$ for SAMBA); **Right:** reconstruction terms (evaluated at $\mu_{\boldsymbol{z}|\boldsymbol{x}}$, i.e., without the SAM step for a fair comparison). The encoder variance and $\boldsymbol{\Sigma}_{SAM}$ are learned, showcasing the additional degree of freedom of our method compared to the RAE (which has fixed variance), leading to comparable performance as a VAE on CIFAR10. Since the $\boldsymbol{\Sigma}$ has different values at each step, we plot the weighted gradient norm, which might confound some of the differences. Error bars are calculated across 10 seeds

## Appendix B. Notation

**Acronyms**

**ELBO** evidence lower bound

**AE** AutoEncoder

**KL** Kullback-Leibler Divergence

**LVM** Latent Variable Model

**MFVI** Mean Field Variational Inference

**MSE** Mean Squared Error

**RAE** Regularized Autoencoder

**SAM** Sharpness-Aware Minimization
**SAMBA** SAM-Based Autoencoder

**VAE** Variational Autoencoder
**VI** Variational Inference

## Nomenclature

### Sharpness-Aware Minimization

$\boldsymbol{\eta}$ SAM normalized and weighted gradient

$\boldsymbol{\Sigma}_{SAM}$ SAM norm weighting parameter

$\boldsymbol{\rho}$ SAM hyberball radius

$\mathcal{L}_{\mathrm{SAMBA}}$ SAMBA loss

$\mathcal{L}_{\mathrm{SAM}}$ SAM loss

### Variational Autoencoders

$\boldsymbol{\phi}$ parameters of the variational posterior $q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})$

$\boldsymbol{\theta}$ parameters of the decoder $p_{\boldsymbol{\theta}}(\boldsymbol{x}|\boldsymbol{z})$

$\boldsymbol{\Sigma}_{\boldsymbol{z}|\boldsymbol{x}}^{\boldsymbol{\phi}}$ covariance matrix of $q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})$

$\mathcal{L}_{RAE}$ RAE loss function

$\mu_{\boldsymbol{z}|\boldsymbol{x}}$ mean encoder of the VAE, i.e., $\mathbb{E}_{\boldsymbol{z}\sim q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})}(\boldsymbol{z})$, mapping $\boldsymbol{x} \mapsto \boldsymbol{z}$

$p_0(\boldsymbol{z})$ latent prior distribution

$p_{\boldsymbol{\theta}}(\boldsymbol{z}|\boldsymbol{x})$ true posterior distribution of the decoded samples of the VAE, mapping $\boldsymbol{x} \mapsto \boldsymbol{z}$, parametrized by $\boldsymbol{\theta}$

$p_{\boldsymbol{\theta}}(\boldsymbol{x})$ marginal likelihood

$p_{\boldsymbol{\theta}}(\boldsymbol{x}|\boldsymbol{z})$ conditional distribution of the decoded samples of the VAE, mapping $\boldsymbol{z} \mapsto \boldsymbol{x}$, parametrized by $\boldsymbol{\theta}$

$q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})$ variational posterior of the VAE, mapping $\boldsymbol{x} \mapsto \boldsymbol{z}$ parametrized by $\boldsymbol{\phi}$

$\mu_k^{\boldsymbol{\phi}}(\boldsymbol{x})$ mean of $q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})$ in dimension $k$

$\sigma_k^{\boldsymbol{\phi}}(\boldsymbol{x})^2$ variance of $q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})$ in dimension $k$

$\boldsymbol{\Psi}$ neural network parameters

$\boldsymbol{f}$ decoder map $\mathcal{Z} \to \mathcal{X}$

$\boldsymbol{g}$ encoder map $\mathcal{X} \to \mathcal{Z}$

$\mathcal{L}_{\mathrm{MFVI}}$ MFVI loss

$\mathcal{L}$ loss function

### Algebra

$\alpha$ scalar field

$\mathbf{0}$ a vector of zeros

$\mathbf{H}$ Hessian matrix

$\mathbf{I}$ identity matrix

$\mathbf{J}$ Jacobian matrix

### Latents

$\boldsymbol{z}$ latent vector

$\mathcal{Z}$ latents

$d$ dimensionality of the latent space $\mathcal{Z}$

### Observations

$D$ dimensionality of the observation space $\mathcal{X}$

$\boldsymbol{x}$ observation vector

$\mathcal{X}$ observation space

### Probability theory

$\boldsymbol{\Sigma}$ covariance matrix