UNIFORM MANIFOLD APPROXIMATION WITH TWO-PHASE OPTIMIZATION

ABSTRACT

We present a dimensionality reduction algorithm called Uniform Manifold Approximation with Two-phase Optimization (UMATO), that aims to preserve both the global and local structures of high-dimensional data. Most existing dimensionality reduction algorithms have focused on only one of these two aspects, and this insufficiency can provide a biased view of data, leading to overlooking or misinterpreting important patterns in high-dimensional space. UMATO takes a two-phase optimization approach: global optimization to obtain the overall skeleton of data and local optimization to identify the regional characteristics of local areas. In our experiments with one synthetic and three real-world datasets, UMATO outperformed widely used baseline algorithms, such as PCA, t-SNE, UMAP, topological autoencoders and Anchor t-SNE, in terms of quality metrics and 2D projection results. We further discuss extensions to multi-phase optimization and the projection stability of UMATO.

1 INTRODUCTION

We present a novel dimensionality reduction method, Uniform Manifold Approximation with Two-phase Optimization (UMATO) to capture both the global and local structures of high-dimensional data. One effective way of understanding high-dimensional data in various domains is to reduce its dimensionality and investigate the projection on a lower-dimensional space. For example, in life sciences, reducing dimensionality is the most common way of analyzing single-cell data (Amir et al. (2013); Haghverdi et al. (2015); Krieg et al. (2018); Becht et al. (2019)), since visualization provides a deep understanding of the relationships both between and within tissues, which offers diverse perspectives to interpret the development, differentiation, and disease of individual cells (Benoist & Hacohen (2011); Bendall et al. (2012); Bendall & Nolan (2012)). Missing either of the two structures in projections could mislead the data interpretation, and create serious errors in the conclusion.

Most previous algorithms have mainly focused on preserving only one of the two structures of high-dimensional data; the global structures (i.e., the pairwise distances in a high-dimensional space) or the local structures (i.e., the relationships between neighboring points in a high-dimensional space); however, this can provide a biased view on the other aspect. For instance, t-Stochastic Neighbor Embedding (t-SNE, Maaten & Hinton (2008)), which adopts Kullback-Leibler (KL) divergence as its loss function, mainly focused on preserving the local structures of data at the cost of the projection fidelity of global structures. Meanwhile, topological autoencoders (Moor et al. (2020))—a generative model that produces a global structure in latent space by applying a topological constraint in its loss function—marginally reflect the local aspects of data.

To the best of our knowledge, Anchor t-SNE (At-SNE, Fu et al. (2019)) is the only method to consider the trade-off between global and local structures. It optimizes two different loss functions in turn, one for anchor points (i.e., the skeleton of manifolds), the centroids resulting from the k-means clustering algorithm, and the other for the rest. Nonetheless, At-SNE inherits the conventional limitations of t-SNE, naïvely applying KL divergence as its loss function; KL divergence exerts little effect on distant points in a high-dimensional space, leaving a meager impact beyond its coverage (Appendix B). Furthermore, in Anchor t-SNE, even the positions of anchor points are updated per iteration based on the location of points only in the same cluster, leading to a distortion in the previously captured global structures.

UMATO partitions the optimization process into two phases: global optimization and local optimization. We first generate the overall hierarchy of the data and then organize each part of the substructures. The latter phase attains regional characteristics without impairing the global structure obtained in the first phase. We leverage the cross-entropy loss function as in Uniform Manifold Approximation and Projection (UMAP, McInnes et al. (2018)), which is known to charge a penalty for points that are distant in the original space being close in the projection space and for points that are close in the original space being distant in the projection space (Appendix B). UMAP considers all points in the optimization at once with diverse sampling techniques (i.e., negative sampling and edge sampling), which causes the bias to concentrate more on the local than global aspect. In UMATO, we pick hubs so that they are good representatives that approximate the manifold in which the data resides. Selecting the hubs makes the global optimization faster as it runs with fewer points (i.e., hubs) and preserves the pairwise distances in the original space to the final projection due to the hub points' guidance which is introduced into the local optimization for all other points.

We compared UMATO with popular dimensionality reduction techniques including PCA, t-SNE, UMAP, topological autoencoders and At-SNE. We used one synthetic (101 dimensional spheres) and three real-world (MNIST, Fashion MNIST, and Kuzushiji MNIST) datasets and analyzed the projection results with several quality metrics. In conclusion, UMATO demonstrated better performance than the baseline techniques in all datasets in terms of KL_σ with different σ values, meaning that it reasonably preserved the density of data over diverse length scales. Finally, we presented the 2D projections of each dataset, including the replication of an experiment using the synthetic Spheres dataset introduced by Moor et al. (2020) where data points locally constitute multiple small balls globally contained in a larger sphere. Here, we demonstrate that UMATO can better preserve both structures compared to the baseline algorithms (top row of Figure 3).

2 RELATED WORK

Dimensionality reduction. Most previous dimensionality reduction algorithms focused on preserving the data's local structures. For example, Maaten & Hinton (2008) proposed t-SNE to visualize high-dimensional data through projection produced by performing stochastic gradient descent on the KL divergence between two density functions in the original and projection spaces. After that, grounded in Riemannian geometry and algebraic topology, McInnes et al. (2018) introduced UMAP as an alternative to t-SNE. Leveraging the cross-entropy function as its loss function, UMAP reduced the computation time by employing negative sampling from Word2Vec (Mikolov et al. (2013)) and edge sampling from LargeVis (Tang et al. (2015; 2016)) (Table 1). Moreover, they showed that UMAP can generate stable projection results compared to t-SNE over repetition.

On the other hand, there also exist algorithms that aim to capture the global structures of data. Global t-SNE (Zhou & Sharpee (2018)) converted the joint probability distribution, P, in the high-dimensional space from Gaussian to Student's-t distribution, and proposed a variant of KL divergence. By adding it with the original loss function of t-SNE, Global t-SNE assigns a relatively large penalty for a pair of distant data points in high-dimensional space being close in the projection space. Another example is topological autoencoders (Moor et al. (2020)), a deep-learning approach that uses a generative model to make the latent space resemble the high-dimensional space by appending a topological loss to the original reconstruction loss of autoencoders. However, they required a huge amount of time for hyperparameter exploration and training for a dataset, and only focused on the global aspect of data. Unlike other techniques that presented a variation of loss functions in a single pipeline, UMATO is novel as it preserves both structures by dividing the optimization into two phases; this makes it outperform the baselines with respect to quality metrics in our experiments.

Hubs, landmarks, and anchors. Many dimensionality reduction techniques have tried to draw sample points to better model the original space; these points are usually called hubs, landmarks, or anchors. Silva & Tenenbaum (2003) proposed Landmark Isomap, a landmark version of classical multidimensional scaling (MDS) to alleviate its computation cost. Based on the Landmark Isomap, Yan et al. (2018) tried to retain the topological structures (i.e., homology) of high-dimensional data by approximating the geodesic distances of all data points. However, both techniques have the limitation that landmarks were chosen randomly without considering their importance. UMATO uses a k-nearest neighbor graph to extract significant hubs that can represent the overall skeleton of high-dimensional data. The most similar work to ours is At-SNE (Fu et al. (2019)), which optimized the anchor points and all other points with two different loss functions. However, since the anchors

wander during the optimization and the KL divergence does not care about distant points, it hardly captures the global structure. UMATO separates the optimization process into two phases so that the hubs barely moves but guides other points so that the subareas manifest the shape of the high-dimensional manifold in the projection. Applying different cross-entropy functions to each phase also helps preserve both structures.

3 UMAP

Since UMATO shares the overall pipeline of UMAP (McInnes et al. (2018)), we briefly introduce UMAP in this section. Although UMAP is grounded in a sophisticated mathematical foundation, its computation can be simply divided into two steps, graph construction and layout optimization, a configuration similar to t-SNE. In this section, we succinctly explain the computation in an abstract manner. For more details about UMAP, please consult the original paper (McInnes et al. (2018)).

Graph Construction. UMAP starts by generating a weighted k-nearest neighbor graph that represents the distances between data points in the high-dimensional space. Given an input dataset $X = \{x_1, \ldots, x_n\}$, the number of neighbors to consider k and a distance metric $d : X \times X \to [0, \infty)$, UMAP first computes $\mathcal{N}_i$, the k-nearest neighbors of x_i with respect to d. Then, UMAP computes two parameters, ρ_i and σ_i, for each data point x_i to identify its local metric space. ρ_i is a nonzero distance from x_i to its nearest neighbor:

$$\rho_i = \min_{j \in \mathcal{N}_i} \{d(x_i, x_j) \mid d(x_i, x_j) > 0\}. \tag{1}$$

Using binary search, UMAP finds σ_i that satisfies:

$$\sum_{j \in \mathcal{N}_i} \exp(-\max(0, d(x_i, x_j) - \rho_i)/\sigma_i) = \log_2(k). \tag{2}$$

Next, UMAP computes:

$$v_{j|i} = \exp(-\max(0, d(x_i, x_j) - \rho_i)/\sigma_i), \tag{3}$$

the weight of the edge from a point x_i to another point x_j. To make it symmetric, UMAP computes $v_{ij} = v_{j|i} + v_{i|j} - v_{j|i} \cdot v_{i|j}$, a single edge with combined weight using $v_{j|i}$ and $v_{i|j}$. Note that v_{ij} indicates the similarity between points x_i and x_j in the original space. Let y_i be the projection of x_i in a low-dimensional projection space. The similarity between two projected points y_i and y_j is $w_{ij} = (1 + a\|y_i - y_j\|_2^{2b})^{-1}$, where a and b are positive constants defined by the user. Setting both a and b to 1 is identical to using Student's t-distribution to measure the similarity between two points in the projection space as in t-SNE (Maaten & Hinton (2008)).

Layout Optimization. The goal of layout optimization is to find the y_i that minimizes the difference (or loss) between v_{ij} and w_{ij}. Unlike t-SNE, UMAP employs the cross entropy:

$$C_{UMAP} = \sum_{i \neq j} [v_{ij} \cdot \log(v_{ij}/w_{ij}) - (1 - v_{ij}) \cdot \log((1 - v_{ij})/(1 - w_{ij}))], \tag{4}$$

between v_{ij} and w_{ij} as the loss function. UMAP initializes y_i through spectral embedding (Belkin & Niyogi (2002)) and iteratively optimize its position to minimize C_{UMAP}. Given the output weight w_{ij} as $1/(1 + ad_{ij}^{2b})$, the attractive gradient is:

$$\frac{C_{UMAP}^+}{y_i} = \frac{-2abd_{ij}^{2(b-1)}}{1 + ad_{ij}^{2b}} v_{ij}(y_i - y_j), \tag{5}$$

and the repulsive gradient is:

$$\frac{C_{UMAP}^-}{y_i} = \frac{2b}{(\epsilon + d_{ij}^2)(1 + ad_{ij}^{2b})} (1 - v_{ij})(y_i - y_j), \tag{6}$$

where ϵ is a small value added to prevent division by zero and d_{ij} is a Euclidean distance between y_i and y_j. For efficient optimization, UMAP leverages the negative sampling technique from Word2Vec (Mikolov et al. (2013)). After choosing a target point and its negative samples, the position of the target is updated with the attractive gradient, while the positions of the latter do so with

the repulsive gradient. Moreover, UMAP utilizes edge sampling (Tang et al. (2015; 2016)) to accelerate and simplify the optimization process (Table 1). In other words, UMAP randomly samples edges with a probability proportional to their weights, and subsequently treats the selected ones as binary edges. Considering the previous sampling techniques, the modified objective function is:

$$O = \sum_{(i,j) \in E} v_{ij}(\log(w_{ij}) + \sum_{k=1}^{M} E_{j_k \sim P_n(j)} \gamma \log(1 - w_{ij_k})). \tag{7}$$

Here, v_{ij} and w_{ij} are the similarities in the high and low-dimensional spaces respectively, M is the number of negative samples and $E_{j_k \sim P_n(j)}$ indicates that j_k is sampled according to a noisy distribution, $P_n(j)$, from Word2Vec (Mikolov et al. (2013)).

4 UMATO

Figure 2 illustrates the computation pipeline of UMATO, which delineates the two-phase optimization. As a novel approach, we split the optimization into global and local so that it could generate a low-dimensional projection keeping both structures well-maintained. We present the pseudocode of UMATO in Appendix A, and made the source codes of it publicly available[1].

4.1 POINTS CLASSIFICATION

In the big picture, UMATO follows the pipeline of UMAP. We first find the k-nearest neighbors in the same way as UMAP, by assuming the local connectivity constraint, i.e., no single point is isolated and each point is connected to at least a user-defined number of points. After calculating ρ (Equation 1) and σ (Equation 2) for each point, we obtain the pairwise similarity for every pair of points. Once the k-nearest neighbor indices are established, we unfold it and check the frequency of each point to sort them into descending order so that the index of the popular points come to the front.

Then, we build a k-nearest neighbor graph by repeating the following steps until no points remain unconnected: 1) choose the most frequent point as a hub among points that are not already connected, 2) retrieve the k-nearest neighbors of the chosen point (i.e., hub), and the points selected from steps 1 and 2 will become a connected component. The gist is that we divide the points into three disjoint sets: hubs, expanded nearest neighbors, and outliers (Figure 1). Thanks to the sorted indices, the most popular point in each iteration—but not too densely located—becomes the hub point. Once the hub points are determined, we recursively seek out their nearest neighbors and again look for the nearest neighbors of those neighbors, until there are no points to be newly appended. In

Figure 1: **Points classification using Spheres dataset.** Each point is classified into a hub (red circles), an expanded nearest neighbor (green squares), or an outlier (blue triangles). Best viewed in color.

other words, we find all connected points that are expanded from the original hub points, which, in turn, is called the expanded nearest neighbors. Any remaining point that is neither a hub point nor a part of any expanded nearest neighbors is classified as an outlier. As the characteristics of these classes differ significantly, we take a different approach for each class of points to obtain both structures. That is, we run global optimization for the hub points (Section 4.2), local optimization for the expanded nearest neighbors (Section 4.3), and no optimization for the outliers (Section 4.4). In the next section we explain each in detail.

4.2 GLOBAL OPTIMIZATION

After identifying hub points, we run the global optimization to retrieve the skeletal layout of the data. First, we initialize the positions of hub points using PCA, which makes the optimization process faster and more stable than using random initial positions. Next, we optimize the positions of hub points by minimizing the cross-entropy function (Equation 4). Let $P(X) = \{P(x_i, x_j) | x_i, x_j \in X\}$

---

[1]https://www.github.com/anonymous-author/anonymous-repo

(A) GLOBAL INIT (B) GLOBAL OPT (C) LOCAL INIT (D) FINAL RESULT

Figure 2: **An illustration of UMATO pipeline using 10,000 data points (101 dimensions) of the Spheres.** (A) UMATO first initializes hub points using PCA, (B) then optimize their positions using the cross entropy function. (C) Next, we embed the expanded nearest neighbors to the projection and optimize their positions using sampling techniques for acceleration. (D) Lastly, we append the outliers and achieve the final projection result. Best viewed in color.

and $Q(Y) = \{Q(y_i, y_j)|y_i, y_j \in Y\}$ be two adjacency matrices in high- and low-dimensional spaces. If X_h represents a set of points selected as hubs in high-dimensional space, and Y_h is a set of corresponding points in the projection, we minimize the cross entropy—$CE(P(X_h)||Q(Y_h))$— between $P(X_h)$ and $Q(Y_h)$.

UMAP computes the cross-entropy between all existing points using two sampling techniques, edge sampling and negative sampling, for speed (Table 1). However, this often ends up capturing only the local properties of data because of the sampling biases and thus it cannot be used for cases that require a comprehensive understanding of the data. On the other hand, in its first phase, UMATO only optimizes for representatives (i.e., the hub points) of data, which takes much less time but can still approximate the manifold effectively.

Table 1: **The runtime for each algorithm using MNIST dataset.** UMAP and UMATO take much less time than MulticoreT-SNE (Ulyanov (2016)) when tested on a Linux server with 40-core Intel Xeon Silver 4210 CPUs. The runtimes are averaged over 10 runs.

Algorithm	Runtime (s)
t-SNE	374.85 ± 11.38
UMAP	26.10 ± 3.97
UMATO	73.32 ± 8.39

4.3 LOCAL OPTIMIZATION

In the second phase, UMATO embeds the expanded nearest neighbors to the projection that is computed using only the hub points from the first phase. For each point in the expanded nearest neighbors, we retrieve its nearest m (e.g., 10) hubs in the original high-dimensional space and set its initial position in the projection to the average positions of the hubs in the projection with small random perturbations. We follow a similar optimization process as UMAP in the local optimization with small differences. As explained in Section 3, UMAP first constructs the graph structure; we perform the same task but only with the hubs and expanded nearest neighbors. While doing this, since some points are excluded as outliers, we need to update the k-nearest neighbor indices. This is fast because we recycle the already-built k-nearest neighbor indices by updating the outliers to the new nearest neighbor.

Once we compute the similarity between points (Equation 3), to optimize the positions of points, similar to UMAP, we use the cross-entropy loss function with edge sampling and negative sampling (Equation 7). Here, we try to avoid moving the hubs as much as possible since they have already formed the global structure. Thus, we only sample a point p among the expanded nearest neighbors as one end of an edge, while the point q at the other end of the edge can be chosen from all points except outliers. In UMAP implementation, when q pulls in p, p also drags q to facilitate the optimization (Equation 5). When updating the position of q, we only give a penalty to this (e.g., 0.1), if q is a hub point, not letting its position excessively be affected by p. In addition, because the repulsive force can disperse the local attachment, making the point veer off for each epoch and eventually destroying the well-shaped global layout, we multiply a penalty (e.g., 0.1) when calculating the repulsive gradient (Equation 6) for the points selected as negative samples.

4.4 OUTLIERS ARRANGEMENT

Since the isolated points, which we call outliers, mostly have the same distance to all the other data points in high-dimensional space, due to the curse of dimensionality, they both sabotage the global

structure we have already made and try to mingle with all other points, thus distorting the overall projection. We do not optimize these points but instead simply append them using the already-projected points (e.g., hubs or expanded nearest neighbors), that belong to each outlier's connected component of the nearest neighbor graph. That is, if $x_i \in C_n$ where x_i is the target outlier and C_n is the connected component to which x_i belongs, we find $x_j \in C_n$ that has already been projected and is closest to x_i. We arrange x_i using the position of x_j in the same component offset by a random noise. In this way, we can benefit from the comprehensive composition of the projection that we have already optimized when arranging the outliers. We can ensure that all outliers can find a point as its neighbor since we picked hubs from each connected component of the nearest neighbor graph and thus at least one point is already located and has an optimized position (Section 4.2).

5 EXPERIMENTS

We conducted experiments to evaluate UMATO's ability to capture the global and local structures of high-dimensional data. We compared UMATO with five baseline algorithms, PCA, t-SNE, UMAP, topological autoencoders, and At-SNE in terms of global (i.e., DTM and KL_σ) and local (i.e., trust-worthiness, continuity, and MRREs) quality metrics.

5.1 DATASETS

We used four datasets for the experiments: Spheres, MNIST (LeCun & Cortes (2010)), Fashion MNIST (Xiao et al. (2017)), and Kuzushiji MNIST (Clanuwat et al. (2018)). Spheres is a synthetic dataset that has 10,000 rows of 101 dimensions. It has a high-dimensional structure in which ten small spheres are contained in a larger sphere. Specifically, the dataset's first 5,000 rows are the points sampled from a sphere of radius 25 and 500 points are sampled for each of the ten smaller spheres of radius 5 shifted to a random direction from the origin. This dataset is the one used for the original experiment with topological autoencoders (Moor et al. (2020)). Other datasets are images of digits, fashion items, and Japanese characters, each of which consists of 60,000 784-dimensional (28×28) images from 10 classes.

5.2 EXPERIMENTAL SETTING

Evaluation Metrics. To assess how well projections preserve the global structures of high-dimensional data, we computed the density estimates (Chazal et al. (2011; 2017)), the so-called Distance To a Measure (DTM), between the original data and the projections. Moor et al. (2020) adopted the Kullback-Leibler divergence between density estimates with different scales (KL_σ) to evaluate the global structure preservation. To follow the original experimental setup by Moor et al. (2020), we found the projections with the lowest $\mathrm{KL}_{0.1}$ from all algorithms by adjusting their hyperparameters. Next, to evaluate the local structure preservation of projections, we used the mean relative rank errors (MRREs, Lee & Verleysen (2007)), trustworthiness, and continuity (Venna & Kaski (2001)). All of these local quality metrics estimate how well the nearest neighbors in one space (e.g., high- or low-dimensional space) are preserved in the other space. For more information on the quality metrics, we refer readers to Appendix D.

Baselines. We set the most widely used dimensionality reduction techniques as our baselines, including PCA, t-SNE (Maaten & Hinton (2008)), UMAP (McInnes et al. (2018)), and At-SNE (Fu et al. (2019)). In addition, we compared with topological autoencoders (Moor et al. (2020)) that were developed to capture the global properties of the data using a deep learning-based generative model. Following the convention of visualization in dimensionality reduction, we determined our result projected onto 2D space. We tuned the hyperparameters of each technique to minimize the $\mathrm{KL}_{0.1}$. Appendix E further describes the details of the hyperparameters settings.

5.3 QUANTITATIVE RESULTS

Table 2 displays the experiment results. For all datasets, UMATO had the lowest (best) $\mathrm{KL}_{0.1}$ and DTM, even compared to topological autoencoders that have been trained to minimize those metrics. Moreover, except for Kuzushiji MNIST, UMATO had the lowest or the second lowest DTM and KL_σ at all the given scales, which confirms that it better preserved the global aspect of high-dimensional data than the baselines. For local metrics, t-SNE and UMAP generally had the upper-hand, but UMATO showed comparable MRRE_X and continuity in Fashion MNIST and Kuzushiji MNIST datasets. Meanwhile, UMATO outperformed topological autoencoders and At-SNE with respect to

Table 2: **Quantitative results of UMATO and five baseline algorithms.** The hyperparameters of the algorithms are chosen to minimize $KL_{0.1}$. The best one is in bold and underlined, and the runner-up is in bold.

Dataset	Method	Global quality metrics				Local quality metrics			
		DTM	$KL_{0.01}$	$KL_{0.1}$	KL_1	Cont	Trust	$MRRE_X$	$MRRE_Z$
Spheres	PCA	0.9950	0.7568	0.6525	0.0153	0.7983	0.6088	0.7985	0.6078
	t-SNE	0.9116	0.6070	0.5365	0.0128	**0.8903**	**0.7073**	**0.9032**	**0.7261**
	UMAP	0.9209	0.6100	0.5383	0.0134	**0.8760**	0.6499	**0.8805**	0.6494
	TopoAE	**0.6890**	**0.2063**	0.3340	**0.0076**	0.8317	0.6339	0.8317	0.6326
	A*t*-SNE	0.9448	0.6584	0.5712	0.0138	0.8721	0.6433	0.8768	0.6424
	UMATO	**0.3888**	**0.1341**	**0.1434**	**0.0014**	0.7884	**0.6558**	0.7887	**0.6557**
Fashion MNIST	PCA	**0.2315**	**0.6929**	0.0454	**0.0006**	0.9843	0.9117	0.9853	0.9115
	t-SNE	0.2879	0.7889	0.0702	0.0021	0.9898	**0.9951**	0.9919	**0.9958**
	UMAP	0.2755	0.8396	0.0641	0.0016	**0.9950**	0.9584	**0.9955**	0.9584
	TopoAE	0.2329	0.7301	**0.0446**	**0.0008**	0.9908	0.9591	0.9913	0.9590
	A*t*-SNE	0.2973	0.8389	0.0702	0.0017	0.9826	**0.9847**	0.9849	**0.9848**
	UMATO	**0.2035**	**0.6852**	**0.0342**	**0.0008**	0.9911	0.9500	**0.9919**	0.9502
MNIST	PCA	0.4104	1.4981	0.1349	0.0014	0.9573	0.7340	0.9605	0.7342
	t-SNE	0.4134	**1.3431**	0.1230	0.0022	**0.9877**	**0.9961**	**0.9905**	**0.9970**
	UMAP	0.4172	1.5734	0.1430	0.0026	**0.9891**	0.9547	**0.9907**	0.9547
	TopoAE	**0.3686**	1.3818	**0.1048**	**0.0011**	0.9716	0.9429	0.9732	0.9429
	A*t*-SNE	0.4328	1.5623	0.1482	0.0018	0.9768	**0.9765**	0.9830	**0.9777**
	UMATO	**0.3525**	**1.2785**	**0.1017**	0.0014	0.9792	0.8421	0.9813	0.8422
Kuzushiji MNIST	PCA	0.4215	0.1710	0.1317	0.0014	0.9380	0.7213	0.9420	0.7211
	t-SNE	0.3582	**0.0392**	0.0998	0.0019	0.9854	**0.9750**	**0.9881**	**0.9759**
	UMAP	0.3873	**0.0417**	0.1148	0.0026	**0.9893**	0.9563	**0.9908**	0.9564
	TopoAE	0.3730	0.1495	0.1027	**0.0011**	0.9755	0.9442	0.9768	0.9440
	A*t*-SNE	**0.3505**	0.0807	**0.0978**	**0.0013**	0.9786	**0.9671**	0.9824	**0.9676**
	UMATO	**0.3231**	0.1365	**0.0815**	0.0016	**0.9865**	0.8888	**0.9881**	0.8895

$MRRE_X$ and continuity, which proves that UMATO is better than those algorithms in terms of their capability to capture both global and local aspects of high-dimensional data.

5.4 QUALITATIVE RESULTS

Among the five algorithms, only UMATO could preserve both the global and local structure of the Spheres dataset. If we look at the figure made by UMATO, the outer sphere encircles the inner spheres in a circular form, which is the most intuitive to understand the relationship among different classes and the local linkage in detail. In the results from *t*-SNE, UMAP, and A*t*-SNE, the points representing the surrounding giant sphere mix with those representing the other small inner spheres, thus failing to capture the nested relationships among different classes. Meanwhile, topological autoencoders are able to realize the global relationship between classes in an incomplete manner; the points for the outer sphere are too spread out, thus losing the local characteristics of the class. From this result, we can acknowledge how UMATO can work with high-dimensional data effectively to reveal both global and local structures. For other datasets, UMATO showed a similar projection to PCA but with better captured local characteristics. The results from topological autoencoders showed some points detached far apart from their centers, even though the best hyperparameters were used for each. Although A*t*-SNE claimed that it could capture both structures, the results were not significantly different from those of the original *t*-SNE algorithm when projecting the Spheres and Fashion MNIST datasets.

5.5 DISCUSSION

Multi-phase Optimization. The optimization of UMATO can be easily expanded to multiple phases (e.g., three or more phases). Since we have a recursive procedure to expand the nearest neighbors, we can insert the optimization process each time we expand the neighbors to create a multi-phase algorithm. However, our experiment with three- and four-phase optimization with the Fashion MNIST dataset showed that there is no big difference between two-phase optimization and that with more

Figure 3: **2D projections produced by UMATO and five baseline algorithms.** (Top row) t-SNE, At-SNE, and UMAP showed as if the points from a surrounding sphere were attached to inner spheres, not reflecting the data's global structures. PCA and topological autoencoders attempted to preserve the global structures, but failed to manifest the local structures. UMATO was the only algorithm to capture both the global and local structures among all different sphere classes. (Second to fourth rows) UMATO generated similar projections to PCA but with the points more locally connected; this is best viewed in color.

than two phases. Section C.1 contains the quantitative and qualitative results of the experiment for multi-phase optimization.

Projection Stability. Since UMATO adopts the approximated k-nearest neighbors and the stochastic gradient descent for the optimization, the projection results should be different between runs. To check the stability of UMATO compared to the baseline algorithms, which take a similar iterative method (e.g., t-SNE, UMAP, and At-SNE), we replicated the experiment in UMAP using the Flow Cytometry dataset (Spidlen et al. (2012); Brodie et al. (2013)). We randomly selected a portion of points, and measured how the normalized Procrustes distance changes over diverse sub-sample sizes. Consequently, UMATO generated a lower normalized Procrustes distance than the other techniques in most (nine out of ten) sub-sample sizes, which meant the projection results for UMATO were more stable than those algorithms in general. Thanks to the global structures generated by the cross-entropy function as a whole, the projection of UMATO does not vary over repetition. Section C.2 describes this experiment in more detail.

6 CONCLUSION

We present a two-phase dimensionality reduction algorithm called UMATO that can effectively preserve the global and local properties of high-dimensional data. In our experiments with diverse datasets, we have proven that UMATO can outperform previous widely used baselines (e.g., t-SNE and UMAP) both quantitatively and qualitatively. As future work, we plan to accelerate UMATO, as in previous attempts with other dimensionality reduction techniques (Pezzotti et al. (2019); Nolet et al. (2020)), by implementing it on a heterogeneous system (e.g., GPU) for speedups.

REFERENCES

El-ad David Amir, Kara L Davis, Michelle D Tadmor, Erin F Simonds, Jacob H Levine, Sean C Bendall, Daniel K Shenfeld, Smita Krishnaswamy, Garry P Nolan, and Dana Pe'er. visne enables visualization of high dimensional single-cell data and reveals phenotypic heterogeneity of leukemia. *Nature biotechnology*, 31(6):545–552, 2013.

Etienne Becht, Leland McInnes, John Healy, Charles-Antoine Dutertre, Immanuel WH Kwok, Lai Guan Ng, Florent Ginhoux, and Evan W Newell. Dimensionality reduction for visualizing single-cell data using umap. *Nature biotechnology*, 37(1):38–44, 2019.

Mikhail Belkin and Partha Niyogi. Laplacian eigenmaps and spectral techniques for embedding and clustering. In *Advances in neural information processing systems*, pp. 585–591, 2002.

Sean C Bendall and Garry P Nolan. From single cells to deep phenotypes in cancer. *Nature biotechnology*, 30(7):639, 2012.

Sean C Bendall, Garry P Nolan, Mario Roederer, and Pratip K Chattopadhyay. A deep profiler's guide to cytometry. *Trends in immunology*, 33(7):323–332, 2012.

Christophe Benoist and Nir Hacohen. Flow cytometry, amped up. *Science*, 332(6030):677–678, 2011.

Tess Brodie, Elena Brenna, and Federica Sallusto. Omip-018: Chemokine receptor expression on human t helper cells. *Cytometry Part A*, 83(6):530–532, 2013.

Frédéric Chazal, David Cohen-Steiner, and Quentin Mérigot. Geometric inference for probability measures. *Foundations of Computational Mathematics*, 11(6):733–751, 2011.

Frédéric Chazal, Brittany Fasy, Fabrizio Lecci, Bertrand Michel, Alessandro Rinaldo, Alessandro Rinaldo, and Larry Wasserman. Robust topological inference: Distance to a measure and kernel distance. *The Journal of Machine Learning Research*, 18(1):5845–5884, 2017.

Tarin Clanuwat, Mikel Bober-Irizar, Asanobu Kitamoto, Alex Lamb, Kazuaki Yamamoto, and David Ha. Deep learning for classical japanese literature, 2018.

Cong Fu, Yonghui Zhang, Deng Cai, and Xiang Ren. Atsne: Efficient and robust visualization on gpu through hierarchical optimization. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 176–186, 2019.

Antonio Gracia, Santiago González, Victor Robles, and Ernestina Menasalvas. A methodology to compare dimensionality reduction algorithms in terms of loss of quality. *Information Sciences*, 270:1–27, 2014.

Laleh Haghverdi, Florian Buettner, and Fabian J Theis. Diffusion maps for high-dimensional single-cell analysis of differentiation data. *Bioinformatics*, 31(18):2989–2998, 2015.

Tim Head, MechCoder, Gilles Louppe, Iaroslav Shcherbatyi, fcharras, Zé Vinícius, cmmalone, Christopher Schröder, nel215, Nuno Campos, Todd Young, Stefano Cereda, Thomas Fan, rene rex, Kejia (KJ) Shi, Justus Schwabedal, carlosdanielcsantos, Hvass-Labs, Mikhail Pak, So-ManyUsernamesTaken, Fred Callaway, Loïc Estève, Lilian Besson, Mehdi Cherti, Karlson Pfannschmidt, Fabian Linzberger, Christophe Cauet, Anna Gut, Andreas Mueller, and Alexander Fabisch. scikit-optimize/scikit-optimize: v0.5.2, March 2018. URL https://doi.org/10.5281/zenodo.1207017.

Carsten Krieg, Malgorzata Nowicka, Silvia Guglietta, Sabrina Schindler, Felix J Hartmann, Lukas M Weber, Reinhard Dummer, Mark D Robinson, Mitchell P Levesque, and Burkhard Becher. High-dimensional single-cell analysis predicts response to anti-pd-1 immunotherapy. *Nature medicine*, 24(2):144, 2018.

Yann LeCun and Corinna Cortes. MNIST handwritten digit database. 2010. URL http://yann.lecun.com/exdb/mnist/.

John A Lee and Michel Verleysen. *Nonlinear dimensionality reduction*. Springer Science & Business Media, 2007.

John A Lee and Michel Verleysen. Quality assessment of dimensionality reduction: Rank-based criteria. *Neurocomputing*, 72(7-9):1431–1443, 2009.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(Nov):2579–2605, 2008.

Leland McInnes, John Healy, and James Melville. Umap: Uniform manifold approximation and projection for dimension reduction. *arXiv preprint arXiv:1802.03426*, 2018.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In *Advances in neural information processing systems*, pp. 3111–3119, 2013.

Michael Moor, Max Horn, Bastian Rieck, and Karsten Borgwardt. Topological autoencoders. In *Proceedings of the 37th International Conference on Machine Learning (ICML)*, Proceedings of Machine Learning Research. PMLR, 2020.

Corey J Nolet, Victor Lafargue, Edward Raff, Thejaswi Nanditale, Tim Oates, John Zedlewski, and Joshua Patterson. Bringing umap closer to the speed of light with gpu acceleration. *arXiv preprint arXiv:2008.00325*, 2020.

Nicola Pezzotti, Julian Thijssen, Alexander Mordvintsev, Thomas Höllt, Baldur Van Lew, Boudewijn PF Lelieveldt, Elmar Eisemann, and Anna Vilanova. Gpgpu linear complexity t-sne optimization. *IEEE transactions on visualization and computer graphics*, 26(1):1172–1181, 2019.

Vin D Silva and Joshua B Tenenbaum. Global versus local methods in nonlinear dimensionality reduction. In *Advances in neural information processing systems*, pp. 721–728, 2003.

Josef Spidlen, Karin Breuer, Chad Rosenberg, Nikesh Kotecha, and Ryan R Brinkman. Flowrepository: A resource of annotated flow cytometry datasets associated with peer-reviewed publications. *Cytometry Part A*, 81(9):727–731, 2012.

Jian Tang, Meng Qu, Mingzhe Wang, Ming Zhang, Jun Yan, and Qiaozhu Mei. Line: Large-scale information network embedding. In *Proceedings of the 24th international conference on world wide web*, pp. 1067–1077, 2015.

Jian Tang, Jingzhou Liu, Ming Zhang, and Qiaozhu Mei. Visualizing large-scale and high-dimensional data. In *Proceedings of the 25th international conference on world wide web*, pp. 287–297, 2016.

Dmitry Ulyanov. Multicore-tsne. `https://github.com/DmitryUlyanov/Multicore-TSNE`, 2016.

Jarkko Venna and Samuel Kaski. Neighborhood preservation in nonlinear projection methods: An experimental study. In *International Conference on Artificial Neural Networks*, pp. 485–491. Springer, 2001.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms, 2017.

Lin Yan, Yaodong Zhao, Paul Rosen, Carlos Scheidegger, and Bei Wang. Homology-preserving dimensionality reduction via manifold landmarking and tearing. In *Visualization in Data Science (VDS)*, 2018. URL `https://arxiv.org/abs/1806.08460`.

Yuansheng Zhou and Tatyana O Sharpee. Using global t-sne to preserve inter-cluster data structure. *bioRxiv*, 2018. doi: 10.1101/331611.

A   UMATO ALGORITHM PSEUDOCODE

The pseudocode of UMATO is as below:

Algorithm 1 Uniform Manifold Approximation with Two-phase Optimization

---
1: **procedure** UMATO($X, k_X, d, min\_dist, n_h, e_g, e_l$)
Input: High-dimensional data X, number of nearest neighbors k, projection dimension d, minimum distance in projection result min_dist, number of hub points n_h, epochs for global and local optimization e_g, e_l
Output: Low-dimensional projection Y
2:        Compute k-nearest neighbors of X
3:        Obtain sorted list using indices' frequency of k-nearest neighbors
4:        Build k-nearest neighbor graph structure
5:        Classify points into hubs, expanded nearest neighbors, and outliers
6:        Optimize $CE(P(X_h)||Q(Y_h))$ to preserve global configuration (Equation 4)
7:        Initialize expanded nearest neighbors using hub locations
8:        Update k-nearest neighbors & compute weights (Equation 3)
9:        Optimize $CE(P(X)||Q(Y))$ to preserve local configuration (Equation 7)
10:       Position outliers
11:       **return** Y
12: **end procedure**

B   THE MEANING OF USING DIFFERENT LOSS FUNCTIONS IN DIMENSIONALITY REDUCTION

Following the notations from above, we set the similarity between points in high-dimensional space x_i and x_j as v_{ij} and the low-dimensional space y_i and y_j as w_{ij}. Then we can write the KL divergence and cross entropy loss function as:

$$KL = \sum_{i \neq j} v_{ij} \cdot \log(v_{ij}/w_{ij}), \tag{8}$$

$$CE = \sum_{i \neq j} v_{ij} \cdot \log(v_{ij}/w_{ij}) - \sum_{i \neq j} (1 - v_{ij}) \cdot \log((1 - v_{ij})/(1 - w_{ij})). \tag{9}$$

Table 3: **Analysis of the KL divergence and cross-entropy loss function for imposing penalties when updating the positions of points in low-dimensional space.** (Upper table) The KL divergence and the first term of the cross-entropy function impose a big penalty when w_{ij} is small but v_{ij} is large. (Lower table) In contrast, the second term of cross-entropy function imposes a big penalty when v_{ij} is small but w_{ij} is large.

| | | Low d | |
		Large w_{ij}	Small w_{ij}
High d	Large v_{ij}	a. Small penalty	b. Big penalty (preserves local structures)
	Small v_{ij}	c. Small penalty (ignores global structures)	d. Small penalty

| | | Low d | |
		Large w_{ij}	Small w_{ij}
High d	Large v_{ij}	e. Small penalty	f. Small penalty (ignores local structures)
	Small v_{ij}	g. Big penalty (preserves global structures)	h. Small penalty

If we use the same probability distributions, v_{ij} and w_{ij}, the KL divergence and the first term of cross-entropy are exactly the same. If v_{ij} and w_{ij} are both large (Table 3 a.) or both small (Table 3 d.), this means that the relationship between points in high-dimensional space is well-retained in the projection. Thus, the positions of points in the low-dimensional space do not have to move. As v_{ij} and w_{ij} are similar, $\log(v_{ij}/w_{ij})$ becomes zero, producing a small cost in the end.

However, we need to modify the position of w_{ij} if there exists a gap between v_{ij} and w_{ij}. The KL divergence imposes a big penalty when v_{ij} is small but w_{ij} is large (Table 3 b.). That is, if the neighboring points in high-dimensional space are not captured well in the projection, the KL divergence imposes a high penalty to move the point (v_{ij}) into the right position. Thus, we can understand why t-SNE is able to capture the local characteristics of high-dimensional space, but not the global ones. However, the second term of cross-entropy imposes a big penalty when v_{ij} is large but w_{ij} is small (Table 3 g.). Therefore, it moves points that are close together in the high-dimensional space but far apart in the projection.

C ADDITIONAL EXPERIMENTS

C.1 MULTI-PHASE OPTIMIZATION

We report the result of multi-phase optimization (e.g., three and four-phase) using the Fashion MNIST dataset both quantitatively (Table 4) and qualitatively (Figure 4). As in Figure 4, we were unable to find any significant differences between the 2D projections, although some outliers were located in different places. Moreover, the quality metrics were almost the same for all three results. The original UMATO was the winner in DTM, $KL_{0.1}$, KL_1, continuity, and $MRRE_Z$ but came last in other quality metrics. In addition, the gap in metrics between UMATO and the multi-phase optimizations indicated a trivial difference. Thus, we concluded that developing a multi-phase optimization for UMATO does not bring about any notable improvement in the projection result.

Table 4: **Quantitative evaluation of UMATO and UMATO with multi-phase optimizations.** Although the optimization process of UMATO can be simply expandable for multiple phases, no apparent distinctions are found in the the results with different numbers of optimization phases. The winner is in bold.

Dataset	Method	DTM	$KL_{0.01}$	$KL_{0.1}$	KL_1	Cont	Trust	$MRRE_X$	$MRRE_Z$
Fashion MNIST	UMATO	**0.2035**	0.6852	**0.0342**	**0.0008**	**0.9911**	0.9500	**0.9919**	0.9502
	3-Phases	0.2058	0.6546	0.0343	**0.0008**	0.9900	**0.9556**	0.9909	**0.9561**
	4-Phases	0.2095	**0.6533**	0.0359	**0.0008**	0.9895	0.9532	0.9904	0.9536

Figure 4: **2D projections of the Fashion MNIST dataset using UMATO and UMATO with multi-phase optimizations.** Although there was a small difference such as the locations of outliers, we observed that the projection results were quite similar to each other.

C.2 PROJECTION STABILITY

Table 5 denotes the results of our experiment on the projection stability of UMATO and other dimensionality reduction techniques. When the data size grows, we want to sample a portion of it to speed up the visualization. However, the concern is whether the projection run with the sampled indices is consistent with the part of the projection result with indices selected from the full dataset. If the algorithm can generate stable and consistent results, the two projections should contain the

least bias possible. To compute the projection stability of dimensionality reduction techniques, we used the normalized Procrustes distance to measure the distance between two comparable distributions. Specifically, given two datasets $X = \{x_1, x_2, \ldots, x_n\}$ and $Y = \{y'_1, y'_2, \ldots, y'_n\}$ where y'_i corresponds to x_i, the Procrustes distance is defined as $d_P(X, Y) = \sqrt{\sum_{i=1}^{N} (x_i - y'_i)}$. To replicate the experiment by McInnes et al. (2018), we used the same Flow Cytometry dataset and ran optimal translation, uniform scaling, and rotation to minimize the Procrustes distance between the two distributions. As we can see in Table 5, UMATO outperformed t-SNE and At-SNE for all sub-sample sizes. Moreover, although UMAP is known as stable among existing algorithms, UMATO showed even better (lower) Procrustes distance except for one sub-sample size (60%). From this result, we can acknowledge that UMATO can generate the more stable and consistent results regardless of sub-sample size than many other dimensionality reduction techniques.

Table 5: **The normalized Procrustes distance between two projection results by the percentage of sub-samples.** From four dimensionality reduction techniques, we measured the normalized Procrustes distance to check the projection stability using the Flow Cytometry dataset. The winner is in bold.

Sample (%)	1	2	5	10	20	30	50	60	80	100
t-SNE	0.9835	0.9944	0.9544	0.9736	0.9824	0.9924	0.9959	0.9819	0.9944	0.9765
UMAP	0.4002	0.3319	0.2341	0.1324	0.1327	0.1577	0.1109	**0.0713**	0.0951	0.0597
At-SNE	0.8958	0.9510	0.7593	0.7980	0.9062	0.9376	0.9999	0.9460	0.9599	0.9999
UMATO	**0.3153**	**0.1528**	**0.1206**	**0.0988**	**0.0520**	**0.1411**	**0.0526**	0.1732	**0.0529**	**0.0535**

D QUALITY METRICS

As UMATO presents a dimensionality reduction technique that can capture both the global and local structures of high-dimensional data, we used several quality metrics to evaluate each aspect respectively. We have referred to some review papers (Gracia et al. (2014); Lee & Verleysen (2009)) for the best use and implementation. Among many quality metrics, we leveraged 1) Distance To a Measure (DTM, Chazal et al. (2011; 2017)), 2) KL divergence between two density functions, 3) trustworthiness and continuity (Venna & Kaski (2001)), and 4) mean relative rank errors (MRREs, Lee & Verleysen (2007)). The first two metrics are used to test the preservation of global structures and the last two metrics are suggested for the preservation of the local structures.

Distance To a Measure considers the dispersion of high- and low-dimensional data, where it is defined for a given point as $f_\sigma^X(x) := \sum_{y \in X} \exp\left(-\text{dist}(x, y)^2/\sigma\right)$. By summing up the element-wise absolute values between two distributions, $\sum_{x \in X, z \in Z} f_\sigma^X(x) - f_\sigma^Z(z)$ where x is the point in high-dimensional space X and the z is the corresponding projected point in low-dimensional space Z, we can examines the similarity of two datasets. In our experiments, we used the Euclidean distance and the values were normalized between 0 and 1. The $\sigma \in \mathcal{R}_{>0}$, which represents the length scale parameter, was set to 0.1. Moor et al. (2020) proposed the KL divergence of two probability distributions, $\text{KL}_\sigma := \text{KL}(f_\sigma^X \| f_\sigma^Z)$, a variation of DTM. Changing σ as a normalizing factor of the distribution, the authors investigated if the algorithms can preserve the global structure of the high-dimensional data. Following the same notion as the experiment in the paper (Moor et al. (2020)), we used three σ values, 1.0, 0.1, and 0.01, to test whether each algorithm can capture the global aspect with respect to diverse density estimates.

Trustworthiness and continuity measure how much the nearest neighbors are preserved in a space (i.e., high- or low-dimensional space) compared to the other space by analyzing the ranks of k-nearest neighbors in both spaces. The difference between trustworthiness and continuity comes from which space is held as the base space. Specifically, we first need to find the k-nearest neighbors in both high- and low-dimensional space. Then, we compute the trustworthiness by checking whether the ranks of nearest neighbors in low-dimensional space resemble those of high-dimensional space. If so, we can achieve a high score in trustworthiness. Meanwhile, we achieve a high score in continuity if the ranks of nearest neighbors in high-dimensional space resemble those of low-dimensional space. MRREs take a similar approach to trustworthiness and continuity as it calculates and compares the ranks of the k-nearest neighbors in both spaces, but the normalizing factor is slightly

different. Originally, it was better if MRREs had lower values. However, for the ease of comparing local quality metrics, we defined it as MRREs := $1 -$ MRREs, so higher MRREs mean that they have better retained the k-nearest neighbors like trustworthiness and continuity.

E   HYPERPARAMETER SETTING

As explained in Section 5.2, we generated projections for each dimensionality reduction algorithm that had the lowest $\text{KL}_{0.1}$ measure. To tune each algorithm's hyperparameters, we employed the grid search for t-SNE, UMAP, and At-SNE. For t-SNE and At-SNE, we changed the perplexity from 5 to 50 with an interval of 5, and learning rate from 0.1 to 1.0 with a log-uniform scale. In the case of UMAP, we changed the number of nearest neighbors from 5 to 50 with an interval of 5, and the minimum distance between points in the projection from 0.1 to 1.0 with an interval of 0.1. We used the Python library scikit-optimize (Head et al. (2018)) to find the best hyperparameters for topological autoencoders. UMATO has several hyperparameters such as the number of hub points, the number of epochs, and the learning rate for global and local optimization. In our experiments, we configured everything except the number of hub points to the same setting for UMATO. We used 200 hub points for the Spheres dataset and had 300 hubs for others. We used fewer hub points for the Spheres since it has only 10,000 data points in total, while the other datasets have 60,000 data points. We set the number of epochs to 100 for global optimization and to 50 for the local optimization. Lastly, the global learning rate was set to 0.0065, and the local learning rate was set to 0.01.

F   SYNTHETIC SPHERES DATASET

We leveraged the exact same Spheres dataset that Moor et al. (2020) used in their experiments of topological antoencoders. The Spheres dataset contains eleven high-dimensional spheres which reside in 101-dimensional space. We first generated ten spheres of radius of 5, and shifted each sphere by adding the same Gaussian noise to a random direction. For this aim, we created d-dimensional Gaussian vectors $X \sim N(0, I(10/\sqrt{d}))$, where d is 101. As to embed an interesting geometrical structure to the dataset, the ten spheres of relatively small radii of 5 were enclosed by another larger sphere of radius of 25.