Cardinality-Regularized Hawkes-Granger Model

Abstract

We propose a new sparse Granger-causal learning framework for temporal event data. We focus on a specific class of point processes called the Hawkes process. We begin by pointing out that most of the existing sparse causal learning algorithms for the Hawkes process suffer from a singularity in maximum likelihood estimation. As a result, their sparse solutions can appear only as numerical artifacts. In this paper, we propose a mathematically well-defined sparse causal learning framework based on a cardinality-regularized Hawkes process, which remedies the pathological issues of existing approaches. We leverage the proposed algorithm for the task of instance-wise causal event analysis, where sparsity plays a critical role. We validate the proposed framework with two real use-cases, one from the power grid and the other from the cloud data center management domain.

1 Introduction

The *Hawkes process* [15] is one of the most popular models for analyzing temporal events in the machine learning (ML) community. It has been applied in a variety of application areas including analysis of human activities on social networks [23, 34, 37, 16, 36, 22, 3, 42], healthcare event analysis [7, 49, 13], search query analysis [21, 20], and even water pipe maintenance [46]. In the studies of Hawkes processes, there have been two major milestones to date. One is the *minorization-maximization (MM)* algorithm [17]. The other is *Granger causal analysis* through Hawkes processes.

The first milestone was marked by Veen and Schoenberg [40]. Based on the intuition of branching process of earthquake aftershocks, they introduced the first MM-based maximum likelihood algorithm, which is often loosely referred to as EM (expectation-maximization) due to their similarity (See Eq. (14) and the discussion below). As their paper pointed out, the standard gradient-based maximum likelihood estimation (MLE) of multivariate Hawkes processes suffered from numerical stability issues, limiting their applicability in practice.

The second milestone was achieved by a few pioneers including Kim et al. [18] who first proposed an approach to Granger causal learning through the Hawkes process; Zhou et al. [50] who introduced ℓ_1 regularized MLE of a multivariate Hawkes process; and Eichler et al. [10] who theoretically established the equivalence between the Hawkes-based causality and the Granger causality [14].

Given these achievements and the well-known importance of sparsity in Granger causal learning [4, 24], the MM algorithm combined with a sparsity-enforcing regularizer would seem to be a promising path for Granger-causal analysis for stochastic events. This is especially true when the main interest is in analyzing *causal triggering mechanism* of event *instances* since the MM framework provides instance-wise triggering probabilities as a side product. Interestingly, however, the likelihood function of the MM algorithm has a singularity that in fact prohibits any sparse solutions. Despite its significance, to date little attention has been paid to this issue in the ML community.

In this paper, we provide a mathematically well-defined solution to sparse causal learning on temporal event data for the first time. Specifically, we introduce a novel *cardinality-regularized* MM framework

Figure 1: The Hawkes-Granger model allows two different levels of causal analysis: (a) instance-wise and (b) type-wise, in which well-defined *sparsity* is essential for causal diagnosis. (c) Example of five-variate point process data, where each '|' represents an event instance.

for the Hawkes process. Unlike existing ℓ_1-regularization approaches [50, 44], it is free from pathological issues due to the logarithmic singularity at zero. Although ℓ_0-regularized optimization problems are generally hard to solve, we derive a semi-analytic solution by exploiting a specific mathematical structure of the MM algorithm. By leveraging the well-defined sparsity and the side product provided by the MM framework, we tackle the task of instance-wise causal diagnosis in multiple real world domains. Since any event instance occurring in the past is a potential candidate cause of a given event of interest, achieving sufficient sparsity in the learned causal structure has proven critical in these applications. (See also Fig. 1 for illustration.)

To the best of our knowledge, this work represents the first ℓ_0-regularized MM learning framework for the Hawkes process applied to simultaneous instance- and type-level causal analysis.

2 Related work

Graphical Granger models: For multivariate temporal data, sparse graphical causal modeling with a (group) lasso penalty [4, 24] has been a standard approach in the machine learning community for Granger causal analysis. Their neural extension has also been proposed recently [38]. However, most of those studies assume multivariate time-series data as the input and are not directly applicable to event data. We come back to this point in Sec. 6 to validate the proposed Hawkes-Granger model.

Conventional MLE: Since Hawkes' original proposal [15], gradient-based MLE has been a mainstream approach to fitting Hawkes processes (see, e.g. [32]). In particular, it has been used extensively in the field of seismology [30]. However, as Veen and Schoenberg [40] and Mark and Weber [25] convincingly demonstrated, gradient-based MLE tends to have numerical instability issues. Unless detailed prior knowledge on the data generating mechanism is available, its applicability to industrial stochastic event data can be limited. Stochastic optimization can be leveraged (e.g. [29]), but it brings in extra variability to inference. In addition to conventional MLE, there are a few other methods to fit multivariate Hawkes processes, such as least squares [45, 6] and moment matching [2]. They trade off the direct linkage to the likelihood principle for computational stability, and are out of our scope. This paper focuses on how to enhance the MM algorithm through cardinality regularization.

Neural Hawkes models: Neural point process models typically replace all or part of the terms of the Hawkes intensity function to capture nonlinear temporal dependencies [9, 43, 26, 39, 31, 12, 51]. However, most of the works either assume equi-time-interval input or lack the perspective of instance-wise causal triggering. Recently, Zhang et al. [48] proposed an RNN (recurrent neural network)-based point process model featuring an autoregressive attention mechanism. It can analyze instance-level causal triggering structure, but assumes equi-interval input.

Sparse MM algorithms: As discussed in Introduction, [50] and [44] are among the pioneering works that attempted to combine sparsity-enforcing regularizers with the MM algorithm. Unfortunately, due to the logarithmic singularity of the likelihood function, sparsity can only be achieved as a numerical artifact. See Sec. 5 for details.

Applications of Hawkes processes: Somewhat related to our motivation, there are a few recent studies that pay particular attention to the duality between microscopic (instance-level) and macroscopic (type- or aggregate-level) random processes. For instance, Wang et al. [41] discuss the relationship

between a point process and a rate equation at an aggregate level, Li et al. [19] discuss macroscopic information diffusion through human interactions, and Zhang et al. [47] discuss failure propagation in compressor stations. None of them, however, explicitly performs simultaneous instance- and type-level causal analysis. As discussed in Sec. 6, our framework can be viewed as a disciplined and effective solution to the issue of "warning fatigue," which prevails across many industries [11, 27, 8].

3 Preliminaries

This section provides the problem setting and recapitulates the basics of stochastic point processes.

3.1 Problem setting

Before getting into the formal definitions, let us take a brief look at a concrete use-case from cloud data center management (See Sec. 6 for more details). In a data center, various computer and network devices continuously produce numerous event logs, which can be viewed as marked temporal event data with "marks" being the warning types. Due to inter-connectivity of the devices, one event from a device, such as a warning of type "response time too long," may trigger many related events downstream. The more critical the original error, the more numerous the resulting set of events tend to be. Thus for a given event *instance* of interest (called the target), it is desirable to find which event instances in the past are causally related to it. We call this task *event causal diagnosis*.

There are two essential requirements in event causal diagnosis. The *first* one is the ability of providing instance-specific causal information in addition to the type-level causality. For instance, even if the i-th event type is *on average* likely to have a causal relationship with the j-th type, one specific *instance* of the i-th event type may have occurred spontaneously. A practical solution for event causal analysis must therefore perform type- and instance-level causal analysis simultaneously. The *second* requirement is the ability of providing *sparse* causal relationship. Since the number of event instances can be large, the capability of effectively shortlisting the candidates that may be causally related to a target event is essential in practice. To the best of our knowledge, our sparse Hawkes-Granger model is the first that meets these two requirements.

We are given an event sequence of $N + 1$ event *instances*:

$$\mathcal{D} = \{(t_0, d_0), (t_1, d_1), \ldots, (t_N, d_N)\}, \tag{1}$$

where t_n and d_n are the timestamp and the *event type* of the n-th event, respectively. The timestamps have been sorted in non-decreasing order $t_0 \leq t_1 \leq \cdots \leq t_N$. There are D event types $\{1, 2, \ldots, D\}$ with $D \ll N$. We take the first time stamp t_0 as the time origin. Hence, the remaining N instances are thought of as realization of random variables, given d_0. As a general rule, we use t or u as a free variable representing time while those with a subscript denote an instance.

The main goal of event causal diagnosis, which is an *unsupervised learning task*, is to compute the instance *triggering probabilities* $\{q_{n,i}\}$, where $q_{n,i}$ is the probability for the n-th event ($n = 1, \ldots, N$) instance to be triggered by the i-th event ($i = 0, \ldots, n$). By definition, $n \geq i$, and

$$\sum_{i=0}^{n} q_{n,i} = 1, \quad \forall n \in \{1, \ldots, N\}. \tag{2}$$

We call $q_{n,n}$ the *self* triggering (or simply self) probability. Note that providing $\{q_{n,i}\}$ amounts to providing weighted ranking of candidate triggering (or causing) events, where the weights sum to one. We wish to have as few candidates as possible with the aid of sparse causal learning.

3.2 Likelihood and intensity function

Since all the events are supposed to be correlated, the most general probabilistic model is the joint distribution of the N events. By the chain rule of probability density functions (pdf), the joint distribution can be represented as

$$f((t_1, d_1), \ldots, (t_N, d_N) \mid (t_0, d_0)) = \prod_{n=1}^{N} f(t_n, d_n \mid \mathcal{H}_{n-1}),$$

where $\mathcal{H}_{n-1}$ denotes the event history up to t_{n-1}, namely, $\mathcal{H}_{n-1} \triangleq \{(t_0, d_0), \ldots, (t_{n-1}, d_{n-1})\}$. We use $f(\cdot)$ to symbolically denote a pdf. This decomposition readily leads to the definition of the base likelihood function L_0:

$$L_0 \triangleq \sum_{n=1}^{N} \ln f(t_n \mid d_n, \mathcal{H}_{n-1}) + \sum_{n=1}^{N} \ln f(d_n \mid \mathcal{H}_{n-1}). \tag{3}$$

The distribution $f(t \mid d_n, \mathcal{H}_{n-1})$ is defined on $t_{n-1} \leq t < \infty$ and satisfies the normalization condition in that domain. For the task of causal diagnosis, the first term in Eq. (3) plays the central role. We omit the second term in what follows, assuming $f(d_n \mid \mathcal{H}_{n-1})$ is a constant.

The intensity function given $\mathcal{H}_{n-1}$ is defined as the probability density that the first event since t_{n-1} occurs. This is a conditional density. When considering the density at t, the condition reads "no event occurred in $[t_{n-1}, t)$." Hence,

$$\lambda_d(t \mid \mathcal{H}_{n-1}) \triangleq \frac{f(t \mid d, \mathcal{H}_{n-1})}{1 - \int_{t_{n-1}}^{t} \mathrm{d}u \, f(u \mid d, \mathcal{H}_{n-1})}, \tag{4}$$

where $\lambda_d(t \mid \mathcal{H}_{n-1})$ is the intensity function for the d-th event type, given the history $\mathcal{H}_{n-1}$. Notice that the r.h.s. can be written as $-\frac{\mathrm{d}}{\mathrm{d}t} \ln \left(1 - \int_{t_{n-1}}^{t} \mathrm{d}u \, f(u \mid d_n, \mathcal{H}_{n-1})\right)$. Integrating the both sides and arranging the terms, we have

$$f(t \mid d, \mathcal{H}_{n-1}) = \lambda_d(t \mid \mathcal{H}_{n-1}) \exp\left\{ -\int_{t_{n-1}}^{t} \mathrm{d}u \, \lambda_d(u \mid \mathcal{H}_{n-1}) \right\}, \tag{5}$$

which allows representing L_0 in terms of the intensity:

$$L_0 = \sum_{n=1}^{N} \left\{ \ln \lambda_{d_n}(t_n \mid \mathcal{H}_{n-1}) - \int_{t_{n-1}}^{t_n} \mathrm{d}u \, \lambda_{d_n}(u \mid \mathcal{H}_{n-1}) \right\}. \tag{6}$$

Notice the dependency of the event intervals on n in the second term. When $D > 1$, the summation over n cannot be performed in the second term due to d_n being dependent on n. This fact is sometimes incorrectly ignored in the literature.

4 Cardinality-Regularized Hawkes-Granger Model

This section provides a specific model for the intensity function and discusses the connection to Granger causality to define the Hawkes-Granger model.

4.1 Intensity function and Granger causality

For the intensity function in Eq. (6), we introduce a specific parameterization of the Hawkes process:

$$\lambda_d(t \mid \mathcal{H}_{n-1}) = \mu_d + \sum_{i=0}^{n-1} A_{d,d_i} \phi_d(t - t_i). \tag{7}$$

where $\mu_d \geq 0$ and $\phi_d(t - t_i)$ are called the baseline intensity and the decay function, respectively, of the d-th type. A_{d,d_i} is the (d, d_i)-element of a matrix $\mathsf{A} \in \mathbb{R}^{D \times D}$, which is called the impact matrix (a.k.a. triggering or kernel matrix).

The Hawkes process has potential indistinguishability issues in the second term due to the product form. We remove some of the indistinguishability by (i) imposing the normalization condition $\int_0^\infty \phi_d(u) \, \mathrm{d}u = 1$ and (ii) making ϕ_d independent of d_i. In this parameterizaton, A_{d,d_i} is the triggering impact from event type d_i to d while ϕ_d represents the susceptibility of d. Also, μ_d represents the tendency of spontaneous occurrence. Due to the arbitrariness of the time unit, the decay function has the form $\phi_d(u) = \beta_d \varphi(\beta_d u)$, where $\varphi(\cdot)$ is a nondimensional function and β_d is called the decay rate. Popular choices for φ are the exponential $\exp(-u)$ and power $\eta(1 + u)^{-\eta-1}$ functions with $\eta > 1$ being a given constant.

150 Figure 2 illustrates the model (7), in which $\lambda_d(t \mid \mathcal{H}_4)$ is shown with an arbitrary decay function.
151 We assume that $A_{d,d_1} = A_{d,d_3} = 0$ and $A_{d,d_2} > A_{d,d_4}$. The effect of the 2nd instance on (t, d) is
152 smaller than that of the 4th due to time decay despite the larger A_{d,d_2}. On the other hand, as shown
153 with the dashed lines, the 1st and 3rd instances have no effect on the occurrence probability for the
154 assumed d-th type in any future time point. This is in fact how Eichler et al. [10] defined the Granger
155 non-causality in the Hawkes model (see also [2]):

Theorem 1 (Hawkes process and Granger non-causality [10]). *If $A_{d,d'} = 0$, event instances of the*
157 *d'-type are Granger-non-causal to those of the d-th type.*

158 Theorem 1 states that estimating A amounts to
159 learning a Granger causal graph. This Granger
160 non-causality characterization holds also in nonlin-
161 ear Hawkes models, where the r.h.s. of Eq. (7)
162 is replaced with $g(\mu_d + \sum_{i=0}^{n-1} A_{d,d_i}\phi_d(t - t_i))$
163 with $g(\cdot)$ being a nonlinear function. In that case,
164 however, the original meaning of μ_d and A_{d,d_i}
165 no longer holds. For example, μ_d contributes
166 not only to spontaneous occurrences but also to
167 causal triggering, due to cross-terms between

Figure 2: Illustration of Hawkes model in Eq. (7), showing $\lambda_d(t \mid \mathcal{H}_4)$ as an example. The d_1- and d_3-types are not causally related to d.

168 μ_d and $A_{d,d_i}\phi_d$ in the intensity function. Also, as the MM strategy is no longer applicable, there is
169 no natural way of defining the triggering probabilities (see the next subsection). Given that our main
170 interest lies in causal diagnosis ("who caused this?"), rather than black-box data fitting, the linear
171 additive form Eq. (7) is particularly convenient, and hence is our primary model.

4.2 Cardinality-regularized minorization-maximization framework

173 As we saw in Fig. 2, achieving sparsity in A is of critical importance in instance-wise causal analysis:
174 It directly leads to reducing the number of event candidates to be causally associated. To guarantee
175 sparsity, we propose the following *cardinality-regularized* maximum likelihood:

$$\max_{\mathsf{A},\boldsymbol{\mu},\boldsymbol{\beta}} \left\{ L_0(\mathsf{A}, \boldsymbol{\mu}, \boldsymbol{\beta}) - \tau \|\mathsf{A}\|_0 - R_2(\mathsf{A}, \boldsymbol{\mu}, \boldsymbol{\beta}) \right\}, \quad R_2 \triangleq \frac{1}{2} \left(\nu_\mu \|\boldsymbol{\mu}\|_2^2 + \nu_\beta \|\boldsymbol{\beta}\|_2^2 + \nu_A \|\mathsf{A}\|_F^2 \right) \quad (8)$$

176 where we have defined $\boldsymbol{\beta} \triangleq (\beta_1, \ldots, \beta_D)^\top$ and $\boldsymbol{\mu} \triangleq (\mu_1, \ldots, \mu_D)^\top$ and the ℓ_0 norm $\|\mathsf{A}\|_0$ represents
177 the cardinality (the number of nonzero elements) of A. Also, $\| \cdot \|_2$ is the 2-norm and $\| \cdot \|_F$
178 is the Frobenius norm. $\tau, \nu_\beta, \nu_\mu, \nu_A$ are constants for regularization strength. For τ, we note
179 that Eq. (15) can be viewed as MAP (maximum a posteriori) estimation with the Bernoulli prior
180 $(1 - \gamma)^{\|\mathsf{A}\|_0} \gamma^{D^2 - \|\mathsf{A}\|_0}$, where $0.5 < \gamma < 1$ is the probability of getting 0 in the matrix elements. By
181 taking the logarithm and equating to $-\tau \|\mathsf{A}\|_0$, we have

$$\tau = (1/2) \ln[\gamma/(1 - \gamma)]. \quad (9)$$

182 With γ having the specific interpretation, this equation makes the choice of a τ value easier.

183 As mentioned earlier, numerically solving for MLE is known to be challenging even when $\tau = 0$,
184 mainly due to the log-sum term $\ln \lambda_d$ in Eq. (6). The MM algorithm leverages the additive structure
185 of the Hawkes process in Eq. (7) to apply Jensen's inequality in a manner similar to the EM algorithm
186 for mixture models [28]. Specifically, we rewrite Eq. (7) as $\lambda_{d_n}(t_n|\mathcal{H}_{n-1}) = \sum_{i=0}^n \Phi_{n,i}^{d_n,d_i}$, where

$$\Phi_{n,i}^{d_n,d_i} \triangleq \begin{cases} \mu_{d_n}, & i = n \\ A_{d_n,d_i}\phi_d(t_n - t_i), & i = 0, \ldots, n - 1. \end{cases} \quad (10)$$

187 With an arbitrary distribution $q_{n,i}$ over i such that $\sum_{i=0}^n q_{n,i} = 1$ for $\forall n$, Jensen's inequality
188 guarantees $\ln \sum_{i=0}^n \Phi_{n,i}^{d_n,d_i} \geq \sum_{i=0}^n q_{n,i} \ln \frac{\Phi_{n,i}^{d_n,d_i}}{q_{n,i}}$, which leads to a lower bound of the log likelihood:

$$L_0 \geq L_1 \triangleq \sum_{n=1}^N \left\{ \sum_{i=0}^n q_{n,i} \ln \frac{\Phi_{n,i}^{d_n,d_i}}{q_{n,i}} - \mu_{d_n}\Delta_{n,n-1} - \sum_{i=0}^{n-1} A_{d_n,d_i} \int_{\Delta_{n-1,i}}^{\Delta_{n,i}} du \, \phi_{d_n}(u) \right\}, \quad (11)$$

189 where we defined $\Delta_{n,i} \triangleq t_n - t_i$. The tightest bound is obtained by maximizing the r.h.s. with
190 respect to $q_{n,i}$ under the normalization condition:

$$q_{n,i} = \begin{cases} \lambda_{d_n}(t_n|\mathcal{H}_{n-1})^{-1}\mu_{d_n}, & i = n, \\ \lambda_{d_n}(t_n|\mathcal{H}_{n-1})^{-1}A_{d_n,d_i}\phi_{d_n}(t_n - t_i), & i \neq n. \end{cases} \quad (12)$$

With a proper initialization, the MM algorithm estimates $\{q_{n,i}\}$ and $(\boldsymbol{\mu}, \boldsymbol{\beta}, \mathsf{A})$ alternately. The whole procedure is concisely summarized as

$$\boldsymbol{\mu}, \boldsymbol{\beta}, \mathsf{A} = \arg\max \{L_1 - \tau\|\mathsf{A}\|_0 - R_2\}, \quad \text{given} \quad \{q_{n,i}\} \tag{13}$$

$$\{q_{n,i}\} = (\text{Eq. (12)}), \quad \text{given} \quad \boldsymbol{\mu}, \boldsymbol{\beta}, \mathsf{A}. \tag{14}$$

Similarity to the EM algorithm [28] is evident, but they differ since we apply Jensen's inequality only partially in L_0. In this framework, $\{q_{n,i}\}$ was introduced as a mathematical artifact in Jensen's inequality. However, it opens a new door to instance-level causal analysis. We interpret $q_{n,i}$ as the *instance triggering probability* that the n-th instance has been triggered by the i-th instance. The MM-based Hawkes process is causal both at the instance-level and the type-level. With this in mind, we call the framework of Eqs. (13)-(14) the *Hawkes-Granger model*.

5 Sparse Causal Learning via Cardinality Regularization

This section discusses how to find the solution A in Eq. (13). We leave the estimation procedure of $\boldsymbol{\mu}$ and $\boldsymbol{\beta}$ to **Appendix A** (all the Appendices are in the supplementary material).

By Eqs. (8) and (11), the optimization problem of Eq. (13) with respect to A is rewritten as

$$\max_{\mathsf{A}} \left\{ \sum_{k,l=1}^{D} (Q_{k,l} \ln A_{k,l} - H_{k,l} A_{k,l}) - \frac{\nu_A}{2}\|\mathsf{A}\|_{\mathrm{F}}^2 - \tau\|\mathsf{A}\|_0, \right\}, \tag{15}$$

where we have defined matrices Q and H as

$$Q_{k,l} \triangleq \sum_{(n,i)} \delta_{d_n,k} \delta_{d_i,l} q_{n,i}, \quad H_{k,l} \triangleq \sum_{(n,i)} \delta_{d_n,k} \delta_{d_i,l} h_{n,i}, \quad h_{n,i} \triangleq \int_{\Delta_{n-1,i}}^{\Delta_{n,i}} \mathrm{d}u \, \phi_{d_n}(u). \tag{16}$$

$Q_{k,l}$ represents how likely the type k and l become a cause-effect pair. For ease of exposition, consider the vectorized version of the problem by defining $\boldsymbol{x} \triangleq \mathrm{vec}\,\mathsf{A}$, $\boldsymbol{h} \triangleq \mathrm{vec}\,\mathsf{H}$, and $\boldsymbol{g} \triangleq \mathrm{vec}\,\mathsf{Q}$:

$$\max_{\boldsymbol{x}} \left\{ \sum_m \Psi_m(x_m) - \tau\|\boldsymbol{x}\|_0 \right\}, \quad \Psi_m(x_m) \triangleq \left(g_m \ln x_m - h_m x_m - \frac{\nu_A}{2} x_m^2 \right), \tag{17}$$

where $g_m, h_m \geq 0$, $\tau, \nu_A > 0$ hold. This is the main problem we consider in this section.

Let us first look at what would happen if we instead used the popular ℓ_1 or $\ell_{2,1}$ regularizer here. The following theorem holds:

Theorem 2. *The ℓ_1-regularized problem $\max_{\boldsymbol{x}} \left\{ \sum_m \Psi_m(x_m) - \tau\|\boldsymbol{x}\|_1 \right\}$ is convex and has a unique solution. Let $\boldsymbol{x}^{**}$ be its solution. If $g_m > 0$, $x_m^{**} \neq 0$ for $\forall m$.*

(*Proof*) The convexity follows from $\frac{\mathrm{d}^2}{\mathrm{d}x_m^2}\Psi(x_m) = -(g_m/x_m^2) - \nu_A < 0$ and the convexity of the ℓ_1-norm. The second statement follows from $\lim_{x\to 0} \ln x = -\infty$. $\square$

In the MM iteration, we need to start with some $Q_{k,l} > 0$ to make all the event types eligible in causal analysis. In that case, $A_{k,l}$ cannot be zero. Therefore, any "sparse" solution must be viewed as a numerical artifact. A similar discussion holds for the $\ell_{2,1}$ regularizer. One can avoid this issue by employing a non-MM approach for MLE, but, as discussed earlier, it is not a viable solution in practice due to the well-known numerical difficulties of the conventional MLE [40, 25].

This situation is reminiscent of the issue with density estimation with probabilistic mixture models as discussed by [33], which introduced the notion of "ϵ-sparsity." Here we employ a similar approach. To handle the singularity at zero, we introduce a small constant $\epsilon > 0$ and we propose to solve

$$\boldsymbol{x}^* = \max_{\boldsymbol{x}} \sum_m \left\{ \Psi_m(x_m) - \tau I(x_m \geq \epsilon) \right\}, \tag{18}$$

to get an ϵ-sparse solution instead of the original ℓ_0-regularized problem (17), where $I(\cdot)$ is the indicator function that returns 1 when the argument is true and 0 otherwise. Note that the condition $\nu_A > 0$ is important for stable learning when some g_m are close to zero; It makes the objective

---

Algorithm 1 L_0Hawkes: sparse learning impact matrix A

1: **Input:** $\boldsymbol{g} = \text{vec}\, Q$, $\boldsymbol{h} = \text{vec}\, H$, and $\nu_A > 0, \tau \geq 0, \epsilon > 0$.
2: **for all** $m = 1, \ldots, D^2$ **do**
3:     compute $\bar{x}_m$ with Eq. (23).
4:     compute $\Delta \Psi_m$ with Eqs. (18) and (25).
5:     **if** $\Delta \Psi_m > 0$ **then**
6:         $x_m^* = \min\{\epsilon, \bar{x}_m\}$ $(\because\ m \in \mathcal{O})$
7:     **else**
8:         $x_m^* = \bar{x}_m$ $(\because\ m \notin \mathcal{O})$
9:     **end if**
10: **end for**
11: **return** $A^* = \text{vec}^{-1}\, \boldsymbol{x}^*$ (i.e. convert back to matrix)

---

strongly convex (easily seen from the proof of Theorem 2) and thus makes the problem (17) well-behaved. We remark that while it is possible to use an analogous ϵ-sparsity approach with the ℓ_1 or $\ell_{2,1}$ regularizer, it may not be as well-behaved due to the piece-wise linearity of ℓ_1-norm.

We solve the problem for each value of $m_0 \triangleq D^2 - I(x_m \geq \epsilon)$. Let $\mathcal{O}$ be the set of indexes that satisfy $x_m \leq \epsilon$. Given m_0, Eq. (18) is written as

$$\max_{\boldsymbol{x}} \sum_m \Psi_m(x_m) + \tau m_0 \quad \text{subject to} \quad \epsilon - x_{m'} \geq 0,\ m' \in \mathcal{O}. \tag{19}$$

With a Lagrange multiplier $\xi_{m'}$, the Karush–Kuhn–Tucker (KKT) condition is given by

$$\frac{g_m}{x_m} - h_m - \nu_A x_m - \xi_m = 0, \quad m \in \mathcal{O} \tag{20}$$

$$\xi_m(\epsilon - x_m) = 0, \quad \epsilon \geq x_m, \quad \xi_m \geq 0, \quad m \in \mathcal{O} \tag{21}$$

$$\frac{g_m}{x_m} - h_m - \nu_A x_m = 0, \quad m \notin \mathcal{O}. \tag{22}$$

For $m \notin \mathcal{O}$, we solve Eq. (22) to get

$$x_m^* = \bar{x}_m \triangleq \frac{1}{2\nu_A}\left(-h_m + \sqrt{h_m^2 + 4\nu_A g_m}\right), \quad m \notin \mathcal{O}. \tag{23}$$

For $m \in \mathcal{O}$, there are two possibilities:

$$x_m^* = \min\{\epsilon, \bar{x}_m\}, \quad m \in \mathcal{O}. \tag{24}$$

The final question is how to choose the set $\mathcal{O}$. This can be easily done by computing

$$\Delta \Psi_m \triangleq \Psi_m(\epsilon) - \Psi_m(\bar{x}_m) + \tau \tag{25}$$

for $\forall m$. Since $\Delta \Psi_m$ is viewed as the gain to turn off x_m, we put m into $\mathcal{O}$ whenever $\Delta \Psi_m > 0$.

Algorithm summary Algorithm 1 summarizes L_0Hawkes, the proposed algorithm, which is used as part of the iterative MM procedure in Eq. (13). The estimation procedure for $\boldsymbol{\mu}, \boldsymbol{\beta}$ can be found in **Appendix A**. The total complexity is $\mathcal{O}(N^2 + D^2)$, which is the same as for the existing MM algorithm. For input parameters, τ can be fixed to a value of user's choice in $0.5 < \gamma < 1$ through Eq. (9). The parameters $\nu_A, \nu_\beta, \nu_\mu$ are important for stable convergence. It is recommended to start with a small positive value, such as 10^{-5}, and increase it if numerical issues occur. These parameters should eventually be cross-validated with independent episodes of event data, or ground through causality data. In Sec. 6, we presents an approach to determine ϵ as the one that gives the break-even accuracy. If validation dataset is unavailable at all, the use of Akaike's information criterion (AIC) can be one viable approach, given that $\|A\|_0$ approximates the total number of free parameters fitted.

6   Experiments

Our focus in this section is to (1) show the impact of the equi-time-interval assumption of the existing Granger causal learning models, (2) demonstrate how L_0Hawkes produce a sparse solution, and (3) show its utility in real-world use-cases. We leave the detail of the experimental setup to **Appendix B**.

Figure 3: True positive (red) and true negative (blue) rates as a function of log regularization strength. L_0Hawkes uses $\tau = 1$.

Figure 4: Comparison of $\boldsymbol{x}^*$ (flattened A in each row) computed with 100 different τ values.

Comparison with neural Granger models. We generated two synthetic multivariate event datasets, sparse5 and dense10, with a standard point process simulator tick [5]. One has $D = 5$ with a sparse causal graph, as shown in Fig. 1 (b). The other has $D = 10$ and was generated with a relatively dense and noisy causal graph. Both have $N \sim 1\,000$ event instances. More details are in Appendix.

First, we compared L_0Hawkes with cLSTM and cMLP [38], state-of-the-art Granger causal learning algorithms, on sparse5. We generated 5 different datasets by changing the random seed of tick, one of which has been shown in Fig. 1 (c). We estimated A or the Granger causal matrix with many different values of the regularization parameters. We chose $\nu_A, \nu_\beta, \nu_\mu$ to be 0.1 and tested $\tau = 0.5, 1, 2$. The goal is to retrieve the simple causal graph in Fig. 1 (b), which has 2 positive and 18 negative edges as the ground truth, omitting the self-loops. For cLSTM and cMLP, the dataset was converted into 5-dimensional equi-interval time-series of event counts with N time points, based on a sliding window whose size is 10 times larger than the mean event inter-arrival time. The number of hidden units was 100 (from [38]) and the lag (or LSTM's 'context' length) is 10 for both. The mean computational time was (46, 881, 382) seconds per one parameter set for (L_0Hawkes, cMLP, cLSTM), respectively, on a laptop PC (i7 CPU, 32GB memory, Quadro P3200 GPU).

Figure 3 compares the true positive (TP) and true negative (TN) rates as a function of log regularization strength. The plot allows us to directly choose one regularization strength and is more useful than the ROC (receiver operating

Table 1: Break-even accuracies in Fig. 3.

L_0Hawkes	cLSTM	cMLP
1.00 ± 0.11	0.43 ± 0.09	0.31 ± 0.10

characteristic) curve. The fitting curves were computed with Gaussian process regression (GBR) [35] with optimized hyperparameters (details in Appendix). The TP rate at the intersection with the TN curve are called the *break-even accuracy*, which can be thought of as an overall performance metric. Table 1 summarizes the break-even accuracies, where the standard deviation was estimated with the GPR fitting. The contrast is clear. cLSTM and cMLP failed to capture the very simple causality while L_0Hawkes reproduced it almost perfectly. The main reason is that the event density of self-exciting events can be highly non-uniform in time (as seen from Fig. 1 (c)), which is inconsistent to the equi-interval assumption of the autoregressive or RNN-type models.

Comparison with sparse Hawkes models. Next, we compared L_0Hawkes with ℓ_1-regularizatoin based [50] ('L$_1$') and $\ell_{2,1}$-regularization based [44] ('L$_{2,1}$') models on dense10. Figure 4 compares the solution A* obtained by the three methods. We solved Eq. (17) 100 times for each, changing the value of the regularization strength τ from 0 to 2. We used $\epsilon = 0.01$ for L_0Hawkes. All the three methods share the same values of τ and $\nu_A = 10^{-9}$. The matrix elements are sorted in the ascending order of the value of $\bar{\boldsymbol{x}}$ in Eq. (23). As shown in the figure, L$_1$ and L$_{2,1}$ produce a smooth *non*-sparse profile, as expected from Theorem 2. In contrast, L_0Hawkes gets more "off" entries (shown in black) as τ increases. Note that the result is *different from naive thresholding on $\bar{\boldsymbol{x}}$* (Eq. (23)). In fact, we see irregular sparsity patterns as τ increases, depending on the relative magnitude of g_m and h_m.

Now that we have confirmed the capability of L_0Hawkes in sparse Granger causal learning, let us leverage it in real-world causal diagnosis tasks.

Power grid failure diagnosis. We obtained failure event data ('grid') of power grid from U.S. Department of Energy [1]. The failure events represent abrupt changes in the voltage and/or current signals measured with phasor measurement units (PMUs), which are deployed in geographically distributed locations in the power grid. The network topology is not given for privacy concerns. Only anonymized PMU IDs are given. We are interested in discovering a hidden causal relationship in a data-driven manner from the temporal event data alone. This is a type-level causal diagnosis task.

Figure 5: Sparsity pattern of estimated A on the grid data with L_0Hawkes (left), L$_1$ (middle), and L$_{2,1}$ (right).

Figure 6: Results on the cloud data. (Left) Nonzero elements of $\{q_{n,i}\}$. (Right) Triggering probabilities for the 150th instance (i.e. $q_{150,i}$).

The dataset records $N = 3\,811$ failure events labeled as "line outages" from $D = 22$ PMUs over a 10-month period. We grid-searched the model parameters based on AIC to get $5 \times (10^{-3}, 10^{-4}, 10^{-4})$ for $(\nu_\mu, \nu_\beta, \mu_A)$ and $(1, 1)$ for (τ, ϵ). The value of ϵ corresponds to about 3% of $\max_{k,l} A_{k,l}$. We used the same τ for the ℓ_1 and $\ell_{2,1}$ regularizers. We used the power decay of $\eta = 2$ to capture long-tail behaviors. Figure 5 compares computed A, in which nonzero matrix elements are shown in black. In L$_1$ and L$_{2,1}$, zero entries can appear only when $Q_{k,l}$ happens to be numerically zero. In contrast, L_0Hawkes enjoys guaranteed sparsity. From the computed A, a hidden causal structure among PMUs were successfully discovered. In particular, a PMU called B904 seems to be a dominatingly influential source of failures. We leave further details to Appendix.

Data center warning event diagnosis. Finally, we applied L_0Hawkes to a real data center management task. We obtained $N = 718$ warning events from a real cloud system. These events result from filtering logs emitted by network devices and each has its type. There are $D = 14$ unique event types in our dataset ('cloud'). This is an *instance-level* causal diagnosis task ("who caused this?").

Figure 6 (left) visualizes nonzero entries of $\{q_{n,i}\}$, where those with $q_{n,i} < 0.01$ are omitted. As expected, $\{q_{n,i}\}$ is quite sparse, and hence, event consolidation can be straightforwardly performed by picking nonzero triggering probabilities. The right panel shows such an example, showing $q_{150,i}$, in which the rightmost slot (in red) corresponds to the self probability $q_{150,150}$. For each i, its event type d_i is shown below the bar. The type of the event in question, ETH_INIT, is related to the process of initializing an Ethernet interface. Note in the figure that the self probability of this instance was computed as 0, while several preceding instances of the same type have positive triggering probabilities, leading to successful suppression of duplication.

Many instances have zero triggering probability despite their time proximity (the six events with positive probabilities were within 27 seconds from the 150th event), thanks to the sparsity of A. For example, this dataset contains 416 instances of event type UPDOWN adding considerable noise but were appropriately ignored by our method. Unlike naive hard-windowing approaches, our framework is able to sift for genuine causal relationships. See Appendix for more details.

7 Concluding remarks

We proposed a new sparse Granger-causal learning framework for stochastic event data. We pointed out that the existing sparse MM algorithms do not have a sparse solution (Theorem 2). We also showed that the neural Granger framework is of limited use for event data, mainly due to its equi-time-interval assumption. The proposed Hawkes-Granger model produces mathematically well-defined sparsity and allows simultaneous instance- and type-level causal event diagnosis with good interpretability enabled by the sparsity.

Limitations and future work. We have discussed the indistinguishability issue of the Hawkes-Granger model in Sec. 4.1. The current model still has some arbitrariness in additive and multiplicative operations. Although the ℓ_2 regularizer can control some of it, detailed empirical and theoretical studies are needed for more stable Granger-causal learning.

References

[1] To be made publicly available by the Department of Energy.

[2] M. Achab, E. Bacry, S. Gaïffas, I. Mastromatteo, and J.-F. Muzy. Uncovering causality from multivariate Hawkes integrated cumulants. *Journal of Machine Learning Research*, 18(1):6998–7025, 2017.

[3] H. Alvari and P. Shakarian. Hawkes process for understanding the influence of pathogenic social media accounts. In *2019 2nd International Conference on Data Intelligence and Security (ICDIS)*, pages 36–42. IEEE, 2019.

[4] A. Arnold, Y. Liu, and N. Abe. Temporal causal modeling with graphical Granger methods. In *Proceedings of the 13th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 66–75, 2007.

[5] E. Bacry, M. Bompaire, P. Deegan, S. Gaïffas, and S. V. Poulsen. tick: a Python library for statistical learning, with an emphasis on Hawkes processes and time-dependent models. *Journal of Machine Learning Research*, 18(214):1–5, 2018.

[6] E. Bacry, M. Bompaire, S. Gaïffas, and J.-F. Muzy. Sparse and low-rank multivariate Hawkes processes. *Journal of Machine Learning Research*, 21(50):1–32, 2020.

[7] E. Choi, N. Du, R. Chen, L. Song, and J. Sun. Constructing disease network and temporal progression model via context-sensitive Hawkes process. In *2015 IEEE International Conference on Data Mining*, pages 721–726. IEEE, 2015.

[8] K. N. Dominiak and A. R. Kristensen. Prioritizing alarms from sensor-based detection models in livestock production–A review on model performance and alarm reducing methods. *Computers and Electronics in Agriculture*, 133:46–67, 2017.

[9] N. Du, H. Dai, R. Trivedi, U. Upadhyay, M. Gomez-Rodriguez, and L. Song. Recurrent marked temporal point processes: Embedding event history to vector. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 1555–1564, 2016.

[10] M. Eichler, R. Dahlhaus, and J. Dueck. Graphical modeling for multivariate Hawkes processes with nonparametric link functions. *Journal of Time Series Analysis*, 38(2):225–242, 2017.

[11] H. T. Elshoush and I. M. Osman. Alert correlation in collaborative intelligent intrusion detection systems–A survey. *Applied Soft Computing*, 11(7):4349–4365, 2011.

[12] J. Enguehard, D. Busbridge, A. Bozson, C. Woodcock, and N. Hammerla. Neural temporal point processes for modelling electronic health records. In *Machine Learning for Health*, pages 85–113. PMLR, 2020.

[13] J. V. Escobar. A Hawkes process model for the propagation of covid-19: Simple analytical results. *EPL (Europhysics Letters)*, 131(6):68005, 2020.

[14] C. W. J. Granger. Investigating causal relations by econometric models and cross-spectral methods. *Econometrica*, 37(3):424–438, 1969.

[15] A. Hawkes. Spectra of some self-exciting and mutually exciting point processes. *Biometrika*, 58(1):83–90, 1971.

[16] S. A. Hosseini, A. Khodadadi, A. Arabzadeh, and H. R. Rabiee. HNP3: A hierarchical nonparametric point process for modeling content diffusion over social media. In *2016 IEEE 16th International Conference on Data Mining (ICDM)*, pages 943–948. IEEE, 2016.

[17] D. R. Hunter and K. Lange. A tutorial on MM algorithms. *The American Statistician*, 58(1):30–37, 2004.

[18] S. Kim, D. Putrino, S. Ghosh, and E. N. Brown. A Granger causality measure for point process models of ensemble neural spiking activity. *PLoS Comput Biol*, 7(3):e1001110, 2011.

[19] H. Li, H. Li, and S. S. Bhowmick. CHASSIS: Conformity meets online information diffusion. In *Proceedings of the 2020 ACM SIGMOD International Conference on Management of Data*, pages 1829–1840, 2020.

[20] L. Li, H. Deng, J. Chen, and Y. Chang. Learning parametric models for context-aware query auto-completion via Hawkes processes. In *Proceedings of the Tenth ACM International Conference on Web Search and Data Mining*, pages 131–139, 2017.

[21] L. Li, H. Deng, A. Dong, Y. Chang, and H. Zha. Identifying and labeling search tasks via query-based Hawkes processes. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 731–740, 2014.

[22] S. Li, X. Gao, W. Bao, and G. Chen. FM-Hawkes: A Hawkes process based approach for modeling online activity correlations. In *Proceedings of the 2017 ACM on Conference on Information and Knowledge Management*, pages 1119–1128, 2017.

[23] J. C. Louzada Pinto and T. Chahed. Modeling user and topic interactions in social networks using Hawkes processes. In *Proceedings of the 8th International Conference on Performance Evaluation Methodologies and Tools*, pages 58–65, 2014.

[24] A. Lozano, N. Abe, Y. Liu, and S. Rosset. Grouped graphical Granger modeling for gene expression regulatory networks discovery. *Bioinformatics*, 25(12):110–118, 2009.

[25] M. Mark and T. A. Weber. Robust identification of controlled Hawkes processes. *Physical Review E*, 101(4):043305, 2020.

[26] H. Mei and J. M. Eisner. The neural Hawkes process: A neurally self-modulating multivariate point process. In *Advances in Neural Information Processing Systems*, pages 6754–6764, 2017.

[27] J. Moyne and J. Iskandar. Big data analytics for smart manufacturing: Case studies in semiconductor manufacturing. *Processes*, 5(3):39, 2017.

[28] R. M. Neal and G. E. Hinton. A view of the EM algorithm that justifies incremental, sparse, and other variants. In *Learning in graphical models*, pages 355–368. Springer, 1998.

[29] M. Nickel and M. Le. Learning multivariate Hawkes processes at scale. *arXiv:2002.12501*, 2020.

[30] Y. Ogata. Seismicity analysis through point-process modeling: A review. In *Seismicity patterns, their statistical significance and physical meaning*, pages 471–507. Springer, 1999.

[31] T. Omi and K. A. Naonori Ueda and. Fully neural network based model for general temporal point processes. In *Advances in Neural Information Processing Systems*, pages 2122–2132, 2019.

[32] T. Ozaki. Maximum likelihood estimation of Hawkes' self-exciting point processes. *Annals of the Institute of Statistical Mathematics*, 31(1):145–155, 1979.

[33] D. Phan and T. Idé. ℓ_0-regularized sparsity for probabilistic mixture models. In *Proc. SIAM Intl. Conf. Data Mining*, pages 172–180. SIAM, 2019.

[34] J. C. L. Pinto, T. Chahed, and E. Altman. Trend detection in social networks using Hawkes processes. In *Proceedings of the 2015 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining 2015*, pages 1441–1448, 2015.

[35] C. E. Rasmussen and C. Williams. *Gaussian Processes for Machine Learning*. MIT Press, 2006.

[36] M.-A. Rizoiu, L. Xie, S. Sanner, M. Cebrian, H. Yu, and P. Van Hentenryck. Expecting to be hip: Hawkes intensity processes for social media popularity. In *Proceedings of the 26th International Conference on World Wide Web*, pages 735–744, 2017.

[37] Y. Tanaka, T. Kurashima, Y. Fujiwara, T. Iwata, and H. Sawada. Inferring latent triggers of purchases with consideration of social effects and media advertisements. In *Proceedings of the Ninth ACM International Conference on Web Search and Data Mining*, pages 543–552. ACM, 2016.

[38] A. Tank, I. Covert, N. Foti, A. Shojaie, and E. B. Fox. Neural Granger causality. *IEEE Transactions on Pattern Analysis & Machine Intelligence*, (01):1–1, 2021.

[39] A. C. Türkmen, Y. Wang, and A. J. Smola. Fastpoint: Scalable deep point processes. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 465–480, 2019.

[40] A. Veen and F. P. Schoenberg. Estimation of space–time branching process models in seismology using an EM–type algorithm. *Journal of the American Statistical Association*, 103(482):614–624, 2008.

[41] Y. Wang, X. Ye, H. Zhou, H. Zha, and L. Song. Linking micro event history to macro prediction in point process models. In *Artificial Intelligence and Statistics*, pages 1375–1384, 2017.

[42] O. G. Ward, J. Wu, T. Zheng, A. L. Smith, and J. P. Curley. Network Hawkes process models for exploring latent hierarchy in social animal interactions. *arXiv preprint arXiv:2012.09598*, 2020.

[43] S. Xiao, J. Yan, X. Yang, H. Zha, and S. M. Chu. Modeling the intensity function of point process via recurrent neural networks. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence*, pages 1597–1603, 2017.

[44] H. Xu, M. Farajtabar, and H. Zha. Learning Granger causality for Hawkes processes. In *Proceedings of the International Conference on Machine Learning*, pages 1717–1726, 2016.

[45] H. Xu, D. Luo, and L. Carin. Online continuous-time tensor factorization based on pairwise interactive point processes. In *Proc. IJCAI*, pages 2905–2911, 2018.

[46] C. Zhang, H. Wu, R. Bie, R. Mehmood, and A. Kos. Dynamic modeling of failure events in preventative pipe maintenance. *IEEE Access*, 6:12539–12550, 2018.

[47] L.-n. Zhang, X. Zuo, and J.-w. Liu. Derivative failure of compressor station analysis based on Hawkes process. In *2020 39th Chinese Control Conference (CCC)*, pages 4089–4096, 2020.

[48] Q. Zhang, A. Lipani, O. Kirnap, and E. Yilmaz. Self-attentive Hawkes process. In *International Conference on Machine Learning*, pages 11183–11193, 2020.

[49] Y. Zhao, X. Qi, Z. Liu, Y. Zhang, and T. Zheng. Mining medical records with a klipi multi-dimensional Hawkes model. In *Proc. SIGKDD Workshop Health Informat.*, pages 1–8, 2015.

[50] K. Zhou, H. Zha, and L. Song. Learning social infectivity in sparse low-rank networks using multi-dimensional Hawkes processes. In *Artificial Intelligence and Statistics*, pages 641–649, 2013.

[51] S. Zuo, H. Jiang, Z. Li, T. Zhao, and H. Zha. Transformer Hawkes process. In *International Conference on Machine Learning*, pages 11692–11702. PMLR, 2020.