REVERSE ENGINEERING OF IMPERCEPTIBLE ADVERSARIAL IMAGE PERTURBATIONS

ABSTRACT

It has been well recognized that neural network based image classifiers are easily fooled by images with tiny perturbations crafted by an adversary. There has been a vast volume of research to generate and defend such adversarial attacks. However, the following problem is left unexplored: *How to reverse-engineer adversarial perturbations from an adversarial image?* This leads to a new adversarial learning paradigm—Reverse Engineering of Deceptions (RED). If successful, RED allows us to estimate adversarial perturbations and recover the original images. However, carefully crafted, tiny adversarial perturbations are difficult to recover by optimizing a unilateral RED objective. For example, the pure image denoising method may overfit to minimizing the reconstruction error but hardly preserves the classification properties of the true adversarial perturbations. To tackle this challenge, we formalize the RED problem and identify a set of principles crucial to the RED approach design. Particularly, we find that prediction alignment and proper data augmentation (in terms of spatial transformations) are two criteria to achieve a generalizable RED approach. By integrating these RED principles with image denoising, we propose a new Class-Discriminative Denoising based RED framework, termed CDD-RED. Extensive experiments demonstrate the effectiveness of CDD-RED under different evaluation metrics (ranging from the pixel-level, prediction-level to the attribution-level alignment) and a variety of attack generation methods (*e.g.*, FGSM, PGD, CW, AutoAttack, and adaptive attacks).

1 INTRODUCTION

Deep neural networks (DNNs) are susceptible to adversarially-crafted tiny input perturbations during inference. Such imperceptible perturbations, *a.k.a.* adversarial attacks, could cause DNNs to draw manifestly wrong conclusions. The existence of adversarial attacks was first uncovered in the domain of image classification (Goodfellow et al., 2014; Carlini & Wagner, 2017; Papernot et al., 2016b), and was then rapidly extended to the other domains, such as object detection (Xie et al., 2017; Serban et al., 2020), language modeling (Cheng et al., 2020; Srikant et al., 2021), and medical machine learning (Finlayson et al., 2019; Antun et al., 2020). Despite different applications, the underlying attack formulations and generation methods commonly obey the ones used in image classification.

A vast volume of existing works have been devoted to designing defenses against such attacks, mostly focusing on either detecting adversarial examples (Grosse et al., 2017; Yang et al., 2020; Metzen et al., 2017; Meng & Chen, 2017; Wójcik et al., 2020) or acquiring adversarially robust DNNs (Madry et al., 2017; Zhang et al., 2019; Wong & Kolter, 2017; Salman et al., 2020; Wong et al., 2020; Carmon et al., 2019; Shafahi et al., 2019). Despite the plethora of prior work on adversarial defenses, it seems impossible to achieve 'perfect' robustness. Given the fact that adversarial attacks are inevitable (Shafahi et al., 2020), we ask whether or not an adversarial attack can be reverse-engineered so that one can recognize the adversary's information (*e.g.*, adversarial perturbations) behind the attack instances. The above problem is referred to as *Reverse Engineering of Deceptions (RED)*, fostering a new adversarial learning regime. The development of RED technologies will also enable the adversarial situation awareness in high-stake applications.

To the best of our knowledge, few work studied the RED problem. The most relevant one that we are aware of is (Pang et al., 2020), which proposed the so-called query of interest (QOI) estimation model to infer the adversary's target class by model queries. However, the work (Pang et al., 2020) was

restricted to the black-box attack scenario and thus lacks a general formulation of RED. Furthermore, it has not built a complete RED pipeline, which should not only provide a solution to estimating the adversarial example but also formalizing evaluation metrics to comprehensively measure the performance of RED. In this paper, we aim to take a solid step towards addressing the RED problem.

1.1 CONTRIBUTIONS

The main contributions of our work is listed below.

• We formulate the Reverse Engineering of Deceptions (RED) problem that is able to estimate adversarial perturbations and provides the feasibility of inferring the strategy of an adversary, *e.g.*, 'adversary saliency regions' of an adversarial image.

• We identify a series of RED principles to effectively estimate the adversarially-crafted tiny perturbations. We find that the class-discriminative ability is crucial to evaluate the RED performance. We also find that data augmentation, *e.g.*, spatial transformations, is another key to improve the RED result. Furthermore, we integrate the developed RED principles into image denoising and propose a denoiser-assisted RED approach.

• We build a comprehensive evaluation pipeline to quantify the RED performance from different perspectives, such as pixel-level reconstruction error, prediction-level alignment, and attribution-level adversary saliency region recovery. With an extensive experimental study, we show that, compared to image denoising baselines, our proposal yields a consistent improvement across diverse RED evaluation metrics and attack generation methods, *e.g.*, FGSM (Goodfellow et al., 2014), CW (Carlini & Wagner, 2017), PGD (Madry et al., 2017) and AutoAttack (Croce & Hein, 2020).

1.2 RELATED WORK

Adversarial attacks. Different types of adversarial attacks have been proposed, ranging from digital attacks (Goodfellow et al., 2014; Carlini & Wagner, 2017; Madry et al., 2017; Croce & Hein, 2020; Xu et al., 2019b; Chen et al., 2017a; Xiao et al., 2018) to physical attacks (Eykholt et al., 2018; Li et al., 2019; Athalye et al., 2018; Chen et al., 2018; Xu et al., 2019c). The former gives the most fundamental threat model that commonly deceives DNN models during inference by crafting imperceptible adversarial perturbations. The latter extends the former to fool the victim models in the physical environment. Compared to digital attacks, physical attacks require much larger perturbation strengths to enhance the adversary's resilience to various physical conditions such as lightness and object deformation (Athalye et al., 2018; Xu et al., 2019c).

In this paper, we focus on ℓ_p-norm ball constrained attacks, *a.k.a.* ℓ_p attacks, for $p \in \{1, 2, \infty\}$, most widely-used in digital attacks. Examples include FGSM (Goodfellow et al., 2014), PGD (Madry et al., 2017), CW (Carlini & Wagner, 2017), and the recently-released attack benchmark AutoAttack (Croce & Hein, 2020). Based on the adversary's intent, ℓ_p attacks are further divided into untargeted attacks and targeted attacks, where in contrast to the former, the latter designates the (incorrect) prediction label of a victim model. When an adversary has no access to victim models' detailed information (such as architectures and model weights), ℓ_p attacks can be further generalized to black-box attacks by leveraging either surrogate victim models (Papernot et al., 2017; 2016a; Dong et al., 2019; Liu et al., 2017) or input-output queries from the original black-box models (Chen et al., 2017b; Liu et al., 2019; Cheng et al., 2019).

Adversarial defenses. To improve the robustness of DNNs, a variety of approaches have been proposed to defend against ℓ_p attacks. One line of research focuses on enhancing the robustness of DNNs during training, *e.g.*, adversarial training (Madry et al., 2017), TRADES (Zhang et al., 2019), randomized smoothing (Wong & Kolter, 2017), and their variants (Salman et al., 2020; Wong et al., 2020; Carmon et al., 2019; Shafahi et al., 2019; Uesato et al., 2019; Chen et al., 2020). Another line of research is to detect adversarial attacks without altering the victim model or the training process. The key technique is to differentiate between benign and adversarial examples by measuring their 'distance.' Such a distance measure has been defined in the input space via pixel-level reconstruction error (Meng & Chen, 2017; Liao et al., 2018), in the intermediate layers via neuron activation anomalies (Xu et al., 2019a), and in the logit space by tracking the sensitivity of deep feature attributions to input perturbations (Yang et al., 2020).

In contrast to RED, *adversarial detection is a relatively simpler problem* as a roughly approximated distance possesses detection-ability (Meng & Chen, 2017; Luo et al., 2015). Among the existing

adversarial defense techniques, the recently-proposed Denoised Smoothing (DS) method (Salman et al., 2020) is more related to ours. In (Salman et al., 2020), an image denoising network is prepended to an existing victim model so that the augmented system can be performed as a smoothed image classifier with certified robustness. Although DS is not designed for RED, its denoised output can be regarded as a benign example estimate. The promotion of classification stability in DS also motivates us to design the RED methods with class-discriminative ability. Thus, DS will be a main baseline approach for comparison.

2 REVERSE ENGINEERING OF DECEPTIONS: FORMULATION AND CHALLENGES

In this section, we first introduce the threat model of our interest: adversarial attacks on images. Based on that, we formalize the Reverse Engineering of Deceptions (RED) problem and demonstrate its challenges through some 'warm-up' examples.

Preliminaries on threat model. We focus on ℓ_p attacks, where the *adversary's goal* is to generate imperceptible input perturbations to fool a well-trained image classifier. Formally, let $\mathbf{x}$ denote a benign image, and $\boldsymbol{\delta}$ an additive perturbation variable. Given a victim classifier f and a perturbation strength tolerance ϵ (in terms of, *e.g.*, ℓ_∞-norm constraint $\|\boldsymbol{\delta}\|_\infty \leq \epsilon$), the desired *attack generation algorithm* $\mathcal{A}$ then seeks the optimal $\boldsymbol{\delta}$ subject to the perturbation constraints. Such an attack generation process is denoted by $\boldsymbol{\delta} = \mathcal{A}(\mathbf{x}, f, \epsilon)$, resulting in an adversarial example $\mathbf{x}' = \mathbf{x} + \boldsymbol{\delta}$. Here $\mathcal{A}$ can be fulfilled by different attack methods, e.g., FGSM (Goodfellow et al., 2014), CW (Carlini & Wagner, 2017), PGD (Madry et al., 2017), and AutoAttack (Croce & Hein, 2020).

Problem formulation of RED. Different from conventional defenses to detect or reject adversarial instances (Pang et al., 2020; Liao et al., 2018; Shafahi et al., 2020; Niu et al., 2020), RED aims to address the following question.

> **(RED problem)** Given an adversarial instance, can we reverse-engineer the adversarial perturbations $\boldsymbol{\delta}$, and infer the adversary's objective and knowledge, *e.g.*, true image class behind deception and adversary saliency image region?

Formally, we aim to recover $\boldsymbol{\delta}$ from an adversarial example $\mathbf{x}'$ under the prior knowledge of the victim model f or its substitute $\hat{f}$ if the former is a black box. We denote the RED operation as $\boldsymbol{\delta} = \mathcal{R}(\mathbf{x}', \hat{f})$, which covers the white-box scenario ($\hat{f} = f$) as a special case. We propose to learn a parametric model $\mathcal{D}_{\boldsymbol{\theta}}$ (*e.g.*, a denoising neural network that we will focus on) as an approximation of $\mathcal{R}$ through a training dataset of adversary-benignity pairs $\Omega = \{(\mathbf{x}', \mathbf{x})\}$. Through $\mathcal{D}_{\boldsymbol{\theta}}$, RED will provide a **benign example estimate** $\mathbf{x}_{\mathrm{RED}}$ and a **adversarial example estimate** $\mathbf{x}'_{\mathrm{RED}}$ as below:

$$\mathbf{x}_{\mathrm{RED}} = \mathcal{D}_{\boldsymbol{\theta}}(\mathbf{x}'), \quad \mathbf{x}'_{\mathrm{RED}} = \underbrace{\mathbf{x}' - \mathbf{x}_{\mathrm{RED}}}_{\text{perturbation estimate}} + \mathbf{x}, \tag{1}$$

where a **perturbation estimate** is given by subtracting the RED's output with its input, $\mathbf{x}' - \mathcal{D}_{\boldsymbol{\theta}}(\mathbf{x}')$.

We **highlight** that RED yields a new defensive approach aiming to 'diagnose' the perturbation details of an existing adversarial example in a post-hoc, forensic manner. This is different from adversarial detection (AD). Fig.1 provides a visual comparison of RED with AD. Although AD is also designed in a post-hoc manner, it aims to determine whether an input is an adversarial example for a victim model based on certain statistics on model features or logits. Besides, AD might be used as a pre-processing step of RED, where the former provides 'detected' adversarial examples for fine-level RED diagnosis. Therefore, RED and AD are isolated but complementary building blocks.

Figure 1: Overview of RED versus AD.

Challenges of RED In this work, we will specify the RED model $\mathcal{D}_{\boldsymbol{\theta}}$ as a denoising network. However, it is highly non-trivial to design a proper denoiser for RED. Speaking at a high level, there

exist two main challenges. First, unlike the conventional image denoising strategies (Zhang et al., 2017), the design of an RED-aware denoiser needs to take into account the effects of victim models and data properties of adversary-benignity pairs. Second, it might be insufficient to merely minimize the reconstruction error as the adversarial perturbation is finely-crafted (Niu et al., 2020). Therefore, either under- or over-denoising will lead to poor RED performance.

3 RED EVALUATION METRICS AND DENOISING-ONLY BASELINE

Since RED is different from existing defensive approaches, we first develop new performance metrics of RED, ranging from pixel-level reconstruction error to attribution-level adversary saliency region. We next leverage the proposed performance metrics to demonstrate why a pure image denoiser is incapable of fulfilling RED.

RED evaluation metrics. Given a learned RED model $\mathcal{D}_{\boldsymbol{\theta}}$, the RED performance will be evaluated over a testing dataset $(\mathbf{x}', \mathbf{x}) \in \mathcal{D}_{\text{test}}$; see implementation details in Sec. 5. Here, $\mathbf{x}'$ is used as the testing input of the RED model, and $\mathbf{x}$ is the associated ground-truth benign example for comparison. The benign example estimate $\mathbf{x}_{\text{RED}}$ and adversarial example estimate $\mathbf{x}'_{\text{RED}}$ are obtained following (1). RED evaluation pipeline is conducted from the following aspects: ① pixel-level reconstruction error, ② prediction-level inference alignment, and ③ attribution-level adversary saliency region.

➤ ① **Pixel-level**: Reconstruction error given by $d(\mathbf{x}, \mathbf{x}_{\text{RED}}) = \mathbb{E}_{(\mathbf{x}', \mathbf{x}) \in \mathcal{D}_{\text{test}}}[\|\mathbf{x}_{\text{RED}} - \mathbf{x}\|_2]$.

➤ ② **Prediction-level**: Prediction alignment (PA) between the pair of *benign* example and its estimate $(\mathbf{x}_{\text{RED}}, \mathbf{x})$ and PA between the pair of *adversarial* example and its estimate $(\mathbf{x}'_{\text{RED}}, \mathbf{x}')$, given by

$$\text{PA}_{\text{benign}} = \frac{\text{card}(\{(\mathbf{x}_{\text{RED}}, \mathbf{x}) \mid F(\mathbf{x}_{\text{RED}}) = F(\mathbf{x})\})}{\text{card}(\mathcal{D}_{\text{test}})}, \ \text{PA}_{\text{adv}} = \frac{\text{card}(\{(\mathbf{x}'_{\text{RED}}, \mathbf{x}') \mid F(\mathbf{x}'_{\text{RED}}) = F(\mathbf{x}')\})}{\text{card}(\mathcal{D}_{\text{test}})}$$

where $\text{card}(\cdot)$ denotes a cardinality function of a set and F refers to the prediction label provided by the victim model f.

➤ ③ **Attribution-level**: Input attribution alignment (IAA) between the benign pair $(\mathbf{x}_{\text{RED}}, \mathbf{x})$ and between the adversarial pair $(\mathbf{x}'_{\text{RED}}, \mathbf{x}')$. In this work, we adopt GradCAM (Selvaraju et al., 2020) to attribute the predictions of classes back to input saliency regions. The rationale behind IAA is that the unnoticeable adversarial perturbations (in the pixel space) can introduce an evident input attribution discrepancy with respect to (w.r.t.) the true label y and the adversary's target label y' (Boopathy et al., 2020; Xu et al., 2019b). Thus, an accurate RED should be able to erase the adversarial attribution effect through $\mathbf{x}_{\text{RED}}$, and estimate the adversarial intent through the saliency region of $\mathbf{x}'_{\text{RED}}$ (see Fig. 1 for illustration).

Denoising-Only (DO) baseline. We further show that how a pure image denoiser, a 'must-try' baseline, is insufficient of tackling the RED problem. This failure case drive us to rethink the denoising strategy through the lens of RED. First, we obtain the denoising network by minimizing the reconstruction error between $\mathcal{D}_{\boldsymbol{\theta}}(\mathbf{x}')$ and $\mathbf{x}$:

Figure 2: IAA of DO compared with ground-truth.

$$\underset{\boldsymbol{\theta}}{\text{minimize}} \quad \ell_{\text{denoise}}(\boldsymbol{\theta}; \Omega) := \mathbb{E}_{(\mathbf{x}', \mathbf{x}) \in \Omega} \|\mathcal{D}_{\boldsymbol{\theta}}(\mathbf{x}') - \mathbf{x}\|_1, \tag{2}$$

where a Mean Absolute Error (MAE)-type loss is used for denoising (Liao et al., 2018), and the creation of training dataset Ω is illustrated in Sec. 5.1. Let us then evaluate the performance of DO through the non-adversarial prediction alignment $\text{PA}_{\text{benign}}$ and IAA. We find that $\text{PA}_{\text{benign}} = 42.8\%$ for DO. And Fig. 2 shows the IAA performance of DO w.r.t. an input example. As we can see, DO is not capable of exactly recovering the adversarial saliency regions compared to the ground-truth adversarial perturbations. These suggest that DO-based RED lacks the reconstruction ability at the prediction and the attribution levels.

4 CLASS-DISCRIMINATIVE DENOISING FOR RED

In this section, we propose a novel Class-Discriminative Denoising based RED approach termed CDD-RED; see Fig. 3 for an overview. CDD-RED contains two key components. First, we propose a PA regularization to enforce the prediction-level stabilities of both estimated benign example $\mathbf{x}_{\mathrm{RED}}$ and adversarial example $\mathbf{x}'_{\mathrm{RED}}$ with respect to their true counterparts $\mathbf{x}$ and $\mathbf{x}'$, respectively. Second, we propose a data augmentation strategy to improve the RED's generalization without losing its class-discriminative ability.

Figure 3: CDD-RED overview.

Benign and adversarial prediction alignment. To accurately estimate the adversarial perturbation from an adversarial instance, the lessons from the DO approach suggest to preserve the class-discriminative ability of RED estimates to align with the original predictions, given by $\mathbf{x}_{\mathrm{RED}}$ vs. $\mathbf{x}$, and $\mathbf{x}'_{\mathrm{RED}}$ vs. $\mathbf{x}'$. Spurred by that, the training objective of CDD-RED is required not only to minimize the reconstruction error like (2) but also to maximize PA, namely, 'clone' the class-discriminative ability of original data. To achieve this goal, we augment the denoiser $\mathcal{D}_{\boldsymbol{\theta}}$ with a known classifier $\hat{f}$ to generate predictions of estimated benign and adversarial examples (see Fig. 3), *i.e.*, $\mathbf{x}_{\mathrm{RED}}$ and $\mathbf{x}'_{\mathrm{RED}}$ defined in (1). By contrasting $\hat{f}(\mathbf{x}_{\mathrm{RED}})$ with $\hat{f}(\mathbf{x})$, and $\hat{f}(\mathbf{x}'_{\mathrm{RED}})$ with $\hat{f}(\mathbf{x}')$, we can promote PA by minimizing the prediction gap between true examples and estimated ones:

$$\ell_{\mathrm{PA}}(\boldsymbol{\theta};\Omega) = \mathbb{E}_{(\mathbf{x}',\mathbf{x})\in\Omega}[\ell_{\mathrm{PA}}(\boldsymbol{\theta};\mathbf{x}',\mathbf{x})], \ \ell_{\mathrm{PA}}(\boldsymbol{\theta};\mathbf{x}',\mathbf{x}) := \underbrace{\mathrm{CE}(\hat{f}(\mathbf{x}_{\mathrm{RED}}),\hat{f}(\mathbf{x}))}_{\text{PA for benign prediction}} + \underbrace{\mathrm{CE}(\hat{f}(\mathbf{x}'_{\mathrm{RED}}),\hat{f}(\mathbf{x}'))}_{\text{PA for adversarial prediction}}, \quad (3)$$

where CE denotes the cross-entropy loss. To enhance the class-discriminative ability, it is desirable to integrate the denoising loss (2) with the PA regularization (3), leading to $\ell_{\mathrm{denoise}} + \lambda\ell_{\mathrm{PA}}$, where $\lambda > 0$ is a regularization parameter. To address this issue, we will further propose a data augmentation method to improve the denoising ability without losing the advantage of PA regularization.

Proper data augmentation improves RED. The rationale behind incorporating image transformations into CDD-RED lies in two aspects. First, application of data transformation can make RED foveated to the most informative attack artifacts since an adversarial instance could be sensitive to input transformations (Luo et al., 2015; Athalye et al., 2018; Xie et al., 2019; Li et al., 2020). Second, the identification of transformation-resilient benign/adversarial instances may enhance the capabilities of PA and IAA.

Figure 4: The influence of different data augmentations. Here 'base' refers to the base training without using augmentation.

However, it is highly non-trivial to determine the most appropriate data augmentation operations. For example, a pixel-sensitive data transformation, e.g., Gaussian blurring and colorization, would hamper the reconstruction-ability of the original adversary-benignity pair $(\mathbf{x}', \mathbf{x})$. Therefore, we focus on spatial image transformations, including rotation, translation, cropping & padding, cutout, and CutMix (Yun et al., 2019), which keep the original perturbation in a linear way. In Fig.4, we evaluate the RED performance, in terms of pixel-level reconstruction error and prediction-level alignment accuracy, for different kinds of spatial image transformations. As we can see, CutMix and cropping & padding can increase the pixel-level and prediction-level performance simultaneously, thus are considered as the appropriate augmentation methods to boost the RED performance. Furthermore, we empirically find that combining these two transformations can further improve the performance.

Let $\mathcal{T}$ denote a transformation set, including cropping & padding and CutMix operations. With the aid of the denoising loss (2), PA regularization (3), and data transformations $\mathcal{T}$, we then cast the overall training objective of CDD-RED as

$$\underset{\boldsymbol{\theta}}{\text{minimize}} \quad \underbrace{\mathbb{E}_{(\mathbf{x}',\mathbf{x})\in\Omega, t\sim\mathcal{T}} \|\mathcal{D}_{\boldsymbol{\theta}}(t(\mathbf{x}')) - t(\mathbf{x})\|_1}_{\ell_{\text{denoise}} \text{ (2) with data augmentations}} + \underbrace{\lambda\mathbb{E}_{(\mathbf{x}',\mathbf{x})\in\Omega, t\sim\check{\mathcal{T}}}[\ell_{\text{PA}}(\boldsymbol{\theta}; t(\mathbf{x}'), t(\mathbf{x}))]}_{\ell_{\text{PA}} \text{ (3) with data augmentation via } \check{\mathcal{T}}}, \quad (4)$$

where $\check{\mathcal{T}}$ denotes a properly-selected subset of $\mathcal{T}$, and $\lambda > 0$ is a regularization parameter. In the PA regularizer (4), we need to avoid the scenario of over-transformation where data augmentation alters the classifier's original decision. This suggests $\check{\mathcal{T}} = \{t \in \mathcal{T} \mid \hat{F}(t(\mathbf{x})) = \hat{F}(\mathbf{x}), \hat{F}(t(\mathbf{x}')) = \hat{F}(\mathbf{x}')\}$, where $\hat{F}$ represents the prediction label of the pre-trained classifier $\hat{f}$, *i.e.*, $\hat{F}(\cdot) = \text{argmax}(\hat{f}(\cdot))$.

5 EXPERIMENTS

In this section, we demonstrate the effectiveness of our proposed method in 4 aspects: **a)** reconstruction error of adversarial perturbation inversion, *i.e.* $d(\mathbf{x}, \mathbf{x}_{\text{RED}})$, **b)** class-discriminative ability of the benign and the adversarial example estimate, *i.e.*, $\text{PA}_{\text{benign}}$ and PA_{adv} by victim models, **c)** adversary saliency region recovery, *i.e.*, attribution alignment, and **d)** RED evaluation over unseen attack types and adaptive attacks.

5.1 EXPERIMENT SETUP

Attack datasets. To train and test RED models, we generate adversarial examples on the ImageNet dataset (Deng et al., 2009). We consider 3 **attack methods** including PGD (Madry et al., 2017), FGSM (Goodfellow et al., 2014), and CW attack (Carlini & Wagner, 2017), applied to 5 **models** including pre-trained ResNet18 (Res18), Resnet50 (Res50) (He et al., 2015), VGG16, VGG19, and InceptionV3 (IncV3) (Szegedy et al., 2015). By default, PGD attack and FGSM attack are bounded by ℓ_∞-norm constraint and CW attack is bounded by ℓ_2-norm. The range of the perturbation strength ϵ for PGD attack and FGSM attack are $[1/255, 40/255)$ and $[1/255, 20/255)$, respectively. As for CW attack, the adversary's confidence parameter k is uniformly sampled from from $[1, 20]$. One attack method is applied to one victim model to obtain **3K successfully attacked images**. As a consequence, 45K ($3 \times 5 \times 3K$) adversarial images are generated in total: 37.5K for training and 7.5K for validating. The testing set contains 28K adversarial images generated with the same attack method & victim model. Furthermore, to evaluate the RED performance on unseen perturbation types during training, additional 2K adversarial examples generated by **AutoAttack** (Croce & Hein, 2020) and 1K adversarial examples generated by **Feature Attack** (Sabour et al., 2015) are included as the unseen testing dataset. AutoAttack is applied on VGG19, Res50 and **two new victim models**, i.e., Alexet and Robust Resnet50 (R-Res50), via fast adversarial training (Wong et al., 2020) while Feature Attack is applied on VGG19 and Alexnet. The rational behind considering Feature Attack is that feature adversary has been recognized as an effective way to circumvent adversarial detection (Tramer et al., 2020). Thus, it provides a supplement on detection-aware attacks.

RED model configuration, training and evaluation. During the training of the RED denoisers, VGG19 (Simonyan & Zisserman, 2015) is chosen as the pretrained classifier $\hat{f}$ for PA regularization. Although different victim models were used for generating adversarial examples, we will show that the inference guided by VGG19 is able to accurately estimate the true image class and the intent of the adversary. In terms of the architecture of $\mathcal{D}_{\boldsymbol{\theta}}$, DnCNN (Zhang et al., 2017) is adopted. The RED problem is solved using an Adam optimizer (Kingma & Ba, 2015) with the initial learning rate of 10^{-4}, which decays 10 times for every 140 training epochs. In (4), the regularization parameter λ is set as 0.025. The transformations for data augmentation include CutMix and cropping & padding. The maximum number of training epochs is set as 300.

Baselines. We compare CDD-RED with two baseline approaches: **a)** the conventional denoising-only (DO) approach with the objective function (2); **b)** The state-of-the-art Denoised Smmothing (DS) (Salman et al., 2020) approach that considers both the reconstruction error and the PA for benign examples in the objective function. Both methods are tuned to their best configurations.

5.2 MAIN RESULTS

Reconstruction error $d(\mathbf{x}, \mathbf{x}_{\text{RED}})$ **and PA.** Table 1 presents the comparison of CDD-RED with the baseline denoising approaches in terms of $d(\mathbf{x}, \mathbf{x}_{\text{RED}})$, $d(f(\mathbf{x}), f(\mathbf{x}_{\text{RED}}))$, $d(f(\mathbf{x}'), f(\mathbf{x}'_{\text{RED}}))$, $\text{PA}_{\text{benign}}$, and PA_{adv} on the testing dataset. As we can see, our approach (CDD-RED) improves the class-discriminative ability from benign perspective by 42.91% and adversar-

Table 1: The performance comparison among DO, DS and CDD-RED on the testing dataset.

	DO	DS	CDD-RED
$d(\mathbf{x}, \mathbf{x}_{\text{RED}})$	9.32	19.19	13.04
$d(f(\mathbf{x}), f(\mathbf{x}_{\text{RED}}))$	47.81	37.21	37.07
$d(f(\mathbf{x}'), f(\mathbf{x}'_{\text{RED}}))$	115.09	150.02	78.21
$\text{PA}_{\text{benign}}$	42.80%	86.64%	85.71%
PA_{adv}	71.97%	72.47%	80.43%

ial perspective by 8.46% with a slightly larger reconstruction error compared with the DO approach. In contrast to DS, CDD-RED achieves similar $\text{PA}_{\text{benign}}$ but improved pixel-level denoising error and PA_{adv}. Furthermore, CDD-RED achieves the best logit-level reconstruction error for both $f(\mathbf{x}_{\text{RED}})$ and $f(\mathbf{x}'_{\text{RED}})$ among the three approaches. This implies that $\mathbf{x}_{\text{RED}}$ rendered by CDD-RED can achieve highly similar prediction to the true benign example $\mathbf{x}$, and the perturbation estimate $\mathbf{x}' - \mathbf{x}_{\text{RED}}$ yields a similar misclassification effect to the ground-truth perturbation.

Figure 5: Interpretation (I) of benign ($\mathbf{x}/\mathbf{x}_{\text{RED}}$) and adversarial ($\mathbf{x}'/\mathbf{x}'_{\text{RED}}$) image w.r.t. the true label y='ptarmigan' and the adversary targeted label y'='shower curtain'. We compare three methods of RED training, DO, DS, and CDD-RED as our method, to the ground-truth interpretation. Given an RED method, the first column is $I(\mathbf{x}_{\text{RED}}, y)$ versus $I(\mathbf{x}'_{\text{RED}}, y)$, the second column is $I(\mathbf{x}_{\text{RED}}, y')$ versus $I(\mathbf{x}'_{\text{RED}}, y')$, and all maps under each RED method are normalized w.r.t. their largest value. For the ground-truth, the first column is $I(\mathbf{x}, y)$ versus $I(\mathbf{x}', y)$, the second column is $I(\mathbf{x}, y')$ versus $I(\mathbf{x}', y')$.

Attribution alignment. In addition to pixel-level alignment and prediction-level alignment to evaluate the RED performance, attribution alignment is examined in what follows. Following the proposed RED evaluation pipeline in Sec. 4, Fig. 5 presents attribution maps generated by GradCAM in terms of $\mathcal{I}(\mathbf{x}, y)$, $\mathcal{I}(\mathbf{x}', y)$, $\mathcal{I}(\mathbf{x}, y')$, and $\mathcal{I}(\mathbf{x}', y')$. From left to right is the attribution map over DO, DS, CDD-RED (our method), and the ground-truth. Compared with DO and DS, CDD-RED yields a closer attribution alignment with the ground-truth especially when making a comparison between $I(\mathbf{x}_{\text{RED}}, y)$ and $I(\mathbf{x}, y)$. At the dataset level, Fig. 6 shows the distribution of attribution IoU scores. It is observed that the IoU distribution of CDD-RED, compared with DO and DS, has a denser concentration over the high-value area, corresponding to closer alignment with the attribution map by adversary. This feature indicates an interesting application of the proposed RED approach, which is to achieve the recovery of adversary's saliency region, in terms of the class-discriminative image regions that the adversary focused on.

Figure 6: IoU distributions of the attribution alignment by three RED methods. Higher IoU is better. For each subfigure, there are four IoU scores, each standing for $\text{IoU}(\mathbf{x}_{\text{RED}}, \mathbf{x}, y)$, $\text{IoU}(\mathbf{x}_{\text{RED}}, \mathbf{x}, y')$, $\text{IoU}(\mathbf{x}'_{\text{RED}}, \mathbf{x}', y)$, and $\text{IoU}(\mathbf{x}'_{\text{RED}}, \mathbf{x}', y')$.

(a) Accuracy of $\mathbf{x}'^p_{\mathrm{RED}}$ (b) Success rate of $\mathbf{x}'^p_{\mathrm{RED}}$

(c) $d(f(\mathbf{x}'^p_{\mathrm{RED}}), f(\mathbf{x}))$ (d) $d(\mathbf{x}'^p_{\mathrm{RED}}, \mathbf{x})$

Figure 7: Reverse engineer partially-perturbed data under different interpolation portion p.

RED vs. unforeseen attack types. The experiments on the recovery of unforeseen attack types are composed of two parts: **a)** partially-perturbed data via linear interpolation, and **b)** the unseen attack type, AutoAttack, Feature Attack, and Adaptive Attack.

First, we construct partially-perturbed data by adding a portion $p \in \{0\%, 20\%, \cdots, 100\%\}$ of the perturbation $\mathbf{x}' - \mathbf{x}$ to the true benign example $\mathbf{x}$, namely, $\mathbf{x}'^p = \mathbf{x} + p(\mathbf{x}' - \mathbf{x})$. The interpolated $\mathbf{x}'^p$ is then used as the input to an RED model. We aim to investigate whether or not the proposed RED method can recover partial perturbations (even not successful attacks).

Fig. 7 (a) and (b) show the accuracy and attack success rate, i.e., the prediction alignment with y and y', of the adversarial example estimate $\mathbf{x}'^p_{\mathrm{RED}} = \mathbf{x}'^p - \mathcal{D}_{\boldsymbol{\theta}}(\mathbf{x}'^p) + \mathbf{x}$ by different RED models. Fig. 7 (c) shows the logit distance between the prediction of the partially-perturbed adversarial example estimate and the prediction of the benign example while Fig. 7 (d) demonstrates the pixel distance between $\mathbf{x}'^p_{\mathrm{RED}}$ and the benign example.

First, a smaller gap between the ground-truth curve (in red) and the adversarial example estimate $\mathbf{x}'^p_{\mathrm{red}}$ curve indicates a better performance. As we can see, CDD-RED performs the best with the smallest gap. Specifically, Fig. 7 (a) and (b) show that the recovered perturbation portion by CDD-RED yields the closet adversary's performance to the ground-truth in terms of the prediction accuracy and attack success rate. This is also verified by the distance of prediction logits in Fig. 7 (c). Fig. 7 (d) shows that DS largely over-estimates the additive perturbation, while CDD-RED maintains the perturbation estimation performance closest to the ground-truth.

Moreover, from the leftmost point in the figure, which are benign examples with $p = 0\%$ perturbations, we notice that even if the RED denoiser does not see benign example pair $(\mathbf{x}, \mathbf{x})$ during training, it will not much influence the performance of the benign example recovery. This feature indicates that CDD-RED can handle the case with a mixture of adversarial examples and benign examples. That is to say, even if a benign example, detected as adversarial, is wrongly fed into RED framework, our method is able to recover the original perturbation close to the ground-truth.

Table 2 shows the RED performance on the unseen attack type, AutoAttack, Feature Attack, and Adaptive Attack. For AutoAttack and Feature Attack, CDD-RED outperforms both DO and DS in terms of PA from both benign and adversarial perspectives. Specifically, CDD-RED increases the $\mathrm{PA}_{\mathrm{adv}}$ for Feature Attack by 36.51% and 27.64% compared to DO and DS, respectively.

As for adaptive attack, we assume that the attacker has access to the knowledge of RED model, *i.e.*, $D_{\boldsymbol{\theta}}$. It can then perform PGD attack method to generate successful prediction-evasion attacks even after taking the RED operation. We use PGD methods to generate such attacks within the ℓ_{∞}-ball of

perturbation radius $\epsilon = 20/255$. Table 2 shows that Adaptive Attack is much stronger than Feature Attack and AutoAttack, leading to larger pixel-level reconstruction error and lower PA accuracies. However, CDD-RED still outperforms DO and DS in PA_{benign} and PA_{adv}. And compared to DS, it achieves a more graceful tradeoff with denoising error $d(\mathbf{x}, \mathbf{x}_{RED})$.

In general, CDD-RED can achieve high PA even if the attack type is not seen

Table 2: The $d(\mathbf{x}, \mathbf{x}_{RED})$, PA_{benign}, and PA_{adv} performance of the denoisers on the unforeseen perturbation type AutoAttack, Feature Attack, and Adaptive Attack.

		DO	DS	CDD-RED
$d(\mathbf{x}, \mathbf{x}_{RED})$	AutoAttack	6.41	16.64	8.81
	Feature Attack	5.51	16.14	7.99
	Adaptive Attack	9.76	16.21	12.24
PA_{benign}	AutoAttack	84.69%	92.64%	94.58%
	Feature Attack	82.90%	90.75%	93.25%
	Adaptive Attack	33.20%	27.27%	36.29%
PA_{adv}	AutoAttack	85.53%	83.30%	88.39%
	Feature Attack	26.97%	35.84%	63.48%
	Adaptive Attack	51.21%	55.41%	57.11%

during training, which indicates the generalization-ability of our method to estimate not only new adversarial examples (generated from the same attack method), but also new attack types.

RED to infer correlation between adversaries. In what follows, we investigate whether the RED model guided by the single classifier (VGG19) enables to identify different adversary classes, given by combinations of attack types (FGSM, PGD, CW) and victim model types (Res18, Res50, VGG16, VGG19, IncV3).

Fig. 8 presents the correlation between every two adversary classes in the logit space. Fig. 8 (a) shows the ground-truth correlation map. Fig. 8 (b) shows correlations between logits of $\mathbf{x}'_{RED}$ estimated by our RED method (CDD-RED) and logits of the true $\mathbf{x}'$. Along the diagonal of each correlation matrix, the darker implies the better RED estimation under the same adversary class. By peering into off-diagonal entries, we find

(a) Groundtruth (b) CDD-RED (ours)

Figure 8: Correlation matrices between different adversaries. For each correlation matrix, rows and columns represent adversarial example estimate $\mathbf{x}'_{RED}$ and true adversarial example $\mathbf{x}'$ (For the ground-truth correlation matrix, $\mathbf{x}'_{RED} = \mathbf{x}'$). Each entry represents the average Spearman rank correlation between the logits of two adversary settings $\in \{(\text{victim model, attack type})\}$.

that FGSM attacks are more resilient to the choice of a victim model (see the cluster of high correlation values at the bottom right corner of Fig. 8). Meanwhile, the proposed CDD-RED precisely recovers the correlation behavior of the true adversaries. Such a correlation matrix can help explain the similarities between different attacks' properties. Given an inventory of existing attack types, if a new attack appears, then one can resort to RED to estimate the correlations between the new attack type and the existing attack types. Based on the correlation screening, it can infer the properties of the new attack type based on its most similar counterpart in the existing attack library.

6 CONCLUSION

In this paper, we study the problem of Reverse Engineering of Deceptions (RED), with the goal to recover the attack toolchain signatures (*e.g.* adversarial perturbations and adversary salience image regions) from an adversarial instance. To the best of our knowledge, RED has not been well studied and left many questions to be resolved. Our work makes a solid step towards formalizing the RED problem and developing a systematic RED pipeline, covering not only a solution method but also a complete set of evaluation metrics. We have identified a series of RED principles, ranging from the pixel level to the attribution level, desired to reverse-engineer adversarial attacks. We have also developed an effective denoiser-assisted RED approach by integrating class-discrimination and data augmentation into an image denoising network. With an extensive experimental study, we show that our approach outperforms the existing baseline methods and generalizes well to unseen attack types.

REFERENCES

Vegard Antun, Francesco Renna, Clarice Poon, Ben Adcock, and Anders C Hansen. On instabilities of deep learning in image reconstruction and the potential costs of ai. *Proceedings of the National Academy of Sciences*, 2020.

A. Athalye, L. Engstrom, A. Ilyas, and K. Kwok. Synthesizing robust adversarial examples. In *International Conference on Machine Learning (ICML)*, 2018.

Akhilan Boopathy, Sijia Liu, Gaoyuan Zhang, Cynthia Liu, Pin-Yu Chen, Shiyu Chang, and Luca Daniel. Proper network interpretability helps adversarial robustness in classification. In *International Conference on Machine Learning (ICML)*, 2020.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *IEEE Symposium on Security and Privacy (S&P)*. IEEE, 2017.

Yair Carmon, Aditi Raghunathan, Ludwig Schmidt, John C Duchi, and Percy S Liang. Unlabeled data improves adversarial robustness. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

Pin-Yu Chen, Yash Sharma, Huan Zhang, Jinfeng Yi, and Cho-Jui Hsieh. Ead: elastic-net attacks to deep neural networks via adversarial examples. *arXiv*, 2017a.

Pin-Yu Chen, Huan Zhang, Yash Sharma, Jinfeng Yi, and Cho-Jui Hsieh. Zoo: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models. In *Proceedings of the ACM Workshop on Artificial Intelligence and Security*. ACM, 2017b.

Shang-Tse Chen, Cory Cornelius, Jason Martin, and Duen Horng Polo Chau. Shapeshifter: Robust physical adversarial attack on faster r-cnn object detector. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases (ECML)*. Springer, 2018.

T. Chen, S. Liu, S. Chang, Y. Cheng, L. Amini, and Z. Wang. Adversarial robustness: From self-supervised pretraining to fine-tuning. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

Minhao Cheng, Simranjit Singh, Patrick Chen, Pin-Yu Chen, Sijia Liu, and Cho-Jui Hsieh. Sign-opt: A query-efficient hard-label adversarial attack. *arXiv*, 2019.

Minhao Cheng, Jinfeng Yi, Pin-Yu Chen, Huan Zhang, and Cho-Jui Hsieh. Seq2sick: Evaluating the robustness of sequence-to-sequence models with adversarial examples. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, 2020.

Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *International Conference on Machine Learning (ICML)*. PMLR, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Computer Vision and Pattern Recognition*, 2009.

Yinpeng Dong, Tianyu Pang, Hang Su, and Jun Zhu. Evading Defenses to Transferable Adversarial Examples by Translation-Invariant Attacks. In *CVPR*, 2019.

K. Eykholt, I. Evtimov, E. Fernandes, B. Li, A. Rahmati, C. Xiao, A. Prakash, T. Kohno, and D. Song. Robust physical-world attacks on deep learning visual classification. In *Proceedings of the Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

Samuel G Finlayson, John D Bowers, Joichi Ito, Jonathan L Zittrain, Andrew L Beam, and Isaac S Kohane. Adversarial attacks on medical machine learning. *Science*, 363(6433):1287–1289, 2019.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Kathrin Grosse, Praveen Manoharan, Nicolas Papernot, Michael Backes, and Patrick McDaniel. On the (statistical) detection of adversarial examples. *arXiv preprint arXiv:1702.06280*, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *CoRR*, 2015.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015.

Juncheng Li, Frank Schmidt, and Zico Kolter. Adversarial camera stickers: A physical camera-based attack on deep learning systems. In *International Conference on Machine Learning (ICML)*, 2019.

Qizhang Li, Yiwen Guo, and Hao Chen. Practical no-box adversarial attacks against dnns. *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

Fangzhou Liao, Ming Liang, Yinpeng Dong, Tianyu Pang, Xiaolin Hu, and Jun Zhu. Defense against Adversarial Attacks Using High-Level Representation Guided Denoiser. *arXiv:1712.02976 [cs]*, May 2018.

Sijia Liu, Pin-Yu Chen, Xiangy Chen, and Mingyi Hong. signSGD via zeroth-order oracle. In *International Conference on Learning Representations (ICLR)*, 2019.

Yanpei Liu, Xinyun Chen, Chang Liu, and Dawn Song. Delving into Transferable Adversarial Examples and Black-box Attacks. *arXiv:1611.02770 [cs]*, February 2017.

Yan Luo, Xavier Boix, Gemma Roig, Tomaso Poggio, and Qi Zhao. Foveation-based mechanisms alleviate adversarial examples. *arXiv preprint arXiv:1511.06292*, 2015.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Dongyu Meng and Hao Chen. Magnet: a two-pronged defense against adversarial examples. In *the Conference on Computer and Communications Security (CCS)*. ACM, 2017.

Jan Hendrik Metzen, Tim Genewein, Volker Fischer, and Bastian Bischoff. On detecting adversarial perturbations. *arXiv preprint arXiv:1702.04267*, 2017.

Zhonghan Niu, Zhaoxi Chen, Linyi Li, Yubin Yang, Bo Li, and Jinfeng Yi. On the Limitations of Denoising Strategies as Adversarial Defenses. *arXiv:2012.09384 [cs]*, 2020.

Ren Pang, Xinyang Zhang, Shouling Ji, Xiapu Luo, and Ting Wang. Advmind: Inferring adversary intent of black-box attacks. In *the International Conference on Knowledge Discovery & Data Mining (KDD)*, 2020.

Nicolas Papernot, Patrick McDaniel, and Ian Goodfellow. Transferability in Machine Learning: from Phenomena to Black-Box Attacks using Adversarial Samples. *arXiv:1605.07277 [cs]*, 2016a.

Nicolas Papernot, Patrick McDaniel, Somesh Jha, Matt Fredrikson, Z Berkay Celik, and Ananthram Swami. The limitations of deep learning in adversarial settings. In *IEEE European Symposium on Security and Privacy (EuroS&P)*. IEEE, 2016b.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z. Berkay Celik, and Ananthram Swami. Practical Black-Box Attacks against Machine Learning. *arXiv:1602.02697 [cs]*, 2017.

Sara Sabour, Yanshuai Cao, Fartash Faghri, and David J Fleet. Adversarial manipulation of deep representations. *arXiv preprint arXiv:1511.05122*, 2015.

Hadi Salman, Mingjie Sun, Greg Yang, Ashish Kapoor, and J Zico Kolter. Denoised smoothing: A provable defense for pretrained classifiers. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

Ramprasaath R. Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-CAM: Visual Explanations from Deep Networks via Gradient-based Localization. *International Journal of Computer Vision*, 2020.

Alex Serban, Erik Poll, and Joost Visser. Adversarial examples on object recognition: A comprehensive survey. *ACM Computing Surveys (CSUR)*, 53(3):1–38, 2020.

Ali Shafahi, Mahyar Najibi, Mohammad Amin Ghiasi, Zheng Xu, John Dickerson, Christoph Studer, Larry S Davis, Gavin Taylor, and Tom Goldstein. Adversarial training for free! In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

Ali Shafahi, W. Ronny Huang, Christoph Studer, Soheil Feizi, and Tom Goldstein. Are adversarial examples inevitable? *arXiv:1809.02104 [cs, stat]*, February 2020.

Karen Simonyan and Andrew Zisserman. Very Deep Convolutional Networks for Large-Scale Image Recognition. In *International Conference on Learning Representations (ICLR)*, 2015.

Shashank Srikant, Sijia Liu, Tamara Mitrovska, Shiyu Chang, Quanfu Fan, Gaoyuan Zhang, and Una-May O'Reilly. Generating adversarial computer programs using optimized obfuscations. In *International Conference on Learning Representations (ICLR)*, 2021.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jonathon Shlens, and Zbigniew Wojna. Re-thinking the inception architecture for computer vision. *CoRR*, 2015.

Florian Tramer, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On adaptive attacks to adversarial example defenses. *arXiv preprint arXiv:2002.08347*, 2020.

Jonathan Uesato, Jean-Baptiste Alayrac, Po-Sen Huang, Robert Stanforth, Alhussein Fawzi, and Pushmeet Kohli. Are labels required for improving adversarial robustness? *Neural Information Processing Systems (NeurIPS)*, 2019.

Bartosz Wójcik, Paweł Morawiecki, Marek Śmieja, Tomasz Krzyżek, Przemysław Spurek, and Jacek Tabor. Adversarial examples detection and analysis with layer-wise autoencoders. *arXiv preprint arXiv:2006.10013*, 2020.

Eric Wong and J Zico Kolter. Provable defenses against adversarial examples via the convex outer adversarial polytope. *arXiv preprint arXiv:1711.00851*, 2017.

Eric Wong, Leslie Rice, and J. Zico Kolter. Fast is better than free: Revisiting adversarial training. In *International Conference on Learning Representations (ICLR)*, 2020.

Chaowei Xiao, Jun-Yan Zhu, Bo Li, Warren He, Mingyan Liu, and Dawn Song. Spatially transformed adversarial examples. In *International Conference on Learning Representations (ICLR)*, 2018.

Cihang Xie, Jianyu Wang, Zhishuai Zhang, Yuyin Zhou, Lingxi Xie, and Alan Yuille. Adversarial examples for semantic segmentation and object detection. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, 2017.

Cihang Xie, Zhishuai Zhang, Yuyin Zhou, Song Bai, Jianyu Wang, Zhou Ren, and Alan L Yuille. Improving transferability of adversarial examples with input diversity. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

Kaidi Xu, Sijia Liu, Gaoyuan Zhang, Mengshu Sun, Pu Zhao, Quanfu Fan, Chuang Gan, and Xue Lin. Interpreting adversarial examples by activation promotion and suppression. *arXiv preprint arXiv:1904.02057*, 2019a.

Kaidi Xu, Sijia Liu, Pu Zhao, Pin-Yu Chen, Huan Zhang, Quanfu Fan, Deniz Erdogmus, Yanzhi Wang, and Xue Lin. Structured adversarial attack: Towards general implementation and better interpretability. In *International Conference on Learning Representations (ICLR)*, 2019b.

Kaidi Xu, Gaoyuan Zhang, Sijia Liu, Quanfu Fan, Mengshu Sun, Hongge Chen, Pin-Yu Chen, Yanzhi Wang, and Xue Lin. Evading real-time person detectors by adversarial t-shirt. *arXiv preprint arXiv:1910.11099*, 2019c.

Puyudi Yang, Jianbo Chen, Cho-Jui Hsieh, Jane-Ling Wang, and Michael Jordan. Ml-loo: Detecting adversarial examples with feature attribution. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, 2020.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 6023–6032, 2019.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P Xing, Laurent El Ghaoui, and Michael I Jordan. Theoretically principled trade-off between robustness and accuracy. *International Conference on Machine Learning (ICML)*, 2019.

Kai Zhang, Wangmeng Zuo, Yunjin Chen, Deyu Meng, and Lei Zhang. Beyond a Gaussian Denoiser: Residual Learning of Deep CNN for Image Denoising. *IEEE Transactions on Image Processing*, 2017.