Conditional Local Importance by Quantile Expectations

Abstract

Global variable importance measures are commonly used to interpret the results of machine learning models. Local variable importance techniques assess how variables contribute to individual observations. Current, popular methods, including LIME and SHAP, typically fail to accurately reflect locally dependent relationships between variables and instead focus on marginal importance values. Additionally, they are not natively adapted for multi-class classification problems. We propose a new model-agnostic method for calculating local variable importance, CLIQUE, that captures locally dependent relationships, provides improvements over permutation-based methods, and can be directly applied to multi-class classification problems. Simulated and real-world examples show that CLIQUE emphasizes locally dependent information, captures interaction behavior beyond what can be evaluated by correlations, and properly reduces bias in regions where variables do not affect the response.

1 Introduction

Variable importance measures are essential for interpreting machine learning models, as they evaluate the contribution of each feature to the model's performance or predictions. In particular, global variable importance methods quantify a feature's overall influence across the entire dataset and have been extensively researched. Breiman (2001) introduced a global permutation technique (Permute-and-Predict or PaP) for an internal validation set within Random Forests, which was later generalized to model-agnostic approaches (Model-Reliance) (Fisher et al., 2019). Other global variable importance methods include Leave-One-Covariate-Out (LOCO) (Lei et al., 2018; Hooker et al., 2021; Bladen & Cutler, 2024), the Knockoff Filter (Barber & Candès, 2015; Candes et al., 2018), and using the spread of predictions in Partial Dependence Plots (PDPs) (Greenwell, 2017; Greenwell et al., 2018).

Local variable importance seeks to measure the relative contribution of each feature to the performance or prediction of individual observations. Existing methods include Individual Conditional Expectations (ICE) (Goldstein et al., 2015), Individual Conditional Importance (ICI) (Casalicchio et al., 2019), Local Interpretable Model-agnostic Explanations (LIME) (Ribeiro et al., 2016), Shapley Additive Explanations (SHAP) (Shapley et al., 1953; Lundberg, 2017), Counterfactual Explanations (Wachter et al., 2017; Dandl et al., 2020), and Anchors (Ribeiro et al., 2018). Global importance extensions often can be obtained by aggregating these local measures across all samples. SHAP and LIME are particularly popular because of their theoretical foundations, applications to a variety of data types, and their intuitive results (Molnar, 2020). SHAP values are calculated by considering coalitions of feature values. This involves changing the value of a given variable for a given observation, while allowing other variables to change, and observing the resulting impact on the prediction. The average change in prediction across all coalitions yields the SHAP value. Because this allows other variables to change, SHAP values can capture aspects of interactive effects as well as marginal effects. However, our experiments show that individual SHAP values do not always capture local interactions properly.

LIME is another local method which uses interpretable models such as linear regression or classification trees to explain individual predictions of black-box models (Ribeiro et al., 2016). LIME creates a new dataset of perturbed features (noise added), where the black-box predictions become the response (Molnar, 2020). An interpretable model is built on the new dataset, weighted by proximity to a given observation of interest.

The local importances for that observation are then computed from the global variable importances for the interpretable model. The resulting output requires many simple models: one for each observation. The variables in the models have weights and can be used to create a matrix of weights or importances. We show in our experiments that LIME tends to focus almost entirely on marginal variable effects and struggles to detect variable interactions.

ICI extends permutation-based global variable importance (PaP and Model-Reliance) to the local level by measuring how prediction error changes for an individual observation when a single feature is permuted (Casalicchio et al., 2019). ICI values are generally plotted on a curve that shows how the local importance varies across permutations, and its aggregate—Partial Importance (PI)—summarizes how feature relevance may change across the feature domain. ICI was designed to overcome the limitations of global permutation importance by revealing heterogeneous or conditional effects that may indicate interactions (Casalicchio et al., 2019). However, ICI requires the analyst to specify conditional groupings or interaction structures to meaningfully interpret different importance curves (Molnar et al., 2020). In practice, ICI can also exhibit high variance, requiring repeated permutations for every feature and observation, thus becoming computationally expensive for moderate to large datasets. Our experiments further show that ICI struggles to reliably detect conditional importance when interacting features are not manually pre-identified, limiting its utility for automated discovery of interaction effects in complex models.

Compared to other local importance techniques, SHAP, LIME, and ICI stand out because they provide an importance value for every observation in a dataset. For this reason, we focus primarily on comparing our results with these methods. Despite their popularity and flexibility, these approaches share important limitations. In our experiments, SHAP, LIME, and uninformed ICI routinely assign false-positive importance in regions of the feature space where a variable has no effect on the response, leading to inaccurate local interpretations. Additionally, extending prediction-based decomposition methods such as SHAP and LIME to multi-category classification settings introduces further complexity, since importance must be defined separately for each response class. Meanwhile, ICI, though designed to uncover heterogeneous effects, requires interaction structures or conditioning sets to be specified by the user and can exhibit high variance due to repeated permutations. Collectively, these challenges highlight the need for a local importance technique that can reliably detect conditional effects without manual specification, avoid spurious attributions, and remain stable across diverse modeling settings.

To address these limitations, we propose Conditional Local Importance by QUantile Expectations (CLIQUE), a new framework for assessing local variable importance. CLIQUE is specifically designed to assign zero importance to locally invariant features and detect interaction-driven effects without requiring user input. By grounding local importance in quantile expectation comparisons, CLIQUE offers a principled alternative to existing local and global approaches, with particular advantages in stability and interpretability across regression, binary, and multi-class classification settings. The remainder of this paper defines CLIQUE, establishes its key properties, and demonstrates its empirical performance across a range of simulated and real-world scenarios.

2 Local Variable Importances with CLIQUE

2.1 CLIQUE Definition

Consider a dataset $(\mathbf{x}_1, y_1), \ldots, (\mathbf{x}_n, y_n) = (X, Y)$, where $X \in \mathbb{R}^{n \times p}$ is the data matrix and $Y \in \mathbb{R}^n$ contains the labels. Unlike classical permutation measures such as PaP and Model-Reliance, which evaluate global importance, CLIQUE focuses on local effects, yielding observation-level importance measures. CLIQUE shares algorithmic similarities with ICI but addresses several limitations of existing local importance methods. Like ICI, CLIQUE is model-agnostic and evaluates observation-specific changes in error. However, it differs fundamentally in that it defines local importance in terms of cross-validated errors rather than changes in predictions from a single fitted model. CLIQUE also replaces random permutations with robust quantile-grid replacements (motivated by ICE curves of Goldstein et al. (2015)), improving stability and substantially reducing the number of perturbations required for reliable importance estimates (see Section 3.1.1).

This distinction clarifies the conceptual difference between the two methods. ICI seems to assess the influence of observation i on variable j by permuting all variables except j. In contrast, CLIQUE assesses the importance of variable j to observation i by altering only that variable while holding the remaining features fixed. In this sense, the local importance of feature j to a given data point $\mathbf{x}_i$ is measured by the change in model error induced by perturbing the variable value.

Mathematically, consider the data point $\mathbf{x}_i$ with its corresponding CV model. We aim to compute the local importance for variable j, which we denote as V_{ij}. Let $\hat{f}(\mathbf{x}_i)$ represent the original prediction of y_i given $\mathbf{x}_i$, obtained from the CV model trained on a fold that excludes $\mathbf{x}_i$. Let $\tilde{\mathbf{x}}_i(j, m)$ denote the altered version of $\mathbf{x}_i$, where the jth variable is replaced by the mth value from its quantile grid, constructed between the minimum and maximum of the jth variable in the training data. The CLIQUE value is

$$V_{ij} = \frac{1}{M} \sum_{m=1}^{M} \mathcal{L}\left(\hat{f}\left(\tilde{\mathbf{x}}_i(j, m)\right), y_i\right) - \mathcal{L}\left(\hat{f}(\mathbf{x}_i), y_i\right), \tag{1}$$

where M is the number of altered values in the quantile grid and $\mathcal{L}$ is the loss function of interest (e.g. squared error in regression). Quantile-based interventions provide a deterministic and distribution-driven approach for probing local sensitivity, while avoiding the instability introduced by random sampling or binning. Also, because CLIQUE defines local importance in terms of performance rather than prediction changes, it extends naturally to multi-class classification settings, where prediction-based local importance measures can be difficult to interpret. A complete workflow for CLIQUE is shown in Algorithm 1. Note that $V_{:j}$ refers to the jth column in V.

Algorithm 1 CLIQUE

1: **Input:** data $\underset{n \times p}{X}$, labels $\underset{n \times 1}{Y}$, model, quantiles M
2: $mod \leftarrow \text{model}(X, Y)$
3: $cvmod \leftarrow$ individual CV models
4: $\underset{n \times 1}{Err} \leftarrow \mathcal{L}(\text{predict}(cvmod, X), Y)$
5: $\underset{n \times p}{V} \leftarrow \underset{n \times p}{0}$
6: **for** $j = 1$ **to** p **do**
7:    $\underset{M \times 1}{grid} \leftarrow M$ quantile values for variable j
8:    **for** $m = 1$ **to** M **do**
9:       $\underset{n \times p}{W} \leftarrow \underset{n \times p}{X}$
10:      $\underset{n \times 1}{W_{:j}} \leftarrow grid[m]$
11:      $\underset{n \times 1}{\widetilde{Err}_j} \leftarrow \mathcal{L}(\text{predict}(cvmod, W), Y)$
12:      $\underset{n \times 1}{V_{:j}} \leftarrow V_{:j} + \frac{\widetilde{Err}_j - Err}{M}$
13:    **end for**
14: **end for**

We note that CLIQUE captures conditional information in the sense that an effect is conditional if it depends on, or changes with, another effect. Thus, we are not referring to conditional information in a formal probabilistic sense. We also note that for our work, "local" suggests at least some location-dependence on the importance of a variable. If such location-dependence is absent, local importance should largely agree with global importance measures, which can be assessed using existing global methods.

2.2 CLIQUE Properties

Our CLIQUE algorithm is designed to satisfy several properties when assessing local importance:

    P1 If the model output for a given observation is invariant to changes in a variable, then CLIQUE assigns that variable zero population importance and negligible empirical importance for that observation.

P2 CLIQUE importance values exhibit stability with relatively low variances.

P3 CLIQUE is model-agnostic.

P4 CLIQUE applies directly to multi-class problems without extensive modification.

P5 CLIQUE values offer meaningful and intuitive aggregation across observations to assess subgroup/global behavior.

P6 CLIQUE is computationally competitive with other local importance methods.

P7 CLIQUE defines importance in terms of model error rather than predictions.

P8 CLIQUE evaluates importance on non-training data.

These properties collectively outline the criteria that guide our formulation of a new local importance measure. **P1** expresses an intuitive notion of importance. While not strictly required for all local importance methods, this property carries strong conceptual merit, since assigning nonzero importance to variables with no influence risks undermining interpretability (Fisher et al., 2019; Hooker et al., 2021). This is especially true when only a small subset of variables is truly important for a given datapoint. In such cases, unimportant variables may be incorrectly flagged as important. In our empirical results, we show that CLIQUE achieves **P1** while other local importance methods fail partially or entirely. Furthermore, the following proposition and accompanying proof formally shows that CLIQUE assigns zero importance to locally invariant features and thus satisfies **P1**.

Proposition 1 (Feature invariance)**.** *Let $\hat{f}$ be a fixed prediction function and $\mathcal{L}$ be any loss function. If, for a given observation $\mathbf{x}_i$, the prediction $\hat{f}(\mathbf{x}_i)$ does not depend on feature j, then the corresponding CLIQUE importance $V_{ij} = 0$.*

Proof. By assumption, for all quantile-based replacements $\tilde{\mathbf{x}}_i(j, m)$ that modify only feature j for x_i,

$$\hat{f}(\tilde{\mathbf{x}}_i(j, m)) = \hat{f}(\mathbf{x}_i). \tag{2}$$

Substituting this into the definition of CLIQUE (Equation 1) yields

$$
\begin{aligned}
V_{ij} &= \frac{1}{M} \sum_{m=1}^{M} \mathcal{L}\left(\hat{f}\left(\tilde{\mathbf{x}}_i(j, m)\right), y_i\right) - \mathcal{L}\left(\hat{f}(\mathbf{x}_i), y_i\right) \\
&= \frac{1}{M} \sum_{m=1}^{M} \mathcal{L}\left(\hat{f}(\mathbf{x}_i), y_i\right) - \mathcal{L}\left(\hat{f}(\mathbf{x}_i), y_i\right) \\
&= \mathcal{L}(\hat{f}(\mathbf{x}_i), y_i) - \mathcal{L}(\hat{f}(\mathbf{x}_i), y_i) = 0.
\end{aligned}
\tag{3}
$$

$\square$

This proposition mathematically illustrates how CLIQUE's formulation ensures satisfaction of **P1**. Although the result holds exactly at the population level, an approximate analogue also holds in finite-sample or noisy settings provided the loss function is continuous, as is the case for most commonly used losses. In subsequent simulations, we show that this behavior is observed empirically for CLIQUE, but is not guaranteed by other local importance methods.

P2 is inherently desirable, provided that it does not come at the cost of extra bias or excessive computation. It is motivated by the idea that the best importance results are achieved by replacing a specific value with all other possible variable distribution values. Unfortunately, this practice is quite computationally expensive (Molnar, 2020). Our use of quantile-replacements in CLIQUE, rather than permuting or dropping variables, offers an efficient proxy for comparing individual points to the entire variable distribution. To show that CLIQUE's quantile grid can outperform repeated permutations, we include a simulation in Section 3.1.1 that

offers a comparison between CLIQUE and a variation of CLIQUE that we refer to as Local Permute. Local Permute and CLIQUE are nearly identical, except that Local Permute performs M variable permutations, while CLIQUE replaces a variable with M quantile values.

P3 is desirable so that CLIQUE can be applied to a wide range of predictive models without relying on internal structure. This makes it broadly usable, robust to and comparable across models, and easier to integrate into diverse scientific workflows. Therefore, **P3** increases both the practical value and the scientific reliability of the method. To briefly illustrate the model-agnostic extensions of CLIQUE, we provide results in Section 3 for both Random Forest and Artificial Neural Network models.

P4 is advantageous because it allows CLIQUE to extend naturally to multi-class settings, avoiding the need for specialized derivations or one-vs-all decompositions as is common for methods such as LIME and SHAP. This makes CLIQUE broadly applicable and computationally efficient, while providing a unified treatment of variable importance across all predicted classes. To demonstrate the application of CLIQUE to multi-class settings, we provide analyses based on the MNIST classification task in Section 4.3 and Appendix A.

P5 is a valuable property for local importance methods because it connects observation-level explanations to coherent subgroup or global summaries. The creators of SHAP emphasize that consistent local attributions should naturally aggregate to form reliable global importance measures (Lundberg, 2017). Similarly, CLIQUE offers very natural aggregation across subgroups through classical summary metrics such as means, medians, and measures of dispersion. In this way, CLIQUE satisfies **P5**, allowing it to provide both fine-grained local diagnostics and broader group assessments. We illustrate several applications for this in Section 4.

P6 is inherently desirable, provided this efficiency does not come at the cost of additional bias or variance. To illustrate that CLIQUE satisfies **P6**, we include a simulation in Appendix A.3 that offers a time comparison between CLIQUE, ICI, SHAP, and LIME.

P7 is not inherently superior or inferior to importances that are interpreted on predictions. Rather, it highlights the type of information CLIQUE is designed to capture, distinguishing it from prediction-based approaches like LIME and SHAP. Error-based importance is not universally required, but it can be particularly valuable for diagnosing model weaknesses and identifying features that most contribute to local misfit (Rudin, 2019). This perspective offers practitioners an alternative way to examine model behavior, complementing existing prediction-focused interpretability tools.

Finally, **P8** aligns with best practices in interpretable machine learning and model evaluation, ensuring that importance is assessed on data outside of the fitting process (Molnar, 2020). This reduces overfitting concerns and helps importance reflect generalizable behavior rather than artifacts of the training set. To capitalize on the benefits associated with **P8**, CLIQUE computes local importance using CV errors by training multiple CV models with the same hyperparameters determined for the full model. Each variable is systematically modified for every data point and predictions are generated from a CV model that excluded that point from training. Comparing the CV error rate of the modified data to the original CV error rate yields the local importance measure.

3 Simulated Experiments

To demonstrate how CLIQUE outperforms the popular methods LIME, SHAP and ICI in capturing locally dependent relationships, we compare the methods on simulated data with known structures. For all analyses, we use $M = 25$ quantiles for CLIQUE and 25 permutations for ICI. This value was initially chosen based on considerations related to the Central Limit Theorem, which stabilizes estimates and reduces variance. Further exploratory analysis of the impact of M on CLIQUE values and their variance is provided in Section 3.1.1. For each of the following three simulations, all features are independent and identically distributed (iid) from a uniform distribution $\mathcal{U}(-1, 1)$, and we generate 400 training observations.

In our implementation of Algorithm 1, we use absolute error as the loss function. The prediction function returns class probabilities rather than raw labels for all models and datasets in Sections 3 and 4, except for the neural network example in Section 3.2. When raw labels are used, absolute error reduces to a 0–1 loss.

Figure 1: Scatterplot results for the AND gate data. Left-half: Interaction predictors v_1 and v_2 colored by the label y as computed in Equation 4. When $v_2 < -1/3$, the value of v_1 should have no impact on the output of the trained model and should thus have no importance. Right-half: v_1 Local variable importances colored by whether $v_2 > -1/3$. CLIQUE values output the known conditional relationships of an importance of zero when $v_2 < -1/3$ and a nonzero importance otherwise. LIME, SHAP, and ICI each demonstrate false-positive assessments of v_1 when $v_2 < -1/3$. Additionally, LIME and ICI fail to distinguish between the two v_2 regions entirely.

When probabilities are used, the response is one-hot encoded, and absolute error is computed for each class probability and averaged across classes.

3.1 AND Gate Data

We begin with a simple simulation based on an AND gate (Figure 1). To create this data, we generate three features and produce the response using:

$$y = \begin{cases} 1, & \text{if } v_1 > -\frac{1}{3} \ \& \ v_2 > -\frac{1}{3} \\ 0, & \text{otherwise.} \end{cases} \tag{4}$$

Note that v_3 has no influence on the output.

We build a Random Forest model using the randomForest package (Liaw & Wiener, 2002) in the R programming language (R Core Team, 2022). From this model, we extract ICI values using the `featureImportance` package (Casalicchio, 2025), LIME values using the `lime` package (Hvitfeldt et al., 2022), and SHAP values using the `treeshap` package (Komisarczyk et al., 2024).

Based on the geometry of the data in Figure 1, when $v_2 < -1/3$ the model output is effectively insensitive to changes in v_1. Thus, the local importance of v_1 should be near zero in this region. In contrast, when $v_2 > -1/3$, variation in v_1 has a substantial effect on the model output, and its importance should therefore be strongly positive. From Figure 1, we see this in the CLIQUE values. When $v_2 < -1/3$, the importance of v_1 is practically zero, while for $v_2 > -1/3$, v_1 has a positive importance. In contrast, LIME and ICI show no discernible differences in the importance of v_1 relative to v_2, indicating that they fail to capture the conditional information in the data. SHAP falls between LIME and CLIQUE. It displays two distinct trends for v_1, but still assigns nonzero importance when $v_2 < -1/3$. In other words, CLIQUE satisfies property **P1** while LIME, ICI, and SHAP do not.

Figure 2: Plot showing data scatterplot regions and the relationship between importance value distributions and the hyper-parameter M. All plots are colored by regions of interest with respect to $V1$ and its importance values. "A" and "B" are regions where $V1$ should be important, but with different levels due to distribution. "C" denotes points where $V1$ should not be important. Left: Scatter-plot showing $V1$, $V2$, and their associated regions. Center: Plot showing the distribution of Local Permute values across the hyper-parameter M, colored by region. Right: Plot showing the distribution of CLIQUE values across the hyper-parameter M, colored by region. CLIQUE values achieve a distinctly smaller variance for each value of M.

3.1.1 Effect of M on Permutation vs. Quantile Replacement

To assess the advantages of quantile-based importance, we compare Local Permute (CLIQUE with permutation instead of quantile replacement) to CLIQUE. We also examine the effect of M (the number of replacements) on these values for the AND gate data from Section 3.1.

Figure 2 illustrates that CLIQUE achieves substantial gains with respect to **P2**, as Local Permute values exhibit much higher variance than CLIQUE values in both regions where v_1 is expected to have non-zero local importance. The results in Figure 2 also provide guidance on selecting an appropriate M. As noted in Section 3, we chose $M = 25$ with the intent to stabilize estimates and reduce variance. Figure 2 reveals that CLIQUE variances remain remarkably consistent across all M, while the value centers show some initial bias and volatility before correctly stabilizing around M of 15 or 20. Beyond this point, higher M values provide diminishing returns at an increased computational cost.

Considering these findings alongside expected stability properties of the Central Limit Theorem, we suggest that M values between 20 and 50 are generally conservative enough to yield desirable estimates. However, larger M values may be warranted for datasets with highly complex interactions or decision boundaries.

3.2 Corners Data

The AND Gate is a symmetric problem, where the results for v_1 mirror the results for v_2. We now simulate values for a non-symmetric dataset that we call the Corners data (Figure 3). We generate three features with response:

$$y = \begin{cases} 1, & \text{if } v_1 > 0 \ \& \ |v_2| > \frac{1}{4} \\ 0, & \text{otherwise.} \end{cases} \tag{5}$$

In this data, we expect that v_2 is not important when $v_1 < 0$ and v_1 is not important when $|v_2| < 1/4$. To demonstrate **P3**, the model-agnostic capability of CLIQUE, we develop a basic Artificial Neural Network (ANN) structure in Python for modeling the Corners data and extract LIME, SHAP, ICI, and CLIQUE values, which are shown in Figure 4.

Figure 3: Scatterplot of the Corners data colored by the label y (see Equation 5). v_2 is not important when $v_1 < 0$. v_1 is not important when $|v_2| < 1/4$.

Figure 4: Scatterplots of local variable importances vs. variable values from the Corners data experiment. Left-half: v_1 importances colored by whether $|v_2| > 1/4$. Right-half: v_2 importances colored by whether $v_1 > 0$. As in Figure 1, the CLIQUE values capture the known conditional relationships between v_1 and v_2, while LIME, ICI, and SHAP largely fail.

Figure 5: Scatterplots of the response variable (left-half) and local variable importances (right-half) vs. v_1 for the Regression Interaction data. Each plot is colored by whether $v_3 > 0$ (see Equation 6). v_1 is not important when $v_3 < 0$. v_2 is not important when $v_3 > 0$. CLIQUE captures the known conditional relationships between $v1$ and $v3$, while LIME, SHAP, and ICI largely or partially fail.

The behaviors of each of the importance methods match the trends found in Figure 1. The LIME values again show only marginal impact information, while the ICI values show only marginal importance. SHAP values offer two distinct conditional trends, but assign nonzero impact when $|v_2| < 1/4$ and $v_1 < 0$. CLIQUE provides conditional importance values, with effectively zero importance when $|v_2| < 1/4$ and $v_1 < 0$. Additionally, it gives a distinctly positive importance for v_1 when $|v_2| > 1/4$ and for v_2 when $v_1 > 0$. That is, CLIQUE satisfies **P1** while the others do not.

3.3 Regression Interaction Data

We now turn to a location-dependent regression simulation (Figure 5) with four features that produce the response:

$$y = \begin{cases} v_1 + \epsilon, & \text{if } v_3 > 0 \\ v_2 + \epsilon, & \text{if } v_3 < 0. \end{cases} \quad (6)$$

where $\epsilon \sim \mathcal{N}(\text{mean} = 0, \text{sd} = 0.01)$.

In this data, v_1 should not be important when $v_3 < 0$ and v_2 should not be important when $v_3 > 0$. We build a Random Forest model and again extract LIME, SHAP, ICI and CLIQUE values, with the results shown in Figure 5. The trends are similar to previous findings: CLIQUE satisfies property **P1** while LIME, SHAP, and ICI fail to. As in Section 3.1, SHAP values show differences between the two regions, but most values remain nonzero for the region where no v_1 importance is expected.

3.4 Quantifying Results

While Figures 1, 4, and 5 illustrate qualitative differences in local importance behavior under known data-generating mechanisms, we additionally quantify the extent to which these methods assign spurious importance to features with no true effect. To this end, we compute the false-positive mean absolute error (FP-MAE), defined as the mean absolute difference between estimated local importance values and their true zero values, after standardization ($\frac{v}{|\max(v)|}$) to ensure comparability across methods and subset to only observations with zero feature effect.

Table 1 summarizes FP-MAE across all simulation settings. In every scenario, CLIQUE exhibits substantially smaller false-positive errors than competing methods, often by an order of magnitude. In contrast,

	LIME	SHAP	ICI	CLIQUE
AND Gate	0.405	0.216	0.466	0.005
Corners-v1	0.735	0.278	0.566	0.043
Corners-v2	0.277	0.188	0.368	0.011
Regression	0.342	0.196	0.306	0.030

Table 1: Comparison of false-positive mean absolute errors (FP-MAE). Errors are computed, following standardization, between true zero importance values and estimated local importance values for each method.

LIME, SHAP, and ICI consistently assign non-negligible importance to null features, indicating a tendency toward false-positive attribution even in controlled settings. These results empirically reinforce property **P1**, demonstrating that CLIQUE not only satisfies feature invariance in theory, but also suppresses spurious local importance in practice—an important consideration for maintaining interpretability and trust in local explanation methods.

4 Real Data Experiments

Here we apply CLIQUE to real data, including the concrete regression dataset (Yeh, 1998), the lichen dataset (Cutler et al., 2007) and the MNIST dataset (Alpaydin & Kaynak, 1998).

4.1 Concrete Regression

To illustrate an application of our method in a regression setting, we use the Concrete Compressive Strength data (Yeh, 1998). This dataset is available on the UCI data repository and consists of 1030 observations. There are eight quantitative ingredients or features and a response listed with their respective units as: Cement (kg/m^3), Blast Furnace Slag (kg/m^3), Fly Ash (kg/m^3), Water (kg/m^3), Superplasticizer (kg/m^3), Coarse Aggregate (kg/m^3), Fine Aggregate (kg/m^3), Age (days), and Concrete Compression Strength (MPa).

Figure 6: Left: Permutation-based global importances from a random forest model for all features in the Concrete data. Center-Right: PDPs for Age and Cement, the top two features.

With this data, we build a random forest model to predict Concrete Strength and extract LIME, SHAP, ICI, and CLIQUE values from it. Results for permutation-based global variable importances and PDPs are shown in Figure 6. These results show that Age and Cement appear to be the most important ingredients for determining Concrete Strength. We especially notice that the Cement PDP shows a consistent trend upward, whereas the Age PDP shows Strength predictions initially rising rapidly, but then stabilizing at an Age between 50 and 100 days. These results raise the question: Does Cement importance change for different Ages?

To answer this question, we divide our local importances into two groups based on whether the Age exceeded 75 days or not. The CLIQUE boxplots in Figure 7 show that Cement has a greater importance when Age is

Figure 7: Distributions for Cement importances for different Age thresholds. Importances are scaled by their maximum absolute value within each method. Classically defined outliers are included in whiskers. The CLIQUE values show a greater contrast between the two regions compared to LIME, SHAP, and ICI.

lower (**P5**). In other words, concrete strength accuracy is more influenced by cement amount in lower ages. Little difference is observed in the LIME or ICI values, while the SHAP values in Figure 7 do show a slightly larger spread when Age is less than 75. This effect is distinctly diminished compared to the difference seen in the CLIQUE distributions. Aggregate SHAP values, calculated by averaging the SHAP magnitudes, yield a ratio of 1.36, whereas the mean of the CLIQUE values produces a ratio of 1.68 times higher for lower ages compared to higher ages.

Figure 8: CLIQUE, SHAP, ICI, and LIME values of all predictor variables for three instances in the Concrete data. Importances are scaled by their maximum absolute value within each method. Based on the CLIQUE values, each of the selected observations has a distinctly unique set of important variables, which deviates substantially from the global trends.

This dataset provides an excellent opportunity to examine observation-level importance metrics. In Figure 8, we show LIME, SHAP, ICI, and CLIQUE values for three observations: the first, fourth, and eighth instances of the concrete dataset. For Observation 1, Cement definitively has the largest importance. A brief empirical check shows that the Cement importance for Observation 1 is the largest CLIQUE value across the entire dataset. The LIME and SHAP values for Cement are also large, which, when considered alongside

Figure 9: Global importances (left) and PDPs (right) for top features in the Lichen data.

the Cement PDP in Figure 6, suggests that the Cement value for this observation is high. In contrast, the other visualized observations do not have Cement as a top contributing variable according to CLIQUE. For Observation 4, CLIQUE indicates that Superplasticizer, Age, and Water are the most important features for determining Strength. The other importance methods generally agree, although they give higher priority to Age due to its strong global influence. Meanwhile for Observation 8, CLIQUE shows that Water is distinctly the most important, while the other methods again emphasize Age or Cement for their strong marginal effects.

4.2 Lichen Classification

In the lichen data, each observation is a different location in a survey region of the Pacific Northwest. This dataset consists of many climate, vegetation, and topographic features for assessing a binary response of the presence or absence of a species of lichen (Lobaria oregana). We build a Random Forest model using all available features, and extract LIME, SHAP, ICI, and CLIQUE values. Results for permutation-based global variable importances (Breiman, 2001) and selected PDPs are shown in Figure 9. MinTempAve (minimum temperature) and ACONIF (age of conifers) are among the most important variables globally for classifying the presence of Lichen. Descriptive analyses show that MinTempAve is highly collinear with AmbVapPressAve ($r = 0.997$) and Elevation ($r = -0.978$), while being almost orthogonal to ACONIF ($r = -0.116$). We focus on MinTempAve, recognizing that very similar patterns will exist for AmbVapPressAve and Elevation. The ACONIF PDP shows a steady upward trend, whereas MinTempAve exhibits a plateau, followed by a steep increase, and another plateau. We aim to determine whether the importance of ACONIF changes for different minimum temperatures.

To do this, we split our data based on whether MinTempAve is below 65 and aggregate importances (**P5**). The resulting boxplots in Figure 10 show that ACONIF has essentially zero CLIQUE importance when minimum temperatures are lower. This makes sense, as lichen struggle to survive in areas with low or freezing temperatures, making ACONIF less important in those regions. If it is sufficiently warm for lichen to survive, then ACONIF more strongly influences their success. The SHAP value distributions in Figure 10 show apparent differences in spread when MinTempAve is above or below 65, but the potentially false-positive effect is more evident in the CLIQUE comparisons. In contrast, the LIME and ICI ACONIF importance boxplots are very similar across low and high MinTempAve conditions.

4.3 MNIST Digit Classification

As another illustrative example, we analyze a down-sampled version of the MNIST Digit test dataset (Al-paydin & Kaynak, 1998) available from scikit-learn (Pedregosa et al., 2011). This dataset consists of 64 features, each a pixel value, with x and y-coordinates ranging from 1 to 8. These pixel values help determine which hand-drawn digit each observation corresponds to. Since this is a multi-class problem, it offers a prime example for illustrating **P4** in CLIQUE, while SHAP and LIME are not natively adapted to provide local

Figure 10: Distributions of ACONIF importances for different MinTempAve thresholds. Importances are scaled by their maximum absolute value within each method. Classically defined outliers are included in whiskers. The CLIQUE values show the greatest contrast between the two regions compared to the other methods, while SHAP offers the next best.

Figure 11: Aggregate tile plots for four digits from the down-sampled MNIST Digit test data. Pixel values are averaged across each observation of a particular digit class to generate these plots.

importances. An example plot of digits is shown in Figure 11. We train a Random Forest model on this data to obtain CLIQUE values. Results for the top permutation-based global importance variables and PDPs are shown in Figure 12.

The global results show that `x4y6` and `x3y6` are two of the most important variables for classifying digits and they neighbor each other. The `x4y6` PDP in Figure 12 shows a distinct region of changing probabilities for low values followed by a plateau effect after about 4.5. The `x3y6` PDP shows a clear crossing pattern at a value of about 7.5. These results suggest the possibility that `x4y6` may be more or less important for low or high values of `x3y6`. They especially imply that `x3y6` may be more or less important for low or high values of `x4y6`.

The left-panel boxplots in Figure 13 show that `x4y6` has a greater importance when `x3y6` is less than 7.5, while `x3y6` has a greater importance when `x4y6` is less than 4.5. These results imply an interaction between these pixels, where each pixel value is more important when the other has a lower value. This behavior is similar to results seen in the AND Gate data of Section 3.1.

In addition to comparing pixel importances against pixel values, we also compare them across digit labels. We present this from two different perspectives. The first is found in the right-panels of Figure 13 which shows CLIQUE boxplots grouped by labels, effectively illustrating that CLIQUE provides **P4** and **P5**. Both `x4y6` and `x3y6` vary in their importance across different digit labels. Pixel `x4y6` has its highest CLIQUE

Figure 12: Global permutation importances (left) and Partial Dependence Plots (center & right) for top features in the downsampled MNIST Digits test data.

Figure 13: Distributions for `x4y6` (top) and `x3y6` (bottom) CLIQUE values across digit classes (left) and identified cutoffs (right). Classically defined outliers are included in whiskers, rather than as distinct points. Digit-aggregated plots show different levels of importance across class-levels. Cutoff-aggregated plots imply an interaction between these pixels, where each pixel value is more important when the other has a lower value.

values for the digits 3 and 9. Although initially surprising, further analysis reveals that for digits 3 and 9, `x4y6` equals 0 more than 80% of the time, while for other digits, it equals 0 less than 60% of the time. Therefore, a value of 0 strongly indicates that a digit is likely a 3 or 9, whereas a value above 0 suggests otherwise. The results also show that `x3y6` has particularly high CLIQUE values for the digit 6. These results suggest that `x3y6` contains information useful for potentially distinguishing the digit 6 from all other digits. When considered alongside trends from Figure 12, low values of `x3y6` appear to correspond with a distinctly lower likelihood that a digit is a 6 rather than another label.

We can do further analysis using a dimensionality reduction method known as PHATE (Moon et al., 2019). PHATE is a visualization tool that balances global and local structures in data. Here, we reduce the data down to two dimensions and create scatterplots of those dimensions in Figure 14. We color this plot by class labels and discretized CLIQUE categories to identify further trends and patterns in our data. From Figure 14, PHATE appears to separate the data into 12 natural clusters, which mostly align with the digit labels, with class 1 and 9 being split.

Beginning with x4y6 in Figure 14, we can see that high CLIQUE values tend to especially appear in the bottom-left quadrant of the plot. Low CLIQUE values tend to fit into the top-right section. Generally, digits 3 and 9 show high values, while digits 0 and 6 show low. One digit class especially catches our attention though: the number 5. Its cluster shows up as a gradient with low CLIQUE values in the top section and high CLIQUE values in the bottom. This suggests that x4y6 CLIQUE values may be a good metric for distinguishing between different ways of writing the number 5.

Figure 14: Scatterplots of PHATE embeddings for the MNIST Digit data. Top-Left: Default plot. Top-Right: PHATE colored by actual digit classes. Bottom-Left: PHATE colored by x4y6 importances cut into three equally sized bins. Bottom-Right: PHATE colored by x3y6 importances cut into three equally sized bins. Digits 3 and 9 have comparably higher x4y6 CLIQUE values, while digits 5, 6, and 9 have comparably higher x3y6 CLIQUE values.

Surprisingly, x3y6 highlights opposing regions in Figure 14 despite its proximity to x4y6. High CLIQUE values generally appear in the bottom right quadrant, while low values fall in the top left. We can visually see that digits 2, 4, and 7 show low values, while digits 5, 6, and 9 show high values. The digits 3 and 9 have overlapping groups, yet we can fairly distinguish them by whether their x3y6 CLIQUE value was high or low.

Additionally, the CLIQUE values of `x3y6` appear to be a good metric for distinguishing between the groups of digit 1. The top-right group has strictly high CLIQUE values for `x3y6`, while the larger main group tends to have lower CLIQUE values. This shows that `x3y6` or its CLIQUE values may be a useful metric for parsing out this subgroup structure. See Appendix A.1 and A.2 for additional results.

5 Discussion and Conclusion

CLIQUE offers a unique perspective on local importance, highlighting conditional or locally dependent information that SHAP, LIME, and ICI do not provide with the same degree of success. While this paper focuses on comparing the values themselves, we acknowledge that **P6**, computation speed, is often a key consideration. Time-cost comparison plots and analyses can be found in Appendix A.3. From this analysis we found that SHAP and CLIQUE are noticeably faster than LIME and ICI. Additionally, CLIQUE scales linearly with more observations, which is better than the quadratic scaling found in SHAP. Conversely, SHAP scales roughly independently with respect to the number of features, which is superior to the linear scaling of CLIQUE. Thus the current version of CLIQUE is competitive with SHAP, LIME, and ICI, with room for further improvements.

In assessing the local importances, we observe that LIME values consistently capture marginal information exclusively. This is not surprising, since LIME tends to be focused on explaining individual predictions, and is rarely applied globally as we have done here. ICI also captures marginal information when considering the importance of variable j on observation i, as we have done throughout this paper. SHAP provides a decomposition that blends marginal and conditional information, but the conditional structure is often biased by the dominant signal. In conditional/ interaction predictor settings, LIME, ICI, and SHAP are each characterized by false-positive importance, overstating the practical relevance of a variable.

In contrast, CLIQUE is explicitly conditional, measuring how a variable value affects prediction error rather than the prediction itself. Near-zero values indicate little effect on individual error, while positive values suggest the variable meaningfully reduces it. By focusing on conditional error reduction, CLIQUE mitigates the risk of false-positive importance arising from correlated predictors or marginal associations that do not improve predictive performance locally. Global assessments can be constructed from the centers and spreads of CLIQUE values. We note that if a variable is more important in a particular region of the feature space, the center and the spread of its CLIQUE values will generally be higher in that region.

In summary, we have provided the structure for a new and novel local importance algorithm. We have shown many applications and contributions of CLIQUE, including its powerful use in capturing conditional or locally dependent importances, mitigating false-positive discovery, improvement over permutation-based methods, and direct use in multi-class classification problems. This research offers many future opportunities for expansion into global importance methods and improving permutation-based algorithms generally.

Code & Data Availability

The code and data for generating the findings of this study are available, and we will include a link after acceptance of the manuscript.

References

E. Alpaydin and C. Kaynak. Optical recognition of handwritten digits. UCI Machine Learning Repository, 1998. DOI: https://doi.org/10.24432/C50P49.

Rina Foygel Barber and Emmanuel J Candès. Controlling the false discovery rate via knockoffs. *The Annals of statistics*, pp. 2055–2085, 2015.

Kelvyn Bladen and D Richard Cutler. Assessing agreement between permutation and dropout variable importance methods for regression and random forest models. *Electronic Research Archive*, 32(7):4495–4514, 2024.

Leo Breiman. Random forests. *Machine learning*, 45(1):5–32, 2001.

Emmanuel Candes, Yingying Fan, Lucas Janson, and Jinchi Lv. Panning for gold:'model-x'knockoffs for high dimensional controlled variable selection. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 80(3):551–577, 2018.

Giuseppe Casalicchio. *featureImportance: Model-agnostic feature importance with the mlr package*, 2025. URL `https://github.com/giuseppec/featureImportance`. R package version 0.9, commit cf064ddc757f73db1efbc7e9722869fbfff8e6ba.

Giuseppe Casalicchio, Christoph Molnar, and Bernd Bischl. Visualizing the feature importance for black box models. In *Machine Learning and Knowledge Discovery in Databases: European Conference, ECML PKDD 2018, Dublin, Ireland, September 10–14, 2018, Proceedings, Part I 18*, pp. 655–670. Springer, 2019.

D Richard Cutler, Thomas C Edwards Jr, Karen H Beard, Adele Cutler, Kyle T Hess, Jacob Gibson, and Joshua J Lawler. Random forests for classification in ecology. *Ecology*, 88(11):2783–2792, 2007.

Susanne Dandl, Christoph Molnar, Martin Binder, and Bernd Bischl. Multi-objective counterfactual explanations. In *International conference on parallel problem solving from nature*, pp. 448–469. Springer, 2020.

Aaron Fisher, Cynthia Rudin, and Francesca Dominici. All models are wrong, but many are useful: Learning a variable's importance by studying an entire class of prediction models simultaneously. *Journal of Machine Learning Research*, 20(177):1–81, 2019.

Alex Goldstein, Adam Kapelner, Justin Bleich, and Emil Pitkin. Peeking inside the black box: Visualizing statistical learning with plots of individual conditional expectation. *journal of Computational and Graphical Statistics*, 24(1):44–65, 2015.

Brandon M. Greenwell. pdp: An R package for constructing partial dependence plots. *The R Journal*, 9(1): 421–436, 2017. URL `https://journal.r-project.org/archive/2017/RJ-2017-016/index.html`.

Brandon M Greenwell, Bradley C Boehmke, and Andrew J McCarthy. A simple and effective model-based variable importance measure. *arXiv preprint arXiv:1805.04755*, 2018.

Giles Hooker, Lucas Mentch, and Siyu Zhou. Unrestricted permutation forces extrapolation: variable importance requires at least one more model, or there is no free variable importance. *Statistics and Computing*, 31:1–16, 2021.

Emil Hvitfeldt, Thomas Lin Pedersen, and Michaël Benesty. *lime: Local Interpretable Model-Agnostic Explanations*, 2022. URL `https://CRAN.R-project.org/package=lime`. R package version 0.5.3.

Konrad Komisarczyk, Pawel Kozminski, Szymon Maksymiuk, and Przemyslaw Biecek. *treeshap: Compute SHAP Values for Your Tree-Based Models Using the 'TreeSHAP' Algorithm*, 2024. URL `https://CRAN.R-project.org/package=treeshap`. R package version 0.3.1.

Jing Lei, Max G'Sell, Alessandro Rinaldo, Ryan J Tibshirani, and Larry Wasserman. Distribution-free predictive inference for regression. *Journal of the American Statistical Association*, 113(523):1094–1111, 2018.

Andy Liaw and Matthew Wiener. Classification and regression by randomforest. *R News*, 2(3):18–22, 2002. URL `https://CRAN.R-project.org/doc/Rnews/`.

Scott Lundberg. A unified approach to interpreting model predictions. *arXiv preprint arXiv:1705.07874*, 2017.

Scott M Lundberg, Gabriel G Erion, and Su-In Lee. Consistent individualized feature attribution for tree ensembles. *arXiv preprint arXiv:1802.03888*, 2018.

Christoph Molnar. *Interpretable machine learning*. Lulu.com, 2020. Chapter 8.5 and Chapter 9, accessed: 2025-01.

Christoph Molnar, Giuseppe Casalicchio, and Bernd Bischl. Pitfalls and best practices in algorithmic interpretability. *arXiv preprint arXiv:2007.04131*, 2020. URL https://arxiv.org/abs/2007.04131.

Kevin R Moon, David Van Dijk, Zheng Wang, Scott Gigante, Daniel B Burkhardt, William S Chen, Kristina Yim, Antonia van den Elzen, Matthew J Hirn, Ronald R Coifman, et al. Visualizing structure and transitions in high-dimensional biological data. *Nature biotechnology*, 37(12):1482–1492, 2019.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

R Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria, 2022. URL https://www.R-project.org.

D Rene. Coarse-grained 6x6 pixel mnist dataset, 2025. URL https://www.mathworks.com/matlabcentral/fileexchange/79580-coarse-grained-6x6-pixel-mnist-dataset. MATLAB Central File Exchange, Retrieved: 2025-01.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "why should i trust you?" explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pp. 1135–1144, 2016.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. *Anchors: High-precision model-agnostic explanations*, 2018.

Cynthia Rudin. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence*, 2019.

Lloyd S Shapley et al. *A value for n-person games*, 1953.

Sandra Wachter, Brent Mittelstadt, and Chris Russell. Counterfactual explanations without opening the black box: Automated decisions and the gdpr. *Harv. JL & Tech.*, 31:841, 2017.

I-Cheng Yeh. Concrete Compressive Strength. UCI Machine Learning Repository, 1998. DOI: https://doi.org/10.24432/C5PK67.

A Additional MNIST Results

Here we show extended results from the MNIST digit classification dataset. We also compare the computational cost of CLIQUE with SHAP, LIME, and ICI.

A.1 MNIST Results by Class

In Section 4.3, we explored CLIQUE importances for MNIST pixel groups. We now take a different approach of assessing top pixels across each digit class. This is done by calculating the mean CLIQUE value for each pixel across each class (**P7**). We collect the top five pixels for each class and show them in Figure 15. From these results, we see that no pixels containing x1 or x8 are included. This matches trends in Figure 11, where we see those two columns of pixels are always zero for each of the example digits. We also observe that digits 3 and 9 share x4y6 as a top pixel. In Section 4.3, we showed that the distribution of x4y6 CLIQUE values was elevated substantially for these two digits in comparison to the others.

Meanwhile, digits 5 and 6 both share x6y3 as their most important pixel. This was followed by x3y6, which we discuss in Section 4.3 as a strong discriminator for these digits. x6y3 does not seem like a powerful pixel for splitting 5s and 6s, since both digits tend to have low values for this pixel. However, it is very effective for splitting 5s and 6s into their own cluster, away from the remaining digits, which generally have high values for x6y3. A noteworthy takeaway is that CLIQUE importance is focused on how a value compares to

Figure 15: Plot showing top 5 predictor variables based on mean CLIQUE values for each digit class. Using the CLIQUE values, digits can be identified that benefit from globally important pixels of `x4y6` and `x6y3`.

the whole distribution of that variable. If eight classes have a high pixel value, while two have a low value, that pixel will be very important for the two different classes, but not as important for the other eight.

We can see this in digit 0, which has a very high CLIQUE value for `x5y5` and `x5y4`. Despite this, both pixels never show up in the top five pixels for any other digit. A likely reason is that these pixel values are low for 0, but higher for all other digits on average. Thus, digit 0 is anomalous with respect to these pixels, making them very effective for distinguishing 0s from the rest of the digits.

A.2 MNIST Samples

In addition to examining top pixels across digit classes, we further explore the two PHATE clusters for digit 1. We select central points from these clusters (denoted A and B, respectively), visualize them, and compare their top CLIQUE pixels in Figure 16. CLIQUE highlights pixels that distinguish these digit 1 samples from other digits. Although the images are visually distinct (A includes an underline whereas B does not), they share some top-ranked pixels, `x4y3` and `x4y4`. Both pixels have high values for the two samples, indicating similar local importance patterns despite morphological differences.

Perhaps more notable are the differences that emerge. Sample B has comparatively high values for `x5y3`, `x7y8`, and `x8y8`, increasing their importance for that observation, whereas sample A does not share these intensities, rendering these pixels less influential for its classification. Conversely, sample A has distinctly low values for `x6y3` and `x3y2`, along with a high value for `x5y2`. These intensities increase the corresponding importances for sample A, whereas the same pixels are not as extreme for sample B, implying that they are less influential for predicting its label.

A.3 Time Cost Comparison

Here we perform a computational time comparison between CLIQUE, SHAP, ICI, and LIME. We use the MNIST dataset with images aggregated to a 6x6 pixel resolution (Rene, 2025) to test the effects of increasing both the number of observations and the number of features on computational time. To ensure compatibility with both SHAP and LIME (which are adapted natively only to binary classification), we limited the dataset to just two digit classes: 3 and 8. These comparisons were all conducted on a Windows computer with an AMD Ryzen 7 4700U 2.00 GHz processor, featuring 8 cores and 16 GB of RAM.

Figure 16: Plot showing samples from the two digit 1 PHATE clusters. Top-Left: PHATE colored by digit 1 class. Bottom-Left: PHATE colored by samples A and B. Middle: Tile plot of A and B. Right: Top 8 pixels from CLIQUE values for A and B.

Figure 17: Plot showing computation time results as features increase, faceted by observations. The points and error bars represent the minimum, median, and maximum times from 20 Monte Carlo simulations.

Figure 17 shows the computational time in seconds for all four methods as a function of the number of features and for different sample sizes. From these results, we observe that both SHAP and CLIQUE are significantly faster than LIME and ICI (**P6**). Additionally, the figure reveals that the SHAP runtime is approximately non-increasing with respect to the number of features, although the variance can be high. In contrast, the CLIQUE runtime increases linearly with the number of features but is more stable.

Figure 18 shows the same results with the computational time as a function of sample size across different numbers of features. From these graphics, we observe that the SHAP runtime generally increases quadratically with the number of observations, while the CLIQUE runtime remains linear.

These results suggest that CLIQUE scales better with increasing observations, while SHAP scales better with more features. This aligns with the expectations set by the authors of TreeSHAP (Lundberg et al., 2018), who describe a fast SHAP implementation with time complexity $O(TLD^2)$, where T is a model hyperparameter, L is the maximum number of tree nodes (which is largely dependent on the number of observations n), and $D = log(L)$. Notably, the SHAP time complexity does not depend on the number of features p, implying that computational cost remains roughly constant across different values of p. While p does influence L, this relationship is not monotonic and is significantly weaker than the effect of n.

Figure 18: Plot showing computation time results as the number of observations increase, faceted by variables. The points and error bars represent the minimum, median, and maximum times from 20 Monte Carlo simulations.