# THE BOOTSTRAP FRAMEWORK: GENERALIZATION THROUGH THE LENS OF ONLINE OPTIMIZATION

## ABSTRACT

We propose a new framework for reasoning about generalization in deep learning. The core idea is to couple the Real World, where optimizers take stochastic gradient steps on the empirical loss, to an Ideal World, where optimizers take steps on the population loss. This leads to an alternate decomposition of test error into: (1) the Ideal World test error plus (2) the gap between the two worlds. If the gap (2) is universally small, this reduces the problem of generalization in offline learning to the problem of optimization in online learning. We then give empirical evidence that this gap between worlds can be small in realistic deep learning settings, in particular supervised image classification. For example, CNNs generalize better than MLPs on image distributions in the Real World, but this is "because" they optimize faster on the population loss in the Ideal World. This suggests our framework is a useful tool for understanding generalization in deep learning, and lays a foundation for future research in the area.

## 1 INTRODUCTION

The goal of a generalization theory in supervised learning is to understand when and why trained models have small test error. The classical framework of generalization decomposes the test error of a model $f_t$ as:

$$\text{TestError}(f_t) = \text{TrainError}(f_t) + \underbrace{[\text{TestError}(f_t) - \text{TrainError}(f_t)]}_{\text{Generalization gap}} \quad (1)$$

and studies each part separately (e.g. Vapnik & Chervonenkis (1971); Blumer et al. (1989); Shalev-Shwartz & Ben-David (2014)). Many works have applied this framework to study generalization of deep networks (e.g. Bartlett (1997); Bartlett et al. (1999); Bartlett & Mendelson (2002); Anthony & Bartlett (2009); Neyshabur et al. (2015b); Dziugaite & Roy (2017); Bartlett et al. (2017); Neyshabur et al. (2017); Harvey et al. (2017); Golowich et al. (2018); Arora et al. (2018; 2019); Allen-Zhu et al. (2019); Long & Sedghi (2019); Wei & Ma (2019)). However, there are at least two obstacles to understanding generalization of modern neural networks via the classical approach.

1. Modern methods can *interpolate*, reaching TrainError $\approx 0$, while still performing well. In these settings, the decomposition of Equation (1) does not actually reduce test error into two different subproblems: it amounts to writing TestError = 0 + TestError. That is, understanding the generalization gap here is exactly equivalent to understanding the test error itself.

2. Most if not all techniques for understanding the generalization gap (e.g. uniform convergence, VC-dimension, regularization, stability, margins) remain vacuous (Zhang et al., 2017; Belkin et al., 2018a;b; Nagarajan & Kolter, 2019) and not predictive (Nagarajan & Kolter, 2019; Jiang et al., 2019) for overparameterized deep networks.

In this work, we propose an alternate approach to understanding generalization to help overcome these obstacles. The key idea is to consider an alternate decomposition:

$$\text{TestError}(f_t) = \underbrace{\text{TestError}(f_t^{\text{iid}})}_{\text{A: Online Learning}} + \underbrace{[\text{TestError}(f_t) - \text{TestError}(f_t^{\text{iid}})]}_{\text{B: Bootstrap error}} \quad (2)$$

where $f_t$ is the neural-network after $t$ optimization steps (the "Real World"), and $f_t^{\text{iid}}$ is a network trained identically to $f_t$, but using fresh samples from the distribution in each mini-batch step (the

Figure 1: Test Soft-Error of two architectures in the Real World and Ideal World, on CIFAR-5m (a CIFAR-10-like task). The test performance in the Real and Ideal worlds remain close, although the Real World has a large generalization gap and sees $100\times$ less samples.

"Ideal World"). That is, $f_t^{\text{iid}}$ is the result of optimizing on the *population loss* for $t$ steps, while $f_t$ is the result of optimizing on the *empirical loss* as usual (we define this more formally later).

This leads to a different decoupling of concerns, and proposes an alternate research agenda to understand generalization. To understand generalization in the bootstrap framework, it is sufficient to understand:

(A) **Online Learning:** How quickly models optimize on the population loss, in the infinite-data regime (the Ideal World).

(B) **Finite-Sample Deviations:** How closely models behave in the finite-data vs. infinite-data regime (the bootstrap error).

Although neither of these points are theoretically understood for deep networks, they are closely related to rich areas in optimization and statistics, whose tools have not been brought fully to bear on the problem of generalization. The first part (A) is purely a question in online stochastic optimization: We have access to a stochastic gradient oracle for a population loss function, and we are interested in how quickly an online optimization algorithm (e.g. SGD, Adam) reaches small population loss. This problem is well-studied in the online learning literature for convex functions (Bubeck, 2011; Hazan, 2019; Shalev-Shwartz et al., 2011), and is an active area of research in non-convex settings (Jin et al., 2017; Lee et al., 2016; Jain & Kar, 2017; Gao et al., 2018; Yang et al., 2018; Maillard & Munos, 2010). In the context of neural networks, optimization is usually studied on the empirical loss landscape (Arora et al., 2019; Allen-Zhu et al., 2019), but we propose studying optimization on the population loss landscape directly. This highlights a key difference in our approach: we never compare test and train quantities— we only consider test quantities.

The second part (B) involves approximating fresh samples with "reused" samples, and reasoning about behavior of certain functions under this approximation. This is closely related to the *non-parametric bootstrap* in statistics (Efron, 1979; Efron & Tibshirani, 1986), where sampling from the population distribution is approximated by sampling with replacement from an empirical distribution. Bootstrapped estimators are widely used in applied statistics, and their theoretical properties are known in certain cases (e.g. Hastie et al. (2009); James et al. (2013); Efron & Hastie (2016); Van der Vaart (2000)). Although current bootstrap theory does not apply to neural networks, it is conceivable that these tools could eventually be extended to our setting.

**Experimental Validation.** Beyond the theoretical motivation, our main experimental claim is that the bootstrap decomposition is actually useful: in realistic settings, the bootstrap error is often small, and the performance of real classifiers is largely captured by their performance in the Ideal World. Figure 1 shows one example of this, as a preview of our more extensive experiments in Section 4. We plot the test error of a ResNet and an MLP on a CIFAR-10-like task, over increasing minibatch SGD iterations. The Real World is trained on 50K samples for 100 epochs. The Ideal World is trained on 5 million samples with a single pass. Notice that the bootstrap error is small for both architectures, although the generalization gap can be large. In particular, the convnet generalizes

better than the MLP on finite data, but this is "because" it optimizes faster on the population loss with infinite data.

**Our Contributions.**

- **Framework:** We propose the Bootstrap Framework for understanding generalization in deep learning, which connects offline generalization to online optimization. (Section 2).
- **Validation:** We give evidence that the bootstrap error is small in realistic settings for supervised image classification, by conducting extensive experiments on large-scale tasks (including variants of CIFAR-10 and ImageNet) for many architectures (Section 4). Thus,

  *The generalization of models in offline learning is largely determined by their optimization speed in online learning.*

- **Implications:** We highlight how our framework can unify and yield insight into important phenomena in deep learning, including implicit bias, model selection, data-augmentation and pretraining (Section 5). For example, we observe a surprising phenomena in practice, which is captured by our framework:

  *The same techniques (architectures and training methods) are used in practice in both over- and under-parameterized regimes.*

**Additional Related Work.** The bootstrap error is also related to algorithmic stability (e.g. Bousquet & Elisseeff (2001); Hardt et al. (2016)), since both quantities involve replacing samples with fresh samples. However, stability-based generalization bounds cannot tightly bound the bootstrap error, since there are many settings where the generalization gap is high, but bootstrap error is low.

## 2 THE BOOSTRAP FRAMEWORK

Here we more formally describe the bootstrap framework and our main claims. Let $\mathcal{F}$ denote a learning algorithm, including architecture and optimizer. We consider optimizers which can be used in online learning, such as stochastic gradient descent and variants. Let $\text{Train}_{\mathcal{F}}(\mathcal{D}, n, t)$ denote training in the "Real World": using the architecture and optimizer specified by $\mathcal{F}$, on a train set of $n$ samples from distribution $\mathcal{D}$, for $t$ optimizer steps. Let $\text{Train}_{\mathcal{F}}(\mathcal{D}, \infty, t)$ denote this same optimizer operating on the population loss (the "Ideal World"). Note that these two procedures use identical architectures, learning-rate schedules, mini-batch size, etc – the only difference is, the Ideal World optimizer sees a fresh minibatch of samples in each optimization step, while the Real World reuses samples in minibatches. Let the Real and Ideal World trained models be:

$$\text{Real World:} \quad f_t \leftarrow \text{Train}_{\mathcal{F}}(\mathcal{D}, n, t)$$

$$\text{Ideal World:} \quad f_t^{\text{iid}} \leftarrow \text{Train}_{\mathcal{F}}(\mathcal{D}, \infty, t)$$

We now claim that for all $t$ until the Real World converges, these two models $f_t, f_t^{\text{iid}}$ have similar test performance. In our main claims, we differ slightly from the presentation in the Introduction in that we consider the "soft-error" of classifiers instead of their hard-errors. The soft-accuracy of classifiers is defined as the softmax probability on the correct label, and (soft-error) := $1 -$ (soft-accuracy). Formally, let $p(x)$ be the softmax distribution of the classifier on input $x$, as a distribution over the label space $\mathcal{Y}$. Then the soft-error is $\mathbb{E}_{x,y\sim\mathcal{D}}[1 - p(x)_y]$. Now define $\varepsilon$ as the bootstrap error – the gap in soft-error between Real and Ideal worlds at time $t$:

$$\text{TestSoftError}_{\mathcal{D}}(f_t) = \text{TestSoftError}_{\mathcal{D}}(f_t^{\text{iid}}) + \varepsilon(n, \mathcal{D}, \mathcal{F}, t) \tag{3}$$

Our main experimental claim is that the bootstrap error $\varepsilon$ is uniformly small in realistic settings.

**Claim 1 (Bootstrap Approximation, informal)** *For choices of $(n, \mathcal{D}, \mathcal{F})$ corresponding to realistic settings in deep learning for supervised image classification, the bootstrap error $\varepsilon(n, \mathcal{D}, \mathcal{F}, t)$ is small for all $t \leq T_0$. The "stopping time" $T_0$ is defined as the time when the Real World reaches small training error (we use 1%) – that is, when Real World training has essentially converged.*

The restriction on $t \leq T_0$ is necessary, since as $t \to \infty$ the Ideal World will continue to improve, but the Real World will at some point essentially stop changing (when train error $\approx 0$). However, we claim that these worlds are close for "as long as we can hope"— as long as the Real World optimizer is still moving.

**Error vs. Soft-Error.** We chose to measure soft-error instead of hard-error in our framework for both empirical and theoretically-motivated reasons. Empirically, we found that the bootstrap gap is often smaller with respect to soft-errors. Theoretically, we want to define the bootstrap gap such that it converges to 0 as data and model size are scaled to infinity. Specifically, if we consider an *overparameterized* scaling limit where the Real World models always interpolate the train data, then Distributional Generalization (Nakkiran & Bansal, 2020) implies that the bootstrap gap for test error will *not* converge to 0 on distributions with non-zero Bayes risk. Roughly, this is because the Ideal World classifier will converge to the Bayes optimal one ($\operatorname{argmax}_y p(y|x)$), while the Real World interpolating classifier will converge to a *sampler* from $p(y|x)$. Considering soft-errors instead of errors nullifies this issue. We elaborate further on the differences between the worlds in Section 6.

## 3 EXPERIMENTAL SETUP

Our bootstrap framework could apply to any setting where an iterative optimizer for online learning is applied in an offline setting. In this work we primarily consider stochastic gradient descent (SGD) applied to deep neural networks for image classification. This setting is well-developed both in practice and in theory, and thus serves as an appropriate first step to vet theories of generalization, as done in many recent works (e.g. Jiang et al. (2019); Neyshabur et al. (2018); Zhang et al. (2017); Arora et al. (2019)). Our work does not depend on overparameterization— it holds for both under and over parameterized networks, though it is perhaps most interesting in the overparameterized setting. We now describe our datasets and experimental methodology.

### 3.1 DATASETS

Measuring the bootstrap error in realistic settings presents some challenges, since we do not have enough samples to instantiate the Ideal World. For example, for a Real World CIFAR-10 network trained on 50K samples for 100 epochs, the corresponding Ideal World training would require 5 million samples (fresh samples in each epoch). Since we do not have 5 million samples for CIFAR-10, we use the following datasets as proxies. More details, including sample images, in Appendix D.

**CIFAR-5m.** We construct a dataset of 6 million synthetic CIFAR-10-like images, by sampling from the CIFAR-10 Denoising Diffusion generative model of Ho et al. (2020), and labeling the unconditional samples by a 98.5% accurate Big-Transfer model (Kolesnikov et al., 2019). These are synthetic images, but close to CIFAR-10 for research purposes. For example, a ResNet-18 trained on 50K samples from CIFAR-5m reaches 92% test accuracy on CIFAR-10 test set. We use 5 million images for training, and reserve the rest for the test set. We release this dataset for public use.

**ImageNet-DogBird.** To test our framework in more complex settings, with real images, we construct a distribution based on ImageNet ILSVRC-2012 (Russakovsky et al., 2015). Recall that we need a setting with a large number of samples relative to the difficulty of the task: if the Real World performs well with few samples and few epochs, then we can simulate it in the Ideal World. Thus, we construct a simpler binary classification task out of ImageNet by collapsing classes into the superclasses "hunting dog" and "bird." This is a roughly balanced task with 155K total images.

### 3.2 METHODOLOGY

For experiments on CIFAR-5m, we exactly simulate the Real and Ideal worlds as described in Section 2. That is, for every Real World architecture and optimizer we consider, we construct the corresponding Ideal World by executing the exact same training code, but using fresh samples in each epoch. The rest of the training procedure remains identical, including data-augmentation and learning-rate schedule. For experiments on ImageNet-DogBird, we do not have enough samples to exactly simulate the Ideal World. Instead, we approximate the Ideal World by using the full training set ($N = 155K$) and data-augmentation. Formally, this corresponds to approximating $\operatorname{Train}_{\mathcal{F}}(\mathcal{D}, \infty, t)$ by $\operatorname{Train}_{\mathcal{F}}(\mathcal{D}, 155K, t)$. In practice, we train the Real World on $n = 10K$ samples for 120 epochs, so we can approximate this with less than 8 epochs on the full $155K$ train set. Since we train with data augmentation (crop+resize+flip), each of the 8 repetitions of each sample will undergo different random augmentations, and thus this plausibly approximates fresh samples.

(a) Standard architectures.       (b) Random DARTS architectures.

Figure 2: **Real vs Ideal World: CIFAR-5m.** SGD with 50K samples. (a): Varying learning-rates $0.1$ (●), $0.01$ (■), $0.001$ (▲). (b): Random architectures from DARTS space (Liu et al., 2019).

**Stopping time.** We stop both Real and Ideal World training when the Real World reaches a small value of train error (which we set as $1\%$ in all experiments). This stopping condition is necessary, as described in Section 2. Thus, for experiments which report test performance "at the end of training", this refers to either when the target number of epochs is reached, or when Real World training has converged ($< 1\%$ train error). We always compare Real and Ideal Worlds after the exact same number of train iterations.

## 4 MAIN EXPERIMENTS

We now give evidence to support our main experimental claim, that the bootstrap error $\varepsilon$ is often small for realistic settings in deep learning for image classification. In all experiments in this section, we instantiate the same model and training procedure in the Real and Ideal Worlds, and observe that the test soft-error is close at the end of training. Full experimental details are in Appendix C.2.

**CIFAR-5m.** In Figure 2a we consider a variety of standard architectures on CIFAR-5m, from fully-connected nets to modern convnets. In the Real World, we train these architectures with SGD on $n = 50K$ samples from CIFAR-5m, for 100 total epochs. We then construct the corresponding Ideal Worlds for each architecture, trained in the same way with fresh samples each epoch. Figure 2a shows the test soft-error of the trained classifiers in the Real and Ideal Worlds at the end of training. Observe that test performance is very close in Real and Ideal worlds, although the Ideal World sees $100\times$ unique samples during training.

To test our framework for more diverse architectures, we also sample 500 random architectures from the DARTS search space (Liu et al., 2019). These are deep convnets of varying width and depth, which range in size from 70k to 5.5 million parameters. Figure 2b shows the Real and Ideal World test performance at the end of training— these are often within $3\%$.

**ImageNet: DogBird.** We now test various ImageNet architectures on ImageNet-DogBird. The Real World models are trained with SGD on $n = 10K$ samples with standard ImageNet data augmentation. We approximate the Ideal World by training on $155K$ samples as described above. Figure 3a plots the Real vs. Ideal World test error at the end of training, for various architectures. Figure 3b shows this for ResNet-18s of varying widths.

## 5 DEEP PHENOMENA THROUGH THE BOOTSTRAP LENS

Here we show that our bootstrap framework can be insightful to study phenomena and design choices in deep learning. For example, many effects in the Real World can be seen through their corresponding effects in the Ideal World. Full details for experiments provided in Appendix C.

**Model Selection in the Over- and Under-parameterized Regimes.** Much of theoretical work in deep learning focuses on overparameterized networks, which are large enough to fit their train sets.

(a) Standard architectures.

(b) ResNet-18s of varying width.

Figure 3: **ImageNet-DogBird.** Real World models trained on 10K samples.

However, in modern practice, state-of-the-art networks can be either over or *under*-parameterized, depending on the scale of data. For example, SOTA models on 300 million JFT images or 1 billion Instagram images are underfitting, due to the massive size of the train set (Sun et al., 2017; Mahajan et al., 2018). In NLP, modern models such as GPT-3 and T5 are trained on massive internet-text datasets, and so are solidly in the underparameterized regime (Kaplan et al., 2020; Brown et al., 2020; Raffel et al., 2019). We highlight one surprising aspect of this situation:

*The same techniques (architectures and training methods)*
*are used in practice in both over- and under-parameterized regimes.*

For example, ResNet-101 is competitive both on 1 billion images of Instagram (when it is underparameterized) and on 50k images of CIFAR-10 (when it is overparameterized). This observation was made recently in Bornschein et al. (2020) for overparameterized architectures, and we observe it extends to the underparameterized regime. It is apriori surprising that the same architectures do well in both over and underparameterized regimes, since there are very different considerations in each regime. In the overparameterized regime, architecture matters for generalization reasons: there are many ways to fit the train set, and some architectures lead SGD to minima that generalizes better. In the underparameterized regime, architecture matters for purely optimization reasons: all models will have small generalization gap with 1 billion+ samples, but we seek models which are capable of reaching low values of test loss, and which do so quickly (with few optimization steps). Thus, it should be surprising that in practice, we use essentially the same architectures in both regimes.

Our work suggests that these phenomena are closely related: If the boostrap error is small, then we should expect that architectures which optimize well in the infinite-data (underparameterized) regime also generalize well in the finite-data (overparameterized) regime. This unifies the two apriori different principles guiding model-selection in over and under-parameterized regimes, and helps understand why the same architectures are used in both regimes.

**Implicit Bias via Explicit Optimization.** Much recent theoretical work has focused on the *implicit bias* of gradient descent (e.g. Neyshabur et al. (2015a); Soudry et al. (2018); Gunasekar et al. (2018b;a); Ji & Telgarsky (2019); Chizat & Bach (2020)). For overparameterized networks, there are many minima of the empirical loss, some which have low test error and others which have high test error. Thus studying why interpolating networks generalize amounts to studying why SGD is "biased" towards finding empirical minima with low population loss. Our framework suggests an alternate perspective: instead of directly trying to characterize which empirical minima SGD reaches, it may be sufficient to study why SGD optimizes quickly on the population loss. That is, instead of studying implicit bias of optimization on the empirical loss, we could study explicit properties of optimization on the population loss.

The following experiment highlights this approach. Consider the D-CONV and D-FC architectures introduced recently by Neyshabur (2020). D-CONV is a deep convolutional network and D-FC is its fully-connected counterpart: an MLP which subsumes the convnet in expressive capacity. That is, D-FC is capable of representing all functions that D-CONV can represent, since it replaces all conv layers with fully-connected layers and unties all the weights. Both networks reach close to 0 train

(a) ResNet-18, varying samples.  (b) All architectures, varying samples.

Figure 4: **Effect of Sample Size.**

error on 50K samples from CIFAR-5m, but the convnet generalizes much better. The traditional explanation for this is that the "implicit bias" of SGD biases the convnet to a better-generalizing minima than the MLP. We show that, in fact, this generalization is captured by the fact that D-CONV optimizes much faster on the population loss than D-FC. Figure 5c shows the test and train errors of both networks when trained on 50K samples from CIFAR-5m, in the Real and Ideal Worlds. Observe that the Real and Ideal world test performances are nearly identical.

**Sample Size.** In Figure 4, we consider the effect of varying the train set size in the Real World. Note that in this case, the Ideal World does not change. There are two effects of increasing $n$: (1) The stopping time extends— Real World training continues for longer before converging. And (2) the bootstrap error decreases. Of these, (1) is the dominant effect. Figure 4a illustrates this behavior in detail by considering a single model: ResNet-18 on CIFAR-5m. We plot the Ideal World behavior of ResNet-18, as well as different Real Worlds for varying $n$. All Real Worlds are stopped when they reach $< 1\%$ train error, as we do throughout this work. After this point their test performance is essentially flat (shown as faded lines). However, until this stopping point, all Real Worlds are roughly close to the Ideal World, becoming closer with larger $n$. These learning curves are representative of most architectures in our experiments. Figure 4b shows the same architectures of Figure 2a, trained on various sizes of train sets from CIFAR-5m. The Real and Ideal worlds may deviate from each other at small $n$, but become close for realistically large values of $n$.

**Data Augmentation.** Data augmentation in the Ideal World corresponds to randomly augmenting each fresh sample before training on it (as opposed to re-using the same sample for multiple augmentations). There are 3 potential effects of data augmentation in our framework: (1) it can affect the Ideal World optimization, (2) it can affect the bootstrap gap, and (3) it can affect the Real World stopping time (time until training converges). We find that the dominant factors are (1) and (3), though data augmentation does typically reduce the bootstrap gap as well. Figure 5a shows the effect of data augmentation on ResNet-18 for CIFAR-5m. In this case, data augmentation does not change the Ideal World much, but it extends the time until the Real World training converges. This view suggests that good data augmentations should (1) not hurt optimization in the Ideal World (i.e., not destroy true samples much), and (2) obstruct optimization in the Real World (so the Real World can improve for longer before converging). This is aligned with the "affinity" and "diversity" view of data augmentations in Gontijo-Lopes et al. (2020). See Appendix B.2 for more figures, including examples where data augmentation hurts the Ideal World.

**Pretraining.** Figure 5b shows the effect of pretraining for Image-GPT (Chen et al., 2020), a transformer pretrained for generative modeling on ImageNet. We fine-tune iGPT-S on 2K samples of CIFAR-10 (not CIFAR-5m, since we have enough samples in this case) and compare initializing from an early checkpoint vs. the final pretrained model. The fully-pretrained model generalizes better in the Real World, and also optimizes faster in the Ideal World. An additional experiment of ImageNet-pretraining for MLPs is in Appendix B.4.

**Random Labels.** Our approach of comparing Real and Ideal worlds also captures generalization in the random-label experiment of Zhang et al. (2017). Specifically, if we train on a distribution with purely random labels, both Real and Ideal world models will have trivial test error.

(a) Data Aug: ResNet-18.        (b) Pretrain: Image-GPT ($n = 2K$).        (c) Implicit Bias.

Figure 5: **Deep Phenomena in Real vs. Ideal Worlds.**

# 6    DIFFERENCES BETWEEN THE WORLDS

In our framework, we only compare the test soft-error of models in the Real and Ideal worlds. We do not claim these models are close in all respects— in fact, this is not true. For example, Figure 6 shows the same ResNet-18s trained in the Introduction (Figure 1), measuring three different metrics in both worlds. Notably, the test *loss* diverges drastically between the Real and Ideal worlds, although the test soft-error (and to a lesser extent, test error) remains close. This is because training to convergence in the Real World will cause the network weights to grow unboundedly, and the softmax distribution to concentrate (on both train and test). In contrast, training in the Ideal World will generally not cause weights to diverge, and the softmax will remain diffuse. This phenomenon also means that the Error and Soft-Error are close in the Real World, but can be slightly different in the Ideal World, which is consistent with our experiments.

Figure 6: **SoftError vs. Error vs. Loss: ResNet-18.**

# 7    CONCLUSION AND DISCUSSION

We propose the Bootstrap Framework for understanding generalization in deep learning. Our approach is to compare the Real World, where optimizers take steps on the empirical loss, to an Ideal World, where optimizers have infinite data and take steps on the population loss. We find that in modern settings, the test performance of models is close between these worlds. This establishes a new connection between the fields of generalization and online learning: models which learn quickly (online) also generalize well (offline). Our framework thus provides a new lens on deep phenomena, and lays a promising route towards theoretically understanding generalization in deep learning.

Our work takes first steps towards characterizing the bootstrap error, but fully understanding this is an important area for future study. The bootstrap error is not universally small for all models and learning tasks: for example, we found the gap was larger at limited sample sizes and without data augmentation. Moreover, it can be large in simple settings like linear regression (Appendix A), or settings when the Real World test error is non-monotonic (e.g. due to epoch double-decent (Nakkiran et al., 2020)). Nevertheless, the gap appears to be small in realistic deep learning settings, and we hope that future work can help understand why.

# REFERENCES

Zeyuan Allen-Zhu, Yuanzhi Li, and Yingyu Liang. Learning and generalization in overparameterized neural networks, going beyond two layers. In *Advances in neural information processing systems*, pp. 6158–6169, 2019.

Martin Anthony and Peter L Bartlett. *Neural network learning: Theoretical foundations*. cambridge university press, 2009.

Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach. *arXiv preprint arXiv:1802.05296*, 2018.

Sanjeev Arora, Simon Du, Wei Hu, Zhiyuan Li, and Ruosong Wang. Fine-grained analysis of optimization and generalization for overparameterized two-layer neural networks. In *International Conference on Machine Learning*, pp. 322–332, 2019.

Peter L Bartlett. For valid generalization the size of the weights is more important than the size of the network. In *Advances in neural information processing systems*, pp. 134–140, 1997.

Peter L Bartlett and Shahar Mendelson. Rademacher and gaussian complexities: Risk bounds and structural results. *Journal of Machine Learning Research*, 3(Nov):463–482, 2002.

Peter L Bartlett, Vitaly Maiorov, and Ron Meir. Almost linear vc dimension bounds for piecewise polynomial networks. In *Advances in neural information processing systems*, pp. 190–196, 1999.

Peter L Bartlett, Dylan J Foster, and Matus J Telgarsky. Spectrally-normalized margin bounds for neural networks. In *Advances in Neural Information Processing Systems*, pp. 6240–6249, 2017.

Mikhail Belkin, Daniel J Hsu, and Partha Mitra. Overfitting or perfect fitting? risk bounds for classification and regression rules that interpolate. In *Advances in neural information processing systems*, pp. 2300–2311, 2018a.

Mikhail Belkin, Siyuan Ma, and Soumik Mandal. To understand deep learning we need to understand kernel learning. *arXiv preprint arXiv:1802.01396*, 2018b.

Anselm Blumer, Andrzej Ehrenfeucht, David Haussler, and Manfred K Warmuth. Learnability and the vapnik-chervonenkis dimension. *Journal of the ACM (JACM)*, 36(4):929–965, 1989.

Jörg Bornschein, Francesco Visin, and Simon Osindero. Small data, big decisions: Model selection in the small-data regime. *ICML*, 2020.

Olivier Bousquet and André Elisseeff. Algorithmic stability and generalization performance. In *Advances in Neural Information Processing Systems*, pp. 196–202, 2001.

Wieland Brendel and Matthias Bethge. Approximating cnns with bag-of-local-features models works surprisingly well on imagenet. *arXiv preprint arXiv:1904.00760*, 2019.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Sébastien Bubeck. Introduction to online optimization. *Lecture Notes*, 2, 2011.

Mark Chen, Alec Radford, Rewon Child, Jeff Wu, Heewoo Jun, Prafulla Dhariwal, David Luan, and Ilya Sutskever. Generative pretraining from pixels. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.

Lenaic Chizat and Francis Bach. Implicit bias of gradient descent for wide two-layer neural networks trained with the logistic loss. *arXiv preprint arXiv:2002.04486*, 2020.

Xuanyi Dong and Yi Yang. Nas-bench-201: Extending the scope of reproducible neural architecture search. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=HJxyZkBKDr`.

Gintare Karolina Dziugaite and Daniel M Roy. Computing nonvacuous generalization bounds for deep (stochastic) neural networks with many more parameters than training data. *arXiv preprint arXiv:1703.11008*, 2017.

B. Efron. Bootstrap methods: Another look at the jackknife. *Ann. Statist.*, 7(1):1–26, 01 1979. doi: 10.1214/aos/1176344552. URL `https://doi.org/10.1214/aos/1176344552`.

Bradley Efron and Trevor Hastie. *Computer age statistical inference*, volume 5. Cambridge University Press, 2016.

Bradley Efron and Robert Tibshirani. Bootstrap methods for standard errors, confidence intervals, and other measures of statistical accuracy. *Statistical science*, pp. 54–75, 1986.

Xiand Gao, Xiaobo Li, and Shuzhong Zhang. Online learning with non-convex losses and non-stationary regret. In *International Conference on Artificial Intelligence and Statistics*, pp. 235–243, 2018.

Noah Golowich, Alexander Rakhlin, and Ohad Shamir. Size-independent sample complexity of neural networks. In *Conference On Learning Theory*, pp. 297–299. PMLR, 2018.

Raphael Gontijo-Lopes, Sylvia J Smullin, Ekin D Cubuk, and Ethan Dyer. Affinity and diversity: Quantifying mechanisms of data augmentation. *arXiv preprint arXiv:2002.08973*, 2020.

Suriya Gunasekar, Jason Lee, Daniel Soudry, and Nathan Srebro. Characterizing implicit bias in terms of optimization geometry. *arXiv preprint arXiv:1802.08246*, 2018a.

Suriya Gunasekar, Jason D Lee, Daniel Soudry, and Nati Srebro. Implicit bias of gradient descent on linear convolutional networks. In *Advances in Neural Information Processing Systems*, pp. 9461–9471, 2018b.

Moritz Hardt, Ben Recht, and Yoram Singer. Train faster, generalize better: Stability of stochastic gradient descent. In *International Conference on Machine Learning*, pp. 1225–1234. PMLR, 2016.

Nick Harvey, Christopher Liaw, and Abbas Mehrabian. Nearly-tight vc-dimension bounds for piecewise linear neural networks. In *Conference on Learning Theory*, pp. 1064–1068, 2017.

Trevor Hastie, Robert Tibshirani, and Jerome Friedman. *The elements of statistical learning: data mining, inference, and prediction*. Springer Science & Business Media, 2009.

Elad Hazan. Introduction to online convex optimization. *arXiv preprint arXiv:1909.05207*, 2019.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *arXiv preprint arxiv:2006.11239*, 2020.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Like Hui and Mikhail Belkin. Evaluation of neural architectures trained with square loss vs cross-entropy in classification tasks. *arXiv preprint arXiv:2006.07322*, 2020.

Prateek Jain and Purushottam Kar. Non-convex optimization for machine learning. *arXiv preprint arXiv:1712.07897*, 2017.

Gareth James, Daniela Witten, Trevor Hastie, and Robert Tibshirani. *An introduction to statistical learning*, volume 112. Springer, 2013.

Ziwei Ji and Matus Telgarsky. The implicit bias of gradient descent on nonseparable data. In *Conference on Learning Theory*, pp. 1772–1798, 2019.

Yiding Jiang, Behnam Neyshabur, Hossein Mobahi, Dilip Krishnan, and Samy Bengio. Fantastic generalization measures and where to find them. *arXiv preprint arXiv:1912.02178*, 2019.

Chi Jin, Rong Ge, Praneeth Netrapalli, Sham M Kakade, and Michael I Jordan. How to escape saddle points efficiently. *arXiv preprint arXiv:1703.00887*, 2017.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Large scale learning of general visual representations for transfer. *arXiv preprint arXiv:1912.11370*, 2019.

A. Krizhevsky. Learning multiple layers of features from tiny images. Master's thesis, Computer Science Department, University of Toronto, 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pp. 1097–1105, 2012.

Jason D Lee, Max Simchowitz, Michael I Jordan, and Benjamin Recht. Gradient descent only converges to minimizers. In *Conference on learning theory*, pp. 1246–1257, 2016.

Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: Differentiable architecture search. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=S1eYHoC5FX.

Philip M Long and Hanie Sedghi. Generalization bounds for deep convolutional neural networks. *arXiv preprint arXiv:1905.12600*, 2019.

Dhruv Mahajan, Ross Girshick, Vignesh Ramanathan, Kaiming He, Manohar Paluri, Yixuan Li, Ashwin Bharambe, and Laurens van der Maaten. Exploring the limits of weakly supervised pretraining. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 181–196, 2018.

Odalric-Ambrym Maillard and Rémi Munos. Online learning in adversarial lipschitz environments. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 305–320. Springer, 2010.

Vaishnavh Nagarajan and J. Zico Kolter. Uniform convergence may be unable to explain generalization in deep learning, 2019.

Preetum Nakkiran and Yamini Bansal. Distributional generalization: A new kind of generalization. *arXiv preprint arXiv:2009.08092*, 2020.

Preetum Nakkiran, Gal Kaplun, Yamini Bansal, Tristan Yang, Boaz Barak, and Ilya Sutskever. Deep double descent: Where bigger models and more data hurt. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=B1g5sA4twr.

Behnam Neyshabur. Towards learning convolutions from scratch. *arXiv preprint arXiv:2007.13657*, 2020.

Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. In search of the real inductive bias: On the role of implicit regularization in deep learning. In *ICLR (Workshop)*, 2015a.

Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. Norm-based capacity control in neural networks. In *Conference on Learning Theory*, pp. 1376–1401, 2015b.

Behnam Neyshabur, Srinadh Bhojanapalli, and Nathan Srebro. A pac-bayesian approach to spectrally-normalized margin bounds for neural networks. *arXiv preprint arXiv:1707.09564*, 2017.

Behnam Neyshabur, Zhiyuan Li, Srinadh Bhojanapalli, Yann LeCun, and Nathan Srebro. Towards understanding the role of over-parametrization in generalization of neural networks. *arXiv preprint arXiv:1805.12076*, 2018.

David Page. How to train your resnet, 2018.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. dAlché Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/ 9015-pytorch-an-imperative-style-high-performance-deep-learning-library. pdf.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *arXiv preprint arXiv:1910.10683*, 2019.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115(3):211–252, 2015. doi: 10.1007/s11263-015-0816-y.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4510–4520, 2018.

Shai Shalev-Shwartz and Shai Ben-David. *Understanding machine learning: From theory to algorithms*. Cambridge university press, 2014.

Shai Shalev-Shwartz et al. Online learning and online convex optimization. *Foundations and trends in Machine Learning*, 4(2):107–194, 2011.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. In *ICLR*, 2015.

Daniel Soudry, Elad Hoffer, Mor Shpigel Nacson, Suriya Gunasekar, and Nathan Srebro. The implicit bias of gradient descent on separable data. *The Journal of Machine Learning Research*, 19 (1):2822–2878, 2018.

Chen Sun, Abhinav Shrivastava, Saurabh Singh, and Abhinav Gupta. Revisiting unreasonable effectiveness of data in deep learning era. In *Proceedings of the IEEE international conference on computer vision*, pp. 843–852, 2017.

Aad W Van der Vaart. *Asymptotic statistics*, volume 3. Cambridge university press, 2000.

V. N. Vapnik and A. Y. Chervonenkis. On the uniform convergence of relative frequencies of events to their probabilities. *Theory of Probability and its Applications*, XVI(2):264–280, 1971.

Colin Wei and Tengyu Ma. Improved sample complexities for deep neural networks and robust classification via an all-layer margin. In *International Conference on Learning Representations*, 2019.

Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1492–1500, 2017.

Lin Yang, Lei Deng, Mohammad H Hajiesmaili, Cheng Tan, and Wing Shing Wong. An optimal algorithm for online non-convex learning. *Proceedings of the ACM on Measurement and Analysis of Computing Systems*, 2(2):1–25, 2018.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. In *ICLR*, 2017.

## A   TOY EXAMPLE

Here we present a theoretically-inspired toy example, giving a simple setting where the bootstrap gap is small, but the generalization gap is large. We also give an analogous example where the bootstrap error is large. The purpose of these examples is (1) to present a simple setting where the bootstrap framework can be more useful than studying the generalization gap. And (2) to illustrate that the bootstrap gap is not always small, and can be large in certain standard settings.

We consider the following setup. Let us pass to a regression setting, where we have a distribution over $(x, y) \in \mathbb{R}^d \times \mathbb{R}$, and we care about mean-square-error instead of classification error. That is, for a model $f$, we have $\text{TestMSE}(f) := \mathbb{E}_{x,y}[(f(x) - y)^2]$. Both our examples are from the following class of distributions in dimension $d = 1000$.

$$x \sim \mathcal{N}(0, V)$$
$$y := \sigma(\langle \beta^*, x \rangle)$$

where $\beta^* \in \mathbb{R}^d$ is the ground-truth, and $\sigma$ is a pointwise activation function. The model family is linear,

$$f_\beta(x) := \langle \beta, x \rangle$$

We draw $n$ samples from the distribution, and train the model $f_\beta$ using full-batch gradient descent on the empirical loss:

$$\text{TrainMSE}(f_\beta) := \frac{1}{n} \sum_i (f(x_i) - y_i)^2 = \frac{1}{n} ||X\beta - y||^2$$

We chose $\beta^* = e_1$, and covariance $V$ to be diagonal with 10 eigenvalues of 1 and the remaining eigenvalues of 0.1. That is, $x$ is essentially 10-dimensional, with the remaining coordinates "noise."

The two distributions are instances of the above setting for different choices of parameters.

- **Setting A.** Linear activation $\sigma(x) = x$. With $n = 20$ train samples.
- **Setting B.** Sign activation $\sigma(x) = \text{sgn}(x)$. With $n = 100$ train samples.

Setting A is a standard well-specified linear regression setting. Setting B is a misspecified regression setting. Figure 7 shows the Real and Ideal worlds in these settings, for gradient-descent on the empirical loss (with step-size $\eta = 0.1$). Observe that in the well-specified Setting A, the Ideal World performs much better than the Real World, and the bootstrap framework is not as useful. However, in the misspecified Setting B, the bootstrap gap remains small even as the generalization gap grows.

Figure 7: **Toy Example.** Examples of settings with large and small bootstrap error.

This toy example is contrived to help isolate factors important in more realistic settings. We have observed behavior similar to Setting B in other simple settings with real data, such as regression on MNIST/Fashion-MNIST, as well as in the more complex settings in the body of this paper.

# B  ADDITIONAL FIGURES

## B.1  DARTS ARCHITECTURES

Figure 8 shows the Real vs Ideal world for trained random DARTS architectures.

(a) All architectures.

(b) High accuracy architectures.

Figure 8: **Random DARTS Architectures.** Panel (b) shows zoomed view of panel (a).

## B.2  EFFECT OF DATA AUGMENTATION

Figure 9 shows the effect of data-augmentation in the Ideal World, for several selected architectures on CIFAR-5m. Recall that data augmentation in the Ideal World corresponds to randomly augmenting each fresh sample once, as opposed to augmenting the same sample multiple times. We train with SGD using the same hyperparameters as the main experiments (described in Appendix C.2). We use standard CIFAR-10 data augmentation: random crop and random horizontal flip.

The test performance without augmentation is shown as solid lines, and with augmentation as dashed lines. Note that VGG and ResNet do not behave differently with augmentation, but augmentation significantly hurts AlexNet and the MLP. This may be because VGG and ResNet have global spatial pooling, which makes them (partially) shift-invariant, and thus more amenable to the random cropping. In contrast, augmentation hurts the architectures without global pooling, perhaps because for these architectures, augmented samples appear more out-of-distribution.

Figure 9: Effect of Data Augmentation in the Ideal World.

Figure 10a shows the same architectures and setting as Figure 2 but trained without data augmentation. That is, we train on 50K samples from CIFAR-5m, using SGD with cosine decay and initial learning rate $\{0.1, 0.01, 0.001\}$.

Figure 10b shows learning curves with and without data augmentation of a ResNet-18 on $n = 10k$ samples. This is the analogous setting of Figure 5a in the body, which is for $n = 50k$ samples.

(a) No Data-augmentation. Compare to Figure 2.

(b) ResNet-18 on 10K samples.

Figure 10: **Effect of Data Augmentation.**

## B.3 ADAM

Figure 11 shows several experiments with the Adam optimizer (Kingma & Ba, 2014) in place of SGD. We train all architectures on 50K samples from CIFAR-5m, with data-augmentation, batchsize 128, using Adam with default parameters (lr=0.001, $\beta_1 = 0.9, \beta_2 = 0.999$).

(a) Real vs. Ideal learning curves.

(b) Real vs. Ideal world at the end of training.

Figure 11: **Adam Experiments.** For various architectures on 50K samples from CIFAR-5m.

## B.4 PRETRAINING

Figure 12 shows the effect of pretraining for an MLP (3x2048) on CIFAR-5m, by comparing training from scratch (random initialization) to training from an ImageNet-pretrained initialization. The pretrained MLP generalizes better in the Real World, and also optimizes faster in the Ideal World. We fine tune on 50K samples from CIFAR-5m, with no data-augmentation.

For ImageNet-pretraining, we train the MLP[3x2048] on full ImageNet (224px, 1000 classes), using Adam with default settings, and batchsize 1024. We use standard ImageNet data augmentation (random resized crop + horizontal flip) and train for 500 epochs. This MLP achieves test accuracy 21% and train accuracy 30% on ImageNet. For fine-tuning, we adapt the network to 32px input size by resizing the first layer filters from 224x224 to 32x32 via bilinear interpolation. We then replace the classification layer, and fine-tune the entire network on CIFAR-5m.

Figure 12: ImageNet-Pretraining: MLP[3x2048].

## B.5 DIFFERENCE BETWEEN WORLDS

Figure 13 shows test soft-error, test error, and test loss for VGG-11 from Figure 1.

Figure 13: **SoftError vs. Error vs. Loss: VGG-11.**

## B.6 ERROR VS. SOFTERROR

Here we show the results of several of our experiments if we measure the bootstrap gap with respect to Test Error instead of SoftError. The bootstrap gap is often reasonably small even with respect to Error, though it is not as well behaved as SoftError.

Figure 14 shows the same setting as Figure 2a in the body, but measuring Error instaed of SoftError.

Figure 14: Measuring Test Error instead of SoftError. Compare to Figure 2a

### B.6.1 TRAINING WITH MSE

We can measure Test Error even for networks which do not naturally output a probability distribution. Here, we train various architectures on CIFAR-5m using the squared-loss (MSE) directly on logits, with no softmax layer. This follows the methodology in Hui & Belkin (2020). We train all Real-World models using SGD, batchsize 128, momentum 0.9, initial learning rate 0.002 with cosine decay for 100 epochs.

Figure 15 shows the Test Error and Test Loss in the Real and Ideal Worlds. The bootstrap gap, with respect to test error, for MSE-trained networks is reasonably small – though there are deviations in the low error regime. Compare this to Figure 2a, which measures the SoftError for networks trained with cross-entropy.

(a) Test Error.

(b) Test Loss.

Figure 15: **Real vs. Ideal: Training with Squared Loss.**

# C  APPENDIX: EXPERIMENTAL DETAILS

## C.1  INTRODUCTION EXPERIMENT

All architectures trained in the Real World with $n = 50K$ samples from CIFAR-5m, using SGD with batch size 128, cross-entropy loss, initial learning rate 0.1, cosine learning rate decay, for 100 epochs, with random crop+horizontal flip data-augmentation (i.e. standard CIFAR-10 data augmentation). The MLP was additional trained with momentum 0.9 to improve convergence. We plot median over 10 trials (with random sampling of the train set, random initialization, and random SGD order in each trial).

We use an MLP with 5 hidden layers of width 2048, with batch norm. Figure 1 plots the Test Soft-Error and Train Soft-Errors over the course of training.

## C.2  MAIN EXPERIMENTS

For CIFAR-5m we use the following architectures: AlexNet (Krizhevsky et al., 2012), VGG (Simonyan & Zisserman, 2015), ResNet (He et al., 2016), DenseNet (Huang et al., 2017). The Myrtle5 architecture is a 5-layer CNN introduced by (Page, 2018). All our experiments are implemented in PyTorch (Paszke et al., 2019).

In the Real World, we train these architectures on $n = 50K$ samples from CIFAR-5m using cross-entropy loss. All models are trained with SGD with batchsize 128, initial learning rate $\{0.1, 0.01, 0.001\}$, cosine learning rate decay, for 100 total epochs, with data augmentation: random horizontal flip and `RandomCrop(32, padding=4)`. We plot median over 10 trials (with random sampling of the train set, random initialization, and random SGD order in each trial).

**DARTS Architectures.** We sample architectures from the DARTS search space (Liu et al., 2019), as implemented in the codebase of Dong & Yang (2020). We follow the parameters used for CIFAR-10 in Dong & Yang (2020), while also varying width and depth for added diversity. Specifically, we use 4 nodes, number of cells $\in \{1, 5\}$, and width $\in \{16, 64\}$. We train all DARTS architectures with SGD, batchsize 128, initial learning rate 0.1, cosine learning rate decay, for 100 total epochs, with random crop+flip data-augmentation.

**ImageNet: DogBird** All architectures for ImageNet-DogBird are trained with SGD, batchsize 128, learning rate 0.01, momentum 0.9, for 120 epochs, with standard ImageNet data augmentation (random resized crop to 224px, horizontal flip). We report medians over 10 trials for each architecture.

We additional include the ImageNet architectures: BagNet (Brendel & Bethge, 2019), MobileNet (Sandler et al., 2018), and ResNeXt (Xie et al., 2017). The architectures SCONV9 and SCONV33 refer to the S-CONV architectures defined by Neyshabur (2020), instantiated for ImageNet with base-width 48, image size 224, and kernel size $\{9, 33\}$ respectively.

## C.3  IMPLICIT BIAS

We use the D-CONV architecture from (Neyshabur, 2020), with base width 32, and the corresponding D-FC architecture. PyTorch specification of these architectures are provided in Appendix E for convenience. We train both architectures with SGD, batchsize 128, initial learning rate 0.1, cosine learning rate decay, for 100 total epochs, with random crop + horizontal flip data-augmentation. We plot median errors over 10 trials.

## C.4  IMAGE-GPT FINETUNING

We fine-tune iGPT-S, using the publicly available pretrained model checkpoints from Chen et al. (2020). The "Early" checkpoint in Figure 5b refers to checkpoint 131000, and the "Final" checkpoint is 1000000. Following Chen et al. (2020), we use Adam with ($lr = 0.003, \beta_1 = 0.9, \beta_2 = 0.95$), and batchsize 128. We do not use data augmentation. For simplicity, we differ slightly from Chen et al. (2020) in that we simply attach the classification head to the [average-pooled] last transformer layer, and we fine-tune using only classification loss and not the joint generative+classification loss used in Chen et al. (2020). Note that we fine-tune the entire model, not just the classification head.

# D APPENDIX: DATASETS

## D.1 CIFAR-5M

CIFAR-5m is a dataset of 6 million synthetic CIFAR-10-like images. The images are RGB $32 \times 32$px. We generate samples from the Denoising Diffusion generative model of Ho et al. (2020) trained on the CIFAR-10 train set (Krizhevsky, 2009). We use the publicly available trained model and sampling code provided by the authors at `https://github.com/hojonathanho/diffusion`. We then label these unconditional samples by a 98.5% accurate Big-Transfer model (Kolesnikov et al., 2019). Specifically, we use the pretrained BiT-M-R152x2 model, fine-tuned on CIFAR-10 using the author-provided code at `https://github.com/google-research/big_transfer`. We use 5 million images for training, and reserve the remaining images for the test set. We release this dataset publicly (URL omitted for anonymity during review.)

Random samples from CIFAR-5m are shown in Figure 18. For comparison, we show random samples from CIFAR-10 in Figure 17.

## D.2 IMAGENET: DOGBIRD

The ImageNet-DogBird task is constructed by collapsing classes from ImageNet. The task is to distinguish dogs from birds. The dogs are all ImageNet classes under the WordNet synset "hunting dog" (including 63 ImageNet classes) and birds are all classes under synset "bird" (including 59 ImageNet classes). The listing of the ImageNet wnids included in each class is provided below.

This is a relatively easy task compared to full ImageNet: A ResNet-18 trained on 10K samples from ImageNet-DogBird, with standard ImageNet data augmentation, can achieve test accuracy 95%.

**Hunting Dogs (n2087122):** `n02091831, n02097047, n02088364, n02094433, n02097658, n02089078, n02090622, n02095314, n02102040, n02097130, n02096051, n02098105, n02095889, n02100236, n02099267, n02102318, n02097474, n02090721, n02102973, n02095570, n02091635, n02099429, n02090379, n02094258, n02100583, n02092002, n02093428, n02098413, n02097298, n02093754, n02096177, n02091032, n02096437, n02087394, n02092339, n02099712, n02088632, n02093647, n02098286, n02096585, n02093991, n02100877, n02094114, n02101388, n02089973, n02088094, n02088466, n02093859, n02088238, n02102480, n02101556, n02089867, n02099601, n02102177, n02101006, n02091134, n02100735, n02099849, n02093256, n02097209, n02091467, n02091244, n02096294`

**Birds (n1503061):** `n01855672, n01560419, n02009229, n01614925, n01530575, n01798484, n02007558, n01860187, n01820546, n01817953, n01833805, n02058221, n01806567, n01558993, n02056570, n01797886, n02018207, n01828970, n02017213, n02006656, n01608432, n01818515, n02018795, n01622779, n01582220, n02013706, n01534433, n02027492, n02012849, n02051845, n01824575, n01616318, n02002556, n01819313, n01806143, n02033041, n01601694, n01843383, n02025239, n02002724, n01843065, n01514859, n01796340, n01855032, n01580077, n01807496, n01847000, n01532829, n01537544, n01531178, n02037110, n01514668, n02028035, n01795545, n01592084, n01518878, n01829413, n02009912, n02011460`

Figure 16: **CIFAR-5m Samples.** Random samples from each class (by row).

Figure 17: **CIFAR-10 Samples.** Random samples from each class (by row).

Figure 18: **ImageNet-DogBird Samples.** Random samples from each class. Annotated by their original ImageNet class for reference.

## E   D-CONV, D-FC ARCHITECTURE DETAILS

For convenience, we provide PyTorch specifications for the D-CONV and D-FC architectures from Neyshabur (2020) which we use in this work.

**D-CONV.** This model has 6563498 parameters.

```
Network(
  (features): Sequential(
    (0): Conv2d(3, 32, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1)
, bias=False)
    (1): BatchNorm2d(32, eps=1e-05, momentum=0.1, affine=True)
    (2): ReLU(inplace=True)
    (3): Conv2d(32, 64, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1)
, bias=False)
    (4): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True)
    (5): ReLU(inplace=True)
    (6): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1)
, bias=False)
    (7): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True)
    (8): ReLU(inplace=True)
    (9): Conv2d(64, 128, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1)
, bias=False)
    (10): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True)
    (11): ReLU(inplace=True)
    (12): Conv2d(128, 128, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1)
, bias=False)
    (13): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True)
    (14): ReLU(inplace=True)
    (15): Conv2d(128, 256, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1)
, bias=False)
    (16): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True)
    (17): ReLU(inplace=True)
    (18): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1)
, bias=False)
    (19): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True)
    (20): ReLU(inplace=True)
    (21): Conv2d(256, 512, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1)
, bias=False)
    (22): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True)
    (23): ReLU(inplace=True)
  )
  (classifier): Sequential(
    (0): Linear(in_features=2048, out_features=2048
, bias=False)
    (1): BatchNorm1d(2048, eps=1e-05, momentum=0.1, affine=True)
    (2): ReLU(inplace=True)
    (3): Dropout(p=0.5, inplace=False)
    (4): Linear(in_features=2048, out_features=10, bias=True)
  )
)
```

**D-FC.** This model has 1170419722 parameters.

```
Network(
  (features): Sequential(
    (0): Linear(in_features=3072, out_features=32768, bias=False)
    (1): BatchNorm1d(32768, eps=1e-05, momentum=0.1, affine=True
    (2): ReLU(inplace=True)
    (3): Linear(in_features=32768, out_features=16384, bias=False)
```

```
      (4): BatchNorm1d(16384, eps=1e-05, momentum=0.1, affine=True)
      (5): ReLU(inplace=True)
      (6): Linear(in_features=16384, out_features=16384, bias=False)
      (7): BatchNorm1d(16384, eps=1e-05, momentum=0.1, affine=True)
      (8): ReLU(inplace=True)
      (9): Linear(in_features=16384, out_features=8192, bias=False)
      (10): BatchNorm1d(8192, eps=1e-05, momentum=0.1, affine=True)
      (11): ReLU(inplace=True)
      (12): Linear(in_features=8192, out_features=8192, bias=False)
      (13): BatchNorm1d(8192, eps=1e-05, momentum=0.1, affine=True)
      (14): ReLU(inplace=True)
      (15): Linear(in_features=8192, out_features=4096, bias=False)
      (16): BatchNorm1d(4096, eps=1e-05, momentum=0.1, affine=True)
      (17): ReLU(inplace=True)
      (18): Linear(in_features=4096, out_features=4096, bias=False)
      (19): BatchNorm1d(4096, eps=1e-05, momentum=0.1, affine=True)
      (20): ReLU(inplace=True)
      (21): Linear(in_features=4096, out_features=2048, bias=False)
      (22): BatchNorm1d(2048, eps=1e-05, momentum=0.1, affine=True)
      (23): ReLU(inplace=True)
    )
    (classifier): Sequential(
      (0): Linear(in_features=2048, out_features=2048, bias=False)
      (1): BatchNorm1d(2048, eps=1e-05, momentum=0.1, affine=True)
      (2): ReLU(inplace=True)
      (3): Dropout(p=0.5, inplace=False)
      (4): Linear(in_features=2048, out_features=10, bias=True)
    )
)
```