Optimistic Posterior Sampling for Reinforcement Learning with Few Samples and Tight Guarantees

Abstract

We consider reinforcement learning in an environment modeled by an episodic, finite, stage-dependent Markov decision process of horizon H with S states, and A actions. The performance of an agent is measured by the regret after interacting with the environment for T episodes. We propose an optimistic posterior sampling algorithm for reinforcement learning (OPSRL), a simple variant of posterior sampling that only needs a number of posterior samples logarithmic in H, S, A, and T per state-action pair. For OPSRL we guarantee a high-probability regret bound of order at most $\widetilde{\mathcal{O}}(\sqrt{H^3SAT})$ ignoring $\operatorname{poly}\log(HSAT)$ terms. The key novel technical ingredient is a new sharp anti-concentration inequality for linear forms which may be of independent interest. Specifically, we extend the normal approximation-based lower bound for Beta distributions by Alfers and Dinges [1984] to Dirichlet distributions. Our bound matches the lower bound of order $\Omega(\sqrt{H^3SAT})$, thereby answering the open problems raised by Agrawal and Jia [2017b] for the episodic setting.

1 Introduction

In reinforcement learning an agent interacts with an environment, whose underlying mechanism is unknown, by sequentially taking actions, receiving rewards, and transitioning to the next state [Sutton and Barto, 1998]. With the goal of maximizing the expected sum of the collected rewards, the agent must carefully balance between *exploring* in order to gather more information about the environment and *exploiting* the current knowledge to collect the rewards. In this paper, we are interested in solving this exploration-exploitation dilemma by injecting noise into the agent's decision-making process.

We model the environment as an episodic, finite, unknown Markov decision process (MDP) of horizon H, with S states and A actions. In particular, we consider the *stage-dependent* setting where the rewards and the transition probability distributions can vary within an episode. After T episodes the performance of an agent is measured through *regret*: the difference between the cumulative reward the agent could have obtained by acting optimally and what the agent really obtained. Jin et al. [2018] and Domingues et al. [2020] provide a problem-independent lower bound of order $\Omega(\sqrt{H^3SAT})$ for this setting; see also Azar et al. [2017] for a lower bound when the transitions are stage-independent.

One generic solution to the exploration-exploitation dilemma is the *principle of optimism in the face of uncertainty*. A simple way to implement this principle consists in building *upper confidence bound (UCB)* on the optimal Q-value function through the addition of *bonuses* to the rewards. This is done by either model-based algorithms [Azar et al., 2017, Dann et al., 2017, Zanette and Brunskill, 2019] or model-free algorithms [Jin et al., 2018, Zhang et al., 2020, Menard et al., 2021]; see also [Jaksch et al., 2010, Fruit et al., 2018, Talebi and Maillard, 2018] for the non-episodic setting. Notably, among others, both the upper confidence bound value iteration (UCBVI) of Azar et al. [2017] and the

UCB-Advantage algorithm of Zhang et al. [2020] enjoys a problem-independent regret bound[1] of order[2] $\widetilde{\mathcal{O}}(\sqrt{H^3 SAT})$ that matches the aforementioned lower bound for T large enough and up to terms poly-logarithmic in H, S, A, T.

Another way is to implement the optimism by *injecting noise*. A typical example is the random least-square value iteration (RLSVI, Osband et al., 2016b, Russo, 2019) algorithm which at each episode computes new Q-values by noisy value iteration from an estimated model and then acts greedily with respect to them. In particular, a Gaussian noise is added to the reward before applying the Bellman operator to encourage exploration. Indeed, when the variance of the noise is carefully chosen, it allows to obtain optimistic Q-values with at least a fixed probability. Russo [2019] first proved a regret bound of order $\widetilde{\mathcal{O}}(H^2 S^{3/2}\sqrt{AT})$ for RLSVI. Later, Xiong et al. [2021] obtained an optimal regret bound of order $\widetilde{\mathcal{O}}(\sqrt{H^3 SAT})$ for a modified version of RLSVI where the variance of the injected Gaussian noise is scaled by a term similar to the Bernstein bonuses used in UCBVI. Recently, Pacchiano et al. [2021] analyzed a version of RLSVI where the Gaussian noise is replaced by a bootstrap sample of *the past rewards* and added pseudo rewards in the same fashion as Kveton et al. [2019]. The algorithm proposed by Pacchiano et al. [2021], comes with a regret bound of order $\widetilde{\mathcal{O}}(H^2 S\sqrt{AT})$.

By generalizing the Thompson sampling algorithm [Thompson, 1933] originally given for stochastic multi-armed bandit, Osband et al. [2013] propose a posterior sampling for reinforcement learning (PSRL). PSRL algorithm also relies on noise to drive exploration. The general idea behind it is to maintain a *surrogate Bayesian model* on the MDP, for instance, a Dirichlet posterior on the transition probability distribution if the rewards are known. At each episode, a new MDP is sampled (i.e., a transition probability for each state-action pair) according to the posterior distribution of the Bayesian model. Then, the agent acts optimally in this sampled MDP. As the posterior is not well concentrated in the unexplored region of the MDP, the probability that the Q-value of the sampled MDP is optimistic in this region is high. Therefore, the agent will be incentivized to explore. Although the original Thompson sampling is well-studied in the frequentist setting [Agrawal and Goyal, 2012, Kaufmann et al., 2012, Agrawal and Goyal, 2013] and the Bayesian setting [Thompson, 1933, Russo and Roy, 2016, Russo and Van Roy, 2014], most of the analysis of PSRL only provide Bayesian regret bounds [Osband et al., 2013, Abbasi-Yadkori and Szepesvári, 2015, Osband et al., 2016b, Ouyang et al., 2017, Osband and Van Roy, 2017], i.e., when the true MDP is effectively sampled according to the prior of the surrogate Bayesian model. Despite this lack of guarantees, PSRL demonstrates competitive empirical performance in comparison to bonus-based algorithms [Osband et al., 2013, Osband and Van Roy, 2017]. Additionally, the exploration mechanism used by PSRL (and RLSVI) was successfully extended outside the tabular setting and used in deep RL environments [Osband et al., 2016a, 2018, 2019].

One exception to the above is the work of Agrawal and Jia [2017b] that studies PSRL from a *frequentist* perspective in the infinite-horizon, non-episodic average reward setting. In particular, they provide a regret bound[3] of order[4] $\widetilde{\mathcal{O}}(H^2 S\sqrt{AT})$ for an optimistic version of PSRL that we call SOS-OPS-RL since it switches between two types of sampling of the transitions: (1) *simple optimistic sampling*, when the number of observed transitions at a given state-action pair is too small. In this case, the sampled transition is a random mixture between the uniform distribution over the states and an empirical estimate of the true transition biased by some bonus-like terms; or if the number of observed transitions at a given state-action pair is large enough (2) *optimistic posterior sampling*, where $\widetilde{\mathcal{O}}(S)$ samples from an inflated Dirichlet posterior are used instead of one sample used in PSRL. Then, from these $\widetilde{\mathcal{O}}(S)$ sampled transition probabilities we select the most optimistic one i.e., the one leading to the largest optimal Q-value.

---

[1]We translate all the bounds to the *stage-dependent* setting by multiplying the regret bounds in the stage-independent setting by $\sqrt{H}$, see Jin et al. [2018].

[2]In the $\widetilde{\mathcal{O}}(\cdot)$ notation we ignore terms poly-log in H, S, A, T.

[3]As acknowledged by the authors, there was a mistake in the initial submission of their work where the previously announced bound was claimed to be $\sqrt{S}$ better, see Agrawal and Jia [2017a], Qian et al. [2020]

[4]We translate all the bounds from the infinite-horizon, non-episodic average reward setting to our setting by identifying the diameter with the horizon H and multiplying the bound by $\sqrt{H}$ because of our stage-dependent transitions assumption.

The key idea underpinning the analysis of `SOS-OPS-RL`, and `PSRL`-like algorithms in general, is to control the deviations of the Dirichlet posterior on the transition probability distributions. In particular, we need to show that the *posterior spreads enough to ensure optimism.* To this end, Agrawal and Jia [2017b] derive an anti-concentration bound for any fixed projection of a Dirichlet random vector. The latter result in turn relies upon an equivalent representation of a Dirichlet vector in terms of independent Beta random variables and an anti-concentration bound for the corresponding Beta distribution. However, this anti-concentration inequality is not uniformly tight, in particular its polynomial dependence on the number of states S is suboptimal.

Agrawal and Jia [2017b] conclude with two open problems. The first question is whether one can reduce the number of posterior samples required per state-action pair from $\widetilde{\mathcal{O}}(S)$ to constant or logarithmic in S. The second asks if it is possible to obtain a near-optimal regret bound and in particular to improve the dependence on S. In this paper, we *answer both of them in the affirmative* in the episodic setting. Indeed, we propose optimistic posterior sampling algorithm for reinforcement learning (`OPSRL`) that only requires $\widetilde{\mathcal{O}}(1)$ samples from an inflated posterior while enjoying a near-optimal problem independent regret bound of order $\widetilde{\mathcal{O}}(\sqrt{H^3SAT})$. `OPSRL` is a simple optimistic variant of `PSRL` which, in particular, does not rely at all on "simple" (bonus-based) optimistic sampling.

The essential ingredient for `OPSRL`'s analysis is our *novel anti-concentration bound for the projections of a Dirichlet random vector* (Theorem 3.3). We base it on a tight Gaussian approximation for linear forms of a Dirichlet random vector. This latter approximation can be seen as a substantial generalization to Dirichlet distributions of the result obtained by Alfers and Dinges [1984] for the case of Beta distributions. We obtain this approximation through a refined non-asymptotic analysis of the integral representation for the density of a linear form of a Dirichlet random vector, which was first derived[5] by Tiapkin et al. [2022]. We believe that the new anti-concentration inequality presented in this work could be of independent interest, e.g., to tighten or simplify analysis of non-parametric Thompson sampling like algorithms [Riou and Honda, 2020, Baudry et al., 2021a,b] for stochastic multi-armed bandits.

- We propose the `OPSRL` algorithm for tabular, stage-dependent, episodic RL. It is a simple optimistic variant of the `PSRL` algorithm that only needs $\widetilde{\mathcal{O}}(1)$ posterior samples per state-action pair. For `OPSRL`, we provide a regret bound of order $\widetilde{\mathcal{O}}(\sqrt{H^3SAT})$ matching the problem independent lower bound up to poly-$\log$ terms. In particular we answer positively to two open questions by Agrawal and Jia [2017b] in the episodic setting.

- We derive a new anti-concentration inequality for a linear form of a Dirichlet random vector (Theorem 3.3) which is essential for the analysis of `OPSRL`. This result is a generalization to the Dirichlet case of the one provided by Alfers and Dinges [1984] for Beta distributions.

2   Setting

We consider a finite episodic MDP $\big(\mathcal{S}, \mathcal{A}, H, \{p_h\}_{h\in[H]}, \{r_h\}_{h\in[H]}\big)$, where $\mathcal{S}$ is the set of states, $\mathcal{A}$ is the set of actions, H is the number of steps in one episode, $p_h(s'|s,a)$ is the probability transition from state s to state s' by taking the action a at step h, and $r_h(s,a) \in [0,1]$ is the bounded deterministic[6] reward received after taking the action a in state s at step h. Note that we consider the general case of rewards and transition functions that are possibly non-stationary, i.e., that are allowed to depend on the decision step h in the episode. We denote by S and A the number of states and actions, respectively.

Policy & value functions   A *deterministic* policy π is a collection of functions $\pi_h : \mathcal{S} \rightarrow \mathcal{A}$ for all $h \in [H]$, where every π_h maps each state to a *single* action. The value functions of π, denoted by V_h^π, as well as the optimal value functions, denoted by $V_h^\star$ are given by the Bellman and the optimal

---

[5]Note that the anti-concentration inequality proved by Tiapkin et al. [2022] based on the same integral representation is insufficient for our needs, see Remark 3.4 for a discussion.

[6]We study deterministic rewards to simplify the proofs but our result extend to bounded random rewards as well.

128 Bellman equations,

$$Q_h^\pi(s,a) = r_h(s,a) + p_h V_{h+1}^\pi(s,a) \qquad\qquad V_h^\pi(s) = \pi_h Q_h^\pi(s)$$
$$Q_h^\star(s,a) = r_h(s,a) + p_h V_{h+1}^\star(s,a) \qquad\qquad V_h^\star(s) = \max_a Q_h^\star(s,a),$$

129 where by definition, $V_{H+1}^\star \triangleq V_{H+1}^\pi \triangleq 0$. Furthermore, $p_h f(s,a) \triangleq \mathbb{E}_{s' \sim p_h(\cdot|s,a)}[f(s')]$ denotes the
130 expectation operator with respect to the transition probabilities p_h and $\pi_h g(s) \triangleq g(s, \pi_h(s))$ denotes
131 the composition with the policy π at step h.

132 **Learning problem**   The agent, to which the transitions are *unknown* (the rewards are assumed
133 to be known for simplicity), interacts with the environment during T episodes of length H, with
134 a *fixed* initial state s_1.[7] Before each episode t the agent selects a policy π^t based only on the past
135 observed transitions up to episode $t - 1$. At each step $h \in [H]$ in episode t, the agent observes a state
136 $s_h^t \in \mathcal{S}$, takes an action $\pi_h^t(s_h^t) = a_h^t \in \mathcal{A}$ and makes a transition to a new state s_{h+1}^t according to
137 the probability distribution $p_h(s_h^t, a_h^t)$ and receives a deterministic reward $r_h(s_h^t, a_h^t)$.

138 **Regret**   The quality of an agent is measured through its regret, that is the difference between what it
139 could obtain (in expectation) by acting optimally and what it really gets,

$$\mathfrak{R}^T \triangleq \sum_{t=1}^T V_1^\star(s_1) - V_1^{\pi^t}(s_1).$$

140 **Counts**   The number of times the state action-pair (s,a) was visited in step h in the first t
141 episodes is denoted as $n_h^t(s,a) \triangleq \sum_{i=1}^t \mathbb{1}\{(s_h^i, a_h^i) = (s,a)\}$. Next, we define $n_h^t(s'|s,a) \triangleq$
142 $\sum_{i=1}^t \mathbb{1}\{(s_h^i, a_h^i, s_{h+1}^i) = (s,a,s')\}$ the number of transitions from s to s' at step h.

143 **Improper Dirichlet distribution**   For $m \in \mathbb{N}^*$, the probability simplex of dimension m is denoted
144 by Δ_m. For $\alpha \in (\mathbb{R}_{++})^{m+1}$, we denote by $\mathcal{D}\mathrm{ir}(\alpha)$ the Dirichlet distribution on Δ_m with parameter α.
145 We also extend this distribution to improper parameter $\alpha \in (\mathbb{R}_+)^{m+1}$ such that $\sum_{i=0}^m \alpha_i > 0$ by in-
146 jecting $\mathcal{D}\mathrm{ir}((\alpha_i)_{i:\alpha_i>0})$ into Δ_m. Precisely, we say that $p \sim \mathcal{D}\mathrm{ir}(\alpha)$ if $(p_i)_{i:\alpha_i>0} \sim \mathcal{D}\mathrm{ir}((\alpha_i)_{i:\alpha_i>0})$
147 and all other coordinates are zero.

148 **Additional notation**   For $N \in \mathbb{N}_{++}$, we define the set $[N] \triangleq \{1, \dots, N\}$. We denote the
149 uniform distribution over this set by $\mathcal{U}\mathrm{nif}[N]$. The vector of dimension N with all entries one
150 is $\mathbf{1}^N \triangleq (1, \dots, 1)^\intercal$. The empirical probability distribution $\widehat{p}_h^t(s,a)$ is defined as $\widehat{p}_h^t(s'|s,a) =$
151 $n_h^t(s'|s,a)/n_h^t(s,a)$ if $n_h^t(s,a) > 0$ and $\widehat{p}_h^0(s'|s,a) = 1/S$ otherwise. Appendix A references all
152 the notation used.

3   Algorithm

154 In this section we describe the OPSRL algorithm. In spirit, OPSRL proceeds similarly as PSRL except
155 that it uses several posterior samples instead and acts optimistically with respect to them, explaining
156 the name *Optimistic Posterior Sampling for Reinforcement Learning* (OPSRL).

157 **Optimistic pseudo-state**   In order to define the prior used by OPSRL, we extend the state space $\mathcal{S}$ by
158 an absorbing pseudo-state s_0 with reward $r_h(s_0, a) \triangleq r_0 > 1$ for all h, a and transition probability
159 distribution $p_h(s'|s_0, a) \triangleq \mathbb{1}\{s' = s_0\}$. A similar pseudo-state was already introduce in previous
160 works, see for example Brafman and Tennenholtz [2002], Szita and Lőrincz [2008]. We denote by
161 $\mathcal{S}' = \mathcal{S} \cup \{s_0\}$ the augmented states space and by $\Delta_{\mathcal{S}'}$ the set of probability distributions over $\mathcal{S}'$.

162 **Pseudo-counts**   We define the pseudo-counts, $\overline{n}_h^t(s,a) \triangleq n_h^t(s,a) + n_0$, as the counts shifted by an
163 initial value n_0. This shift corresponds to prior transitions to the pseudo-state, that is $\overline{n}_h^t(s'|s,a) \triangleq$
164 $n_h^t(s'|s,a) + n_0 \mathbb{1}\{s' = s_0\}$. Similar to the empirical transitions, we define a pseudo-empirical
165 transition probability distribution as $\overline{p}_h^t(s,a) = \overline{n}_h^t(s'|s,a)/\overline{n}_h^t(s,a)$.

---

[7]As explained by Fiechter [1994] and Kaufmann et al. [2020], if the first state is sampled randomly as
$s_1 \sim p$, we can simply add an artificial first state $s_{1'}$ such that for any action a, the transition probability is
defined as the distribution $p_{1'}(s_{1'}, a) \triangleq p$.

166 **Inflated Bayesian model**   Like PSRL, we define a Bayesian model on the transition probability
167 distributions, except that the prior/posterior is inflated. The practice of inflating the posterior is
168 common in the analysis of Thompson sampling like algorithm, see Agrawal and Jia [2017b], Abeille
169 and Lazaric [2017]. Precisely, the inflated prior is a Dirichlet distribution $\mathcal{D}\mathrm{ir}\Big(\big(\overline{n}_h^0(s'|s,a)/\kappa\big)_{s'\in\mathcal{S}'}\Big)$
170 parameterized by the initial pseudo-counts, and some constant $\kappa > 0$ controlling the inflation. Thus
171 the prior is a Dirac distribution at a deterministic transition leading to the artificial state s_0. Then
172 the inflated posterior is also a Dirichlet distribution $\mathcal{D}\mathrm{ir}\Big(\big(\overline{n}_h^t(s'|s,a)/\kappa\big)_{s'\in\mathcal{S}'}\Big)$. Note that the prior
173 is a proper prior (i.e., a valid probability distribution), but it will be updated in an improper way,
174 i.e., probability transitions with no mass under the prior could get mass in the posterior, as they get
175 positive counts.

176 **Optimistic posterior sampling**   After episode t, for each state-action pair (s, a) and step
177 $h \in [H]$ we sample J independent transition probability distributions $\widetilde{p}_h^{t,j}(s, a) \sim$
178 $\mathcal{D}\mathrm{ir}\Big(\big(\overline{n}_h^t(s'|s,a)/\kappa\big)_{s'\in\mathcal{S}'}\Big)$ from the inflated posterior. Then, the Q-values are obtained by op-
179 timistic backward induction with these transitions. Precisely the value after the last step is zero
180 $\overline{V}_{H+1}^t(s) \triangleq 0$ and the optimal Bellman equations become

$$
\begin{aligned}
\overline{Q}_h^t(s, a) &\triangleq r_h(s, a) + \max_{j \in [J]} \widetilde{p}_h^{t,j} \overline{V}_{h+1}^t(s, a), \\
\overline{V}_h^t(s) &\triangleq \max_{a \in \mathcal{A}} \overline{Q}_h^t(s, a).
\end{aligned}
\tag{1}
$$

181 The next policy is greedy with the Q-values $\pi_h^{t+1}(s) \in \arg\max_{a \in \mathcal{A}} \overline{Q}_h^t(s, a)$. The complete proce-
182 dure of OPSRL is described in Algorithm 1 for a general family of distributions parameterized by the
183 pseudo-counts over the transitions instead of the inflated Dirichlet prior/posterior.

Algorithm 1 OPSRL

1: **Input:** Family of probability distributions $\rho : \mathbb{N}_+^{S+1} \to \Delta_{\mathcal{S}'}$ over transitions, initial pseudo-
   count $\overline{n}_h^0$, number of posterior samples J.
2: **for** $t \in [T]$ **do**
3:     For all $(s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H]$, sample J independent transitions

$$
\widetilde{p}_h^{t-1,j}(s, a) \sim \rho\big(\overline{n}_h^{t-1}(s'|s,a)_{s'\in\mathcal{S}'}\big), \quad j \in [J].
$$

4:     Optimistic backward induction: set $\overline{V}_{H+1}^{t-1}(s) = 0$ and recursively for $h \in [H]$, compute

$$
\begin{aligned}
\overline{Q}_h^{t-1}(s, a) &= r_h(s, a) + \max_{j \in [J]}\big\{\widetilde{p}_h^{t-1,j} \overline{V}_{h+1}^{t-1}(s, a)\big\}, \\
\overline{V}_h^{t-1}(s) &= \max_{a \in \mathcal{A}} \overline{Q}_h^{t-1}(s, a), \\
\pi_h^t(s) &\in \arg\max_{a \in \mathcal{A}} \overline{Q}_h^{t-1}(s, a).
\end{aligned}
$$

5:     **for** $h \in [H]$ **do**
6:         Play $a_h^t = \pi_h^t(s_h^t)$.
7:         Observe $s_{h+1}^t \sim p_h(s_h^t, a_h^t)$.
8:         Increment the pseudo-count $\overline{n}_h^t(s_{h+1}^t|s_h^t, a_h^t)$.
9:     **end for**
10: **end for**

---

184 ### 3.1   Analysis

185 We fix $\delta \in (0, 1)$ and the number of samples

$$
J \triangleq \lceil c_J \cdot \log(2SAHT/\delta) \rceil,
$$

where $c_J = 1/\log(2/(1+\Phi(1)))$ and $\Phi(\cdot)$ is the cumulative distribution function (CDF) of a normal distribution. Note that J has a logarithmic dependence on S, A, H, T, and $1/\delta$.

We now state the regret bound of `OPSRL` with a full proof in Appendix B. and a sketch in Section 3.2.

Theorem 3.1. *Consider a parameter $\delta \in (0,1)$. Let $\kappa \triangleq 2(\log(12SAH/\delta) + 3\log(e\pi(2T + 1)))$, $n_0 \triangleq \lceil \kappa(c_0 + \log_{17/16}(T)) \rceil$, $r_0 \triangleq 2$, where c_0 is an absolute constant defined in (4); see Appendix B.2. Then for* `OPSRL`*, with probability at least $1 - \delta$,*

$$\mathfrak{R}^T = \mathcal{O}\Big(\sqrt{H^3SATL^3} + H^3S^2AL^3\Big),$$

where $L \triangleq \mathcal{O}(\log(HSAT/\delta))$.

Computational complexity   `OPSRL` is a model-based algorithm, and thus gets the $\mathcal{O}(HS^2A)$ space complexity as PSRL. Since we need $\widetilde{\mathcal{O}}(1)$ posterior samples per state-action pair the time complexity of `OPSRL` is of order $\widetilde{\mathcal{O}}(HS^2A)$ per episode, the same as PSRL up to poly-logarithmic terms. Building on the idea of Efroni et al. [2019], in Appendix F we propose the `Lazy-OPSRL` algorithm a more time-efficient version of `OPSRL`. Instead of recomputing the Q-value by backward induction before each episode, `Lazy-OPSRL` only performs one step of optimistic incremental planning at the visited states. It enjoys a regret bound of the same order $\widetilde{\mathcal{O}}(\sqrt{H^3SAT})$ as `OPSRL` but with an improved time-complexity per episode of $\mathcal{O}(HSA)$, see Theorem F.1 in Appendix F.

Comparison with `SOS-OPS-RL` **and** `PSRL`   One structural difference between `OPSRL` and `SOS-OPS-RL` of Agrawal and Jia [2017a] is that `OPSRL` only relies on optimistic posterior sampling while `SOS-OPS-RL` also uses simple optimistic sampling: a mixture of the uniform distribution over the states and an empirical estimate of the true transition kernel biased by some bonus-like terms. In particular, `OPSRL` does not use bonus-like quantities which could lead to poor empirical performance [Osband and Van Roy, 2017]. Another important issue is the number of posterior samples. `SOS-OPS-RL` needs $\widetilde{\mathcal{O}}(S)$ posterior samples in order to obtain a regret bound of order $\widetilde{\mathcal{O}}(H^2S\sqrt{AT})$ whereas `OPSRL` needs *only* $\widetilde{\mathcal{O}}(1)$ samples *and* obtains a better regret bound. Note that if we choose the number of posterior samples as $J = 1$ in `OPSRL` we recover PSRL up to two technical differences: First, the posterior is inflated in order to increase its variance. This technical trick was already used by Agrawal and Jia [2017a] and allows to guarantee optimism with a small number of posterior samples, see Section 3.2. Second, `OPSRL` uses a particular prior which is a Dirac distribution at a deterministic transition towards an optimistic pseudo-state. This prior is needed to control the deviations of the (inflated) posterior, see Theorem D.2.

Comparison with `RLSVI`   Both `OPSRL` and `RLSVI` build on the same mechanism for exploration. `RLSVI` just adds an Gaussian noise to the Q-values whereas `OPSRL` injects the noise naturally via a random transition sampled from a Dirichlet distribution. As controlling the deviation of the Q-value obtained with additive Gaussian noise is not difficult, the analysis of `RLSVI` is relatively straightforward [Russo, 2019]. On the contrary the analysis of `OPSRL` is much more involved, see Section 3.2. However, the benefit of optimistic posterior sampling in `OPSRL` is that it adapts *automatically* to the variance of the estimates of the transitions which is central for a regret bound with an optimal dependence on the horizon H [Azar et al., 2017]. Adapting to the variance with `RLSVI` is much more involved and artificial, see Xiong et al. [2021]. This is probably one reason why `RLSVI` performs empirically worse than PSRL [Osband et al., 2016a].

3.2   Proof sketch

The proof of Theorem 3.1 consists of three important steps. The first step is devoted to the approximation for tails of weighted sums of Dirichlet distribution and embodies the main technical contribution of the paper.

Step 1. Exponential and Gaussian approximation for Dirichlet distribution   The first result generalizes Riou and Honda [2020] to Dirichlet distributions with real parameters. Let us first recall the definition of the minimum Kullback-Leibler divergence for $p \in \Delta_m$ where $m \in \mathbb{N}^+$, a function $f : \{0, \ldots, m\} \to [0, b]$ for some $b \in \mathbb{R}^+$ and $u \in \mathbb{R}$,

$$\mathcal{K}_{\text{inf}}(p, u, f) \triangleq \inf\{\text{KL}(p, q) : q \in \Delta_m, qf \geq u\},$$

where we recall that $pf \triangleq \mathbb{E}_{X \sim p} f(X)$. This quantity appears already in the analysis of non-parametric bounded multi-arm stochastic bandits, see Honda and Takemura [2010], Cappé et al. [2013]. As the Kullback-Leibler divergence, the minimum Kullback-Leibler divergence admits a variational formula by Lemma 18 of Garivier et al. [2018] up to rescaling for any $u \in (0, b)$,

$$\mathcal{K}_{\mathrm{inf}}(p, u, f) = \max_{\lambda \in [0, 1/(b-u)]} \mathbb{E}_{X \sim p}[\log(1 - \lambda(f(X) - u))]. \tag{2}$$

Theorem 3.2 (Exponential upper bound, see Theorem D.1). *For any $\alpha = (\alpha_0, \alpha_1, \dots, \alpha_m) \in \mathbb{R}_{++}^{m+1}$ define $\overline{p} \in \Delta_m$ such that $\overline{p}(\ell) = \alpha_\ell / \overline{\alpha}, \ell = 0, \dots, m$, where $\overline{\alpha} = \sum_{j=0}^{m} \alpha_j$. Then for any $f \colon \{0, \dots, m\} \to [0, b]$ and $0 < \mu < b$, we have*

$$\mathbb{P}_{w \sim \mathcal{D}\mathrm{ir}(\alpha)}[wf \geq \mu] \leq \exp(-\overline{\alpha} \, \mathcal{K}_{\mathit{inf}}(\overline{p}, \mu, f)).$$

The second result is devoted to a tight Gaussian lower bound for the distribution of a linear function of Dirichlet random vector. Here we follow the ideas of Alfers and Dinges [1984] and use the exact expression for the density of a linear form of Dirichlet random vector derived by Tiapkin et al. [2022].

Theorem 3.3 (Gaussian lower bound, see Theorem D.2). *For any $\alpha = (\alpha_0 + 1, \alpha_1, \dots, \alpha_m) \in \mathbb{R}_{++}^{m+1}$, define $\overline{p} \in \Delta_m$ such that $\overline{p}(\ell) = \alpha_\ell / \overline{\alpha}, \ell = 0, \dots, m$, where $\overline{\alpha} = \sum_{j=0}^{m} \alpha_j$. Fix $\varepsilon \in (0, 1)$ and assume that $\alpha_0 \geq c(\varepsilon) + \log_{17/16}(\overline{\alpha})$ for $c(\varepsilon)$ defined in (10), Appendix D, and $\overline{\alpha} \geq 2\alpha_0$. Then for any $f \colon \{0, \dots, m\} \to [0, b_0]$ such that $f(0) = b_0$, $f(j) \leq b < b_0/2, j \in \{1, \dots, m\}$ and $\mu \in (\overline{p}f, b_0)$,*

$$\mathbb{P}_{w \sim \mathcal{D}\mathrm{ir}(\alpha)}[wf \geq \mu] \geq (1 - \varepsilon) \mathbb{P}_{g \sim \mathcal{N}(0,1)} \left[g \geq \sqrt{2\overline{\alpha} \, \mathcal{K}_{\mathit{inf}}(\overline{p}, \mu, f)} \right].$$

We emphasize that increasing the parameter α_0 corresponding to the largest value of f by 1 is crucial. The same technique was used by Alfers and Dinges [1984] to derive a lower bound on the tails of the Beta distribution.

Remark 3.4. We stress that the anti-concentration inequality of Tiapkin et al. [2022, Theorem D.2] is not sufficient for our purposes; their additional factor $\overline{\alpha}^{-3/2}$ in front of the exponent makes it unusable for the analysis of OPSRL. Indeed, this inequality would imply $\widetilde{\mathcal{O}}(T^{3/2})$ samples from the inflated posterior in order to get optimism with high-probability, whereas with our refined bound (Theorem 3.3) we only need $\widetilde{\mathcal{O}}(1)$ posterior samples.

Proof sketch of Theorem 3.3. We start from the integral representation for the density by Tiapkin et al. [2022, Proposition D.3]. Define $Z \triangleq wf$ for $w \sim \mathcal{D}\mathrm{ir}(\alpha_0 + 1, \alpha_1, \dots, \alpha_m)$, then for any $u \in (0, b_0)$,

$$p_Z(u) = \frac{\overline{\alpha}}{2\pi} \int_{\mathbb{R}} (1 + \mathrm{i}(b_0 - u)s)^{-1} \prod_{j=0}^{m} (1 + \mathrm{i}(f(j) - u)s)^{-\alpha_j} \, \mathrm{d}s.$$

One additional term $(1 + \mathrm{i}(b_0 - u)s)^{-1}$ comes from increasing the parameter α_0 by 1 corresponding to the value $f(0) = b_0$.

In the same spirit as it was done by Tiapkin et al. [2022], we apply the method of saddle point (see Fedoryuk, 1977, Olver, 1997) to the complex integral above. Informally, for $\alpha_0, \overline{\alpha}, b_0$ large enough the following approximation holds

$$p_Z(u) \approx \sqrt{\frac{\overline{\alpha}}{2\pi\sigma^2(1 - \lambda^\star(b_0 - u))^2}} \exp(-\overline{\alpha} \, \mathcal{K}_{\mathrm{inf}}(\overline{p}, u, f)),$$

where $\lambda^\star$ is the unique solution to the problem (2) and $\sigma^2 = \mathbb{E}_{X \sim \overline{p}} \left[\left(\frac{f(X) - u}{1 - \lambda^\star(f(X) - u)} \right)^2 \right]$. The formal statement can be found in Lemma D.5 of Appendix D.

Next we perform a change of variables $t^2/2 = \mathcal{K}_{\mathrm{inf}}(\overline{p}, u, f)$ in the above expression to get

$$\mathbb{P}_{w \sim \mathcal{D}\mathrm{ir}(\alpha_0 + 1, \alpha_1, \dots, \alpha_m)}[wf \geq \mu] \approx \int_{\mu}^{b_0} \sqrt{\frac{\overline{\alpha}}{2\pi\sigma^2(1 - \lambda^\star(b_0 - u))^2}} \exp(-\overline{\alpha} \, \mathcal{K}_{\mathrm{inf}}(\overline{p}, u, f)) \, \mathrm{d}u$$

$$\approx \int_{\sqrt{2\mathcal{K}_{\mathrm{inf}}(\overline{p}, \mu, f)}}^{\infty} D(u(t)) \phi(t | 0, \overline{\alpha}) \, \mathrm{d}t,$$

where $\phi(x|\mu, \sigma^2)$ is a density of $\mathcal{N}(\mu, \sigma^2)$ and $D(u)$ is a weight function bounded from below by 1 (see Lemma D.6 of Appendix D). This lower bound on $D(u)$ concludes the proof. $\qquad\square$

We emphasise that our technique of deriving a Gaussian-like lower bound is substantially different from the methodology used by Agrawal and Jia [2017b]. The latter one was based on reduction of a weighted sum of Dirichlet random vector to a weighted sum of independent Beta distributed random variables and a subsequent application of the Berry-Esseen inequality, whereas our approach relies on the integral representation for the density of the corresponding linear projection of Dirichlet random vector.

Step 2. Optimism Next, we apply Theorem 3.3 to prove that the estimate of Q-function $\overline{Q}_h^t$ is optimistic with high probability for our choice of inflation parameter κ and a number of posterior samples J: $\overline{Q}_h^t(s, a) \geq Q_h^\star(s, a)$ for any $(s, a, h, t) \in \mathcal{S} \times \mathcal{A} \times [H] \times [T]$.

We show that the inequalities $\max_{j \in [J]}\{\widetilde{p}_h^{t,j} V_{h+1}^\star(s, a)\} \geq p_h V_{h+1}^\star(s, a)$ hold for all $(s, a, h, t) \in \mathcal{S} \times \mathcal{A} \times [H] \times [T]$ with high probability. First, we notice that $\widetilde{p}_h^{t,j}(s, a) \sim \mathcal{D}ir(\alpha_0 + 1, \alpha_1, \ldots, \alpha_S)$ for $\alpha_0 = n_0/\kappa - 1, \alpha_i = n_h^t(s_i|s, a)/\kappa$ and $\overline{\alpha} = (\overline{n}_h^t(s, a) - \kappa)/\kappa$. Additionally, define a probability distribution $q \in \Delta_S$ such that $q(i) = \alpha_i/\overline{\alpha}$. This distribution slightly differs from $\overline{p}_h^t(s, a)$ because of an additional $+1$ in the parameters of the Dirichlet distribution. Next, we may apply Theorem 3.3 with $\varepsilon = 1/2$ and a proper choice of $n_0 = n_0(\varepsilon)$,

$$\mathbb{P}_{\widetilde{p}_h^{t,j}(s,a) \sim \mathcal{D}ir(\alpha_0+1, \alpha_1, \ldots, \alpha_S)}\left[\widetilde{p}_h^{t,j} V_{h+1}^\star(s, a) \geq p_h V_{h+1}^\star(s, a)\right] \geq \frac{1}{2}\left(1 - \Phi\left(\sqrt{\frac{2\zeta}{\kappa}}\right)\right),$$

where $\zeta \triangleq (\overline{n}_h^t - \kappa)\,\mathcal{K}_{\inf}(q, p_h V_{h+1}^\star(s, a), V_{h+1}^\star)$ and $\Phi(\cdot)$ is a cumulative distribution function (CDF) of a standard normal distribution. By a concentration argument we have

$$\zeta \leq n_h^t\,\mathcal{K}_{\inf}(\widehat{p}_h^t(s, a), p_h V_{h+1}^\star(s, a), V_{h+1}^\star) \leq \kappa/2,$$

with high probability for an appropriate choice of $\kappa = \widetilde{\mathcal{O}}(1)$. For this step of the proof the presence of the inflation parameter κ is crucial: this parameter increases the variance of $\widetilde{p}_h^{t,j}(s, a)$ to ensure that the above inequality holds with a constant probability. Next, by taking the maximum over $J = \mathcal{O}(\log(SATH/\delta))$ samples and applying union bound, we guarantee that the inequality $\max_{j \in [J]}\{\widetilde{p}_h^{t,j} V_{h+1}^\star(s, a)\} \geq p_h V_{h+1}^\star(s, a)$ holds simultaneously for all $(s, a, h, t) \in \mathcal{S} \times \mathcal{A} \times [H] \times [T]$ with probability at least $1 - \delta/2$. The formal statement and the proof could be found in Proposition B.4 of Appendix B.2.

Finally, the standard backward induction over $h \in [H]$ concludes optimism. Indeed, the base of induction $h = H + 1$ is trivial. Next, by the Bellman equations for $\overline{Q}_h^t$ and $Q_h^\star$ we have

$$\overline{Q}_h^t(s, a) - Q_h^\star(s, a) = \max_{j \in [J]}\{\widetilde{p}_h^{t,j} \overline{V}_{h+1}^t(s, a)\} - p_h V_{h+1}^\star(s, a).$$

The induction hypothesis implies $\overline{V}_{h+1}^t(s') \geq \overline{Q}_{h+1}^t(s', \pi^\star(s')) \geq Q_{h+1}^\star(s', \pi^\star(s')) = V_{h+1}^\star(s')$ for any $s' \in \mathcal{S}$. Hence,

$$\overline{Q}_h^t(s, a) - Q_h^\star(s, a) \geq \max_{j \in [J]}\{\widetilde{p}_h^{t,j} V_{h+1}^\star(s, a)\} - p_h V_{h+1}^\star(s, a) \geq 0$$

with probability at least $1 - \delta/2$.

Step 3. Regret bound The rest of proof directly follows Azar et al. [2017], where UCBVI algorithm with Bernstein bonuses was analyzed. By the optimism, we have

$$\mathfrak{R}^T = \sum_{t=1}^T [V_1^\star(s_1) - V_1^{\pi^t}(s_1)] \leq \sum_{t=1}^T \delta_1^t,$$

where $\delta_h^t \triangleq \overline{V}_h^{t-1}(s_h^t) - V_h^{\pi^t}(s_h^t)$. The quantity δ_h^t can be decomposed as follows using the Bellman equation for V^{π^t} and $\overline{Q}_h^{t-1}$,

$$\delta_h^t = \overline{Q}_h^{t-1}(s_h^t, a_h^t) - Q_h^{\pi^t}(s_h^t, a_h^t) = \max_{j \in [J]}\left\{\widetilde{p}_h^{t-1,j}\overline{V}_{h+1}^{t-1}(s_h^t, a_h^t)\right\} - p_h V_{h+1}^{\pi^t}(s_h^t, a_h^t)$$

$$= \underbrace{\max_{j \in [J]}\left\{\widetilde{p}_h^{t-1,j}\overline{V}_{h+1}^{t-1}(s_h^t, a_h^t)\right\} - \overline{p}_h^{t-1}\overline{V}_{h+1}^{t-1}(s_h^t, a_h^t)}_{(\mathbf{A})} + \underbrace{[\overline{p}_h^{t-1} - \widehat{p}_h^{t-1}]\overline{V}_{h+1}^{t-1}(s_h^t, a_h^t)}_{(\mathbf{B})}$$

$$+ \underbrace{[\widehat{p}_h^{t-1} - p_h][\overline{V}_{h+1}^{t-1} - V_{h+1}^{\star}](s_h^t, a_h^t)}_{(\mathbf{C})} + \underbrace{[\widehat{p}_h^{t-1} - p_h]V_{h+1}^{\star}(s_h^t, a_h^t)}_{(\mathbf{D})}$$

$$+ \underbrace{p_h[\overline{V}_{h+1}^{t-1} - V_{h+1}^{\pi^t}](s_h^t, a_h^t) - [\overline{V}_{h+1}^{t-1} - V_{h+1}^{\pi^t}](s_{h+1}^t)}_{\xi_h^t} + \delta_{h+1}^t.$$

The terms $(\mathbf{C})$, $(\mathbf{D})$, and ξ_h^t are standard in the analysis of the optimistic algorithms. The term $(\mathbf{B})$ could be upper-bounded by $\frac{r_0 \cdot n_0 \cdot H}{\overline{n}_h^{t-1}(s_h^t, a_h^t)}$ and turns out to be one of second-order terms. The analysis of $(\mathbf{A})$ is novel and requires application of the Bernstein inequality for Dirichlet distributions that follows from Theorem 3.2 and is spelled out in the following lemma.

Lemma 3.5 (see Lemma C.6 in Appendix C). *For any $\alpha = (\alpha_0, \alpha_1, \ldots, \alpha_m) \in \mathbb{R}_{++}^{m+1}$ define $\overline{p} \in \Delta_m$ such that $\overline{p}(\ell) = \alpha_\ell/\overline{\alpha}, \ell = 0, \ldots, m$, where $\overline{\alpha} = \sum_{j=0}^m \alpha_j$. Then for any $f : \{0, \ldots, m\} \to [0, b]$ such that $f(0) = b$ and $\delta \in (0, 1)$,*

$$\mathbb{P}_{w \sim \mathcal{D}ir(\alpha)}\left[wf \geq \overline{p}f + 2\sqrt{\frac{\mathrm{Var}_{\overline{p}}(f)\log(1/\delta)}{\overline{\alpha}}} + \frac{3b \cdot \log(1/\delta)}{\overline{\alpha}}\right] \leq \delta.$$

As opposed to Lemma C.8 of Tiapkin et al. [2022], the last result applies to Dirichlet distributions with non-integer parameters as in our case (due to the presence of the inflation parameter κ). Therefore, we see that the term $(\mathbf{A})$ can be upper bounded by a quantity which has the same role as in the analysis of UCBVI. After using the Bernstein bound, the rest of the proof follows from the analysis of UCBVI with the Bernstein bonuses and Bayes-UCBVI; see Azar et al., 2017 and Tiapkin et al., 2022.

4 Conclusion

In this work, we presented the OPSRL algorithm which can be viewed as a simple optimistic variant of the PSRL algorithm. Notably, OPSRL only needs $\widetilde{\mathcal{O}}(1)$ posterior samples per state-action. We proved that the regret of OPSRL is upper-bounded with high probability by $\widetilde{\mathcal{O}}(\sqrt{H^3 SAT})$, matching the problem-independent lower-bound of order $\Omega(\sqrt{H^3 SAT})$ for T large enough and up to terms poly-logarithmic in H, S, A, and T. While our work addresses the open questions raised by Agrawal and Jia [2017b] in the episodic setting, obtaining the same results in the infinite-horizon average reward setting remains an open issue. We believe that it is possible to adapt our analysis to this other setting up to some technical adjustments. Ultimately, another open question, is to obtain a high-probability regret bound for PSRL, that is, when using only a *single* posterior sample and not inflating the posterior. As a further future research direction we believe it could be interesting to obtain a model-free algorithm that relies on the same mechanism as OPSRL for exploration. Indeed, such an algorithm could avoid the use of complicated bonuses adopted by the current model-free algorithms while reducing the memory complexity of OPSRL.

References

Yasin Abbasi-Yadkori and Csaba Szepesvári. Bayesian optimal control of smoothly parameterized systems. In *Proceedings of the Thirty-First Conference on Uncertainty in Artificial Intelligence*, UAI'15, page 2–11, Arlington, Virginia, USA, 2015. AUAI Press. ISBN 9780996643108.

Marc Abeille and Alessandro Lazaric. Linear Thompson Sampling Revisited. In Aarti Singh and Jerry Zhu, editors, *Proceedings of the 20th International Conference on Artificial Intelligence*

and Statistics, volume 54 of *Proceedings of Machine Learning Research*, pages 176–184. PMLR, 20–22 Apr 2017. URL https://proceedings.mlr.press/v54/abeille17a.html.

Shipra Agrawal and Navin Goyal. Analysis of thompson sampling for the multi-armed bandit problem. In Shie Mannor, Nathan Srebro, and Robert C. Williamson, editors, *Proceedings of the 25th Annual Conference on Learning Theory*, volume 23 of *Proceedings of Machine Learning Research*, pages 39.1–39.26, Edinburgh, Scotland, 25–27 Jun 2012. PMLR. URL https://proceedings.mlr.press/v23/agrawal12.html.

Shipra Agrawal and Navin Goyal. Further optimal regret bounds for thompson sampling. In Carlos M. Carvalho and Pradeep Ravikumar, editors, *Proceedings of the Sixteenth International Conference on Artificial Intelligence and Statistics*, volume 31 of *Proceedings of Machine Learning Research*, pages 99–107, Scottsdale, Arizona, USA, 29 Apr–01 May 2013. PMLR. URL https://proceedings.mlr.press/v31/agrawal13a.html.

Shipra Agrawal and Randy Jia. Posterior sampling for reinforcement learning: worst-case regret bounds. *CoRR*, abs/1705.07041, 2017a. URL http://arxiv.org/abs/1705.07041.

Shipra Agrawal and Randy Jia. Optimistic posterior sampling for reinforcement learning: worst-case regret bounds. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017b. URL https://proceedings.neurips.cc/paper/2017/file/3621f1454cacf995530ea53652ddf8fb-Paper.pdf.

D. Alfers and H. Dinges. A normal approximation for beta and gamma tail probabilities. *Zeitschrift für Wahrscheinlichkeitstheorie und Verwandte Gebiete*, 65(3):399–420, Feb 1984. ISSN 1432-2064. doi: 10.1007/BF00533744. URL https://doi.org/10.1007/BF00533744.

Mohammad Gheshlaghi Azar, Ian Osband, and Rémi Munos. Minimax regret bounds for reinforcement learning. In *International Conference on Machine Learning*, 2017. URL https://arxiv.org/pdf/1703.05449.pdf.

Dorian Baudry, Romain Gautron, Emilie Kaufmann, and Odalric Maillard. Optimal thompson sampling strategies for support-aware cvar bandits. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 716–726. PMLR, 18–24 Jul 2021a. URL https://proceedings.mlr.press/v139/baudry21a.html.

Dorian Baudry, Patrick Saux, and Odalric-Ambrym Maillard. From optimality to robustness: Dirichlet sampling strategies in stochastic bandits. In *Neurips 2021*, 2021b.

Ronen I. Brafman and Moshe Tennenholtz. R-MAX - A general polynomial time algorithm for near-optimal reinforcement learning. *Journal of Machine Learning Research*, 3:213–231, 2002.

O. Cappé, A. Garivier, O-A. Maillard, R. Munos, and G. Stoltz. Kullback-Leibler upper confidence bounds for optimal sequential allocation. *Annals of Statistics*, 41(3):1516–1541, 2013.

Christoph Dann, Tor Lattimore, and Emma Brunskill. Unifying PAC and regret: Uniform PAC bounds for episodic reinforcement learning. In *Neural Information Processing Systems*, 2017. URL https://arxiv.org/pdf/1703.07710.pdf.

Omar Darwiche Domingues, Pierre Ménard, Matteo Pirotta, Emilie Kaufmann, and Michal Valko. Regret bounds for kernel-based reinforcement learning. *arXiv preprint arXiv:2004.05599*, 2020. URL http://arxiv.org/abs/2004.05599.

Yonathan Efroni, Nadav Merlis, Mohammad Ghavamzadeh, and Shie Mannor. Tight regret bounds for model-based reinforcement learning with greedy policies. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/25caef3a545a1fff2ff4055484f0e758-Paper.pdf.

M. V. Fedoryuk. *Metod perevala*. Izdat. "Nauka", Moscow, 1977.

Claude-Nicolas Fiechter. Efficient reinforcement learning. In *Conference on Learning Theory*, 1994. URL http://citeseerx.ist.psu.edu/viewdoc/download;jsessionid=7F5F8FCD1AA7ED07356410DDD5B384FE?doi=10.1.1.49.8652&rep=rep1&type=pdf.

Ronan Fruit, Matteo Pirotta, Alessandro Lazaric, and Ronald Ortner. Efficient bias-span-constrained exploration-exploitation in reinforcement learning. In *International Conference on Machine Learning*, pages 1578–1586. PMLR, 2018.

Aurélien Garivier, Hédi Hadiji, Pierre Menard, and Gilles Stoltz. Kl-ucb-switch: optimal regret bounds for stochastic bandits from both a distribution-dependent and a distribution-free viewpoints. *arXiv preprint arXiv:1805.05071*, 2018.

Junya Honda and Akimichi Takemura. An asymptotically optimal bandit algorithm for bounded support models. In Adam Tauman Kalai and Mehryar Mohri, editors, *COLT*, pages 67–79. Omnipress, 2010. ISBN 978-0-9822529-2-5. URL http://dblp.uni-trier.de/db/conf/colt/colt2010.html#HondaT10.

Thomas Jaksch, Ronald Ortner, and Peter Auer. Near-optimal regret bounds for reinforcement learning. *Journal of Machine Learning Research*, 99:1563–1600, 2010. URL http://www.jmlr.org/papers/volume11/jaksch10a/jaksch10a.pdf.

Chi Jin, Zeyuan Allen-Zhu, Sébastien Bubeck, and Michael I. Jordan. Is Q-learning provably efficient? In *Neural Information Processing Systems*, 2018. URL https://arxiv.org/pdf/1807.03765.pdf.

Anders Jonsson, Emilie Kaufmann, Pierre Ménard, Omar Darwiche Domingues, Edouard Leurent, and Michal Valko. Planning in markov decision processes with gap-dependent sample complexity. *arXiv preprint arXiv:2006.05879*, jun 2020. URL http://arxiv.org/abs/2006.05879.

Emilie Kaufmann, Nathaniel Korda, and Rémi Munos. Thompson sampling: An asymptotically optimal finite-time analysis. In *Proceedings of the 23rd International Conference on Algorithmic Learning Theory*, ALT'12, page 199–213, Berlin, Heidelberg, 2012. Springer-Verlag. ISBN 9783642341052. doi: 10.1007/978-3-642-34106-9_18. URL https://doi.org/10.1007/978-3-642-34106-9_18.

Emilie Kaufmann, Pierre Ménard, Omar Darwiche Domingues, Anders Jonsson, Edouard Leurent, and Michal Valko. Adaptive reward-free exploration. *arXiv preprint arXiv:2006.06294*, 2020. URL https://arxiv.org/pdf/2006.06294.pdf.

Branislav Kveton, Csaba Szepesvari, Sharan Vaswani, Zheng Wen, Tor Lattimore, and Mohammad Ghavamzadeh. Garbage in, reward out: Bootstrapping exploration in multi-armed bandits. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 3601–3610. PMLR, 09–15 Jun 2019. URL https://proceedings.mlr.press/v97/kveton19a.html.

Pierre Menard, Omar Darwiche Domingues, Xuedong Shang, and Michal Valko. Ucb momentum q-learning: Correcting the bias without forgetting, 2021. URL https://arxiv.org/abs/2103.01312.

Frank W. J. Olver. *Asymptotics and special functions*. AKP Classics. A K Peters, Ltd., Wellesley, MA, 1997. ISBN 1-56881-069-5. Reprint of the 1974 original [Academic Press, New York; MR0435697 (55 #8655)].

Ian Osband and Benjamin Van Roy. Why is posterior sampling better than optimism for reinforcement learning? In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 2701–2710. PMLR, 06–11 Aug 2017. URL https://proceedings.mlr.press/v70/osband17a.html.

Ian Osband, Daniel Russo, and Benjamin Van Roy. (more) efficient reinforcement learning via posterior sampling. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q.

Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 26. Curran Associates, Inc., 2013. URL https://proceedings.neurips.cc/paper/2013/file/6a5889bb0190d0211a991f47bb19a777-Paper.pdf.

Ian Osband, Charles Blundell, Alexander Pritzel, and Benjamin Van Roy. Deep exploration via bootstrapped dqn. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016a. URL https://proceedings.neurips.cc/paper/2016/file/8d8818c8e140c64c743113f563cf750f-Paper.pdf.

Ian Osband, Benjamin Van Roy, and Zheng Wen. Generalization and exploration via randomized value functions. In Maria Florina Balcan and Kilian Q. Weinberger, editors, *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pages 2377–2386, New York, New York, USA, 20–22 Jun 2016b. PMLR. URL https://proceedings.mlr.press/v48/osband16.html.

Ian Osband, John Aslanides, and Albin Cassirer. Randomized prior functions for deep reinforcement learning. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/file/5a7b238ba0f6502e5d6be14424b20ded-Paper.pdf.

Ian Osband, Benjamin Van Roy, Daniel J. Russo, and Zheng Wen. Deep exploration via randomized value functions. *Journal of Machine Learning Research*, 20(124):1–62, 2019. URL http://jmlr.org/papers/v20/18-339.html.

Yi Ouyang, Mukul Gagrani, Ashutosh Nayyar, and Rahul Jain. Learning unknown markov decision processes: A thompson sampling approach. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, NIPS'17, page 1333–1342, Red Hook, NY, USA, 2017. Curran Associates Inc. ISBN 9781510860964.

Aldo Pacchiano, Philip Ball, Jack Parker-Holder, Krzysztof Choromanski, and Stephen Roberts. Towards tractable optimism in model-based reinforcement learning. In Cassio de Campos and Marloes H. Maathuis, editors, *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence*, volume 161 of *Proceedings of Machine Learning Research*, pages 1413–1423. PMLR, 27–30 Jul 2021. URL https://proceedings.mlr.press/v161/pacchiano21a.html.

Jian Qian, Ronan Fruit, Matteo Pirotta, and Alessandro Lazaric. Concentration inequalities for multinoulli random variables. *CoRR*, abs/2001.11595, 2020. URL https://arxiv.org/abs/2001.11595.

Charles Riou and Junya Honda. Bandit algorithms based on thompson sampling for bounded reward distributions. In Aryeh Kontorovich and Gergely Neu, editors, *Proceedings of the 31st International Conference on Algorithmic Learning Theory*, volume 117 of *Proceedings of Machine Learning Research*, pages 777–826. PMLR, 08 Feb–11 Feb 2020. URL https://proceedings.mlr.press/v117/riou20a.html.

Daniel Russo. Worst-case regret bounds for exploration via randomized value functions. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/451ae86722d26a608c2e174b2b2773f1-Paper.pdf.

Daniel Russo and Benjamin Van Roy. An information-theoretic analysis of thompson sampling. *Journal of Machine Learning Research*, 17(68):1–30, 2016. URL http://jmlr.org/papers/v17/14-087.html.

Daniel Russo and Benjamin Van Roy. Learning to optimize via information-directed sampling. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc., 2014. URL https://proceedings.neurips.cc/paper/2014/file/301ad0e3bd5cb1627a2044908a42fdc2-Paper.pdf.

R. Sutton and A. Barto. *Reinforcement Learning: an Introduction*. MIT press, 1998.

István Szita and András Lőrincz. The many faces of optimism: A unifying approach. In *Proceedings of the 25th International Conference on Machine Learning*, ICML '08, page 1048–1055, New York, NY, USA, 2008. Association for Computing Machinery. ISBN 9781605582054. doi: 10.1145/1390156.1390288. URL https://doi.org/10.1145/1390156.1390288.

Mohammad Sadegh Talebi and Odalric-Ambrym Maillard. Variance-aware regret bounds for undiscounted reinforcement learning in mdps. In *Algorithmic Learning Theory*, pages 770–805, 2018.

William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3-4):285–294, 12 1933. ISSN 0006-3444. doi: 10.1093/biomet/25.3-4.285. URL https://doi.org/10.1093/biomet/25.3-4.285.

Daniil Tiapkin, Denis Belomestny, Eric Moulines, Alexey Naumov, Sergey Samsonov, Yunhao Tang, Michal Valko, and Pierre Menard. From Dirichlet to Rubin: Optimistic exploration in rl without bonuses, 2022. URL https://arxiv.org/abs/2205.07704.

Zhihan Xiong, Ruoqi Shen, and Simon S. Du. Randomized exploration is near-optimal for tabular MDP. *CoRR*, abs/2102.09703, 2021. URL https://arxiv.org/abs/2102.09703.

Andrea Zanette and Emma Brunskill. Tighter problem-dependent regret bounds in reinforcement learning without domain knowledge using value function bounds. In *Proceedings of the 36th International Conference on Machine Learning, (ICML)*, 2019.

Zihan Zhang, Yuan Zhou, and Xiangyang Ji. Almost optimal model-free reinforcement learning via reference-advantage decomposition. In *Advances in Neural Information Processing Systems*, 2020. URL https://arxiv.org/pdf/2004.10019.pdf.