Interval Bound Interpolation for Few-shot Learning with Few Tasks

Abstract

Few-shot learning aims to transfer the knowledge acquired from training on a diverse set of tasks to unseen tasks from the same task distribution, with a limited amount of labeled data. The underlying requirement for effective few-shot generalization is to learn a good representation of the task manifold. This becomes more difficult when only a limited number of tasks are available for training. In such a few-task few-shot setting, it is beneficial to explicitly preserve the local neighborhoods from the task manifold and exploit this to generate artificial tasks for training. To this end, we introduce the notion of *interval bounds* from the provably robust training literature to few-shot learning. The interval bounds are used to characterize neighborhoods around the training tasks. These neighborhoods can then be preserved by minimizing the distance between a task and its respective bounds. We then use a novel strategy to artificially form new tasks for training by interpolating between the available tasks and their respective interval bounds. We apply our framework to both model-agnostic meta-learning as well as prototype-based metric-learning paradigms. The efficacy of our proposed approach is evident from the improved performance on several datasets from diverse domains in comparison to recent methods.

1 Introduction

Few-shot learning methods attempt to leverage the knowledge acquired by training on a large pool of tasks so as to easily generalize to unseen tasks from the same distribution, using only a few labeled examples. Since the unseen tasks are sampled from the same underlying manifold governing the task distribution, learning a good representation of the task manifold is a natural way to effectively generalize to the new tasks using a limited amount of labeled data. Manifold learning methods (Tenenbaum et al., 2000; Roweis & Saul, 2000; Van der Maaten & Hinton, 2008) function by aiming to preserve the neighborhoods from the high-dimensional manifold during the lower dimensional projection. Similarly, the feature embedding learned by the few-shot learner should conserve the neighborhoods from the high-dimensional task manifold. However, existing few-shot learning methods lack an explicit mechanism for achieving this. Further, real-world few-shot learning scenarios like rare disease detection may not have the large number of training tasks required for effective learning, due to various constraints such as data collection costs, privacy concerns, and/or data availability in newer domains (Yao et al., 2022). In such scenarios, few-shot learning methods are prone to overfit the training tasks, thus limiting the ability to generalization to unseen tasks. Therefore, in this work, we develop a method to explicitly constrain the feature embedding in an attempt to preserve neighborhoods from the high-dimensional task manifold and to construct artificial tasks within these neighborhoods in the feature space, to improve the performance when a limited number of training tasks are available.

The proposed approach relies on characterizing the neighborhoods from the high-dimensional task manifold and propagating them through the network with the intent to preserve the task neighborhood in the feature space. We achieve this by employing the concept of interval bounds from the provably robust training literature (Gowal et al., 2019), i.e. the axis-aligned bounds for the activations in each layer, obtained using interval arithmetic (Sunaga, 1958). Concretely, as shown in Figure 1, we use Interval Bound Propagation (IBP, Gowal et al. (2019)) to first define a small ϵ-neighborhood for each few-shot training task and then obtain the bounding box around the mapping of the corresponding neighborhood in the feature embedding space. We then explicitly attempt to preserve

the ϵ-neighborhoods by minimizing the distance between a task and its respective interval bounds in addition to optimizing the few-shot classification objective. We further devise a mechanism to construct the artificial tasks by interpolating between a task and its corresponding IBP bounds. It is important to notice that this setup is distinct from provably robust training for few-shot learning in that we do not attempt to minimize (or calculate for that matter) the worst-case classification loss.

Figure 1: Illustration of the proposed interval bound propagation–aided few-shot learning setup (best viewed in color): We use interval arithmetic to define a small ϵ-neighborhood around a training task $\mathcal{T}_i$ sampled from the task distribution $p(\mathcal{T})$. IBP is then used to obtain the bounding box around the mapping of the said neighborhood in the embedding space f_{θ^S} given by the first S layers of the learner f_θ. While training the learner f_θ to minimize the classification loss $\mathcal{L}_{CE}$ on the query set $\mathcal{D}_i^q$, we additionally attempt to minimize the losses $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$, forcing the ϵ-neighborhood to be compact in the embedding space as well.

Various methods have been proposed to mitigate the few-task few-shot problem using approaches such as explicit regularization (Jamal & Qi, 2019; Yin et al., 2019), intra-task augmentation (Lee et al., 2020; Ni et al., 2021; Yao et al., 2021), and inter-task interpolation to construct new artificial tasks (Yao et al., 2022). While inter-task interpolation has been shown to be the most effective among these existing approaches, it suffers from the limitation that the artificially created tasks may be generated away from the task manifold depending on the curvature of the feature embedding space, as there is no natural way to select pairs of task which are close to each other on the manifold (see Figure 2(a)). The interval bounds obtained using IBP, on the other hand, are likely to be close to the original task embedding as we explicitly minimize the distance between a task and its interval bounds. Thus, using them for interpolation is likely to keep the generated tasks close to the manifold (see Figure 2(b)).

(a)   (b)

Figure 2: Interval bound–based task interpolation (best viewed in color): (a) Existing inter-task interpolation methods create new artificial tasks by combining pairs of original tasks (blue ball). However, depending on how flat the task-manifold embedding is at the layer where interpolation is performed, the artificial tasks may either be created close to the task-manifold (green cross) or away from the task-manifold (red box). (b) The proposed interval bound–based task interpolation creates artificial tasks by combining an original task with one of its interval bounds (yellow ball). Such artificial tasks are likely to be in the vicinity of the task manifold as the interval bounds are forced to be close to the task embedding by the losses $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$.

In essence, the key contributions made in this article advance the existing literature in the following ways: **(1)** In Section 4.1, we present for the first time, a novel method to synergize few-shot learning

with interval bound propagation (Gowal et al., 2019) so as to explicitly lend the ability to preserve task neighborhoods in the feature embedding space of the few-shot learner. **(2)** In Section 4.2, we propose the interval bound–based task interpolation technique which can create new tasks (as opposed to augmenting each individual task (Lee et al., 2020; Ni et al., 2021; Yao et al., 2021)), by interpolating between a task sampled from the task distribution and its interval bounds. **(3)** Unlike existing inter-task interpolation methods that require paired tasks for interpolation (Yao et al., 2022), our framework can generate new tasks from only a single task. This allows the proposed framework to be seamlessly integrated with existing few-shot learning paradigms.

In Section 5, we empirically demonstrate the effectiveness of our proposed approach on both gradient-based meta-learning and prototype-based metric-learning on few-task real-world datasets from multiple domains, in comparison to the recent prior methods. Finally, we make concluding remarks and also discuss future scopes of research in Section 6.

2 RELATED WORKS

Manifold learning: IBP (Gowal et al., 2019) was proposed for provably robust training of classifiers against adversarial attacks. We repurpose IBP to define ϵ-neighborhoods around few-shot learning tasks and constrain the learned feature embedding to preserve the said neighborhoods. This is similar in spirit to traditional manifold learning approaches such as ISOMAP (Tenenbaum et al., 2000), LLE (Roweis & Saul, 2000), t-SNE (Van der Maaten & Hinton, 2008), etc.

Task augmentation: To train on datasets with a limited number of tasks, some works directly impose regularization on the few-shot learner (Jamal & Qi, 2019; Yin et al., 2019). Another line of work performs data augmentation on the individual tasks (Lee et al., 2020; Ni et al., 2021; Yao et al., 2021). Finally, a third direction is to employ inter-task interpolation to mitigate task scarcity (Yao et al., 2022). Our approach is similar to the third category in that we directly create new artificial tasks. But, we also differs from all of the above-mentioned methods in that we neither undertake intra-task augmentation nor inter-task interpolation.

3 PRELIMINARIES

In a few-shot learning problem, we deal with tasks $\mathcal{T}_i \sim p(\mathcal{T})$. Each task $\mathcal{T}_i$ is associated with a dataset $\mathcal{D}_i = (X_i, Y_i)$, that we further subdivide into a support set $\mathcal{D}_i^s = (X_i^s, Y_i^s) = \{(\mathbf{x}_{i,r}^s, y_{i,r}^s)\}_{r=1}^{N_s}$ and a query set $\mathcal{D}_i^q = (X_i^q, Y_i^q) = \{(\mathbf{x}_{i,r}^q, y_{i,r}^q)\}_{r=1}^{N_q}$. Given a learning model f_θ, where θ denotes the model parameters, few-shot learning algorithms attempt to learn θ to minimize the loss on the query set $\mathcal{D}_i^q$ for each of the sampled tasks using the data-label pairs from the corresponding support set $\mathcal{D}_i^s$. Thereafter, the trained model f_θ and the support set $\mathcal{D}_j^s$ for new tasks $\mathcal{T}_j$ can be used to perform inference on the corresponding query set $\mathcal{D}_j^q$. In the following subsection, we discuss gradient-based meta-learning while the prototype-based metric-learning is detailed in Appendix A.

Gradient-based meta-learning: In gradient-based meta-learning, the aim is to learn initial parameters θ^* such that a typically small number of gradient update steps using the data-label pairs in the support set $\mathcal{D}_i^s$ results in a model f_{ϕ_i} that performs well on the query set of task $\mathcal{T}_i$. During the meta-training stage, first, a base learner is trained on multiple support sets $\mathcal{D}_i^s$, and the performance of the resulting models f_{ϕ_i} is evaluated on the corresponding query sets $\mathcal{D}_i^q$. The meta-learner parameters θ are then updated such that the expected loss of the base learner on query sets is minimized. In the meta-testing stage, the final meta-trained model f_{θ^*} is fine-tuned on the support set $\mathcal{D}_j^s$ for the given test task $\mathcal{T}_j$ to obtain the adapted model f_{ϕ_j} that can then be used for inference on the corresponding query set $\mathcal{D}_j^q$. Considering Model-Agnostic Meta-Learning (MAML) (Finn et al., 2017) as an example, the bi-level optimization of the gradient-based meta-learning is formulated as:

$$\theta^* \leftarrow \arg\min_\theta \mathbb{E}_{\mathcal{T}_i \sim p(\mathcal{T})}[\mathcal{L}(f_{\phi_i}; \mathcal{D}_i^q)], \text{ where } \phi_i = \theta - \eta_0 \nabla_\theta \mathcal{L}(f_\theta; \mathcal{D}_i^s), \tag{1}$$

while η_0 denotes the inner-loop learning rate used by the base learner to train on $\mathcal{D}_i^s$ for task $\mathcal{T}_i$, and $\mathcal{L}$ is the loss function, which is usually the cross-entropy loss for classification problems:

$$\mathcal{L}_{CE} = \mathbb{E}_{\mathcal{T}_i \sim p(\mathcal{T})}[-\sum_r \log p(y_{i,r}^q | \mathbf{x}_{i,r}^q, f_{\phi_i})]. \tag{2}$$

A key requirement for effective few-shot generalization to new tasks for both gradient-based meta-learning and prototype-based metric-learning is to learn a good embedding of the high-dimensional manifold characterizing the task distribution $p(\mathcal{T})$, i.e. the task manifold. Ideally, the learned embedding should conserve the neighborhoods from the high-dimensional task manifold (Tenenbaum et al., 2000; Roweis & Saul, 2000). Hence, in the following subsection, we discuss Interval Bound Propagation (IBP) (Gowal et al., 2019) that can be employed to define a neighborhood around a task.

Interval bound propagation: Let us consider a neural network f_θ consisting of a sequence of transformations $h_l, (l \in \{1, 2, \cdots, L\})$ for each of its L layers. We start from an initial input $\mathbf{z}_0 = \mathbf{x}$ to the network along with lower bound $\underline{\mathbf{z}}_0(\epsilon) = \mathbf{x} - \mathbf{1}\epsilon$ and upper bound $\overline{\mathbf{z}}_0(\epsilon) = \mathbf{x} + \mathbf{1}\epsilon$ for an ϵ-neighborhood around the input $\mathbf{x}$. In each of the subsequent layers $l \in \{1, 2, \cdots, L\}$ of the network, we get an activation $\mathbf{z}_l = h_l(\mathbf{z}_{l-1})$. Additionally, IBP uses interval arithmetic to obtain the corresponding bounds on the activation $\mathbf{z}_l$ for the l-th layer (see Appendix C). The bounds are characterized by axis-aligned bounding boxes of the form $\underline{\mathbf{z}}_l(\epsilon) \leq \mathbf{z}_l \leq \overline{\mathbf{z}}_l(\epsilon)$ (where the relation $\leq$ must hold individually for all coordinates of the vectors). Based on the specific nature of the transformation h_l in the l-th layer, interval arithmetic yields corresponding lower and upper bound transformations $\underline{\mathbf{z}}_l(\epsilon) = \underline{h}_l(\underline{\mathbf{z}}_{l-1}(\epsilon), \overline{\mathbf{z}}_{l-1}(\epsilon))$, and $\overline{\mathbf{z}}_l(\epsilon) = \overline{h}_l(\underline{\mathbf{z}}_{l-1}(\epsilon), \overline{\mathbf{z}}_{l-1}(\epsilon))$, such that each of the coordinates $\underline{z}_{l,c}(\epsilon)$ and $\overline{z}_{l,c}(\epsilon)$ of $\underline{\mathbf{z}}_l(\epsilon)$ and $\overline{\mathbf{z}}_l(\epsilon)$ respectively, satisfies the conditions:

$$\underline{z}_{l,c}(\epsilon) = \min_{\underline{\mathbf{z}}_{l-1}(\epsilon) \leq \mathbf{z}_{l-1} \leq \overline{\mathbf{z}}_{l-1}(\epsilon)} \mathbf{e}_c^\mathsf{T} h_l(\mathbf{z}_{l-1}) \text{ and } \overline{z}_{l,c}(\epsilon) = \max_{\underline{\mathbf{z}}_{l-1}(\epsilon) \leq \mathbf{z}_{l-1} \leq \overline{\mathbf{z}}_{l-1}(\epsilon)} \mathbf{e}_c^\mathsf{T} h_l(\mathbf{z}_{l-1}), \quad (3)$$

where $\mathbf{e}_c$ is the standard c-th basis vector. Further extending to multiple layers, such as the first S layers of the neural network f_{θ^S}, the individual transformations $\underline{h}_l$ and $\overline{h}_l$ for $l \in \{1, 2, \cdots, S\}$ can be composed to respectively obtain the corresponding functions $\underline{f}_{\theta^S}$ and $\overline{f}_{\theta^S}$, such that $\underline{\mathbf{z}}_S(\epsilon) = \underline{f}_{\theta^S}(\mathbf{z}_0, \epsilon)$, and $\overline{\mathbf{z}}_S(\epsilon) = \overline{f}_{\theta^S}(\mathbf{z}_0, \epsilon)$. See Appendix C for more details.

4 PROPOSED METHOD

Our proposed method aims to enable the learner f_θ to learn a feature embedding that attempts to preserve the ϵ-neighborhoods in the task manifold. Therefore, in the following subsection, we describe the notion of an ϵ-neighborhood for a training task $\mathcal{T}_i$ using IBP and show how they can be preserved to aid in few-shot learning problems.

4.1 FEW-SHOT LEARNING WITH INTERVAL BOUNDS

For a given training task $\mathcal{T}_i$, we define the ϵ-neighborhood of the task as consisting of the sets $\mathcal{I}_i^s(\epsilon)$ and $\mathcal{I}_i^q(\epsilon)$. These sets respectively consist of the interval bounds for the data instances in the support set $\mathcal{D}_i^s$ and the query set $\mathcal{D}_i^q$ of the task, calculated at the S-th layer of the learner:

$$\mathcal{I}_i^s(\epsilon) = \{\underline{f}_{\theta^S}(\mathbf{x}_{i,r}^s, \epsilon)\}_{r=1}^{N_s} \cup \{\overline{f}_{\theta^S}(\mathbf{x}_{i,r}^s, \epsilon)\}_{r=1}^{N_s}, \text{ and } \mathcal{I}_i^q(\epsilon) = \{\underline{f}_{\theta^S}(\mathbf{x}_{i,r}^q, \epsilon)\}_{r=1}^{N_q} \cup \{\overline{f}_{\theta^S}(\mathbf{x}_{i,r}^q, \epsilon)\}_{r=1}^{N_q},$$
$$(4)$$

where $S \ (\leq L)$ is an user-specified layer number meant to demarcate the boundary between the portion f_{θ^S} of the model that focuses on feature representation and the subsequent portion $f_{\theta^{L-S}}$ responsible for the classification, such that $f_\theta = f_{\theta^{L-S}} \circ f_{\theta^S}$.

The Euclidean distances between the embedding $f_{\theta^S}(\mathbf{x}_{i,r}^q)$ for the query instances in a given training task $\mathcal{T}_i$ and their respective interval bounds $\underline{f}_{\theta^S}(\mathbf{x}_{i,r}^q, \epsilon)$ and $\overline{f}_{\theta^S}(\mathbf{x}_{i,r}^q, \epsilon)$ is a measure of how well the ϵ-neighborhood of the task $\mathcal{T}_i$ is preserved in the learned feature embedding:

$$\mathcal{L}_{LB} = \frac{1}{N_q} \sum_{r=1}^{N_q} ||f_{\theta^S}(\mathbf{x}_{i,r}^q) - \underline{f}_{\theta^S}(\mathbf{x}_{i,r}^q, \epsilon)||_2^2 \text{ and} \quad (5)$$

$$\mathcal{L}_{UB} = \frac{1}{N_q} \sum_{r=1}^{N_q} ||f_{\theta^S}(\mathbf{x}_{i,r}^q) - \overline{f}_{\theta^S}(\mathbf{x}_{i,r}^q, \epsilon)||_2^2. \quad (6)$$

To ensure that the small ϵ-neighborhoods get mapped to small interval bounds by the feature embedding f_{θ^S}, we can minimize the losses $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$ in addition to the classification loss $\mathcal{L}_{CE}$ in (2). Notice that the losses $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$ are never used for the support instances $\mathbf{x}_{i,r}^s$.

Attempting to minimize a naïve sum of the three losses can cause some issues. For example, weighing the classification loss $\mathcal{L}_{CE}$ too high essentially reduces the proposed method to vanilla few-shot learning. On the other hand, assigning very high weights to the interval losses $\mathcal{L}_{LB}$ and/or $\mathcal{L}_{UB}$ may diminish learnability as the preservation of ϵ-neighborhoods gets precedence over classification performance. Moreover, such static weighting approaches are not capable of adapting to (and consequently mitigating) situations where one of the losses comes to unduly dominate the others. Thus, we minimize a convex weighted sum $\mathcal{L}$ of the three losses:

Figure 3: Dynamic weights for MAML+IBP on miniImageNet when γ is set to 1 for ease of visualisation.

$$\mathcal{L}(t) = w_{CE}(t)\mathcal{L}_{CE}(t) + w_{LB}(t)\mathcal{L}_{LB}(t) + w_{UB}(t)\mathcal{L}_{UB}(t), \quad (7)$$

where t denotes the current training step and $w_e(t)$ is the weight for the corresponding loss $\mathcal{L}_e$, $e \in \{CE, LB, UB\}$ at the t-th training step, which is dynamically calculated based on a softmax across the current values of the three losses:

$$w_e(t) = \frac{\exp(\mathcal{L}_e(t)/\gamma)}{\sum_{e' \in \{CE, LB, UB\}} \exp(\mathcal{L}_{e'}(t)/\gamma)}. \quad (8)$$

The hyperparameter γ controlling the relative importance of the losses. If any of the losses become too large, the dynamic weighing scheme strives to restore balance by assigning very high weightage to the concerned loss, thus prioritizing its minimization over that of the other losses. The changes in the dynamic weights over training steps for IBP-aided MAML (hereafter called MAML+IBP) using "4-CONV" network (Vinyals et al., 2016) on the miniImageNet dataset (Vinyals et al., 2016) is illustrated in Figure 3. We can observe that while there is a clear ordering to the magnitude of the weights (and therefore the corresponding losses) throughout the entire training run, the weights are in fact able to adapt to changes in loss values to maintain the status quo among the different losses.

Motivating results:

In Table 1, we demonstrate the effect of employing IBP-aided training for MAML using "4-CONV" network. We see that MAML+IBP

Table 1: Effect of IBP on MAML for miniImageNet and tieredImageNet datasets in terms of 5-way 1-shot Accuracy and intra-task compactness

Algorithm	Accuracy		1-NN distance	
	miniImageNet	tieredImageNet	miniImageNet	tieredImageNet
MAML (Finn et al., 2017)	48.70±1.75%	51.67±1.81%	0.97±0.02	0.98±0.02
MAML+IBP (ours)	**50.76±0.83%**	**54.36±0.80%**	**0.90±0.02**	**0.96±0.02**

outperforms vanilla MAML in terms of 5-way 1-shot classification accuracy on the miniImageNet and tieredImageNet (Ren et al., 2018) datasets. Moreover, we also illustrate that the feature embedding learned by IBP-aided training exhibits better intra-task compactness in terms of the mean Euclidean distances from the nearest neighbor in the same class for 100 query instances for 600 tasks, in the feature space characterized by f_{θ^S}. Recent works (Ni et al., 2021; Yao et al., 2022) have shown that augmenting the training data with artificial tasks can improve performance in domains with a limited amount of tasks. Therefore, while IBP-aided training improves the performance of vanilla MAML (as well as other baselines, detailed in Appendix F.3.1), we are particularly interested in the added advantage that it lends by facilitating the generation of artificial tasks within the neighborhoods defined by the interval bounds.

4.2 INTERVAL BOUND–BASED TASK INTERPOLATION

Since minimizing the additional losses $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$ is expected to ensure that the ϵ-neighborhood around a task is mapped to a small interval in the feature embedding space, artificial tasks formed within such intervals are naturally expected to be close to the task manifold. Therefore, we create additional artificial tasks by interpolating between an original task and its corresponding interval bounds (i.e., either the upper or the lower interval bound). In other words, for a training task $\mathcal{T}_i$, a corresponding artificial task $\mathcal{T}_i'$ is characterized by a support set $\mathcal{D}_i^{s'} = \{(\mathbf{H}_{i,r}^{s'}, \mathbf{y}_{i,r}^s)\}_{r=1}^{N_s}$ in the embedding space. The artificial support instances $\mathbf{H}_{i,r}^{s'}$ are created as:

$$\mathbf{H}_{i,r}^{s'} = (1-\lambda_k)f_{\theta^S}(\mathbf{x}_{i,r}^s) + (1-\nu_k)\lambda_k \underline{f}_{\theta^S}(\mathbf{x}_{i,r}^s, \epsilon) + \nu_k \lambda_k \overline{f}_{\theta^S}(\mathbf{x}_{i,r}^s, \epsilon), \quad (9)$$

Figure 4: Interval bound propagation–based few-shot training (best viewed in color): For each query data-label pair $(\mathbf{x}, y)$ in a given training task $\mathcal{T}_i$, we start by defining a ϵ-neighborhood $[\mathbf{x} - \mathbf{1}\epsilon, \mathbf{x} + \mathbf{1}\epsilon]$ around $\mathbf{x}$. The bounding box $[\underline{f}_{\theta^s}(\mathbf{x}, \epsilon), \overline{f}_{\theta^s}(\mathbf{x}, \epsilon)]$ around the embedding $f_{\theta^S}(\mathbf{x})$ after the first S layers of the learner is found using IBP. In addition to the classification loss $\mathcal{L}_{CE}$, we also minimize the losses $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$ which respectively measure the distances of $f_{\theta^S}(\mathbf{x})$ to $\underline{f}_{\theta^s}(\mathbf{x}, \epsilon)$ and $\overline{f}_{\theta^s}(\mathbf{x}, \epsilon)$. A softmax across the three loss values is used to dynamically calculate the convex weights for the losses, so as to prioritize the minimization of the dominant loss(es) at any given training step. For IBP-based interpolation, artificial tasks $\mathcal{T}_i'$ are created with instances $\mathbf{H}'$ formed by interpolating both the support and query instances with their corresponding lower or upper bounds. The mean of the classification loss $\mathcal{L}_{CE}$ for the $\mathcal{T}_i$ and the corresponding extra loss $\mathcal{L}_{CE}'$ for $\mathcal{T}_i'$ is minimized.

where k denotes the class to which $\mathbf{x}_{i,r}^s$ belongs, $\lambda_k \in [0, 1]$ is sampled from a Beta distribution $Beta(\alpha, \beta)$, and the random choice of $\nu_k \in \{0, 1\}$ dictates which of the bounds is chosen randomly for each class. The labels $\mathbf{y}_{i,r}^s$ for the artificial task remain identical to that of the original task. The query set $\mathcal{D}_i^{q'}$ for the artificial task is also constructed analogously. We then minimize the mean of the additional classification loss $\mathcal{L}_{CE}'$ for the artificial task $\mathcal{T}_i'$ and the classification loss $\mathcal{L}_{CE}$ for the original task $\mathcal{T}_i$ for query instances (also the support instances in case of meta-learning). As a reminder, the losses $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$ are also additionally minimized for the query instances. The complete IBP-based task interpolation or Interval Bound Interpolation (IBI) training setup is illustrated in Figure 4. Since IBI does not play any part during the testing phase, the testing recipe remains identical to that of vanilla few-shot learning. The detailed pseudocode of MAML+IBI (along with the IBI variant of ProtoNet) can be found in Appendix B.

Theoretical analysis: The data X_i ($i = 1, 2, \cdots, N$) for tasks $\mathcal{T}_i$ can be thought of as i.i.d. observations from a marginal distribution $\mathbb{P}_X$ defined on a compact subset $\mathcal{X}$ of $\mathbb{R}^d$ ($d \geq 1$), paired with corresponding Y_i drawn from the marginal distribution $\mathbb{P}_Y$. The map f_{θ^S} is bestowed with the task of producing a lower-dimensional representation of the input X. Let us denote the embedding space by $\mathcal{H} \subseteq \mathbb{R}^k$, given that $k \leq d$. The spaces $\mathcal{X}$ and $\mathcal{H}$ are endowed with l_2 norm for simplicity and conformity to our convention. One may observe that $f_{\theta^S} = h_1 \circ h_2 \circ \cdots \circ h_S$, where in general $h_l(\mathbf{z}) = \sigma(A_l \mathbf{z} + \mathbf{b}_l)$ given that $A_l \in \mathbb{R}^{d_{l+1} \times d_l}$ and $\mathbf{b}_l \in \mathbb{R}^{d_{l+1}}$, $l = 1, \cdots, S$. The function σ denotes the activation (such as ReLU), applied component-wise. Evidently, in our notation $d_1 = d$ and $d_{S+1} = \kappa$. With this setup, we proceed to undertake the theoretical analysis of our approach. Please find the detailed proofs in Appendix C.

Definition 1 (Perturbation). *Given any $\mathbf{x}_1 \in \mathcal{X}$, an ε-perturbation corresponding to $\mathbf{x}_1$ is the set of points $\mathbf{x}_1(\varepsilon) \subset \mathcal{X}$ such that $\|\mathbf{x}_1 - \mathbf{x}_2\| = \varepsilon, \forall \mathbf{x}_2 \in \mathbf{x}_1(\varepsilon); \varepsilon > 0$.*

For the particular choice of the l_2 norm, Definition 1 characterizes ε-perturbation as a hollow ball of radius $\varepsilon = \epsilon\sqrt{d}$ around a given point.

Lemma 1 (Lipschitz networks ensure bounded IBP). *Let $\overline{\mathbf{x}}$ and $\underline{\mathbf{x}}$ be ε-perturbations of $\mathbf{x} \sim \mathbb{P}_X$ for an $\varepsilon > 0$ (i.e. $\overline{\mathbf{x}}, \underline{\mathbf{x}} \in \mathbf{x}(\varepsilon)$). Given that the activation σ is Lipschitz continuous (such as ReLU) with constant $c_\sigma > 0$, there exists a constant $D = D(c_\sigma; A_1, A_2, \cdots, A_S; \varepsilon)$ such that $\underline{f}_{\theta^S}(\mathbf{x}, \varepsilon)$ and $\overline{f}_{\theta^S}(\mathbf{x}, \varepsilon)$) will at most be an $\hat{\varepsilon}$-perturbed version of $f_{\theta^S}(\mathbf{x})$, where $\hat{\varepsilon} = \varepsilon D$.*

The minimization objective function of IBI can be rephrased as $\mathcal{L} = \mathcal{L}_{CE} + \omega_1 \mathcal{L}_{LB} + \omega_2 \mathcal{L}_{UB}$, where $\omega_1, \omega_2 \geq 0$ are Lagrangian multipliers. The forthcoming result, however, relies on the constrained formulation (Boyd & Vandenberghe, 2004) of the objective as $\min\{\mathcal{L}_{CE}\}$ subject to $\mathcal{L}_{LB} \leq t_1$ and $\mathcal{L}_{UB} \leq t_2$, where $t_1, t_2 \geq 0$. Lemma 1 implies that the two losses ($\mathcal{L}_{UB}$ and $\mathcal{L}_{LB}$) appearing

in the constraints can always be made arbitrarily small, depending upon ε. Hence, we present a generalization bound on the sample classification loss in Theorem 1.

Theorem 1 (Generalization bound). *Let $\tilde{\mathbb{P}}$ be the joint distribution of $(f_{\theta^S}(X), Y)$, supported on $\mathcal{H} \times \mathbb{R}$. For a bounded loss function $\mathcal{L}_{CE} : \mathbb{R} \times \mathbb{R} \to [0, a](a \geq 0)$, if the neural network-induced map $f_{\theta^{L-S}}$ is such that $\left|\nabla f_{\theta^{L-S}}(\cdot)\right| < \infty$, we ensure:*

$$\left| \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{H}_i^*), y_i) - \int_{\mathcal{H} \times \mathbb{R}} \mathcal{L}_{CE}(f_{\theta^{L-S}}(x), y) d\tilde{\mathbb{P}}(x, y) \right|$$

$$\leq \tilde{\lambda} + 2^{L-S+1} \sqrt{\frac{2 \log(2k+2)}{N}} + a \sqrt{\frac{2 \log(\frac{2}{\delta})}{N}}$$

holds with probability at least $1 - \delta$ where $\tilde{\lambda} = \tilde{\lambda}(\hat{\varepsilon}, \lambda)$.

Theorem 1 implies that the absolute difference between the sample and the population risk, when deviated from $\tilde{\lambda}$, turns out to be $\mathcal{O}(N^{-\frac{1}{2}})$ with high probability. In practice, $\tilde{\lambda}$ depending on the user-defined parameter ε, can be made arbitrarily small.

5 EXPERIMENTS

Experiment protocol: The experiments are conducted on few-task few-shot image classification datasets, viz. a subset of the miniImageNet dataset called miniImageNet-S (Yao et al., 2022), and two medical images datasets namely DermNet-S (Yao et al., 2022), and ISIC (Codella et al., 2018; Li et al., 2020). We begin our experiments with a few analyses and ablations to better understand the properties of our proposed method. We then empirically demonstrate the effectiveness of our proposed IBI method on the gradient-based meta-learning method MAML (Finn et al., 2017) as well as the prototype-based metric-learner ProtoNet (Snell et al., 2017) to show that IBI can be seamlessly integrated with multiple few-shot learning paradigms. For our experiments, we employ the commonly used "4-CONV" network (Vinyals et al., 2016) as well as the larger ResNet-12 network (Lee et al., 2019) to demonstrate the scalability of the proposed method (further details on scalability in Appendix E). We perform 5-way 1-shot and 5-way 5-shot classification on all the above datasets (except ISIC where we use 2-way classification problems, similar to Yao et al. (2021), due to the lack of sufficient training classes). Further discussion on the datasets and implementation details of IBI along with the choice of hyperparameters can be found in the Appendix.

Ablation studies on task interpolation: We undertake an ablation study to highlight the importance of generating artificial tasks using IBP bound–based interpolation by comparing IBI with (1) inter-task interpolation on images, (2) inter-task interpolation

Table 2: Ablation on task interpolation strategies in terms of mean Accuracy and average median distance between original and interpolated tasks over 600 tasks on miniImageNet-S (mIS), ISIC and DermNet-S (DS).

Algorithm	Accuracy			Average median distance		
	mIS	ISIC	DS	mIS	ISIC	DS
MAML+Inter-task interpolation in image space	40.90%	55.25%	48.30%	N/A	N/A	N/A
MAML+Inter-task interpolation after f_{θ^S}	41.00%	61.33%	47.43%	3.08	1.23	2.99
MAML+MLTI (Yao et al., 2022)	41.58%	61.79%	48.03%	3.24	1.36	3.05
MAML+IBI without $\mathcal{L}_{UB}$ and $\mathcal{L}_{LB}$ losses	35.26%	48.94%	41.30%	N/A	N/A	N/A
MAML+IBI (ours)	**42.20%**	**68.58%**	**49.13%**	**2.74**	**0.60**	**2.65**

The Average median distance is calculated with features after the third block for all cases.

in the feature embedding learned by f_θ^S, (3) MLTI (Yao et al., 2022), which performs MixUp (Zhang et al., 2017) at randomly chosen layers of the learner, and (4) IBP bound–based interpolation without minimizing the $\mathcal{L}_{UB}$ and $\mathcal{L}_{LB}$ while only optimizing $\mathcal{L}_{CE}$. We perform the ablation study on 5-way 1-shot classification with the "4-CONV" network on miniImageNet-S, ISIC, and DermNet-S. From Table 2, we observe that IBI performs best in all cases. Moreover, inter-class interpolation at the same fixed layer S as IBI and at randomly selected task-specific layers in MLTI shows worse performance, demonstrating the superiority of the proposed interval bound–based interpolation mechanism. Further, it is interesting to observe that IBI, when performed without minimizing the $\mathcal{L}_{UB}$ and $\mathcal{L}_{LB}$, performs the worst. This behavior is not unexpected as the neighborhoods are no

longer guaranteed to be preserved by the learned embedding in this case, thus potentially resulting in the generation of out-of-manifold artificial tasks.

To further check whether the tasks generated by IBI indeed follow the distribution, we undertake an additional comparison based on the similarity of the artificial tasks with the corresponding original tasks. Concretely, we define the distance between a task and its artificial counterpart as the median of the pairwise distances between the corresponding data instances in the two tasks. If an artificial task is created by combining two tasks, *a la* MLTI (Yao et al., 2022), we consider the smaller of the two median distances. We observe from Table 2, that the average median distance over 600 tasks is smaller for the proposed method compared to MLTI, as well as inter-task interpolation in the feature embedding learned by f_θ^S. This indicates that the tasks generated by IBI are more likely to lie close to the original task distribution.

Importance of dynamic loss weighting:
To validate the usefulness of softmax-based dynamic weighting of the three losses for both IBP and IBI, we first find the average weights for each loss in a dynamic weight run and then plug in the respective values as static weights for new runs. All experiments in Table 3 are conducted on the miniImageNet-S dataset. From the upper half of Table 3, we can see that the three average weights are always distinct with a definite trend in that $\mathcal{L}_{CE}$ gets maximum importance followed by $\mathcal{L}_{UB}$ while $\mathcal{L}_{LB}$ contributes very little to the total loss $\mathcal{L}$.

Table 3: Average loss weights for the two proposed methods, and a comparison of the static weighting and dynamic weighting versions, including transferability of static weight values across variants.

	MAML+IBP	MAML+IBI
Average of dynamic loss weights calculated for IBP and IBI.		
w_{CE}	0.8600	0.8658
w_{UB}	0.1369	0.1314
w_{LB}	0.0029	0.0027
Accuracy of algorithms with different weight choices.		
Dynamic weighting	**41.30±0.79%**	**42.20±0.82%**
Static average weights for MAML+IBP	40.55±0.81%	N/A
Static average weights for MAML+IBI	N/A	40.72±0.79%

This may be due to the particular "4-CONV" architecture used in this study which employs ReLU activations, thus implicitly limiting the spread of the lower bound (Gowal et al., 2019). Further, the average weights of IBP and IBI are similar for a particular learner highlighting their commonalities, while they are distinct over different learners stressing their learner-dependent behavior. Further, in the lower half of Table 3, we explore the effect of using static weights as well as the transferability of the loss weights across learners. In all cases, the softmax-based dynamic weighting outperforms static weighting, thus demonstrating the importance of dynamic weighting.

Results on few-task few-shot classification problems: For evaluating the few-shot classification performance of IBI in few-task situations, we compare against the regularization-based meta-learning methods TAML (Jamal & Qi, 2019), Meta-Reg (Yin et al., 2019), and Meta-Dropout (Lee et al., 2020) for MAML. We also compare against data augmentation–based methods like MetaMix (Yao et al., 2021), Meta-Maxup (Ni et al., 2021), and MLTI (Yao et al., 2022) for both MAML and ProtoNet. The results in Table 4 show that in keeping with the observation in Table 1, IBP without task interpolation can improve upon the corresponding baselines. The incorporation of IBP-based task interpolation in IBI generally improves the results even further. Overall, we observe that both IBP and IBI outperform the other competitors, with the largest gains being observed for the ISIC dataset.

Cross-domain transferability analysis: The miniImageNet-S and DermNet-S datasets both allow 5-way 1-shot classification. Moreover, miniImageNet-S contains images from natural scenes while DermNet-S consists of medical images. Therefore, we undertake a cross-domain transferability study in Table 5. We summarize the Accuracy values obtained by a source model trained on DermNet-S but tested on miniImageNet-S and vice-versa (denoted DS $\rightarrow$ mIS and mIS $\rightarrow$ DS, respectively). We can see that in most cases the IBP variant is able to improve upon the corresponding baseline. Further, the interpolation-based methods, i.e. MLTI and IBI are able to further improve performance, with IBI achieving the best performance in most cases, thus

Table 5: Transferability comparison of MAML and ProtoNet, with their MLTI, IBP, and IBI variants in terms of Accuracy over 600 tasks.

Algorithms	Accuracy	
	DS $\rightarrow$ mIS	mIS $\rightarrow$ DS
MAML	25.06%	33.40%
MAML+MLTI (Yao et al., 2022)	30.03%	**36.74%**
MAML+IBP (Ours)	27.06%	33.90%
MAML+IBPI (Ours)	**30.23%**	36.21%
ProtoNet	28.76%	34.03%
ProtoNet*+MLTI (Yao et al., 2022)	30.06%	35.46%
ProtoNet+IBP (Ours)	29.60%	34.13%
ProtoNet+IBPI (Ours)	**30.32%**	**35.63%**

*: ProtoNet implementation as per Yao et al. (2022).

showing that IBI training can improve cross-domain transferability.

Table 4: Performance comparison of the proposed method with baselines and contending algorithms in terms of mean Accuracy over 600 tasks.

Backbone Network	Algorithm	miniImageNet-S		ISIC		DermNet-S	
		1-shot	5-shot	1-shot	5-shot	1-shot	5-shot
4-CONV	MAML (Finn et al., 2017; Yao et al., 2022)	38.27%	52.14%	57.59%	65.24%	43.47%	60.56%
	MAML+Meta-Reg (Yin et al., 2019; Yao et al., 2022)	38.35%	51.74%	58.57%	68.45%	45.01%	60.92%
	TAML (Jamal & Qi, 2019; Yao et al., 2022)	38.70%	52.75%	58.39%	66.09%	45.73%	61.14%
	MAML+Meta-Dropout (Lee et al., 2020; Yao et al., 2022)	38.32%	52.53%	58.40%	67.32%	44.30%	60.86%
	MAML+MetaMix (Yao et al., 2021; 2022)	39.43%	54.14%	60.34%	69.47%	46.81%	63.52%
	MAML+Meta-Maxup (Ni et al., 2021; Yao et al., 2022)	39.28%	53.02%	58.68%	69.16%	46.10%	62.64%
	MAML+MLTI (Yao et al., 2022)	41.58%	55.22%	61.79%	70.69%	48.03%	64.55%
	MAML+IBP (ours)	41.30%	54.36%	64.91%	78.75%	48.33%	63.33%
	MAML+IBI (ours)	**42.20%**	**55.23%**	**68.58%**	**79.75%**	**49.13%**	**65.43%**
	ProtoNet* (Snell et al., 2017; Yao et al., 2022)	36.26%	50.72%	58.56%	66.25%	44.21%	60.33%
	ProtoNet (Snell et al., 2017)	40.70%	53.16%	65.58%	75.25%	46.86%	62.03%
	ProtoNet*+MetaMix (Yao et al., 2021; 2022)	39.67%	53.10%	60.58%	70.12%	47.71%	62.68%
	ProtoNet*+Meta-Maxup (Ni et al., 2021; Yao et al., 2022)	39.80%	53.35%	59.66%	68.97%	46.06%	62.97%
	ProtoNet*+MLTI (Yao et al., 2022)	41.36%	55.34%	62.82%	71.52%	49.38%	65.19%
	ProtoNet+IBP (ours)	41.46%	55.00%	**70.75%**	81.01%	48.66%	**67.26%**
	ProtoNet+IBI (ours)	**43.30%**	**55.73%**	70.25%	**81.16%**	**51.13%**	65.93%
ResNet-12	MAML (Finn et al., 2017; Yao et al., 2022)	40.02%	52.56%	59.41%	67.66%	47.58%	63.13%
	MAML+MetaMix (Yao et al., 2021; 2022)	42.26%	54.65%	62.06%	72.18%	51.40%	64.82%
	MAML+MetaMaxup (Ni et al., 2021; Yao et al., 2022)	41.97%	53.92%	61.64%	72.04%	50.82%	64.24%
	MAML+MLTI (Yao et al., 2022)	43.35%	54.89%	63.25%	73.56%	52.03%	65.12%
	MAML+IBP (ours)	43.50%	55.13%	**64.50%**	73.91%	50.40%	65.40%
	MAML+IBI (ours)	**43.90%**	**57.00%**	62.16%	**75.66%**	**52.10%**	**66.50%**
	ProtoNet* (Snell et al., 2017; Yao et al., 2022)	40.96%	53.77%	61.91%	72.97%	48.65%	64.61%
	ProtoNet (Snell et al., 2017)	42.60%	55.00%	63.01%	75.91%	50.66%	65.40%
	ProtoNet*+MetaMix (Yao et al., 2021; 2022)	42.95%	56.95%	65.55%	78.33%	51.18%	66.80%
	ProtoNet*+MetaMaxup (Ni et al., 2021; Yao et al., 2022)	42.68%	56.07%	64.17%	77.62%	50.96%	66.38%
	ProtoNet*+MLTI (Yao et al., 2022)	44.08%	57.14%	66.02%	79.15%	52.01%	67.28%
	ProtoNet+IBP (ours)	43.33%	57.40%	66.66%	81.00%	51.33%	67.57%
	ProtoNet+IBI (ours)	**45.33%**	**58.23%**	**66.75%**	**81.83%**	**52.53%**	**68.00%**

* ProtoNet implementation as per Yao et al. (2022).

6 CONCLUSION AND FUTURE WORKS

In this paper, we attempt to explore the utility of IBP beyond its originally-intended usage for building and verifying classifiers that are provably robust against adversarial attacks. In summary, we identify the potential of IBP to conserve a neighborhood from the input image space to the learned feature space through the layers of a deep neural network by minimizing the distances of the feature embedding from the two bounds. This can be effective in few-shot classification problems to obtain feature embeddings where task neighborhoods are preserved, thus enabling easy adaptability to unseen tasks. Further, since interpolating between training tasks and their corresponding IBP bounds can yield artificial tasks with a higher chance of lying on the task manifold, we exploit this property of IBP to prevent overfitting to seen tasks in the few-task scenario. The resulting IBI training scheme is shown to be effective in both the meta-learning and metric-learning paradigms of few-shot learning.

We demonstrate in our results that IBI can be effectively scaled to relatively large networks like ResNet-12 as we typically only need to apply IBP to a few initial layers (see Appendix E). However, this still adds extra computational cost which scales linearly with the number of layers subjected to IBP. Therefore, to limit the additional complexity and computational cost, a future direction of research may be to investigate the applicability of more advanced provably robust training methods that yield more efficient and tighter bounds (Lyu et al., 2021). Moreover, few-shot learners can also be improved with adaptive hyperparameters (Baik et al., 2020), feature reconstruction (Lee & Chung, 2021), knowledge distillation (Tian et al., 2020), embedding propagation (Rodríguez et al., 2020), etc. Thus, it may be interesting to observe the performance gains from these orthogonal techniques when coupled with IBI. However, this may not be a straightforward endeavor, given the complex dynamic nature of such frameworks.

REPRODUCIBILITY STATEMENT

We have included the pseudo-codes and PyTorch based Python implementation for the proposed method in Appendices B and G, respectively. The description of all datasets used in this study along

with other key implementation details are available in Appendices D, E. The hyperparameter settings for different algorithms along with their tuning strategy are listed in Appendix F. For the theoretical analyses, complete proofs are provided in Appendix C.

REFERENCES

Kelsey Allen, Evan Shelhamer, Hanul Shin, and Joshua Tenenbaum. Infinite mixture prototypes for few-shot learning. In *International Conference on Machine Learning*, pp. 232–241. PMLR, 2019.

Sungyong Baik, Myungsub Choi, Janghoon Choi, Heewon Kim, and Kyoung Mu Lee. Meta-learning with adaptive hyperparameters. *Advances in Neural Information Processing Systems*, 33: 20755–20765, 2020.

Luca Bertinetto, Joao F. Henriques, Philip Torr, and Andrea Vedaldi. Meta-learning with differentiable closed-form solvers. In *International Conference on Learning Representations*, 2019.

Stephen Boyd and Lieven Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

Noel CF Codella, David Gutman, M Emre Celebi, Brian Helba, Michael A Marchetti, Stephen W Dusza, Aadi Kalloo, Konstantinos Liopyris, Nabin Mishra, Harald Kittler, et al. Skin lesion analysis toward melanoma detection: A challenge at the 2017 international symposium on biomedical imaging (isbi), hosted by the international skin imaging collaboration (isic). In *2018 IEEE 15th international symposium on biomedical imaging (ISBI 2018)*, pp. 168–172. IEEE, 2018.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International conference on machine learning*, pp. 1126–1135. PMLR, 2017.

Sven Gowal, Krishnamurthy (Dj) Dvijotham, Robert Stanforth, Rudy Bunel, Chongli Qin, Jonathan Uesato, Relja Arandjelovic, Timothy Mann, and Pushmeet Kohli. Scalable verified training for provably robust image classification. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, October 2019.

Erin Grant, Chelsea Finn, Sergey Levine, Trevor Darrell, and Thomas Griffiths. Recasting gradient-based meta-learning as hierarchical bayes. In *International Conference on Learning Representations*, 2018.

Muhammad Abdullah Jamal and Guo-Jun Qi. Task agnostic meta-learning for few-shot learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11719–11727, 2019.

Dong Hoon Lee and Sae-Young Chung. Unsupervised embedding adaptation via early-stage feature reconstruction for few-shot classification. In *International Conference on Machine Learning*, pp. 6098–6108. PMLR, 2021.

Hae Beom Lee, Taewook Nam, Eunho Yang, and Sung Ju Hwang. Meta dropout: Learning to perturb latent features for generalization. In *International Conference on Learning Representations*, 2020.

Kwonjoon Lee, Subhransu Maji, Avinash Ravichandran, and Stefano Soatto. Meta-learning with differentiable convex optimization. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 10657–10665, 2019.

Xiaomeng Li, Lequan Yu, Yueming Jin, Chi-Wing Fu, Lei Xing, and Pheng-Ann Heng. Difficulty-aware meta-learning for rare disease diagnosis. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 357–366. Springer, 2020.

Zhenguo Li, Fengwei Zhou, Fei Chen, and Hang Li. Meta-SGD: Learning to learn quickly for few-shot learning. *arXiv preprint arXiv:1707.09835*, 2017.

Zhaoyang Lyu, Minghao Guo, Tong Wu, Guodong Xu, Kehuan Zhang, and Dahua Lin. Towards evaluating and training verifiably robust neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 4308–4317, June 2021.

Renkun Ni, Micah Goldblum, Amr Sharaf, Kezhi Kong, and Tom Goldstein. Data augmentation for meta-learning. In *International Conference on Machine Learning*, pp. 8152–8161. PMLR, 2021.

Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms. *arXiv preprint arXiv:1803.02999*, 2018.

Jaehoon Oh, Hyungjun Yoo, ChangHwan Kim, and Se-Young Yun. {BOIL}: Towards representation change for few-shot learning. In *International Conference on Learning Representations*, 2021.

Viraj Prabhu, Anitha Kannan, Murali Ravuri, Manish Chaplain, David Sontag, and Xavier Amatriain. Few-shot learning for dermatological disease diagnosis. In *Proceedings of the 4th Machine Learning for Healthcare Conference*, volume 106, pp. 532–552. PMLR, 2019.

Mengye Ren, Eleni Triantafillou, Sachin Ravi, Jake Snell, Kevin Swersky, Joshua B Tenenbaum, Hugo Larochelle, and Richard S Zemel. Meta-learning for semi-supervised few-shot classification. *arXiv preprint arXiv:1803.00676*, 2018.

Pau Rodríguez, Issam Laradji, Alexandre Drouin, and Alexandre Lacoste. Embedding propagation: Smoother manifold for few-shot classification. In *European Conference on Computer Vision*, pp. 121–138. Springer, 2020.

Sam T Roweis and Lawrence K Saul. Nonlinear dimensionality reduction by locally linear embedding. *Science*, 290(5500):2323–2326, 2000.

Victor Garcia Satorras and Joan Bruna Estrach. Few-shot learning with graph neural networks. In *International Conference on Learning Representations*, 2018.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. *Advances in neural information processing systems*, 30, 2017.

Teruo Sunaga. Theory of an interval algebra and its application to numerical analysis. *RAAG memoirs*, 2:29–46, 1958.

Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip H.S. Torr, and Timothy M. Hospedales. Learning to compare: Relation network for few-shot learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

Joshua B Tenenbaum, Vin de Silva, and John C Langford. A global geometric framework for nonlinear dimensionality reduction. *Science*, 290(5500):2319–2323, 2000.

Yonglong Tian, Yue Wang, Dilip Krishnan, Joshua B Tenenbaum, and Phillip Isola. Rethinking few-shot image classification: a good embedding is all you need? In *European Conference on Computer Vision*, pp. 266–282. Springer, 2020.

Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. *Advances in neural information processing systems*, 29, 2016.

Stephan Wojtowytsch and Weinan E. On the banach spaces associated with multi-layer relu networks: Function representation, approximation theory and gradient descent dynamics. *arXiv preprint arXiv:2007.15623*, 2020.

Huaxiu Yao, Long-Kai Huang, Linjun Zhang, Ying Wei, Li Tian, James Zou, Junzhou Huang, et al. Improving generalization in meta-learning via task augmentation. In *International Conference on Machine Learning*, pp. 11887–11897. PMLR, 2021.

Huaxiu Yao, Linjun Zhang, and Chelsea Finn. Meta-learning with fewer tasks through task interpolation. In *International Conference on Learning Representations*, 2022.

Mingzhang Yin, George Tucker, Mingyuan Zhou, Sergey Levine, and Chelsea Finn. Meta-learning without memorization. *arXiv preprint arXiv:1912.03820*, 2019.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *arXiv preprint arXiv:1710.09412*, 2017.

A Prototype-based metric-learning:

Metric-based few-shot learning aims to obtain a feature embedding of the task manifold suitable for non-parametric classification. Prototype-based metric-learning, specifically Prototypical Network (ProtoNet) (Snell et al., 2017), assigns a query point to the class having the nearest (in terms of Euclidean distance) prototype in the learned embedding space. Given the model f_θ and a task $\mathcal{T}_i$, we first compute class prototypes $\{c_k\}_{k=1}^K$ as the mean of $f_\theta(x_{i,r}^s)$ for the instances $x_{i,r}^s$ belonging to class k:

$$c_k = \frac{1}{N_s} \sum\nolimits_{(x_{i,r}^s, y_{i,r}^s) \in \mathcal{D}_i^{s,k}} f_\theta(x_{i,r}^s), \tag{10}$$

where $\mathcal{D}_i^{s,k} \subset \mathcal{D}_i^s$ represents the subset of N_s support samples from class k. Given a sample $x_{i,r}^q$ from the query set, the probability $p(y_{i,r}^q = k | x_{i,r}^q)$ of assigning it to the k-th class is calculated using the distance function $d(.,.)$ between the representation $f_\theta(x_{i,r}^q)$ and the prototype c_k:

$$p(y_{i,r}^q = k | x_{i,r}^q, f_\theta) = \frac{\exp(-d(f_\theta(x_{i,r}^q), c_k))}{\sum_{k'} \exp(-d(f_\theta(x_{i,r}^q), c_{k'}))}. \tag{11}$$

Thereafter, the parameters θ for the model f_θ can be trained by minimizing cross-entropy loss (2). In the testing stage, each query sample $x_{j,r}^q$ is assigned to the class having the maximal probability, i.e., $y_{j,r}^q = \arg\max_k p(y_{j,r}^q = k | x_{j,r}^q)$.

B Algorithms of MAML and ProtoNet coupled with IBP and IBI

The steps for MAML+IBP/IBI and ProtoNet+IBP/IBI are respectively presented in Algorithm 1 and 2. Please consult the main paper for various notations and equations used in the algorithms.

Remark 1. The way in which the training support set $\mathcal{D}_i^s$ informs the loss calculation on the corresponding query set $\mathcal{D}_i^q$ differs between the MAML and ProtoNet variants. While a limited number of training steps on the support set is undertaken to obtain the model f_{ϕ_i} where the loss is calculated on the query set for MAML, the support set is used to calculate the prototypes $\{c_k\}_{k=1}^K$ for the loss calculation on the query set for ProtoNet.

C Proof of Lemmas and Theorems

Interval bound propagation for networks with affine layer: Let us assume a network f with L layers where the 0-th layer denotes the initial input. Let us also consider a layer $l \le L$ that is not the 0-th input layer. The 0-th layer of f takes the input along with its perturbed counterparts as shown in Section 3 in the main paper. If at the end of $l-1$-th layer the activation, upper bound, and lower bound are respectively z_{l-1}, $\overline{z}_{l-1}$ and $\underline{z}_{l-1}$. If the l-th layer performs an affine transformation (such as a convolutional, fully connected, batch normalization, etc.) followed by a monotonic activation function (such as ReLU, sigmoid, tanh, etc.) i.e. $z_l = \sigma(A_l z_{l-1} + b_l)$, then as per Gowal et al. (2019), we can calculate the interval bounds for the subsequent l-th layer as follows:

$$\underline{z}_l = \sigma(\mu_l - \psi_l), \tag{12}$$
$$\overline{z}_l = \sigma(\mu_l + \psi_l), \text{ where,} \tag{13}$$
$$\psi_l = |A_l|\psi_{l-1},$$
$$\mu_l = A_l \mu_{l-1} + b_l, \text{ given,}$$
$$\mu_{l-1} = \frac{\underline{z}_{l-1} + \overline{z}_{l-1}}{2},$$
$$\psi_{l-1} = \frac{\underline{z}_{l-1} - \overline{z}_{l-1}}{2}.$$

Algorithm 1 IBP/IBI for MAML training

Requires: Task distribution $p(\mathcal{T})$, batch size B, learning rates η_0 and η_1, interval coefficient ϵ.

1: Randomly initialize the meta-learner parameters θ.
2: **while** not converged **do**
3:     Sample a batch of B tasks from the distribution $\rho(\mathcal{T})$.
4:     For IBI, randomly sample an index $1 \leq m \leq B$ to perform the interpolation.
5:     **for** all $i \in \{1, 2, \cdots, B\}$ **do**
6:         Initialize base learner to meta-learner state.
7:         Sample a support set $\mathcal{D}_i^s$ of data-label pairs $\{(\mathbf{x}_{i,r}^s, \mathbf{y}_{i,r}^s)\}_{r=1}^{N_s}$ from task $\mathcal{T}_i$.
8:         Calculate the classification loss $\mathcal{L}_{CE}$ using $f_\theta(\mathbf{x}_{i,r}^s)$ and $\mathbf{y}_{i,r}^s$.
9:         **if** $i = m$ **then**
10:            Generate interpolated support and query instances $\mathbf{H}_{i,r}^{s'}$ and $\mathbf{H}_{i,r}^{s'}$ using (9).
11:            Calculate classification loss $\mathcal{L}_{CE}'$ using $f_{\theta^{L-S}}(\mathbf{H}_{i,r}^{s'})$ and $\mathbf{y}_{i,r}^s$.
12:            Set $\mathcal{L}_{CE} = \frac{1}{2}(\mathcal{L}_{CE} + \mathcal{L}_{CE}')$.
13:         **end if**
14:         Update base learner parameters to $\phi_i = \theta - \eta_0 \nabla_\theta \mathcal{L}_{CE}$.
15:         Sample a query set $\mathcal{D}_i^q$ of data-label pairs $\{(\mathbf{x}_{i,r}^q, \mathbf{y}_{i,r}^q)\}_{r=1}^{N_q}$ from task $\mathcal{T}_i$.
16:         Calculate the classification loss $\mathcal{L}_{CE}$ with $f_{\phi_i}(\mathbf{x}_{i,r}^q)$ and $\mathbf{y}_{i,r}^q$.
17:         Calculate $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$ respectively using (5) and (6).
18:         **if** $i = m$ **then**
19:            Calculate classification loss $\mathcal{L}_{CE}'$ using $f_{\phi^{L-S}}(\mathbf{H}_{i,r}^{q'})$ and $\mathbf{y}_{i,r}^q$.
20:            Set $\mathcal{L}_{CE} = \frac{1}{2}(\mathcal{L}_{CE} + \mathcal{L}_{CE}')$.
21:         **end if**
22:         Calculate $\mathcal{L}$ by accumulating $\mathcal{L}_{CE}$, $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$ using (7).
23:     **end for**
24:     Update meta-learner parameters $\theta = \theta - \eta_1 \frac{1}{B} \sum_{i=1}^{B} \nabla_\theta \mathcal{L}$.
25: **end while**

Algorithm 2 IBP/IBI for ProtoNet training

Requires: Task distribution $p(\mathcal{T})$, learning rate η, interval coefficient ϵ.

1: Randomly initialize the learner parameters θ.
2: **while** not converged **do**
3:     For IBI, randomly select if interpolation is to be performed.
4:     Sample a support set $\mathcal{D}_i^s$ of data-label pairs $\{(\mathbf{x}_{i,r}^s, \mathbf{y}_{i,r}^s)\}_{r=1}^{N_s}$ from task $\mathcal{T}_i$.
5:     Calculate the features $f_{\theta^L}(\mathbf{x}_{i,r}^s)$ and find the prototypes $\{\mathbf{c}_k\}_{k=1}^K$ using (10).
6:     **if** interpolation to be performed **then**
7:         Generate interpolated support and query instances $\mathbf{H}_{i,r}^{s'}$ and $\mathbf{H}_{i,r}^{s'}$ using (9).
8:         Calculate features $f_{\theta^{L-S}}(\mathbf{H}_{i,r}^{s'})$ and find prototypes $\{\mathbf{c}_k'\}_{k=1}^K$.
9:     **end if**
10:     Sample a query set $\mathcal{D}_i^q$ of data-label pairs $\{(\mathbf{x}_{i,r}^q, \mathbf{y}_{i,r}^q)\}_{r=1}^{N_q}$ from task $\mathcal{T}_i$.
11:     Calculate the loss $\mathcal{L}_{CE}$ using (11) and (2).
12:     Calculate $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$ using (5) and (6).
13:     **if** interpolation to be performed **then**
14:         Calculate classification loss $\mathcal{L}_{CE}'$ with $f_{\theta^{L-S}}(\mathbf{H}_{i,r}^{q'})$, $\{\mathbf{c}_k'\}_{k=1}^K$ and $\mathbf{y}_{i,r}^q$ by (11) and (2).
15:         Set $\mathcal{L}_{CE} = \frac{1}{2}(\mathcal{L}_{CE} + \mathcal{L'}_{CE})$.
16:     **end if**
17:     Calculate $\mathcal{L}$ by accumulating $\mathcal{L}_{CE}$, $\mathcal{L}_{LB}$ and $\mathcal{L}_{UB}$ using (7).
18:     Update learner parameters $\theta = \theta - \eta \nabla_\theta \mathcal{L}$.
19: **end while**

Lemma 1 (Lipschitz networks ensure bounded IBP). *Let $\overline{\mathbf{x}}$ and $\underline{\mathbf{x}}$ be ε-perturbations of $\mathbf{x} \sim \mathbb{P}_X$ for an $\varepsilon > 0$ (i.e. $\overline{\mathbf{x}}, \underline{\mathbf{x}} \in \mathbf{x}(\varepsilon)$). Given that the activation σ is Lipschitz continuous (such as ReLU)*

with constant $c_\sigma > 0$, there exists a constant $D = D(c_\sigma; A_1, A_2, \cdots, A_S; \varepsilon)$ such that $\underline{f}_{\theta^S}(\mathbf{x}, \varepsilon)$ and $\overline{f}_{\theta^S}(\mathbf{x}, \varepsilon))$ will at most be an $\hat{\varepsilon}$-perturbed version of $f_{\theta^S}(\mathbf{x})$, where $\hat{\varepsilon} = \varepsilon D$.

Proof. Given that $\mathbf{x}_1, \mathbf{x}_2 \in \mathcal{X}$

$$
\begin{aligned}
\left\| h_1(\mathbf{x}_1) - h_1(\mathbf{x}_2) \right\| &= \left\| \sigma(A_1 \mathbf{x}_1 + \mathbf{b}_1) - \sigma(A_1 \mathbf{x}_2 + \mathbf{b}_1) \right\| \\
&\leq c_\sigma \left\| A_1(\mathbf{x}_1 - \mathbf{x}_2) \right\| \\
&\leq c_\sigma \|A_1\| \|\mathbf{x}_1 - \mathbf{x}_2\|
\end{aligned}
\tag{14}
$$

where $\|A_1\| = \sup_{\|\mathbf{x}\|=1} \|A_1 \mathbf{x}\|$. The inequality 14 is due to the Lipschitz continuity of σ. Commonly used activation functions, such as ReLU, tend to satisfy this condition. In particular, for ReLU, $c_\sigma = 1$. As such, the map h_1 also turns out to be Lipschitz continuous. A similar argument also proves that h_l, $l = 2, \cdots, S$ all follow the same trait. As a result, f_{θ^S} also becomes Lipschitz continuous with accompanying constant $(c_\sigma A)^S$, where $A = \max\{\|A_l\|\}$.

The recurrence relation of extremities in IBP, as suggested by Gowal et al. (2019), can be written as:

$$
\overline{f}_{\theta^l}(\mathbf{x}, \varepsilon) = \sigma \left\{ \frac{(A_l + |A_l|)}{2} \overline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) + \frac{(A_l - |A_l|)}{2} \underline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) + \mathbf{b}_l \right\},
$$

$$
\text{and } \underline{f}_{\theta^l}(\mathbf{x}, \varepsilon) = \sigma \left\{ \frac{(A_l - |A_l|)}{2} \overline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) + \frac{\{A_l + |A_l|\}}{2} \underline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) + \mathbf{b}_l \right\},
$$

where the $|\cdot|$ operator results in a matrix with all elements replaced by their corresponding absolute values, and $l = 1, 2, ..., S$. Thus,

$$
\begin{aligned}
&\left\| \overline{f}_{\theta^l}(\mathbf{x}, \varepsilon) - f_{\theta^l}(\mathbf{x}) \right\| \\
=& \left\| \sigma \left\{ \frac{(A_l + |A_l|)}{2} \overline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) + \frac{(A_l - |A_l|)}{2} \underline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) + \mathbf{b}_l \right\} - \sigma \left(A_l f_{\theta^{l-1}}(\mathbf{x}) + \mathbf{b}_l \right) \right\| \\
\leq& c_\sigma \left\| \frac{(A_l + |A_l|)}{2} \overline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) + \frac{(A_l - |A_l|)}{2} \underline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) - A_l f_{\theta^{l-1}}(\mathbf{x}) \right\| \\
=& c_\sigma \left\| \frac{(A_l + |A_l|)}{2} \left(\overline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) - f_{\theta^{l-1}}(\mathbf{x}) \right) + \frac{(A_l - |A_l|)}{2} \left(\underline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) - f_{\theta^{l-1}}(\mathbf{x}) \right) \right\| \\
\leq& c_\sigma \left\{ \left\| \frac{(A_l + |A_l|)}{2} \left(\overline{f}_{1(\theta^{l-1}}(\mathbf{x}, \varepsilon) - f_{\theta^{l-1}}(\mathbf{x}) \right) \right\| + \left\| \frac{(|A_l| - A_l)}{2} \left(f_{\theta^{l-1}}(\mathbf{x}) - \underline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) \right) \right\| \right\} \\
\leq& c_\sigma \left\{ \left\| \frac{A_l + |A_l|}{2} \right\| \left\| \overline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) - f_{\theta^{l-1}}(\mathbf{x}) \right\| + \left\| \frac{|A_l| - A_l}{2} \right\| \left\| f_{\theta^{l-1}}(\mathbf{x}) - \underline{f}_{\theta^{l-1}}(\mathbf{x}, \varepsilon) \right\| \right\}.
\end{aligned}
$$

Observe that, in particular for $l = 1$

$$
\begin{aligned}
\left\| \overline{f}_{\theta^1}(\mathbf{x}, \varepsilon) - f_{\theta^1}(\mathbf{x}) \right\| &\leq c_\sigma \left\{ \left\| \frac{A_1 + |A_1|}{2} \right\| \|\overline{\mathbf{x}} - \mathbf{x}\| + \left\| \frac{|A_1| - A_1}{2} \right\| \|\mathbf{x} - \underline{\mathbf{x}}\| \right\} \\
&= c_\sigma \varepsilon \left\{ \left\| \frac{A_1 + |A_1|}{2} \right\| + \left\| \frac{|A_1| - A_1}{2} \right\| \right\} = \varepsilon_1 \text{ say,}
\end{aligned}
$$

i.e., the deviation in the first layer can be made arbitrarily small based on ε. The quantity $\left\| f_{\theta^1}(\mathbf{x}) - \underline{f}_{\theta^1}(\mathbf{x}, \varepsilon) \right\|$ can be shown to be upper bounded using a similar argument. In other words, both $\overline{f}_{\theta^1}(\mathbf{x}, \varepsilon)$ and $\underline{f}_{\theta^1}(\mathbf{x}, \varepsilon)$ are at most ε_1-perturbed from $f_{\theta^1}(\mathbf{x})$. By the method of induction we eventually get a $D = D(c_\sigma; A_1, A_2, \cdots, A_S; \varepsilon) > 0$ for which the lemma holds. $\qquad \square$

Theorem 1 (Generalization bound). *Let $\tilde{\mathbb{P}}$ be the joint distribution of $(f_{\theta^S}(X), Y)$, supported on $\mathcal{H} \times \mathbb{R}$. For a bounded loss function $\mathcal{L}_{CE} : \mathbb{R} \times \mathbb{R} \to [0, a](a \geq 0)$, if the neural network-induced*

map $f_{\theta^{L-S}}$ is such that $\left|\nabla f_{\theta^{L-S}}(\cdot)\right| < \infty$, we ensure:

$$\left|\frac{1}{N}\sum_{i=1}^{N}\mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{H}_i^*), y_i) - \int_{\mathcal{H}\times\mathbb{R}}\mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{x}), y)d\tilde{\mathbb{P}}(\mathbf{x}, y)\right|$$

$$\leq \tilde{\lambda} + 2^{L-S+1}\sqrt{\frac{2\log(2\kappa+2)}{N}} + a\sqrt{\frac{2\log(\frac{2}{\delta})}{N}}$$

holds with probability at least $1 - \delta$, where $\tilde{\lambda} = \tilde{\lambda}(\hat{\varepsilon}, \lambda)$.

Proof. Before beginning with the proof we point out that based on Definition 1, given $\varepsilon > 0$ and $\mathbf{x} \in \mathcal{X}$, any $\mathbf{x}' \in \mathbf{x}(\varepsilon)$ can be written as $\mathbf{x}' = \mathbf{x} + \eta(\varepsilon)$. For example, in the simplest case, $\eta(\varepsilon)$ can be a function in the family $\pm\epsilon\mathbf{1}$. Thus, in case of IBI, the $\underline{f}_{\theta^S}(\mathbf{x}_i, \varepsilon)$ and $\overline{f}_{\theta^S}(\mathbf{x}_i, \varepsilon)$ can both be expressed as $f_{\theta^S}(\mathbf{x}_i) + \eta(\hat{\varepsilon})$ with corresponding $\eta(\hat{\varepsilon})$. In essence $\mathbf{H}_i^* = (1-\lambda)f_{\theta^S}(\mathbf{x}_i) + \lambda(f_{\theta^S}(\mathbf{x}_i) + \eta(\hat{\varepsilon}))$, where $\lambda \in [0, 1]$. Now, we can observe that,

$$\begin{aligned}
f_{\theta^{L-S}}(\mathbf{H}_i^*) &= f_{\theta^{L-S}}\left((1-\lambda)f_{\theta^S}(\mathbf{x}_i) + \lambda\left[f_{\theta^S}(\mathbf{x}_i) + \eta(\hat{\varepsilon})\right]\right) \\
&= f_{\theta^{L-S}}\left(f_{\theta^S}(\mathbf{x}_i) + \lambda\eta(\hat{\varepsilon})\right) \\
&= f_{\theta^{L-S}}\left(f_{\theta^S}(\mathbf{x}_i)\right) + \lambda\nabla f_{\theta^{L-S}}\left(f_{\theta^S}(\mathbf{x}_i)\right)\eta(\hat{\varepsilon}),
\end{aligned}$$
(15)

where $\eta(\hat{\varepsilon}) \in \mathbb{R}^k$, $\hat{\varepsilon}$ being as mentioned in lemma 1. We obtain (15) by using the Taylor expansion of $f_{\theta^{L-S}}$ up to the first order. Given that $\left|\nabla f_{\theta^{L-S}}(\cdot)\right| < \infty$, the second term $\lambda\nabla f_{\theta^{L-S}}\left(f_{\theta^S}(\mathbf{x}_i)\right)\eta(\hat{\varepsilon})$ can be made arbitrarily small. The higher-order terms in the expansion all follow suit, which justifies their omission. Now,

$$\begin{aligned}
&\left|\frac{1}{N}\sum_{i=1}^{N}\mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{H}_i^*), y_i) - \int_{\mathcal{H}\times\mathbb{R}}\mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{x}), y)d\tilde{\mathbb{P}}(\mathbf{x}, y)\right| \\
&= \left|\frac{1}{N}\sum_{i=1}^{N}\left[\mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{H}_i^*), y_i) - \mathcal{L}_{CE}(f_{\theta^{L-S}}(f_{\theta^S}(\mathbf{x}_i)), y_i)\right]\right. \\
&\quad \left. + \frac{1}{N}\sum_{i=1}^{N}\mathcal{L}_{CE}(f_{\theta^{L-S}}(f_{\theta^S}(\mathbf{x}_i)), y_i) - \int_{\mathcal{H}\times\mathbb{R}}\mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{x}), y)d\tilde{\mathbb{P}}(\mathbf{x}, y)\right| \\
&\leq \frac{1}{N}\sum_{i=1}^{N}\left|\mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{H}_i^*), y_i) - \mathcal{L}_{CE}(f_{\theta^{L-S}}(f_{\theta^S}(\mathbf{x}_i)), y_i)\right| \\
&\quad + \left|\frac{1}{N}\sum_{i=1}^{N}\mathcal{L}_{CE}(f_{\theta^{L-S}}(f_{\theta^S}(\mathbf{x}_i)), y_i) - \int_{\mathcal{H}\times\mathbb{R}}\mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{x}), y)d\tilde{\mathbb{P}}(\mathbf{x}, y)\right|.
\end{aligned}$$
(16)

Since our networks use ReLU activation, the map induced by $f_{\theta^{L-S}}$ can be shown to be continuous. Given $\mathcal{H}$ is compact the output space also becomes compact. Restricted to such a space, the cross-entropy loss $\mathcal{L}_{CE}$ (similarly, regularized cross-entropy loss) turns out to be Lipschitz continuous. Consequently,

$$\begin{aligned}
|\mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{H}_i^*), y_i) &- \mathcal{L}_{CE}(f_{\theta^{L-S}}(f_{\theta^S}(\mathbf{x}_i)), y_i)| \\
&\leq c_L\left\|f_{\theta^{L-S}}(\mathbf{H}_i^*) - f_{\theta^{L-S}}\left(f_{\theta^S}(\mathbf{x}_i)\right)\right\| = \tilde{\lambda}(\hat{\varepsilon}, \lambda),
\end{aligned}$$
(17)

where $c_L > 0$ is the Lipschitz constant associated with $\mathcal{L}_{CE}$. Without loss of generality we can construct the map $f_{\theta^{L-S}}$ such that $\|f_{\theta^{L-S}}\| \leq 1$. Thus, using Corollary 3.14 of Wojtowytsch & E

(2020) we obtain:

$$\left| \frac{1}{N} \sum_{i=1}^{N} \mathcal{L}_{CE}(f_{\theta^{L-S}}(f_{\theta^{S}}(\mathbf{x}_i)), y_i) - \int_{\mathcal{H} \times \mathbb{R}} \mathcal{L}_{CE}(f_{\theta^{L-S}}(\mathbf{x}), y) d\tilde{\mathbb{P}}(\mathbf{x}, y) \right|$$

$$\leq 2^{L-S+1} \sqrt{\frac{2 \log(2\kappa + 2)}{N}} + a \sqrt{\frac{2 \log(\frac{2}{\delta})}{N}} \tag{18}$$

holds with probability at least $1 - \delta$. Combining (16), (17) and (18) we conclude the proof. □

D   DETAILS OF DATASETS USED IN THIS STUDY

miniImageNet: The miniImageNet dataset (Vinyals et al., 2016) is a commonly used subset of ImageNet (Deng et al., 2009) for evaluating few-shot classifiers. The dataset contains a total of 100 classes each containing 600 images of resolution $84 \times 84 \times 3$. Following the directives of Vinyals et al. (2016) from the total 100 classes 64 are kept in the Training set, 16 are retained for Validation, and the rest of the 20 classes are used for testing.

tieredImageNet: In (Ren et al., 2018) the authors proposed a new larger subset of ImageNet (Deng et al., 2009) for addressing the limitations of miniImageNet. In miniImageNet it is not ensured that the classes used for training are distinct from those contained in the Test set. Evidently, this contains the risk of information leakage and may not provide a fair evaluation of the few-shot classifier. As a remedy Ren et al. (2018) proposed to go higher in the class hierarchy in ImageNet. This enables tieredImageNet to use higher-level categories in the Training, Validation, and Test sets maintaining significant diversity between the three. In essence, a total of 608 ImageNet leaf-level classes are considered that can be categorized into 34 groups. Among these 34 higher-level groups, 20 are used for training, 6 are kept for validation, and the rest 8 are included in the Test set.

miniImageNet-S: This dataset is created by only using a subset of the original miniImageNet Training set for training the few-shot learner in a few-task scenario Yao et al. (2022).

```
Training Classes:  n03017168, n07697537, n02108915, n02113712,
n02120079, n04509417, n02089867, n03888605, n04258138, n03347037,
n02606052, n06794110
```

Validation and Test sets are kept as same as those used in miniImageNet.

DermNet-S: DermNet-S (Yao et al., 2022) is a subset of the "Dermnet Skin Disease Atlas" publicly available at `http://www.dermnet.com/`. The dataset after discarding the duplicates contains more than 22,000 medical images spread across 625 classes of dermatological diseases. Following the preprocessing suggested by Prabhu et al. (2019) the authors of (Yao et al., 2022) created DermNet-S by first extracting the 203 classes containing more than 30 images. Then from the long-tailed data distribution of the 203 disease classes, the top 30 larger classes are kept for training while the smaller 53 bottom classes are considered for meta-testing. The images are resized to $84 \times 84 \times 3$ to match the resolution of miniImageNet. We follow the same dataset construction strategy in our case. Moreover, we use random classes not included in the Training or Test set as the Validation set. The complete list of classes in the Training and Test sets are listed as follows:

```
Training Classes:  Seborrheic Keratoses Ruff, Herpes Zoster,
Atopic Dermatitis Adult Phase, Psoriasis Chronic Plaque, Eczema
Hand, Seborrheic Dermatitis, Keratoacanthoma, Lichen Planus,
Epidermal Cyst, Eczema Nummular, Tinea (Ringworm) Versicolor,
Tinea (Ringworm) Body, Lichen Simplex Chronicus, Scabies,
Psoriasis Palms Soles, Malignant Melanoma, Candidiasis large
Skin Folds, Pityriasis Rosea, Granuloma Annulare, Erythema
Multiforme, Seborrheic Keratosis Irritated, Stasis Dermatitis
and Ulcers, Distal Subungual Onychomycosis, Allergic Contact
Dermatitis, Psoriasis, Molluscum Contagiosum, Acne Cystic,
Perioral Dermatitis, Vasculitis, Eczema Fingertip

Testing Classes:  Warts, Ichthyosis Sex Linked, Atypical Nevi,
Venous Lake, Erythema Nodosum, Granulation Tissue, Basal Cell
```

```
Carcinoma Face, Acne Closed Comedo, Scleroderma, Crest Syndrome,
Ichthyosis Other Forms, Psoriasis Inversus, Kaposi Sarcoma,
Trauma, Polymorphous Light Eruption, Dermagraphism, Lichen
Sclerosis Vulva, Pseudomonas, Cutaneous Larva Migrans, Psoriasis
Nails, Corns, Lichen Sclerosus Penis, Staphylococcal Folliculitis,
Chilblains Perniosis, Psoriasis Erythrodermic, Squamous Cell
Carcinoma Ear, Basal Cell Carcinoma Ear, Ichthyosis Dominant,
Erythema Infectiosum, Actinic Keratosis Hand, Basal Cell Carcinoma
Lid, Amyloidosis, Spiders, Erosio Interdigitalis Blastomycetica,
Scarlet Fever, Pompholyx, Melasma, Eczema Trunk Generalized,
Metastasis, Warts Cryotherapy, Nevus Spilus, Basal Cell Carcinoma
Lip, Enterovirus, Pseudomonas Cellulitis, Benign Familial Chronic
Pemphigus, Pressure Urticaria, Halo Nevus, Pityriasis Alba,
Pemphigus Foliaceous, Cherry Angioma, Chapped Fissured Feet,
Herpes Buttocks, Ridging Beading
```

ISIC: Following Yao et al. (2022) for "ISIC 2018: Skin Lesion Analysis Towards Melanoma Detection" (Codella et al., 2018; Li et al., 2020) we select the third task where 10,015 medical images are categorized into seven classes based on lesion types. We first resize the images to $84 \times 84 \times 3$ to match the miniImageNet resolution. Then among the seven classes in the ISIC dataset, we select the 4 classes containing a higher number of samples for training while considering the rest for meta-testing as per the directives of Yao et al. (2022). Since there are only 4 classes in the Training set setting the number of ways to 2 results in six possible class combinations in a task. This in consequence offers an extreme few-task scenario. For hyper-parameter tuning random classes are used as a Validation set following the cross-validation-based approach employed in (Yao et al., 2022). The list of classes in the Training and the Test sets are listed as follows:

```
Training Set:  Nevus, Melanoma, Benign Keratoses, Basal Cell
Carcinoma
```

```
Testing Set:  Dermatofibroma, Pigmented Bowen's, Vascular
```

E   IMPLEMENTATION DETAILS

Scheduling of ϵ: In their paper Gowal et al. (2019) recommended starting with an initial perturbation $\epsilon_0 = 0$ and gradually increasing it to the intended perturbation ϵ over the training steps. In our case, we follow a similar approach for scheduling the value of perturbation ϵ_t at the t-th training step. We have observed that a fast increase in perturbation usually slows down training while a very slow increment fails to aid the learner. From extensive experimentation with various scheduling techniques such as linear, cosine, etc., we have found that the following strategy works well in practice. If the maximum allowed number of training steps is set to T then for the step t the perturbation ϵ_t is calculated as:

$$\epsilon_t = \begin{cases} \epsilon \text{ if } t > \lceil 0.9T \rceil \\ \frac{t}{0.9T}\epsilon \end{cases} \qquad . \tag{19}$$

In essence, we linearly increase ϵ_t starting from 0 up to ϵ over 90% of the maximum training steps T and keep it fixed at ϵ for the remainder of the training.

Frequency of interpolation for IBI variants: Performing IBP bound–based interpolation for every task during training may not be beneficial and may instead mislead the learner. For MAML, we have seen that performing interpolation once in every batch of B tasks aids the training process. In the case of ProtoNet, we have found that performing IBP bound–based interpolation with a 25% probability results in the best outcome.

Modifications to network architecture: We have used two networks for our experiments namely "4-CONV" and "ResNet-12". The "4-CONV" network can be seamlessly integrated with IBI for both MAML and ProtoNet. This network consists of 4 blocks, each having a convolution, batch normalization, max pooling, and ReLU in sequential order. IBI can be performed after any one of the blocks. The ResNet-12 network also consists of 4 blocks where a block (except the first one) receives inputs from (1) the output of the preceding block, and (2) the input of the preceding block through a skip connection. While the idea of applying IBI after any of the blocks seems appealing,

the presence of skip connections may hinder a straightforward integration of IBI in this case. To understand how ResNet-12 can be customized to accommodate MAML+IBP (and consequently MAML+IBI) we undertake an ablation study on the miniImageNet-S dataset in a 5-way 1-shot classification problem as described in Table 6. We can observe that in our initial hyperparameter tuning experiment, MAML+IBP can not match the performance of vanilla MAML on ResNet-12. Moreover, the performance gap increases as IBP is applied deeper into the network. This may be explained by the fact that the interval bounds become gradually loose as they progress through the network. Thus, with increasing depth, the magnitude of the bound losses (especially $\mathcal{L}_{UB}$ as the ReLU activations prevent $\mathcal{L}_{LB}$ from becoming too large) will largely outscale the classification loss and consequently affect convergence (see Remark 2). Applying IBP after only the first block still fails to achieve parity with the baseline because IBP induces a distortion in the feature space, due to its regularization effect. While the sequential part of the blocks after IBP can adapt to this distortion due to their complexity, the simpler skip paths can not do so. Hence, the effect of the distortion keeps propagating to the deeper blocks via skip connections. To aid the network in such a situation, we investigate three approaches to modify the skip connection immediately after the block(s) subjected to IBP, viz. (1) remove the skip connection for the subsequent block (2) introduce additional layers in the skip connection for the subsequent block to make it deeper and more complex (3) use a skip after one or more of the initial sub-block(s) (consisting sequentially of one convolution, one batch normalization, and one ReLU layer) of the next block. Among the three approaches, we empirically found that MAML+IBP (consequently MAML+IBI) performs best when the skip connection starts after the second sub-block in block 2. Due to the comparatively powerful learning strategy of ProtoNet, no such modifications to ResNet-12 are necessary for ProtoNet+IBI.

Table 6: Ablation study of ResNet-12 modifications for MAML+IBP on miniImageNet-S in terms of mean Accuracy over 600 tasks with 95% confidence interval.

Algorithm	IBP position	Accuracy
MAML	None (Baseline)	40.02±0.78%
MAML+IBP	after block 4	21.24±0.54%
MAML+IBP	after block 3	23.77±0.59%
MAML+IBP	after block 2	29.62±0.62%
MAML+IBP	after block 1	37.95±0.83%
MAML+IBP	after block 1 with no-skip at block 2	37.81±0.85%
MAML+IBP	after block 1 with deeper skip at block 2	38.54±0.81%
MAML+IBP	after block 1 with skip and output combination at block 2	40.50±0.83%
MAML+IBP	after block 1 with skip after 1 sub-block in block 2	42.18±0.82%
MAML+IBP	after block 1 with skip after 2 sub-blocks in block 2	**43.50±0.86%**

Remark 2. [Scalability of IBI] IBP (and consequently IBI) requires the propagation of the two interval bounds along with the input data. This introduces a computational overhead, especially in deeper networks. However, in practice even in a deeper network, we may not need to perform IBP except in the initial few layers, as the bound losses will optherwise overwhelm the classification loss and consequently impact convergence. To demonstrate this, we plot the losses (up to 5000 training steps for the ease of visualization) in the following Figure 5 for MAML+IBI using a ResNet-12 network for 5-way 1-shot miniImageNet-S classification, when IBP is applied up to blocks 1-4. We can see that the three losses have comparable scales only when IBP is applied after block 1. In all other cases, $\mathcal{L}_{UB}$ heavily dominates the total loss. But, due to its sheer magnitude, the optimizer is unable to minimize it. Thus, in practice, IBP should only be limited to a few initial layers in deeper networks. Consequently, IBI easily scales to deeper networks despite the computational overhead.

F HYPERPARAMETERS USED IN IBP AND IBI

F.1 NAMES AND FUNCTIONS OF HYPERPARAMETERS

The following Table 7 describes the hyperparameters used in the vanilla MAML, MAML+IBP, and MAML+IBI.

(a)   (b)   (c)   (d)

Figure 5: In the four plots above of losses against training steps the Blue, Green, Red, and Magenta lines respectively denote IBI applied after blocks 1,2,3, and 4 in ResNet-12 without any additional modifications. (a) Plot of $\mathcal{L}_{UB}$ in $\log$ scale for ease of visualization. (b) Plot of $\mathcal{L}_{LB}$. (c) Plot of $\mathcal{L}_{CE}$. (d) Plot of $\mathcal{L}$ in $\log$ scale for ease of visualization.

Table 7: Descriptions of hyperparameters used in vanilla MAML, MAML+IBP, MAML+IBI

Hyperarameter name	Hyperparameter description
Hyperparameters used in MAML	
Meta-shots	Number of shots in the query set in the training phase.
Inner loop iterations	Number of iterations of the inner loop during training on support set.
Inner loop learning rate η_0	Learning rate for SGD in the inner loop during training on support set.
Meta-step size η_1	Learning rate for ADAM in the meta-learner update during training.
Meta-batch B	Batch size of task during training.
Meta-iterations T	Number of training steps.
Evaluation iterations	Number of fine-tuning steps on support set during meta-testing.
Additional hyperparameters introduced in MAML+IBP	
Interval coefficient ϵ	Perturbation required for IBP.
Softmax coefficient γ	Controls the relative importance of the three losses used in MAML+IBP during softmax-based weighting in training phase.
Layer S	A layer in the network where IBP losses will be calculated.
Additional hyperparameters introduced in MAML+IBI	
α and β	Hyperparameters associated with the $Beta$ distribution required for performing IBP bounds-based interpolation.

The following Table 8 describes the hyperparameters used in the vanilla ProtoNet, ProtoNet+IBP, and ProtoNet+IBI.

F.2   HYPERPARAMETER SEARCH SPACE AND TUNING

For hyperparameter tuning, we employ a grid search. In Table 9, we list the search spaces for each of the hyperparameters used in MAML+IBP and MAML+IBI. Moreover, in Table 10, we also detail the search spaces for each of the hyperparameters used in ProtoNet+IBP and ProtoNet+IBI. For all other learners used in Tables 1 and 2 in the main paper, the results are either taken from the corresponding article or reproduced using the originally recommended hyperparameter settings.

In Tables 11 and 12, we report the optimal dataset-specific hyperparameters for MAML+IBP and MAML+IBI. Similarly, Tables 13 and 14 detail the optimal dataset-specific hyperparameter choices for ProtoNet+IBP and ProtoNet+IBI.

For Table 3 in the main paper, the methods using static weights share the same hyperparameter settings with their dynamic weighted counterpart except for γ, which is not used for the static weight runs. For Table 4 in the main paper, all the MAML variants use the same settings as vanilla MAML. Further, for all the different interpolation strategies $Beta$ distribution is used with the choices of α and β matching those of the MAML+IBI settings.

Table 8: Descriptions of hyperparameters used in vanilla ProtoNet, ProtoNet+IBP, ProtoNet+IBI

Hyperarameter name	Hyperparameter description
Hyperparameters used in MAML	
Number of ways in training	Traditional ProtoNet Snell et al. (2017) usually considers a higher number of ways during training.
Meta-shots	Number of shots in the query set in training phase.
Meta-step size η	Learning rate for ADAM in the learner update during training.
Meta-iterations T	Number of training steps.
Distance metric	Choice of distance measure, Euclidean or Cosine.
Additional hyperparameters introduced in ProtoNet+IBP	
Interval coefficient ϵ	Perturbation required for IBP.
Softmax coefficient γ	Controls the relative importance of the three losses used in ProtoNet+IBP during softmax-based weighting in training phase.
Layer S	A layer in the network where IBP losses will be calculated.
Additional hyperparameters introduced in ProtoNet+IBI	
α and β	Hyperparameters associated with the $Beta$ distribution required for performing IBP bounds-based interpolation.

Table 9: Grid search space of hyperparameters used in vanilla MAML, MAML+IBP, MAML+IBI

Hyperarameter name	Hyperparameter search space
Hyperparameters used in MAML	
Meta-shots	Set to 15 following Finn et al. (2017).
Inner loop iterations	Set to 5 following Finn et al. (2017).
Inner loop learning rate η_0	Set to 0.01 following Finn et al. (2017).
Meta-step size η_1	Set to 0.001 following Finn et al. (2017).
Meta-batch B	Set to 4 following Finn et al. (2017).
Meta-iterations T	Set to 60000 for miniImageNet and tieredImageNet following Finn et al. (2017). Set to 50000 for miniImageNet-S, DermNet-S, and ISIC following Yao et al. (2022).
Evaluation iterations	Set to 10 following Finn et al. (2017).
Additional hyperparameters introduced in MAML+IBP	
Interval coefficient ϵ	Searched in the set $\{0.05, 0.1, 0.2\}$.
Softmax coefficient γ	Searched in the set $\{0.01, 1, 10\}$.
Layer S	For the "4-CONV" learner containing 4 blocks of Convolution, Batch normalization, Max pooling, and ReLU, S is searched at the block level in the set $\{1, 2, 3, 4\}$. For example, $S = 2$ means IBP losses are calculated after the second block. For the "ResNet-12" network the ablation study in Appendix E provides the optimum choice of S.
Additional hyperparameters introduced in MAML+IBI	
α and β	Search space contains three pairs of choices $(0.1, 1)$, $(0.25, 1)$, and $(0.5, 0.5)$ where a tuple contains the value of α and β in order.

F.3 FULL RESULTS

F.3.1 RESULTS ON MINIIMAGENET AND TIEREDIMAGENET

As contending meta-learning algorithms, we choose the vanilla MAML along with notable meta-learners such as Meta-SGD Li et al. (2017), Reptile Nichol et al. (2018), LLAMA Grant et al. (2018), R2-D2 Bertinetto et al. (2019), and BOIL Oh et al. (2021). Moreover, considering the regularizing effect of IBP and IBI, we also include meta-learners such as TAML Jamal & Qi (2019), Meta-Reg Yin et al. (2019), and Meta-Dropout Lee et al. (2020) which employ explicit regularization. We further include data augmentation–reliant learners such as MetaMix Yao et al. (2021), Meta-Maxup

Table 10: Grid search space of hyperparameters used in vanilla ProtoNet, ProtoNet+IBP, ProtoNet+IBI

Hyperaramter name	Hyperparameter search space
Hyperparameters used in ProtoNet	
Number of ways in training	Set to 30 for miniImageNet and tieredImageNet following Snell et al. (2017). Set to 5 for miniImageNet-S and DermNet-S, and 2 for ISIC as the benefit of training using higher ways cannot be leveraged in the few-task scenario Yao et al. (2022).
Meta-shots	Set to 15 following Snell et al. (2017).
Meta-step size η	Set to 0.001 following Snell et al. (2017).
Meta-iterations T	Set to 20000 for miniImageNet and tieredImageNet following Snell et al. (2017). Our implementation of ProtoNet, unlike Yao et al. (2022), does not require an additional hyperparameter B, analogous to MAML, for IBP or IBI training. Thus, for miniImageNet-S, DermNet-S, and ISIC also we set T to 20000.
Distance metric	Set to Euclidean following Snell et al. (2017).
Additional hyperparameters introduced in ProtoNet+IBP	
Interval coefficient ϵ	Searched in the set $\{0.05, 0.1, 0.2\}$.
Softmax coefficient γ	Searched in the set $\{0.01, 1, 10\}$.
Layer S	For the "4-CONV" learner containing 4 blocks of Convolution, Batch normalization, Max pooling, and ReLU, S is searched at the block level in the set $\{1, 2, 3, 4\}$. For example, $S = 2$ means IBP losses are calculated after the second block. For the "ResNet-12" network the ablation study in Appendix E provides the optimum choice of S.
Additional hyperparameters introduced in ProtoNet+IBI	
α and β	Search space contains three pairs of choices $(0.1, 1)$, $(0.25, 1)$, and $(0.5, 0.5)$ where a tuple contains the value of α and β in order.

Table 11: Optimal hyperparamter setting for MAML+IBP, MAML+IBI in 1-shot settings when "4-CONV" network is used.

Hyperaramter	Hyperparameter settings for datasets				
	miniImageNet	tieredImageNet	miniImageNet-S	DermNet-S	ISIC
Additional hyperparameters introduced in MAML+IBP					
ϵ	0.1	0.05	0.1	0.2	0.05
γ	0.1	0.1	0.1	0.1	0.1
S	3	3	3	3	3
Additional hyperparameters introduced in MAML+IBI					
α and β	(0.25, 1)	(0.25, 1)	(0.5, 0.5)	(0.5, 0.5)	(0.25, 1)

Ni et al. (2021), as well as the inter-task interpolation method MLTI Yao et al. (2022). In case of metric-learners, we compare against the vanilla ProtoNet in addition to other notable methods like MatchingNet Vinyals et al. (2016), RelationNet Sung et al. (2018), IMP Allen et al. (2019), and GNN Satorras & Estrach (2018). We also compare against ProtoNet coupled with data augmentation methods such as MetaMix, Meta-Maxup, and MLTI, as done in Yao et al. (2022). While Yao et al. (2022) had to modify the training strategy of the canonical ProtoNet to accommodate the changes introduced by MetaMix, Meta-Maxup, and MLTI, the flexibility of IBP and IBI imposes no such requirements. We summarize the findings in Table 16. We can observe that either IBP or IBI or both achieve better Accuracy than the competitors in all cases. The slightly better performance of IBP with ProtoNet seems to imply that IBP-based task interpolation is often unnecessary for ProtoNet when a large number of tasks is available.

Table 12: Optimal hyperparamter setting for MAML+IBP, MAML+IBI in 5-shot settings when "4-CONV" network is used.

Hyperarameter	Hyperparameter settings for datasets				
	miniImageNet	tieredImageNet	miniImageNet-S	DermNet-S	ISIC
Additional hyperparameters introduced in MAML+IBP					
ϵ	0.1	0.05	0.1	0.2	0.05
γ	0.1	0.1	0.1	0.1	0.1
S	3	3	3	3	3
Additional hyperparameters introduced in MAML+IBI					
α and β	(0.1, 1)	(0.1, 1)	(0.5, 0.5)	(0.5, 0.5)	(0.25, 1)

Table 13: Optimal hyperparamter setting for ProtoNet+IBP, ProtoNet+IBI in 1-shot settings when "4-CONV" network is used.

Hyperarameter	Hyperparameter settings for datasets				
	miniImageNet	tieredImageNet	miniImageNet-S	DermNet-S	ISIC
Additional hyperparameters introduced in ProtoNet+IBP					
ϵ	0.05	0.05	0.1	0.1	0.05
γ	1	1	1	1	1
S	1	1	1	1	1
Additional hyperparameters introduced in ProtoNet+IBI					
α and β	(0.1, 1)	(0.25, 1)	(0.5, 0.5)	(0.25, 1)	(0.1, 1)

Table 14: Optimal hyperparamter setting for ProtoNet+IBP, ProtoNet+IBI in 5-shot settings when "4-CONV" network is used.

Hyperarameter	Hyperparameter settings for datasets				
	miniImageNet	tieredImageNet	miniImageNet-S	DermNet-S	ISIC
Additional hyperparameters introduced in ProtoNet+IBP					
ϵ	0.05	0.05	0.1	0.1	0.05
γ	1	1	1	1	1
S	1	1	1	1	1
Additional hyperparameters introduced in ProtoNet+IBI					
α and β	(0.1, 1)	(0.1, 1)	(0.5, 0.5)	(0.5, 0.5)	(0.25, 1)

The full version of Table 2 is detailed in Table 17. The full version of Table 4 in the main paper is provided here across Tables 18 and 19. Moreover, the full version of Table 5 in the main paper is presented in Table 20.

Table 15: Optimal hyperparameter settings for MAML+IBP/IBI and ProtoNet+IBP/IBI when "ResNet-12" is used as the network.

			Datasets		
Learner	Shots	Parameter	miniImageNet-S	DermNet-S	ISIC
MAML+IBP	1 and 5	ϵ	0.1	0.1	0.1
MAML+IBP	1 and 5	γ	0.1	0.1	0.1
MAML+IBP	1 and 5	S^*	1	1	1
MAML+IBI (Additional)	1 and 5	α and β	(0.1, 1)	(0.1, 1)	(0.1, 1)
ProtoNet+IBP	1 and 5	ϵ	0.05	0.05	0.05
ProtoNet+IBP	1 and 5	γ	0.1	0.1	0.1
ProtoNet+IBP	1 and 5	S^*	1	1	1
ProtoNet+IBI (Additional)	1 and 5	α and β	(0.1, 1)	(0.1, 1)	(0.1, 1)

*: Set as per Appendix E with necessary modifications.

Table 16: Performance comparison of the two proposed methods with baselines and competing algorithms on miniImageNet and tieredImageNet datasets. The results are reported in terms of mean Accuracy over 600 tasks with 95% confidence interval.

Dataset	Learner type	Algorithm	1-shot	5-shot
miniImageNet	Meta-learners	MAML Finn et al. (2017)	48.70±1.75%	63.11±0.91%
		Meta-SGD Li et al. (2017)	50.47±1.87%	64.03±0.94%
		Reptile Nichol et al. (2018)	49.97±0.32%	65.99±0.58%
		LLAMA Grant et al. (2018)	49.40±0.84%	-
		R2-D2 Bertinetto et al. (2019)	49.50±0.20%	65.40±0.20%
		TAML Jamal & Qi (2019); Yao et al. (2022)	46.40±0.82%	63.26±0.68%
		BOIL Oh et al. (2021)	49.61±0.16%	66.45±0.37%
		MAML+Meta-Reg Yin et al. (2019); Yao et al. (2022)	47.02±0.77%	63.19±0.69%
		MAML+Meta-Dropout Lee et al. (2020); Yao et al. (2022)	47.47±0.81%	64.11±0.71%
		MAML+MetaMix Yao et al. (2021; 2022)	47.81±0.78%	64.22±0.68%
		MAML+Meta-Maxup Ni et al. (2021); Yao et al. (2022)	47.68±0.79%	63.51±0.75%
		MAML+MLTI Yao et al. (2022)	48.62±0.76%	64.65±0.70%
		MAML+IBP (ours)	50.76±0.83%	67.13±0.81%
		MAML+IBI (ours)	**52.16±0.84%**	**67.56±0.86%**
	Metric-learners	MatchingNet Vinyals et al. (2016)	43.44±0.77%	55.31±0.73%
		RelationNet Sung et al. (2018)	50.44±0.82%	65.32±0.70%
		IMP Allen et al. (2019)	49.60±0.80%	68.10±0.80%
		GNN Satorras & Estrach (2018)	49.02±0.98%	63.50±0.84%
		ProtoNet Snell et al. (2017)	49.42±0.78%	68.20±0.66%
		ProtoNet*+MetaMix Yao et al. (2021; 2022)	47.21±0.76%	64.38±0.67%
		ProtoNet*+Meta-Maxup Ni et al. (2021); Yao et al. (2022)	47.33±0.79%	64.43±0.69%
		ProtoNet*+MLTI Yao et al. (2022)	48.11±0.81%	65.22±0.70%
		ProtoNet+IBP (ours)	50.48±0.83%	68.33±0.79%
		ProtoNet+IBI (ours)	**51.79±0.81%**	**68.46±0.79%**
tieredImageNet	Meta-learners	MAML Finn et al. (2017)	51.67±1.81%	70.30±0.08%
		Meta-SGD Li et al. (2017)	48.97±0.21%	66.47±0.21%
		Reptile Nichol et al. (2018)	49.97±0.32%	65.99±0.58%
		BOIL Oh et al. (2021)	49.35±0.26%	69.37±0.12%
		MAML+IBP (ours)	**54.36±0.80%**	**71.30±0.77%**
		MAML+IBI (ours)	54.16±0.79%	71.00±0.84%
	Metric-learners	MatchingNet Vinyals et al. (2016)	54.02±0.79%	70.11±0.82%
		RelationNet Sung et al. (2018)	54.48±0.93%	71.32±0.78%
		ProtoNet Snell et al. (2017)	53.31±0.20%	72.69±0.74%
		ProtoNet+IBP (ours)	53.83±0.81%	**75.26±0.83%**
		ProtoNet+IBI (ours)	**55.16±0.77%**	74.96±0.82%

* ProtoNet implementation as per Yao et al. (2022).

Table 17: Full version of Table 2 for performance comparison of MAML+IBI against inter-task interpolation on images, at a fixed intermediate layer S, MLTI Yao et al. (2022), and interpolation with IBP bounds while only $\mathcal{L}_{CE}$ (and not $\mathcal{L}_{LB}$ and $\mathcal{L}_{LB}$) is minimized, in the 5-way 1-shot setting. The results are reported in terms of mean Accuracy over 600 tasks along with the 95% confidence intervals.

Algorithm	mIS	ISIC	DS
MAML+Inter-task interpolation in image space	40.90±0.86%	55.25±1.58%	48.30±0.81%
MAML+Inter-task interpolation after $f_{\theta S}$	41.00±0.83%	61.33±1.52%	47.43±0.78%
MAML+MLTI Yao et al. (2022)	41.58±0.72%	61.79±1.00%	48.03±0.80%
MAML+IBI without $\mathcal{L}_{UB}$ and $\mathcal{L}_{LB}$ losses	35.26±0.79%	48.94±1.36%	41.30±0.81%
MAML+IBI	42.20±0.82%	68.58±0.93%	49.13±0.80%

Table 18: Full results for MAML variants on miniImageNet-S, DermNet-S, and ISIC in Table 4 of the main paper. All results are reported in terms of Accuracy over 600 tasks along with 95% confidence level.

Algorithm	4-CONV		ResNet-12	
	5-way 1-shot	5-way 5-shot	5-way 1-shot	5-way 5-shot
miniImageNet-S				
MAML Finn et al. (2017)	38.27±0.74%	52.14±0.65%	40.02±0.78%	52.56±0.85%
MAML+Meta-Reg Yin et al. (2019); Yao et al. (2022)	38.35±0.76%	51.74±0.68%	-	-
TAML Jamal & Qi (2019); Yao et al. (2022)	38.70±0.77%	52.75±0.70%	-	-
MAML+Meta-Dropout Lee et al. (2020); Yao et al. (2022)	38.32±0.75%	52.53±0.69%	-	-
MAML+MetaMix Yao et al. (2021; 2022)	39.43±0.77%	54.14±0.73%	42.26±0.75%	54.65±0.87%
MAML+Meta-Maxup Ni et al. (2021); Yao et al. (2022)	39.28±0.77%	53.02±0.72%	41.97±0.78%	53.92±0.85%
MAML+MLTI Yao et al. (2022)	41.58±0.72%	55.22±0.76%	43.35±0.90%	54.89±0.88%
MAML+IBP (ours)	41.30±0.79%	54.36±0.81%	43.50±0.86%	55.13±0.90%
MAML+IBI (ours)	**42.20±0.82%**	**55.23±0.81%**	**43.90±0.90%**	**57.00±0.88%**
ISIC				
MAML Finn et al. (2017)	57.59±0.79%	68.24±0.77%	59.41±1.98%	67.66±1.92%
MAML+Meta-Reg Yin et al. (2019); Yao et al. (2022)	58.57±0.94%	68.45±0.81%	-	-
TAML Jamal & Qi (2019); Yao et al. (2022)	58.39±1.00%	66.09±0.71%	-	-
MAML+Meta-Dropout Lee et al. (2020); Yao et al. (2022)	58.40±1.02%	67.32±0.92%	-	-
MAML+MetaMix Yao et al. (2021; 2022)	60.34±1.03%	69.47±0.60%	62.06±1.77%	72.18±1.75%
MAML+Meta-Maxup Ni et al. (2021); Yao et al. (2022)	58.68±0.86%	69.16±0.61%	61.64±1.81%	72.04±1.79%
MAML+MLTI Yao et al. (2022)	61.79±1.00%	70.69±0.68%	63.25±1.88%	73.56±1.82%
MAML+IBP (ours)	64.91±0.92%	78.75±0.94%	**64.50±1.48%**	73.91±1.42%
MAML+IBI (ours)	**68.58±0.93%**	**79.75±0.91%**	62.16±1.51%	**75.66±1.56%**
DermNet-S				
MAML Finn et al. (2017)	43.47±0.83%	60.56±0.74%	47.58±0.93%	63.13±0.85%
MAML+Meta-Reg Yin et al. (2019); Yao et al. (2022)	45.01±0.83%	60.92±0.69%	-	-
TAML Jamal & Qi (2019); Yao et al. (2022)	45.73±0.84%	61.14±0.72%	-	-
MAML+Meta-Dropout Lee et al. (2020); Yao et al. (2022)	44.30±0.84%	60.86±0.73%	-	-
MAML+MetaMix Yao et al. (2021; 2022)	46.81±0.81%	63.52±0.73%	51.40±0.89%	64.82±0.87%
MAML+Meta-Maxup Ni et al. (2021); Yao et al. (2022)	46.10±0.82%	62.64±0.72%	50.82±0.85%	64.24±0.86%
MAML+MLTI Yao et al. (2022)	48.03±0.79%	64.55±0.74%	52.03±0.90%	65.12±0.88%
MAML+IBP (ours)	48.33±0.83%	63.33±0.84%	50.40±0.88%	65.40±0.89%
MAML+IBI (ours)	**49.13±0.80%**	**65.43±0.79%**	**52.10±0.87%**	**66.50±0.92%**

Table 19: Full results for ProtoNet variants on miniImageNet-S, ISIC, and DermNet-S in Table 4 of the main paper. All results are reported in terms of Accuracy over 600 tasks along with 95% confidence level.

Algorithm	4-CONV		ResNet-12	
	5-way 1-shot	5-way 5-shot	5-way 1-shot	5-way 5-shot
miniImageNet-S				
ProtoNet* Snell et al. (2017); Yao et al. (2022)	36.26±0.70%	50.72±0.70%	-	-
ProtoNet Snell et al. (2017)	40.70±0.79%	53.16±0.77%	40.96±0.75%	55.00±0.86%
ProtoNet*+MetaMix Yao et al. (2021; 2022)	39.67±0.71%	53.10±0.74%	42.95±0.87%	56.95±0.89%
ProtoNet*+Meta-Maxup Ni et al. (2021); Yao et al. (2022)	39.80±0.73%	53.35±0.68%	42.68±0.78%	56.07±0.85%
ProtoNet*+MLTI Yao et al. (2022)	41.36±0.75%	55.34±0.74%	44.08±0.83%	57.14±0.90%
ProtoNet+IBP (ours)	41.46±0.79%	55.00±0.81%	43.33±0.82%	57.40±0.90%
ProtoNet+IBI (ours)	**43.30±0.81%**	**55.73±0.80%**	**45.33±0.85%**	**58.23±0.92%**
ISIC				
ProtoNet* Snell et al. (2017); Yao et al. (2022)	58.56±1.01%	66.25±0.96%	-	-
ProtoNet Snell et al. (2017)	65.58±0.91%	75.25±0.90%	61.91±1.94%	75.91±1.92%
ProtoNet*+MetaMix Yao et al. (2021; 2022)	60.58±1.17%	70.12±0.94%	65.55±1.80%	78.33±1.76%
ProtoNet*+Meta-Maxup Ni et al. (2021); Yao et al. (2022)	59.66±1.13%	68.97±0.83%	64.17±1.85%	77.62±1.86%
ProtoNet*+MLTI Yao et al. (2022)	62.82±1.13%	71.52±0.89%	66.02±1.88%	79.15±1.87%
ProtoNet+IBP (ours)	**70.75±0.95%**	81.01±0.93%	66.66±1.52%	81.00±1.49%
ProtoNet+IBI (ours)	70.25±0.91%	**81.16±0.94%**	**66.75±1.63%**	**81.83±1.58%**
DermNet-S				
ProtoNet* Snell et al. (2017); Yao et al. (2022)	44.21±0.75%	60.33±0.70%	-	-
ProtoNet Snell et al. (2017)	46.86±0.77%	62.03±0.79%	48.65±0.85%	65.40±0.81%
ProtoNet*+MetaMix Yao et al. (2021; 2022)	47.71±0.83%	62.68±0.71%	51.18±0.90%	66.80±0.83%
ProtoNet*+Meta-Maxup Ni et al. (2021); Yao et al. (2022)	46.06±0.78%	62.97±0.74%	50.96±0.88%	66.38±0.85%
ProtoNet*+MLTI Yao et al. (2022)	49.38±0.85%	65.19±0.73%	52.01±0.93%	67.28±0.87%
ProtoNet+IBP (ours)	48.06±0.81%	**67.26±0.84%**	51.33±0.91%	67.57±0.88%
ProtoNet+IBI (ours)	**51.13±0.80%**	65.93±0.82%	**52.53±0.94%**	**68.00±0.88%**

* ProtoNet implementation as per Yao et al. (2022).

Table 20: Full result for Table 5 describing transferability comparison of MAML and ProtoNet, with their MLTI, IBP and IBI variants. All results are reported in terms of Accuracy over 600 tasks along with the 95% confidence intervals. Here, $A \rightarrow B$ indicates the model trained on dataset A is tested on dataset B.

Algorithms	Accuracy	
	DermNet-S → miniImageNet-S	miniImageNet-S → DermNet-S
MAML	25.06±0.79%	33.40±0.77%
MAML+MLTI	30.03±0.58%	**36.74±0.64%**
MAML+IBP (Ours)	27.06±0.78%	33.90±0.81%
MAML+IBPI (Ours)	**30.23±0.82%**	36.21±0.84%
ProtoNet	28.76±0.82%	34.03±0.80%
ProtoNet*+MLTI	30.06±0.56%	35.46±0.63%
ProtoNet+IBP (Ours)	29.60±0.81%	34.13±0.82%
ProtoNet+IBPI (Ours)	**30.32±0.84%**	**35.63±0.83%**

*: ProtoNet implementation as per Yao et al. (2022).

G CODES

The following code can be used to run MAML, MAML+IBP, and MAML+IBI. Please put the data in a folder with the dataset name. The data should be in ".jpg" image format typically of resolution 84×84. The data is expected to be arranged in train, validation, and test folders each containing folders for individual classes. The main code is kept inside the "src" folder while the helper code can reside outside. The "main" function resides in the "run_learner.py".

Helper code: image_data_process.py

```python
import os
import random

from PIL import Image
import numpy as np
import torch

def read_dataset(data_dir, val_presence=True):

    # Read the image dataset.

    if val_presence is True:
        return tuple(_read_classes(os.path.join(data_dir, x)) for x in ['train', 'val', 'test'])
    else:
        return tuple(_read_classes(os.path.join(data_dir, x)) for x in ['train', 'test', 'test'])

def _read_classes(dir_path):

    # Read the class directories in a train/val/test directory.
    # Images should be in ".jpg" format.

    return [ImageProcessClass(os.path.join(dir_path, f)) for f in os.listdir(dir_path)]

class ImageProcessClass:

    # Loading and using the image dataset.
    # To use these APIs, you should prepare a directory that
    # contains three sub-directories: train, test, and val.

    def __init__(self, dir_path):
        self.dir_path = dir_path
        self._cache = {}

    def sample(self, num_images):

        # Sample images (as pytorch tensor) from the class.

        names = [f for f in os.listdir(self.dir_path) if f.endswith('.jpg')]
        random.shuffle(names)
        images = []
        for name in names[:num_images]:
            images.append(self._read_image(name))
        return images

    def _read_image(self, name):

        # For reading images and transformations as necessary.
        # Image resolution is set to 84x84.

        if name in self._cache:
            return self._cache[name]
        with open(os.path.join(self.dir_path, name), 'rb') as in_file:
            img = Image.open(in_file).resize((84, 84)).convert('RGB')
            img = np.array(img).astype('float32') / 0xff
            img = np.rollaxis(img, 2, 0)
            self._cache[name] = torch.tensor(img)
            return self._read_image(name)
```

Main code: run_learner.py

```python
import random
import os
import sys
import numpy as np
import torch

import argparse
from img_data_process import read_dataset
from datetime import datetime
from copy import deepcopy

from src.models import NetworkModel
from src.eval_model import bulk_evaluate
from src.train_model import train
from src.learners import Learner

def argument_parser():
    # Get an argument parser for a training script.
```

```python
    parser = argparse.ArgumentParser(formatter_class=argparse.ArgumentDefaultsHelpFormatter)
    parser.add_argument('--dataset', help='name_of_dataset', default=None)
    parser.add_argument('--algorithm', help='name_of_algorithm', default=None)
    parser.add_argument('--seed', help='random_seed', default=0, type=int)
    parser.add_argument('--order', help='order_for_MAML_and_variants.', default=None, type=int)
    parser.add_argument('--classes', help='number_of_classes_per_inner_task', default=None, type=int)
    parser.add_argument('--shots', help='number_of_examples_per_class', default=None, type=int)
    parser.add_argument('--meta-shots', help='shots_for_meta_update', default=None, type=int)
    parser.add_argument('--inner-iters', help='inner_iterations', default=None, type=int)
    parser.add_argument('--learning-rate', help='inner_loop_learning_rate', default=None, type=float)
    parser.add_argument('--meta-step', help='outer_loop_learning_rate', default=None, type=float)
    parser.add_argument('--meta-batch', help='meta-training_batch_size', default=None, type=int)
    parser.add_argument('--meta-iters', help='meta-training_iterations', default=None, type=int)
    parser.add_argument('--eval-iters', help='evaluation_inner_iterations', default=None, type=int)
    parser.add_argument('--eval-samples', help='evaluation_samples', default=None, type=int)
    parser.add_argument('--eval-interval', help='evaluation_interval_during_training', default=None, type=int)
    parser.add_argument('--eval-interval-sample', help='evaluation_samples_during_training', default=None, type=int)
    parser.add_argument('--ibp-eps', help='IBP_neighborhood_size', default=0, type=float)
    parser.add_argument('--softmax-temp', help='softmax_temperature', default=None, type=float)
    parser.add_argument('--only-evaluation', help='for_only_evaluation', action='store_true', default=False)
    parser.add_argument('--checkpoint', help='load_saved_checkpoint_from_path', default=None)
    parser.add_argument('--test-iters', help='number_of_evaluations', default=None, type=int)
    parser.add_argument('--beta-a', help='beta_distrebution_parameter_a', default=None, type=float)
    parser.add_argument('--beta-b', help='beta_distrebution_parameter_b', default=None, type=float)
    parser.add_argument('--mixup', help='set_to_use_mixup_task', action='store_true', default=False)
    parser.add_argument('--ibp-layers', help='number_layer_to_perform_IBP/IBI', default=None, type=int)
    return parser

def model_kwargs(parsed_args):

    # Parameters used for initializing the learner.

    return {
        'update_lr': parsed_args.learning_rate,
        'meta_step_size': parsed_args.meta_step,
        'beta_a': parsed_args.beta_a,
        'beta_b': parsed_args.beta_b,
        'softmax_temp': parsed_args.softmax_temp
    }

def train_kwargs(parsed_args):

    # Parameters used for training.

    return {
        'order': parsed_args.order,
        'num_classes': parsed_args.classes,
        'num_shots': parsed_args.shots,
        'meta_shots': parsed_args.meta_shots,
        'inner_iters': parsed_args.inner_iters,
        'meta_batch_size': parsed_args.meta_batch,
        'meta_iters': parsed_args.meta_iters,
        'eval_inner_iters': parsed_args.eval_iters,
        'eval_interval': parsed_args.eval_interval,
        'eval_interval_sample': parsed_args.eval_interval_sample,
        'ibp_epsilon': parsed_args.ibp_eps,
        'mixup': parsed_args.mixup,
        'ibp_layers': parsed_args.ibp_layers
    }

def evaluate_kwargs(parsed_args):

    # Parameters used for evaluation over multiple tasks.

    return {
        'num_classes': parsed_args.classes,
        'num_shots': parsed_args.shots,
        'eval_inner_iters': parsed_args.eval_iters,
        'num_samples': parsed_args.eval_samples
    }

def main():

    args = argument_parser().parse_args()

    torch.manual_seed(args.seed)
    random.seed(args.seed)
    np.random.seed(args.seed)

    # Edit here according to need.
    DATA_DIR = '/home/<userName>/<workingDirectory>/data/' + args.dataset

    # Create directory for storing results and initiate logging.
    if os.path.exists(os.path.join(DATA_DIR, 'val')):
        val_presence = True
        print("Validation_set_is_present.")
    else:
        val_presence = False
        print("Validation_set_is_not_found._Exiting.")
        sys.exit()

    time_string = datetime.now().strftime("%m%d%Y_%H:%M:%S")
```

```
        output_folder = args.dataset + '_' + args.algorithm + '_output_folder_' + time_string
        output_file = output_folder + '/' + 'log_' + time_string + '.txt'

        if not os.path.exists(output_folder):
            os.makedirs(output_folder)

        with open(output_file, 'a+') as fp:
            print('\n'.join(f'{k}={v}' for k, v in vars(args).items()), file=fp)

        device = torch.device('cuda')

        # Instantiate the dataset.
        train_set, val_set, test_set = read_dataset(DATA_DIR, val_presence)

        # Instantiate the learner
        model=NetworkModel(args.classes)

        learner = Learner(model, device, **model_kwargs(args))

        # Perform training or evaluation as per need.
        if args.only_evaluation is False:
            train(learner, train_set, val_set, output_file, output_folder, **train_kwargs(args))
        else:
            assert args.checkpoint is not None, 'For_evaluating_without_training_please_provide_a_checkpoint'
            print('Evaluating...')

            res_file = output_folder + '/' + 'test_performance_' + time_string + '_.txt'
            with open(res_file, 'a+') as fp:
                print('Evalulation_checkpoint:_' + args.checkpoint, file=fp)

            checkpoint_model = torch.load(args.checkpoint, map_location='cuda:0')
            learner.net.load_state_dict(checkpoint_model['model_state'])
            learner.meta_optim.load_state_dict(checkpoint_model['meta_optim_state'])

            train_accuracy, val_accuracy, test_accuracy = [], [], []
            train_cnf, val_cnf, test_cnf = [], [], []

            for ii in range(args.test_iters):

                train_acc, train_div = bulk_evaluate(learner, train_set, **evaluate_kwargs(args))
                val_acc, val_div = bulk_evaluate(learner, val_set, **evaluate_kwargs(args))
                test_acc, test_div = bulk_evaluate(learner, test_set, **evaluate_kwargs(args))

                train_accuracy.append(train_acc)
                val_accuracy.append(val_acc)
                test_accuracy.append(test_acc)

                train_cnf.append(train_div)
                val_cnf.append(val_div)
                test_cnf.append(test_div)

                with open(res_file, 'a+') as fp:
                    print('Test_iteration:_' + str(ii + 1), file=fp)
                    print('Train_accuracy:_' + str(train_accuracy[-1]) + '_+/-_' + str(train_cnf[-1]), file=fp)
                    print('Validation_accuracy:_' + str(val_accuracy[-1]) + '_+/-_' + str(val_cnf[-1]), file=fp)
                    print('Test_accuracy:_' + str(test_accuracy[-1]) + '_+/-_' + str(test_cnf[-1]) + '\n', file=fp)
        save_path = output_folder + '/' + 'results' + '.npz'
        train_accuracy = np.array(train_accuracy)
        val_accuracy = np.array(val_accuracy)
        test_accuracy = np.array(test_accuracy)

        train_cnf = np.array(train_cnf)
        val_cnf = np.array(val_cnf)
        test_cnf = np.array(test_cnf)

        np.savez(save_path, train_accuracy=train_accuracy, val_accuracy=val_accuracy,
            test_accuracy=test_accuracy, train_confidence=train_cnf, val_confidence=val_cnf,
            test_confidence=test_cnf)

if __name__ == '__main__':
    main()
```

Model: "src/models.py"

```
import torch
import torch.nn as nn
import torch.nn.functional as F
import numpy as np

# A regular 4-CONV network
class NetworkModel(nn.Module):

    def __init__(self, k_way):

        # Initialize the network layers.

        super(NetworkModel, self).__init__()

        self.conv1 = nn.Conv2d(3, 64, kernel_size=3, stride=1, padding=(1, 1))
        self.batch1 = nn.BatchNorm2d(64, track_running_stats=False)
```

```python
        self.conv2 = nn.Conv2d(64, 64, kernel_size=3, stride=1, padding=(1, 1))
        self.batch2 = nn.BatchNorm2d(64, track_running_stats=False)

        self.conv3 = nn.Conv2d(64, 64, kernel_size=3, stride=1, padding=(1, 1))
        self.batch3 = nn.BatchNorm2d(64, track_running_stats=False)

        self.conv4 = nn.Conv2d(64, 64, kernel_size=3, stride=1, padding=(1, 1))
        self.batch4 = nn.BatchNorm2d(64, track_running_stats=False)

        self.lin1 = nn.Linear(64*5*5, k_way)

    def forward(self, x):

        # A forward function only for reference.

        x = F.relu(F.max_pool2d(self.batch1(self.conv1(x)), 2))
        x = F.relu(F.max_pool2d(self.batch2(self.conv2(x)), 2))
        x = F.relu(F.max_pool2d(self.batch3(self.conv3(x)), 2))
        x = F.relu(F.max_pool2d(self.batch4(self.conv4(x)), 2))

        x = x.view(-1, 64*5*5)
        x = self.lin1(x)

        return x

    def functional_forward(self, x,
        weight_dict,
        layer_index=None,
        mixup_flag=None,
        k_way=None,
        beta_a=None,
        beta_b=None):

        # A functional forward that will actually be used for all requirements.
        # It only uses functionals thus explicitly needs the weights to be passes.
        # The functionals can use the regular layer function or their IBP form as required.

        robust = True
        if layer_index is None:
            y, robust = None, False

        # Block 1
        x = robust_conv_forward(
            x, weight_dict['conv1.weight'], weight_dict['conv1.bias'], stride=1, padding=(1, 1), robust=robust)
        x = robust_batch_norm_forward(
            x, weight_dict['batch1.weight'], weight_dict['batch1.bias'], robust=robust)
        x = F.max_pool2d(x, kernel_size=2, stride=2)
        x = F.relu(x)

        if layer_index == 1:
            y, x, robust = intra_class_mixup(x, mixup_flag, k_way, beta_a, beta_b)

        # Block 2
        x = robust_conv_forward(
            x, weight_dict['conv2.weight'], weight_dict['conv2.bias'], stride=1, padding=(1, 1), robust=robust)
        x = robust_batch_norm_forward(
            x, weight_dict['batch2.weight'], weight_dict['batch2.bias'], robust=robust)
        x = F.max_pool2d(x, kernel_size=2, stride=2)
        x = F.relu(x)

        if layer_index == 2:
            y, x, robust = intra_class_mixup(x, mixup_flag, k_way, beta_a, beta_b)

        # Block 3
        x = robust_conv_forward(
            x, weight_dict['conv3.weight'], weight_dict['conv3.bias'], stride=1, padding=(1, 1), robust=robust)
        x = robust_batch_norm_forward(
            x, weight_dict['batch3.weight'], weight_dict['batch3.bias'], robust=robust)
        x = F.max_pool2d(x, kernel_size=2, stride=2)
        x = F.relu(x)

        if layer_index == 3:
            y, x, robust = intra_class_mixup(x, mixup_flag, k_way, beta_a, beta_b)

        # Block 4
        x = robust_conv_forward(
            x, weight_dict['conv4.weight'], weight_dict['conv4.bias'], stride=1, padding=(1, 1), robust=robust)
        x = robust_batch_norm_forward(
            x, weight_dict['batch4.weight'], weight_dict['batch4.bias'], robust=robust)
        x = F.max_pool2d(x, kernel_size=2, stride=2)
        x = F.relu(x)

        if layer_index == 4:
            y, x, robust = intra_class_mixup(x, mixup_flag, k_way, beta_a, beta_b)

        # Map to number of classes.
        x = x.view(-1, 64*5*5)
        x = F.linear(
            x, weight=weight_dict['lin1.weight'], bias=weight_dict['lin1.bias'])

        return y, x
```

```python
def robust_conv_forward(x, weight, bias, stride, padding, robust):

    # Convolution function that can propagate interval bounds.

    if robust is False:
        # Regular convolution
        x = F.conv2d(x, weight, bias, stride, padding)
        return x

    # Convolution propagating interval bounds.
    b_size = x.shape[0]//3

    input_p = x[:b_size]
    input_o = x[b_size:2*b_size]
    input_n = x[2*b_size:]

    u = (input_p + input_n)/2
    r = (input_p - input_n)/2

    out_u = F.conv2d(u, weight, bias, stride, padding)
    out_r = F.conv2d(r, torch.abs(weight), None, stride, padding)
    out_o = F.conv2d(input_o, weight, bias, stride, padding)

    return torch.cat([out_u + out_r, out_o, out_u - out_r], 0)

def robust_batch_norm_forward(x, weight, bias, robust):

    # Batch normalization function that can propagate interval bounds.

    if robust is False:
        # Regular batch normalization.
        x = F.batch_norm(x, running_mean=None, running_var=None,
            weight=weight, bias=bias, training=True)
        return x

    # Batch normalization propagating interval bounds.
    b_size = x.shape[0]//3
    eps = 1e-5

    input_p = x[:b_size]
    input_o = x[b_size:2*b_size]
    input_n = x[2*b_size:]

    # Equivalent to input_o.mean((0, 2, 3))
    mean = input_o.transpose(0, 1).contiguous().view(
        input_o.shape[1], -1).mean(1)
    var = input_o.transpose(0, 1).contiguous().view(
        input_o.shape[1], -1).var(1, unbiased=False)

    # Element-wise multiplier
    multiplier = torch.rsqrt(var + eps)
    multiplier = multiplier * weight

    offset = (-multiplier * mean) + bias

    multiplier = multiplier.unsqueeze(0).unsqueeze(2).unsqueeze(3)
    offset = offset.unsqueeze(0).unsqueeze(2).unsqueeze(3)

    # Because the scale might be negative, we need to apply a strategy similar to linear
    u = (input_p + input_n)/2
    r = (input_p - input_n)/2

    out_u = torch.mul(u, multiplier) + offset
    out_r = torch.mul(r, torch.abs(multiplier))
    out_o = torch.mul(input_o, multiplier) + offset

    return torch.cat([out_u + out_r, out_o, out_u - out_r], 0)

def intra_class_mixup(y, mixup_flag, k_way, beta_a, beta_b):

    # Perform interval bound interpolation

    robust = False
    b_size = y.shape[0]//3
    u = y[:b_size]
    l = y[2*b_size:]
    o = y[b_size:2*b_size]

    if mixup_flag is True:

        num_shots = b_size // k_way
        mixup_params = np.repeat(np.random.beta(beta_a, beta_b, k_way), num_shots)
        mixup_params = torch.tensor(mixup_params, dtype=torch.float).view(b_size, 1, 1, 1).to(y.device)

        rand_ext = np.repeat(np.random.randint(0, 2, k_way), num_shots)
        rand_ext = torch.tensor(rand_ext, dtype=torch.float).view(b_size, 1, 1, 1).to(y.device)

        mixup_params_c = 1 - mixup_params
        rand_ext_c = 1 - rand_ext

        ulo = (mixup_params_c*o +
```

```
                mixup_params*rand_ext*u +
                mixup_params*rand_ext_c*l)

        x = torch.cat([o, ulo], 0)
        return y, x, robust

    return y, o, robust
```

Learner: "src/learners.py"

```python
import random

import torch
import torch.nn.functional as F
from torch import optim
import numpy as np

import torch.optim as optim
from copy import deepcopy
from collections import OrderedDict

class Learner:

    # Base Learner class for MAML and IBP/IBI variants.

    def __init__(self, model, device, update_lr, meta_step_size, beta_a, beta_b, softmax_temp):

        # Initialization.
        self.device = device
        self.net = model.to(self.device)
        self.meta_optim = optim.Adam(self.net.parameters(), lr=meta_step_size)
        self.update_lr = update_lr
        self.beta_a, self.beta_b = beta_a, beta_b
        self.softmax_temp = softmax_temp

    def train_step(self,
                dataset,
                order,
                num_classes,
                num_shots,
                meta_shots,
                inner_iters,
                meta_batch_size,
                ibp_epsilon,
                mixup,
                ibp_layers):

        # Training function for MAML, MAML+IBP, and MAML+IBI learners.

        # For record keeping
        upper_loss_rec, lower_loss_rec, task_loss_rec, total_loss_rec = 0, 0, 0, 0

        # Triigers FOMAML and variants if required.
        create_graph, retain_graph = True, True
        if order == 1:
            create_graph, retain_graph = False, False

        self.meta_optim.zero_grad()

        if mixup is True:
            random_task = np.random.rand(0, meta_batch_size)

        # Iterate over tasks in a meta-batch
        for task_ind in range(meta_batch_size):

            fast_weight = OrderedDict(self.net.named_parameters())

            train_set, test_set = _split_train_test(
                _sample_mini_dataset(dataset, num_classes, num_shots+meta_shots), test_shots=meta_shots)

            # Support set
            inputs, labels = zip(*train_set)
            inputs = torch.stack(inputs).to(self.device)
            labels = torch.tensor(labels).to(self.device)

            # Fix ordering
            labels, sort_index = torch.sort(labels)
            inputs = inputs[sort_index]

            inputs_cat = torch.cat([inputs+ibp_epsilon, inputs, inputs-ibp_epsilon], 0)

            # Fast adaptation steps
            for _ in range(inner_iters):

                if mixup is True and task_ind == random_task:
                    # For MAML+IBI
                    _, logits = self.net.functional_forward(inputs_cat, fast_weight,
                        ibp_layers, mixup, num_classes, self.beta_a, self.beta_b)

                    b_size = logits.shape[0]//2
                    logits_o = logits[:b_size]
```

```
                    logits_ulo = logits[b_size:]

                    fast_loss = (F.cross_entropy(logits_o, labels) +
                        F.cross_entropy(logits_ulo, labels))/2
                else:
                    # For MAML and MAML+IBP
                    _, logits = self.net.functional_forward(inputs, fast_weight,
                        None, False, None, None, None)

                    fast_loss = F.cross_entropy(logits, labels)

                fast_gradients = torch.autograd.grad(fast_loss, fast_weight.values(),
                    create_graph=create_graph)

                fast_weight = OrderedDict(
                    (name, param - self.update_lr * grad_param)
                    for ((name, param), grad_param) in zip(fast_weight.items(), fast_gradients))

            # Query set
            inputs, labels = zip(*test_set)
            inputs = torch.stack(inputs).to(self.device)
            labels = torch.tensor(labels).to(self.device)

            # Fix ordering
            labels, sort_index = torch.sort(labels)
            inputs = inputs[sort_index]

            if ibp_layers is None:
                # Vanilla MAML
                _, logits = self.net.functional_forward(inputs, fast_weight,
                    None, False, None, None, None)
                total_loss = F.cross_entropy(logits, labels)
                task_loss_rec = task_loss_rec + total_loss.item()
                total_loss_rec = total_loss_rec + total_loss.item()

            else:
                # For MAML+IBP and MAML+IBI
                inputs_cat = torch.cat([inputs+ibp_epsilon, inputs, inputs-ibp_epsilon], 0)

                if mixup is True and task_ind == random_task:
                    # For MAML+IBI
                    ibp_estimate, logits = self.net.functional_forward(
                        inputs_cat, fast_weight, ibp_layers, mixup, num_classes,
                        self.beta_a, self.beta_b)

                    b_size = logits.shape[0]//2
                    logits_o = logits[:b_size]
                    logits_ulo = logits[b_size:]

                    task_loss = (F.cross_entropy(logits_o, labels) +
                        F.cross_entropy(logits_ulo, labels))/2
                else:
                    # For MAML+IBP
                    ibp_estimate, logits = self.net.functional_forward(
                        inputs_cat, fast_weight, ibp_layers, False, None, None, None)

                    task_loss = F.cross_entropy(logits, labels)

                # Find the propagated bounds
                b_size = ibp_estimate.shape[0]//3

                ibp_estimate_u = ibp_estimate[:b_size]
                ibp_estimate_o = ibp_estimate[b_size:2*b_size]
                ibp_estimate_l = ibp_estimate[2*b_size:]

                # Calculate $\mathcal{L}_{UB}$ and $\mathcal{L}_{LB}$.
                upper_loss = F.mse_loss(ibp_estimate_u, ibp_estimate_o)
                lower_loss = F.mse_loss(ibp_estimate_l, ibp_estimate_o)

                # Dynamic weighting of losses
                concat_loss = torch.cat([task_loss.unsqueeze(0),
                    upper_loss.unsqueeze(0), lower_loss.unsqueeze(0)], 0)

                weights = F.softmax(concat_loss/self.softmax_temp, dim=0)
                total_loss = torch.sum(concat_loss * weights)

                # Record keeping
                upper_loss_rec = upper_loss_rec + upper_loss.item()
                lower_loss_rec = lower_loss_rec + lower_loss.item()
                task_loss_rec = task_loss_rec + task_loss.item()
                total_loss_rec = total_loss_rec + total_loss.item()

            total_loss.backward(retain_graph=retain_graph)

    # Averaging the loss over meta batches
    for params in self.net.parameters():
        params.grad = params.grad / meta_batch_size

    # update the meta learner parameters
    self.meta_optim.step()
    self.meta_optim.zero_grad()
```

```python
            upper_loss_rec = upper_loss_rec / meta_batch_size
            lower_loss_rec = lower_loss_rec / meta_batch_size
            task_loss_rec = task_loss_rec / meta_batch_size
            total_loss_rec = total_loss_rec / meta_batch_size

            return upper_loss_rec, lower_loss_rec, task_loss_rec, total_loss_rec

    def evaluate(self,
                 dataset,
                 num_classes,
                 num_shots,
                 inner_iters):

        # Run a single evaluation of the model.

        # Preserve currently trained model.
        old_state = deepcopy(self.net.state_dict())
        fast_weight = OrderedDict(self.net.named_parameters())

        train_set, test_set = _split_train_test(_sample_mini_dataset(dataset, num_classes, num_shots+1))

        # Support set
        inputs, labels = zip(*train_set)
        inputs = (torch.stack(inputs)).to(self.device)
        labels = (torch.tensor(labels)).to(self.device)

        # Fast adaptation
        for _ in range(inner_iters):

            _, logits = self.net.functional_forward(inputs, fast_weight,
                None, False, None, None, None)
            fast_loss = F.cross_entropy(logits, labels)
            fast_gradients = torch.autograd.grad(fast_loss, fast_weight.values())

            fast_weight = OrderedDict(
                (name, param - self.update_lr * grad_param)
                for ((name, param), grad_param) in zip(fast_weight.items(), fast_gradients))

        # Query set
        inputs, labels = zip(*test_set)
        inputs = (torch.stack(inputs)).to(self.device)
        labels = (torch.tensor(labels)).to(self.device)

        # Inference
        _, logits = self.net.functional_forward(inputs, fast_weight,
            None, False, None, None, None)
        test_preds = (F.softmax(logits, dim=1)).argmax(dim=1)

        # Accuracy
        num_correct = torch.eq(test_preds, labels).sum()

        # Return network to original state for safety.
        self.net.load_state_dict(old_state)

        return num_correct.item()

def _sample_mini_dataset(dataset, num_classes, num_shots):

    # Sample a few shot task from a dataset.

    shuffled = list(dataset)
    random.shuffle(shuffled)
    for class_idx, class_obj in enumerate(shuffled[:num_classes]):
        for sample in class_obj.sample(num_shots):
            yield (sample, class_idx)

def _mini_batches(samples, batch_size, num_batches):

    # Generate mini-batches from some data.

    samples = list(samples)
    cur_batch = []
    batch_count = 0
    while True:
        random.shuffle(samples)
        for sample in samples:
            cur_batch.append(sample)
            if len(cur_batch) < batch_size:
                continue
            yield cur_batch
            cur_batch = []
            batch_count += 1
            if batch_count == num_batches:
                return

def _split_train_test(samples, test_shots=1):

    # Split a few-shot task into a train and a test set.

    train_set = list(samples)
    test_set = []
    labels = set(item[1] for item in train_set)
```

```
            for _ in range(test_shots):
                for label in labels:
                    for i, item in enumerate(train_set):
                        if item[1] == label:
                            del train_set[i]
                            test_set.append(item)
                            break
            if len(test_set) < len(labels) * test_shots:
                raise IndexError('not_enough_examples_of_each_class_for_test_set')
            return train_set, test_set
```

Training function: "src/train_model.py"

```python
import os
import numpy as np

import torch
from .learners import Learner

def train(learner,
          train_set,
          val_set,
          model_output_file=None,
          model_save_path=None,
          order=None,
          num_classes=None,
          num_shots=None,
          meta_shots=None,
          inner_iters=None,
          meta_batch_size=None,
          meta_iters=None,
          eval_inner_iters=None,
          eval_interval=None,
          eval_interval_sample=None,
          ibp_epsilon=None,
          mixup=False,
          ibp_layers=None):

    # Train a model on a dataset.
    train_accuracy, val_accuracy = [], []
    upper_loss_store, lower_loss_store, task_loss_store, total_loss_store = [], [], [], []

    # Loop over the training steps.
    for i in range(meta_iters+1):

        # Find current value of interval coefficient.
        cur_ibp_epsilon = eps_scheduler(i, meta_iters, ibp_epsilon)

        # Train the learner for a step.
        upper_loss, lower_loss, task_loss, total_loss = learner.train_step(train_set, order=order,
                                                     num_classes=num_classes, num_shots=num_shots,
                                                     meta_shots=meta_shots,
                                                     inner_iters=inner_iters,
                                                     meta_batch_size=meta_batch_size,
                                                     ibp_epsilon=cur_ibp_epsilon,
                                                     mixup=mixup,
                                                     ibp_layers=ibp_layers)

        # Record losses
        upper_loss_store.append(upper_loss)
        lower_loss_store.append(lower_loss)
        task_loss_store.append(task_loss)
        total_loss_store.append(total_loss)

        if i % eval_interval == 0:

            # Perform intermediate evaluation.
            total_correct = 0
            for _ in range(eval_interval_sample):
                total_correct = total_correct + learner.evaluate(train_set,
                                                 num_classes=num_classes, num_shots=num_shots,
                                                 inner_iters=eval_inner_iters)

            train_accuracy.append(total_correct / (eval_interval_sample * num_classes))

            save_path = model_save_path + '/intermediate_' + str(i) + '_model.pt'

            torch.save({'model_state': learner.net.state_dict(),
                        'meta_optim_state': learner.meta_optim.state_dict()},
                       save_path)

            total_correct = 0
            for _ in range(eval_interval_sample):
                total_correct = total_correct + learner.evaluate(val_set,
                                                 num_classes=num_classes, num_shots=num_shots,
                                                 inner_iters=eval_inner_iters)
            val_accuracy.append(total_correct / (eval_interval_sample * num_classes))

            with open(model_output_file, 'a+') as fp:
                print('batch_%d:_train=%f_val=%f' % (i,
                      train_accuracy[-1], val_accuracy[-1]), file=fp)
```

```
        # Intermediate record keeping.
        res_save_path = model_save_path + '/' + 'intermediate_accuracies.npz'
        loss_save_path = model_save_path + '/' + 'intermediates_losses.npz'

        np.savez(res_save_path, train_accuracy=np.array(train_accuracy),
            val_accuracy=np.array(val_accuracy))

        np.savez(loss_save_path, upper_loss=np.array(upper_loss_store),
            lower_loss=np.array(lower_loss_store), task_loss=np.array(task_loss_store),
            total_loss=np.array(total_loss_store))

def eps_scheduler(i, meta_iters, ibp_epsilon):

    # Schedule the value of interval coefficient.

    if i < meta_iters*0.9:
        return (i / (meta_iters*0.9)) * ibp_epsilon

    return ibp_epsilon
```

Inference function: "src/eval_model.py"

```
"""
Helpers for evaluating models.
"""
import numpy as np
from .learners import Learner

def bulk_evaluate(learner,
            dataset,
            num_classes=5,
            num_shots=5,
            eval_inner_iters=10,
            num_samples=10000):

    # For evaluating the learner on a set of tasks.
    total_correct = []
    for _ in range(num_samples):
        total_correct.append(learner.evaluate(dataset,
                        num_classes=num_classes, num_shots=num_shots,
                        inner_iters=eval_inner_iters))

    total_accuracies = np.array(total_correct) / num_classes
    test_accuracy = total_accuracies.sum() / num_samples
    test_cnf = np.std(total_accuracies)

    # For confidence interval 0.95%
    # z_score = 1.96
    # test_cnf = z_score * (test_cnf / (np.sqrt(num_samples)))

    return test_accuracy, test_cnf
```