A FUNCTIONAL PERSPECTIVE ON MULTI-LAYER OUT-OF-DISTRIBUTION DETECTION

ABSTRACT

A crucial component for implementing reliable classifiers is detecting examples far from the reference (training) distribution, referred to as out-of-distribution (OOD) samples. A key feature of OOD detection is to exploit the network by extracting statistical patterns and relationships through the pre-trained multi-layer classifier. Despite achieving solid results, state-of-the-art methods require either additional OOD examples, expensive computation of gradients, or are tightened to a particular architecture, limiting their applications. This work adopts an original approach based on a functional view of the network that exploits the sample's trajectories through the various layers and their statistical dependencies. In this new framework, OOD detection translates into detecting samples whose trajectories differ from the typical behavior characterized by the training set. Our method significantly decreases the OOD detection error of classifiers trained on ImageNet and outperforms the state-of-the-art methods on average AUROC and TNR at 95% TPR. We demonstrate that the functional signature left by a sample in a network carries relevant information for OOD detection.

1 INTRODUCTION

The current ability of a Deep Neural Network (DNN) to generalize to new data is mostly restricted to priorly known concepts in the training dataset. In real-world scenarios, Machine Learning (ML) models may encounter Out-Of-Distribution (OOD) samples, such as data belonging to novel concepts (classes) (Pimentel et al., 2014), abnormal samples (Tishby & Zaslavsky, 2015), or even carefully crafted attacks designed to exploit the model (Szegedy et al., 2013). The behavior of ML systems on unseen data is of great concern for safety-critical applications (Amodei et al., 2016b;a), such as medical diagnosis in healthcare (Subbaswamy & Saria, 2020), autonomous vehicle control in transportation (Bojarski et al., 2016) among others. To address safety issues arising from the presence of OOD samples, a successful line of work aims at augmenting ML models with an OOD binary detector to distinguish between abnormal and in-distribution examples (Hendrycks & Gimpel, 2017). An analogy to the detector is the human body's immune system, with the task of differentiating between antigens and the body itself.

Distinguishing OOD samples is challenging, and previous works developed detectors by combining scores at the various layers of the multi-layer pre-trained classifier (Sastry & Oore, 2020; Lee et al., 2018; Gomes et al., 2022; Huang et al., 2021). These detectors require either a held-out OOD dataset (e.g., adversarially generated or OOD data) or ad-hoc methods to linearly combine OOD scores computed on each layer embedding tightened to a particular architecture. A key observation is that existing aggregation techniques overlook the sequential nature of the underlying problem and, thus, limit the discriminative power of those methods. Indeed, an input sample passes consecutively through each layer and generates a highly correlated signature that can be statistically characterized. Our observations in this work motivate the fact that:

The input's trajectory through a network is key for discriminating typical from atypical samples.

In this paper, we introduce a significant change of perspective. Instead of looking at each layer score independently, we cast them into a sequential representation that captures the statistical trajectory of an input sample through the various layers of a multi-layer neural network. To this end, we adopt a functional point of view by considering the sequential representation as curves parametrized by

Figure 1: The left-hand side of the figure shows the feature extraction process of a deep neural network classifier f. The mapping of the hidden representations of an input sample into a functional representation is given by a function ϕ. The functional representation of samples encodes valuable information for the downstream task of OOD detection. The right hand side of the figure shows how our method computes the OOD score s of a sample during test time. A projection of the sample's trajectory into the training reference trajectory $\hat{u}$ is computed. A threshold γ is set to obtain a binary OOD discriminator g.

each layer. Consequently, we redefine the problem of OOD detection as that of detecting samples whose trajectories are abnormal (or atypical) compared to reference trajectories characterized by the training set. Our method, which requires little parameter tuning and, perhaps more importantly, no additional OOD data, can identify OOD samples from their trajectories. Furthermore, we show that typical multivariate detection methods fail to detect OOD patterns, which may manifest in an isolated fashion by shifting in magnitude or overall shape. Figure 1 summarizes our method.

Contributions. This work presents a new principle and unsupervised method for detecting OOD samples that do not require OOD (or extra) data and brings novel insights into the problem of OOD detection. Our main contributions can be summarized as follows.

1. *A novel problem formulation.* We reformulate the problem of OOD detection through a functional perspective that effectively captures the statistical dependencies of an input sample's path across a multi-layer neural classifier. Moreover, we propose a map from the multivariate feature space (at each layer) to a functional space that relies on the Cosine similarity between the test sample and a training reference at the layer and the sample's ℓ_2 norm. It is computationally efficient and straightforward.

2. *Computing OOD scores from trajectories.* We extract the training trajectories to have an average reference trajectory on which we project test trajectories to measure their similarity w.r.t the training centroid. Low similarity indicates that the test sample is likely sampled from OOD.

3. *Empirical evaluation.* We validate the value of the proposed method using a mid-size OOD detection benchmark on ImageNet-1k. We obtain competitive results, demonstrating an average ROC gain of up to 3% across three architectures and four OOD datasets. We release our code anonymized online.

2 RELATED WORKS

This section briefly discusses prior work in OOD detection, highlighting confidence-based and feature-based methods without special training as they resonate the most with our work. Another thread of research relies on re-training for learning more appropriate representations adapted to OOD detection (Mohseni et al., 2020; Bitterwolf et al.; Mahmood et al., 2021), either through contrastive training (Hendrycks et al., 2019; Winkens et al., 2020; Sehwag et al., 2021), regularization (Lee et al., 2021; Nandy et al., 2021; Hein et al., 2019; Du et al., 2022), generative (Schlegl et al., 2017; ood, 2019; Xiao et al.; Ren et al.; Zhang et al., 2021), or ensemble (Vyas et al., 2018; Choi & Jang,

2018) based approaches. Related subfields are open set recognition (Geng et al., 2021), novelty detection (Pimentel et al., 2014), anomaly detection (Chandola et al., 2009; Chalapathy & Chawla, 2019), outlier detection (Hodge & Austin, 2004), and adversarial attacks detection (Akhtar & Mian, 2018).

Confidence-based OOD detection. A natural measure of uncertainty of a sample's label is the classification model's softmax output. Hendrycks & Gimpel (2017) observed that the maximum of the softmax output could be used as a discriminative score between in-distribution and OOD samples. Hein et al. (2019) observed that it may still assign overconfident values to OOD examples. Liang et al. (2018) and Hsu et al. (2020) propose re-scaling the softmax response with a temperature value and a pre-processing technique that further separates in- from out-of-distribution examples. Authors of Liu et al. (2020) propose an energy-based OOD detection score by replacing the softmax confidence score with the free energy function. Sun & Li (2022) proposes sparsification of the classification layer weights to improve OOD detection by regularizing predictions.

Feature-based OOD detection. This line of research focuses on exploring latent representations for OOD detection. For instance, Haroush et al. (2021) considers using statistical tests, Sastry & Oore (2020) rely on higher-order Grams matrices, Quintanilha et al. (2019) uses mean and standard deviation within feature maps, Sun et al. (2021) proposes clipping the activations to boost OOD detection performance, while recent work Huang et al. (2021) also explores the gradient space. Normalizing and residual flows to estimate the probability distribution of the feature space were proposed in Kirichenko et al. and Zisselman & Tamar (2020). Perhaps one of the most widely used techniques relies on the Gaussian mixture assumption for the hidden representations and the Mahalanobis distance (Lee et al., 2018; Ren et al., 2021) or further information geometry tools (Gomes et al., 2022). The reasons are its simplicity, performance, and geometrical explanation. Efforts toward combining multiple features to improve performance were previously explored (Lee et al., 2018; Sastry & Oore, 2020; Gomes et al., 2022). The strategy relies heavily upon having additional data for tuning the detector or focusing on specific model architectures, which are limiting factors in real-world applications. Lin et al. (2021) rely on networks with multiple classifiers and introduces a dynamic OOD detection method which selects the index of the layer in test time to compute the score from. Sun et al. (2022) proposes non-parametric nearest-neighbor based on the Euclidean distance for OOD detection.

3 PRELIMINARIES

We start by recalling the general setting of the OOD detection problem from a mathematical point of view. Then, we motivate our method through a simple illustrative example.

3.1 BACKGROUND

Let (X, Y) be a random variable valued in a space $\mathcal{X} \times \mathcal{Y}$ with unknown probability density function (pdf) p_{XY} and probability distribution P_{XY}. Here, $\mathcal{X} \subseteq \mathbb{R}^d$ represents the covariate space and $\mathcal{Y} = \{1, \ldots, C\}$ corresponds to the labels attached to elements from $\mathcal{X}$. The training dataset $\mathcal{S}_N = \{(\boldsymbol{x}_i, y_i)\}_{i=1}^N$ is defined as independent and identically distributed (i.i.d) realizations of P_{XY}. From this formulation, detecting OOD samples boils down to building a binary rule $g : \mathcal{X} \rightarrow \{0, 1\}$ through a soft scoring function $s : \mathcal{X} \rightarrow \mathbb{R}$ and a threshold $\gamma \in \mathbb{R}$. Namely, a new observation $\boldsymbol{x} \in \mathcal{X}$ is then considered as *in-distribution*, i.e., generated by P_{XY}, when $g(\boldsymbol{x}) = 0$ and as OOD when $g(\boldsymbol{x}) = 1$. Finding this rule g from $\mathcal{X}$ can become intractable when the dimension d is large. Thus, previous work rely on a multi-layer pre-trained classifier $f_\theta : \mathcal{X} \rightarrow \mathcal{Y}$ defined as:

$$f_\theta(\cdot) = h \circ f_L \circ f_{L-1} \circ \cdots \circ f_1(\cdot),$$

with $L \geq 1$ layers, where $f_\ell : \mathbb{R}^{d_{\ell-1}} \rightarrow \mathbb{R}^{d_\ell}$ is the ℓ-th layer of the multi-layer neural classifier, d_ℓ denotes the dimension of the latent space induced by the ℓ-th layer ($d_0 = d$), and h indicates the classifier that outputs the logits. We also define $\boldsymbol{z}_\ell = (f_\ell \circ \cdots \circ f_1)(\boldsymbol{x})$ as the latent vectorial representation at the ℓ-th layer for an input sample $\boldsymbol{x}$. We will refer to the logits as $\boldsymbol{z}_{L+1}$ and h as f_{L+1} to homogenize notation. It is worth emphasizing that the trajectory of $(\boldsymbol{z}_1, \boldsymbol{z}_2, \ldots, \boldsymbol{z}_{L+1})$ corresponding to a test input $\boldsymbol{x}_0$ are dependent random variables whose joint distribution strongly depends on the underlying distribution of the input.

Therefore, the design of function $g(\cdot)$ is typically based on the three key steps:

(a) Example of a mispecified model in a toy example in 2D caused by held-out OOD dataset.

(b) Trajectory of data through a network with 25% and 75% percentile bounds.

(c) Correlation between layers training scores in a network, highlighting structure in the trajectories.

Figure 2: Figure 2a summarizes the limitation of current supervised methods for aggregating layer scores that rely on held-out OOD or pseudo-OOD data. It biases the decision boundary (D.B) that doesn't generalize well to other types of OOD data. We observed that in-distribution and OOD data have disparate trajectories through a network (Fig. 2b). We can observe a clear separation on the last five features. Also, these features are correlated in a sequential fashion, as observed in Fig. 2c.

(i) A similarity measure $d(\cdot\,;\cdot)$ (e.g., Cosine similarity, Mahalanobis distance, etc.) between a sample and a population is applied at each layer to measure the similarity (or dissimilarity) of a test input $\boldsymbol{x}_0$ at the ℓ-th layer $\boldsymbol{z}_{\ell,0} = (f_\ell \circ \cdots \circ f_1)(\boldsymbol{x}_0)$ w.r.t. the population of the training examples observed at the same layer $\{\boldsymbol{z}_\ell = (f_\ell \circ \cdots \circ f_1)(\boldsymbol{x}) : \boldsymbol{x} \in \mathcal{S}_N\}$.

(ii) The layer-wise score obtained is then mapped to the real line collecting the OOD scores.

(iii) Lastly, a threshold is chosen to build the final decision function.

A fundamental ingredient remains in step (ii):

How to consistently leverage the information collected from multiple layers outputs in an unsupervised way, i.e., without resorting to OOD or pseudo-OOD examples?

3.2 FROM INDEPENDENT MULTI-LAYER SCORES TO A SEQUENTIAL PERSPECTIVE OF OOD DETECTION

Previous multi-feature OOD detection works treat step (ii) as a supervised learning problem (Lee et al., 2018; Gomes et al., 2022) for which the solution is a linear binary classifier. The objective is to find a linear combination of the scores obtained at each layer that will sufficiently separate in-distribution from OOD samples. A held-out OOD dataset is collected from true (or pseudo-generated) OOD samples. The linear soft novelty score function s_α writes:

$$s_\alpha(\boldsymbol{x}_0) = \sum_{\ell=1}^{L} \alpha_\ell \cdot d\left(\boldsymbol{x}_0; \{(f_\ell \circ \cdots \circ f_1)(\boldsymbol{x}) : \boldsymbol{x} \in \mathcal{S}_N\}\right).$$

The shortcomings of this method are the need for extra data or ad-hoc parameters, which results in decision boundaries that underfit the problem and fail to capture certain types of OOD samples. To illustrate this phenomenon, we designed a toy example (see Figure 2a) where scores are extracted from two features fitting a linear discriminator on held-out in-distribution (IND) and OOD samples. We show an area of unreliable predictions where OOD samples cannot be detected due to the misspecification of the linear model. Of course, one could introduce a non-linear discriminator that better captures the geometry of the data for this 2D toy example. However, it becomes challenging as we move to higher dimensions with limited data.

The sequential nature of feature extraction matters. By reformulating the problem from a functional point of view, we can identify trends and typical trajectories presented in the data. Figure 2 shows the dispersion of trajectories at step (ii) coming from the in-distribution and OOD samples. These patterns are extracted from multiple latent representations and aligned on a time-series-like object, clearly distinguishing training samples. *We observed that trajectories coming from OOD*

samples exhibit a different shape when compared to typical trajectories from training data. Thus, to determine if an instance belongs to a reference distribution, we can test if the observed path is close to the functional data extracted from the training set. We will do so class-wise as we plan to retain the most structural information about the downstream task while showcasing the relevant shape differences.

4 FUNCTIONAL OUT-OF-DISTRIBUTION DETECTION

This section presents our OOD detection framework, which applies to any pre-trained multi-layer neural network with no requirements for OOD samples. We describe our method through two key steps: functional representation of the input sample (see Section 4.1) and test time OOD score computation (see Section 4.2).

4.1 TOWARDS A FUNCTIONAL REPRESENTATION

The first step to obtaining a functional representation of the data from the multivariate hidden representations is to reduce each one to a scalar or vector. To do so, we first compute the training population references defined as the layer-wise class-conditional average vectors:

$$\boldsymbol{\mu}_{\ell,y} = \frac{1}{N_y} \sum_{i=1}^{N_y} \boldsymbol{z}_{\ell,i}, \tag{1}$$

where $N_y = \left| \{ \boldsymbol{z}_{\ell,i} \mid y_i = y, \forall i \in \{1..N\} \} \right|$, $1 \leq \ell \leq L+1$ and $\boldsymbol{z}_{\ell,i} = (f_\ell \circ \cdots \circ f_1)(\boldsymbol{x}_i)$.

Given an arbitrary input example, we compute its features (including the logits) and their similarity w.r.t. the training average for each class y weighted averaged by the prediction probability vector $f_\theta(\cdot)$, leading to $L+1$ scores. We rely on the probability weighted scalar projection[1] of the sample features' $\boldsymbol{z}_\ell$ onto the direction of the average training features as similarity score:

$$\mathrm{d}_\ell(\boldsymbol{x}; \boldsymbol{\mu}_\ell) = \sum_{y=1}^{C} \sigma_y(\boldsymbol{x}) \cdot \mathrm{proj}_{\boldsymbol{\mu}_{\ell,y}} \boldsymbol{z}_\ell = \|\boldsymbol{z}_\ell\| \sum_{y=1}^{C} \sigma_y(\boldsymbol{x}) \cos\left(\angle\left(\boldsymbol{z}_\ell, \boldsymbol{\mu}_{\ell,y}\right)\right), \tag{2}$$

where $\|\cdot\|$ is the ℓ_2-norm, $\angle(\cdot, \cdot)$ is the angle between two vectors, and $\sigma_y(\boldsymbol{x}; f_\theta)$ is the softmax function on the logits $f_\theta(\boldsymbol{x})$. Hence, our layer-wise scores rely on the notions of vector length and angle between vectors, which can be generalized to any n-dimensional inner product space without imposing any geometrical constraints.

It is worth emphasizing that our layer score has some advantages compared to the class conditional Gaussian model first introduced in Lee et al. (2018) and the Gram matrix based-method introduced in Sastry & Oore (2020). Our layer score encompasses a broader class of distributions as we do not suppose an specific underlying probability distribution. We avoid computing covariance matrices, which are often ill-conditioned for latent representations of DNNs. Since we do not store covariance matrices, our functional approach has a negligible overhead regarding memory requirements. Also, our method can be applied to any vector-based hidden representation, not being restricted to matrix-based representations as in Sastry & Oore (2020). Thus, our approach applies to a broader range of models, including transformers.

By computing the scalar projection at each layer, we obtain the following *functional neural-representation* extraction function:

$$\begin{aligned} \phi : \mathcal{X} &\to \mathbb{R}^{L+1} \\ \boldsymbol{x} &\mapsto \left[\mathrm{d}_1\left(\boldsymbol{x}; \boldsymbol{\mu}_1\right), \ldots, \mathrm{d}_{L+1}\left(\boldsymbol{x}; \boldsymbol{\mu}_{L+1}\right) \right]. \end{aligned} \tag{3}$$

We apply ϕ to the training input $\boldsymbol{x}_i$ to obtain the representation of the training sample across the network $\boldsymbol{u}_i = \phi(\boldsymbol{x}_i)$. We consider the related vectors $\boldsymbol{u}_i, \forall i \in [1 : N]$ as curves parameterized by the layers of the network. Thus, we can map samples from the representation to a functional space while retaining information on the typicality of the sample w.r.t the training dataset. We build a training dataset $\mathcal{U} = \{\boldsymbol{u}_i\}_{i=1}^{N}$ from these functional representations that will be useful for detecting

---

[1] Other metrics to measure the similarity of an input w.r.t. the population of examples can also be used.

OOD samples during test time. We then rescale the training set trajectories w.r.t the maximum value found at each coordinate to obtain layer-wise scores on the same scaling for each coordinate. Hence, for $j \in \{1, \ldots, L+1\}$, let $\max(\mathcal{U}) := [\max_i u_{i,1}, \ldots, \max_i u_{i,L+1}]^\top$, we can compute a reference trajectory $\bar{\boldsymbol{u}}$ for the entire training dataset defined in equation 4 that will serve as a global *typical reference* to compare test trajectories with.

$$\bar{\boldsymbol{u}} = \frac{1}{N} \sum_{i=1}^{N} \frac{\boldsymbol{u}_i}{\max(\mathcal{U})}. \tag{4}$$

4.2 COMPUTING THE OOD SCORE AT TEST TIME

At inference time, we first re-scale the test sample's trajectory as we did with the training reference $\tilde{\phi}(\boldsymbol{x}) = \phi(\boldsymbol{x})/\max(\mathcal{U})$. Then, we compute a similarity score w.r.t this typical reference that will be our OOD score. We choose as metric also the scalar projection of the test vector to the training reference. In practical terms, it boils down to the *inner product* between the test sample's trajectory and the training set's typical reference trajectory since the norm of the average trajectory is constant for all test samples. Mathematically, our scoring function $s : \mathcal{X} \mapsto \mathbb{R}$ writes:

$$s(\boldsymbol{x}; \bar{\boldsymbol{u}}) = \langle \tilde{\phi}(\boldsymbol{x}), \bar{\boldsymbol{u}} \rangle = \sum_{j=1}^{L+1} \tilde{\phi}(\boldsymbol{x})_j \bar{\boldsymbol{u}}_j. \tag{5}$$

which is bounded by Cauchy-Schwartz's inequality. From this OOD score, we can derive a binary classifier g by fixing a threshold $\gamma \in \mathbb{R}$:

$$g(\boldsymbol{x}; s, \gamma) = \left\{ \begin{array}{ll} 1, & \text{if } s(\boldsymbol{x}) \leq \gamma \\ 0, & \text{otherwise,} \end{array} \right. \tag{6}$$

where $g(\boldsymbol{x}) = 1$ means that the input sample $\boldsymbol{x}$ is classified as being out-of-distribution. Please refer to Appendix (see Section A.1) for further details on the algorithm.

5 EXPERIMENTAL SETTING

This section describes the experimental setting, including the datasets used, the pre-trained DNN architectures, the evaluation metrics, and other essential information. We open-source our code anonymized in https://github.com/ood-trajectory/ood-trajectory.

5.1 DATASETS

We set as *in-distribution* dataset *ImageNet-1k* (= ILSVRC2012; Deng et al., 2009) for all of our experiments, which is a challenging mid-size and realistic dataset that have been incorporated recently to OOD detection (Huang & Li, 2021). It contains around 1.28M training samples and 50,000 test samples belonging to 1000 different classes. For the *out-of-distribution* datasets, we take the same dataset splits introduced by Huang & Li (2021). The *iNaturalist* (Horn et al., 2017) dataset contains over 5,000 species of plant and animals. We consider a split with 10,000 test samples with concepts from 110 classes different from the in-distribution ones. The *Sun* (Xiao et al., 2010) dataset is a scene dataset of 397 categories. We considered a split with 10,000 randomly sampled test examples belonging to 50 categories. The *Places365* (Zhou et al., 2017) is also a scenes dataset with 365 different concepts. We also considered a random split with 10,000 samples from 50 disjoint categories. For the DTD or *Textures* (Cimpoi et al., 2014) dataset is composed of textural patterns. We considered all of the 5,640 available test samples. Note that there is a couple of overlaps between the semantics of classes of this dataset and ImageNet. We decided to keep the entire dataset in order to be comparable with Huang et al. (2021). We provide a study case on this in Section 6.

5.2 MODELS

We ran experiments with three models of different architectures. A *DenseNet-121* (Huang et al., 2017) pre-trained on ILSVRC-2012 with 8M parameters and test set top-1 accuracy of 74.43%. We reduced the intermediate representations from the transition blocks with an *adaptive max pooling*

| (a) Functional trajectories. | (b) OOD score histogram. | (c) ROC curve. |

Figure 3: Functional representation with 5 and 95% quantiles, histogram and ROC curve for our OOD score on a DenseNet-121 model with Textures as OOD dataset.

operation obtaining a final vector with a dimension equal to the number of channels of each output. The dimensions are 128, 256, 512, and 1024, respectively. We resize input images to 224×224 pixels. A *BiT-S-101* (Kolesnikov et al., 2020) model based on a ResNetv2-101 architecture with top-1 test set accuracy of 77.41% and 44.5M parameters. We extract features from the outputs of layers 1 to 4 and the penultimate layer, obtaining representations with sizes 256, 512, 1024, and 2048, respectively after max pooling. We resize input images to 480×480. We also ran experiments with a Vision Transformer (*ViT-B-16*; Dosovitskiy et al., 2021), which is trained on the ILSVRC2012 dataset with 82.64% top-1 test accuracy and 70M parameters. We take the output's class tokens for layers 1 to 13 and the encoder's output as latent representations, totaling 14 features of dimension 768 each. We resize images to 224×224. We download the DenseNet and Vision Transformer weights from PyTorch (Paszke et al., 2019) hub and the weights of Big Transfer from Kolesnikov et al. (2020). All models are trained from scratch on ImageNet-1k.

5.3 EVALUATION METRICS

We evaluate the methods in terms of ROC and TNR. The Area Under The Receiving Operation Curve (ROC) is the Area Under the curve representing the true negative rate against the false positive rate when considering a varying threshold. It measures how well can the OOD score distinguish between out- and in-distribution data in a threshold-independent manner. The True Negative Rate at 95% True Positive Rate (TNR at 95% TPR or TNR for short) is a threshold-dependent metric that provides the detector's performance in a reasonable choice of novelty threshold. It measures the accuracy in detecting OOD samples when the accuracy of detecting in-distribution samples is fixed at 95%. For both measures, higher is better.

5.4 BASELINE HYPERPARAMETERS

For ODIN (Liang et al., 2018), we set the temperature to 1000 and the noise magnitude to zero. We take a temperature equal to one for Energy (Liu et al., 2020). We set the temperature to one for GradNorm (GradN. for short; Huang et al., 2021). For Mahalanobis (Maha. for short; Lee et al., 2018), we take only the scores of the outputs of the penultimate layer of the network. The MSP (Hendrycks & Gimpel, 2017) does not have any hyperparameters. For ReAct (Sun et al., 2021), we compute the activation clipping threshold with a percentile equals to 90. For KNN (Sun et al., 2022) we set as hyperparameters $\alpha = 1\%$ and $k = 10$.

6 RESULTS AND DISCUSSION

We report our main results in Table 1, which includes the performance for the three pre-trained architectures, four OOD datasets, and seven detection methods. Our results are across the board consistent, obtaining an AUROC of 90% on average (see Table 1). It improves existing methods by a margin on all datasets and models.

Multivariate OOD Scores is Not Enough. Even though well-known multivariate novelty (or anomaly) detection techniques, such as One-class SVM (Cortes & Vapnik, 1995), Isolation Forest (Liu et al., 2008), Extended Isolation Forest (Hariri et al., 2021), Local Outlier Factor (LOF;

Table 1: Comparison against post-hoc state-of-the-art methods for OOD detection on the ImageNet benchmark. M+Ours stands for using the Mahalanobis distance-based layer score with our proposed unsupervised score aggregation algorithm based on trajectory similarity. Values are in percentage.

		iNaturalist		SUN		Places		Textures		Average	
		TNR	ROC	TNR	ROC	TNR	ROC	TNR	ROC	TNR	ROC
BiT-S-101	MSP	35.9	87.9	28.8	81.9	21.3	79.3	21.9	77.5	27.0	81.7
	ODIN	29.3	86.7	36.7	86.8	26.0	82.7	24.1	79.3	29.0	83.9
	Energy	25.0	84.5	39.8	87.3	27.2	82.7	24.2	78.8	29.0	83.3
	Mahalanobis	16.5	78.3	13.2	74.5	10.5	69.6	86.6	97.3	31.7	79.9
	GradNorm	41.3	86.0	55.2	88.2	39.0	83.3	41.2	81.0	44.2	84.6
	ReAct	46.2	88.9	10.7	65.9	7.0	62.0	8.5	65.8	18.1	70.7
	KNN	39.7	88.9	22.1	77.5	20.6	75.9	54.1	89.7	34.1	83.0
	Ours	**67.0**	**91.7**	**59.5**	**89.4**	**40.8**	82.3	85.1	96.7	**63.1**	**90.0**
DenseNet-121	MSP	50.7	89.1	33.0	81.5	30.8	81.1	32.9	79.2	36.9	82.7
	ODIN	60.4	92.8	45.2	87.0	40.3	85.1	45.3	85.0	47.8	87.5
	Energy	60.3	92.7	48.0	87.4	42.2	85.2	47.9	85.4	49.6	87.7
	Mahalanobis	3.5	59.7	4.8	57.0	4.6	54.8	54.4	88.3	16.8	64.9
	GradNorm	73.3	93.4	59.1	88.8	48.0	84.1	56.7	87.7	59.3	88.5
	ReAct	68.8	93.9	51.3	89.6	44.5	86.6	48.1	87.6	53.2	89.4
	KNN	57.1	92.1	33.2	83.6	26.8	79.6	81.5	96.5	49.7	88.0
	Ours	65.7	92.8	**68.0**	**92.1**	**52.4**	87.3	88.3	97.5	68.6	92.4
	ReAct+Ours	**80.4**	**96.4**	62.2	91.8	52.3	**88.0**	81.8	96.5	**69.2**	**93.2**
ViT-B-16	MSP	48.5	88.2	33.5	80.9	31.3	80.4	39.8	83.0	38.3	83.1
	ODIN	49.9	86.0	31.5	75.2	33.7	76.5	42.6	81.2	39.4	79.7
	Energy	35.9	79.2	27.2	70.2	25.7	68.4	41.5	79.3	32.6	74.3
	Mahalanobis	**81.2**	**96.0**	40.7	**85.3**	**40.0**	**84.2**	46.3	87.5	52.1	88.2
	GradNorm	53.5	91.2	**41.5**	85.3	38.3	83.4	48.1	86.5	45.3	86.6
	ReAct	33.4	85.5	26.9	78.8	25.6	77.3	42.2	84.5	32.0	81.5
	KNN	41.0	88.9	17.8	79.4	18.2	77.7	44.0	87.8	30.3	83.4
	Ours	58.6	93.3	32.2	82.1	31.5	80.7	56.7	91.1	44.7	86.8
	M+Ours	77.9	95.5	34.8	83.2	32.6	81.4	**79.1**	**94.9**	**56.1**	**88.8**

Breunig et al., 2000), k-NN approaches (Fix & Hodges, 1989) and distance-based approaches (Mahalanobis, 1936) are adapted to various scenarios, they showed to be inefficient for integrating layers' information. A hypothesis that explains this failure is the important sequential dependence pattern we noticed in the in-distribution layer-wise scores. Table 2 shows the performance of a few unsupervised aggregation methods based on a multivariate OOD detection paradigm. We tried typical methods: evaluating the Euclidean distance w.r.t the training set Gaussian representation, fitting an Isolation Forest, and a One-class SVM. We compare the results with the performance of taking *only* the penultimate layer scores, and we observe that the standard multivariate aggregation fails to improve the scores for DenseNet-121.

Table 2: The first two rows show single-layer baselines where *proj. penult.* is our layer score on the penultimate layer of the model. The subsequent rows show the performance of other unsupervised multivariate aggregation methods and our method. We ran experiments with a DenseNet-121 model.

	iNaturalist		SUN		Places		Textures		Average	
	TNR	ROC	TNR	ROC	TNR	ROC	TNR	ROC	TNR	ROC
Grad Norm	73.3	93.4	59.1	88.8	48.0	84.1	56.7	87.7	59.3	88.5
Penultimate layer	**78.9**	**95.2**	61.9	90.0	51.6	86.0	68.8	90.7	65.3	90.5
Euclidian distance	63.7	88.8	53.6	84.8	40.8	78.4	83.5	95.6	60.4	86.9
Mahalanobis distance	40.1	82.8	26.6	74.5	20.8	69.4	73.5	93.5	40.3	80.1
Isolation Forest	60.3	87.6	46.9	82.6	36.3	76.7	81.0	95.3	56.1	85.6
One Class SVM	64.2	89.0	54.0	85.0	41.2	78.6	83.8	95.7	60.8	87.0
Proj. (Ours)	65.7	92.8	**68.0**	**92.1**	**52.4**	**87.3**	**88.3**	**97.5**	**68.6**	**92.4**

Qualitative Evaluation of the Functional Dataset. The test in-distribution trajectories follow a well-defined trend very similar to the training distribution (see Figure 3a). While the OOD trajectories manifest mainly as shape and magnitude anomalies (w.r.t. the taxonomy of Hubert et al., 2015). These characteristics reflects on the histogram of our detection score (see Figure 3b). The

(a) A few examples from the Textures sharing semantic overlap with ImageNet classes.

(b) Trajectories of the leftmost examples of Fig. 4a and their OOD scores in parenthesis.

Figure 4: Study case on OOD detection of individual samples for our method. The badge on each image on Fig. 4a shows the label given by our OOD discriminator. We set as threshold 95% TPR.

in-distribution histogram is generally symmetric, while the histogram for the OOD data is typically skewed and has a smaller average. Please refer to the Appendix A.5 for additional figures.

Study Case. There are a few overlaps in terms of the semantics of class names in the Textures and ImageNet datasets. In particular, "honeycombed" in Textures versus "honeycomb" in ImageNet, "stripes" vs. "zebra", "tiger", and "tiger cat", and "cobwebbed" vs. "spider web". We showed that our method decreases the false negatives in this OOD benchmark. In order to better understand how our method can discriminate where baselines often fail, we designed a simple study case. Take the Honeycombed vs. Honeycomb, for instance (the first row of Fig. 4a shows four examples of this partition and a couple of examples from ImageNet). The honeycomb from ImageNet references natural honeycombs, usually found in nature, while honeycombed have a wider definition attached to artificial patterns. In this class, the Energy baseline makes 108 false negative mistakes, while we only make 20 mistakes. We noticed that some of our mistakes are aligned with real examples of honeycombs (e.g., the second example from the first row), whilst we confidently classify other patterns correctly as OOD. For the Spider webs class, most examples from Textures are visually closer to ImageNet. For the striped case (middle row), our method flags only 16 examples as being in-distribution, but we noticed an average higher score for the trajectories. Overall, the study shows that our scores are aligned with the semantic proximity between samples and the training set. Note that, for the animal classes, the context and head are essential features for classifying them.

Potential Shortcomings of our Method. We believe this work is only the first step in paving the way for efficient post-score aggregation as we have tackled an open and challenging problem of combining multi-layer information. However, we believe there is room for improvement since our metric lives in the inner product space, which is a case for more general structures found in Hilbert spaces that might contain more adequate metrics. Another concern that may arise is that, from a practical point of view, current third-party ML services often restrict the practitioner from accessing the intermediate outputs of the model in production. Nonetheless, the service provider has access to this information and could leverage it to deliver OOD detection as a service, for instance.

7 CONCLUSION

In this work, we introduced an original approach to OOD detection based on a functional view of the pre-trained multi-layer neural network. Our method detects samples whose trajectories differ from the typical behavior characterized by the training set. The key ingredient relies on the statistical dependencies of the scores extracted at each layer, using a purely self-supervised algorithm. Beyond the novelty and practical advantages of the algorithm, our results establish the value of using a functional approach as an unsupervised technique to combine multiple scores, which offers an exciting alternative to usual single-layer approaches. We hope this work will be a first step to pave a new way for future research to enhance the safety of AI systems.

REFERENCES

Out-of-distribution detection in classifiers via generation. In *Neural Information Processing Systems (NeurIPS 2019), Safety and Robustness in Decision Making Workshop*, 12/2019 2019.

Naveed Akhtar and Ajmal Mian. Threat of adversarial attacks on deep learning in computer vision: A survey. *CoRR*, abs/1801.00553, 2018. URL http://arxiv.org/abs/1801.00553.

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*, 2016a.

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul F. Christiano, John Schulman, and Dan Mané. Concrete problems in AI safety. *CoRR*, abs/1606.06565, 2016b.

Julian Bitterwolf, Alexander Meinke, and Matthias Hein. Certifiably adversarially robust detection of out-of-distribution data. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, pp. 16085–16095. Curran Associates, Inc.

Mariusz Bojarski, Davide Del Testa, Daniel Dworakowski, Bernhard Firner, Beat Flepp, Prasoon Goyal, Lawrence D Jackel, Mathew Monfort, Urs Muller, Jiakai Zhang, et al. End to end learning for self-driving cars. *arXiv preprint arXiv:1604.07316*, 2016.

Markus M. Breunig, Hans-Peter Kriegel, Raymond T. Ng, and Jörg Sander. Lof: Identifying density-based local outliers. 29(2), 2000. ISSN 0163-5808.

Raghavendra Chalapathy and Sanjay Chawla. Deep learning for anomaly detection: A survey. *CoRR*, abs/1901.03407, 2019. URL http://arxiv.org/abs/1901.03407.

Varun Chandola, Arindam Banerjee, and Vipin Kumar. Anomaly detection: A survey. 41(3), 2009. ISSN 0360-0300.

Hyun-Jae Choi and Eric Jang. Generative ensembles for robust anomaly detection. *ArXiv*, abs/1810.01392, 2018.

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2014.

Corinna Cortes and Vladimir Vapnik. Support-vector networks. *Machine learning*, 20(3):273–297, 1995.

J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *CVPR09*, 2009.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *ArXiv*, abs/2010.11929, 2021.

Xuefeng Du, Zhaoning Wang, Mu Cai, and Yixuan Li. Vos: Learning what you don't know by virtual outlier synthesis. *ArXiv*, abs/2202.01197, 2022.

Evelyn Fix and J. L. Hodges. Discriminatory analysis. nonparametric discrimination: Consistency properties. *International Statistical Review / Revue Internationale de Statistique*, 57(3):238–247, 1989. ISSN 03067734, 17515823.

Chuanxing Geng, Sheng-Jun Huang, and Songcan Chen. Recent advances in open set recognition: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 43(10):3614–3631, oct 2021. doi: 10.1109/tpami.2020.2981604.

Eduardo Dadalto Camara Gomes, Florence Alberge, Pierre Duhamel, and Pablo Piantanida. Igeood: An information geometry approach to out-of-distribution detection. In *International Conference on Learning Representations*, 2022.

Sahand Hariri, Matias Carrasco Kind, and Robert J. Brunner. Extended isolation forest. *IEEE Transactions on Knowledge and Data Engineering*, 33:1479–1489, 2021.

Matan Haroush, Tzviel Frostig, Ruth Heller, and Daniel Soudry. A statistical framework for efficient out of distribution detection in deep neural networks, 2021.

Matthias Hein, Maksym Andriushchenko, and Julian Bitterwolf. Why relu networks yield high-confidence predictions far away from the training data and how to mitigate the problem. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 41–50, 2019.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *International Conference on Learning Representations*, 2017.

Dan Hendrycks, Mantas Mazeika, and Thomas Dietterich. Deep anomaly detection with outlier exposure. In *International Conference on Learning Representations*, 2019.

Victoria Hodge and Jim Austin. A survey of outlier detection methodologies. 22(2), 2004. ISSN 0269-2821.

Grant Van Horn, Oisin Mac Aodha, Yang Song, Alexander Shepard, Hartwig Adam, Pietro Perona, and Serge J. Belongie. The inaturalist challenge 2017 dataset. *ArXiv*, abs/1707.06642, 2017.

Yen-Chang Hsu, Yilin Shen, Hongxia Jin, and Zsolt Kira. Generalized odin: Detecting out-of-distribution image without learning from out-of-distribution data. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10948–10957, 2020.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q. Weinberger. Densely connected convolutional networks. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 2261–2269, 2017. doi: 10.1109/CVPR.2017.243.

Rui Huang and Yixuan Li. Mos: Towards scaling out-of-distribution detection for large semantic space. *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 8706–8715, 2021.

Rui Huang, Andrew Geng, and Yixuan Li. On the importance of gradients for detecting distributional shifts in the wild. *ArXiv*, abs/2110.00218, 2021.

M. Hubert, P.J. Rousseeuw, and Pieter Segaert. Multivariate functional outlier detection. *Statistical Methods and Applications*, 24(2):177–202, 2015. ISSN 1613-981X. doi: 10.1007/s10260-015-0297-8.

Polina Kirichenko, Pavel Izmailov, and Andrew G Wilson. Why normalizing flows fail to detect out-of-distribution data. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, pp. 20578–20589. Curran Associates, Inc.

Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (bit): General visual representation learning. In *ECCV*, 2020.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 7167–7177. Curran Associates, Inc., 2018.

Saehyung Lee, Changhwa Park, Hyungyu Lee, Jihun Yi, Jonghyun Lee, and Sungroh Yoon. Removing undesirable feature contributions using out-of-distribution data. In *International Conference on Learning Representations*, 2021.

Shiyu Liang, Yixuan Li, and R. Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *International Conference on Learning Representations*, 2018.

Ziqian Lin, Sreya Dutta Roy, and Yixuan Li. Mood: Multi-level out-of-distribution detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021.

Fei Tony Liu, Kai Ming Ting, and Zhi-Hua Zhou. Isolation forest. In *2008 Eighth IEEE International Conference on Data Mining*, pp. 413–422, 2008. doi: 10.1109/ICDM.2008.17.

Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. *Advances in Neural Information Processing Systems*, 2020.

Prasanta Chandra Mahalanobis. On the generalized distance in statistics. *Proceedings of the National Institute of Sciences (Calcutta)*, 2:49–55, 1936.

Ahsan Mahmood, Junier Oliva, and Martin Styner. Multiscale score matching for out-of-distribution detection, 2021.

Sina Mohseni, Mandar Pitale, JBS Yadawa, and Zhangyang Wang. Self-supervised learning for generalizable out-of-distribution detection. *Proceedings of the AAAI Conference on Artificial Intelligence*, 34(04):5216–5223, Apr. 2020. doi: 10.1609/aaai.v34i04.5966.

Jay Nandy, Wynne Hsu, and Mong Li Lee. Towards maximizing the representation gap between in-domain & out-of-distribution examples, 2021.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.

Marco AF Pimentel, David A Clifton, Lei Clifton, and Lionel Tarassenko. A review of novelty detection. *Signal processing*, 99:215–249, 2014.

Igor M. Quintanilha, Roberto de M. E. Filho, José Lezama, Mauricio Delbracio, and Leonardo O. Nunes. Detecting out-of-distribution samples using low-order deep features statistics, 2019.

Jie Ren, Peter J. Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark Depristo, Joshua Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*. Curran Associates, Inc.

Jie Ren, Stanislav Fort, Jeremiah Liu, Abhijit Guha Roy, Shreyas Padhy, and Balaji Lakshminarayanan. A simple fix to mahalanobis distance for improving near-ood detection. *arXiv preprint arXiv:2106.09022*, 2021.

Chandramouli Shama Sastry and Sageev Oore. Detecting out-of-distribution examples with Gram matrices. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 8491–8501. PMLR, 13–18 Jul 2020.

Thomas Schlegl, Philipp Seeböck, Sebastian M. Waldstein, Ursula Schmidt-Erfurth, and Georg Langs. Unsupervised anomaly detection with generative adversarial networks to guide marker discovery, 2017.

Vikash Sehwag, Mung Chiang, and Prateek Mittal. Ssd: A unified framework for self-supervised outlier detection. *ArXiv*, abs/2103.12051, 2021.

Adarsh Subbaswamy and Suchi Saria. From development to deployment: dataset shift, causality, and shift-stable models in health ai. *Biostatistics*, 21(2):345–352, April 2020. ISSN 1465-4644. doi: 10.1093/biostatistics/kxz041.

Yiyou Sun and Yixuan Li. Dice: Leveraging sparsification for out-of-distribution detection. In *European Conference on Computer Vision*, 2022.

Yiyou Sun, Chuan Guo, and Yixuan Li. React: Out-of-distribution detection with rectified activations. In *NeurIPS*, 2021.

Yiyou Sun, Yifei Ming, Xiaojin Zhu, and Yixuan Li. Out-of-distribution detection with deep nearest neighbors. In *ICML*, 2022.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Naftali Tishby and Noga Zaslavsky. Deep learning and the information bottleneck principle. In *2015 ieee information theory workshop (itw)*, pp. 1–5. IEEE, 2015.

Apoorv Vyas, Nataraj Jammalamadaka, Xia Zhu, Dipankar Das, Bharat Kaul, and Theodore L. Willke. Out-of-distribution detection using an ensemble of self supervised leave-out classifiers. pp. 560–574, 2018.

Jim Winkens, Rudy Bunel, Abhijit Guha Roy, Robert Stanforth, Vivek Natarajan, Joseph R. Ledsam, Patricia MacWilliams, Pushmeet Kohli, Alan Karthikesalingam, Simon A. A. Kohl, taylan. cemgil, S. M. Ali Eslami, and Olaf Ronneberger. Contrastive training for improved out-of-distribution detection. *ArXiv*, abs/2007.05566, 2020.

J. Xiao, J. Hays, K. A. Ehinger, A. Oliva, and A. Torralba. Sun database: Large-scale scene recognition from abbey to zoo. In *2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pp. 3485–3492, 2010. doi: 10.1109/CVPR.2010.5539970.

Zhisheng Xiao, Qing Yan, and Yali Amit. Likelihood regret: An out-of-distribution detection score for variational auto-encoder. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, pp. 20685–20696. Curran Associates, Inc.

Yufeng Zhang, Wanwei Liu, Zhenbang Chen, Ji Wang, Zhiming Liu, Kenli Li, and Hongmei Wei. Out-of-distribution detection with distance guarantee in deep generative models, 2021.

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2017.

Ev Zisselman and Aviv Tamar. Deep residual flow for out of distribution detection. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.