ILLITERATE DALL·E LEARNS TO COMPOSE

ABSTRACT

DALL·E has shown an impressive ability of composition-based systematic generalization in image generation. This is possible because it utilizes the dataset of text-image pairs where the text provides the source of compositionality. Following this result, an important extending question is whether this compositionality can still be achieved even without conditioning on text. In this paper, we propose an architecture called *Slot2Seq* that achieves this text-free DALL·E by learning compositional slot-based representations purely from images, an ability lacking in DALL·E. Unlike existing object-centric representation models that decode pixels independently for each slot and each pixel location and compose them via mixture-based alpha composition, we propose to use the Image GPT decoder conditioned on the slots for a more flexible generation by capturing complex interaction among the pixels and the slots. In experiments, we show that this simple architecture achieves zero-shot generation of novel images without text and better quality in generation than the models based on mixture decoders.

1 INTRODUCTION

Unsupervised learning of compositional representation is a core ability of human intelligence (Yuille & Kersten, 2006; Frankland & Greene, 2020). Observing a visual scene, we perceive it not simply as a monolithic entity but as a geometric composition of key components such as objects, borders, and space (Kulkarni et al., 2015; Yuille & Kersten, 2006; Epstein et al., 2017; Behrens et al., 2018). Furthermore, this understanding of the structure of the scene composition enables the ability for *zero-shot imagination*, i.e., composing a novel, counterfactual, or systematically manipulated scenes that are significantly different from the training distribution. As such, realizing this ability has been considered a core challenge in building a human-like AI system (Lake et al., 2017).

DALL·E (Ramesh et al., 2021) has recently shown an impressive ability to systematically generalize for zero-shot image generation. Trained with a dataset of text-image pairs, it can generate plausible images even from an unfamiliar text prompt such as "avocado chair" or "lettuce hedgehog", a form of systematic generalization (Lake & Baroni, 2018; Bahdanau et al., 2018) in the text-to-image domain. However, from the perspective of compositionality, this success is somewhat expected because the text prompt already brings the composable structure. That is, the text is already discretized into a sequence of concept modules, i.e., words, which are composable, reusable, and encapsulated. DALL·E then learns to produce an image with global consistency by smoothly stitching over the discrete concepts via an Image GPT (Chen et al., 2020) decoder.

Building from the success of DALL·E, an important question is if we can achieve such systematic generalization for zero-shot image generation only from images without text. This would require realizing an ability lacking in DALL·E: extracting a set of composable representations from an image to play a similar role as that of word tokens. The most relevant direction towards this is object-centric representation learning (Greff et al., 2019; Locatello et al., 2020; Lin et al., 2020b; Greff et al., 2020b). While these can obtain a set of slots from an input image and reconstruct the same image from the slots, we argue that its systematic generalization ability to handle arbitrary *reconfiguration* of slots is significantly limited due to the way it decodes the slots.

In this paper, we propose a model that can achieve composition-based systematic generalization for image generation like DALL·E but by learning compositional representations from images instead of providing a text prompt. We call this model, Illiterate-DALL·E. To do this, we first introduce the slot-decoding dilemma and the pixel independence problem observed in the pixel-mixture decoder

Figure 1: Overview of our proposed model with respect to prior works. Left: In DALL·E, words in the input text act as the composable units for generating the desired novel image. The generated images have global consistency because each pixel depends non-linearly on all previous pixels and the input word embeddings. **Middle:** Unlike DALL·E that requires text supervision, Slot Attention provides an auto-encoding framework in which object slots act as the composable units inferred purely from raw images. However, during rendering, object slots are composed via a simple weighted sum of pixels obtained without any dependency on other pixels and slots which harms image consistency and quality. **Right:** Our model combines the best of both models. Like Slot Attention our model is free of text-based supervision and like DALL·E, produces novel image compositions with global consistency using the proposed decoder *Slot2Seq*.

of traditional object-centric representation models. Then, we hypothesize that achieving compositional systematic generalization in image generation requires not only compositional slots but also a powerful expressive decoder that can model complex interactions among the slots and other pixels. To this end, we propose the *slot-to-sequence* (Slot2Seq) decoder, which is an Image GPT decoder that takes the extracted slots as input instead of text. In experiments, we show that this simple architecture achieves the desired properties.

The main contribution of the paper is to show for the first time that the compositional systematic generalization, shown in DALL·E, can be achieved without text. We also show that making a powerful and expressive decoder work with slot representations is crucial in achieving this. In this regard, we introduce a new architecture, Illiterate-DALL·E, and a new slot decoding framework, Slot2Seq. The paper also introduces a new dataset, CLEVR-Mirror, and other tasks useful to evaluate the systematic generalization ability in image generation. Lastly, the experiment results strongly support the benefits of our model, and suggest that future object-centric models may benefit from building on the advantages of the proposed framework alongside the pixel-mixture decoder.

2 PRELIMINARIES

2.1 OBJECT-CENTRIC REPRESENTATION LEARNING WITH PIXEL-MIXTURE DECODER

A common framework for learning object-centric representations is via a form of auto-encoders (Locatello et al., 2020; Burgess et al., 2019; Lin et al., 2020b). An encoder takes an input image to return a *set* of object representation vectors or slot vectors $\{\mathbf{s}_1, \ldots, \mathbf{s}_N\} = f_\phi(\mathbf{x})$. A decoder then reconstructs the image by composing the decoded result of each slot $\hat{\mathbf{x}} = g_\theta(\mathbf{s}_{1:N})$. To encourage the emergence of object concepts in the slots, the decoder usually uses an architecture implementing an inductive bias about the scene composition such as the pixel-mixture decoders.

Pixel-mixture decoders are the most common approach to construct an image from slots. This method assumes that the final image is constructed by the pixel-wise weighted mean of the slot images. Specifically, each slot n generates its own slot image $\boldsymbol{\mu}_n$ and its corresponding alpha-mask $\boldsymbol{\pi}_n$. Then, the slot images are weighted-summed with the alpha-mask weights as follows:

$$\hat{\mathbf{x}}_i = \sum_{n=1}^{N} \pi_{n,i} \cdot \boldsymbol{\mu}_{n,i} \quad \text{where} \quad \boldsymbol{\mu}_n = g_\theta^{\text{RGB}}(\mathbf{s}_n) \quad \text{and} \quad \boldsymbol{\pi}_n = \frac{\exp g_\theta^{\text{mask}}(\mathbf{s}_n)}{\sum_{m=1}^{N} \exp g_\theta^{\text{mask}}(\mathbf{s}_m)},$$

where $i \in [1, HW]$ is the pixel index with H and W the image height and width, respectively.

2.2 Limitations of Pixel-Mixture Decoders

The pixel-mixture decoder has two main limitations. The first is what we term as the **slot-decoding dilemma**. As there is no explicit incentive for the encoder to make a slot focus on the pixel area corresponding to an object, it is usually required to employ a weak decoder for g_θ^{RGB} such as the Spatial Broadcast Network (Watters et al., 2019) to make object concepts emerge in the slots. By limiting the capacity of the slot-decoder, it prevents a slot from modeling multiple objects or the entire image and instead incentivizes the slot to focus on a local area that shows a statistical regularity such as an object of a simple color. However, this comes with a side effect: the weak decoder can make the generated image blur the details. When we use a more expressive decoder such as a CNN to capture such details, the object disentanglement tends to fail with encoder producing slots that capture the whole image, hence a dilemma (See Appendix D.1).

The second problem is the **pixel independence**. In pixel-mixture decoders, each slot's contribution to a generated pixel, i.e., $\pi_{n,i}$ and $\boldsymbol{\mu}_{n,i}$, is independent of the other slots and pixels. This may not be an issue if the aim of the slots is only to reconstruct the input image. However, it becomes an issue when we consider that an important desired property for object representations is to use them as *concept modules* i.e., to be able to *reuse* them in an arbitrary configuration in the same way as word embeddings can be reused to compose an arbitrary sentence. The lack of flexibility of the decoder due to the pixel independence, however, prevents the slots from having such reconfigurability. For example, when decoding an arbitrary set of slots, the rendered image would look like a mere superposition of individual object patches without *global semantic consistency*, producing a Frankenstein-like image as the examples in Section 5 shall show. In contrast, this zero-shot global semantic consistency for concept reconfiguration is achieved in DALL·E by using the Image GPT decoder.

2.3 Image GPT and DALL·E

Image GPT (Chen et al., 2020a) is an autoregressive generative model for images implemented using Transformer (Vaswani et al., 2017; Brown et al., 2020). For computational efficiency, Image GPT first down-scales the image of size $H \times W$ by a factor of K using a VQ-VAE encoder (van den Oord et al., 2017). This turns an image $\mathbf{x}$ into a sequence of discrete image tokens $\{\mathbf{z}_i\}$ where i indexes the tokens in a raster-scan order from 1 to HW/K^2. The transformer is then trained to model an auto-regressive distribution over this token sequence by maximizing the log-likelihood $\sum_i \log p_\theta(\mathbf{z}_i|\mathbf{z}_{<i})$. During generation, the transformer samples the image tokens sequentially conditioning on the previously generated tokens, i.e., $\hat{\mathbf{z}}_i \sim p_\theta(\hat{\mathbf{z}}_i|\hat{\mathbf{z}}_{<i})$ where $\hat{\mathbf{z}}_i$ is the image token generated for the position i in the sequence. Lastly, a VQ-VAE decoder takes all the generated tokens and produces the final image $\hat{\mathbf{x}}$. Crucially, due to the autoregressive generation of $\mathbf{z}_i$, unlike the pixel-mixture decoder, the generated pixels are not independent. The autoregressive generation powered by the direct memory access of the transformer makes Image GPT one of the most powerful decoder models in image generation and completion tasks. However, Image GPT does not provide a way to learn high-level semantic representations such as object-centric representations that can provide a way to semantically control image generation.

DALL·E (Ramesh et al., 2021) shows that the image generation of Image GPT can be controlled by conditioning on a text prompt. In particular, it shows the impressive ability of zero-shot generation *with global semantic consistency* for rather an arbitrary reconfiguration of the words in the text prompt. DALL·E can be seen as a conditional Image GPT model, $\hat{\mathbf{z}}_i \sim p_\theta(\hat{\mathbf{z}}_i|\hat{\mathbf{z}}_{<i}, \mathbf{c}_{1:N})$, where $\mathbf{c}_{1:N}$ are the text prompt tokens. The key limitation from the perspective of this work is that it requires supervision in terms of text-image pairs. This means that it does not need to learn the compositional structure by itself since the discrete concepts are inherently provided by the prompt text even though it learns the word embeddings provided the structure. Therefore, it is important to investigate if we can make a text-free DALL·E by learning to infer such compositional structure and representation only from images.

3 Illiterate DALL·E with Slot-To-Sequence Decoder

In this section, we propose a method that can provide global semantic consistency in the zero-shot image generation setting without text by learning object slots from images. To do this, we

shall lift the use of inductive biases in the slot decoder about object composition by making use of a transformer (Vaswani et al., 2017) as our image decoder while replacing the text prompt with a concept library constructed from image slots. Our central hypothesis is that a powerful auto-regressive decoder such as Transformer after training with a sufficiently diverse set of raw images should learn the rules of composition without domain specifications.

Obtaining Image Tokens using DVAE. To make the training of transformer computationally feasible for high-resolution images, we first downscale the input image $\mathbf{x}$ of size $H \times W$ by a factor of K using Discrete VAE (Im et al., 2017). To do this, we split the image into $K \times K$-sized patches resulting in T patches where $T = HW/K^2$. We provide each patch $\mathbf{x}_i$ as input to an encoder network f_ϕ to return log probabilities (denoted as $\mathbf{o}_i$) for a categorical distribution with V classes. With these log probabilities, we use a relaxed categorical distribution (Jang et al., 2016) with a temperature τ to sample a relaxed one-hot vector $\mathbf{z}_i^{\text{soft}}$. We then decode these soft vectors to obtain patch reconstructions. This process is summarized as follows:

$$\mathbf{o}_i = f_\phi(\mathbf{x}_i) \quad \Longrightarrow \quad \mathbf{z}_i^{\text{soft}} \sim \text{RelaxedCategorical}(\mathbf{o}_i; \tau) \quad \Longrightarrow \quad \tilde{\mathbf{x}}_i = g_\theta(\mathbf{z}_i^{\text{soft}}) \,.$$

By minimizing an MSE reconstruction objective for the image patches i.e. $\mathcal{L}_{\text{DVAE}} = \sum_{i=1}^{T}(\tilde{\mathbf{x}}_i - \mathbf{x}_i)^2$, we train the DVAE encoder $f_\phi(\cdot)$ and the decoder $g_\theta(\cdot)$ networks.

Inferring Object Slots. To infer the object slots from a given image $\mathbf{x}$, we first use the DVAE encoder as described above to obtain a discrete token $\mathbf{z}_i$ for each patch i. Next, we map each token $\mathbf{z}_i$ to an embedding by using a learned dictionary. To incorporate the position information into these patch embeddings, we sum them with learned positional embeddings. This results in an embedding $\mathbf{u}_i$ which now has both the content and the position information for the patch. These embeddings $\mathbf{u}_{1:T}$ are then given as input to a Slot-Attention encoder (Locatello et al., 2020) with N slots.

$$\mathbf{o}_i = f_\phi(\mathbf{x}_i) \quad \Longrightarrow \quad \mathbf{z}_i \sim \text{Categorical}(\mathbf{o}_i) \quad \Longrightarrow$$
$$\mathbf{u}_i = \text{Dictionary}_\phi(\mathbf{z}_i) + \mathbf{p}_{\phi,i} \quad \Longrightarrow \quad \mathbf{s}_{1:N}, A_{1:N} = \text{SlotAttention}_\phi(\mathbf{u}_{1:T}) \,.$$

This results in N object slots $\mathbf{s}_{1:N}$ and N attention maps $A_{1:N}$ from the last refinement iteration of the Slot-Attention encoder.

Reconstruction using Transformer. To reconstruct the input image, we decode the slots $\mathbf{s}_{1:N}$ and first reconstruct the DVAE tokens $\hat{\mathbf{z}}_{1:T}$ using a Transformer. We then use the DVAE decoder g_θ to decode the DVAE tokens and reconstruct the image patches $\hat{\mathbf{x}}_i$ and therefore the image $\hat{\mathbf{x}}$.

$$\hat{\mathbf{o}}_i = \text{Transformer}_\theta(\hat{\mathbf{u}}_{<i}; \mathbf{s}_{1:N}) \quad \Longrightarrow \quad \hat{\mathbf{z}}_i = \arg\max_{v \in [1,V]} \hat{o}_{i,v} \quad \Longrightarrow \quad \hat{\mathbf{x}}_i = g_\theta(\hat{\mathbf{z}}_i) \,.$$

where $\hat{\mathbf{u}}_i = \text{Dictionary}_\phi(\hat{\mathbf{z}}_i) + \mathbf{p}_{\phi,i}$ and $\hat{o}_{i,v}$ is the log probability of token v among the V classes of the categorical distribution represented by $\hat{\mathbf{o}}_i$. To train the transformer, the slot attention encoder and the embeddings, we minimize the cross-entropy of predicting each token $\mathbf{z}_i$ conditioned on the preceding tokens $\mathbf{z}_{<i}$ and the slots $\mathbf{s}_{1:N}$. Let the predicted log-probabilities for the token at position i be $\bar{\mathbf{o}}_i = \text{Transformer}_\theta(\mathbf{u}_{<i}; \mathbf{s}_{1:N})$. Then the cross-entropy training objective can be written as $\mathcal{L}_{\text{ST}} = \sum_{i=1}^{T} \text{CrossEntropy}(\mathbf{z}_i, \bar{\mathbf{o}}_i)$.

Learning Objective and Training. The complete training objective is given by $\mathcal{L} = \mathcal{L}_{\text{ST}} + \mathcal{L}_{\text{DVAE}}$ and all modules of our model are trained jointly. We apply a decay on the DVAE temperature τ from 1.0 to 0.1 at the start of the training. We also apply a learning rate warm-up for the parameters of Slot-Attention and Transformer at the start of the training as we found that this led to stable training.

Multi-headed Slot Attention. For representing images, we found that slots of standard Slot Attention encoder (Locatello et al., 2020) can suffer in expressiveness when representing objects with complex shapes and textures. This is because the slots collect information from the input cells via dot-product attention in which the attended input values are pooled using a simple weighted sum. As such, this pooling method can be too weak for representing complex objects. To address this, we propose an extension of Slot Attention called *Multi-headed Slot Attention* in which each slot attends to the input cells via multiple heads. Thus each slot can attend to different parts of the same object. When the slot state is computed, the attended values of different heads are concatenated which allows these partial object features to interact more flexibly and produce a significantly better object representation. Full details of the implementation and an ablation experiment to show the benefits of multiple heads are provided in Appendix A.3.

3.1 VISUAL CONCEPT LIBRARY

The above model extracts a set of concepts or slots belonging to a particular image whereas an intelligent agent would build a *library of reusable concepts* from diverse experience. In DALL·E, a vocabulary of word embeddings plays the role of this library and provides reusable concepts. Similarly, to build a library of visual concepts from the dataset, we use the following simple approach based on K-means clustering to construct a library of reusable visual concepts. To do this, (i) collect N slots $\mathcal{S}_i = \{\mathbf{s}_1^i, \ldots, \mathbf{s}_N^i\}$ and their attention maps $\mathcal{A}_i = \{A_1^i, \ldots, A_N^i\}$ from each image i in the training dataset. (ii) Run K-means clustering on $\mathcal{S} = \bigcup_i \mathcal{S}_i$ with cosine similarity between slots as a distance metric where K is the number of total concepts in the library. If the object position is more important for building the concept library, cluster the slots using IOU between the attention maps as a similarity metric. (iii) Use each cluster as a concept and the slots assigned to the cluster as the instantiations of the concept. (iv) To compose an arbitrary image, choose the concepts from the library and randomly choose a slot for each concept and build a *slot prompt* similar to a text prompt in DALL·E. (v) Provide this prompt to the decoder to compose and generate the image.

4 RELATED WORK

Compositional Generation via Object-Centric Learning. Self-supervised object-centric approaches (Burgess et al., 2019; Greff et al., 2019; Locatello et al., 2020; Kabra et al., 2021; Greff et al., 2017; Engelcke et al., 2020; 2021; Eslami et al., 2016; Crawford & Pineau, 2019b; Lin et al., 2020b; Jiang & Ahn, 2020; Kosiorek et al., 2018; Jiang et al., 2019; Crawford & Pineau, 2019a; Lin et al., 2020a; Deng et al., 2021; Anciukevicius et al., 2020; von Kügelgen et al., 2020; Wu et al., 2021) typically perform mixture-based alpha compositing for rendering with contents of each slot decoded independently. Savarese et al. (2021) and Yang et al. (2020) rely on minimizing mutual information between predicted object segments as a learning signal while Yang et al. (2021) leverage optical flow. However, these approaches either cannot compose novel scenes or require specialized losses for object discovery unlike ours which uses a simple reconstruction loss. DINO (Caron et al., 2021) combining Vision Transformer (Dosovitskiy et al., 2021) and a self-supervised representation learning objective (Chen et al., 2020b; He et al., 2020; Grill et al., 2020; Touvron et al., 2021; Hinton, 2021; van den Oord et al., 2018) discovers object-centric attention maps but, unlike ours, cannot compose novel scenes. TIMs (Lamb et al., 2021; Goyal et al., 2021) with an Image GPT decoder show object-centric attention maps but, unlike ours, do not investigate compositional generation.

Compositional Generation using GANs. Chai et al. (2021) show compositional generation using a collage of patches encoded and decoded using a pretrained GAN. However, the collage needs to be provided manually and object discovery requires a specialized process unlike our model. Bielski & Favaro (2019) and Chen et al. (2019) show object discovery from given images by randomly re-drawing or adding a random jitter (Voynov et al., 2021) to the foreground followed by an adversarial loss. As these models use alpha compositing, their compositional ability is limited. Some works (Donahue et al., 2016; Donahue & Simonyan, 2019) infer abstract representations for images that emphasize the high-level semantics, but these, unlike ours, cannot be used for compositional image generation. Niemeyer & Geiger (2021), Nguyen-Phuoc et al. (2020); Chen et al. (2016), van Steenkiste et al. (2020), Liao et al. (2020) and Ehrhardt et al. (2020) introduce GANs which generate images conditioned on object-wise or factor-wise noise and optionally on camera pose. Lacking an inference module, these cannot perform compositional editing of a given image unlike ours. While Kwak & Zhang (2016) provide an encoder to discover objects, the decoding relies on alpha compositing. Reed et al. (2016a) show compositional generation in GANs and improved generation quality (Johnson et al., 2018; Hinz et al., 2019) via an object-centric or a key-point based pathway for scene rendering. However, these require supervision for the bounding boxes and the keypoints.

Compositional Generation with Latent Variable Models and Text. Early approaches focused on disentangling the independent factors of the observation generating process using β-VAE (Higgins et al., 2017) or ensuring that independently sampling each latent factor should produce images indistinguishable from the training distribution (Kim & Mnih, 2018; Kumar et al., 2017; Chen et al., 2018). However unlike ours, these approaches providing a monolithic single vector representation can suffer in multi-object scenes due to *superposition catastrophe* (Greff et al., 2020a; Jiang & Ahn, 2020). Another line of approaches learn to map text to images to compose novel scenes (Ramesh et al., 2021; Reed et al., 2016b; Li et al., 2019; Higgins et al., 2018) or conditional image generation

	FID ($\downarrow$)		Human ($\uparrow$)
Dataset	SA	Ours	Favor Ours
3D Shapes	44.14	**36.75**	50.36%
CLEVR	63.76	**41.62**	84.66%
Shapestacks	155.74	**51.27**	78.00%
Bitmoji	71.43	**15.83**	95.06%
TexMNIST	245.09	**64.15**	-

(a) Compositional Generation

	MSE ($\downarrow$)		FID ($\downarrow$)	
Dataset	SA	Ours	SA	Ours
3D Shapes	**47.94**	71.79	58.84	**58.59**
CLEVR	**29.59**	49.95	55.95	**37.42**
Shapestacks	233.72	**111.86**	139.72	**30.22**
Bitmoji	388.72	**261.10**	67.66	**11.89**
TexMNIST	822.73	**149.02**	179.95	**55.00**

(b) Image Reconstruction

Table 1: Comparison of Compositional Generation (left) and Image Reconstruction (right) between Slot-Attention (SA) and our model. For comparison of compositional generation, we report the FID score and average vote percentage received in favor of the generated images from our model. Vote percentage higher than 50% implies that our model was preferred over the Slot Attention baseline. For image reconstruction quality, we report the MSE and the FID score.

Figure 2: Comparison of training curves of a discriminator to compare the quality of compositional generation between Slot-Attention and our model. A CNN discriminator tries to discriminate between real images and model-generated images. We note that the curves converge more slowly for our model than for Slot Attention and show that our generations are more realistic.

(Sohn et al., 2015; Yan et al., 2016; Johnson et al., 2018; Ashual & Wolf, 2019; Bar et al., 2021; Herzig et al., 2020; 2019; Du et al., 2020). However such approaches rely on supervision.

5 EXPERIMENTS

In experiments, we evaluate the benefits of Slot2Seq over pixel-mixture decoder in: 1) generating novel images from an arbitrary configuration of slots, 2) image reconstruction, and 3) generating novel images not belonging to the training image distribution. As the baseline, we compare with an unsupervised object-centric framework having a slot attention encoder like ours but using a mixture decoder for decoding instead of Slot2Seq. Hereafter, we refer to this model as simply Slot Attention (Locatello et al., 2020). We evaluate the models on four datasets: 3D Shapes (Burgess & Kim, 2018), CLEVR-Mirror which we develop from the CLEVR (Johnson et al., 2017) dataset by adding a mirror in the scene (see Appendix E.1), Shapestacks (Groth et al., 2018), Bitmoji (Graux, 2021) and Textured-MNIST. For brevity, we shall refer to CLEVR-Mirror as simply CLEVR. In each dataset, a scene can be described in terms of composable entities such as blocks, walls, floors, hair, or face. Our models take only raw images without any other supervision or annotations.

5.1 COMPOSITIONAL IMAGE GENERATION

We evaluate how effectively the known slots can be reused to generate novel scenes. For this, we evaluate the quality of image generations produced by our model from arbitrarily composed slot prompts. To build these prompts, we first build a concept library using K-means as described in Section 3.1. In 3D Shapes and Bitmoji, we apply K-means clustering on the slots. In 3D Shapes, this results in clusters for *wall*, *object* and *floor* and in Bitmoji for *dress*, *hair*, *neck*, *eyes*, *face* and *collar*. These clusters make up our concept library and are visualized in Appendix C. To build novel prompts from this library, we simply pick one slot from each cluster. In CLEVR and Shapestacks datasets, to build a prompt, it is more natural to pick the object positions first and then sample a slot from the library for that position on the canvas. Hence, for CLEVR, we pick a set of random

Figure 3: Comparison of compositional generation between Slot Attention and our model in 3D Shapes and Bitmoji datasets. We visualize the slot prompts provided to Slot2Seq and the resulting compositions. To visualize the prompt slots, we show the image from which the slot was taken masked using its input attention map. Note that these attention maps had emerged in the source images implicitly without any supervision. We note that our decoder performs zero-shot generalization to novel slot inputs while the mixture decoder fails to compose arbitrary slots well.

Figure 4: Object Replacement and Out-of-Distribution Compositions in Bitmoji. We show that in our model, it is possible to edit the image by taking a specific slot and replacing it with an arbitrary slot drawn from the concept library for the same concept. We also show OOD compositions by replacing the slot with those from the opposite gender.

positions keeping a certain distance between the picked positions. For Shapestacks, we pick a set of random positions in a vertical tower-like configuration. In this way, we generate 40000 prompts for each dataset and render the corresponding images. We then evaluate the quality of the images by computing the FID score with respect to the true images. To support this metric, we also report the training curves of a CNN discriminator that tries to classify between real and model-generated images. If generated images are close to the true data distribution, then it should be harder for the discriminator to discriminate and the resulting training curve should converge more slowly.

From Table 1a and Figure 2, we note that our compositional generations are significantly more realistic than the generations from the mixture decoder. The qualitative samples shown in Figures 3, 4, 5 and 6 show that our decoder can compose the desired image accurately and make an effective reuse of the known slots. Additional qualitative results are provided in Appendix C. We also note that for visually complex Shapestacks and Bitmoji datasets, the improvement in the FID score provided by our model is much larger than that for the visually simpler CLEVR and 3D Shapes datasets.

These results provide evidence that *i)* our model resolves the *slot-decoding dilemma* and consequently, it benefits from the flexibility of the Image GPT decoder that can render the fine details such as floor texture in Shapestacks and complex facial features in Bitmoji while the mixture decoder suffers. Notice that the attention segments of the visualized slots effectively focus on the specific object regions of the respective images that were provided during concept library creation.

Slots Added Cumulatively

Figure 5: Compositional Generation in CLEVR. We show compositional generation in the CLEVR by adding object slots one at a time. In training, only 3-6 objects were shown. However, we note that our model can generalize in generating 1-2 and 7-8 objects including the empty scene. We also note that our mirror reflections are significantly more clear than those of Slot Attention.

Figure 6: Compositional generation in Shapestacks Dataset. We show compositional generation in Shapestacks by composing arbitrary blocks drawn from the concept library in a tower configuration. We note that Slot2Seq can render the details such as the texture of the floor and the wall significantly better than the mixture decoder.

This emergent object localization occurs despite the powerful decoder, thus resolving the dilemma. Because our slots attend on the DVAE tokens, hence our attention is patch-level and our attention segments may appear coarser than those of Slot Attention in which slots attend on the CNN feature cells having the same resolution as the input image. *ii)* Because the mixture decoder has the *pixel-independence assumption*, we see in Figure 3 that it suffers when slots are combined in arbitrary configurations. In 3D Shapes, the object shadows are controlled by the floor component of the mixture and are either too large or too small for the 3D object. This is because after arbitrarily choosing a different 3D object, the floor slot has no knowledge that the object which casts the shadow has changed and it continues to draw the shadow mask of the source image which has now become obsolete in the new slot configuration. Slot Attention suffers even more severely in Bitmoji as the composed mixture components and masks are mutually incompatible in the new slot configuration and produce an inaccurate alpha composition. In contrast, Slot2Seq is robust to this problem because the slots and pixels can interact. For instance, in 3D Shapes, as the pixels of the floor are being rendered, the predictor is aware of the object that will cast the shadow via the previous pixels and the input slots and can thus predict a globally consistent pixel value.

5.2 RECONSTRUCTION QUALITY

A natural test about whether an auto-encoder learns accurate representations of the given input is through an evaluation of the reconstruction error. For this, we report two metrics: 1) MSE to evaluate how well the reconstructed image preserves the contents of the original image and 2) FID score to show how realistic is the reconstructed image with respect to the true image distribution. We compute these metrics on a held-out set and report in Table 1b. We find that our model outperforms Slot Attention in all datasets in terms of FID which shows that the image quality of our model is better

Figure 7: Out-of-Distribution Generalization in Shapestacks Dataset. We provide slot prompts to render two towers instead of one. The models were trained only on images with one tower.

	FID (↓)	
Dataset	SA	Ours
Shapestacks	172.82	**82.38**
CLEVR	62.44	**43.77**
Bitmoji	81.66	**22.75**

Table 2: FID Comparison for OOD Compositions.

due to its powerful decoder. In MSE, our model performance is comparable for synthetic datasets such as 3D Shapes and CLEVR while we outperform on the visually more complex Shapestacks, Bitmoji and Textured-MNIST. The performance gain from our model, in both MSE and FID, increases as the visual complexity of the dataset increases. Despite the better MSE of the mixture decoder in 3D Shapes and CLEVR, the gap is not severe given the broader limitations of the mixture decoder in handling novel slot configurations.

5.3 GENERALIZATION TO OUT-OF-DISTRIBUTION (OOD) SLOT RECONFIGURATIONS

Because the Slot2Seq decoder is based on Transformer and does not have an explicit inductive bias about scene composition, we test whether it can generalize in composing slots when their configurations are different from the training distribution. For this, *i)* in Shapestacks, we compose slot prompts to render two towers while only single-tower images were shown during training. *ii)* In CLEVR, we compose prompts to render fewer or more objects than were shown during training. *iii)* Lastly, in Bitmoji, we annotated the gender of 500 images and used it to construct 1600 OOD slot prompts by composing hair and face only from opposite genders. By doing this, we change the distribution of the slot configurations with respect to the training distribution. Note that such slot prompts were already a part of the Bitmoji compositions in Section 5.1. However, with this experiment, we evaluate the specific OOD subset of those prompts. We show the results in Figures 4, 5 and 7 and a comparison of FID score with respect to the mixture decoder in Table 2. From these, we note that our decoder is able to generalize to the OOD slot configurations and it also outperforms the mixture decoder in image quality.

6 DISCUSSION

We presented Illiterate DALL·E, a model for text-free zero-shot imagination by learning slot representations only from images. Our model combines the best of DALL·E and object-centric representation learning via the proposed decoder *Slot2Seq*. It provides a significant improvement over pixel-mixture decoders in reconfigurability of slots for zero-shot imagination. These results suggest that future object-centric models may benefit from building on the advantages of the proposed framework alongside the pixel-mixture decoder.

The proposed Slot2Seq, with its Transformer-based implementation, can also be seen as a graphics engine that learns to mimic the physical laws governing the rendering of the image through its exposure to a large dataset. Thus to render a scene, the only information that the Transformer requires and requests from the encoder is the abstract object-level *what* and *where* in the form of slots. Knowing these objects, the Transformer then fills in the rest and implicitly handles the mechanisms that give rise to the observed object appearance, occlusions, shadows, reflections, and transparency.

An interesting future direction is to consider that an intelligent agent may collect new experience indefinitely, and thus our approach of building the library of reusable concepts can be made more formal by learning discrete concepts and growing this library using online clustering (Liberty et al., 2016) or Bayesian non-parametric clustering (Neal, 2000). Another direction is to learn a slot-level prior for fast density modeling and sampling scenes at the representation level.

7 ETHICS STATEMENT

For future applications, negative societal consequences should also be considered. The current model does not generate images realistic enough to deceive humans if used with malicious intent. However future versions of the model after scaling up its size and the training dataset can have such potential. Despite these considerations, these consequences are not imminent.

REFERENCES

Titas Anciukevicius, Christoph H. Lampert, and Paul Henderson. Object-centric image generation with factored depths, locations, and appearances. *arXiv preprint arXiv:2004.00642*, 2020.

Oron Ashual and Lior Wolf. Specifying object attributes and relations in interactive scene generation. In *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 4561–4569, 2019.

Dzmitry Bahdanau, Shikhar Murty, Michael Noukhovitch, Thien Huu Nguyen, Harm de Vries, and Aaron Courville. Systematic generalization: what is required and can it be learned? *arXiv preprint arXiv:1811.12889*, 2018.

Amir Bar, Roi Herzig, Xiaolong Wang, Anna Rohrbach, Gal Chechik, Trevor Darrell, and Amir Globerson. Compositional video synthesis with action graphs. In *ICML 2021: 38th International Conference on Machine Learning*, pp. 662–673, 2021.

Timothy EJ Behrens, Timothy H Muller, James CR Whittington, Shirley Mark, Alon B Baram, Kimberly L Stachenfeld, and Zeb Kurth-Nelson. What is a cognitive map? organizing knowledge for flexible behavior. *Neuron*, 100(2):490–509, 2018.

Adam Bielski and Paolo Favaro. Emergence of object segmentation in perturbed generative models. In *Advances in Neural Information Processing Systems*, volume 32, pp. 7254–7264, 2019.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Chris Burgess and Hyunjik Kim. 3d shapes dataset. https://github.com/deepmind/3dshapes-dataset/, 2018.

Christopher P Burgess, Loic Matthey, Nicholas Watters, Rishabh Kabra, Irina Higgins, Matt Botvinick, and Alexander Lerchner. Monet: Unsupervised scene decomposition and representation. *arXiv preprint arXiv:1901.11390*, 2019.

Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *ICCV 2021 - International Conference on Computer Vision*, 2021.

Lucy Chai, Jonas Wulff, and Phillip Isola. Using latent space regression to analyze and leverage compositionality in gans. In *ICLR 2021: The Ninth International Conference on Learning Representations*, 2021.

Mark Chen, Alec Radford, Rewon Child, Jeffrey Wu, Heewoo Jun, David Luan, and Ilya Sutskever. Generative pretraining from pixels. In *International Conference on Machine Learning*, pp. 1691–1703. PMLR, 2020.

Mark Chen, Alec Radford, Rewon Child, Jeffrey K Wu, Heewoo Jun, David Luan, and Ilya Sutskever. Generative pretraining from pixels. In *ICML 2020: 37th International Conference on Machine Learning*, volume 1, pp. 1691–1703, 2020a.

Mickaël Chen, Thierry Artières, and Ludovic Denoyer. Unsupervised object segmentation by redrawing. In *Advances in Neural Information Processing Systems 32 (NIPS 2019)*, volume 32, pp. 12705–12716, 2019.

Tian Qi Chen, Xuechen Li, Roger B Grosse, and David K Duvenaud. Isolating sources of disentanglement in variational autoencoders. In *Advances in Neural Information Processing Systems*, pp. 2610–2620, 2018.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *ICML 2020: 37th International Conference on Machine Learning*, volume 1, pp. 1597–1607, 2020b.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: interpretable representation learning by information maximizing generative adversarial nets. In *NIPS'16 Proceedings of the 30th International Conference on Neural Information Processing Systems*, volume 29, pp. 2180–2188, 2016.

Eric Crawford and Joelle Pineau. Exploiting spatial invariance for scalable unsupervised object tracking. *arXiv preprint arXiv:1911.09033*, 2019a.

Eric Crawford and Joelle Pineau. Spatially invariant unsupervised object detection with convolutional neural networks. In *Proceedings of AAAI*, 2019b.

Fei Deng, Zhuo Zhi, Donghun Lee, and Sungjin Ahn. Generative scene graph networks. In *ICLR 2021: The Ninth International Conference on Learning Representations*, 2021.

Jeff Donahue and Karen Simonyan. Large scale adversarial representation learning. In *Advances in Neural Information Processing Systems*, volume 32, pp. 10541–10551, 2019.

Jeff Donahue, Philipp Krähenbühl, and Trevor Darrell. Adversarial feature learning. In *ICLR (Poster)*, 2016.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *ICLR 2021: The Ninth International Conference on Learning Representations*, 2021.

Yilun Du, Shuang Li, and Igor Mordatch. Compositional visual generation with energy based models. In *Advances in Neural Information Processing Systems*, volume 33, pp. 6637–6647, 2020.

Sebastien Ehrhardt, Oliver Groth, Aron Monszpart, Martin Engelcke, Ingmar Posner, Niloy Mitra, and Andrea Vedaldi. Relate: Physically plausible multi-object scene synthesis using structured latent spaces, 2020.

Martin Engelcke, Adam R. Kosiorek, Oiwi Parker Jones, and Ingmar Posner. Genesis: Generative scene inference and sampling with object-centric latent representations. In *ICLR 2020 : Eighth International Conference on Learning Representations*, 2020.

Martin Engelcke, Oiwi Parker Jones, and Ingmar Posner. Genesis-v2: Inferring unordered object representations without iterative refinement. *arXiv preprint arXiv:2104.09958*, 2021.

Russell A Epstein, Eva Zita Patai, Joshua B Julian, and Hugo J Spiers. The cognitive map in humans: spatial navigation and beyond. *Nature neuroscience*, 20(11):1504–1513, 2017.

SM Ali Eslami, Nicolas Heess, Theophane Weber, Yuval Tassa, David Szepesvari, and Geoffrey E Hinton. Attend, infer, repeat: Fast scene understanding with generative models. In *Advances in Neural Information Processing Systems*, pp. 3225–3233, 2016.

Steven M Frankland and Joshua D Greene. Concepts and compositionality: in search of the brain's language of thought. *Annual review of psychology*, 71:273–303, 2020.

Anirudh Goyal, Alex Lamb, Jordan Hoffmann, Shagun Sodhani, Sergey Levine, Yoshua Bengio, and Bernhard Schölkopf. Recurrent independent mechanisms. In *ICLR 2021: The Ninth International Conference on Learning Representations*, 2021.

Romain Graux. Bitmoji dataset. https://www.kaggle.com/romaingraux/bitmojis/metadata/, 2021.

Klaus Greff, Sjoerd van Steenkiste, and Jürgen Schmidhuber. Neural expectation maximization. In *Advances in Neural Information Processing Systems*, pp. 6691–6701, 2017.

Klaus Greff, Raphaël Lopez Kaufmann, Rishab Kabra, Nick Watters, Chris Burgess, Daniel Zoran, Loic Matthey, Matthew Botvinick, and Alexander Lerchner. Multi-object representation learning with iterative variational inference. *arXiv preprint arXiv:1903.00450*, 2019.

Klaus Greff, Sjoerd van Steenkiste, and Jürgen Schmidhuber. On the binding problem in artificial neural networks. *arXiv preprint arXiv:2012.05208*, 2020a.

Klaus Greff, Sjoerd van Steenkiste, and Jürgen Schmidhuber. On the binding problem in artificial neural networks. *arXiv preprint arXiv:2012.05208*, 2020b.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H. Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, Bilal Piot, Koray Kavukcuoglu, Rémi Munos, and Michal Valko. Bootstrap your own latent: A new approach to self-supervised learning. In *Advances in Neural Information Processing Systems*, volume 33, pp. 21271–21284, 2020.

Oliver Groth, Fabian B. Fuchs, Ingmar Posner, and Andrea Vedaldi. Shapestacks: Learning vision-based physical intuition for generalised object stacking. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 724–739, 2018.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9729–9738, 2020.

Roei Herzig, Amir Bar, Huijuan Xu, Gal Chechik, Trevor Darrell, and Amir Globerson. Learning canonical representations for scene graph to image generation. *arXiv preprint arXiv:1912.07414*, 2019.

Roei Herzig, Amir Bar, Huijuan Xu, Gal Chechik, Trevor Darrell, and Amir Globerson. Learning canonical representations for scene graph to image generation. In *16th European Conference on Computer Vision, ECCV 2020*, pp. 210–227, 2020.

Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *ICLR 2017 : International Conference on Learning Representations 2017*, 2017.

Irina Higgins, Nicolas Sonnerat, Loic Matthey, Arka Pal, Christopher P Burgess, Matko Bosnjak, Murray Shanahan, Matthew Botvinick, Demis Hassabis, and Alexander Lerchner. Scan: Learning hierarchical compositional visual concepts. In *International Conference on Learning Representations*, 2018.

Geoffrey E. Hinton. How to represent part-whole hierarchies in a neural network. *arXiv preprint arXiv:2102.12627*, 2021.

Tobias Hinz, Stefan Heinrich, and Stefan Wermter. Generating multiple objects at spatially distinct locations. In *International Conference on Learning Representations*, 2019.

Daniel Im Jiwoong Im, Sungjin Ahn, Roland Memisevic, and Yoshua Bengio. Denoising criterion for variational auto-encoding framework. In *Thirty-First AAAI Conference on Artificial Intelligence*, 2017.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. In *ICLR (Poster)*, 2016.

Jindong Jiang and Sungjin Ahn. Generative neurosymbolic machines. In *Advances in Neural Information Processing Systems*, 2020.

Jindong Jiang, Sepehr Janghorbani, Gerard De Melo, and Sungjin Ahn. Scalor: Generative world models with scalable object representations. In *International Conference on Learning Representations*, 2019.

Justin Johnson, Bharath Hariharan, Laurens van der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2901–2910, 2017.

Justin Johnson, Agrim Gupta, and Li Fei-Fei. Image generation from scene graphs. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1219–1228, 2018.

Rishabh Kabra, Daniel Zoran, Goker Erdogan, Loic Matthey, Antonia Creswell, Matthew Botvinick, Alexander Lerchner, and Christopher P. Burgess. Simone: View-invariant, temporally-abstracted object representations via unsupervised video decomposition. *arXiv preprint arXiv:2106.03849*, 2021.

Hyunjik Kim and Andriy Mnih. Disentangling by factorising. *arXiv preprint arXiv:1802.05983*, 2018.

Adam Kosiorek, Hyunjik Kim, Yee Whye Teh, and Ingmar Posner. Sequential attend, infer, repeat: Generative modelling of moving objects. In *Advances in Neural Information Processing Systems*, pp. 8606–8616, 2018.

Tejas D Kulkarni, Will Whitney, Pushmeet Kohli, and Joshua B Tenenbaum. Deep convolutional inverse graphics network. *arXiv preprint arXiv:1503.03167*, 2015.

Abhishek Kumar, Prasanna Sattigeri, and Avinash Balakrishnan. Variational inference of disentangled latent concepts from unlabeled observations. In *International Conference on Learning Representations*, 2017.

Hanock Kwak and Byoung-Tak Zhang. Generating images part by part with composite generative adversarial networks. *arXiv preprint arXiv:1607.05387*, 2016.

Brenden Lake and Marco Baroni. Generalization without systematicity: On the compositional skills of sequence-to-sequence recurrent networks. In *International conference on machine learning*, pp. 2873–2882. PMLR, 2018.

Brenden M Lake, Tomer D Ullman, Joshua B Tenenbaum, and Samuel J Gershman. Building machines that learn and think like people. *Behavioral and brain sciences*, 40, 2017.

Alex Lamb, Di He, Anirudh Goyal, Guolin Ke, Chien-Feng Liao, Mirco Ravanelli, and Yoshua Bengio. Transformers with competitive ensembles of independent mechanisms. In *arXiv e-prints*, 2021.

Wenbo Li, Pengchuan Zhang, Lei Zhang, Qiuyuan Huang, Xiaodong He, Siwei Lyu, and Jianfeng Gao. Object-driven text-to-image synthesis via adversarial training. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 12174–12182, 2019.

Yiyi Liao, Katja Schwarz, Lars Mescheder, and Andreas Geiger. Towards unsupervised learning of generative models for 3d controllable image synthesis. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 5871–5880, 2020.

Edo Liberty, Ram Sriharsha, and Maxim Sviridenko. An algorithm for online k-means clustering. In *2016 Proceedings of the eighteenth workshop on algorithm engineering and experiments (ALENEX)*, pp. 81–89. SIAM, 2016.

Zhixuan Lin, Yi-Fu Wu, Skand Vishwanath Peri, Jindong Jiang, and Sungjin Ahn. Improving generative imagination in object-centric world models. In *International Conference on Machine Learning*, pp. 4114–4124, 2020a.

Zhixuan Lin, Yi-Fu Wu, Skand Vishwanath Peri, Weihao Sun, Gautam Singh, Fei Deng, Jindong Jiang, and Sungjin Ahn. Space: Unsupervised object-oriented scene representation via spatial attention and decomposition. In *International Conference on Learning Representations*, 2020b.

Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention, 2020.

Radford M Neal. Markov chain sampling methods for dirichlet process mixture models. *Journal of computational and graphical statistics*, 9(2):249–265, 2000.

Thu Nguyen-Phuoc, Christian Richardt, Long Mai, Yong-Liang Yang, and Niloy Mitra. Block-gan: Learning 3d object-aware scene representations from unlabelled images. *arXiv preprint arXiv:2002.08988*, 2020.

Michael Niemeyer and Andreas Geiger. Giraffe: Representing scenes as compositional generative neural feature fields. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11453–11464, 2021.

Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation, 2021.

Scott Reed, Zeynep Akata, Santosh Mohan, Samuel Tenka, Bernt Schiele, and Honglak Lee. Learning what and where to draw. In *NIPS'16 Proceedings of the 30th International Conference on Neural Information Processing Systems*, volume 29, pp. 217–225, 2016a.

Scott Reed, Zeynep Akata, Xinchen Yan, Lajanugen Logeswaran, Bernt Schiele, and Honglak Lee. Generative adversarial text to image synthesis. In *ICML'16 Proceedings of the 33rd International Conference on International Conference on Machine Learning - Volume 48*, pp. 1060–1069, 2016b.

Pedro Savarese, Sunnie S. Y. Kim, Michael Maire, Greg Shakhnarovich, and David McAllester. Information-theoretic segmentation by inpainting error maximization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4029–4039, 2021.

Kihyuk Sohn, Xinchen Yan, and Honglak Lee. Learning structured output representation using deep conditional generative models. In *NIPS'15 Proceedings of the 28th International Conference on Neural Information Processing Systems - Volume 2*, volume 28, pp. 3483–3491, 2015.

Hugo Touvron, Matthieu Cord, Douze Matthijs, Francisco Massa, Alexandre Sablayrolles, and Herve Jegou. Training data-efficient image transformers and distillation through attention. In *ICML 2021: 38th International Conference on Machine Learning*, pp. 10347–10357, 2021.

Aaron van den Oord, Oriol Vinyals, and koray kavukcuoglu. Neural discrete representation learning. In *Advances in Neural Information Processing Systems*, volume 30, pp. 6306–6315, 2017.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv: Learning*, 2018.

Sjoerd van Steenkiste, Karol Kurach, Jürgen Schmidhuber, and Sylvain Gelly. Investigating object compositionality in generative adversarial networks. *Neural Networks*, 130:309–325, 2020.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Julius von Kügelgen, Ivan Ustyuzhaninov, Peter V. Gehler, Matthias Bethge, and Bernhard Schölkopf. Towards causal generative scene models via competition of experts. *arXiv preprint arXiv:2004.12906*, 2020.

Andrey Voynov, Stanislav Morozov, and Artem Babenko. Big gans are watching you: Towards unsupervised object segmentation with off-the-shelf generative models. In *arxiv:cs.LG*, 2021.

Nicholas Watters, Loic Matthey, Christopher P. Burgess, and Alexander Lerchner. Spatial broadcast decoder: A simple architecture for learning disentangled representations in vaes. *arXiv preprint arXiv:1901.07017*, 2019.

Yi-Fu Wu, Jaesik Yoon, and Sungjin Ahn. Generative video transformer: Can objects be the words? In *International Conference on Machine Learning*, pp. 11307–11318. PMLR, 2021.

Xinchen Yan, Jimei Yang, Kihyuk Sohn, and Honglak Lee. Attribute2image: Conditional image generation from visual attributes. In *European Conference on Computer Vision*, pp. 776–791, 2016.

Charig Yang, Hala Lamdouar, Erika Lu, Andrew Zisserman, and Weidi Xie. Self-supervised video object segmentation by motion grouping. *arXiv: Computer Vision and Pattern Recognition*, 2021.

Yanchao Yang, Yutong Chen, and Stefano Soatto. Learning to manipulate individual objects in an image. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6558–6567, 2020.

Alan Yuille and Daniel Kersten. Vision as bayesian inference: analysis by synthesis? *Trends in cognitive sciences*, 10(7):301–308, 2006.

A ILLITERATE DALL·E USING SLOT2SEQ

A.1 ARCHITECTURE

Figure 8: Architecture of Slot2Seq. Our model receives an input image and we split it into patches. We encode each patch as a discrete token using a feedforward network (shown as the DVAE encoder). A DVAE decoder is trained to reconstruct each patch from its respective token using a simple MSE loss. We shall call this the DVAE reconstruction and this provides one of the two reconstruction pathways that we have in our architecture. For the second reconstruction pathway, the tokens obtained from the DVAE encoder are mapped to embeddings. To these embeddings, we add learned positional embedding to add the position information to the embedding of each token or the respective image patch. These resulting set of embeddings are provided as input to Slot Attention to discover N slots that summarize the contents of the discrete tokens and thereby summarizing the input image. The slots are then provided to a Transformer decoder which is trained to decode and reconstruct the discrete tokens of the input image using a cross-entropy loss. Given the slots, the tokens can be generated by the Transformer auto-regressively and then be decoded via the DVAE decoder to produce a reconstruction of the input image. This forms the slot-based reconstruction pathway and, unless specified, the term *reconstruction* would refer to this slot-based pathway.

A.2 DVAE

Motivation. Our motivation for using DVAE is to quantize each patch (4x4 pixels in size) in the image as a discrete token and to ensure that the discrete token can accurately reconstruct the patch via the DVAE decoder. We decided to use DVAE (Ramesh et al., 2021) over VQ-VAE (van den Oord et al., 2017) because DVAE is simpler than VQ-VAE and requires only a simple reconstruction loss to train while VQ-VAE requires additional loss terms. Furthemore, because DALL-E also uses DVAE, it becomes a more natural choice to adopt.

Omitting the KL Term. In training the DVAE, we only use the reconstruction loss i.e. a simple MSE reconstruction objective rather than additionally using a KL term to impose a prior on the inferred tokens. This choice is made because we found the training to be more stable when we used smaller β coefficients (such as 0.04 or smaller) for the KL term including setting β to 0. This suggested that the KL term did not play a useful role in our model and hence setting the β coefficient to 0 is a more simpler choice to adopt. This is equivalent to removing the KL term.

A.3 MULTI-HEADED SLOT ATTENTION

In Slot-Attention (Locatello et al., 2020), each slot undergoes several rounds of interactions with the input image in order to collect the contents for the slot representation. In each iteration, this interaction of a slot with the input image is performed using dot-product attention with slot as the query. The value returned by this attention is a simple weighted sum of the input cells being attended by the slot. This weighted sum as a pooling method and method of interaction between the attended cells can be insufficient for properly representing the attended cells. This is especially the case when the object has a complex shape and texture. To address this, we propose a multi-headed extension of slot attention. In this, we replace the dot-product attention with a multi-headed dot-product attention. By doing this, each slot attends to the different parts of the same object simultaneously and the result of the attention is concatenated. As this concatenated result passes through the RNN layers, these

features for different parts of the same object can interact flexibly and result in a more rich encoding of the attended object. Recall that in standard slot attention, because there is only one attention head, different parts of the same object can only interact via the weighted sum which serves as a weak form of interaction as our results below shall indicate.

Implementation. We implement iterations of the Multi-headed Slot Attention as follows. For a given iteration, we first project the slots $\mathbf{S} = \mathbf{s}_{1:N}$ from the previous iteration into query vectors for each head. Similarly, we project the input cells $\mathbf{U} = \mathbf{u}_{1:T}$ into key and value vectors for each head.

$$\mathbf{Q}_m = \mathbf{W}_m^Q \mathbf{S},$$
$$\mathbf{K}_m = \mathbf{W}_m^K \mathbf{U},$$
$$\mathbf{V}_m = \mathbf{W}_m^V \mathbf{U}.$$

Next, we compute unnormalized attention proportions for each head m as by taking a dot-product as follows:

$$\frac{\mathbf{Q}_m \mathbf{K}_m^T}{\sqrt{D_K}}.$$

where D_K is the size of the key vectors. The attention weights for the input cells for each slot n and each head m is given by taking a softmax over both the N slots and the M heads.

$$[\mathbf{A}_{n,1}; \ldots; \mathbf{A}_{n,M}] = \text{softmax}\left(\left[\frac{\mathbf{Q}_1 \mathbf{K}_1^T}{\sqrt{D_K}}; \ldots; \frac{\mathbf{Q}_M \mathbf{K}_M^T}{\sqrt{D_K}}\right], \texttt{dim} = \text{`slots'} \text{ and `heads'}\right).$$

We then obtain the attention result for a given slot n as follows.

$$\texttt{updates}_n = [\mathbf{A}_{n,1}\mathbf{V}_1; \ldots; \mathbf{A}_{n,M}\mathbf{V}_M]\mathbf{W}^O \tag{1}$$

where $\mathbf{W}^O$ is an output project matrix. With this update vector, the slot state is updated as follows as done in the standard Slot Attention (Locatello et al., 2020).

$$\mathbf{s}_n \leftarrow \text{GRU}(\texttt{updates}_n, \mathbf{s}_n),$$
$$\mathbf{s}_n \leftarrow \mathbf{s}_n + \text{MLP}(\text{LayerNorm}(\mathbf{s}_n)).$$

This results in the update slot that is given to the next iteration.

Results. We apply Multi-headed Slot Attention in the Bitmoji dataset for our model. We found significant improvement in the MSE when we used 4 heads as compared to the standard Slot Attention (equivalent to 1 head). This is reported in Table 3.

Model	MSE
Ours (`num_slot_heads=1, num_slots=8`)	391.15
Ours (`num_slot_heads=1, num_slots=15`)	371.05
Ours (`num_slot_heads=4, num_slots=8`)	**136.29**

Table 3: Effect of number of slots and number of slot heads on the reconstruction quality in Bitmoji dataset in Slot2Seq. We compare the benefits of increasing the number of heads in our slot attention module and the effect of increasing the number of slots. We note that simply increasing the number of slots (from 8 to 15) does not improve the reconstruction quality significantly. However, increasing the number of heads (from 1 to 4) while keeping the number of slots same significantly improves the reconstruction quality.

We also noted that when using mixture decoder, using multi-headed slot attention does not help because the performance bottleneck is the Spatial Broadcast decoder (Watters et al., 2019) of the mixture decoder. This comparison is shown in Table 4.

Limitations. While multi-head attention helps information in the slots, in datasets with simple objects, having multiple heads can harm disentanglement of objects into different slots. This can occur because as each slots becomes more expressive, the network may be incentivised to collect information about multiple objects into the same slot. Therefore for our experiments on 3D Shapes, CLEVR and Shapestacks datasets, we used regular slot attention module with 1 head. Because Bitmoji can have complex hair and face shapes, we used 4-headed slot attention module for this dataset in our model.

Model	MSE
SA (`num_slot_heads=1, num_slots=8`)	394.5
SA (`num_slot_heads=4, num_slots=8`)	410.1

Table 4: Effect of number of slot heads on the reconstruction quality in Bitmoji dataset using Slot Attention (SA) with mixture-decoder. We note that with mixture decoder, having multiple heads does not benefit reconstruction as the performance bottleneck is the weak object component decoder based on Spatial Broadcast decoder (Watters et al., 2019)

Model	FID
Our Model (VQ Input + Transformer Decoder)	36.75
Ablation (CNN Input + Transformer Decoder)	32.07
Ablation (VQ Input + Mixture Decoder)	174.83
Slot Attention (CNN Input + Mixture Decoder)	44.14

Table 5: Ablation of Model Architecture. We ablate our model by replacing the discrete token input (VQ) to the slot attention encoder with a CNN feature map as originally used by Locatello et al. (2020). We also ablate our model by replacing the Transformer decoder with the mixture decoder. These suggest that the main driver of generation quality is the use of Transformer decoder as the mixture decoder suffers in performance.

A.4 Ablation of Architecture

To better justify our design, we perform two additional experiments that we describe here. In terms of architectural components, our model can be seen as VQ-Input + Slot Attention + Transformer Decoder while our baseline (Locatello et al., 2020) can be seen as CNN Input + Slot Attention + Mixture Decoder. Hence, the components that differ between our model and the baseline are *i)* providing VQ-Input and *ii)* using a Transformer decoder. We analyze the effect of these individual components by performing two ablations. In the first ablation, we take our model and replace the VQ-Input with CNN Input. We refer to this ablation as *CNN Input + Transformer Decoder*. In the second ablation, we take our model and replace the Transformer decoder with the mixture decoder. We refer to this ablation as *VQ-Input + Mixture Decoder*. We report the results in Table 5. We also visualize the object attention maps of the ablation models in Figure 26.

B Hyperparameters and Computational Requirements

We report the hyperparameters and the computational requirements for training our model in Table 6.

Dataset		3D Shapes	CLEVR	Shapestacks	Bitmoji
Training Images		400K	200K	230K	100K
Batch Size		50	50	50	50
LR Warmup Steps		30000	30000	30000	30000
Peak LR		0.0001	0.0003	0.0003	0.0001
Dropout		0.1	0.1	0.1	0.1
DVAE	Vocabulary Size	1024	4096	4096	4096
	Temp. Cooldown	1.0 to 0.1	1.0 to 0.1	1.0 to 0.1	1.0 to 0.1
	Temp. Cooldown Steps	30000	30000	30000	30000
	LR (no warmup)	0.0003	0.0003	0.0003	0.0003
Image Size		64	128	96	128
Image Tokens		256	1024	576	1024
Transformer Decoder Specifications	Layers	4	8	8	8
	Heads	4	8	8	8
	Hidden Dim.	192	192	192	192
Slot Attention Specifications	Slots	3	12	12	8
	Iterations	3	7	7	3
	Slot Dim.	192	192	192	192
Training Cost	GPU Usage	8GB	64GB	14GB	64GB
	Days	11 hours	5 Days	5 Days	3.5 Days

Table 6: Hyperparameters used for our model and computation requirements for each dataset.

C   ADDITIONAL QUALITATIVE RESULTS

Figure 9: Clusters in the concept library obtained by applying K-means on slots obtained from the 3D Shapes dataset.

Figure 10: Clusters in the concept library obtained by applying K-means on slots obtained from the Textured MNIST dataset.

Figure 11: Clusters in the concept library obtained by applying K-means on slots obtained from the Bitmoji dataset.

Figure 12: Qualitative Results for Hair Slot Replacements in Bitmoji dataset. For each image, the first row shows the hair slot that will be used as a replacement and the second row shows the generation from our model after the hair slot is replaced. This also provides examples of OOD compositions when the given image has the opposite gender from that of the source image from which the replacement slot is taken.

Slot Prompt   Composition

Figure 13: Qualitative Results for Compositional Generation in Bitmoji dataset using our model.

Figure 14: Qualitative Results for Compositional Generation in Bitmoji dataset using Slot Attention.

Figure 15: Qualitative Comparison of Compositional Generation in 3D Shapes.

Figure 16: Qualitative Comparison of Compositional Generation in Shapestacks.

Figure 17: Qualitative Comparison of Compositional Generation in TexturedMNIST.

Slot Prompt

Composition

Figure 18: Qualitative Samples of Compositional Generation in CLEVR from our model.

Slot Prompt   Composition

Figure 19: Qualitative Samples of Compositional Generation in CLEVR from Slot Attention with pixel-mixture decoder.

Slot Prompt

Compositions

Figure 20: Qualitative Results for Out-of-Distribution Compositional Generation in Shapestacks from our model.

Slot Prompt   Compositions

Figure 21: Qualitative Results for Slot Attention for Out-of-Distribution Compositional Generation in Shapestacks.

D ADDITIONAL DISCUSSION

D.1 STRONG DECODER IN MIXTURE LIKELIHOOD MODELS MAKE SLOTS CAPTURE MULTIPLE OBJECTS

One of the attractive properties of our model is that our Transformer decoder produces images with significantly better detail than Slot Attention. Slot Attention fails to render such details largely because of Spatial Broadcast Decoder that is used to render each object component. Spatial Broadcast Decoder decodes images by mapping a pixel coordinate and the provided slot vector to RGB pixel values and a mask using an MLP. This MLP prefers to learn simple mappings from pixel coordinate to RGB values. At the start of the training, this function tends to be a constant or a linear function of pixel coordinate and only after more training does this function achieve a more complex input-output behavior.

Hence, when a Spatial Broadcast Decoder is used, the decoder of each object component is biased in early training to prefer modeling segments without much RGB variation within the object patch. This property is important to guide the training of Slot Attention encoder to learn to disentangle separate objects and it has been exploited in several prior works on unsupervised object-centric representation learning. To understand why this occurs, consider a grayscale image that contains two balls, one colored white with pixel value 1.0 and the other colored grey with pixel value 0.5. Now consider the case when each slot represents one object in the scene. In this case, the decoder for the white ball simply needs to output a value 1.0 for all pixel coordinates and this is a constant function. Similarly, for the grey ball, the decoder needs to output a value 0.5 for all pixel coordinates. In contrast, consider the case where a single slot represents both the white and the grey balls. In this case, the decoder needs to map the pixels coordinates for the white ball to 1.0 and the pixel coordinates for the grey ball to 0.5 within the same function. This function is not longer a constant and is therefore much more complex than the functions that arose when each slot modeled separate objects. Furthermore, as objects might be positioned randomly, this mapping needs to quickly change when the positions of the balls change in the scene depending on information from the slot representation. This makes the mapping even more complex when more than one objects are modeled by the same slot. Hence, the network naturally prefers to model and decode different objects via different slots. As a result, the encoder is incentivized to cluster the pixels of the input image into objects. While this property could be utilized in simple datasets which have objects without much RGB variation and detail within the object, it can fail to render images properly in datasets such as Shapestacks with floor with complex textures or Bitmoji with complex face details and the shape of the hair.

Figure 22: Analysis of decoder capacity in Slot Attention when using a mixture-based likelihood model for decoding. We note that when we use a powerful CNN decoder to decode the RGB components and decoding masks for the objects, then a single component tries to model all the objects in the scene instead of each slot representing a single object as in the case of Spatial Broadcast decoder.

While one may argue that this could be fixed simply by replacing the Spatial Broadcast Decoder with a more powerful decoder for the object components. However, because weak decoder was encouraging the disentanglement of objects as argued above, hence by the same argument, when a powerful decoder is used, a single slot no longer has the incentive to model one object. Thus each slot can try to represent and model more than one object in the scene. We tested this empirically by replacing the Spatial Broadcast Decoder of Slot Attention with a powerful CNN decoder. We found

that this causes the slots to capture multiple objects and in some cases a single slot may try to model all the contents of the scene as a single object segment. This is shown in Figure 22.

Hence for unsupervised object discovery, this historically presented a trade-off between decoding capacity and the ability of the model to disentangle the objects. In contrast, our work shows that such a trade-off can be eliminated if Transformer is used as the decoder. Our model can not only detect objects without supervision but also render their fine details during decoding.

D.2 OBJECT DISCOVERY AND COLOR BIAS

Another problem that mixture decoders suffer from is what we term as the *color bias*. In mixture decoder, each object slot is commonly decoded using the spatial broadcast decoder to achieve a decoding capacity bottleneck. In this decoder, to decode each pixel, the pixel coordinate and the slot vector are concatenated and given to a decoder MLP to predict the pixel values for that coordinate. Hence, when two pixels are close to each other, the decoder MLP generates very similar pixel outputs for them. This is because the inputs to the MLP are very similar to each other for these two pixels. Given that an MLP, in general, prefers to learn smooth and linear (or constant) functions first before learning more complex functions, hence the output object rendered by a given slot tends to have a uniform or smoothly changing colors. As a consequence, this also biases the object-discovery process to also combine similar colors into a single slot and separate the regions with different colors into different slots.

Consequently, this design creates the problem of *color bias* which arises in two forms when dealing with visually complex images: *i)* First, if a single object is made up of multiple colors, the object may get split into multiple slots to handle the complexity of rendering multiple colors. *ii)* Second, if there are multiple objects having a similar color, those objects can get merged and become represented as a single slot. In visually simple scenes having different objects with separate colors, this might not appear to be a problem. But in more natural scenes in which single objects can be made up of multiple colors and many objects can have similar colors, this becomes a problem and harms the quality of the discovered objects. This phenomenon is demonstrated in the object attention maps of mixture decoder in Figures 23, 25 and 24. In comparison, because our decoder is not biased towards simple or uniform colors, hence our object discovery process is more robust to the color bias issue.

E ADDITIONAL EXPERIMENT DETAILS

E.1 CLEVR-MIRROR

In this work, we introduce a new dataset, CLEVR-Mirror as an extension of the standard CLEVR dataset. In comparison to standard CLEVR, in this dataset, we also introduce a mirror into the scene. CLEVR-Mirror is designed to see whether a model can obtain the ability to model complex global consistency by learning systematic relationship between local components. The standard CLEVR dataset is not proper for this purpose because the scene can easily be modeled without learning this global structure. CLEVR-Mirror requires learning relational knowledge such as the size change of reflected objects relative to the distance of the actual object to the mirror and occlusion among objects. For example, as shown in Figure 5, an object can be occluded in the mirror even if it is not in the non-mirror region.

E.2 CLUSTERING BASED ON ATTENTION MAPS

In CLEVR and Shapestacks, we build a concept library based on object position. For this, we apply K-means but using attention maps of the slots as described in Section 3.1. Thus each cluster corresponds to certain region in the image. For building slot prompts in CLEVR, we randomly pick N clusters without replacement. By doing this, we picked N random locations where we want to place objects. In Shapestacks, we randomly pick N clusters in a vertical tower configuration. We then randomly pick a slot from each cluster to construct the prompt.

Figure 23: Demonstration of Color Bias of Mixture-based Models in CelebA with Hard-to-Distinguish Background. In this comparison, we consider the images in which the background has a very similar color as the hair color. We show the input image, the resulting object attention maps and the reconstruction generated by Slot Attention and by our model. In these, we note that due to the color bias problem, in Slot Attention, the hair and background have become merged into the same slot in most of the cases. However, in our model, this problem is resolved and we can see that the hair and the background are assigned to separate slots which is the desired decomposition. We also note how the mixture decoder produces blurry reconstructions while our reconstructions are significantly more clear.

Figure 24: Analysis of Color Bias of Mixture-based Models in CelebA with Easy-to-Distinguish Background. We analyze the images in which the background has a color distinct from the hair color. This comparison is meant to show that mixture decoder may succeed when the colors of objects are distinct but when the colors are not distinct, it suffers as shown in Figure 23. Here, we show the input image, the resulting object attention maps and the reconstruction generated by Slot Attention and by our model. In these, we note that the color bias issue of mixture decoder is not that severe and both models can identify the hair slot as distinct from the background slot. However, we still observe that the mixture decoder produces blurry reconstructions while our reconstructions are significantly more clear.

Figure 25: Analysis of Color Bias of Mixture-based Models in Textured-MNIST. We analyze the object attention maps of the mixture-based Slot Attention and those generated by our model. Here, we show the input image, the reconstruction and the resulting object attention maps produced by Slot Attention and by our model. In these, we note that Slot Attention suffers because of color bias as often as the parts of the digit and the parts of the background tend to get combined into a single slot. In contrast, in our model, the attention maps for the digits are clear and easily identifiable. Furthermore, our reconstructions are much more clear than those from the mixture-based decoder.

Figure 26: Analysis of Object Attention Maps in Ablation Models. We ablate our model by replacing the discrete token input (VQ) to the slot attention encoder with a CNN feature map as originally used by Locatello et al. (2020). We also ablate our model by replacing the Transformer decoder with the mixture decoder. These attention maps suggest that using DVAE for obtaining a discrete representation of the input image can be synergistic with Transformer decoder for achieving good object discovery.