Instruction-driven history-aware policies
for robotic manipulations

Abstract: In human environments, robots are expected to accomplish a variety of manipulation tasks given simple natural language instructions. Yet, robotic manipulation is extremely challenging as it requires fine-grained motor control, long-term memory as well as generalization to previously unseen tasks and environments. To address these challenges, we propose a unified transformer-based approach that takes advantage of multiple inputs. In particular, our transformer architecture integrates (i) natural language instructions and (ii) multi-view scene observations while (iii) keeping track of the full history of observations and actions. Such an approach enables learning dependencies between history and instructions while improving manipulation precision using multiple views. We evaluate our method on the challenging RLBench benchmark and perform extensive ablations demonstrating advantages of our model. Notably, our approach scales to 74 diverse RLBench tasks, enables learning a single model for multiple tasks and outperforms state of the art. We also address instruction-conditioned tasks with multiple variations in the order in which they are executed, and demonstrate excellent generalization to unseen combinations during evaluation.

Keywords: Robotics Manipulation, Language Instruction, Transformer

1 Introduction

People can naturally follow language instructions and manipulate objects to accomplish a wide range of tasks from cooking to assembly and repair. It is also easy for us to generalize and build upon skills learned from a limited set of tasks to new ones. Hence, one of the long-term goals for robotics is to create generic instruction-following agents that can generalize to multiple tasks and environments.

Thanks to significant advances in learning generic representations for vision and language [1, 2, 3, 4], recent work has made great progress towards this goal [5, 6, 7, 8, 9]. For example, CLIPort [8] exploits CLIP models [4] to encode single-step visual observations and language instructions and to learn a single policy for 10 simulated tasks. BC-Z [9] uses a pre-trained sentence encoder [10] to generalize to multiple manipulation tasks. However, several challenges remain underexplored. One important challenge is that sequential tasks require to track object states that may be hidden from current observations, or to remember previously executed actions. This behaviour is hard to model with recent methods that mainly rely on current observations [8, 9].

Another challenge concerns manipulation tasks that require precise control of the robot end-effector to reach target locations. Such tasks can be difficult to solve with methods that use only one camera [11], especially in situations with visual occlusions and objects of different sizes, *e.g. put money in safe* (see Figure 1 left). While several recent approaches combine views from multiple cameras by converting multi-view images into a unified 2D/3D space [12, 13] or through a late fusion of multi-view predictions [14], learning representations for multiple camera views is an open research problem. Furthermore, cross-modal alignment between vision, action, and text is challenging, in

Submitted to the 6th Conference on Robot Learning (CoRL 2022). Do not distribute.

Figure 1: **Left:** Hiveformer can adapt to simultaneously perform 74 tasks from RLBench [18] given language instructions. **Right:** multiple variations of the *push buttons* task.

particular if we have to follow potentially unseen combinations of objects in instructions, see the *push buttons* task variations shown in Figure 1 (right). Most methods [8, 9, 15, 16] condense instructions into a global vector to condition policies [17] and are prone to lose fine-grained information about different objects.

To address the above challenges, we introduce *Hiveformer* - a **H**istory-aware **i**nstruction-conditioned multi-**vi**ew trans**former**. It converts instructions into language tokens given a pre-trained language encoder [4], and combines visual tokens for both past and current visual observations and proprioception. These tokens are concatenated and fed into a multimodal transformer which jointly models dependencies between the current and historical observations, spatial relations among views from multiple cameras, as well as fine-grained cross-modal alignment between vision and instruction. Based on the output representations from our multimodal transformer, we predict 7-DoF actions, *i.e.*, position, rotation and state of the gripper, with a UNet [19] decoder.

We carry out extensive experiments on RLBench [18] in three setups: single-task learning, multi-task learning, and multi-variation generalization[1]. Our Hiveformer significantly outperforms state-of-the-art models for all the three settings, demonstrating the effectiveness of encoding instruction, history and views from multiple cameras with the proposed transformer. Moreover, we evaluate our model on 74 tasks of RLBench, which goes beyond the 10 tasks used by Liu *et al.* [14]. We manually group all the tasks into 9 categories according to their main challenges and show segment-wise analysis for a better understanding. Hiveformer not only excels in the multiple task setting with seen instructions in training, but also enables generalization to new instructions that represent different variations of the task, even with human-written language instructions. We plan to release our code and pre-trained models.

To summarize, our contributions are three-fold:

- We introduce a new model Hiveformer to solve various challenges in robotics tasks. It jointly models instruction, multiple views, and history via a multimodal transformer for action prediction in robotic manipulation.
- We perform extensive ablations of our model on RLBench with 74 tasks grouped into 9 distinctive categories. The history improves long-term tasks and the multi-view setting is most helpful for tasks requiring high precision or in the presence of visual occlusions.
- We demonstrate that Hiveformer outperforms the state of the art in three setups on RLBench, namely single-task, multi-task and multi-variation. A single Hiveformer trained with synthetic instructions is able to solve multiple tasks or variations, and even generalize to unseen human-written instructions.

---

[1]We follow definitions in RLBench [18] for tasks and variations. A task can be composed of multiple variations that share the same skills but differ in objects, attributes or orders as shown in the example in Figure 1.

2 Related work

Vision-based robotic manipulation. While earlier methods for solving robotics tasks such as visual servoing [20, 21] were designed manually, the need to cope with large variations of objects and environments led to the emergence of learning-based neural approaches [22, 23, 24, 25]. Deep neural networks [26, 27] have achieved impressive results in manipulation for single tasks [28], and recently led to more challenging setups such as multi-task learning [29, 30, 31]. Different multi-tasking approaches are explored by discovering which tasks should be trained together [32, 14], determining shared features across tasks [33, 34], meta-learning [35, 36, 37], goal-conditioned learning [38, 39], or inverse reinforcement learning [40]. These approaches can be generally split in two categories according to the training algorithm: reinforcement learning based methods [41, 42, 43, 44] which learn policies from a reward provided by the environment, and behavioral cloning based methods [45, 46, 47] that learn from demonstrations using supervised learning. Demonstrations can be provided by humans [48], robots [22, 49] or play interactions [47]. The emergence of robotic simulators has also greatly accelerated the development of manipulation methods, such as Gym [50], manipulaTHOR [51], dm_control [52], Sapien [53], CausalWorld [54], and RLBench [18], encompassing the era of embodied agents [55, 56, 57]. In this work, we use behavioral cloning to train policies given scripted demonstrations from RLBench [18] which covers many challenging manipulation tasks.

Instruction-driven vision-based robotic manipulation has received growing attention from manipulations in 2D planar [58] to recent 3D environments [59, 7, 60], and even transferring to the real world [8, 9]. As grounding the language in visual scenes is important, existing works have focused on challenges in object grounding, such as localizing objects based on referring expressions [61, 62, 63] and grounding spatial relationships [64, 6, 65]. Since language describes high-level actions, several works [66, 67, 60] consider a hierarchical approach to decompose a task into sub-goals. In our work, we translate instructions into a sequence of key steps, executable by an off-the-shelf motion planner. Because natural language is rich and diverse, while training resources are limited, further works learn from collected offline data with instructions [9, 16], or leverage pre-trained vision-language models [3, 4] for action prediction [8, 68]. To further improve the precision of manipulation skills, Mees *et al*. [7] align instructions with multiple cameras by fusing input images with known camera parameters. Most of these works [5, 7, 8, 9] are stateless, since they only employ current observations to predict next actions. Instead, our work proposes to jointly model language instructions, history, and multi-view observations.

Transformers [69] have brought significant breakthroughs to natural language processing [1], computer vision [70] and related fields [3, 4, 71]. They have also been used in the context of supervised reinforcement learning, such as the Decision Transformer [72] or the Trajectory Transformer [73]. Recent works in Vision-and-Language Navigation (VLN) [74, 75, 76] further demonstrate that the Transformer allows to better leverage previous observations to improve multi-modal action prediction. Transformers are also used to build a multi-modal, multi-task, multi-embodiment generalist agent, GATO [77]. Inspired by the success of this work, we explore the transformer architecture for instruction-driven and history-aware robotic manipulation.

3 Problem Definition

Our goal is to train a policy $\pi\left(a_{t+1}|\{x_l\}_{l=1}^n, \{o_i\}_{i=1}^t, \{a_i\}_{i=1}^t\right)$ for robotic manipulation conditioned on a natural language instruction $\{x_l\}_{l=1}^n$, visual observations $\{o_i\}_{i=1}^t$, and previous actions $\{a_i\}_{i=1}^t$ where n is the number of words in the instruction and t is the current step. For robotic control, we use macro steps [11] – key turning points in action trajectories where the gripper changes its state (open/close) or velocities of joints are close to zero. In this way, the sequence length of an episode is significantly reduced from hundreds of small steps to typically less than 10 macro steps.

The **observation** o_t at step t consists of RGB images I_t and point clouds P_t aligned with the RGB images. I_t is composed of $\{I_t^k\}_{k=1}^K$ RGB images from K cameras, with each I_t^k having size $H \times W \times 3$ (height, width, 3 channels). Following the setup in previous work [14], we use $K = 3$ with cameras on the wrist, left shoulder and right shoulder of the agent, and $H = W = 128$. Similarly, P_t represents

Figure 2: Hiveformer jointly models instructions, views from multiple cameras, and historical actions and observations with a multimodal transformer for robotic manipulation.

point clouds $\{P_t^k\}_{k=1}^K$ from $K = 3$ cameras. A point cloud $P_t^k \in \mathbb{R}^{H \times W \times 3}$ is obtained by projecting a single channel depth image $H \times W$ from the k-th camera in world coordinates using known camera intrinsics and extrinsics. Therefore, each point in P_t^k has 3D coordinates and is aligned with a pixel in I_t^k.

The **action space** a_t consists of the gripper's pose and its state following the standard setup in RLBench [11]. The gripper's pose is composed of the Cartesian coordinates $p_t = (x_t, y_t, z_t)$ and its rotation is described with a quaternion $q_t = (q_t^0, q_t^1, q_t^2, q_t^3)$ relative to the base frame. The gripper's state c_t is boolean and indicates whether the gripper is open or closed. An object is grasped when it is located in between the gripper's two fingers and the gripper is closing its grasp. The execution of an action is achieved by a motion planner in RLBench.

4   Our Model: Hiveformer

We propose a unified architecture for various robotic tasks called Hiveformer (History-aware instruction-conditioned multi-view transformer), see Figure 2 for an overview. It consists of three modules: feature encoding, multimodal transformer and action prediction. The feature encoding module (Sec. 4.1) generates token embeddings for instructions $\{x_l\}_{l=1}^n$, visual observations $\{o_i\}_{i=1}^t$ and previous actions $\{a_i\}_{i=1}^t$. Then, the multimodal transformer (Sec. 4.2) learns relationships between the instruction, current multi-camera observations and history. Finally, the action prediction module (Sec. 4.3) utilizes a convolutional network (CNN) to predict the next rotation q_{t+1} and gripper's state c_{t+1}, and adopts a UNet decoder [19] to predict the next position p_{t+1}.

4.1   Feature Encoding

We encode the instruction, visual observations, and actions as a sequence of tokens.

Instructions. We employ pre-trained language encoders to tokenize and encode the sentence instruction. Specifically, we use the language encoder in the CLIP model [4]. Thanks to its vision-and-language pre-training, it is better at differentiating vision-related semantics such as colors compared to pure language-only pre-trained models like BERT [1]. We freeze the pre-trained language encoder and use a linear layer on top of it to obtain embeddings $\hat{x}_l \in \mathbb{R}^d$ for each word token:

$$\hat{x}_l = \text{LN}(W_x \tilde{x}_l) + E_T^x, \tag{1}$$

where $\tilde{x}_l$ is the l-th output embedding token after the language encoder, LN is layer normalization [78], W_x is a projection matrix, and E_T^x an embedding to differentiate instructions from visual observations.

Observations and Proprioception. We encode the RGB image I_t^k, point clouds P_t^k, and proprioception A_t^k for each camera k separately. $A_t^k \in \{0,1\}^{H \times W}$ is a binary attention map used to encode the position of the gripper p_t. It takes value one at the location of the gripper center and zero elsewhere. We concatenate I_t^k and A_t^k in the channel dimension and use a UNet encoder to obtain a

feature map $\hat{F}_t^k \in \mathbb{R}^{H^v \times W^v \times d_v}$, where H^v, W^v, d_v are the height, width, and number of channels of the feature map. More details of the CNN structure are presented in the supplementary material. Next, we concatenate $\hat{F}_t^k$ with point cloud representations in the channel dimension to indicate the spatial location of each patch in the feature map. To make the size of P_t^k and $\hat{F}_t^k$ match with each other, we apply max-pooling to P_t^k. The final encoded feature map $F_t^k \in \mathbb{R}^{H^v \times W^v \times (d_v+3)}$ is computed as follows:

$$F_t^k = \left[\text{CNN}([I_t^k; A_t^k]); \text{MaxPool}(P_t^k) \right]. \tag{2}$$

We use patches $f_{t,h,w}^k \in F_t^k, h \in [1, H^v], w \in [1, W^v]$ as separate visual tokens. We further encode $f_{t,h,w}^k$ with embeddings of the camera id E_C^k, of the step id E_S^t, and of the patch location $E_L^{h,w}$ as well as an embedding to indicate the visual nature of the tokens E_T^v as follows:

$$g_{t,h,w}^k = \text{LN}(W_f f_{t,h,w}^k) + E_C^k + E_S^t + E_L^{h,w} + E_T^v. \tag{3}$$

The encoded visual tokens of the k-th camera at step t are denoted as $G_t^k = \{g_{t,h,w}^k\}_{h=1,w=1}^{H^v,W^v} \in \mathbb{R}^{H^v,W^v,d}$. We use the same encoding method for all the cameras and concatenate the encoded tokens in a sequence as $G_t = (G_t^1, \cdots, G_t^K)$.

4.2 Multimodal transformer

Given the encoded tokens at the current macro step t, the multimodal transformer aims to obtain a contextualized representation for G_t conditioned on the encoded instruction $\{\hat{x}_l\}_{l=1}^n$ and history $\{G_i\}_{i=1}^{t-1}$. This enables learning relationships among views from multiple cameras, the current observations and instructions, and between the current observations and history for action prediction. We use the Transformer's attention mechanism [79] to learn such relationships:

$$\text{Attn}(Q, K, V) = \text{Softmax}\left(\frac{W_Q Q (W_K K)^T}{\sqrt{d}}\right) W_V V, \tag{4}$$

where W_Q, W_K, W_V are learnable parameters. Unlike previous work [75] that uses self-attention layers to capture all relationships, we employ different attention layers to capture different types of relationships, in order to reinforce the importance of the context. First, we use a cross-attention layer to learn the inter-modal relationships between G_t and its conditioned contexts C_t consisting of tokens in the instruction $\{\hat{x}_l\}_{l=1}^n$ and history $\{G_i\}_{i=1}^{t-1}$, which is:

$$\tilde{G}_t = \text{CA}(G_t, C_t) = \text{Attn}(G_t, C_t, C_t). \tag{5}$$

Then we learn the intra-modal relationships among patch tokens obtained from the views from multiple cameras through a self-attention layer, $i.e.$ $\text{SA}(\tilde{G}_t) = \text{Attn}(\tilde{G}_t, \tilde{G}_t, \tilde{G}_t)$. Finally, a feed-forward network consisting of a couple linear layers W_1 and W_2 is applied as follows:

$$\hat{G}_t = \text{LN}\left(W_2 \text{ GeLU}\left(W_1 \text{ SA}(\tilde{G}_t)\right)\right). \tag{6}$$

4.3 Action Prediction

We concatenate the output embeddings of the transformer $\hat{G}_t$ in Eq (6) and the original encoded visual representations $\hat{F}_t$ in Sec. 4.1 in the channel dimension and reshape the flattened sequence into a feature map $H_t \in \mathbb{R}^{K \times H^v \times W^v \times (d+d_v)}$ to predict the next action $a_{t+1} = [p_{t+1}; q_{t+1}; c_{t+1}]$. As some RLBench tasks require accurate fine-grained positioning, different from the rotation q_{t+1} and gripper state c_{t+1}, the position p_{t+1} is predicted through a separate module that uses point clouds P_t.

Rotation and gripper's state. We transform H_t into $\mathbb{R}^{H^v \times W^v \times K(d+d_v)}$ and feed it into a CNN decoder. The CNN structure is described in the supplementary material. We then apply average pooling across spatial dimensions and employ a linear layer to regress a 5-dimension vector $[q_{t+1}; c_{t+1}]$.

Position. We decompose the gripper's position prediction p_{t+1} into an expected point based on point clouds p_{t+1}^e and an offset p_{t+1}^o, $i.e.$ $p_{t+1} = p_{t+1}^e + p_{t+1}^o$. The offset allows us to predict a virtual point outside the convex hull of the point cloud, $e.g.$ a robotic arm should first reach above the object at a virtual point and then touch the object. For each camera k, we use a CNN with an upsampling layer to predict an attention map $B_t^k \in \mathbb{R}^{H \times W}$ over the point clouds P_t^k. Each value $B_{t,h,w}^k \in B_t^k$ corresponds

to the probability of reaching the point $P_{t,h,w}^k \in P_t^k$. Therefore, we compute p_{t+1}^e as the expected position over all cameras:

$$p_{t+1}^e = \sum_{k,h,w} \left(B_{t,h,w}^k \cdot P_{t,h,w}^k \right).$$ (7)

The offset p_{t+1}^o is computed based on the instruction and the current step id. Let $E_O \in \mathbb{R}^{N_{task} \times T \times 3}$ be a learnable embedding, where N_{task} is the number of tasks in the RLBench benchmark and T is the maximum length of episodes. We use the instruction to predict the task id: $\Pr(m) = \text{Softmax}\left(W_m \frac{1}{n} \sum_{l=1}^n \tilde{x}_l \right)$, where $\Pr(m) \in [0,1]^{N_{task}}$. Then we obtain the offset as follows: $p_{t+1}^o = \sum_m \Pr(m) \cdot E_O(m,t,:)$.

4.4 Training and Inference

Losses. We use behavioral cloning to train the models. In RLBench, we generate D, a collection of N successful demonstrations for each task. Each demonstration $\delta \in$ D is composed of a sequence of (maximum) T macro-steps with observations $\{o_i^\delta\}_{i=1}^T$, actions $\{a_i^*\}_{i=1}^T$, task m^* and instruction $\{x_l\}_{l=1}^n$. We minimize a loss function $\mathscr{L}$ over a batch of demonstrations B $= \{\delta_j\}_{j=1} \subset$ D. The loss function is the sum of two losses: a mean-square error (MSE) on the gripper's action and a cross-entropy (CE) over the task classification:

$$\mathscr{L} = \frac{1}{|B|} \sum_{\delta \in \mathsf{B}} \left[\sum_{t \le T} \text{MSE}\left(a_t, a_t^*\right) + \text{CE}\left(\Pr(m), m^*\right) \right].$$ (8)

Masking current observation. To ensure that the model uses historical information $\{o_i\}_{i=1}^{t-1}, \{a_i\}_{i=1}^{t-1}$ instead of only relying on the current observation o_t to predict the next action, we randomly mask the current observation with a probability of 0.1. The masking is obtained by zeroing out the randomly selected patch features in the current observation. Therefore, even if the unmasked current observations contain sufficient information, the model still requires to complete the masked observations from the history for action prediction.

5 Experiments

In this section, we carry out extensive experiments on RLBench [18] to demonstrate the effectiveness of our Hiveformer model in three settings: single-task, multi-task, and multi-variation.

5.1 Experimental Setup

Dataset setups. Based on the Coppelia simulator, RLBench [18] is a benchmark of robotic tasks. To compare our method with previous work [14] and unless stated otherwise, we use the same 10 tasks with 100 demonstrations for training. We further evaluate our model on 74 tasks for which we were able to obtain successful demonstrations. We manually group these tasks into 9 categories according to their challenges. More details on the split of the tasks are given in the supplementary material. To minimize variance, we train 5 models over different collections of demonstrations (sampled from the simulator using different random seeds). The success rate is always computed over the same 500 unseen episodes and averaged across random seeds for each task.

Implementation details. We employ an Adam optimizer with a learning rate of 5×10^{-5}. Each batch consists of 32 demonstrations. Models were trained for 100,000 iterations. We apply data augmentation in training including jitter over RGB images I_t^k, and a random crop of I_t^k, P_t^k, and A_t^k while keeping them align. All models are trained on NVIDIA Tesla V100 SXM2 GPUs using a Singularity container with headless rendering.

Baseline methods. We compare our model with state-of-the-art methods on RLBench. ARM [11] is based on reinforcement-learning, uses single-view images, and trains a Q-function to predict relevant pixels from RGB and point clouds, and an agent that refines the Q-function's prediction. Auto-λ [14] uses a UNet encoder and decoder and applies late fusion to predictions from multiple views.

5.2 Ablations

Table 2: Comparison with state-of-the-art methods on 10 tasks.

	Pick & Lift	Pick-Up Cup	Push Button	Put Knife	Put Money	Reach Target	Slide Block	Stack Wine	Take Money	Take Umbrella	Avg.
Single-task learning											
ARM [11]	70	80	-	-	-	100	-	70	-	70	-
Auto-λ [14]	82	72	95	36	31	100	36	23	38	37	55.0
Ours	93.8	82.7	99.5	69.9	96.3	100.0	95.3	82.1	82.3	90.7	88.3
Multi-task learning											
Auto-λ [14]	87	78	95	31	62	100	77	19	64	80	69.3
Ours (w/o inst)	84.0	13.8	97.6	41.8	54.2	98.8	36.0	68.8	74.6	72.6	64.6
Ours	88.8	93.0	100.0	75.0	58.0	100.0	79.8	70.4	79.0	89.2	83.3

Table 3: Comparison with state-of-the-art methods on tasks grouped by sets in single-task learning. The performance of Auto-λ is obtained by using their provided codebase.

	Planning	Tools	Long Term	Rot. Invar.	Motion Planning	Screw	Multi Modal	Precision	Visual Occlusion	Avg
Num. of tasks	9	11	4	7	9	4	5	11	14	74
Auto-λ [14]	58.9	20.0	2.3	73.1	66.7	48.2	47.6	34.6	40.6	44.0
Ours (w/o hist)	78.9	46.7	10.0	84.6	73.3	72.6	60.0	63.8	57.9	60.9
Ours (one view)	57.7	23.2	12.3	57.8	63.2	35.6	40.7	33.7	37.1	40.1
Ours	81.6	53.0	16.9	84.2	72.7	80.9	67.1	64.7	60.2	65.4

Table 1: Ablations on the single-task setting.

	Inputs			Transformer			Training	SR
	Visual Tokens	Point Clouds	Gripper Position	Multi-View	History	Attn	Mask Obs	
R1	×	×	×	×	×	×	×	73.2 ± 3.0
R2	Channel	×	×	✓	×	Self	×	74.3 ± 4.5
R3	Channel	✓	×	✓	×	Self	×	76.7 ± 5.7
R4	Channel	✓	✓	✓	×	Self	×	77.3 ± 5.6
R5	Channel	✓	✓	✓	✓	Self	×	81.8 ± 5.2
R6	Channel	✓	✓	✓	✓	Self	✓	82.3 ± 6.3
R7	Patch	✓	✓	✓	✓	Self	✓	84.5 ± 6.4
R8	Patch	✓	✓	✓	✓	Cross	✓	88.3 ± 5.1

To demonstrate the effectiveness of the proposed model architecture, we report performance for extensive component ablations in Table 1. The model in R1 (row 1) is a UNet architecture similar to Auto-λ [14] except that it is conditioned on instructions rather than task ids. This baseline only uses visual observations at the current step and already achieves promising results with a success rate of 73.2%. On top of R1's architecture, a multimodal transformer with self-attention is added in R2 to improve the modeling of multi-view images. Visual tokens $\{G_t^i\}_{i=1}^K$ are different channels in the feature map instead of spatial patches used in our final model. In R3 and R4, we further add point clouds P_t and gripper position A_t in the feature encoding, which leads to 3% improvement in total. The impact of history, *i.e.* the use of observations from previous steps, $(\{G_j^i\}_{i=1,j=1}^{K,t-1})$ is studied in R5 and R6. The history information brings 4.5% absolute gains and the masking of observations during training further improves the performance by 0.5%. In R7, we replace the tokenization of feature maps from channels $g_{t,c}^k$ to patches $g_{t,h,w}^k$, and obtain another 2.2% gain. This improvement can be attributed to patch tokens that help encode fine-grained spatial information. Finally, we use cross-attention instead of self-attention (Eq. 5) to condition on the instruction and history context. It further boosts the performance with a 3.8% gain.

5.3 Comparison with State of the Art

Single-task evaluation. The upper block in Table 2 presents the results of different models on 10 single tasks in RLBench. We compare our model with ARM [11] and Auto-λ [14], two state-of-the-art methods on RLBench and observe a consistent improvement for all tasks.

Extending tasks in a single-task evaluation setup. In Table 3, we further compare Auto-λ, Hiveformer and its variants across 74 tasks. The variant without history removes the history tokens in Hiveformer, while the variant with one view only uses one camera at each step (we take the best

among the 3 cameras for each task). The full Hiveformer achieves consistently better performance compared to Auto-λ [14] on all types of tasks. Among them, the Long-term, Tools and Planning task groups assess the use of history, where our model brings more gains than the variant without history. Compared to the one view variant, our full model performs significantly better on tasks requiring more fine-grained control or with large occlusions such as Screw, Precision and Visual Occlusion task groups.

Multi-task evaluation. The bottom block in Table 2 shows the results in a multi-task learning setting. Notably, Auto-λ uses better training algorithms for multi-task settings which dynamically adjust the weights of different tasks, while our model simply treats all tasks with equal weights. Nevertheless, our model outperforms Auto-λ by 14%, demonstrating the superiority of our architecture. We further compare our model with a variant without instructions in the input sequence (for this option we also modify the model by predicting p_{t+1}^o from H_t^k). The results show that instructions are important in the multi-task setting. Moreover, the performance of our single-policy model trained for all tasks is only slightly worse compared to performance of individual models for each task.

Generalization to multi-variations. Table 4 shows the results of Hiveformer trained on different variations of two tasks respectively: *Tower* and *Push Buttons*. The *Tower* (resp. *Push Buttons*) task requires the robot to sequentially stack colored cubes (resp. push colored buttons) using the order specified in the instruction, see Figure 1(right). We use 100 variations in training and test models in both seen variations and 100 unseen variations. In this setting, instructions are necessary to generalize to unseen variations (*e.g.* it is impossible to distinguish the order of pushing buttons red-green-blue vs. blue-red-

Table 4: Results on multi-variation learning over seen or unseen variations and synthetic or real instructions.

| # Demos | | Push Buttons | | | Tower | | |
| Per | Instr. | Seen | Unseen | | Seen | Unseen | |
Variation		Synt.	Synt.	Real	Synt.	Synt.	Real
10	Seq.	96.4	71.1	65.7	71.6	49.8	19.4
50	Seq.	99.4	83.1	70.9	74.3	52.1	20.6
100	Seq.	100	86.3	74.2	77.4	56.2	21.3
100	Avg	9.1	1.1	0.0	5.3	0.2	0.0

green by only looking at the scene). We compare the models trained with different numbers of demonstrations per variation. Even in the most challenging case where only 10 demonstrations are available per variation, Hiveformer achieves a success rate of 71.1% for the Push Buttons task and 49.8% for the Tower task in unseen variations. Furthermore, we test the generalization ability to real instructions. We collect 91 human-written instructions and measure the success rate for each instruction on 10 object location randomized episodes. Though our model is only trained on synthetic instructions in RLBench which have a very limited vocabulary and diversity, it manages to perform well on real human instructions. We also test our model with a global language embedding (average over word tokens) as in [8], but observe a dramatic drop of performance. A reason is that the averaged embeddings cannot differentiate action orders, *e.g.* the average cosine similarity with these representations is 0.97.

6 Conclusion

We proposed Hiveformer for instruction-driven robotics manipulation. This multimodal transformer jointly modeled instructions, views from multiple cameras, and history and was shown to be beneficial to solve challenging tasks involving long-term planning and visual occlusions. We evaluated the model on RLBench in three settings: single-task learning, multi-task learning, and multi-variation generalization. Our Hiveformer significantly outperforms the state-of-the-art approaches for all three settings, and generalizes well to unseen task variations and human-written instructions.

Limitations: As Hiveformer leverages transformer to model long-range history and views from multiple cameras, the computational cost is quadratically increased with respect to the length of input sequences. Our model is trained with behavioral cloning, which may also suffer from exposure bias. Future works could improve the efficiency for long-term tasks and also incorporate reinforcement learning to train our model.

References

[1] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *NAACL-HLT*, 2019.

[2] K. He, H. Fan, Y. Wu, S. Xie, and R. Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, 2020.

[3] J. Lu, D. Batra, D. Parikh, and S. Lee. ViLBERT: Pretraining task-agnostic visiolinguistic representations for vision-and-language tasks. In *NeurIPS*, 2019.

[4] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, et al. Learning transferable visual models from natural language supervision. In *ICML*, pages 8748–8763. PMLR, 2021.

[5] C. Lynch and P. Sermanet. Language conditioned imitation learning over unstructured data. *RSS*, 2021.

[6] O. Mees and W. Burgard. Composing pick-and-place tasks by grounding language. In *ISER*, 2021.

[7] O. Mees, L. Hermann, E. Rosete-Beas, and W. Burgard. CALVIN: A benchmark for language-conditioned policy learning for long-horizon robot manipulation tasks. *RA-L*, 2022.

[8] M. Shridhar, L. Manuelli, and D. Fox. CLIPort: What and where pathways for robotic manipulation. In *CoRL*, pages 894–906. PMLR, 2022.

[9] E. Jang, A. Irpan, M. Khansari, D. Kappler, F. Ebert, C. Lynch, S. Levine, and C. Finn. BC-Z: Zero-shot task generalization with robotic imitation learning. In *CoRL*, pages 991–1002. PMLR, 2022.

[10] Y. Yang, D. Cer, A. Ahmad, M. Guo, J. Law, N. Constant, G. H. Abrego, S. Yuan, C. Tar, Y.-H. Sung, et al. Multilingual universal sentence encoder for semantic retrieval. In *ACL*, pages 87–94, 2020.

[11] S. James and A. J. Davison. Q-Attention: Enabling efficient learning for vision-based robotic manipulation. *RA-L*, 2022.

[12] A. Zeng, P. Florence, J. Tompson, S. Welker, J. Chien, M. Attarian, T. Armstrong, I. Krasin, D. Duong, V. Sindhwani, et al. Transporter networks: Rearranging the visual world for robotic manipulation. In *CoRL*, pages 726–747. PMLR, 2021.

[13] S. James, K. Wada, T. Laidlow, and A. J. Davison. Coarse-to-fine Q-Attention: Efficient learning for visual robotic manipulation via discretisation. In *CVPR*, 2022.

[14] S. Liu, S. James, A. J. Davison, and E. Johns. Auto-Lambda: Disentangling dynamic task relationships. *TMLR*, 2022.

[15] L. Shao, T. Migimatsu, Q. Zhang, K. Yang, and J. Bohg. Concept2robot: Learning manipulation concepts from instructions and human demonstrations. *The International Journal of Robotics Research*, 40(12-14):1419–1434, 2021.

[16] S. Nair, E. Mitchell, K. Chen, S. Savarese, C. Finn, et al. Learning language-conditioned robot behavior from offline data and crowd-sourced annotation. In *CoRL*, pages 1303–1315. PMLR, 2022.

[17] E. Perez, F. Strub, H. De Vries, V. Dumoulin, and A. Courville. FiLM: Visual reasoning with a general conditioning layer. In *AAAI*, 2018.

[18] S. James, Z. Ma, D. R. Arrojo, and A. J. Davison. RLBench: The robot learning benchmark & learning environment. *RA-L*, 5(2):3019–3026, 2020.

[19] O. Ronneberger, P. Fischer, and T. Brox. UNet: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

[20] J. Hill. Real time control of a robot with a mobile camera. In *9th Int. Symp. on Industrial Robots, 1979*, pages 233–246, 1979.

[21] F. Chaumette and S. Hutchinson. Visual servo control. i. basic approaches. *IEEE Robotics & Automation Magazine*, 13(4):82–90, 2006.

[22] R. Strudel, A. Pashevich, I. Kalevatykh, I. Laptev, and C. Schmid. Learning to combine primitive skills: A step towards versatile robotic manipulation. In *ICRA*, pages 4637–4643. IEEE, 2020.

[23] A. X. Lee, S. Levine, and P. Abbeel. Learning visual servoing with deep features and fitted q-iteration. In *ICLR*, 2017.

[24] Q. Bateux, E. Marchand, J. Leitner, F. Chaumette, and P. Corke. Training deep neural networks for visual servoing. In *ICRA*, pages 1–8. IEEE, 2018.

[25] P. Florence, C. Lynch, A. Zeng, O. A. Ramirez, A. Wahid, L. Downs, A. Wong, J. Lee, I. Mordatch, and J. Tompson. Implicit behavioral cloning. In *CoRL*, pages 158–168. PMLR, 2022.

[26] A. I. Károly, P. Galambos, J. Kuti, and I. J. Rudas. Deep learning in robotics: Survey on model structures and training strategies. *IEEE Transactions on Systems, Man, and Cybernetics: Systems*, 51(1):266–279, 2020.

[27] Y. Labbe, J. Carpentier, M. Aubry, and J. Sivic. Cosypose: Consistent multi-view multi-object 6d pose estimation. In *ECCV*, 2020.

[28] I. Akkaya, M. Andrychowicz, M. Chociej, M. Litwin, B. McGrew, A. Petron, A. Paino, M. Plappert, G. Powell, R. Ribas, et al. Solving rubik's cube with a robot hand. *arXiv preprint arXiv:1910.07113*, 2019.

[29] R. Caruana. Learning many related tasks at the same time with backpropagation. *NeurIPS*, 7, 1994.

[30] H. B. Ammar, E. Eaton, P. Ruvolo, and M. Taylor. Online multi-task learning for policy gradient methods. In *ICML*, pages 1206–1214. PMLR, 2014.

[31] C. Devin, A. Gupta, T. Darrell, P. Abbeel, and S. Levine. Learning modular neural network policies for multi-task and multi-robot transfer. In *ICRA*, pages 2169–2176. IEEE, 2017.

[32] T. Standley, A. Zamir, D. Chen, L. Guibas, J. Malik, and S. Savarese. Which tasks should be learned together in multi-task learning? In *International Conference on Machine Learning*, pages 9120–9132. PMLR, 2020.

[33] S. Thrun and J. O'Sullivan. Discovering structure in multiple learning tasks: The TC algorithm. In *ICML*, volume 96, pages 489–497, 1996.

[34] B. Chen, A. Sax, G. Lewis, I. Armeni, S. Savarese, A. Zamir, J. Malik, and L. Pinto. Robust policies via mid-level visual representations: An experimental study in manipulation and navigation. *CoRL*, 2020.

[35] C. Finn and S. Levine. Deep visual foresight for planning robot motion. In *ICRA*, pages 2786–2793. IEEE, 2017.

[36] T. Yu, C. Finn, A. Xie, S. Dasari, T. Zhang, P. Abbeel, and S. Levine. One-shot imitation from observing humans via domain-adaptive meta-learning. *RSS*, 2018.

[37] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine. Meta-world: A benchmark and evaluation for multi-task and meta reinforcement learning. In *CoRL*, pages 1094–1100. PMLR, 2020.

[38] C. Finn, T. Yu, T. Zhang, P. Abbeel, and S. Levine. One-shot visual imitation learning via meta-learning. In *CoRL*, pages 357–368. PMLR, 2017.

[39] D. Kalashnikov, J. Varley, Y. Chebotar, B. Swanson, R. Jonschkowski, C. Finn, S. Levine, and K. Hausman. MT-Opt: Continuous multi-task robotic reinforcement learning at scale. *arXiv preprint arXiv:2104.08212*, 2021.

[40] A. S. Chen, S. Nair, and C. Finn. Learning generalizable robotic reward functions from "in-the-wild" human videos. *RSS*, 2021.

[41] R. S. Sutton and A. G. Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[42] T. Haarnoja, A. Zhou, K. Hartikainen, G. Tucker, S. Ha, J. Tan, V. Kumar, H. Zhu, A. Gupta, and P. Abbeel. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

[43] J. Peters, S. Vijayakumar, and S. Schaal. Reinforcement learning for humanoid robotics. In *Proceedings of the third IEEE-RAS international conference on humanoid robots*, pages 1–20, 2003.

[44] A. Pashevich, D. Hafner, J. Davidson, R. Sukthankar, and C. Schmid. Modulated policy hierarchies. *NeurIPS Deep RL Workshop*, 2018.

[45] F. Torabi, G. Warnell, and P. Stone. Behavioral cloning from observation. In *Proceedings of the 27th International Joint Conference on Artificial Intelligence*, pages 4950–4957, 2018.

[46] J. Ho and S. Ermon. Generative adversarial imitation learning. *Advances in neural information processing systems*, 29, 2016.

[47] C. Lynch, M. Khansari, T. Xiao, V. Kumar, J. Tompson, S. Levine, and P. Sermanet. Learning latent plans from play. In *CoRL*, pages 1113–1132. PMLR, 2020.

[48] V. Petrík, M. Tapaswi, I. Laptev, and J. Sivic. Learning object manipulation skills via approximate state estimation from real videos. In *CoRL*, 2020.

[49] Y. Hristov, D. Angelov, M. Burke, A. Lascarides, and S. Ramamoorthy. Disentangled relational representations for explaining and learning from demonstration. In *CoRL*, 2019.

[50] G. Brockman, V. Cheung, L. Pettersson, J. Schneider, J. Schulman, J. Tang, and W. Zaremba. OpenAI Gym. *arXiv preprint arXiv:1606.01540*, 2016.

[51] K. Ehsani, W. Han, A. Herrasti, E. VanderBilt, L. Weihs, E. Kolve, A. Kembhavi, and R. Mottaghi. ManipulaTHOR: A framework for visual object manipulation. In *CVPR*, pages 4497–4506, 2021.

[52] S. Tunyasuvunakool, A. Muldal, Y. Doron, S. Liu, S. Bohez, J. Merel, T. Erez, T. Lillicrap, N. Heess, and Y. Tassa. dm_control: Software and tasks for continuous control. *Software Impacts*, 6:100022, 2020.

[53] F. Xiang, Y. Qin, K. Mo, Y. Xia, H. Zhu, F. Liu, M. Liu, H. Jiang, Y. Yuan, H. Wang, et al. Sapien: A simulated part-based interactive environment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11097–11107, 2020.

[54] O. Ahmed, F. Träuble, A. Goyal, A. Neitz, Y. Bengio, B. Schölkopf, M. Wüthrich, and S. Bauer. CausalWorld: A robotic manipulation benchmark for causal structure and transfer learning. *arXiv preprint arXiv:2010.04296*, 2020.

[55] R. Pfeifer and J. Bongard. *How the body shapes the way we think: a new view of intelligence*. MIT press, 2006.

[56] J. Duan, S. Yu, H. L. Tan, H. Zhu, and C. Tan. A survey of embodied AI: From simulators to research tasks. *IEEE Transactions on Emerging Topics in Computational Intelligence*, 2022.

[57] A. Das, S. Datta, G. Gkioxari, S. Lee, D. Parikh, and D. Batra. Embodied question answering. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, 2018.

[58] D. Misra, J. Langford, and Y. Artzi. Mapping instructions and visual observations to actions with reinforcement learning. *ACL*, 2017.

[59] K. M. Hermann, F. Hill, S. Green, F. Wang, R. Faulkner, H. Soyer, D. Szepesvari, W. M. Czarnecki, M. Jaderberg, D. Teplyashin, M. Wainwright, C. Apps, D. Hassabis, and P. Blunso. Grounded language learning in a simulated 3D world. *NeurIPS Workshop*, 2017.

[60] D. I. A. Team, J. Abramson, A. Ahuja, A. Brussee, F. Carnevale, M. Cassin, F. Fischer, P. Georgiev, A. Goldin, T. Harley, et al. Creating multimodal interactive agents with imitation and self-supervised learning. *arXiv preprint arXiv:2112.03763*, 2021.

[61] R. Paul, J. Arkin, N. Roy, and T. M Howard. Efficient grounding of abstract spatial concepts for natural language interaction with robot manipulators. In *Robotics: Science and Systems Foundation*, 2016.

[62] T. Nguyen, N. Gopalan, R. Patel, M. Corsaro, E. Pavlick, and S. Tellex. Robot object retrieval with contextual natural language queries. *RSS*, 2020.

[63] W. Goodwin, S. Vaze, I. Havoutis, and I. Posner. Semantically grounded object matching for robust robotic scene rearrangement. *ICRA*, 2021.

[64] S. Tellex, T. Kollar, S. Dickerson, M. R. Walter, A. G. Banerjee, S. Teller, and N. Roy. Understanding natural language commands for robotic navigation and mobile manipulation. In *Twenty-Fifth AAAI Conference on Artificial Intelligence*, 2011.

[65] W. Liu, C. Paxton, T. Hermans, and D. Fox. StructFormer: Learning spatial structure for language-guided semantic rearrangement of novel objects. *ICRA*, 2021.

[66] W. Huang, P. Abbeel, D. Pathak, and I. Mordatch. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents. *arXiv preprint arXiv:2201.07207*, 2022.

[67] D. Garg, S. Vaidyanath, K. Kim, J. Song, and S. Ermon. LISA: Learning interpretable skill abstractions from language. *arXiv preprint arXiv:2203.00054*, 2022.

[68] A. Khandelwal, L. Weihs, R. Mottaghi, and A. Kembhavi. Simple but effective: Clip embeddings for embodied ai. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14829–14838, 2022.

[69] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[70] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *ICLR*, 2020.

[71] H. Tan and M. Bansal. Lxmert: Learning cross-modality encoder representations from transformers. In *EMNLP*, 2019.

[72] L. Chen, K. Lu, A. Rajeswaran, K. Lee, A. Grover, M. Laskin, P. Abbeel, A. Srinivas, and I. Mordatch. Decision transformer: Reinforcement learning via sequence modeling. In *NeurIPS*, 2021.

[73] A. L. Putterman, K. Lu, I. Mordatch, and P. Abbeel. Pretraining for language conditioned imitation with transformers. In *NeurIPS*, 2021.

[74] S. Chen, P.-L. Guhur, C. Schmid, and I. Laptev. History aware multimodal transformer for vision-and-language navigation. *Advances in Neural Information Processing Systems*, 34, 2021.

[75] A. Pashevich, C. Schmid, and C. Sun. Episodic transformer for vision-and-language navigation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 15942–15952, 2021.

[76] P.-L. Guhur, M. Tapaswi, S. Chen, I. Laptev, and C. Schmid. Airbert: In-domain pretraining for vision-and-language navigation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1634–1643, 2021.

[77] S. Reed, K. Zolna, E. Parisotto, S. G. Colmenarejo, A. Novikov, G. Barth-Maron, M. Gimenez, Y. Sulsky, J. Kay, J. T. Springenberg, et al. A generalist agent. *arXiv preprint arXiv:2205.06175*, 2022.

[78] J. L. Ba, J. R. Kiros, and G. E. Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

[79] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin. Attention is all you need. *NeurIPS*, 2017.