Relevant or Random: Can LLMs Truly Perform Analogical Reasoning?

Abstract

Analogical reasoning is a unique ability of humans to address unfamiliar challenges by transferring strategies from relevant past experiences. One key finding in psychology is that compared with irrelevant past experiences, recalling *relevant* ones can help humans *better* handle new tasks (Gentner and Smith, 2012). Coincidentally, the NLP community has also recently found that self-generating relevant examples in the context can help large language models (LLMs) better solve a given problem than hand-crafted prompts (Yasunaga et al., 2024). However, it is yet not clear whether relevance is the key factor eliciting such capability, *i.e.,* can LLMs benefit more from self-generated relevant examples than irrelevant ones? In this work, we systematically explore whether LLMs can truly perform analogical reasoning on a diverse set of reasoning tasks. With extensive experiments and analysis, we show that self-generated random examples can surprisingly achieve comparable or even better performance, *e.g.,* 4% performance boost on GSM8K with random biological examples. We find that the accuracy of self-generated examples is the key factor and subsequently design two improved methods with significantly reduced inference costs. Overall, we aim to advance a deeper understanding of LLM analogical reasoning and hope this work stimulates further research in the design of self-generated contexts.

1 Introduction

A hallmark of human intelligence is that they can solve novel problems by drawing analogy from relevant past experiences, a concept known as *analogical reasoning* in cognitive science (Vosniadou and Ortony, 1989). As indicated by the name, recalling previously acquired *relevant* experiences can facilitate humans to *better* tackle new tasks, whereas irrelevant ones are rarely beneficial and can even be distracting (Gentner and Smith, 2012).

Figure 1: Illustration of LLM analogical reasoning in Yasunaga et al. (2024). LLMs are prompted to self-generate relevant examples as context before solving the new problem.

For instance, when faced with a novel math problem about determinants (*e.g.,* calculating the value of a given fourth-order determinant), humans can resolve this by reflecting upon the methodology employed to ascertain the value of a third-order determinant, whereas biological knowledge (*e.g.,* how the human body regulates its temperature) can generally be considered irrelevant.

With the recent advancements in scaling up model size and data, LLMs have demonstrated impressive zero-shot and few-shot performance across various reasoning tasks, especially, through advanced prompting methods like chain-of-thought (CoT) (Wei et al., 2022). Compared to common approaches such as zero or few-shot CoT (Zhou et al., 2022; Kojima et al., 2022; Wang et al., 2022b), Yasunaga et al. (2024) introduce LLM analogical reasoning, *i.e.,* LLMs self-generate examples relevant to the query as context to better solve new problems; see Fig. 1 for an example. However, it remains unclear whether relevance is the key to eliciting such capability in LLMs. While several studies explore the influence of the relevance of

demonstrations in in-context learning and CoT (Liu et al., 2022; Kim et al., 2022; Lyu et al., 2023; Chen et al., 2023; Yang et al., 2023; Wang et al., 2023; Yasunaga et al., 2024), none of them investigate whether self-generated relevant examples consistently outperform irrelevant ones in LLM analogical reasoning.

In this paper, to systematically assess the capability of LLMs to perform analogical reasoning, we conduct a series of ablation experiments on a variety of reasoning tasks including problems from GSM8K (Cobbe et al., 2021), MATH (Hendrycks et al., 2021), and BIG-Bench Hard (BBH) (Suzgun et al., 2022). With extensive experiments, we aim to address the following two research questions:

- **Q1.** Are self-generated *relevant* examples more beneficial to LLMs than *random* ones?

- **Q2.** If not, what is the pivotal factor for LLMs' performance in analogical reasoning?

To answer these questions, we empirically analyze the analogical reasoning abilities of GPT-3.5 (turbo) and Llama series models (Touvron et al., 2023). Surprisingly, experimental results show that prompting LLMs to self-generate random examples can achieve comparable or even better performance on *certain* tasks which is not in line with the key claim of analogical reasoning in Gentner and Smith (2012), indicating that LLMs *cannot always* perform analogical reasoning. As for Q2, we point out through controlled experiments that the key factor is *the accuracy of self-generated examples*. Informed by these findings, we design two approaches that can outperform existing methods with significantly reduced inference costs. Specifically, we ask LLMs to randomly generate a few problems and manually verify their correctness, then use this fixed set of problems as in-context learning demonstrations for all test samples. Consistent observations across different model types consolidate the conclusions. We summarize the major contributions of our work below:

- To the best of our knowledge, we, for the first time, extensively assess the ability of LLMs to perform analogical reasoning and explore their counterintuitive behavior on certain tasks.

- With extensive experiments and analysis, we demonstrate the effectiveness and limitations of different types of self-generated contexts. Our code base is available at `https://anonymous.4open.science/r/Analogical_Reasoning`.

2 Related Work

This work mainly explores whether LLMs can truly perform analogical reasoning. In light of this, we review two lines of research that form the basis of this work: chain-of-thought prompting and LLM analogical reasoning.

2.1 Chain-of-Thought Prompting

Chain-of-thought (CoT) prompting induces LLMs to generate intermediate reasoning steps before generating the final answer (Wei et al., 2022), greatly improving the reasoning capabilities of LLMs. Typical CoT prompting approaches include few-shot CoT (Wei et al., 2022; Zhou et al., 2022; Wang et al., 2022b; Li et al., 2022; Wang et al., 2022a), taking several labeled demonstrations of the reasoning process, and zero-shot CoT, comprising only instructions like "Let's think step by step" (Kojima et al., 2022; Zelikman et al., 2022; Zhang et al., 2023). Other ongoing research on CoT has also explored (*i*) optimizing the demonstration selection (Fu et al., 2022; Lu et al., 2022; Qin et al., 2023), (*ii*) optimizing the quality of reasoning chains (Khot et al., 2022; Chen et al., 2022; Zhao et al., 2023; Shinn et al., 2023), and (*iii*) CoT in smaller language models (Magister et al., 2022; Ho et al., 2022; Fu et al., 2023).

2.2 LLM Analogical Reasoning

While few-shot CoT can provide more detailed reasoning guidance, it requires labeled examples which can be unavailable for a new task. To tackle this problem, Yasunaga et al. (2024) propose analogical prompting to guide LLMs to self-generate relevant exemplars as few-shot demonstrations, which is similar to analogical reasoning, *i.e.,* humans can address new problems by drawing analogy from relevant past experience (Vosniadou and Ortony, 1989; Holyoak, 2012). In this work, we step forward to explore the intrinsic principle of LLM analogical reasoning. Specifically, we aim to investigate whether LLMs can authentically exhibit such reasoning capabilities and determine the extent to which the relevance of self-generated examples contributes to enhancing this process.

3 Methodology

Our analysis is based on the analogical prompting approach outlined in Yasunaga et al. (2024). Specifically, for a given target problem x, analogical prompting introduces instructions like:

Figure 2: Example prompts for GSM8K (mathematical reasoning). ***Top***: The original prompt used in Yasunaga et al. (2024) for self-generating *relevant* math problems. ***Bottom***: The prompt designed for self-generating *random* math problems. We mark the differences between these two prompts in blue and green respectively.

Problem: [x]

Relevant problems: Recall five relevant and diverse problems. For each problem, describe it and explain the solution.

Solve the initial problem:

The goal is to induce LLMs to self-generate *relevant* examples, aiding them to solve the target problem via in-context learning. To ensure better performance and efficiency, several key technical decisions are made in Yasunaga et al. (2024):

- The self-generated examples should be relevant and diverse, achieved through a specially designed instruction.
- Generate relevant problems and the solution to the initial problem in one pass.
- 3 to 5 self-generated examples perform the best.

In this work, we leverage similar prompts[1] to guide LLMs to generate different types of *irrelevant* examples as context; see Fig. 2 for example prompts:

- *N/A*: generate problems that are N/A (not applicable) to the initial problem.
- *Random$_{same}$*: randomly generate examples of the same problem type (*e.g.,* math).
- *Random$_{diff}$*: randomly generate examples of different problem types (*e.g.,* any type except math).
- *Random$_{bio}$*: randomly generate biological problems.

Yasunaga et al. (2024) demonstrate that self-generating relevant examples can consistently outperform zero-shot CoT and few-shot CoT (handcrafted examples or retrieved top-k most similar training samples) on different tasks. Therefore, we do not include these two methods in our work. Interested readers can refer to the corresponding results and analysis in Yasunaga et al. (2024). In addition, we show prompts for different methods on all datasets in Appendix A.1.

4 Experiment

4.1 Experimental Setup

We construct the evaluation suite based on diverse reasoning-intensive tasks, including mathematical reasoning and other reasoning (*e.g.,* logical and temporal reasoning) tasks:

---

[1]Since our work aims to comprehensively explore and analyze the intrinsic principle of LLM analogical reasoning proposed in Yasunaga et al. (2024), we should follow the original design of the instructions to have a fair comparison and reliable analysis.

Method	Temporal sequences	Logical deduction five objects	Reasoning about colored objects	Formal fallacies	Word sorting	Average
Relevant	**60.0**	**51.2**	**76.7**	51.2	76.9	**63.2**
N/A	57.5	45.3	75.5	**53.3**	**77.7**	61.9
Random$_{same}$	53.1	48.8	73.5	52.4	74.1	60.4
Random$_{diff}$	44.3	44.8	72.4	51.2	69.2	56.4
Random$_{bio}$	57.1	49.5	76.1	50.8	74.9	61.7

Table 1: Accuracy (%) of different methods on five reasoning tasks in BBH. **Bold** indicates the best results. Self-generated *relevant* examples achieve the best average performance. Detailed results for different seeds are reported in Appendix A.2.

Method	Task		
	GSM8K	MATH	Average
Relevant	71.5	33.3	52.4
N/A	75.5	36.1	**55.8**
Random$_{same}$	75.1	**36.3**	55.7
Random$_{diff}$	**76.3**	34.1	55.2
Random$_{bio}$	75.3	34.6	54.9

Table 2: Accuracy (%) of different methods on two mathematical reasoning tasks. Self-generated *irrelevant* examples are consistently better than *relevant* ones. Table 13 in Appendix A.2 reports detailed results for different seeds.

- **Mathematical reasoning**. We work with two commonly used datasets, GSM8K (Cobbe et al., 2021) and MATH (Hendrycks et al., 2021). For each dataset, we randomly sample 500 examples from the original test set and run experiments three times with different random seeds (resulting in different test samples).

- **Other reasoning**. Following Yasunaga et al. (2024), we evaluate five reasoning tasks in BIG-Bench Hard (BBH) (Suzgun et al., 2022): temporal sequences (temporal reasoning), logical deduction five objects and reasoning about colored objects (logical reasoning), formal fallacies (deductive reasoning) and word sorting (symbolic reasoning). For each task, we use all test samples for evaluation and run experiments three times with different random seeds.

We mainly use GPT-3.5 (gpt-3.5-turbo) as the LLM and obtain all outputs from it with the temperature set to 0. We ask the LLM to self-generate 5 examples for GSM8K, 3 examples for MATH and BBH following Yasunaga et al. (2024).

4.2 Main Results

We now address the research questions asked in §1 with empirical results.

Q1. Are self-generated relevant examples more beneficial to LLMs than random ones?

The results averaged over all random seeds are reported in Table 1 and Table 2; more detailed results for every seed are shown in Appendix A.2.

- **Self-generated relevant examples achieve the best average performance on BBH.** From the results in Table 1, we can observe that the superiority of self-generated relevant examples is empirically substantiated on BBH. Specifically, using relevant examples, denoted by 'relevant', outperforms other approaches on temporal and logical reasoning tasks. While it performs worse than 'N/A' on deductive and symbolical reasoning, it can still improve the accuracy by **1.3**% on average compared to 'N/A'.

However, the results on mathematical reasoning tasks are quite counterintuitive as described below:

- **Relevant examples do not guarantee better performance.** Different from BBH, all types of self-generated irrelevant examples consistently outperform relevant ones on both mathematical reasoning datasets, showing that LLMs cannot yet perform analogical reasoning on these tasks. Interestingly, when we use randomly generated biological examples (*e.g.,* how the process of photosynthesis occurs in plants), they can yield about **2.5**% better results on average compared to generating relevant math problems. Besides, 'N/A' achieves the best average result as it is the second-best on both datasets.

Problems in MATH span various subjects and difficulty levels. To investigate whether the inferior performance of relevant examples on MATH is accidentally caused by certain categories, we further report the accuracy across different subjects and difficulty levels in Table 3 and Fig. 3. The consistent performance gap between 'relevant' and

Method	Precalculus	Intermediate Algebra	Algebra	Prealgebra	Counting & Probability	Geometry	Number Theory
Relevant	10.4	9.8	51.8	56.8	22.1	24.2	**37.0**
N/A	9.1	15.7	**55.5**	**61.0**	**28.7**	**25.8**	34.2
Random$_{same}$	12.3	**17.6**	54.4	60.6	25.4	**25.8**	34.9
Random$_{diff}$	**13.0**	14.1	52.7	56.8	26.2	24.2	33.6
Random$_{bio}$	**13.0**	12.2	53.0	59.2	**28.7**	**25.8**	32.2

Table 3: Accuracy (%) across different subjects in the MATH dataset. Self-generated irrelevant examples outperform relevant ones on 6 out of 7 subjects.

Figure 3: Comparison of all methods at different difficulty levels on the MATH dataset. Level 1 represents the easiest and level 5 is the hardest. 'relevant' clearly performs worse than other approaches at all difficulty levels.

Method	GSM8K	MATH	Average
Relevant	**0.54**	**0.41**	**0.48**
N/A	0.19	0.28	0.24
Random$_{same}$	0.30	0.20	0.25
Random$_{diff}$	0.15	0.10	0.13
Random$_{bio}$	0.06	0.11	0.09
Oracle	0.65	0.63	0.64

Table 4: Average relevance score (semantic similarity) between self-generated examples and the query. 'Oracle' stands for the average similarity score between the query and k most similar training samples (k is the number of self-generated examples).

	Relevant	N/A	Random$_{same}$
Accuracy	62.0	72.0	86.0

Table 5: Accuracy (%) of self-generated examples on the MATH dataset. The examples generated by 'relevant' are less accurate.

other methods across different problem categories demonstrates the inherent flaws of relevant examples, indicating that *mathematical reasoning tasks exhibit different analogical reasoning paradigms from other reasoning tasks.*

It might present challenges to prompt LLMs to accurately generate specific types of demonstrations. Therefore, given the unexpected results on mathematical reasoning tasks, one may wonder:

Q1-1. Are self-generated examples really relevant or irrelevant to the query?

To quantitatively measure the relevance between the generated examples and the query, we compute the average cosine similarity between them. Following Zhang et al. (2023), we use the sentence transformer (Reimers and Gurevych, 2019) to encode all samples. For each method, the reported result is averaged across three seeds (see Appendix A.3 for the decomposition of relevance).

As observed from Table 4, relevant examples are much more semantically similar to the query

than irrelevant ones and the relevance score of 'relevant' is more biased towards 'oracle' rather than 'random' or 'N/A', demonstrating that *LLMs indeed follow instructions to generate specific types of demonstrations.* Furthermore, we calculate the average similarity score between self-generated relevant examples and queries for BBH (0.46), which is slightly lower than the score of mathematical reasoning tasks (0.48). This result demonstrates that the difference in analogical reasoning performance between BBH (Table 1) and mathematical reasoning (Table 2) is *not* because LLMs can generate more relevant examples for BBH.

We provide a case study in Table 6 to delve deeper into the demonstrations of different methods. As we can notice, the example generated by 'relevant' is more related to the query as they both involve the mathematical concept 'number bases'. In contrast, examples such as 'What is the value of

Query:	For how many ordered pairs (A, B) where A and B are positive integers is $AAA_7 + BBB_7 = 666_7$?
Relevant	In a certain base, the sum of two three-digit numbers is 777. If the digits of one of the numbers are reversed, the sum becomes 888. What is the base of this number system?
N/A	What is the value of x in the equation $2x + 5 = 10$?
Random$_{same}$	In a bag, there are 5 red marbles, 3 blue marbles, and 2 green marbles. If you randomly pick 2 marbles from the bag without replacement, what is the probability that both marbles are red?
Random$_{diff}$	How do you bake chocolate chip cookies?
Random$_{bio}$	How does the process of photosynthesis occur in plants?
Oracle	Find the number of ordered pairs (a, b) of complex numbers such that $a^3b^5 = a^7b^2 = 1$.

Table 6: Demonstration examples of different methods on the MATH dataset. The example generated by 'relevant' is more related to the query than other examples generated by 'N/A' or 'random'.

Variant	GSM8K			MATH		
	Relevant	N/A	Random$_{same}$	Relevant	N/A	Random$_{same}$
ICL	71.2	73.8	72.0	37.0	39.8	39.2
GPT4-Calibration	**75.2**	**75.6**	**75.6**	**44.4**	**41.2**	**40.0**
Random	70.0	72.0	68.4	36.0	38.0	37.8

Table 7: Accuracy (%) of different variants on GSM8K and MATH. When using GPT4-generated answers (mostly accurate), 'GPT4-Calibration' consistently outperforms 'ICL' for all methods. In contrast, 'random' always performs worse than 'ICL'.

x in the equation $2x + 5 = 10$?' (N/A) or 'How do you bake chocolate chip cookies?' (Random$_{diff}$) are less relevant to the query. This comparison highlights once again that relevance may not be the key factor for analogical reasoning performance on mathematical reasoning tasks. To understand better the underlying reasons for the counterintuitive results, we then ask the following question:

Q2. If relevance is not the key factor, what is more important for the accuracy of analogical reasoning?

Looking back at Table 6, an interesting observation is that the self-generated relevant example appears to be more difficult to solve than the irrelevant ones, regardless of whether they are math problems or not. Consequently, the accuracy of relevant examples may be lower. To verify this, we conduct a pilot experiment on MATH. Specifically, we randomly select 50 samples for different types of generated math problems, *i.e.,* Relevant, N/A and Random$_{same}$, and manually evaluate their accuracy. We exclude other methods as it is difficult to define the 'accuracy' of the examples they generate. From the results in Table 5, we can observe that while the examples generated by 'relevant' are more related to the test query, *they are less accurate*, raising the question whether the performance of different approaches on mathematical reasoning tasks is strongly correlated with the accuracy of self-generated examples.

Proxy Approaches However, as the accuracy of the examples located at the output cannot be directly controlled, we meticulously design a variant called *ICL*, which extracts the generated examples from the model output as in-context learning (ICL) demonstrations and combines them with the query as input to LLMs, as a proxy for the original method. We also consider the following two variants: (*a*) *GPT4-Calibration* which replaces the answers of demonstrations in *ICL* with GPT4-generated answers, and (*b*) *Random* changes the answers of demonstrations in *ICL* to random numbers. Our manual verification confirmed that GPT4-generated answers were mostly accurate. We conduct this experiment on GSM8K and MATH with GPT-3.5 as the LLM reasoner.

From the results of different variants reported in Table 7, we can see that increasing the accuracy of generated examples can indeed improve the performance: *GPT4-Calibration* consistently outperforms *ICL* by incorporating more accurate answers. In contrast, *random* always performs the worst among all variants. Therefore, the key factor influencing the performance on mathematical reasoning is *the accuracy of self-generated examples* rather than their relevance.

It is worthwhile to note that while several papers explore how the correctness of demonstration

> **Input**
>
> Randomly recall five examples of math problems. Note that your problems should be distinct from each other (e.g., involving different numbers and names). For each problem:
> - After "Q: ", describe the problem
> - After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

> **Output**
>
> **Q:** If John has 5 apples and he buys 8 more, how many apples does he have in total?
> **A:** To find the total number of apples John has, we add the number of apples he initially has to the number of apples he buys. So, we calculate 5 + 8 = 13. Therefore, John has \boxed{13} apples in total.
> …
>
> **Q:** Find the derivative of the function f(x) = 3x^2 + 2x - 5.
> **A:** To find the derivative of f(x), we apply the power rule to each term. The derivative of 3x^2 is 6x, the derivative of 2x is 2, and the derivative of a constant -5 is 0. Therefore, the derivative of f(x) is f'(x) = 6x + 2. So, the derivative is \boxed{6x + 2}.

Figure 4: Example prompts and outputs for randomly generating math problems. We manually verify the answers to ensure the correctness of the generated examples.

Method	Task		
	GSM8K	MATH	Average
Relevant	71.5	33.3	52.4
N/A	75.5	36.1	55.8
Random$_{same}$	75.1	36.3	55.7
Random$_{diff}$	76.3	34.1	55.2
Random$_{bio}$	75.3	34.6	54.9
ICL$_{math}$	75.7	**36.8**	56.3
ICL$_{bio}$	**77.9**	34.9	**56.4**

Table 8: Comparison of different methods on two mathematical reasoning tasks.

Relevant	N/A	Random$_{same}$	Random$_{diff}$	Random$_{bio}$
71.2	74.9	75.3	**75.9**	74.3

Table 9: Accuracy (%) of different methods with a new prompt.

answers influences in-context learning (Min et al., 2022; Yoo et al., 2022; Wei et al., 2023; Pan et al., 2023; Kossen et al., 2024), our work differs from them in the following aspects: (*i*) The examples in our work are generated by LLMs rather than real data from NLP benchmarks, *i.e.,* randomly sampled from the training set. In addition, there are rationales (CoT) in self-generated examples, which are different from the input-label format of in-context learning investigated in these papers; and (*ii*) These studies mainly evaluate in-context learning on different classification or multi-choice datasets, *i.e.,* the output space is a finite set. In contrast, we are evaluating mathematical reasoning tasks, where the output space is infinite.

Given the above findings, a natural question is:

> **Q2-1.** Can we ask the LLM to randomly generate a few math or biological problems and manually verify their correctness, then use this fixed set of problems as ICL demonstrations for all test queries?

We refer to these two methods as ICL$_{math}$ and ICL$_{bio}$, and conduct experiments with them on GSM8K and MATH (see Fig. 4 for example prompts and outputs for generating math problems).

Detailed prompts and outputs for different methods are provided in Appendix A.4. Following the original setting, we ask the LLM to randomly generate 5 examples for GSM8K and 3 examples for MATH. As observed from Table 8, ensuring the accuracy of self-generated examples does lead to better performance regardless of the problem type. ICL$_{math}$ and ICL$_{bio}$ achieve similar average performance, once again demonstrating that relevance does not matter (see Appendix A.5 for more analysis on relevance). Moreover, both ICL variants only need to generate examples once, which significantly reduces the inference cost and further demonstrates their superiority.

4.3 Further Analysis

Difference from Previous Work Apart from the comprehensive analysis, we have designed two novel ICL-based approaches that are completely different from the one in Yasunaga et al. (2024) (Q2-1). The difference lies mainly in the following two aspects: (*i*) The key claim in Yasunaga et al. (2024) is that we should guide the model to self-generated relevant examples as context. Motivated by the analysis and findings in our work (Q1 and Q2), our methods focus on ensuring the accuracy of self-generated examples rather than their relevance, which leads to better performance regardless of the problem type. (*ii*) As we have demonstrated that the relevance of self-generated examples does not matter, there is no need to generate relevant examples for each test query (the original method in Yasunaga et al. (2024)). In contrast, our meth-

Method	Relevant	N/A	Random$_{same}$	Random$_{diff}$	Random$_{bio}$	ICL$_{math}$	ICL$_{bio}$
Llama-2-70b-Chat	45.1	51.4	50.9	54.3	47.1	55.5	**56.1**
Llama-3-8B-Instruct	69.5	72.3	72.6	74.1	73.5	75.8	**76.8**
Llama-3.1-8B-Instruct	74.8	77.3	78.4	78.8	77.6	80.2	**81.0**

Table 10: Accuracy (%) of different methods on GSM8K using Llama-2-70b-Chat, Llama-3-8B-Instruct and Llama-3.1-8B-Instruct models. Self-generated relevant examples always perform worse than irrelevant ones and both ICL variants outperform other approaches.

Variant	Method		
	Relevant	N/A	Random$_{same}$
ICL	56.2	58.2	58.6
GPT4-Calibration	**60.8**	**61.0**	**60.8**
Random	53.2	54.0	59.6

Table 11: Accuracy (%) of different variants on GSM8K using Llama-2-70b-Chat. 'GPT4-Calibration' consistently performs better than 'ICL' and 'random' for different methods.

Number	Relevant	N/A	Random$_{same}$	Random$_{diff}$	Random$_{bio}$
3	73.1	**77.3**	75.0	75.3	75.5
5	71.5	75.5	75.1	**76.3**	75.3

Table 12: Accuracy (%) of all methods with different numbers of demonstrations.

ods use a fixed set of examples for all test queries, which significantly reduces the inference cost.

Robustness to Prompt Formats To verify the robustness of different methods to prompt formats, we experiment with a new prompt paraphrased from the original one by GPT-4 and present the results on GSM8K in Table 9. We also observe better performance with irrelevant examples than relevant ones, showing the robustness.

Generalization to Open-source LLMs Our experiments and analysis so far used GPT-3.5 as the LLM, which is closed-source and gets updated over time. To verify whether the observations and conclusions are consistent across different models and additionally for reproducibility, we extend the experiments to Llama-2-Chat (Touvron et al., 2023). Specifically, we use vLLM (Kwon et al., 2023) to serve a Llama-2-70b-Chat model for experiments and report the results of different methods/variants on GSM8K in Table 10 and Table 11. We can draw similar observations: (*i*) self-generated relevant examples underperform all types of irrelevant ones, (*ii*) 'GPT4-Calibration' consistently outperforms the other two variants, and (*iii*) ICL$_{math}$ and ICL$_{bio}$ perform better than other approaches, demonstrating that the conclusions can be generalized to different models.

We further conduct experiments with Llama-3-8B-Instruct and Llama-3.1-8B-Instruct. The results reported in Table 10 demonstrate the generalizability of the conclusions across different models. In

addition, since investigating analogical reasoning requires LLMs to self-generate different types of problems, we only experiment with instruction-tuned LLMs to ensure that they can follow the given instructions.

Different Numbers of Demonstrations While we mainly follow the setting in Yasunaga et al. (2024) to ask the LLM to generate $k = 5$ examples for GSM8K, we further investigate the effect of the number of demonstrations. Specifically, we conduct controlled experiments with $k = 3$ and report the results in Table 12. We can observe that irrelevant examples consistently outperform relevant ones across different numbers of demonstrations, emphasizing their effectiveness.

In addition, we show more analysis on ICL$_{math}$ and ICL$_{bio}$, the results of repeating problems, and the generalization to different tasks in Appendix A.6 ~ A.8, respectively.

5 Conclusion

In this work, we have systematically assessed the capability of LLMs to perform analogical reasoning. We have identified key research questions and empirically analyzed a representative set of LLMs on a diverse collection of reasoning tasks. Extensive experimental results and analysis show that LLMs *cannot always* perform analogical reasoning and the key influencing factor is the accuracy of self-generated examples rather than their relevance. Given these findings, we have designed two ICL-based approaches with better performance and significantly reduced inference costs. In the future, we would like to investigate additional analogical prompting methods to generate more accurate examples.

Limitations

This work has several limitations. First, due to the inference cost of ChatGPT[2], we conduct experiments on subsets of the test data for mathematical reasoning tasks. Besides, we include 3 datasets requiring different reasoning capabilities in this work. A further improvement could be to explore more diverse types of tasks.

References

Wei-Lin Chen, Cheng-Kuang Wu, Yun-Nung Chen, and Hsin-Hsi Chen. 2023. Self-ICL: Zero-shot in-context learning with self-generated demonstrations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 15651–15662, Singapore. Association for Computational Linguistics.

Wenhu Chen, Xueguang Ma, Xinyi Wang, and William W Cohen. 2022. Program of thoughts prompting: Disentangling computation from reasoning for numerical reasoning tasks. *arXiv preprint arXiv:2211.12588*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Yao Fu, Hao Peng, Litu Ou, Ashish Sabharwal, and Tushar Khot. 2023. Specializing smaller language models towards multi-step reasoning. *arXiv preprint arXiv:2301.12726*.

Yao Fu, Hao Peng, Ashish Sabharwal, Peter Clark, and Tushar Khot. 2022. Complexity-based prompting for multi-step reasoning. *arXiv preprint arXiv:2210.00720*.

D. Gentner and L. Smith. 2012. Analogical reasoning. In V.S. Ramachandran, editor, *Encyclopedia of Human Behavior (Second Edition)*, second edition edition, pages 130–136. Academic Press, San Diego.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*.

Namgyu Ho, Laura Schmid, and Se-Young Yun. 2022. Large language models are reasoning teachers. *arXiv preprint arXiv:2212.10071*.

Keith J Holyoak. 2012. Analogy and relational reasoning. *The Oxford handbook of thinking and reasoning*, pages 234–259.

Tushar Khot, Harsh Trivedi, Matthew Finlayson, Yao Fu, Kyle Richardson, Peter Clark, and Ashish Sabharwal. 2022. Decomposed prompting: A modular approach for solving complex tasks. *arXiv preprint arXiv:2210.02406*.

Hyuhng Joon Kim, Hyunsoo Cho, Junyeob Kim, Taeuk Kim, Kang Min Yoo, and Sang-goo Lee. 2022. Self-generated in-context learning: Leveraging autoregressive language models as a demonstration generator. *arXiv preprint arXiv:2206.08082*.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. In *Thirty-sixth Conference on Neural Information Processing Systems (NeurIPS 2022)*.

Jannik Kossen, Yarin Gal, and Tom Rainforth. 2024. In-context learning learns label relationships but is not conventional learning. In *The Twelfth International Conference on Learning Representations*.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles*.

Yifei Li, Zeqi Lin, Shizhuo Zhang, Qiang Fu, Bei Chen, Jian-Guang Lou, and Weizhu Chen. 2022. On the advance of making language models better reasoners. *arXiv preprint arXiv:2206.02336*.

Jiachang Liu, Dinghan Shen, Yizhe Zhang, Bill Dolan, Lawrence Carin, and Weizhu Chen. 2022. What makes good in-context examples for GPT-3? In *Proceedings of Deep Learning Inside Out (DeeLIO 2022): The 3rd Workshop on Knowledge Extraction and Integration for Deep Learning Architectures*, pages 100–114, Dublin, Ireland and Online. Association for Computational Linguistics.

Pan Lu, Liang Qiu, Kai-Wei Chang, Ying Nian Wu, Song-Chun Zhu, Tanmay Rajpurohit, Peter Clark, and Ashwin Kalyan. 2022. Dynamic prompt learning via policy gradient for semi-structured mathematical reasoning. *arXiv preprint arXiv:2209.14610*.

Xinxi Lyu, Sewon Min, Iz Beltagy, Luke Zettlemoyer, and Hannaneh Hajishirzi. 2023. Z-ICL: Zero-shot in-context learning with pseudo-demonstrations. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2304–2317, Toronto, Canada. Association for Computational Linguistics.

Lucie Charlotte Magister, Jonathan Mallinson, Jakub Adamek, Eric Malmi, and Aliaksei Severyn. 2022. Teaching small language models to reason. *ArXiv preprint*, abs/2212.08410.

---

[2]experiments done between 12/2023 and 07/2024

Sewon Min, Xinxi Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2022. Rethinking the role of demonstrations: What makes in-context learning work? In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 11048–11064, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Jane Pan, Tianyu Gao, Howard Chen, and Danqi Chen. 2023. What in-context learning "learns" in-context: Disentangling task recognition and task learning. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 8298–8319, Toronto, Canada. Association for Computational Linguistics.

Chengwei Qin, Aston Zhang, Anirudh Dagar, and Wenming Ye. 2023. In-context learning with iterative demonstration selection. *arXiv preprint arXiv:2310.09881*.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3982–3992, Hong Kong, China. Association for Computational Linguistics.

Noah Shinn, Federico Cassano, Beck Labash, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning.

Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc V Le, Ed H Chi, Denny Zhou, et al. 2022. Challenging big-bench tasks and whether chain-of-thought can solve them. *arXiv preprint arXiv:2210.09261*.

Alon Talmor, Jonathan Herzig, Nicholas Lourie, and Jonathan Berant. 2019. CommonsenseQA: A question answering challenge targeting commonsense knowledge. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4149–4158, Minneapolis, Minnesota. Association for Computational Linguistics.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Stella Vosniadou and Andrew Ortony. 1989. *Similarity and analogical reasoning*. Cambridge University Press.

Boshi Wang, Sewon Min, Xiang Deng, Jiaming Shen, You Wu, Luke Zettlemoyer, and Huan Sun. 2023. Towards understanding chain-of-thought prompting: An empirical study of what matters. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2717–2739, Toronto, Canada. Association for Computational Linguistics.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, and Denny Zhou. 2022a. Rationale-augmented ensembles in language models. *arXiv preprint arXiv:2207.00747*.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, and Denny Zhou. 2022b. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Ed Chi, Quoc Le, and Denny Zhou. 2022. Chain of thought prompting elicits reasoning in large language models. In *Thirty-sixth Conference on Neural Information Processing Systems (NeurIPS 2022)*.

Jerry Wei, Jason Wei, Yi Tay, Dustin Tran, Albert Webson, Yifeng Lu, Xinyun Chen, Hanxiao Liu, Da Huang, Denny Zhou, et al. 2023. Larger language models do in-context learning differently. *arXiv preprint arXiv:2303.03846*.

Jinghan Yang, Shuming Ma, and Furu Wei. 2023. Auto-icl: In-context learning without human supervision. *arXiv preprint arXiv:2311.09263*.

Michihiro Yasunaga, Xinyun Chen, Yujia Li, Panupong Pasupat, Jure Leskovec, Percy Liang, Ed H. Chi, and Denny Zhou. 2024. Large language models as analogical reasoners. In *The Twelfth International Conference on Learning Representations*.

Kang Min Yoo, Junyeob Kim, Hyuhng Joon Kim, Hyunsoo Cho, Hwiyeol Jo, Sang-Woo Lee, Sang-goo Lee, and Taeuk Kim. 2022. Ground-truth labels matter: A deeper look into input-label demonstrations. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 2422–2437, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Eric Zelikman, Yuhuai Wu, and Noah D Goodman. 2022. Star: Bootstrapping reasoning with reasoning. *arXiv preprint arXiv:2203.14465*.

Zhuosheng Zhang, Aston Zhang, Mu Li, and Alex Smola. 2023. Automatic chain of thought prompting in large language models. In *The Eleventh International Conference on Learning Representations (ICLR 2023)*.

Ruochen Zhao, Xingxuan Li, Shafiq Joty, Chengwei Qin, and Lidong Bing. 2023. Verify-and-edit: A knowledge-enhanced chain-of-thought framework. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5823–5840, Toronto, Canada. Association for Computational Linguistics.

Denny Zhou, Nathanael Schärli, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Olivier Bousquet, Quoc Le, and Ed Chi. 2022. Least-to-most prompting enables complex reasoning in large language models. *arXiv preprint arXiv:2205.10625*.

A Appendix

A.1 Prompts for Different Methods

The prompts for different methods on all datasets are shown in Fig. 5 ~ Fig. 7.

A.2 Detailed Results for Different Random Seeds

We report detailed results for different random seeds in Table 13 ~ Table 14.

A.3 Decomposition of Relevance

The relevance can be further separated into semantic relevance and procedure (reasoning steps) relevance. Our analysis in Q1-1 has demonstrated that semantic relevance does not matter. To investigate the importance of procedure relevance, we perform a similar analysis. Specifically, we compute the average cosine similarity between the rationales of the generated examples and the rationale of the query to quantitatively measure their relevance. The results on GSM8K are reported in Table 15, which highlight that procedure relevance is not the key factor for analogical reasoning performance on mathematical reasoning tasks.

A.4 Prompts and Outputs for Example Generation

We show detailed prompts and outputs for randomly generating math and biological problems in Fig. 8 and Fig. 9, respectively.

A.5 Guided Problem Generation

In addition to random problem generation in §4.2-Q2-1, we further investigate guided problem generation. Specifically, we randomly select 5 training samples to guide LLMs to self-generate relevant math problems. We then manually verify their correctness and use this fixed set of problems as ICL demonstrations for experiments. The performance of this approach (56.1) is slightly lower than that of ICL_{math} (56.3), verifying that relevance is not the key influencing factor.

A.6 More Analysis on ICL_{math} and ICL_{bio}

Our designed method ICL_{math} generates *correct and relevant* examples, and ICL_{bio} generates *correct and irrelevant* examples. From the results in Table 8, we can see that ICL_{math} and ICL_{bio} achieve similar average performance, demonstrating that relevance does not matter.

We further change the correct answers of the demonstrations in ICL_{math} and ICL_{bio} to random answers, obtaining ICL_{math}^{wrong} and ICL_{bio}^{wrong}. Obviously, ICL_{math}^{wrong} generates *incorrect and relevant* examples, and ICL_{bio}^{wrong} generates *incorrect and irrelevant* examples. The comparison between these four methods in Table 16 further supports our claim that the key factor influencing the performance on mathematical reasoning is the accuracy of self-generated examples rather than their relevance.

A.7 Repeating Problems

While generating a few accurate problems as ICL demonstrations can achieve better performance, a bolder idea might be to generate one problem and repeat it multiple times as few-shot demonstrations for ICL. To investigate this, we randomly select a generated math problem and repeat it to perform ICL, denoted by ICL_{math_repeat}. From the results shown in Table 17, we can see that ICL_{math_repeat} consistently performs worse than ICL_{math} on both datasets, indicating that the diversity of generated problems also matters.

A.8 Generalization to Different Tasks

To test the generalizability of our findings beyond the math domain, we further conduct experiments on CommonsenseQA (commonsense reasoning) (Talmor et al., 2019). The comparison between different methods is shown in Table 18, which demonstrates that our findings can be generalized to different types of tasks.

Seed	GSM8K					MATH				
	Relevant	N/A	Random_{same}	Random_{diff}	Random_{bio}	Relevant	N/A	Random_{same}	Random_{diff}	Random_{bio}
42	71.8	**76.6**	73.2	74.0	74.0	37.4	**42.2**	41.6	39.0	39.2
100	71.2	75.2	75.2	**75.8**	74.8	29.0	30.6	**32.6**	29.4	31.2
1000	71.4	74.8	77.0	**79.2**	77.0	33.6	**35.6**	34.6	34.0	33.4
Average	$71.5_{\pm0.3}$	$75.5_{\pm0.8}$	$75.1_{\pm1.5}$	$\mathbf{76.3}_{\pm2.1}$	$75.3_{\pm1.2}$	$33.3_{\pm3.4}$	$36.1_{\pm4.7}$	$\mathbf{36.3}_{\pm3.8}$	$34.1_{\pm3.9}$	$34.6_{\pm3.3}$

Table 13: Accuracy (%) of all methods with different random seeds on two mathematical reasoning tasks.

Seed		Temporal sequences	Logical deduction five objects	Reasoning about colored objects	Formal fallacies	Word sorting	Average
42	Relevant	**58.0**	**52.8**	76.0	50.4	**77.2**	**62.9**
	N/A	56.4	44.8	**77.6**	**54.0**	76.8	61.9
	Random_{same}	52.4	48.8	74.8	51.6	72.8	60.1
	Random_{diff}	43.2	46.8	74.0	52.4	67.6	56.8
	Random_{bio}	56.8	52.0	74.0	52.0	76.4	62.2
100	Relevant	**58.4**	**50.8**	78.4	51.2	76.8	**63.1**
	N/A	55.2	46.0	74.8	52.8	**79.2**	61.6
	Random_{same}	50.8	48.4	73.6	**53.2**	75.2	60.2
	Random_{diff}	46.4	46.8	72.8	50.0	70.4	57.3
	Random_{bio}	58.0	48.4	**78.4**	51.2	73.6	61.9
1000	Relevant	**63.6**	**50.0**	75.6	52.0	76.8	**63.6**
	N/A	60.8	45.2	74.0	**53.2**	**77.2**	62.1
	Random_{same}	56.0	49.2	72.0	52.4	74.4	60.8
	Random_{diff}	43.2	40.8	70.4	51.2	69.6	55.0
	Random_{bio}	56.4	48.0	**76.0**	49.2	74.8	60.9
Average	Relevant	$\mathbf{60.0}_{\pm2.6}$	$\mathbf{51.2}_{\pm1.2}$	$\mathbf{76.7}_{\pm1.2}$	$51.2_{\pm0.7}$	$76.9_{\pm0.2}$	$\mathbf{63.2}_{\pm0.3}$
	N/A	$57.5_{\pm2.4}$	$45.3_{\pm0.5}$	$75.5_{\pm1.5}$	$\mathbf{53.3}_{\pm0.5}$	$\mathbf{77.7}_{\pm1.0}$	$61.9_{\pm0.2}$
	Random_{same}	$53.1_{\pm2.1}$	$48.8_{\pm0.3}$	$73.5_{\pm1.1}$	$52.4_{\pm0.6}$	$74.1_{\pm1.0}$	$60.4_{\pm0.3}$
	Random_{diff}	$44.3_{\pm1.5}$	$44.8_{\pm2.8}$	$72.4_{\pm1.5}$	$51.2_{\pm1.0}$	$69.2_{\pm1.2}$	$56.4_{\pm1.0}$
	Random_{bio}	$57.1_{\pm0.7}$	$49.5_{\pm1.8}$	$76.1_{\pm1.8}$	$50.8_{\pm1.2}$	$74.9_{\pm1.1}$	$61.7_{\pm0.6}$

Table 14: Accuracy (%) of all methods with different random seeds on BBH.

	Relevant	N/A	Random_{same}	Random_{diff}	Random_{bio}	Oracle
GSM8K	**0.50**	0.16	0.28	0.19	0.08	0.62

Table 15: Procedure (reasoning steps) relevance between self-generated examples and the query.

ICL_{math}	$\text{ICL}_{math}^{wrong}$	ICL_{bio}	ICL_{bio}^{wrong}
56.3	50.9	56.4	51.3

Table 16: Comparison between different ICL variants.

Method	Task		
	GSM8K	MATH	Average
ICL_{math}	**75.7**	**36.8**	**56.3**
ICL_{math_repeat}	73.8	36.2	55.0

Table 17: Comparison of two ICL variants on the GSM8K and MATH datasets.

Relevant	N/A	Random_{same}	Random_{diff}	Random_{bio}	ICL_{cs}	ICL_{bio}
70.8	73.4	71.2	72.9	72.6	**74.6**	74.1

Table 18: Accuracy (%) of different methods on CommonsenseQA. 'cs' in ICL_{cs} stands for 'commonsense'.

Prompt: self-generate relevant examples

Your task is to tackle mathematical problems. When presented with a math problem, recall **relevant** problems as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure that your response follows the instructions below.

Analogous Problems:
Offer five diverse examples of math problems that are **relevant or analogous** to the initial problem. For each problem, elaborate on the solution and conclude with the ultimate answer (enclosed in \boxed{}). For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate N/A examples

Your task is to tackle mathematical problems. When presented with a math problem, recall **n/a** problems as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure that your response follows the instructions below.

N/A Problems:
Offer five diverse examples of math problems that are **n/a** to the initial problem. For each problem, elaborate on the solution and conclude with the ultimate answer (enclosed in \boxed{}). For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate random math examples

Your task is to tackle mathematical problems. When presented with a math problem, recall **random** problems as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure that your response follows the instructions below.

Random Problems:
Randomly offer five diverse examples of math problems. For each problem, elaborate on the solution and conclude with the ultimate answer (enclosed in \boxed{}). For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate random no-math examples

Your task is to tackle mathematical problems. When presented with a math problem, recall **random problems (remember not to output math problems)** as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure that your response follows the instructions below.

Random Problems:
Randomly offer five diverse examples of **any type, except math** problems. For each problem, elaborate on the solution and conclude with the ultimate answer (enclosed in \boxed{}). For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate random biological examples

Your task is to tackle mathematical problems. When presented with a math problem, recall **random biological problems (remember not to output math problems)** as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure that your response follows the instructions below.

Random Problems:
Randomly offer five diverse examples of **biological problems (remember not to output math problems)**. For each problem, elaborate on the solution and conclude with the ultimate answer (enclosed in \boxed{}). For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Figure 5: Prompts for different methods on GSM8K.

Prompt: self-generate relevant examples

Your task is to tackle mathematical problems. When presented with a math problem, recall **relevant** problems as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure to include all of the following points:

Relevant Problems:
Recall three examples of math problems that are **relevant** to the initial problem. Note that your problems should be distinct from each other and from the initial problem (e.g., involving different numbers and names). For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Say "Let's solve the following math problem." Then formulate your response in the following format:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate N/A examples

Your task is to tackle mathematical problems. When presented with a math problem, recall **n/a** problems as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure to include all of the following points:

N/A Problems:
Recall three examples of math problems that are **n/a** to the initial problem. Note that your problems should be distinct from each other and from the initial problem (e.g., involving different numbers and names). For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Say "Let's solve the following math problem." Then formulate your response in the following format:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate random math examples

Your task is to tackle mathematical problems. When presented with a math problem, recall **random** problems as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure to include all of the following points:

Random Problems:
Randomly recall three examples of math problems. Note that your problems should be distinct from each other and from the initial problem (e.g., involving different numbers and names). For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Say "Let's solve the following math problem." Then formulate your response in the following format:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate random no-math examples

Your task is to tackle mathematical problems. When presented with a math problem, recall **random problems (remember not to output math problems)** as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure to include all of the following points:

Random Problems:
Randomly recall three examples of **any type, except math** problems. Note that your problems should be distinct from each other and from the initial problem. For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Say "Let's solve the following math problem." Then formulate your response in the following format:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate random biological examples

Your task is to tackle mathematical problems. When presented with a math problem, recall **random biological problems (remember not to output math problems)** as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure to include all of the following points:

Random Problems:
Randomly recall three examples of **biological problems (remember not to output math problems)**. Note that your problems should be distinct from each other and from the initial problem. For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Say "Let's solve the following math problem." Then formulate your response in the following format:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Figure 6: Prompts for different methods on MATH.

Prompt: self-generate relevant examples

Your task is to tackle reasoning problems. When presented with a problem, recall **relevant** problems as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure to include all of the following points:

Relevant Problems:
Recall three examples of problems that are **relevant** to the initial problem. Note that your problems must be distinct from each other and from the initial problem. For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Say "Let's solve the following reasoning problem." Then formulate your response in the following format:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate N/A examples

Your task is to tackle reasoning problems. When presented with a problem, recall **n/a** problems as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure to include all of the following points:

N/A Problems:
Recall three examples of problems that are **n/a** to the initial problem. Note that your problems must be distinct from each other and from the initial problem. For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Say "Let's solve the following reasoning problem." Then formulate your response in the following format:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate random reasoning examples

Your task is to tackle reasoning problems. When presented with a problem, recall **random** problems as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure to include all of the following points:

Random Problems:
Randomly recall three examples of reasoning problems. Note that your problems must be distinct from each other and from the initial problem. For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Say "Let's solve the following reasoning problem." Then formulate your response in the following format:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate random no-reasoning examples

Your task is to tackle reasoning problems. When presented with a problem, recall **random problems (remember not to output reasoning problems)** as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure to include all of the following points:

Random Problems:
Randomly recall three examples of **any type, except reasoning** problems. Note that your problems must be distinct from each other and from the initial problem. For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Say "Let's solve the following reasoning problem." Then formulate your response in the following format:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Prompt: self-generate random biological examples

Your task is to tackle reasoning problems. When presented with a problem, recall **random biological problems (remember not to output reasoning problems)** as examples. Afterward, proceed to solve the initial problem.

Initial Problem:
[*The target problem*]

Instructions:
Make sure to include all of the following points:

Random Problems:
Randomly recall three examples of **biological problems (remember not to output reasoning problems)**. Note that your problems must be distinct from each other and from the initial problem. For each problem:
- After "Q: ", describe the problem
- After "A: ", explain the solution and enclose the ultimate answer in \boxed{}.

Solve the Initial Problem:
Say "Let's solve the following reasoning problem." Then formulate your response in the following format:
Q: Copy and paste the initial problem here.
A: Explain the solution and enclose the ultimate answer in \boxed{} here.

Figure 7: Prompts for different methods on BBH.

Figure 8: Prompts and outputs for generating math problems.

Figure 9: Prompts and outputs for generating biological problems.