Graph Neural Networks Designed for Different Graph Types: A Survey

Abstract

Graphs are ubiquitous in nature and can therefore serve as models for many practical but also theoretical problems. For this purpose, they can be defined as many different types which suitably reflect the individual contexts of the represented problem. To address cutting-edge problems based on graph data, the research field of Graph Neural Networks (GNNs) has emerged. Despite the field's youth and the speed at which new models are developed, many recent surveys have been published to keep track of them. Nevertheless, it has not yet been gathered which GNN can process what kind of graph types. In this survey, we give a detailed overview of already existing GNNs and, unlike previous surveys, categorize them according to their ability to handle different graph types and properties. We consider GNNs operating on static and dynamic graphs of different structural constitutions, with or without node or edge attributes. Moreover, we distinguish between GNN models for discrete-time or continuous-time dynamic graphs and group the models according to their architecture. We find that there are still graph types that are not or only rarely covered by existing GNN models. We point out where models are missing and give potential reasons for their absence.

1 Introduction

Over the last decades, neural networks (NNs) have become increasingly important. Their development dates back to the early 1940s (Anderson & Rosenfeld, 1988) [1]. With increasing computational power and the possibility of utilizing Deep Learning (DL), their applications have reached most parts of society, from detecting cancer (McKinney et al., 2020) to playing computer games (Ibarz et al., 2018; Silver et al., 2018). Nevertheless, classical NNs are limited to Euclidean data. Given the rising amount of non-Euclidean data (Bronstein et al., 2017) and the fact that graphs are a suitable mathematical representation for many theoretical and practical problems, several authors started investigating NNs on particular graph problems (Cimikowski & Shope, 1996; Lai et al., 1994) or so-called "structures" (Sperduti, 1997; Sperduti & Starita, 1997) in the 90s. With an ever-increasing amount of graph data available (see, e.g., repositories Rossi & Ahmed (2015), or OGB Hu et al. (2020)) in many applications (e.g., traffic (Ma et al., 2020; Rossi & Ahmed, 2015), citation (Feng et al., 2019; Ioannidis et al., 2019; Ren et al., 2021; Tran & Tran, 2020), biological or medical (La Gatta et al., 2020; Wang et al., 2020; Yadati et al., 2019; Zitnik et al., 2018), social (Pareja et al., 2020; Rossi et al., 2020; Trivedi et al., 2019), recommendation (Sankar et al., 2020; Wang et al., 2021; Yang et al., 2020)), so-called Graph Neural Networks (GNNs) have become a thriving research field.

Therefore, many surveys have recently conducted intensive research on GNN models, e.g., Barros et al. (2021); Kazemi et al. (2020); Skarding et al. (2021); Zhou et al. (2020). However, most GNN models are either limited to a specific graph type or developed to address particular problems. E.g., Hier-GNN Chen et al. (2022) is developed especially for hierarchical graphs, MXMNet Zhang et al. (2020a) for multiplex graphs, and EpiGNN La Gatta et al. (2020) focuses on learning the evolution of an epidemic. On the other hand, real-world graphs are diverse. In many cases, they contain heterogeneous nodes or edges and evolve dynamically. One example of a heterogeneous graph is a power grid representation in which the nodes could have different types, such as "solar power plants", "wind parks", or "nuclear power plants". An example of a

---

[1] Anderson & Rosenfeld (1988) provides a historical overview up to the end of the 1980s.

dynamic graph is a social network with time-changing nodes and the connections among them. However, no comprehensive overview is available that investigates which graph types are addressed by existing GNN models. Since the graph type plays a vital role in choosing a model to solve a graph problem, it is essential to provide an overview of the latest collection of GNNs.

This survey aims to fill this gap by providing an outline of GNNs for all graph types and pointing out the absent GNN models for static and dynamic graphs. As a comprehensive overview of the different graph types is missing, the first contribution of this survey consists of the definition and overview of these. It covers basic structural graph types (e.g., directed, multi-, heterogeneous, or hypergraphs) for static and dynamic graphs in discrete and continuous-time and the so-called semantic graph types (e.g., cyclic, regular, and bipartite graphs). This categorization approach is advantageous because some GNN models are restricted to specific graph properties. The second contribution is an analysis of which graph types can be handled by currently available GNN models. As a third contribution, we group the investigated GNN models by their architecture in the main part.([S-4] wySu) The final contribution consists in analyzing what graph types cannot be handled by current GNN models, including explanations for these gaps.

Due to the vast amount of publications in the field, this survey cannot cover all existing models. Therefore, this survey aims to cover the most important models and list only one or two models for each graph type or property to illustrate the existence of at least one model. The following criteria determine the importance of the models for the choice: 1) Up-to-dateness of the model, 2) relevance of the model concerning the number of citations and its use as a baseline in other publications, 3) the generality of the model (e.g., that it is not only applicable to a particular domain), 4) explicitness in addressing the listed graph properties, and 5) simplicity of the model (e.g., if two models fulfill the same task, priority is given to the simpler one).

This paper is structured as follows. Sec. 2 contains related work. In Sec. 3, the considered graphs and their properties are defined in 3.1, while preliminary definitions concerning GNNs are given in 3.2. Sections 4 to 7 constitute the central part of the paper and deal with GNN models focusing on structural graph properties (Sec. 4), dynamic graph properties (Sec. 5), semantic graph properties (Sec. 6) and combined or other GNN models (Sec. 7). Here, each section contains a table showing which graph types and properties are addressed by existing GNN models, a description of the applied GNN techniques, and an evaluation of why current models might not cover specific properties. Note that many models have the same acronym in the respective publication. Therefore we altered some of them to distinguish the models and improve readability. Finally, Sec. 8 concludes the work and points out future challenges.

2 Related Work

Several surveys that review GNNs concerning different aspects have been proposed over the last few years. Multiple surveys provide a more detailed overview of specific types of methods, such as convolutional GNNs (Gama et al., 2020; Zhang et al., 2018; 2019b), GNNs using attention mechanisms (Lee et al., 2019), or Baysian GNNs (Shi et al., 2021). Furthermore, many existing surveys focus on specific application areas (Jiang & Luo, 2022; Shlomi et al., 2020; Wu et al., 2022), such as natural language processing (Wu et al., 2021), combinatorial optimization (Peng et al., 2021), or power systems (Liao et al., 2021). Other publications reviewing GNN models concentrate on specific aspects such as explainability (Yuan et al., 2021), or the expressive power of GNNs (Sato, 2020). Unlike these publications, we provide a more general survey, which is neither limited to particular types of methods or aspects nor explicit application fields.

Cai et al. (2018) provide a broad survey of graph embedding techniques, including methods apart from deep learning, such as matrix factorization or graph kernels, similar to (Cui et al., 2018; Goyal & Ferrara, 2018; Hamilton et al., 2017). In Bronstein et al. (2017), an overview of deep learning methods applicable to non-Euclidian data is provided. The survey does not only focus on graphs but aims to cover methods of geometric deep learning in general, including its applications, challenges, and future directions. Concerning GNNs, it primarily surveys convolutional methods. However, the aforementioned surveys do not cover methods for dynamic graphs. In contrast, (Wu et al., 2020) covers spatial-temporal GNNs, convolutional methods, recurrent GNNs, and graph autoencoders. The investigated methods are grouped according to these categories. Similarly, (Zhang et al., 2020b) review models by the type of GNN they apply. However, these categories differ from thosse in Wu et al. (2020) such that instead of spatial-temporal GNNs, graph

reinforcement learning and adversarial methods are discussed. Both methods only partially cover dynamic graph models.

Further publications such as Barros et al. (2021); Kazemi et al. (2020); Skarding et al. (2021) explicitly focus on models for dynamic graphs. Skarding et al. (2021) further group the reviewed models concerning the encoded type of dynamics (e.g., node dynamic, edge-growing) and the applied methods. While Barros et al. (2021) and Skarding et al. (2021) survey models for dynamic graphs only, Kazemi et al. (2020) also reviews several static methods. However, the corresponding chapter of this survey aims to understand better the basic concepts for static graphs, which can be extended to dynamic graphs, rather than reviewing methods for static graphs. None of the abovementioned surveys categorizes the reviewed methods for different graph types and their semantic properties. The only survey that explicitly investigates GNN models concerning the graph types is Zhou et al. (2020). However, it does not consider all graph types covered in this survey since we provide a more fine-grained distinction of different graph properties. Moreover, in Zhou et al. (2020) the authors focus on the pipeline of designing a GNN, including identifying the graph type and additional network modules such as pooling or sampling. Accordingly, it takes a different point of view and reviews GNN models amongst other modules, which can be integrated into a deep learning pipeline.

Our contribution is a detailed overview of existing GNNs and their categorization into certain types of methods, but more importantly, the types of graphs they can process. Unlike many existing surveys, we consider static and dynamic graphs. Moreover, we group the corresponding dynamic GNNs into discrete-time and continuous-time dynamic models while considering the node and edge attributes and the graph's structure (R-5).

3 Foundations

The application of graphs takes place in many different fields. The reason for this is the high degree of freedom in designing a graph and, thus, in representing information. Therefore, many different graph types have been developed and extended over time. To give the reader a comprehensive insight into all graph types and associated GNNs, this section defines graph types and properties in detail and presents them in order. Readers familiar with the different graph types and properties may omit this section and go on to the following section, Sec. 4, for an overview of existing GNN models and architectures.

For the remainder of this section, it is assumed that the reader has basic knowledge of analysis and linear algebra (see, for example, Abbott (2001); Strang (1993)). A table containing the most frequently used notation can be found in Sec. 9.

3.1 Graphs And Their Properties

At first, the considered graph properties and graph types have to be defined to survey for which graph types and properties GNN models exist. These definitions are given here, as well as some graph-related terms which are needed throughout the paper. All definitions concerning structural properties are taken from Thomas et al. (2021) and given here for the reader's comfort. In addition, we give definitions of several semantic graph properties which do not affect the graph's structure but result from its interpretation. Some GNNs specialize in such properties since they frequently occur in real-world applications.(2. BMQA)

In the following, elementary graph types are defined. They form the basis for all graphs to which neural networks have already been applied or might be applied in the future.

Definition 3.1 (Static Graphs: Elementary)
1. A **directed (simple) graph** is a tuple $G = (\mathcal{V}, \mathcal{E})$ containing a set of nodes $\mathcal{V} \subset \mathbb{N}$ and a set of directed edges given as tuples $\mathcal{E} \subseteq \mathcal{V} \times \mathcal{V}$.
2. A **(generalized) directed hypergraph** is a tuple $G = (\mathcal{V}, \mathcal{E})$ with nodes $\mathcal{V} \subset \mathbb{N}$ and hyperedges

$$\mathcal{E} \subseteq \{(\mathsf{x}, f_i)_i \mid \mathsf{x} \subseteq \mathcal{V}, \, f_i : \mathsf{x} \to \mathbb{N}_0\}$$

that include a numbering map f_i for the i-th edge $(\mathsf{x}, f)_i$ which indicates the order of the nodes in the (generalized) directed hyperedge. W.l.o.g. it can be assumed that the numbering is gap-free, so if there exists a node $u \in \mathsf{x}$ with $f(u) = k > 1$ then there will also exist a node v s.t. $f(v) = k - 1$.

These graphs are called elementary because every other graph is a composition of them. In this sense, a **directed hypergraph** is a directed simple graph (R-2 wySu) that simultaneously is a hypergraph. Since one can not only combine elementary graphs but also extend them with additional properties, in what follows, different types of graph properties are introduced. Namely the static structural, dynamic structural, and semantic properties. ~~and advanced topological graph properties,~~(R-5 wySu)

Definition 3.2 (Static Structural Graph Properties)
An elementary graph $G = (\mathcal{V}, \mathcal{E})$ is called

1. **undirected** if the edge directions are irrelevant, i.e.,
   - for directed graphs: if $(u, v) \in \mathcal{E}$ whenever $(v, u) \in \mathcal{E}$ for $u, v \in \mathcal{V}$. Then, the edges can be denoted as a set of sets instead of a set of tuples, namely
   $$\mathcal{E} \subseteq \{\{u, v\} \mid u, v \in \mathcal{V}, u \neq v\} \cup \{\{u\} \mid u \in \mathcal{V}\}^2,$$
   - for directed hypergraphs: if $f_i : \mathsf{x} \to 0$ for all $(\mathsf{x}, f_i)_i \in \mathcal{E}^3$. Abbreviated by $\mathcal{E} \subseteq \{\mathsf{x} \mid \mathsf{x} \subseteq \mathcal{V}\}$.

   In what follows $\mathcal{G}_u$ is the set of all undirected graphs.
2. **multigraph** if it is a multi-edge graph, i.e., the edges $\mathcal{E}$ are defined as a multiset[4], a multi-node graph, i.e., the node set $\mathcal{V}$ is a multiset, or both. All multigraphs are written as the set $\mathcal{G}_m$.
3. **heterogeneous** if the nodes or edges can have different types (node- or edge-heterogeneous). Mathematically, the type is appended to the nodes and edges. I.e., the node set is determined by $\mathcal{V} \subseteq \mathbb{N} \times \mathcal{S}$ with a node type set $\mathcal{S}$ and thus, a node $(v, s) \in \mathcal{V}$ is given by the node v itself and its type s. The edges can be extended by a set $\mathcal{R}$ that describes their types, to $(e, r) \; \forall \, e \in \mathcal{E}$ of edge type $r \in \mathcal{R}$.
4. **attributed** if the nodes $\mathcal{V}$ or edges $\mathcal{E}$ are equipped with node- or edge attributes. These attributes are formally given by a node attribute function and an edge attribute function, respectively, i.e. $\alpha : \mathcal{V} \to \mathcal{A}$ and $\omega : \mathcal{E} \to \mathcal{W}$, where $\mathcal{A}$ and $\mathcal{W}$ are arbitrary attribute sets. In case there are only node attributes the graph is called **node-attributed** (or node labeled/node features), in case of just edge attributes it is called **edge-attributed** and if we have $\mathcal{W} \subseteq \mathbb{R}$ it is called **weighted**. The set of all attributed graphs is denoted as $\mathcal{G}_a$.

Fig. 1 shows examples for each graph type up to this point.

Figure 1: Visualization of different elementary static graph types.

---

[2]the second set contains the set of self-loops
[3]$f_i(\mathsf{x}) = 0$ encodes that x is an undirected hyperedge
[4]A multiset is a set that can have entries which occur multiple times.

The term **static** in these structural properties stands for the absence of temporal dependence. This means, in particular, that once the graph is given, it never changes with time. In contrast, the so-called (temporal) dynamic structural graph properties are listed in the following.

Definition 3.3 (Dynamic Structural Graph Properties)
A graph is called

1. **dynamic** if the graph structure or the graph properties are time dependent. In the following, the notion
   $G_i = (\mathcal{V}_i, \mathcal{E}_i)$, $t_i \in T$ is used, where T is a set of timestamps to emphasize the time-dependence and therefore the dynamics.
2. **growing** if it is dynamic and the node or edge sets evolve w.r.t. addition of new nodes and edges respectively. I.e., for all $t_i \in T$ it holds

$$\mathcal{V}_i \subseteq \mathcal{V}_{i+1} \quad \text{or} \quad \mathcal{E}_i \subseteq \mathcal{E}_{i+1}.$$

3. **shrinking** if it is dynamic and we just allow node or edge set evolution w.r.t. deletions of nodes and edges respectively. I.e., for all $t_i \in T$, it is

$$\mathcal{V}_i \supseteq \mathcal{V}_{i+1} \quad \text{or} \quad \mathcal{E}_i \supseteq \mathcal{E}_{i+1}.$$

4. **strictly growing/shrinking** if we consider only real inclusions in definition 2 and 3 above.
5. **structure-dynamic** if it is growing, shrinking or both simultaneously, i.e., in particular, the nodes $\mathcal{V}$ or edges $\mathcal{E}$ evolve over time due to additions or deletions of nodes or edges[5].
6. **attribute-dynamic** if the node or edge attribute function is time-dependent. Thus, we extend our notions of the attribute functions to $\alpha_i : \mathcal{V}_i \to \mathcal{A}$ and $\omega_i : \mathcal{E}_i \to \mathcal{W}$, for all $t_i \in T$.
7. **type-dynamic** if the graph type evolves over time. E.g., an undirected graph becomes directed from one to another time step.

Structurally, these dynamics describe different temporal behaviors of graphs. When processing dynamic graphs, they are typically defined either as discrete-time or continuous-time representations.

Definition 3.4 (Dynamic Graph Representation)
1. A dynamic graph in **discrete-time representation** is given by a set $\mathcal{G} = \{g_1, \ldots, g_k\}$ of graph snapshots g_i at time steps $i = 1, \ldots, k$. Here, $g_i := (\mathcal{V}_i, \mathcal{E}_i)$ are static graphs with nodes $\mathcal{V}$ and edges $\mathcal{E}_i \subseteq \{(u, v) \mid u, v \in \mathcal{V}_i\}$.
2. A dynamic graph in **continuous-time representation** is defined by a set $G = \{g_{t_0}, \mathbb{E}\}$ containing an initial static graph at time stamp $t_0 \in \mathcal{T}$ and a set $\mathbb{E} = \{e_t, t \in \mathcal{T}\}$ of events encoding a structural or attribute change at time stamp $t > t_0 \in \mathcal{T}$.

Not all combined graphs are equally important in the literature and especially for GNNs. The following introduces some combined graph types of specific interest with proper names.

Definition 3.5 (Combined Static Graphs)
1. **Knowledge graphs** are defined in several ways. In Wang et al. (2021), they are defined as heterogeneous directed graphs, while in Yu et al. (2020) knowledge graphs are the same as edge-heterogeneous graphs. But there are also definitions that do not see a knowledge graph as a graph combined from the aforementioned types, see for example Ehrlinger & Wöß (2016) for an overview.
2. A **multi-relational graph** (Hamilton, 2020) is an edge-heterogeneous but node-homogeneous graph.
3. A **content-associated heterogeneous graph** is a heterogeneous graph with node attributes that correspond to heterogeneous data like, e.g., attributes, text or images (Zhang et al., 2019a).
4. A **multiplex graph/multi-channel graph** corresponds to an edge-heterogeneous graph with self-loops (Hamilton, 2020). Here, we have k layers, where each layer consists of the same node set $\mathcal{V}$, but different edge sets $\mathcal{E}^{(k)}$. Additionally, inter-layer edges $\tilde{\mathcal{E}}$ exist between the same nodes across different layers.

---

[5](Kazemi et al., 2020) also mentions splits and merges of nodes and edges. Obviously, these events are sequences of additions and deletions.

5. A **spatio-temporal graph** is a multiplex graph where edges per each layer are interpreted as spatial edges and the inter-layer edges indicate temporal steps between a layer at time step t and $t + 1$. They are called temporal edges (Kapoor et al., 2020).

Remark. All the combined properties mentioned in Def. 3.5 can occur in dynamic graphs as well. (minor 2. 4uat.)

Besides the structural properties, a graph can have semantic properties that do not explicitly change its structure but result from applying or interpreting the graph information. Some GNNs are limited or specialized to these properties defined in the following.

Definition 3.6 (Semantic Graph Properties)
An elementary graph $G = (\mathcal{V}, \mathcal{E})$ is called

1. **complete** if all pairwise different nodes are connected through an edge, i.e., $\mathcal{E} = \{(u, v) \in \mathcal{V} \times \mathcal{V} \mid u \neq v\}$.
2. r-**regular** if each node $v \in \mathcal{V}$ has $r \in \mathbb{N}$ neighbors, i.e.,

$$|\mathcal{N}(v)| := |\{u \in \mathcal{V} \mid (u, v) \in \mathcal{E}\}| = r.$$

3. **bipartite** if there exists a disjoint node decomposition into two sets $\mathcal{V} = \mathcal{U} \uplus \mathcal{W}$, such that the edges are of the form $\mathcal{E} \subseteq \mathcal{U} \times \mathcal{W}$.
4. **connected** if the graph is undirected and for all node pairs $v, w \in \mathcal{V}$ there is a path from v to w in G. An elementary graph is called **weakly connected** if the underlying undirected graph is connected and it is **strongly connected** if for all node pairs $v, w \in \mathcal{V}$ there is a directed path from v to w in G. Otherwise it is unconnected.
5. **cyclic** if it contains a cycle of length $k \in \mathbb{N}$, i.e., there exists a subgraph $H = (\{v_1, \ldots, v_k\}, \{e_1, \ldots, e_k\}) \subseteq G$, $v_i \in \mathcal{V}$, $e_i \in \mathcal{E}$ $\forall i$, such that the series of nodes and edges $v_1, e_1, v_2, \ldots, v_k, e_k, v_1$ is a closed (directed) path called **(directed) cycle** of length k with $v_i \neq v_j$ $\forall i, j$. Otherwise, it is called **acyclic** or a **forest**.
6. **tree** if it is a connected forest. In case each node in the tree has at most two neighbors, it is called **binary tree** (Gessel & Stanley, 1995). A **polytree** is a directed graph whose underlying undirected graph is a tree (Dasgupta, 1999).
7. ~~**recursive**, if an edge e can include nodes as well as edges, i.e., $e \subseteq \mathcal{V} \cup \mathcal{E}$(Yadati, 2020).~~(R6 wySu)
8. **level-$(l+1)$ hierarchical** w.r.t. a level-l base graph $H = (\tilde{\mathcal{V}}, \tilde{\mathcal{E}})$ if one can find a complete partitioning of H into $k \geq 1$ non-empty, connected sets of nodes $\tilde{\mathcal{V}}_1, .., \tilde{\mathcal{V}}_k$. Such that each set of nodes $\tilde{\mathcal{V}}_i \subseteq \tilde{\mathcal{V}}$ induces a subgraph $sub_i(H) = (\tilde{\mathcal{V}}_i, \tilde{\mathcal{E}}_i \subseteq \tilde{\mathcal{E}})$ with $\tilde{\mathcal{E}}_i = \{(v_1, v_2) \in \tilde{\mathcal{E}} \mid v_1, v_2 \in \tilde{\mathcal{V}}_i\}$. Each of these subgraphs, in turn, corresponds to a node in the hierarchical graph G. Edges in G correspond to edges in H between nodes v_i, v_j of two different subgraphs $sub_i(H), sub_j(H)$ (Stoffel et al., 2008).
9. **scale-free**, if its node degree distribution $P(d)$ follows a power law $P(d) \sim d^{-\gamma}$, where γ typically lies within the range $2 < \gamma < 3$.
10. ~~**hyperbolic**, if its hidden underlying space is hyperbolic. This is the case, if G has a tree-like structure, is scale-free and has a high clustering coefficient (Krioukov et al., 2010)~~(R6 wySu)

A (generalized) (directed) hypergraph $G = (\mathcal{V}, \mathcal{E})$ is called

9. **recursive**, if an edge can not only exist between nodes, but also between edges and in a recursive way. E.g. two edges e_1 and e_2 make up edge e_{12}, edges e_3 and e_4 make up edge e_{34} and edge e_5 consists of edges e_{12} and e_{34}. See definition 4 of an ubergraph in Joslyn & Nowak (2017) and figure 1a in Yadati (2020) for a visualization.(R6 wySu)

Fig. 2 shows examples for each semantic graph property by applying it to undirected graphs.

Figure 2: Semantic graph properties illustrated for undirected graphs.

In the following chapter, we introduce the basic architectures for GNNs that make up all the GNNs in this survey. In order to be able to describe these appropriately, we list some frequently occurring graph-related terms beforehand.

Definition 3.7 (Graph related terms)
Let $G \coloneqq (\mathcal{V}, \mathcal{E})$ be a graph.

1. The **degree of a node** $v \in \mathcal{V}$ is given by $\delta(v) = |\{e \in \mathcal{E} \mid v \in e\}|$. For directed graphs, the **out- or in-degree(R11)** of v is the number of edges starting in v or ending in v, respectively. The **degree of an edge** $e \in \mathcal{E}$ is determined by $|e|$, i.e., by the number of nodes contained in the edge.

2. The **graph Laplacian** or **Laplacian matrix** $\boldsymbol{L}$ is defined by $\boldsymbol{L} = \boldsymbol{D} - \boldsymbol{A}$, where $\boldsymbol{D}$ is the degree matrix and $\boldsymbol{A}$ the adjacency matrix. In Graph Convolutional Neural Networks, it is mostly used in a normalized version, e.g., the symmetric and normalized graph Laplacian $\boldsymbol{L}_{norm} = \tilde{\boldsymbol{D}}^{-\frac{1}{2}} \tilde{\boldsymbol{A}} \tilde{\boldsymbol{D}}^{-\frac{1}{2}}$, where $\tilde{\boldsymbol{A}}$ the adjacency matrix with self connections and $\tilde{\boldsymbol{D}}$ the degree matrix with self-loops.

3. An entry $y_{i,j}$ of the **incidence matrix** $\boldsymbol{Y} \in \{0,1\}^{|\mathcal{V}| \times |\mathcal{E}|}$ of a graph $G = (\mathcal{V}, \mathcal{E})$ is 1, if the node i is incident to edge j, and 0 otherwise. For non-hypergraphs, the incidence matrix has exactly 2 entries per row that are non-zero.

4. Let $\tilde{\mathcal{V}} \subseteq \mathcal{V}$ be a set of nodes. Then, the **induced subgraph of** $\tilde{\mathcal{V}}$ is defined by a graph $G(\tilde{\mathcal{V}}) = (\tilde{\mathcal{V}}, \tilde{\mathcal{E}})$ with edges $\tilde{\mathcal{E}} = \{e \in \mathcal{E} \mid e \in \tilde{\mathcal{V}} \times \tilde{\mathcal{V}}\}$ between the nodes of $\tilde{\mathcal{V}}$.(R9)

5. A **path** from $u \in \mathcal{V}$ to $v \in \mathcal{V}$, denoted by $p(u,v) \coloneqq e_1, \ldots, e_k \in \mathcal{E}$ is a sequence of edges, for which there is a sequence of nodes $(z_1, ..., z_{k+1})$ such that $e_i = (z_i, z_{i+1})$ for $i = 2, ..., k$ and $e_1 = (u, x)$ and $e_{k+1} = (y, v)$ for some $x, y \in \mathcal{V}$.

6. The **path length** of a path $p(u,v) = e_1, \ldots e_k$ denotes the sequence length, i.e., $\operatorname{len}(p(u,v)) = k$. (minor 2. BMQA)

7. A **random walk of length** k is a path of length k whose edges are selected iteratively and randomly. (wySu R9, minor 2. BMQA)

8. ~~A **metapath** on a heterogeneous graph describes a relation between two node types in the form of an ordered sequence of node and edge relation types between them.~~ (R10 wySu)

3.2 GNN Preliminaries

GNNs define the adaptation of traditional NNs to graph data and aim to learn high-level representations of graphs in an end-to-end fashion by applying several network layers. They can be applied to all classical machine learning problems, such as classification, regression, or clustering, for entire graphs and subgraphs at a node or edge level. Each layer computes a new representation of the graph or its components. A typical procedure is to update the representation for the nodes in each layer by propagating information through the graph. A task-specific prediction can then be made using the learned representation and a suitable decoder function. For node classification, e.g., a typical choice for the decoder is a standard MLP with a softmax activation as the output function. It maps the learned representation to a vector indicating the class probabilities for all nodes. At the edge level, a frequently considered task is link prediction which aims to predict the probability of the existence of an edge. The corresponding decoder is often implemented as a logistic regression classifier since the existence of an edge can be expressed as a two-class problem.

Different types of GNNs specify the computation of the node representation in the GNN layers. According to Bronstein et al. (2021), the following relation of GNN approaches applies:

$$\text{message-passing} \supseteq \text{attention} \supseteq \text{convolution}$$

Therefore, these are introduced one after the other, from the most general case to special ones. A visualization of the three GNN layer types is shown in figure 3. The Recurrent Neural Networks coexist with the message-passing and will be introduced afterward. Combined with GNNs, it is particularly relevant for dynamic graph learning problems due to its ability to model temporal data.

Figure 3: Visualization of the information propagation process in the different types of GNN layers for node u and its neighbors. The idea for the figure is taken from Bronstein et al. (2021, Fig. 17). *Left:* In convolutional layers, the node features x_v of the neighbors $v \in \{1, \ldots, 3\}$ of node u are multiplied with a constant $c_{u,v}$ to form the message. *Middle:* In attention layers, this multiplier is computed via an attention mechanism $att_{uv} = att(x_u, x_v)$ between the source and the target nodes u, v. *Right:* In message-passing layers, the messages m_{uv} are computed explicitly from the source and target node representations, i.e., $m_{uv} = \psi(x_u, x_v)$. (minor 2. BMQA)

3.2.1 Message-Passing

Message-passing determines which and how much information is forwarded between two nodes, e.g., via their connecting edges. The resulting representation $\boldsymbol{h}_u$ of node u is computed from the node representations $\boldsymbol{x}_v \ \forall v \in \mathcal{V}$:

$$\boldsymbol{h}_u = \phi\left(\boldsymbol{x}_u, \bigoplus_{v \in \mathcal{N}(u)} \psi(\boldsymbol{x}_u, \boldsymbol{x}_v)\right), \tag{1}$$

where ψ is a learnable message function that assigns an information vector to the pair u, v. Typically, ψ is defined as multiplication with a learnable weight matrix, and its output is denoted as a message. The aggregation $\oplus$ depicts the message-passing process on the graph, which in most cases is implemented as a non-parametric operation such as sum, mean, or maximum. $\mathcal{N}(u)$ denotes a neighborhood of node u and ϕ is an activation function (Bronstein et al., 2021).

3.2.2 (Multi-head) Graph Attention

Graph attention is a special case of message-passing (Bronstein et al., 2021). Here, the message is computed by applying a learnable function ψ to each neighboring node weighted by a so-called *attention* factor. Typically, the function ψ is shared across all neighbors, whereas the attention is computed individually for each node pair. The attention mechanism specifies the message-passing rule in the aggregation function as follows:

$$\boldsymbol{h}_u = \phi\left(\boldsymbol{x}_u, \bigoplus_{v \in \mathcal{N}(u)} att(\boldsymbol{x}_u, \boldsymbol{x}_v)\psi(\boldsymbol{x}_v)\right), \tag{2}$$

where the attention function att is learnable and determines the effect of the message from neighbor v with representation $\psi(\boldsymbol{x}_v)$ to the hidden representation $\boldsymbol{h}_u$ of node u. Additionally, the attention coefficients are normalized across all neighbors of the target node. Note that att_k, therefore, depends not only on x_u and x_v but also on all other neighbors of node x_u.(R12) Furthermore, if $\oplus$ is a sum, the aggregation is a linear combination considering feature-specific weights for the neighbors.

Multi-head attention extends the attention mechanism to K different attention functions (Velickovic et al., 2018) and is determined by

$$\boldsymbol{h}_u = \underset{k \in [K]}{\|} \phi\left(\boldsymbol{x}_u, \bigoplus_{v \in \mathcal{N}(u)} \mathrm{att}_k(\boldsymbol{x}_u, \boldsymbol{x}_v)\psi(\boldsymbol{x}_v)\right), \tag{3}$$

where $\|$ denotes the concatenation operation. The K different attention functions also called *attention heads* are computed independently. In Velickovic et al. (2018), an implementation of an attention mechanism is proposed. The according self-attention function $\mathrm{att} : \mathbb{R}^{\dim(\boldsymbol{h})} \times \mathbb{R}^{\dim(\boldsymbol{h})} \longrightarrow \mathbb{R}$ outputs an attention weight. (minor 2. BMQA)

$$\omega_{i,j} \coloneqq \mathrm{att}(\boldsymbol{W}\boldsymbol{h}_i, \boldsymbol{W}\boldsymbol{h}_j)$$

for an edge (i,j) given the incident node embeddings $\boldsymbol{h}_i, \boldsymbol{h}_j$ to indicate the importance of the features of node j to node i for all node pairs $i, j \in \mathcal{V}$. Considering the neighborhoods given in the graph, the attention mechanism can be defined by

$$a_{i,j} \coloneqq \mathrm{softmax}_j(\omega_{i,j}) = \frac{\exp \omega_{i,j}}{\sum_{k \in \mathcal{N}(i)} \exp \omega_{i,k}}.$$

3.2.3 Spatial and Spectral Graph Convolutions

Compared to the attention approach, the graph convolution aggregates the neighbored nodes directly using fixed weights (Bronstein et al., 2021) by

$$\boldsymbol{h}_u = \phi\left(\boldsymbol{x}_u, \bigoplus_{v \in \mathcal{N}(u)} c_{u,v}\psi(\boldsymbol{x}_v)\right), \tag{4}$$

where $c_{u,v}$ is a factor indicating the impact of neighbor v on the hidden representation of node u. Note that $c_{u,v}$ is a pre-defined constant instead of a node-specific function, as is the case for attention layers. For spatial convolution, $c_{u,v}$ is usually given by the (weighted) adjacency matrix and thus includes structural information. For spectral convolution, spectral filters dependent on the graph Laplacian (c.f. 3.7.2) determine the weights of all nodes in the graph integrating structural information implicitly.

If the aggregation is a sum, the layer can be interpreted as linear diffusion or position-dependent linear filtering. An example of a spatial convolution in layer $l - 1$ is given in, e.g., Morris et al. (2019): (minor 2. BMQA)

$$h_u^{(l+1)} = \sigma\left(W_1 h_u + W_2 \sum_{v \in \mathcal{N}(u)} h_v^{(l)}\right). \tag{5}$$

W_1 and W_2 are learnable weight matrices and σ is an activation function such as $\mathrm{ReLU}(\cdot) = \max(0, \cdot)$. An implementation of a standard spectral convolution is given in, e.g., Kipf & Welling (2017). The layer-wise propagation rule in layer l is determined by

$$\boldsymbol{H}^{(l+1)} = \sigma(\underbrace{\tilde{\boldsymbol{D}}^{-\frac{1}{2}}\tilde{\boldsymbol{A}}\tilde{\boldsymbol{D}}^{-\frac{1}{2}}}_{\boldsymbol{L}_{norm}} \boldsymbol{H}^{(l)}\boldsymbol{W}^{(l)}), \tag{6}$$

where $\tilde{\boldsymbol{A}} = \boldsymbol{A} + \boldsymbol{E}$ is the adjacency matrix with added self connections, $\boldsymbol{E}$ is the identity matrix, $\tilde{\boldsymbol{D}}$ is the degree matrix of the graph with self-loops, and $\boldsymbol{L}_{norm}$ is the normalized graph Laplacian. σ is an activation function, and W is a learnable weight matrix functioning as a filter. The idea of spectral graph convolutions comes from signal processing. Vividly, one can imagine it as global message passing on a graph, weighted with a filter. (minor 1 BMQA)

3.2.4 Recurrent Neural Networks

For each time step t, the Recurrent Neural Network (RNN) calculates a hidden representation using historical information together with the current input $\boldsymbol{X}^{(t)}$ (Bronstein et al., 2021). First, the input is transformed by an encoder function f to a representation vector $\boldsymbol{z}^{(t)} = f(\boldsymbol{X}^{(t)})$. Then, $\boldsymbol{z}^{(t)}$ is aggregated together with the previous information by an update function $R : \mathbb{R}^k \times \mathbb{R}^m \to \mathbb{R}^m$ (R13) that additionally considers the hidden representation from the time step before. Altogether, a basic RNN is formalized by

$$h^{(t)} = R(z^{(t)}, h^{(t-1)}).$$

In the context of graph learning, the node feature matrix is commonly used as initial input $\boldsymbol{X}^{(0)}$ (R14). Furthermore, in various GNNs for dynamic graphs, GCN layers are combined with RNNs by, e.g., modeling the GCN weight evolution with an RNN or propagating the learned structural information from one timestamp to the next timestamp.

4 Models Focusing on Structural Graph Properties

Learning on simple graphs is most prevalent in the research of GNNs. The elementary graph structure can already model relations in the data, and the mathematical foundations go back to the 17th century. After the most prominent introduction of Graph Neural Networks by Scarselli et al. (2009) for learning on static node-attributed graphs, many different extensions have been proposed. An overview of GNN models for simple static graphs is discussed in Sec. 4.1. Their approaches often build on the graph information processing scheme of Scarselli et al. and adapt it to new applications and several structural graph properties.

One of the extensions includes the higher-order representation of relational data with the aid of elementary hypergraphs. Hypergraph theory is still a young field and has been essentially developed by Claude Berge Berge (1973) in the 1970s. Learning on hypergraphs has also emerged as part of research in recent years and has much potential for applications on differently structured hypergraphs, as illustrated in table 2(minor 2. BMQA).

4.1 GNNs for Simple Graphs

The number of GNNs for simple graphs has increased immensely in the past years, so table 1(R15) does not list all of them but gives an overview of several GNNs for simple graphs with structural properties defined in Def. 3.2. This demonstrates which graph types have already been considered in GNN research. The models are selected according to their up-to-dateness, relevance, general applicability, explicit addressing of a specific graph type, and simplicity, as discussed in the introduction. Note that in the case of processing attributed graphs, the attributes have to be encoded in d-dimensional vectors. To apply the corresponding models to arbitrary attributed graphs, preprocessing steps have to be utilized as in Zhang et al. (2019a). (minor 2. BMQA)

The most common type of GNNs for simple graphs concerning structural properties are **convolutional** models, which compute new node representations in each layer. A common graph convolution as, for example, defined in GNN* (Scarselli et al., 2009), or WL (Morris et al., 2019), typically assumes attributed nodes and allows for directed and undirected edges without being explicitly designed for either property. Models designed for other graph types typically extend a common spectral or spatial convolution to adapt to the specific structural property they focus on.

To consider directed edges, for example, in GenRecN (Sperduti & Starita, 1997), a standard spectral convolution is applied only on the out-neighbors of a target node, i.e., on those neighbors connected via a directed edge originating from it. A more recent model, MagNet (Zhang et al., 2021), applies a spectral convolution using a complex-valued Hermitian matrix, called magnetic Laplacian, instead of a symmetric and real-valued Laplacian which cannot be computed due to the asymmetric adjacency matrix of a directed graph. The magnitude of the complex Laplacian indicates the presence of an edge but not its direction, while the phase of the complex Laplacian indicates the direction of an edge. (BMQA weakness 3) The lack of models designed for graphs with edge attributes probably results from considering edge attributes only in addition to node attributes since edge attributes are typically not relevant in isolation. In terms of heterogeneity, a similar observation can be made. Corresponding graphs are either heterogeneous in their nodes and edges or node homogeneous, i.e. the, node set remains of one type. Edge heterogeneity is more common than node heterogeneity since it includes widely-used multi-relational graphs. These can be handled by, e.g., an extension of a standard convolution applied separately for each relation (GRNN (Ioannidis et al., 2019)).

Another common procedure is extending a convolutional model using an **attention** mechanism, e.g., as described in Sec. 3.2.2. Attention mechanisms are suitable for node-attributed graphs since they allow the computation of node-specific attention scores that express the importance of one node to another. These attention scores can serve as weights in computing node features to focus on specific nodes. Spectral (CapsGNN (Xinyi & Chen, 2018)), as well as spatial convolutions (GAT (Velickovic et al., 2018)), can be equipped with attention mechanisms. They can also be adapted to attributed edges to process entirely attributed graphs (EGNN (Gong & Cheng, 2019)). Also, attention-based models are a suitable approach for heterogeneous graphs since multi-head attention can be used to model different relation types, as in

AA-HGNN (Ren et al., 2021). A particular case of attention convolution is HAN Wang et al. (2019)(R17), which utilizes a selected set of meta paths for neighborhood aggregation.

It is relatively uncommon for simple graphs to use **RNN-based** methods. However, for example, PG-GNN (Xia & Ku, 2021) learns a graph representation from protein sequences using recurrent layers.

Table 1: **GNN's developed for learning on simple graphs of different structures.** Such models are most prevalent in the research of GNNs.

	Graph Type	Models	Problem	Data Category
graph	directed	GenRecN (Sperduti & Starita, 1997)	graph classification	logic terms
		MagNet Zhang et al. (2021)	link prediction, node classification	linking of websites, synthetic
	undirected	GNN* Scarselli et al. (2009)	subgraph matching, graph classification, web page ranking	synthetic, mutagenesis (molecules)
	node-attributed	GAT Velickovic et al. (2018)	node and graph classification	citation networks, protein interaction
		CapsGNN Xinyi & Chen (2018)		biological-, social networks
		WL Morris et al. (2019)	graph classification, attribute prediction	biological-, social networks, molecules
	edge-attributed	—		
	attributed	EGNN Gong & Cheng (2019), PG-GNN Xia & Ku (2021)	graph classification, node and edge attribute prediction	citation networks, protein structure
	node-heterogeneous	—		
	edge-heterogeneous	GRNN Ioannidis et al. (2019)	node classification	citation networks
	heterogeneous	AA-HGNN Ren et al. (2021), HAN Wang et al. (2019)		news articles & citation networks
	multi	—		

4.2 GNNs for Hypergraphs

Learning on hypergraphs as in Def. 3.1 has been rarely explored. Most approaches involve convolutions adapted to hypergraphs, i.e., the property that an edge can be incident to an arbitrary number of nodes. Table 2 lists GNNs that mainly address node classification on citation networks represented as hypergraphs, which shows that the application of hypergraphs is not yet widespread; hence, the available datasets are currently limited. During the research for hypergraph GNNs, it turned out that, so far, only a few GNNs have been applied to hypergraphs. When it comes to additional structural properties as defined in Def. 3.2, sometimes only one or two models for the specific hypergraphs have been developed. Table 2 indicates that the data is still very homogeneous and that the heterogeneity in graphs is only addressed to a limited extent. (minor 2. BMQA)

One option to handle hypergraphs is to **transform them into simple graphs** and apply standard GNNs afterward. This preprocessing can be done by selecting two representative nodes for each hyperedge, as in HyperGCN (Yadati et al., 2019). Based on the assumption that nodes in a hyperedge are similar, the

representative nodes typically have the most significant difference between their attributes. Another approach presented in LHCN (Bandyopadhyay et al., 2020) represents a hypergraph as a line graph[6]. In this process, each hyperedge of the original graph serves as a simple node in the line graph. The corresponding node attributes are computed by the average across the attributes of all hypernodes in that hyperedge. Both variants allow for processing attributed and undirected hypergraphs using GNN models for simple graphs.(minor 2. BMQA)

Table 2: **GNNs learning on hypergraphs with different additional properties.** The selection of GNNs is still limited, which illustrates gaps and the potential of the young research field.

	Graph Type	Models	Problem	Data Category
hypergraph	directed	NDHGNN Tran & Tran (2020)	node classification	citation networks
	undirected	HyperGCN Yadati et al. (2019)	densest k-subhypergraph problem, node classification	combinatorial optimization, citation networks
		HyperConvAtt Bai et al. (2021)	node classification	citation networks
	node-attributed	LHCN Bandyopadhyay et al. (2020)	node classification	citation networks
	edge-attributed	HGNN Feng et al. (2019)	node classification, object classification	citation networks
	attributed	AHGAE Hu et al. (2021)	graph clustering	citation networks, 3D models
	node-heterogeneous	—		
	edge-heterogeneous	—		
	heterogeneous	HWNN Sun et al. (2021b)	node classification	citation networks
	multi	G-MPNN (multiple edges) Yadati (2020)	link prediction	knowledge (hyper-) graphs

There are also models which are **specifically designed for hypergraphs**, most of them based on spectral convolutions. The graph's incidence matrix can be used to adapt spectral convolutions to attributed hypergraphs and the node and edge degree matrix in the neighborhood aggregation (HGNN (Feng et al., 2019), AHGAE (Hu et al., 2021)). Such a convolution can be additionally equipped with an attention mechanism (HyperConvAtt (Bai et al., 2021)). NDHGNN (Tran & Tran, 2020) uses separate incidence matrices for the source and target nodes to model the graph's Laplacian in the spectral hypergraph convolution to process directed hypergraphs. Such convolutions can also be used for heterogeneous graphs by using edge homogenization, e.g., by working on subgraphs that include hyperedges of only one specific type. In HWNN (Sun et al., 2021b), the spectral convolution is applied on subgraphs, which include hyperedges of only one specific type. Finally, to enable learning on multi-hypergraphs, a message-passing GNN is extended to include multiple relations and node or edge duplicates (Yadati, 2020).

Both approaches, i.e., transforming hypergraphs into simple graphs or directly working on them, have advantages and disadvantages. The first case enables the application of well-established GNN architectures, which have typically been investigated more thoroughly. However, the transformation is often related to information loss, affecting performance. In HyperGCN (Yadati et al., 2019), the information from nodes in

---

[6]The nodes of a line graph w.r.t. an original graph are determined as the edges of the original graph, while the edges are inserted between two edges of the original graph that share an incident node.

hyperedges that do not serve as representative nodes disappear. Models that directly operate on hypergraphs, such as HGNN (Feng et al., 2019), can use the complete information to learn.

5 Models Respecting Dynamic Graph Properties

Many applications include data that changes with time. In the application of graphs, it often appears, e.g., that graphs are growing or structurally changing or that node and edge attributes are evolving, as defined in Def. 3.3. Therefore, the research on GNNs for dynamic graphs has expanded immensely. There are two common approaches in graph learning for representing a graph's dynamical behavior: discrete-time and continuous-time representation (cf. Def. 3.4)(R18). The first approach has been widely used since the snapshots simplify the processing of structures in the graph. Corresponding proposed GNNs in the literature for processing discrete-time graphs are listed in the next section. The continuous-time approach is much more compact in its representation since it stores only events instead of the entire graph for each time step. However, a local evaluation of the graph is required, i.e., the area in the graph affected by an event has to be identified and retrieved to process the event using a GNN. (minor 3. 4uat) Hence, the application of this representation is more complex, which is also reflected in the less frequent use of it in GNN models, which can be seen in Sec. 5.2.

5.1 GNNs for Discrete-Time Graphs

Although dynamic graphs are much more challenging to handle than static graphs due to the additional temporal dependencies, existing dynamic GNN models already cover many structural graph properties. GNN models operating on discrete-time graphs are typically extensions of static GNNs since the discrete-time representation corresponds to a series of static graphs. Therefore, similar gaps appear, i.e., only node-heterogeneous graphs and multi-graphs are not yet covered. The structural component of dynamic graphs can be learned by applying standard GNN models to the graph snapshots.

Those models are often combined with **RNN-based** models to encode the dynamics, which capture the temporal features. Such an approach is pursued in, e.g., GCRN (Seo et al., 2018). The model processes attribute dynamic graphs using a spectral GCN combined with an LSTM. First, the node attributes are preprocessed by a spectral convolution, and the resulting representation is passed to the LSTM, which captures the data distribution. A similar approach is taken in WD/CD-GCN (Manessi et al., 2020), which applies a GCN to transform the input graph sequence into a sequence of node representations, which are then processed by a modified LSTM. EpiGNN (La Gatta et al., 2020) also combines GCNs and LSTMs to predict the parameters of a generic epidemiological model based on historical movement data. The model embeds the graph nodes for each time step, representing locations using a standard GCN. It learns the desired parameters by embedding the current graph and information from previous time steps stored in the LSTM.

Further approaches combining RNNs and GCNs are, e.g., RE-Net (Jin et al., 2019) and EvolveGCN (Pareja et al., 2020). RE-Net computes local representations for all nodes by applying an RNN to its temporal neighborhood, i.e., the neighbors at different time steps. The model is designed for edge-heterogeneous graphs and aggregates the edges of different types using a GCN before the neighborhood aggregation. To obtain a global node representation, the local node representations over time are processed by another RNN. In contrast to the models mentioned above, EvolveGCN uses the RNN to model the GCN weights, which embeds the graph nodes. More specifically, the weights of each GCN layer are generated by an RNN, which takes the weights of the preceding GCN layer and, optionally, the node embeddings as input. This way, the model adapts the GCN weights along the temporal dimension to tackle the problem of changing node attributes.(minor 2. BMQA)

Another way to handle temporal features in GNNs is **temporal attention**. DySat (Sankar et al., 2020), e.g., generalizes the GAT approach (Velickovic et al., 2018) described in Sec. 1 to dynamic graphs. On the one hand, the model extends the structural attention mechanism. On the other hand, it incorporates an additional temporal attention mechanism that enforces an auto-regressive behavior. Similarly, DyHAN (Yang et al., 2020) generates node embeddings using node-level attention and updates them via neighborhood aggregation and edge-level attention. Finally, the node embeddings are aggregated over time using a temporal attention mechanism. Heterogeneity is accounted for by applying node-level attention at each time step to subgraphs of only one edge type. During edge-level attention, the importance of each edge type is learned through a one-layer MLP. DynGEM (Goyal et al., 2018) takes an entirely different approach and is a dynamically

extendable autoencoder for growing graphs. The input and output dimensions are extended respectively for each new incoming node.

Table 3: **GNN's learning on discrete-time dynamic graphs.** Many of these models are extensions of the static case since the discrete-time representation corresponds to a series of static graphs. Therefore also the gaps appear similar to the static case. The □ sign means, that the graph handled by the model can have attributes, but the attributes are static. Thus, they appear or disappear together with their respective nodes or edges but do not change over time.

Graph Type			Models	Nodes		Edges		Attr.		Problem	Data Category
				add	del	add	del	node	edge		
DTR	graph	directed	EpiGNN La Gatta et al. (2020)	×	×	×	×	✓	□[7]	node label prediction	covid-19
		undirected	DySAT Sankar et al. (2020)	×	×	✓	✓	×	□	link prediction	communication, rating networks
			(WD/CD)-GCN Manessi et al. (2020)	×	×	✓	✓	✓	×	node classification	research community
		node-attributed	GCRN Seo et al. (2018)	×	×	×	×	✓	□	video prediction,[8] graph sequence prediction	videos, text
		edge-attributed	DynGEM[9] Goyal et al. (2018)	✓	✓	✓	✓	×	□	graph reconstruction, link prediction, anomaly detection	synthetic, collaboration, communication networks
		attributed	EvolveGCN Pareja et al. (2020)	✓	✓	✓	✓	✓	□[10]	link prediction, edge and node classification	synthetic, social networks, bitcoin, community network
		node-heterogeneous	—								
		edge-heterogeneous	RE-Net Jin et al. (2019)	×	×	✓	✓	×	×	extrapolation link prediction	knowledge graphs
		heterogeneous	DyHAN Yang et al. (2020)	✓	✓	✓	✓	×	×	link prediction	e-commerce, online-community
		multi	—								

---

[7]Only static edge attributes are considered.
[8]The model uses the moving written digits datasat (moving-MNIST dataset) generated by Shi et al. Shi et al. (2015)
[9]Only considers the previous time step, patterns of short duration (length 2) for link prediction and is restricted to weights.
[10]Edges are weighted not generally attributed.

									task	application
hypergraph	directed	DHAT Luo et al. (2021)	×	×	×	×	✓	×	feature prediction	traffic data
	undirected	—								
	node-attributed	STHAN-SR Sawhney et al. (2021)	×	×	×	×	✓	□	node ranking	stock prediction
		HGC-RNN Yi & Park (2020)	×	×	×	×	✓	×	feature prediction	traffic flows
	attributed	Hyper-GNN Hao et al. (2021)	×	×	✓	✓	✓	□[10]	action recognition/graph classification	human motion
	node-, edge heterogeneous	—								
	heterogeneous	MGH Yan et al. (2020)	✓	✓	✓	✓	✓	✓	graph classification	videos
	multi	—								

Since handling hypergraphs is challenging, especially in the dynamic case, few models have been proposed yet. One model that combines RNNs and GCNs is the HGC-RNN (Yi & Park, 2020). It integrates the temporal evolution of higher-ordered structures with two different hypergraph convolutions to encode structural and temporal information, global states, and a subsequent recurrent unit. All other hypergraph models in Tab. 4 involve attention mechanisms. Typically, they combine a hypergraph convolution with a temporal attention mechanism, as in DHAT (Luo et al., 2021), and MGH (Yan et al., 2020). For graph learning on video data, MGH extracts features from classical CNNs of different granularity to define hypergraphs of different types beforehand. The heterogeneity of the edges is then integrated into the model using corresponding attention. (minor 2. BMQA)

A very similar model is Hyper-GNN (Hao et al., 2021). It applies a hypergraph convolution similar to HGNN (Feng et al., 2019) from Sec. 4.2 and a corresponding attention mechanism adapted to neighborhoods on hypergraphs. The overall architecture consists of three parallel networks of the same structure, each processing different input features. STHAN-SR (Sawhney et al., 2021) also applies an attention convolution, which has been designed for static graphs. It applies a HyperGCN model (Yadati et al., 2019) from Sec. 4.2 to process node features that have been generated utilizing an LSTM and a temporal attention mechanism. (minor 2. BMQA)

When considering the types of dynamics the different models can handle, it becomes apparent that most of them focus on specific dynamics, such as dynamic node attributes only (EpiGNN (La Gatta et al., 2020), GCRN (Seo et al., 2018), STHAN-SR (Sawhney et al., 2021), HGC-RNN (Yi & Park, 2020), DHAT (Luo et al., 2021)) or evolving edges (RE-Net (Jin et al., 2019), Hyper-GNN (Hao et al., 2021), WD/CD-GCN (Manessi et al., 2020)). In particular, to the best of our knowledge, MGH (Yan et al., 2020) is the only model capable of processing graphs with changing node and edge sets and node and edge attributes over time. Among all the dynamics, deleting nodes and changing edge attributes have emerged as the least considered and probably most challenging ones. In the case of decreasing node sets, difficulties arise from the changing data structures leading to data gaps, the handling of obsolete data, and in particular, the lack of data and applications in this area. At the same time, the lack of models for changing edge attributes is a consequence of the fact that there are hardly any data and applications for this case.

5.2 GNNs for Graphs in Continuous Time

Regarding dynamic graphs in continuous-time representation, fewer models use the advantages of this compressed representation, although the amount is growing quickly(weakness 3, 4uat). Especially dynamic hypergraphs in this form are currently rarely investigated. Using the continuous-time representation allows the usage of explicit timestamps and an explicit specification of the change in the graph instead of processing a graph snapshot in every time step. Therefore, it drastically reduces the storage requirements. Nevertheless, utilizing this representation is challenging due to the absence of a direct encoding of the graph structure at a particular time and the model's requirement to be updateable in case of occurring events.

Stochastic processes are frequently used to model dynamic graphs represented as a sequence of events. Typically, such processes model the probability of an event occurring at a specific time. These events encode the graph's dynamics, such as a node's appearance or an attribute's change, and an intensity function describes the distribution of the events over time. The occurrence of an event is modeled based on the most recent events involving the nodes or edges of interest.

Examples of approaches utilizing stochastic processes are Know-Evolve (Trivedi et al., 2017) and its extension, DyREP (Trivedi et al., 2019). Know-Evolve considers events of appearing edges of different types. Here, separate embeddings for source and target nodes are computed to take directed edges into account. Furthermore, a learnable function is applied to the difference between a specific node's current and the last event to capture the temporal evolution. Moreover, previous embeddings of the nodes and edges involved in the current event are processed by an RNN-based model to encode the effect of the recurrent participation of each entity in events. The node embedding is further processed by a learnable function, which captures the compatibility of nodes in previous edges. Based on the learned node embeddings, a temporal point process is used to model the probability of an edge occurring between two existing nodes at the next timestamp. Know-Evolve's extension DyREP additionally uses structural information of the graph for two different edge types that represent different ways of communication between nodes. (minor 2. BMQA)

GHNN (Han et al., 2020) also applies a stochastic process, specifically a Hawkes process, to predict missing target nodes v in a tuple (u, e, v, t) of the source node u and edge type e at time t. The node representation used within the Hawkes process is computed using a standard spatial convolution, which considers different edge types. Accordingly, the model can handle edge-heterogeneous graphs.

A different approach is proposed in DyGNN (Ma et al., 2020). It utilizes **LSTMs** in two kinds of units, one for the source and the other for target nodes connected through an edge. In the case of link prediction, node pairs are ranked respecting the cosine similarity of their node representations, and in the case of node classification, the softmax function is utilized. Similarly, TGN (Rossi et al., 2020) enables the usage of a memory module, which can be updated using an RNN such as an LSTM or GRU. The obtained node embedding can be used together with a learnable function to perform, e.g., temporal attention, summation, or projection. Afterward, an MLP processes the node embeddings of node pairs to generate a probability for the edge at the next timestamp to perform future link prediction.

(Souza et al., 2022) proved a deficit in the expressivity of TGN and proposed the Positional-Encoding Injective Temporal Graph Net (PINT) to overcome this deficit. A node embedding at a certain timestamp is determined by an injective temporal aggregation of the neighborhood, where the attributes of the neighbors are calculated with an MLP over the neighboring node attribute concatenated with the corresponding edge attribute. Further, the performance is improved by concatenating the relative positional features that incorporate information from the temporal walk structures with the node features. [Rev. 4uat, Reference [5]]

Jin et al. (2022) propose a model that uses a recurrent unit combined with temporal walks. Such walks are defined as node sequences in which subsequent nodes have previously been involved in an event together. While sampling temporal walks for a target node, nodes that have been involved in an event with the target node more recently are sampled with a higher probability. By anonymizing these walks into relative and node-unspecific encodings, so-called motifs are created. An autoregressive gated recurrent unit processes these to compute the node embeddings. Since the nodes are sampled irregularly for the temporal walks, the motifs are integrated over multiple interaction time intervals.

Table 4: **GNN's learning on continuous-time dynamic graphs.** Due to the difficulties arising from the lack of a direct encoding of the graph structure at each time point, there are only certain graph types covered by models models utilizing graphs in this representation(weakness 3, 4uat).

Graph Type			Models	Nodes		Edges		Attr.		Problem	Data Category
				add	del	add	del	node	edge		
CTR	graph	directed	Know-Evolve (Trivedi et al., 2017)	×	×	✓	×	×	×	link/time prediction	socio-political interactions
		directed	DyGNN (Ma et al., 2020)[11]	✓	×	✓	×	×	×	link prediction, node classification	communication/ trust networks
		undirected / node-attributed	DyRep (Trivedi et al., 2019)	✓	×	✓	×	×	×	link/event time prediction	social networks, github
		edge-attributed	—								
		attributed	NeurTWs (Jin et al., 2022)	×	×	✓	×	×	×	dynamic link prediction	social networks, interaction networks
		node-heterogeneous	—								
		edge-heterogeneous	Know-Evolve (Trivedi et al., 2017)	×	×	✓	×	×	×	link/time prediction	socio-political interactions
		edge-heterogeneous	DyRep (Trivedi et al., 2019)	✓	×	✓	×	×	×	link/event time prediction	social networks, github
		edge-heterogeneous	GHNN (Han et al., 2020)	×	×	✓	×	×	×	link/time prediction	news articles
		heterogeneous	—								
		multi	PINT (Souza et al., 2022), TGN (Rossi et al., 2020)	✓	✓	✓	✓	✓	✓	node classification, edge prediction	social networks
	hypergraph	directed	—								
		undirected	HIT (Liu et al., 2021)	□[12]	×	✓	×	×	×	edge-, pattern-, time prediction	Q&A platform, political interactions, patient medication

---

[11]The baseline models used in the experiments are made for continuous-time dynamic GNNs. All the models used are either made for static graphs (e.g., GCN, GraphSAGE) or discrete-time dynamics (e.g., DynGEM, DANE, Dynamic Triad).
[12]Nodes only appear together with new hyperedges.

		(node, edge) attributed, (node, edge) heterogeneous, multi	—

To the best of our knowledge, the only GNN developed for hypergraphs in continuous-time representation is HIT (Liu et al., 2021). To encode structural and temporal information, it uses temporal random walks defined as a randomly selected set of hyperedges backward in time. Afterward, an aggregation mechanism pools the obtained representation into the final node embedding.

6 Models Utilizing Semantic Graph Properties

Besides the structural graph properties, it is also possible to consider semantic properties in designing a GNN. Although semantic graph properties typically do not explicitly affect the graph's structure (R-5), it can be advantageous to leverage them in GNNs since the graph topology could change or specialized architectures might better preserve the original properties in the learned representation. The necessity for this comes from the data's nature and theoretical considerations to learn structures more efficiently or to explicitly model certain constraints or properties of the data structure. The semantic properties listed in Def. 3.2 are a selection from data-motivated characteristics (e.g., bipartite nodes for user-item modeling, complete graphs for relation prediction) and graph theory (e.g., regular or disconnected graphs, trees). Accordingly, GNNs that integrate some of these properties are presented in Tab. 5.

Some characteristics are considered more often in graph learning than others. These include, e.g., complete, acyclic, and bipartite graphs since they reflect frequently occurring characteristics of graph applications. In contrast, recursive graphs or (poly-)trees are considered explicitly only occasionally. To the best of our knowledge, regular graphs do not play a significant role in graph learning.

Complete graphs represent the existence of a connection between each node pair. Standard Message-Passing GNNs or Convolutional GNNs are theoretically capable of handling complete graphs. However, especially in the case of GCNs, the neighborhood of all nodes is considered equally, and thus, the information flow in the graph is inexpressive. Some GNNs have been developed for complete graphs to overcome this problem.(minor 2. BMQA)

MGCN (Lu et al., 2019), e.g., is specifically designed to predict properties of molecules represented as a complete graph. The network is a standard Message-Passing Neural Network (MPNN), utilizing node and edge attributes. The crucial innovation is how nodes and edges are embedded. The idea is to model quantum interactions between atoms since these influence the overall properties of the molecule. Initially, the atoms of a molecule define nodes of a complete graph, respecting the number of protons in their nuclei. Then, the edge attributes are constructed using a radial basis function (RBF) layer and processed in a hierarchical GCN to weight nodes in the message-passing. A final node embedding is obtained by executing several convolutions and hierarchically aggregating the neighborhood of increasing depth. The learned node and edge embeddings are summed across the graph to infer the prediction of molecule properties. Since molecule datasets typically comprise labels only for a small fraction of the data and only for smaller molecules, the authors mainly focused on generalizability and transferability between different molecule sizes.

As can be observed from the table, there are models focusing on **bipartite graphs**, i.e., graphs that can be divided into two disjoint node sets such that every edge connects a node of one set to a node from the other set. One example is BGNN (He et al., 2019), which focuses on generating a suitable representation for such graphs. For this purpose, information across and within the graph's two partitions (domains) is aggregated to enable inter-domain message passing. The model is trained in a so-called cascade way, i.e., the training of a layer begins after the preceding layer has been fully trained. Thereby, the loss function for the domains is defined layer-wise. Together with a global loss, the quality of the resulting node representation is measured. (minor 2. BMQA)

BipGNN (Wang et al., 2020), in contrast, restricts the convolution to the propagation between the disjoint node sets. The network encoder produces pairwise embeddings for nodes from the two disjoint sets, and the decoder maps these embeddings to an association matrix to perform link prediction between disjoint sets. (minor 2. BMQA)

In the case of **unconnected graphs**, the underlying concept of information flow in GNNs may reach its limits. In standard GNNs, subgraphs without a connection to the rest of the graph are processed isolatedly. Thus, small isolated subgraphs may not provide enough structural information to prevent over-smoothing (Li et al. (2018)of the GNN. To tackle this problem, the generative graph transformer network (GTN) (Yun et al., 2019), e.g., aims to identify valuable connections between unconnected nodes to the rest of the graph. It enables learning on multiple subgraph structures in a heterogeneous graph by concatenating graph convolutions on different meta-paths.

Table 5: **GNNs using semantic graph properties.** The specific semantic properties have been selected due to their rather common appearance in graph data. Since some graph characteristics are considered in more applications or in more popular applications, there exist more GNN models, e.g. bipartite graphs are considered often.

Graph Type	Models	Problem	Data Category
complete	MGCN (Lu et al., 2019)	graph attribute prediction	quantum chemistry
r-regular	—		
bipartite	BipGNN (Wang et al., 2020)	link-rank prediction	drug repurposing
	BGNN (He et al., 2019)	node representation learning	social-/citation networks
unconnected[13]	GTN (Yun et al., 2019)	graph generation, meta-path generation, node classification	citation networks, movie genres
acyclic[14]	DAGNN (Thost & Chen, 2021)	node prediction, longest path prediction	source code, neural architectures, Bayesian networks
trees	GenRecN (Sperduti & Starita, 1997)	graph classification	logic terms
polytrees	CTNN (He et al., 2021)	node classification	3d surfaces in context of hydrological applications
recursive	MPNN-R (Yadati, 2020)	node classification	documents in academic networks
hierarchical	Hier-GNN (Chen et al., 2022)	image classification	images

Acyclic graphs occur across various domains, such as source code, neural architectures, or logic terms. DAGNN (Thost & Chen, 2021) learns a representation for directed acyclic graphs driven by the partial order over the graph nodes. It is an RNN-based message-passing network utilizing an attention module to obtain the messages, which are then forwarded through a GRU. A graph representation is obtained by first concatenating the source and target node representations separately, then max-pooling them and concatenating the results.

---

[13]Since, to the best of our knowledge, most of the models do not specify the connectedness, it is assumed here that they can handle both connected and unconnected graphs.

[14]The majority of GNN models in this survey can handle cycles because they are very common in graphs.

Particular cases of acyclic graphs are **trees**, i.a., examined in GenRecN (Sperduti & Starita, 1997). This early work, as mentioned in Sec. 4.1, applies a spatial neighborhood convolution on the out-neighbors of a node. Polytrees also serve as suitable representations for some types of data, such as surface contours of 3D data. As shown in CTNN (He et al., 2021), polytrees can be used to model the evolution of the surface contours at different elevation levels. The model uses a U-Net (Ronneberger et al., 2015) architecture with ChebyNet (Defferrard et al., 2016) and diffusion Graph Convolution (Li et al., 2017) Layers, using graph pooling and unpooling methods for the characteristic unit architecture.

Another model using a U-Net (Ronneberger et al., 2015) architecture is Hier-GNN (Chen et al., 2022), which explores hierarchical correlations between nodes. For this purpose, specialized pooling and unpooling methods are explicitly defined to encode hierarchical information. Graph convolutions are then applied among a layer in the hierarchy.

Finally, MPNN-R (Yadati, 2020) has been developed to encode **recursive graphs**. It is based on G-MPNN (Yadati, 2020) mentioned in Sec. 4.2 and adapts the message-passing function for recursive multi-relational ordered multi-hypergraphs.

7 Models for Combined Graphs

Arbitrary combinations of graph types can be used to model real-world problems and thus be considered for graph learning purposes. To conclude this work, we give a selected list of graph-type combinations used in several research fields where GNNs are already established. Therefore, this list is not necessarily complete but gives an insight into further research on GNNs considering combined graph types.

The architectures listed in Tab. 6 are GNN models specialized for a particular combination of graph properties. Some of them use a selected non-Euclidean space that is assumed to provide a better fit for the specific data. GCN (Kipf & Welling, 2017), e.g., defines a standard spectral graph convolution for simple graphs allowing for one-dimensional edge weights, whereas Hyperbolic GNN (Liu et al., 2019) defines its extension to hyperbolic space. Hyperbolic GNN operates on Riemannian manifolds[15] and is independent of the underlying space. Since every point of a differentiable Riemannian manifold can be approximated by Euclidean space, all functions with trainable parameters are executed in Euclidean Space. HVGNN (Sun et al., 2021a) uses a hyperbolic model as well. More precisely, it consists of a temporal graph neural network based on convolution and attention modules and a variational graph auto-encoder in hyperbolic space. A map from time to a hyperbolic space encodes time information to handle time in the convolution process. This way, the aggregation of the features is done in a time-aware neighborhood.

The combined graph structures that make up **knowledge graphs** represent a common application for GNNs. They can represent all types of attributes, together with heterogeneity and dynamics. Therefore, many different models have been developed. KGIN (Wang et al., 2021), e.g., uses an attention mechanism that combines different relations into so-called intents to model the user-item relations. These are subsequently used for user and item embeddings modeled via another attention layer to predict the probability of a user adopting an item. A similar use case is approached in SBGNN (Huang et al., 2021), where the two node types of users and items are represented as a bipartite graph connected through signed relations. The model uses a message-passing scheme, including an attention mechanism to encode positive and negative links in recommender, voting, and review systems. HetG (Zhang et al., 2019a) processes a similar graph type. The model is designed to embed heterogeneous graphs with node and edge attributes of any kind. It generates a heterogeneous neighborhood using Random Walk with Restart and applies a Bi-LSTM for heterogeneous content embedding. Different types of nodes are then combined via an attention mechanism.(minor 2. BMQA)

A particular type of graph that can be useful for several applications is the **multiplex graph**. It consists of different layers, each with the same set of nodes but different sets of edges within these layers. Inter-layer edges connect the same nodes across different layers. In MXMNet (Zhang et al., 2020a), a two-layer multiplex graph is utilized such that the so-called local layer is generated with the aid of molecular expert knowledge, and the global layer depends on the neighborhood of the local layer. MXMNet applies a message-passing

---

[15]A Riemannian manifold is a real and smooth manifold equipped with an inner product at each point of the manifold (Liu et al., 2019).

procedure to each layer separately and enables communication between these layers by defining an additional cross-layer mapping function.

Multiplex graphs can also be used to model temporal features without explicitly using a dynamic graph representation as in STGNN (Kapoor et al., 2020). This model is specifically designed to predict the daily new cases of COVID-19 in a particular region based on mobility data. Each layer of the multiplex graph corresponds to a specific period, i.e., a day. Nodes represent regions, and relations within these layers describe human mobility between different regions. Edges between the layers are temporal and define a node's attribute through time. STGNN processes such graphs using spectral graph convolutions.

Table 6: **GNN's for combined graph types.** The graph type combinations were selected to cover combinations in fields where the usage of GNNs is already established.

Graph Type	Models	Problem	Data Category
undirected node-attributed	GCN (Kipf & Welling, 2017)	node classification	citation networks, knowledge graphs
	Hyperbolic GNN (Liu et al., 2019)	graph classification, node regression	synthetic, molecular, blockchain
knowledge graph	KGIN (Wang et al., 2021)	link prediction	recommender systems
content-associated heterogeneous	HetG (Zhang et al., 2019a)	link prediction, recommendation, (inductive) node classification, node clustering	review networks
multiplex	MXMNet (Zhang et al., 2020a)	graph feature prediction	molecules
spatio-temporal	STGNN (Kapoor et al., 2020)	node attribute prediction	disease spreading
multi-relational bipartite	SBGNN (Huang et al., 2021)	link sign prediction	recommender, voting, review systems
bipartite edge-growing in continuous-time	JODIE (Kumar et al., 2019)	future user-item interaction prediction, user state change prediction[16]	social media, wiki, music, student actions
undirected node-attributed edge-dynamic	HVGNN (Sun et al., 2021a)	link prediction, node classification	social, citation, knowledge

JODIE (Kumar et al., 2019) also processes temporal information, but it directly encodes the dynamics using an RNN. It can be considered a particular case of the TGN-Model (Rossi et al., 2020). For node embeddings, it also uses a memory module that can be updated using an RNN. The message-passing function is set to the identity and applied together with a learnable time projection function. The model is evaluated, e.g., on link prediction between users and items inferred from the distance between the embeddings of a pair of nodes.

8 Conclusion and Future Work

This survey provides a fine-grained overview of Graph Neural Networks for graph types of different structural constitutions. To the best of our knowledge, this is the first work to survey which graph types are addressed

---

[16]The task is to predict if an interaction will lead to a state change in user, particularly in two use cases: predicting if a user will be banned and predicting if a student will drop-out of a course.

by published GNNs. We overviewed and defined the most common graph types and properties and the respective GNN models. Moreover, we identified GNN models specialized for specific graph properties and investigated how they handle these. This way, we could relate formal graph properties to the corresponding practical GNN models. Furthermore, we analyzed the architecture of the considered models and grouped them according to the modules they apply, i.e., the type of layer, such as convolutional or recurrent layers. Additionally, we analyzed GNN models concerning dynamics and grouped the models according to the types of dynamics they can process.

Our work allows several conclusions to be drawn and identifies gaps concerning the graph types, properties, and dynamics that GNN models can handle. First, existing GNN models can, in principle, handle the most common structural graph properties (e.g., attributed, directed, node-heterogeneity) for static graphs and hypergraphs. The lack of models for a few properties results from the existence of more general models, e.g., there is no GNN model for node-heterogeneous graphs in discrete time, but there is one for fully heterogeneous graphs. Another reason could be a lack of standard graph data sets for such types. Furthermore, there are many GNN models which consider graphs in discrete-time representation. These models cover the most common graph types and properties except for the multiplicity of nodes or edges. A difficulty in handling multiplicity results from the inability of a standard graph's adjacency matrix to encode duplicate nodes.

When it comes to the models for graphs in continuous time, it is evident that there are substantial gaps in research on GNNs for most of the graph types compared to the discrete case. In particular, only one model for hypergraphs has been found. Generally, developing GNNs for continuous-time graphs is still a young field of GNN research. Another reason for the small number of graph types covered by models for continuous-time graphs(weakness 3, 4uat) could be that such models typically use stochastic point processes to model the dynamic behavior of the graphs. The number of different events increases with the number of dynamic graph properties considered. Since a point process models each event, the model becomes more complex. From the results from Tab. 4, it can be observed that most events model discrete outputs in continuous time, such as whether there is a new edge. When including attribute dynamics for real-valued attributes, the model must deal with continuous values in continuous time, making the model more computationally intensive.

Most dynamic graphs addressed by GNN models exhibit only specific dynamics, such as strictly growing graphs or dynamic node attributes. GNN models for graphs with dynamics in the edge attributes and the deletion of nodes are scarce. To the best of our knowledge, only one model, MGH(Yan et al., 2020), has been developed to process graphs with all dynamics considered in this work, i.e., changing node and edge sets as well as changing node and edge attributes. Reasons for this may be the popularity of problems where graphs are growing over time and node deletions are believed not to play a crucial role (as, e.g., in citation networks, recommender systems, or data networks) and the difficulties that arise when combining known GNN techniques for dynamic graphs. Considering the discrete-time representation of graphs, e.g., GNN techniques for static graphs are usually applied to every graph snapshot and combined with an RNN to capture the dynamics, leading to computationally expensive models.

Finally, existing GNN models have been developed to cover many semantic graph properties or for particular combined graph types dependent on the given data structure, which shows that multiple graph properties can be learned simultaneously by GNN models.

To sum up, the research on GNNs for particular graph types has become a hot area in recent years. However, this extensive survey could reveal gaps in graph types, properties, and dynamics that are not yet considered sufficiently in the GNN community.

9 Notation

Table 7: Notation used throughout this work.

$\mathbb{N}$	natural numbers
$\mathbb{N}_0$	natural numbers starting at 0
$\mathbb{R}$	real numbers
$\mathbb{R}^k$	$\mathbb{R}$ vector space of dimension k
$|a|$	absolute value of a real a
$\|\cdot\|$	norm on $\mathbb{R}$
$|M|$	number of elements of a set M
$\varnothing$	empty set
$\{\cdot\}$	set
$\{\!\{\cdot\}\!\}$	multiset, i.e., set allowing multiple appearances of entries
$\cup$	union of two (multi)sets
$\uplus$	disjoint union of two (multi)sets
$\subseteq$	sub(multi)set
$\times$	factor set of two sets
ψ	learnable message function
ϕ	activation function
σ	sigmoid activation function
$\oplus$	aggregation
$\|$	concatenation
$\boldsymbol{A}$	adjacency matrix
$\tilde{\boldsymbol{A}}$	adjacency matrix with self-loops
$\boldsymbol{B}$	edge degree matrix
$\boldsymbol{D}$	node degree matrix
$\tilde{\boldsymbol{D}}$	node degree matrix with self-loops
$\boldsymbol{E}$	identity matrix
$\boldsymbol{I}$	incidence matrix
$\boldsymbol{L}$	Laplacian matrix
$\boldsymbol{W}$	edge weight matrix

Author Contributions

All authors contributed equally.

Acknowledgments

References

Stephen Abbott. Understanding Analysis, volume 2. Springer, 2001.

James A. Anderson and Edward Rosenfeld. Neurocomputing: Foundations of Research. MIT Press, Cambridge, MA, USA, 1988. ISBN 0262010976.

Song Bai, Feihu Zhang, and Philip HS Torr. Hypergraph convolution and hypergraph attention. Pattern Recognition, 110:107637, 2021.

Sambaran Bandyopadhyay, Kishalay Das, and M Narasimha Murty. Line hypergraph convolution network: Applying graph convolution for hypergraphs. arXiv preprint arXiv:2002.03392, 2020.

Claudio DT Barros, Matheus RF Mendonça, Alex B Vieira, and Artur Ziviani. A survey on embedding dynamic graphs. ACM Computing Surveys (CSUR), 55(1):1–37, 2021. Publisher: ACM New York, NY.

Claude Berge. Graphs and Hypergraphs. 1973.

M. M. Bronstein, J. Bruna, Y. LeCun, A. Szlam, and P. Vandergheynst. Geometric deep learning: Going beyond euclidean data. IEEE Signal Processing Magazine, 34(4):18–42, 2017. doi:10.1109/MSP.2017.2693418.

Michael M. Bronstein, Joan Bruna, Taco Cohen, and Petar Veličković. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges, 2021. URL https://arxiv.org/abs/2104.13478.

Hongyun Cai, Vincent W. Zheng, and Kevin Chen-Chuan Chang. A comprehensive survey of graph embedding: Problems, techniques and applications. arXiv:1709.07604 [cs], February 2018. URL http://arxiv.org/abs/1709.07604. arXiv: 1709.07604.

Cen Chen, Kenli Li, Wei Wei, Joey Tianyi Zhou, and Zeng Zeng. Hierarchical graph neural networks for few-shot learning. IEEE Trans. Circuits Syst. Video Technol., 32(1):240–252, 2022. doi:10.1109/TCSVT.2021.3058098. URL https://doi.org/10.1109/TCSVT.2021.3058098.

Robert J. Cimikowski and Paul Shope. A neural-network algorithm for a graph layout problem. IEEE Trans. Neural Networks, 7(2):341–345, 1996. doi:10.1109/72.485670. URL https://doi.org/10.1109/72.485670.

Peng Cui, Xiao Wang, Jian Pei, and Wenwu Zhu. A survey on network embedding. IEEE transactions on knowledge and data engineering, 31(5):833–852, 2018. Publisher: IEEE.

Sanjoy Dasgupta. Learning polytrees. In Proceedings of the Fifteenth Conference on Uncertainty in Artificial Intelligence, UAI'99, pp. 134–141, San Francisco, CA, USA, 1999. Morgan Kaufmann Publishers Inc. ISBN 1558606149.

Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. Advances in neural information processing systems, 29, 2016.

Lisa Ehrlinger and Wolfram Wöß. Towards a definition of knowledge graphs. SEMANTiCS (Posters, Demos, SuCCESS), 48(1-4):2, 2016.

Yifan Feng, Haoxuan You, Zizhao Zhang, Rongrong Ji, and Yue Gao. Hypergraph neural networks. In The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019, pp. 3558–3565. AAAI Press, 2019. doi:10.1609/aaai.v33i01.33013558. URL https://doi.org/10.1609/aaai.v33i01.33013558.

Fernando Gama, Elvin Isufi, Geert Leus, and Alejandro Ribeiro. Graphs, convolutions, and neural networks: From graph filters to graph neural networks. IEEE Signal Processing Magazine, 37(6):128–138, November 2020. ISSN 1558-0792. doi:10.1109/MSP.2020.3016143.

Ira M. Gessel and Richard P. Stanley. Algebraic enumeration. Handbook of combinatorics, 2:1021–1061, 1995.

Liyu Gong and Qiang Cheng. Exploiting edge features for graph neural networks. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 9211–9219, 2019.

Palash Goyal and Emilio Ferrara. Graph embedding techniques, applications, and performance: A survey. Knowledge-Based Systems, 151:78–94, 2018. Publisher: Elsevier.

Palash Goyal, Nitin Kamra, Xinran He, and Yan Liu. Dyngem: Deep embedding method for dynamic graphs, 2018. URL http://arxiv.org/abs/1805.11273.

William L. Hamilton. Graph Representation Learning. Synthesis Lectures on Artificial Intelligence and Machine Learning, 14(3):1–159, 2020.

William L. Hamilton, Rex Ying, and Jure Leskovec. Representation learning on graphs: Methods and applications. IEEE Data Eng. Bull., 40(3):52–74, 2017. URL http://sites.computer.org/debull/A17sept/p52.pdf.

Zhen Han, Yunpu Ma, Yuyi Wang, Stephan Günnemann, and Volker Tresp. Graph hawkes neural network for forecasting on temporal knowledge graphs, 2020. URL https://doi.org/10.24432/C50018.

Xiaoke Hao, Jie Li, Yingchun Guo, Tao Jiang, and Ming Yu. Hypergraph neural network for skeleton-based action recognition. IEEE Transactions on Image Processing, 30:2263–2275, 2021. doi:10.1109/TIP.2021.3051495.

Chaoyang He, Tian Xie, Yu Rong, Wenbing Huang, Yanfang Li, Junzhou Huang, Xiang Ren, and Cyrus Shahabi. Bipartite graph neural networks for efficient node representation learning. arXiv e-prints, pp. arXiv–1906, 2019.

Wenchong He, Arpan Man Sainju, Zhe Jiang, and Da Yan. Deep neural network for 3d surface segmentation based on contour tree hierarchy. In Carlotta Demeniconi and Ian Davidson (eds.), Proceedings of the 2021 SIAM International Conference on Data Mining, SDM 2021, Virtual Event, April 29 - May 1, 2021, pp. 253–261. SIAM, 2021. doi:10.1137/1.9781611976700.29. URL https://doi.org/10.1137/1.9781611976700.29.

Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. CoRR, abs/2005.00687, 2020. URL https://arxiv.org/abs/2005.00687.

Youpeng Hu, Xunkai Li, Yujie Wang, Yixuan Wu, Yining Zhao, Chenggang Yan, Jian Yin, and Yue Gao. Adaptive hypergraph auto-encoder for relational data clustering. IEEE Transactions on Knowledge and Data Engineering, 2021.

Junjie Huang, Huawei Shen, Qi Cao, Shuchang Tao, and Xueqi Cheng. Signed bipartite graph neural networks. arXiv preprint arXiv:2108.09638, 2021.

Borja Ibarz, Jan Leike, Tobias Pohlen, Geoffrey Irving, Shane Legg, and Dario Amodei. Reward learning from human preferences and demonstrations in atari. In NeurIPS, 2018.

Vassilis N Ioannidis, Antonio G Marques, and Georgios B Giannakis. A recurrent graph neural network for multi-relational data. In ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pp. 8157–8161. IEEE, 2019.

Weiwei Jiang and Jiayun Luo. Graph neural network for traffic forecasting: A survey. arXiv:2101.11174 [cs], February 2022. URL http://arxiv.org/abs/2101.11174. arXiv: 2101.11174.

Ming Jin, Yuan-Fang Li, and Shirui Pan. Neural temporal walks: Motif-aware representation learning on continuous-time dynamic graphs. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), Advances in Neural Information Processing Systems, 2022. URL https://openreview.net/forum?id=NqbktPUkZf7.

Woojeong Jin, Meng Qu, Xisen Jin, and Xiang Ren. Recurrent event network: Autoregressive structure inference over temporal knowledge graphs. arXiv preprint arXiv:1904.05530, 2019.

Cliff A. Joslyn and Kathleen Nowak. Ubergraphs: A definition of a recursive hypergraph structure. CoRR, abs/1704.05547, 2017. URL http://arxiv.org/abs/1704.05547.

Amol Kapoor, Xue Ben, Luyang Liu, Bryan Perozzi, Matt Barnes, Martin Blais, and Shawn O'Banion. Examining covid-19 forecasting using spatio-temporal graph neural networks. arXiv preprint arXiv:2007.03113, 2020.

Seyed Mehran Kazemi, Rishab Goel, Kshitij Jain, Ivan Kobyzev, Akshay Sethi, Peter Forsyth, and Pascal Poupart. Representation Learning for Dynamic Graphs: A Survey. Journal of Machine Learning Research, 21(70):1–73, 2020. URL http://jmlr.org/papers/v21/19-447.html.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In 5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings. OpenReview.net, 2017. URL https://openreview.net/forum?id=SJU4ayYgl.

Dmitri Krioukov, Fragkiskos Papadopoulos, Maksim Kitsak, Amin Vahdat, and Marián Boguñá. Hyperbolic geometry of complex networks. Phys. Rev. E, 82:036106, Sep 2010. doi:10.1103/PhysRevE.82.036106. URL https://link.aps.org/doi/10.1103/PhysRevE.82.036106.

Srijan Kumar, Xikun Zhang, and Jure Leskovec. Predicting dynamic embedding trajectory in temporal interaction networks. In Ankur Teredesai, Vipin Kumar, Ying Li, Rómer Rosales, Evimaria Terzi, and George Karypis (eds.), Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, KDD 2019, Anchorage, AK, USA, August 4-8, 2019, pp. 1269–1278. ACM, 2019. doi:10.1145/3292500.3330895. URL https://doi.org/10.1145/3292500.3330895.

Valerio La Gatta, Vincenzo Moscato, Marco Postiglione, and Giancarlo Sperli. An epidemiological neural network exploiting dynamic graph structured data applied to the covid-19 outbreak. IEEE Transactions on Big Data, 7(1):45–55, 2020.

Jenn-Shiang Lai, Sy-Yen Kuo, and Ing-Yi Chen. Neural networks for optimization problems in graph theory. In 1994 IEEE International Symposium on Circuits and Systems, ISCAS 1994, London, England, UK, May 30 - June 2, 1994, pp. 269–272. IEEE, 1994. doi:10.1109/ISCAS.1994.409578. URL https://doi.org/10.1109/ISCAS.1994.409578.

John Boaz Lee, Ryan A Rossi, Sungchul Kim, Nesreen K Ahmed, and Eunyee Koh. Attention models in graphs: A survey. ACM Transactions on Knowledge Discovery from Data (TKDD), 13(6):1–25, 2019. Publisher: ACM New York, NY, USA.

Qimai Li, Zhichao Han, and Xiao-ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. Proceedings of the AAAI Conference on Artificial Intelligence, 32(1), Apr. 2018. doi:10.1609/aaai.v32i1.11604. URL https://ojs.aaai.org/index.php/AAAI/article/view/11604.

Yaguang Li, Rose Yu, Cyrus Shahabi, and Yan Liu. Diffusion convolutional recurrent neural network: Data-driven traffic forecasting. arXiv preprint arXiv:1707.01926, 2017.

Wenlong Liao, Birgitte Bak-Jensen, Jayakrishnan Radhakrishna Pillai, Yuelong Wang, and Yusen Wang. A review of graph neural networks and their applications in power systems. Journal of Modern Power Systems and Clean Energy, pp. 1–16, 2021. ISSN 2196-5420. doi:10.35833/MPCE.2021.000058. Conference Name: Journal of Modern Power Systems and Clean Energy.

Qi Liu, Maximilian Nickel, and Douwe Kiela. Hyperbolic graph neural networks. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), Advances in Neural Information Processing Systems, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/103303dd56a731e377d01f6a37badae3-Paper.pdf.

Yunyu Liu, Jianzhu Ma, and Pan Li. Neural higher-order pattern (motif) prediction in temporal networks. arXiv preprint arXiv:2106.06039, 2021.

Chengqiang Lu, Qi Liu, Chao Wang, Zhenya Huang, Peize Lin, and Lixin He. Molecular property prediction: A multilevel quantum interactions modeling perspective. In The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019, pp. 1052–1060. AAAI Press, 2019. doi:10.1609/aaai.v33i01.33011052. URL https://doi.org/10.1609/aaai.v33i01.33011052.

Xiaoyi Luo, Jiaheng Peng, and Jun Liang. Directed hypergraph attention network for traffic forecasting. IET Intelligent Transport Systems, n/a(n/a), 2021. doi:https://doi.org/10.1049/itr2.12130. URL https://ietresearch.onlinelibrary.wiley.com/doi/abs/10.1049/itr2.12130.

Yao Ma, Ziyi Guo, Zhaochun Ren, Eric Zhao, Jiliang Tang, and Dawei Yin. Streaming graph neural networks. In Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR' 20, pp. 719–728, 2020.

Franco Manessi, Alessandro Rozza, and Mario Manzo. Dynamic graph convolutional networks. Pattern Recognit., 97, 2020. doi:10.1016/j.patcog.2019.107000. URL https://doi.org/10.1016/j.patcog.2019.107000.

Scott McKinney, Marcin Sieniek, Varun Godbole, Jonathan Godwin, Natasha Antropova, Hutan Ashrafian, Trevor Back, Mary Chesus, Greg Corrado, Ara Darzi, Mozziyar Etemadi, Florencia Garcia-Vicente, Fiona Gilbert, Mark Halling-Brown, Demis Hassabis, Sunny Jansen, Alan Karthikesalingam, Christopher Kelly, Dominic King, Joseph Ledsam, David Melnick, Hormuz Mostofi, Lily Peng, Joshua Reicher, Bernardino Romera-Paredes, Richard Sidebottom, Mustafa Suleyman, Daniel Tse, Kenneth Young, Jeffrey De Fauw, and Shravya Shetty. International evaluation of an ai system for breast cancer screening. Nature, 577: 89–94, 12/2020 2020. ISSN 1476-4687. doi:10.1038/s41586-019-1799-6.

Christopher Morris, Martin Ritzert, Matthias Fey, William L Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In Proceedings of the AAAI conference on artificial intelligence, volume 33, pp. 4602–4609, 2019.

Aldo Pareja, Giacomo Domeniconi, Jie Chen, Tengfei Ma, Toyotaro Suzumura, Hiroki Kanezashi, Tim Kaler, Tao B. Schardl, and Charles E. Leiserson. Evolvegcn: Evolving graph convolutional networks for dynamic graphs. In The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020, pp. 5363–5370. AAAI Press, 2020. URL https://aaai.org/ojs/index.php/AAAI/article/view/5984.

Yun Peng, Byron Choi, and Jianliang Xu. Graph learning for combinatorial optimization: A survey of state-of-the-art. Data Science and Engineering, 6(2):119–141, 2021. Publisher: Springer.

Yuxiang Ren, Bo Wang, Jiawei Zhang, and Yi Chang. Adversarial active learning based heterogeneous graph neural network for fake news detection, 2021. URL https://arxiv.org/abs/2101.11206.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In International Conference on Medical image computing and computer-assisted intervention, pp. 234–241. Springer, 2015.

Emanuele Rossi, Ben Chamberlain, Fabrizio Frasca, Davide Eynard, Federico Monti, and Michael M. Bronstein. Temporal graph networks for deep learning on dynamic graphs, 2020. URL https://arxiv.org/abs/2006.10637.

Ryan A. Rossi and Nesreen K. Ahmed. The network data repository with interactive graph analytics and visualization. In AAAI, 2015. URL https://networkrepository.com.

Aravind Sankar, Yanhong Wu, Liang Gou, Wei Zhang, and Hao Yang. Dysat: Deep neural representation learning on dynamic graphs via self-attention networks. In James Caverlee, Xia (Ben) Hu, Mounia Lalmas, and Wei Wang (eds.), WSDM '20: The Thirteenth ACM International Conference on Web Search and Data Mining, Houston, TX, USA, February 3-7, 2020, pp. 519–527. ACM, 2020. doi:10.1145/3336191.3371845. URL https://doi.org/10.1145/3336191.3371845.

Ryoma Sato. A survey on the expressive power of graph neural networks. arXiv:2003.04078 [cs, stat], October 2020. URL http://arxiv.org/abs/2003.04078. arXiv: 2003.04078.

Ramit Sawhney, Shivam Agarwal, Arnav Wadhwa, Tyler Derr, and Rajiv Ratn Shah. Stock selection via spatiotemporal hypergraph attention network: A learning to rank approach. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 35, pp. 497–504, 2021.

Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. IEEE Transactions on Neural Networks, 20:61–80, 2009. ISSN 1941-0093. doi:10.1109/TNN.2008.2005605.

Youngjoo Seo, Michaël Defferrard, Pierre Vandergheynst, and Xavier Bresson. Structured sequence modeling with graph convolutional recurrent networks. In Long Cheng, Andrew Chi-Sing Leung, and Seiichi Ozawa (eds.), Neural Information Processing - 25th International Conference, ICONIP 2018, Siem Reap, Cambodia, December 13-16, 2018, Proceedings, Part I, volume 11301 of Lecture Notes in Computer Science, pp. 362–373. Springer, 2018. doi:10.1007/978-3-030-04167-0_33. URL https://doi.org/10.1007/978-3-030-04167-0_33.

Hong Shi, Xiaomene Zhang, Shizhong Sun, Lin Liu, and Lin Tang. A survey on bayesian graph neural networks. In 2021 13th International Conference on Intelligent Human-Machine Systems and Cybernetics (IHMSC), pp. 158–161, August 2021. doi:10.1109/IHMSC52134.2021.00044.

Xingjian Shi, Zhourong Chen, Hao Wang, Dit-Yan Yeung, Wai-Kin Wong, and Wang-chun Woo. Convolutional lstm network: A machine learning approach for precipitation nowcasting. In Corinna Cortes, Neil D. Lawrence, Daniel D. Lee, Masashi Sugiyama, and Roman Garnett (eds.), Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada, pp. 802–810, 2015. URL https://proceedings.neurips.cc/paper/2015/hash/07563a3fe3bbe7e3ba84431ad9d055af-Abstract.html.

Jonathan Shlomi, Peter Battaglia, and Jean-Roch Vlimant. Graph neural networks in particle physics. Machine Learning: Science and Technology, 2(2):021001, 2020. Publisher: IOP Publishing.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, Timothy Lillicrap, Karen Simonyan, and Demis Hassabis. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. Science, 362(6419):1140–1144, 2018. doi:10.1126/science.aar6404. URL https://www.science.org/doi/abs/10.1126/science.aar6404.

Joakim Skarding, Bogdan Gabrys, and Katarzyna Musial. Foundations and modelling of dynamic networks using dynamic graph neural networks: A survey. IEEE Access, 9, 2021. ISSN 2169-3536. doi:10.1109/ACCESS.2021.3082932. URL http://arxiv.org/abs/2005.07496. arXiv: 2005.07496.

Amauri H Souza, Diego Mesquita, Samuel Kaski, and Vikas Garg. Provably expressive temporal graph networks. In NeurIPS 2022 Workshop: New Frontiers in Graph Learning, 2022. URL https://openreview.net/forum?id=2neXknZg9ej.

Alessandro Sperduti. Neural networks for processing data structures. In C. Lee Giles and Marco Gori (eds.), Adaptive Processing of Sequences and Data Structures, International Summer School on Neural Networks, "E.R. Caianiello", Vietri sul Mare, Salerno, Italy, September 6-13, 1997, Tutorial Lectures, volume 1387 of Lecture Notes in Computer Science, pp. 121–144. Springer, 1997. doi:10.1007/BFb0053997. URL https://doi.org/10.1007/BFb0053997.

Alessandro Sperduti and Antonina Starita. Supervised neural networks for the classification of structures. IEEE Trans. Neural Networks, 8(3):714–735, 1997. doi:10.1109/72.572108. URL https://doi.org/10.1109/72.572108.

Edgar-Philipp Stoffel, Korbinian Schoder, and Hans Jürgen Ohlbach. Applying hierarchical graphs to pedestrian indoor navigation. In Proceedings of the 16th ACM SIGSPATIAL international conference on Advances in geographic information systems, pp. 1–4, 2008.

Gilbert Strang. Introduction to Linear Algebra, volume 3. Wellesley-Cambridge Press Wellesley, MA, 1993.

Li Sun, Zhongbao Zhang, Jiawei Zhang, Feiyang Wang, Hao Peng, Sen Su, and Philip S Yu. Hyperbolic Variational Graph Neural Network for Modeling Dynamic Graphs. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 35, pp. 4375–4383, 2021a.

Xiangguo Sun, Hongzhi Yin, Bo Liu, Hongxu Chen, Jiuxin Cao, Yingxia Shao, and Nguyen Quoc Viet Hung. Heterogeneous hypergraph embedding for graph classification. In Proceedings of the 14th ACM International Conference on Web Search and Data Mining, pp. 725–733, 2021b.

Josephine M. Thomas, Silvia Beddar-Wiesing, Alice Moallemy-Oureh, and Rüdiger Nather. Graph type expressivity and transformations. CoRR, abs/2109.10708, 2021. URL https://arxiv.org/abs/2109.10708.

Veronika Thost and Jie Chen. Directed acyclic graph neural networks. In International Conference on Learning Representations, 2021. URL https://openreview.net/forum?id=JbuYF437WB6.

Loc Hoang Tran and Linh Hoang Tran. Directed hypergraph neural network. CoRR, abs/2008.03626, 2020. URL https://arxiv.org/abs/2008.03626.

Rakshit Trivedi, Hanjun Dai, Yichen Wang, and Le Song. Know-evolve: Deep temporal reasoning for dynamic knowledge graphs. In Doina Precup and Yee Whye Teh (eds.), Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017, volume 70 of Proceedings of Machine Learning Research, pp. 3462–3471. PMLR, 2017. URL http://proceedings.mlr.press/v70/trivedi17a.html.

Rakshit Trivedi, Mehrdad Farajtabar, Prasenjeet Biswal, and Hongyuan Zha. Dyrep: Learning representations over dynamic graphs. In 7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019. OpenReview.net, 2019. URL https://openreview.net/forum?id=HyePrhR5KX.

Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In 6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings. OpenReview.net, 2018. URL https://openreview.net/forum?id=rJXMpikCZ.

Xiang Wang, Tinglin Huang, Dingxian Wang, Yancheng Yuan, Zhenguang Liu, Xiangnan He, and Tat-Seng Chua. Learning intents behind interactions with knowledge graph for recommendation. In Proceedings of the Web Conference 2021, pp. 878–887, 2021.

Xiao Wang, Houye Ji, Chuan Shi, Bai Wang, Yanfang Ye, Peng Cui, and Philip S Yu. Heterogeneous graph attention network. In The World Wide Web Conference, pp. 2022–2032, 2019.

Zichen Wang, Mu Zhou, and Corey Arnold. Toward heterogeneous information fusion: Bipartite graph convolutional networks for in silico drug repurposing. Bioinformatics, 36(Supplement_1):i525–i533, 2020.

Lingfei Wu, Yu Chen, Kai Shen, Xiaojie Guo, Hanning Gao, Shucheng Li, Jian Pei, and Bo Long. Graph neural networks for natural language processing: A survey. arXiv preprint arXiv:2106.06090, 2021.

Shiwen Wu, Fei Sun, Wentao Zhang, Xu Xie, and Bin Cui. Graph neural networks in recommender systems: A survey. arXiv:2011.02260 [cs], February 2022. URL http://arxiv.org/abs/2011.02260. arXiv: 2011.02260.

Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and S. Yu Philip. A comprehensive survey on graph neural networks. IEEE Transactions on Neural Networks and Learning Systems, 2020.

Tian Xia and Wei-Shinn Ku. Geometric graph representation learning on protein structure prediction. In Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining, pp. 1873–1883, 2021.

Zhang Xinyi and Lihui Chen. Capsule graph neural network. In International Conference on Learning Representations, 2018.

Naganand Yadati. Neural message passing for multi-relational ordered and recursive hypergraphs. Advances in Neural Information Processing Systems, 33, 2020.

Naganand Yadati, Madhav Nimishakavi, Prateek Yadav, Vikram Nitin, Anand Louis, and Partha P. Talukdar. Hypergcn: A new method for training graph convolutional networks on hypergraphs. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada, pp. 1509–1520, 2019.

Yichao Yan, Jie Qin, Jiaxin Chen, Li Liu, Fan Zhu, Ying Tai, and Ling Shao. Learning multi-granular hypergraphs for video-based person re-identification. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), June 2020.

Luwei Yang, Zhibo Xiao, Wen Jiang, Yi Wei, Yi Hu, and Hao Wang. Dynamic heterogeneous graph embedding using hierarchical attentions. Advances in Information Retrieval, 12036:425, 2020.

Jaehyuk Yi and Jinkyoo Park. Hypergraph convolutional recurrent neural network. In Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, pp. 3366–3376, 2020.

Donghan Yu, Chenguang Zhu, Yiming Yang, and Michael Zeng. Jaket: Joint pre-training of knowledge graph and language understanding. arXiv preprint arXiv:2010.00796, 2020.

Hao Yuan, Haiyang Yu, Shurui Gui, and Shuiwang Ji. Explainability in graph neural networks: A taxonomic survey. arXiv:2012.15445 [cs], March 2021. URL http://arxiv.org/abs/2012.15445. arXiv: 2012.15445.

Seongjun Yun, Minbyul Jeong, Raehyun Kim, Jaewoo Kang, and Hyunwoo J Kim. Graph transformer networks. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), Advances in Neural Information Processing Systems, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/9d63484abb477c97640154d40595a3bb-Paper.pdf.

Chuxu Zhang, Dongjin Song, Chao Huang, Ananthram Swami, and Nitesh V. Chawla. Heterogeneous graph neural network. In Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, pp. 793–803, 2019a.

Shuo Zhang, Yang Liu, and Lei Xie. Molecular mechanics-driven graph neural network with multiplex graph for molecular structures, 2020a. URL https://arxiv.org/abs/2011.07457.

Si Zhang, Hanghang Tong, Jiejun Xu, and Ross Maciejewski. Graph convolutional networks: Algorithms, applications and open challenges. In International Conference on Computational Social Networks, pp. 79–91. Springer, 2018.

Si Zhang, Hanghang Tong, Jiejun Xu, and Ross Maciejewski. Graph convolutional networks: a comprehensive review. Computational Social Networks, 6(1):1–23, December 2019b. ISSN 2197-4314. doi:10.1186/s40649-019-0069-y. URL https://computationalsocialnetworks.springeropen.com/articles/10.1186/s40649-019-0069-y. Number: 1 Publisher: SpringerOpen.

Xitong Zhang, Yixuan He, Nathan Brugnone, Michael Perlmutter, and Matthew J. Hirn. Magnet: A neural network for directed graphs. Advances in neural information processing systems, 34:27003–27015, 2021.

Ziwei Zhang, Peng Cui, and Wenwu Zhu. Deep learning on graphs: A survey. IEEE Transactions on Knowledge and Data Engineering, 2020b.

Jie Zhou, Ganqu Cui, Shengding Hu, Zhengyan Zhang, Cheng Yang, Zhiyuan Liu, Lifeng Wang, Changcheng Li, and Maosong Sun. Graph neural networks: A review of methods and applications. AI Open, 1:57–81, 2020.

Marinka Zitnik, Monica Agrawal, and Jure Leskovec. Modeling polypharmacy side effects with graph convolutional networks. Bioinformatics, 34(13):457–466, 2018.