Active Retrosynthetic Planning Aware of Route Quality

Luotian Yuan[1]*, **Yemin Yu**[2,4]*, **Ying Wei**[3]†, **Yongwei Wang**[4], **Zhihua Wang**[4], **Fei Wu**[1,4]†

[1]Zhejiang University, [2]City University of Hong Kong, [3]Nanyang Technological University
[4]Shanghai Institute for Advanced Study of Zhejiang University

`3180105619@zju.edu.cn, yeminyu2-c@my.cityu.edu.hk, ying.wei@ntu.edu.sg`
`yongweiw@ece.ubc.ca, {zhihua.wang, feiwu}@zju.edu.cn`

Abstract

Retrosynthetic planning is a sequential decision-making process of identifying synthetic routes from the available building block materials to reach a desired target molecule. Though existing planning approaches show promisingly high solving rates and route qualities, the trivial route quality evaluation via pre-trained forward reaction prediction models certainly falls short of real-world chemical practice. An alternative option is to annotate the actual quality of a route, such as yield, through chemical experiments or input from chemists, but this often leads to substantial query costs. In order to strike the balance between query costs and route quality evaluation, we propose an Active Retrosynthetic Planning (ARP) framework that remains compatible with the established retrosynthetic planners. On one hand, the proposed ARP trains an actor that decides whether to query the quality of a reaction; on the other hand, it resorts to a critic to estimate the value of a molecule with its preceding reaction quality as input. Those molecules with high reaction qualities are preferred to expand first. We apply our framework to different existing approaches on both the benchmark and an expert dataset and demonstrate that it outperforms the existing state-of-the-art approach by 6.2% in route quality while reducing the query cost by 12.8%. In addition, ARP consistently plans high-quality routes with either abundant or sparse annotations.

1 Introduction

Planning a retrosynthetic route is a central challenge in organic synthesis, requiring the break-down of a target molecule into available building block materials through a sequence of reactions. This process comprises two main components: (1) single-step reaction prediction predicting feasible reactions in a single step, (2) multi-step planning recursively selecting optimal molecules and reactions across multiple steps, where evaluating and ranking routes are of pivotal importance in shaping the planning policy. Previous efforts on multi-step planning have focused on quickly accessing building block materials in a limited number of single-step calls, resulting in an up to a 99.47% success rate Xie et al. (2022) on specific benchmarks. Regrettably, this emphasis on evaluating search aspects overlooks the chemical practicability of planned routes, i.e., whether a route is quality-effective in practice. For example, there is a short but low-quality route in Fig. 1. The crux revolves around the definition of reaction quality, which is simply the predictive probability of a reaction according to a pre-trained forward single-step prediction model in approaches such as Retro* Chen et al. (2020) and GRASP Yu et al. (2022). This single-step model is trained to predict feasibility rather

---

*These authors contributed equally to this work.
†Corresponding authors.

Figure 1: A short but low-quality route.

Figure 2: A low-quality route and a high-quality route. The low-quality reaction will lower the ceiling quality of the route. When selecting the next molecules towards high-quality routes, their preceding reaction qualities are associated consideration.

than the quality of reactions, thereby being biased towards highly feasible and frequent reactions instead of those with high qualities. An analysis illustrate this issue in Appendix B. The ideal reaction qualities that meet real-world chemical practicability, e.g., yield of a reaction, can be either annotated experimentally in a laboratory or by experienced chemists. Yet, annotating each reaction requires labor-intensive lab verification or expert annotations, compounded by the task of soliciting qualities for all reactions along a retrosynthetic route with route lengths ranging from 2.0 to 8.0(Yu et al. (2022),Liu et al. (2023a)). As verifying every reaction quality in the lab causes time delays and hinders automation, a quality metric is required which is expensive but not prohibitively so. In the real-life scenarios, such as online softwares like SYNTHIA(Lin et al. (2023)), it is an ideal candidate to integrate chemists into the AI planning process. Online annotations by chemists not only introduce minimal time delays and manageable labor costs, but also contribute valuable insights beyond mere reaction yields, such as toxicity, material costs, and work-up difficulty.

We are motivated to pursue a framework that strikes a balance between enhancing practical planning performance and minimizing annotation costs. The core idea of the proposed reinforcement learning-based Active Retrosynthetic Planning (ARP) framework constitutes an actor that decides whether to query the quality of a reaction or not and a critic that evaluates whether to expand a molecule or not. Concretely, the actor takes the current reaction as input; observing in Fig. 2 that a molecule with a high preceding reaction quality should be prioritized to expand first, the critic takes both the current molecule and its preceding reaction quality as input. It is noteworthy that the estimated molecule values by existing retrosynthetic planning methods can also be readily incorporated into our critic network. The critic network predicts a value that reflects the molecule's synthesizability together with the expectation of initializing a high-quality route. Simultaneously, the actor is trained to make the decision regarding the quality-effectiveness of querying for the annotated reaction qualities. Since querying for the reaction quality is a non-trivial task that induces an additional cost during annotation, we enforce a query cost to be paid whenever a query decision is made by the model. Given the diverse referential values of different reaction qualities during planning, we dynamically adjust the query cost to enhance the model's capability of identifying those reactions whose query results prove to be most quality-effective, thereby addressing the trade-off issue between query cost and the planning quality. The key contributions of our paper are outlined below. (1) *Practical efficacy:* we, for the first time, draw an insight into the disappointing practicality of existing retrosynthetic planners that regard single-step probabilities as reaction qualities. The ARP framework addresses the issue and improves quality of planned routes by 6.2% on a benchmark and by 4.9% on an annotated dataset. (2) *Generality:* The ARP framework is also compatible with arbitrary off-the-shelf planners and further boosts their chemical practicability.

Figure 3: Our actor-critic framework. The actor receives the reaction candidates and outputs query decisions. The critic receives molecules along with preceding reaction qualities and outputs the estimated values. A pretrained offline estimator can be incorporated with the critic of architecture **A**. When training an online estimator with the critic simultaneously, ARP utilizes a simplified critic architecture variant **B**.

2 RELATED WORK

Single-step prediction Existing single-step methods can be divided into three main categories, template-based, template-free, and semi-template-based. Template-based methods pre-define reaction transformations as templates and select appropriate template candidates (Coley et al. (2017), Segler & Waller (2017), Dai et al. (2019), Chen & Jung (2021), Xie et al. (2023)). Template-free methods predict the reactants in the representation of SMILES sequences(Schwaller et al. (2019), Zhong et al. (2022)) or molecular graphs (Sacha et al. (2021)). Semi-template-based methods decompose the task into two stages, center identification, and synthon completion (Shi et al. (2020), Yan et al. (2020), Somnath et al. (2020)). Chen & Jung (2021) solves the identify-and-complete processes into a local template prediction through a global attention mechanism. Furthermore, Xie et al. (2023) address the issue that fxed parameters might be sub-optimal by the robust non-parametric local reaction template retrieval. Zhong et al. (2022) fixes the problem that SMILES neglects the characteristics of molecular graph topology and reaction atom transformations. Yu et al. (2023) sorts out two types of distribution shifts in retrosynthesis prediction.

Multi-step planning Lin et al. (2020) takes advantage of a single-step seq2seq model and Ishida et al. (2022) further introduces domain knowledge to guide the search direction. Chen et al. (2020) designs a neural-based A*-like algorithm. Rather than a tree-search policy, Xie et al. (2022) proposes to combine a graph-based search policy with the traditional A* algorithm. Kim et al. (2021b) perform two self-improved iteration algorithms to imitate successful trajectories and find an optimal search policy. Afterward, Yu et al. (2022) is capable of biasing the retrosynthetic planning toward a favorable goal prescribed by chemists. Schreck et al. (2019) and Liu et al. (2023a) consider the cost for each reaction as a uniform 1 and optimize towards shortest routes. However, a short route might have a lower yield than a long route. Liu et al. (2023b) introduces a novel multi-step planning approach via in-context learning, departing from conventional search algorithms. However, the primary objective of Liu et al. (2023a) and Liu et al. (2023b) is still evaluating success rates of planned routes. They do not consider the real-world reaction qualities. Tripp et al. (2023), which shares a comparable motivation with ours, addresses the uncertainty of the stochastic retrosynthetic planning processes and focuses on finding several routes to complement their respective shortcomings. The methodologies above require the annotation of costs for every reaction along a route. In the pursuit of incorporating reliable reaction qualities derived from chemists or lab experimentation, which entail significant costs, these methods tend to be economically impractical for real-world deployment.

3 METHODS

3.1 ACTIVE RETROSYNTHETIC PLANNING MDP

In our work, we consider the active retrosynthetic planning scenario modeled as a Markov decision process (MDP), represented by $M = \{S, (A^r, A^q), \mathcal{P}, \mathcal{R}, c\}$. Specifically, S denotes the state space comprising chemical molecules, A^r refers to the action space of candidate reactions, and $A^q = \{0, 1\}$ represents the action space for query decisions. At time step t, given a molecule state s_t, the agent opts for a decision through a basic action pair (a_t^r, a_t^q), where a_t^r denotes a candidate reaction and a_t^q indicates the agent's decision to query (or not) for the annotated reaction quality. The agent observes the reaction quality u_t of a_t^r only if $a_t^q = 1$. The $\mathcal{P}$ represents the deterministic state transition function from s_t to s_{t+1} via execution of reaction a_t^r. $\mathcal{R}$ denotes our reward function and c is the constant query cost. Contrary to prior studies that employed a binary reward function (yielding a reward of 1 if the reaction reaches the building block materials, and 0 otherwise), this work associates the successful reward with both route quality and the query cost, as outlined in Eq. 1.

$$\mathcal{R}(s, a^r, a^q) = \begin{cases} \dfrac{\lambda + u}{\lambda + 1} - N_q c & if \ a^r \ \text{reach} \ I \\ 0 & \text{otherwise} \end{cases} \tag{1}$$

I denotes the building block materials. c^r represents the route quality, defined as the cumulative product of reaction qualities $\prod_{t=0} u_t$. Both route and reaction qualities fall within the interval $[0, 1]$. N_q is the number of the annotated reactions, calculated by $\sum_{t=0} a_t^q$. λ is a hyperparameter employed to stabilize the training when the agent obtains a success route with extremely small u.

3.2 MODEL FRAMEWORK AND TRAINING PROCEDURE

We employ an actor-critic framework for the approach. Given a reaction a^r, the actor $\pi_\phi \colon A^r \to A^q$ is responsible for making a query decision a^q, determining whether to query the reaction quality u or not. The observation function $\mathcal{O}$ transforms the reaction and the query action to a d^M-dimensional embedding of the reaction qualities as expressed in Eq. 2. We use a binning strategy $\mathcal{B}$ to discretize the continuous reaction quality values into N^M buckets and obtain the associated bucket embedding. The bins are constructed in order to cover a similar amount of reactions individually. In addition, we regard $\mathbb{M}$ as a separate bucket embedding. Details are given in Appendix C

$$\mathcal{O}(a^r, a^q) = \begin{cases} \mathcal{B}(u) & if \ a^q = 1 \\ \mathbb{M} & if \ a^q = 0 \end{cases} \tag{2}$$

For a given molecule s with its corresponding reaction quality u, the critic $Q_\theta(s, u)$ estimates the value of s. The predicted values are used to access the value of the next state selection during RL roll-outs. To integrate existing retrosynthetic planners, a standard molecule estimator $\mathcal{E} \colon S \to \mathbb{R}$ is assumed within existing algorithms, whose task is to evaluate the values of molecules within their specific search frameworks. As summarized in Appendix A, existing methods can be roughly divided into offline and online categories. Offline methods, such as neural-based A* search in Chen et al. (2020) and Somnath et al. (2020), train the estimator on the extracted routes from the publicly available reaction databases in an offline manner, including the United States Patent Office (USPTO) or Pistachio(Mayfield et al. (2017)). In contrast, online methods such as Yu et al. (2022) leverage routes generated by online roll-outs. We design the critic network $Q_\theta(\mathcal{E}(s), u) = READOUT(\mathcal{E}(s), u)$ as architecture A shown in Fig. 3. In this design, arbitrary pretrained offline planners can be seamlessly integrated into the critic. Additionally, online planners can be trained simultaneously with ARP training, simplifying the critic architecture to architecture B in Fig. 3.

Algorithm 1: Training algorithm

Initialize the estimator $\mathcal{E}$, the actor policy π_ϕ, the critic value function Q_θ, the initial state s_0

for $t=0$ **to** T **do**

> Observe reaction action space $\{a_i^r\}_{i=1}^k$ of s_t from environment
> Make query decisions $\{a_i^q\}_{i=1}^k$ and observe reaction qualities $\{u_i = \mathcal{O}(a_i^r, a_i^q)\}_{i=1}^k$
> Observe the next step states $\{s_{t+1}^i\}_{i=1}^k$
> Select the next state s_{t+1} by $\arg\max_{1 \le i \le k} Q_\theta(\mathcal{E}(s_{t+1}^i), u_i)$
> Compute reward $r_t = \mathcal{R}(s_t, a_t^r, a_t^q)$
> Append $(s_t, u_{t-1}, (a_t^r, a_t^q), r_t, s_{t+1})$ to the buffer

end

Update π_ϕ and Q_θ by Eq. 3 and Eq. 4

Such synergistic optimization not only conserves training resources for route collection but also substantially enhances both the solving rate and route quality compared in comparison to the two-stage training process.

At time step t, the agent observes state s_t along with a batch of reaction candidates $\{a_i^r\}_{i=1}^k$. The actor chooses query actions $\{a_i^q\}_{i=1}^k$ and observes the corresponding reaction qualities $\{u_i = \mathcal{O}(a_i^r, a_i^q)\}_{i=1}^k$. Subsequently, the respective next states $\{s_{t+1}^i\}_{i=1}^k$ of reaction candidates are obtained by employing the state transition function P. The next state s_{t+1} is then selected with the critic by $\arg\max_{1 \le i \le k} Q_\theta(\mathcal{E}(s_{t+1}^i), u_i)$. This comprises a complete step for executing a single step roll-outs, and a step reward $r_t = \mathcal{R}(s, a^r, a^q)$ is determined by the reward function in Eq. 1. The training procedure performs recursive roll-outs to collect trajectories for training and terminates each roll-out whenever it reaches dead/building-block molecules or maximum depth. We store the transition tuple $(s_t, u_{t-1}, (a_t^r, a_t^q), r_t, s_{t+1})$ into the replay buffer for training.

The actor-critic framework is trained using the TD3 algorithm. The target critic network is updated through the one-step TD equation where Q' and π' denote the target critic and actor networks, respectively, which is initialized using the same parameter from the main critic and actor networks Q_θ and π_ϕ but updated through an asynchronous manner. Utilizing the TD target y_i, the mean square error loss across the batch is computed for the original critic network Q_θ as follows:

$$y^{td} = r_t + \gamma Q'(\mathcal{E}(s_{t+1}), \mathcal{O}(a_t^r, \pi'(a_t^r))) \qquad L(\theta) = \frac{1}{N}\sum_i (y^{td} - Q_\theta(\mathcal{E}(s_t), u_{t-1})) \tag{3}$$

Given the actor's objective is aligned toward maximizing the total return, and the critic network aims to approximate this cumulative return, the actor π_ϕ is trained by maximizing the Q-value, which is achieved through the minimization of loss in Eq. 4. If $\mathcal{E}$ is an offline estimator such as the value estimator in Retro*, it is trained before implementation in our framework. The parameters of $\mathcal{E}$ are frozen and not evolved in training of the critic and $\mathcal{E}' = \emptyset$. If $\mathcal{E}$ is an online estimator, it can be regarded as part of the critic parameters and is wrapped with the other critic parameters for training and $\mathcal{E}' = \mathcal{E}$. The algorithm is summarized in Algorithm 1.

$$L(\phi, \mathcal{E}') = -\frac{1}{N}\sum_i (-Q_\theta(\mathcal{E}(s_t), \mathcal{O}(a_t^r, \pi_\phi(a_t^r)))) \tag{4}$$

3.3 Inference Procedure for Active Retrosynthetic Search

This section demonstrates the inference procedure for planning with partial observation of reaction qualities. In the inference stage, the reaction qualities are annotated by either a surrogate model or a chemist expert. We combine the actor π_θ and the critic Q_θ into the Monte-Carlo tree search (MCTS) on the AND-OR search

Figure 4: The active inference procedure. The active retrosynthetic search comprises three steps: selection, expansion, and update. Firstly, the planner selects a leaf molecule node with the maximum Q^* value. Secondly, the selected node is expanded with an AND-OR stump, and $\pi_\phi(a^r)$ decides whether the new reaction node has an annotated reaction quality. Finally, update Q^* of all nodes along the pathway.

tree. The molecule nodes are 'OR' nodes and the reaction nodes are 'AND' nodes. Moreover, we define a non-building block molecule node to be expandable when it is a leaf node or has an expandable child reaction node. None of the building block molecule nodes are expandable. A reaction node is expandable when there is any expandable child molecule node and none of the children are dead nodes. Molecule nodes are dead when they reach the maximum horizon or there are no reactions proposed by the single-step model. Let $ch(\cdot|T)$ denote the expandable children nodes of a molecule or reaction node.

There are three steps for each rollout during the active retrosynthetic search: selection, expansion, and update. A function $Q^*(s_t, a_t^r)$ in Eq. 5 presents the molecule synthesizability involves exploration. We use a UCT(Upper Confidence Bound applied to Trees) function(Kocsis et al. (2006)) to balance between exploitation of the route with the maximum Q and exploration of those less frequently visited routes. β is a hyper-parameter. $Q(s_t, a_t^r)$ is a value initialized by $Q_\theta(s_{t+1}, \mathcal{O}(a_t^r, \pi_\phi(a_t^r)))$ and updated afterward. A visit count number is denoted by $N(s, a^r)$ and initialized as 1.

$$Q^*(s_t, a_t^r) = Q(s_t, a_t^r) + \beta \frac{\sqrt{N(s_{t-1}, a_{t-1}^r)}}{1 + N(s_t, a_t^r)} \tag{5}$$

Selection The search tree T starts with a single target root molecule node s_0. We recursively perform a reaction action selection $a_t^r = \arg\max_{a^r \in ch(s_t|T)} Q^*(s_t, a^r)$ and obtain the next state s_{t+1} by transition function $\mathcal{P}$ until reaching a leaf molecule node.

Expansion In the expansion step, we expand an AND-OR stump under the selected molecule node s_t by referring to the single-step model. Every candidate reaction proposed is appended as a child reaction node of s_t. For a newly generated reaction node a_t^r, we assign its reaction quality observation by $\mathcal{O}(a_t^r, \pi_\phi(a_t^r))$. Each newly generated reaction node then expands children with the reactant molecule nodes.

Update During the update step, we perform $Q(s_t, a_t^r)$ values and visit counts $N(\cdot|T)$ backward traversal following the path from the selected leaf node back to the root node. Q' is the Q values of newly added state-action pairs. We use a simple moving average for the update with a discount factor γ by Eq. 6.

$$Q'(s_t, a_t^r) = Q(s_t, a_t^r) + \frac{1}{N(s_t, a_t)}(\gamma Q' - Q(s_t, a_t^r)) \qquad N'(s_t, a_t^r) = N(s_t, a_t^r) + 1 \tag{6}$$

ALGORITHM	BENCHMARK TEST SET			EXPERT TEST SET		
	SUCCESS RATE ↑	QUERY RATE ↓	NORMALIZED ROUTE QUALITY ↑	SUCCESS RATE ↑	QUERY RATE ↓	NORMALIZED ROUTE QUALITY ↑
HGSEARCH	36.5%	100%	0.518	49.0%	100%	0.550
RETRO*-0	44.9%	100%	0.644	57.3%	100%	0.765
RETRO*	53.4%	100%	0.705	60.9%	100%	0.787
RETRO*-0+	63.5%	100%	0.621	61.2%	100%	0.665
RETRO*+	72.5%	100%	0.671	68.5%	100%	0.699
EG-MCTS-0	73.6%	100%	0.489	65.4%	100%	0.726
EG-MCTS	85.4%	100%	0.558	75.4%	100%	0.712
GRASP	86.0%	100%	0.602	79.5%	100%	0.666
RETRO*+ WITH ARP	73.0%	87.2%	**0.767**	74.3%	79.9%	0.821
GRASP WITH ARP	**86.5%**	83.4%	0.711	**80.6%**	90.8%	**0.836**

Table 1: Performance of baselines and our approach on the benchmark and expert datasets.

4 EXPERIMENTS

4.1 EXPERIMENT SETUP

Baselines. We compare solving rate and route quality against various open-source baselines including a beam-search-like algorithm guided hyper-graph search method **HgSearch**(Schwaller et al. (2020)), best-first A*-like algorithm guided AND-OR tree search methods **Retro* and Retro*-0**(Chen et al. (2020)), and an experience-guided MCTS-based method **EG-MCTS**(Hong et al. (2023)). We apply ARP on an offline algorithm **Retro*+**(Kim et al. (2021a)) and an online one: **GRASP**(Yu et al. (2022)). **Retro*+** is based on **Retro*** with a self-improved single-step retrosynthetic model. **GRASP** applies a goal-driven actor-critic RL agent. As all of the existing methods rely on the reaction quality for calculating the search heuristics, we set their default query rate to 100%. We change the resource of reaction qualities from the single-step probabilities to our reaction qualities when testing the baselines.

Materials and RL environment. We use two test sets to evaluate our methods. The first one is a widely used USPTO-50k benchmark dataset that has 178 hard molecules raised in Chen et al. (2020). However, the scale of the benchmark dataset is small. Therefore, we include an additional expert dataset that has 8000 molecules and each molecule has a literature reference route extracted by chemist experts. The expert dataset is designed to emphasize retrosynthetic strategies with more challenging but strategically similar molecules. We partition the expert dataset as 0.8/0.1/0.1 into train/valid/test sets. The training set is used as the target molecules. For the single-step retrosynthesis model, we use a similar template-based model in Chen et al. (2020) which is a 2-layer MLP using the Morgan fingerprint as input. We adopt the top-50 single-step reaction candidates and set the maximum number of single-step inference calls as 100. We use the commercially available molecules dataset $eMolecules$ as the building block materials. As for the hyper-parameters, we set the maximum route depth as 6 and λ in Eq. 1 as 4.

Reaction quality annotation Unfortunately, there is no established large-scale available reaction data set with respective reaction qualities or promising reaction performance, e.g. yield, prediction model(Jiang et al. (2022)), and both lab verification and expert annotations are expensive and time-consuming. We adopt a surrogate model to provide reaction quality annotations. Initially, the method in Guo et al. (2020) is employed to pre-train a model utilizing the USPTO-MIT dataset, followed by the fine-tuning of the model in reactions derived from the high-quality, expert-annotated dataset. Conceptually, the model, when trained on the expert-annotated dataset, prioritizes the identification of high-yield reactions over high-frequency reactions. More details about the training of surrogate model are in Appendix D. We provide an experiment to demonstrate a significant correlation between our surrogate model and reaction yields in Appendix E. Dur-

ESTIMATOR	QUERY COST	ACTOR + CRITIC			RANDOM + CRITIC		
		SUCCESS RATE ↑	QUERY RATE ↓	NORMALIZED ROUTE QUALITY ↑	SUCCESS RATE ↑	RANDOM RATE	NORMALIZED ROUTE QUALITY ↑
RETRO*+	-0.01	72.4%	100.0%	0.772	72.4%	100.0%	0.772
	0	73.0%	87.2%	0.767	69.7%	87.0%	0.744
	0.01	72.4%	63.6%	0.759	71.3%	64.0%	0.722
	0.05	71.9%	24.4%	0.702	71.9%	24.0%	0.699
	0.1	73.5%	0.0%	0.685	72.6%	0.0%	0.685
GRASP	0	85.4%	95.9%	0.713	86.0%	96.0%	0.708
	0.005	86.5%	83.4%	0.711	84.8%	83.0%	0.695
	0.01	85.4%	76.6%	0.709	85.4%	77.0%	0.683
	0.02	86.0%	13.4%	0.681	86.0%	13.0%	0.666
	0.05	85.4%	1.2%	0.654	86.0%	1.0%	0.650

Table 2: Experimental results of the active query capability on the benchmark test set.

ESTIMATOR	QUERY COST	ACTOR + CRITIC			RANDOM + CRITIC		
		SUCCESS RATE ↑	QUERY RATE ↓	NORMALIZED ROUTE QUALITY ↑	SUCCESS RATE ↑	RANDOM RATE	NORMALIZED ROUTE QUALITY ↑
RETRO*+	-0.01	73.1%	100.0%	0.830	73.1%	100.0%	0.830
	0	74.3%	79.9%	0.821	70.8%	80.0%	0.765
	0.01	71.2%	53.0%	0.790	72.6%	53.0%	0.739
	0.05	71.5%	12.5%	0.737	72.3%	12.0%	0.721
	0.1	74.5%	0.0%	0.722	73.1%	0.0%	0.722
GRASP	0	80.5%	100.0%	0.842	80.5%	100.0%	0.842
	0.005	80.6%	90.8%	0.836	79.5%	91.0%	0.772
	0.01	80.4%	85.4%	0.839	80.3%	85.0%	0.776
	0.02	79.8%	6.6%	0.749	80.9%	6.0%	0.733
	0.05	80.0%	0.0%	0.732	80.0%	0.0%	0.732

Table 3: Experimental results of the active query capability on the expert test set.

ing deployment, it is practical to replace the surrogate model with a chemist to provide online annotations, e.g. a coarse-grained quality rating from 0 to 10.

Evaluation metrics. We use three main metrics to comprehensively evaluate the performance of different search algorithms. 1. **Success rate**: The success rate is defined as the percentage of solved molecules in the entire test set. 2. **Query rate**: The query rate is defined as the percentage of reactions that are annotated with the reaction qualities in the inference stage. 3. **Normalized route quality:** Given a route, we compute the route quality by a cumulative product of reaction qualities. Both the reactions and route qualities range in $[0, 1]$ and a larger value refers to a higher quality, also a lower quality. We introduce the normalized route quality to evaluate the route quality performance. For each target molecule in the inference test set, we perform an exhaustive brute-force search in limited depth and acquire the maximum $u_{\max}$ and minimum route quality $u_{\min}$ for the success route. Especially, if there is only one successful route, we assume the single route quality as $u_{\min}$ and $u_{\max} = u_{\min} + 0.01$. We further define the normalized route quality as Eq. 7 of a route quality u to eliminate the impact of different target molecules.

$$\text{Quality}_{\text{norm}} = \frac{u_{\max} - u}{u_{\max} - u_{\min}} \tag{7}$$

4.2 RESULTS

Comparision with baselines The performance of all methods are presented in Table. 1. Concerning both the normalized route quality and the query rate metrics, our approach achieves the best performance on both datasets. The best existing method in the normalized route quality metric is identified as **Retro***. In the benchmark dataset, our approach outperforms **Retro*** by a margin of 6.2 %, while achieving a reduction in the query rate by 12.8%. Similarly, within the expert dataset, our approach outperforms **Retro*** by 4.9 % and lowers the query rate by 9.2%. Regarding the success rate, both **Retro*** and **GRASP** achieve a moderately higher success rate compared to the original results, primarily due to the influence of the preceding reaction quality as a potential molecular feature in predicting molecular synthesizability.

Active query capability We evaluate the performance of ARP for balancing the trade-off between the query costs and reaction qualities. In the context of the active query setting, the models are tested under diverse query cost settings. Intuitively, setting a high query cost is to simulate a sparse-annotated environment, compelling the planner to rely on less annotated reactions. Conversely, a near-zero query cost emulates an abundant-annotated setting. The experimental results on both the benchmark and expert datasets are listed in the left columns of Tab. 2 and Tab. 3, respectively. As we increase the query cost, we observe a decline in the query rate, which mildly impacts the success rate and normalized route quality. The phenomenon reflects that our approach is capable of actively selecting reactions that contribute most significantly to the reaction qualities in retrosynthetic planning. To further explore the active query capability of our approach, we conduct an ablation study where the planner chooses to query the reaction quality of a reaction with a fixed random rate p as Eq. 8 instead of employing the trained actor-network for making query decisions.

$$a_i^q \leftarrow \begin{cases} 1 & p \\ 0 & 1-p \end{cases} \tag{8}$$

We adjust the fixed probability p as the same query rate obtained from the baseline result under varied query cost settings in order to eliminate the confounding effect of different query numbers. The results are listed in the right columns of Tab. 2 and Tab. 3 and demonstrate that the actor adeptly selects the most informative reactions to enhance the planning performance. As the random rate p escalates, the critic can utilize more annotated reactions, improving the precision of value estimation and, thereby, optimizing the search process toward discovering routes with higher quality. We observe that the success rate does not increase monotonically with the query rate. Optimizing the success rate and the route quality together can lead to certain trade-offs, as demonstrated by a case study in Appendix F. Additionally, the actor is specifically trained to identify and query the most informative reactions in order to achieve a higher route quality. As a result, when the trade-off appears between the success rate and the route quality, the actor+critic approach might not improve but suppress the success rate when compared to the random+critic baseline.

5 CONCLUSION

The paper proposed ARP, a novel retrosynthetic planning framework aware of the route quality. Unlike existing approaches using a labor-free but trivial reaction evaluation which is biased to the high-frequent reactions, ARP adopts a route-quality evaluation approach aware of chemical practicability Moreover, there exists a trade-off between enhancing the planning performance and saving the query costs of acquiring reaction and is able to perform an active selection of the most informative reactions to observe their reaction qualities. Experimental results demonstrate ARP's capability of capturing high-quality routes under either abundant or sparse-annotation environments.

6 ACKNOWLEDGEMENT

This work is funded by National Natural Scientific Foundation of China (No. 62037001), the Starry Night Science Fund at Shanghai Institute for Advanced Study (Zhejiang University) and Shanghai AI Laboratory.

REFERENCES

Colin Bellinger, Rory Coles, Mark Crowley, and Isaac Tamblyn. Active measure reinforcement learning for observation cost minimization. *CoRR*, abs/2005.12697, 2020. URL https://arxiv.org/abs/2005.12697.

Binghong Chen, Chengtao Li, Hanjun Dai, and Le Song. Retro*: Learning retrosynthetic planning with neural guided a* search. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 1608–1616. PMLR, 13–18 Jul 2020. URL https://proceedings.mlr.press/v119/chen20k.html.

Shuan Chen and Yousung Jung. Deep retrosynthetic reaction prediction using local reactivity and global attention. *JACS Au*, 1(10):1612–1620, 2021. doi: 10.1021/jacsau.1c00246. URL https://doi.org/10.1021/jacsau.1c00246. PMID: 34723264.

Paul Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences, 2023.

Connor W. Coley, Luke Rogers, William H. Green, and Klavs F. Jensen. Computer-assisted retrosynthesis based on molecular similarity. *ACS Central Science*, 3(12):1237–1245, 2017. doi: 10.1021/acscentsci.7b00355. URL https://doi.org/10.1021/acscentsci.7b00355. PMID: 29296663.

Hanjun Dai, Chengtao Li, Connor W. Coley, Bo Dai, and Le Song. *Retrosynthesis Prediction with Conditional Graph Logic Network*. Curran Associates Inc., Red Hook, NY, USA, 2019.

Christian Daniel, Malte Viering, Jan Metz, Oliver Kroemer, and Jan Peters. Active reward learning. In *Proceedings of Robotics: Science and Systems (RSS '14)*, July 2014.

Zhongliang Guo, Stephen Wu, Mitsuru Ohno, and Ryo Yoshida. Bayesian algorithm for retrosynthesis. *Journal of Chemical Information and Modeling*, 60(10):4474–4486, 2020. doi: 10.1021/acs.jcim.0c00320. URL https://doi.org/10.1021/acs.jcim.0c00320. PMID: 32975943.

Siqi Hong, Hankz Hankui Zhuo, Kebing Jin, Guang Shao, and Zhanwen Zhou. Retrosynthetic planning with experience-guided Monte Carlo tree search. *Communications Chemistry*, 6(1):120, June 2023. ISSN 2399-3669. doi: 10.1038/s42004-023-00911-8. URL https://doi.org/10.1038/s42004-023-00911-8.

Shoichi Ishida, Kei Terayama, Ryosuke Kojima, Kiyosei Takasu, and Yasushi Okuno. Ai-driven synthetic route design incorporated with retrosynthesis knowledge. *Journal of Chemical Information and Modeling*, 62(6):1357–1367, 2022. doi: 10.1021/acs.jcim.1c01074. URL https://doi.org/10.1021/acs.jcim.1c01074. PMID: 35258953.

Yinjie Jiang, Yemin Yu, Ming Kong, Yu Mei, Luotian Yuan, Zhengxing Huang, Kun Kuang, Zhihua Wang, Huaxiu Yao, James Zou, Connor W. Coley, and Ying Wei. Artificial intelligence for retrosynthesis prediction. *Engineering*, 2022. ISSN 2095-8099. doi: https://doi.org/10.1016/j.eng.2022.04.021. URL https://www.sciencedirect.com/science/article/pii/S2095809922005665.

Junsu Kim, Sungsoo Ahn, Hankook Lee, and Jinwoo Shin. Self-improved retrosynthetic planning. *CoRR*, abs/2106.04880, 2021a. URL https://arxiv.org/abs/2106.04880.

Junsu Kim, Sungsoo Ahn, Hankook Lee, and Jinwoo Shin. Self-improved retrosynthetic planning. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 5486–5495. PMLR, 18–24 Jul 2021b. URL https://proceedings.mlr.press/v139/kim21b.html.

W. Bradley Knox and Peter Stone. Interactively shaping agents via human reinforcement: The tamer framework. In *Proceedings of the Fifth International Conference on Knowledge Capture*, K-CAP '09, pp. 9–16, New York, NY, USA, 2009. Association for Computing Machinery. ISBN 9781605586588. doi: 10.1145/1597735.1597738. URL https://doi.org/10.1145/1597735.1597738.

Levente Kocsis, Csaba Szepesvari, and Jan Willemson. Improved monte-carlo search. 2006. URL https://api.semanticscholar.org/CorpusID:9831567.

David Krueger, Jan Leike, Owain Evans, and John Salvatier. Active reinforcement learning: Observing rewards at a cost. *CoRR*, abs/2011.06709, 2020. URL https://arxiv.org/abs/2011.06709.

Kangjie Lin, Youjun Xu, Jianfeng Pei, and Luhua Lai. Automatic retrosynthetic route planning using template-free models. *Chem. Sci.*, 11:3355–3364, 2020. doi: 10.1039/C9SC03666K. URL http://dx.doi.org/10.1039/C9SC03666K.

Yingfu Lin, Rui Zhang, Di Wang, and Tim Cernak. Computer-aided key step generation in alkaloid total synthesis. *Science*, 379(6631):453–457, 2023. doi: 10.1126/science.ade8459. URL https://www.science.org/doi/abs/10.1126/science.ade8459.

Guoqing Liu, Di Xue, Shufang Xie, Yingce Xia, Austin Tripp, Krzysztof Maziarz, Marwin Segler, Tao Qin, Zongzhang Zhang, and Tie-Yan Liu. Retrosynthetic planning with dual value networks, 2023a.

Songtao Liu, Zhengkai Tu, Minkai Xu, Zuobai Zhang, Lu Lin, Rex Ying, Jian Tang, Peilin Zhao, and Dinghao Wu. Fusionretro: Molecule representation fusion via in-context learning for retrosynthetic planning, 2023b.

John Mayfield, Daniel Lowe, and Roger Sayle. Pistachio: Search and faceting of large reaction databases. In *ABSTRACTS OF PAPERS OF THE AMERICAN CHEMICAL SOCIETY*, volume 254. AMER CHEMICAL SOC 1155 16TH ST, NW, WASHINGTON, DC 20036 USA, 2017.

Mikohaj Sacha, Mikolaj Blaz, Piotr Byrski, Pawel Dabrowski-Tumanski, Mikolaj Chrominski, Rafal Loska, Pawel Wlodarczyk-Pruszynski, and Stanislaw Jastrzebski. Molecule edit graph attention network: Modeling chemical reactions as sequences of graph edits. *Journal of Chemical Information and Modeling*, 61(7):3273–3284, 2021. doi: 10.1021/acs.jcim.1c00537. URL https://doi.org/10.1021/acs.jcim.1c00537. PMID: 34251814.

William Saunders, Girish Sastry, Andreas Stuhlmüller, and Owain Evans. Trial without error: Towards safe reinforcement learning via human intervention. In *Proceedings of the 17th International Conference on Autonomous Agents and MultiAgent Systems*, AAMAS '18, pp. 2067–2069, Richland, SC, 2018. International Foundation for Autonomous Agents and Multiagent Systems.

John S. Schreck, Connor W. Coley, and Kyle J. M. Bishop. Learning retrosynthetic planning through simulated experience. *ACS Central Science*, 5(6):970–981, 2019. doi: 10.1021/acscentsci.9b00055. URL https://doi.org/10.1021/acscentsci.9b00055. PMID: 31263756.

Sebastian Schulze and Owain Evans. Active reinforcement learning with monte-carlo tree search. *CoRR*, abs/1803.04926, 2018. URL http://arxiv.org/abs/1803.04926.

Philippe Schwaller, Teodoro Laino, Théophile Gaudin, Peter Bolgar, Christopher A. Hunter, Costas Bekas, and Alpha A. Lee. Molecular transformer: A model for uncertainty-calibrated chemical reaction prediction. *ACS Central Science*, 5(9):1572–1583, 2019. doi: 10.1021/acscentsci.9b00576. URL https://doi.org/10.1021/acscentsci.9b00576. PMID: 31572784.

Philippe Schwaller, Riccardo Petraglia, Valerio Zullo, Vishnu H. Nair, Rico Andreas Haeuselmann, Riccardo Pisoni, Costas Bekas, Anna Iuliano, and Teodoro Laino. Predicting retrosynthetic pathways using transformer-based models and a hyper-graph exploration strategy. *Chem. Sci.*, 11:3316–3325, 2020. doi: 10.1039/C9SC05704H. URL http://dx.doi.org/10.1039/C9SC05704H.

Philippe Schwaller, Alain C Vaucher, Teodoro Laino, and Jean-Louis Reymond. Prediction of chemical reaction yields using deep learning. *Machine Learning: Science and Technology*, 2(1):015016, mar 2021. doi: 10.1088/2632-2153/abc81d. URL https://dx.doi.org/10.1088/2632-2153/abc81d.

Marwin H. S. Segler and Mark P. Waller. Neural-symbolic machine learning for retrosynthesis and reaction prediction. *Chemistry – A European Journal*, 23(25):5966–5971, 2017. doi: https://doi.org/10.1002/chem.201605499. URL https://chemistry-europe.onlinelibrary.wiley.com/doi/abs/10.1002/chem.201605499.

Chence Shi, Minkai Xu, Hongyu Guo, Ming Zhang, and Jian Tang. A graph to graphs framework for retrosynthesis prediction. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 8818–8827. PMLR, 13–18 Jul 2020. URL https://proceedings.mlr.press/v119/shi20d.html.

Vignesh Ram Somnath, Charlotte Bunne, Connor W. Coley, Andreas Krause, and Regina Barzilay. Learning graph models for template-free retrosynthesis. *CoRR*, abs/2006.07038, 2020. URL https://arxiv.org/abs/2006.07038.

Kaushik Subramanian, Charles L. Isbell, and Andrea L. Thomaz. Exploration from demonstration for interactive reinforcement learning. In *Proceedings of the 2016 International Conference on Autonomous Agents & Multiagent Systems*, AAMAS '16, pp. 447–456, Richland, SC, 2016. International Foundation for Autonomous Agents and Multiagent Systems. ISBN 9781450342391.

Austin Tripp, Krzysztof Maziarz, Sarah Lewis, Marwin Segler, and José Miguel Hernández-Lobato. Retro-fallback: retrosynthetic planning in an uncertain world, 2023.

Garrett Warnell, Nicholas Waytowich, Vernon Lawhern, and Peter Stone. Deep tamer: Interactive agent shaping in high-dimensional state spaces. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence and Thirtieth Innovative Applications of Artificial Intelligence Conference and Eighth AAAI Symposium on Educational Advances in Artificial Intelligence*, AAAI'18/IAAI'18/EAAI'18. AAAI Press, 2018. ISBN 978-1-57735-800-8.

Shufang Xie, Rui Yan, Peng Han, Yingce Xia, Lijun Wu, Chenjuan Guo, Bin Yang, and Tao Qin. Retrograph: Retrosynthetic planning with graph search. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, KDD '22, pp. 2120–2129, New York, NY, USA, 2022. Association for Computing Machinery. ISBN 9781450393850. doi: 10.1145/3534678.3539446. URL https://doi.org/10.1145/3534678.3539446.

Shufang Xie, Rui Yan, Junliang Guo, Yingce Xia, Lijun Wu, and Tao Qin. Retrosynthesis prediction with local template retrieval, 2023.

Chaochao Yan, Qianggang Ding, Peilin Zhao, Shuangjia Zheng, Jinyu Yang, Yang Yu, and Junzhou Huang. Retroxpert: Decompose retrosynthesis prediction like a chemist. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS'20, Red Hook, NY, USA, 2020. Curran Associates Inc. ISBN 9781713829546.

Yemin Yu, Ying Wei, Kun Kuang, Zhengxing Huang, Huaxiu Yao, and Fei Wu. Grasp: Navigating retrosynthetic planning with goal-driven policy. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 10257–10268. Curran Associates, Inc., 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/file/42beaab8aa8da1c77581609a61eced93-Paper-Conference.pdf.

Yemin Yu, Luotian Yuan, Ying Wei, Hanyu Gao, Xinhai Ye, Zhihua Wang, and Fei Wu. Retroood: Understanding out-of-distribution generalization in retrosynthesis prediction, 2023.

Zipeng Zhong, Jie Song, Zunlei Feng, Tiantao Liu, Lingxiang Jia, Shaolun Yao, Min Wu, Tingjun Hou, and Mingli Song. Root-aligned smiles: a tight representation for chemical reaction prediction. *Chem. Sci.*, 13:9023–9034, 2022. doi: 10.1039/D2SC02763A. URL http://dx.doi.org/10.1039/D2SC02763A.