Improving Complex Reasoning with Dynamic Prompt Corruption: A soft prompt Optimization Approach

Abstract

Prompt-tuning (PT) for large language models (LLMs) can facilitate the performance on various conventional NLP tasks with significantly less trainable parameters, however, our investigation reveals that PT provides limited improvement and may even degrade the primitive performance of LLMs on complex reasoning tasks. Such a phenomenon suggests that soft prompts can positively impact certain instances while negatively affecting others, particularly during the later phases of reasoning. To address these challenges, We first identify an information accumulation within the soft prompt. Through detailed analysis, we demonstrate that this phenomenon is often accompanied by erroneous information flow patterns in the deeper layers of the model, which ultimately lead to incorrect reasoning outcomes. we propose a novel **D**ynamic **P**rompt **C**orruption (DPC) to take better advantage of soft prompts in complex reasoning tasks, which dynamically adjusts the influence of soft prompts based on their impact on the reasoning process. Specifically, it consists of two stages: Dynamic Trigger and Dynamic Corruption. First, Dynamic Trigger measures the impact of soft prompts, identifying whether beneficial or detrimental. Then, Dynamic Corruption mitigates the negative effects of soft prompts by selectively masking key tokens that interfere with the reasoning process. We validate the proposed approach through extensive experiments on various LLMs and reasoning tasks, including GSM8K, MATH, and AQuA. Experimental results demonstrate that DPC can consistently enhance the performance of PT, achieving 4%-8% accuracy gains compared to vanilla prompt tuning, highlighting the effectiveness of our approach and its potential to enhance complex reasoning in LLMs.

1 Introduction

Prompt Tuning (PT) (Lester et al., 2021a) as a promising parameter-efficient fine-tuning (PEFT) approach demands very few trainable continuous prompt vectors to the input, achieving competitive performance compared to the full-parameter fine-tuning Qin et al. (2021); Ding et al. (2023a). Previous efforts have demonstrated the superiority of the PT by generating high-quality soft prompts Shi & Lipani (2024); Yang et al. (2023); Qin et al. (2024), nonetheless, soft prompting underperforms the foundation model on complex reasoning tasks. With a comprehensive investigation, we discover that vanilla prompt tuning provides little performance improvement on complex reasoning tasks and may even lead to negative performance outcomes.

From the perspective of instance, soft prompts may have positive effects for some instances while potentially posing a negative impact on others. Figure 1 illustrates an example from the GSM8K Cobbe et al. (2021):The model can answer the question correctly without a soft prompt, while a soft prompt guides the LLM to an incorrect answer by some intermediate reasoning steps. Therefore, it is crucial to determine whether the effect of soft prompts on reasoning is positive or negative. However, understanding why certain reasoning succeeds while others fail is difficult.

To meet the challenge, we intend to explore the mechanism of soft prompt on the Chain-of-Thought (CoT) Wei et al. (2022) through a lens of information flow. Neuron saliency score analysis is an important tool for analyzing the information flow during LLM inference Dai et al. (2022); Wang et al. (2023a), allowing to probe the models' reasoning mechanism. After a comprehensive investigation across several LLMs and tasks, we find: *soft prompts lead to reaching the right answer when the latter reasoning steps put more emphasis on former tokens compared to soft tokens. In contrast, when the soft prompt significantly impacts the latter reasoning steps, the model may reach an incorrect answer.* This phenomenon revealed by neuron saliency score analysis is similar to the

Figure 1: Input the same question to guide the LLM to answer it. The model was originally able to provide the correct answer, but after adding the soft prompt, it produced an error in reasoning.

thinking process of human beings to some extent: humans always recall the background knowledge related to the question and then answer it. As a carrier of task-related knowledge Xiao et al. (2024) Yu et al. (2024), soft prompts can provide beneficial hints to help models understand the question and generate the initial reasoning steps, then use the question and generated steps to complete the answer. However, if the remaining reasoning steps still attend to the hints, i.e., soft prompt, it may conflict with the question and existing reasoning steps. Furthermore, we discover that soft prompt tokens in certain positions have a strong impact on reasoning, and we can suppress the negative effects of the soft prompt on reasoning by corrupting them.

Inspired by the above findings, we propose a novel two-stage method Dynamic Prompt Corruption (DPC): *Dynamic Trigger* and *Dynamic Corruption*. Concretely, in the 1st stage, we measure the impact factor of the soft prompt on the latter part of the reasoning in the final layer, by which we can differentiate whether the soft prompt can lead to the correct answer; in the 2nd stage, we locate the key token that influences both the question and reasoning steps most in shallow layers, then mitigate the negative impact with key token vector masking and other token sparse masking.

To validate our analysis and evaluate the proposed DPC, we conduct comprehensive experiments with multiple LLMs on various tasks. Experimental results show that the DPC can consistently improve the overall performance of LLMs such as LLaMA2-13B Touvron et al. (2023), LLaMA3-8B Dubey et al. (2024), and Mistral-0.2-7B Jiang et al. (2023) on various reasoning tasks with 4%-8% accuracy enhancement including GSM8K Cobbe et al. (2021), MATH Hendrycks et al. (2021), AQuA Ling et al. (2017) compared to pure prompt tuning, which is in line with our observation and demonstrate the effectiveness of our DPC. Our contributions can be summarized as follows:

- We investigate the relation between the information accumulation in the soft prompt and erroneous information flow patterns through saliency score analysis. Our findings indicate that when the soft prompt influences the later stages of reasoning deeply, the model is more likely to reach an incorrect answer.

- Based on the thorough analysis, we propose DPC, an instance-level prompt tuning optimization strategy, which can dynamically identify and mitigate the negative effects caused by the soft prompt.

- Experiment results manifest our proposed DPC can improve the vanilla prompt tuning for various LLMs on complex reasoning tasks to a large margin, demonstrating the effectiveness of our findings and the superiority of the proposed method.

2 INFORMATION FLOW ANALYSIS FOR SOFT PROMPT

As it is important to figure out the influential factors in CoT reasoning, we intend to analyze the model's inference process. An entire CoT reasoning instance comprises 3 primary components: the Prompt $\mathbf{P}$, the Question $\mathbf{Q}$, and the Rationale $\mathbf{R}$, therefore, we need to analyze the interactivity among these 3 objects with an appropriate tool. The saliency score is a common interpretative analysis tool that has been employed to study the interactions between tokens, which combine gradient and attention values and are particularly effective in analyzing the information flow between different components. This allows saliency to simultaneously reflect the relationships among various

(a) Saliency of layers   (b) Information accumulation

Figure 2: (a)Saliency scores of prompt-to-question, prompt-to-rationale layer by layer (b) illustrates a significant information accumulation phenomenon within the soft prompt. A specific token in the soft prompt conveys strong information to both the Question and the Rationale.

modules and their impact on the output. The saliency score is obtained by taking the Hadamard product of the attention scores $\mathbf{A}$ and its gradients as follows:

$$\mathbf{S} = \left| \sum_h \left(\mathbf{A}_{h,l} \odot \frac{\partial \mathcal{L}(x)}{\partial \mathbf{A}_{h,l}} \right) \right| \tag{1}$$

where $\mathbf{A}_{h,l}$ is the attention weight for the h-th head in layer l, $\odot$ denotes the Hadamard product, and $\mathcal{L}(x)$ is the loss function, which is the cross-entropy in our implementation. The attention matrix describes the interactions between different parts of the sequence, while the gradient indicates the direction of information transfer. Therefore, we can observe the information flow throughout the entire sequence during reasoning by analyzing the saliency score.

2.1 LAYER ANALYSIS

Popular LLMs are composed of multiple stacked Transformer layers, which have specific roles in processing information during model reasoning. To better quantify the interactions between distinct components, we define two metrics to measure the strength of information flow layer-wise:

$\mathbf{S}_{pq}$, **the average significance of information flow from the prompt to question:**

$$\mathbf{S}_{pq}^{(\ell)} = \frac{\sum_{(i,j) \in \mathbb{C}_{pq}} \mathbf{S}_\ell(i,j)}{|\mathbb{C}_{pq}|} \tag{2}$$

$$\mathbb{C}_{pq} = \{(i,j)| p_s \leq i \leq p_e, q_s \leq j \leq q_e\} \tag{3}$$

$\mathbf{S}_{pr}$, **the average significance of information flow from the prompt to rationale:**

$$\mathbf{S}_{pr}^{(\ell)} = \frac{\sum_{(i,j) \in C_{pr}} \mathbf{S}_\ell(i,j)}{|\mathbb{C}_{pr}|} \tag{4}$$

$$\mathbb{C}_{pr} = \{(i,j)| p_s \leq i \leq p_e, r_s \leq j \leq r_e\} \tag{5}$$

where $\mathbf{S}_\ell(i,j)$ represents the intensity of information flow from the i-th to j-th token, $|\mathbb{C}_{pq}|$ and $|\mathbb{C}_{pr}|$ are the number of interactions among prompt and question tokens, prompt and rationale tokens, respectively. p_s, q_s, and r_s are the start tokens of the question, prompt, and rationale, and p_e, q_e, and r_e are the end tokens, separately.

As shown in Figure 2a, we visualize the saliency scores during the LLM processing input across layers, sub-figures show the saliency scores representing the semantic information transfer between different input components: from the prompt to the question, and from the prompt to the rationale.

Figure 3: Schematic illustration of our observation.Correct-answer cases (left) show a balanced accumulation of saliency in shallow layers, where rationale information is evenly gathered from the soft prompt. As the reasoning progresses into deeper layers, attention shifts from the soft prompt to earlier rationale steps and the question itself. In contrast, wrong-answer cases (right) exhibit excessive saliency in shallow layers and disruptions in the information flow in deep layers. The latter part of the reasoning in deep layers overly focuses on the soft prompt, leading to incorrect answers.

We find that distinct peaks for $\mathbf{Q}$ and $\mathbf{R}$ related to the soft prompt $\mathbf{P}$ between layer 2 and layer 10, indicating that the most intense flow of prompt information aggregates in shallow layers (near the input). Furthermore, we need a fine-grained analysis of the information flow phenomenon in shallow layers to explore the underlying mechanisms more precisely.

Figure 2b illustrates the saliency matrix $\mathbf{S}$ of shallow layers during the reasoning, in which we observe a strong flow of information among $\mathbf{P}$, $\mathbf{Q}$, and $\mathbf{R}$ in certain instances, leading to an evident accumulation of information on a specific soft token. Such a phenomenon implies that certain specific soft tokens can have a significant impact on subsequent reasoning in some cases.

2.2 PROMPT TUNING ANALYSIS

After investigating a large number of instances, we find that in wrong-answer cases, the accumulation of saliency in the shallow layers is often accompanied by changes in the information flow pattern in the deep layers, as shown in Figure 3. In contrast, the reasoning of correct-answer cases can gather rationale information evenly from the soft prompt in shallow layers, while in deeper layers, the latter part of reasoning steps focuses on earlier rationale steps and the question rather than soft tokens. For incorrect examples, information accumulation happens in shallow layers, accompanied by changes in the deep information flow patterns: the latter part of the reasoning in deep layers overly focuses on the soft prompt, leading to incorrect answers.

2.2.1 WHAT IS THE RELATIONSHIP BETWEEN INFORMATION ACCUMULATION AND CHANGES IN INFORMATION FLOW PATTERNS?

We notice a potential correlation between information accumulation and changes in information flow patterns through visualization, nevertheless, the phenomenon in a few cases may not prove the universal pattern. In this part, we continue to explore the impact of information accumulation on the information flow pattern.

Setting The information accumulation can be interpreted as a specific token strongly influencing the subsequent reasoning process, and it is visible in the saliency matrix, where a distinct column effect can be observed. To explore the information accumulation, we compute the saliency scores with soft prompt token i to question and rationale:

$$S_{p_iqr}^{(\ell)} = \sum_{(j,i)\in C_{p_iqr}} S_\ell(j,i) \tag{6}$$

$$\mathbb{C}_{p_iqr} = \{(j,i)|q_s \leq j \leq r_e\} \tag{7}$$

(a) (b) (c)

Figure 4: (a) describes the relationship between information accumulation in shallow layers and the change of information flow patterns in deep layers. (b) illustrates the distribution of information flow intensity from the soft prompt to the latter part of the rationale in both good and bad cases. In good cases, the distribution tends to be weaker, while in bad cases, the distribution is stronger. (c) depicts the overall intensity of information flow from the soft prompt to the latter part of the rationale for both good and bad cases.

where $S_\ell(j, i)$ denotes the intensity of information flow from the j-th to the i-th token, q_s is the start tokens of the question and r_e is the end of rationale. When $I_{acc} = \{p_s \le i \le p_e \mid S_{p_i q r}^{(l)} > \alpha \cdot \sum_{i=p_s}^{i=p_e} S_{p_i q r}^{(l)} / (p_e - p_s)\}$, where $\alpha = 10$ by default, is present, we consider that the information accumulation has occurred. When the information flow intensity between the latter reasoning steps and the soft prompt becomes significantly strong, we consider this a change in the information flow pattern. To confirm the existence of the information flow change, we calculate S_{IFP}:

$$S_{IFP} = \frac{\sum_{(i,j) \in C_{pr}} S_{last}(i,j)}{|C_{pr}|} \tag{8}$$

$$C_{pr} = \{(i,j) | p_s \le i \le p_e, r_h \le j \le r_e\} \tag{9}$$

where $S_{last}(i,j)$ represents the intensity of information flow from the i-th to the j-th token In the last layer of the model, $|C_{pr}|$ denotes the number of interactions among prompt tokens and rationale tokens, p_s is the start token of the soft prompt, while r_h corresponds to the intermediate token. Similarly, p_e and r_e denote the end tokens. If S_{IFP} exceeds the defined threshold, we consider it a change in the information flow pattern.

Observation We randomly sample one hundred examples to validate the generality of the pattern on a larger scale. As shown in Figure 4a, the probability of information accumulation in the shallow layers occurring alongside changes in the deep layer information flow patterns is much higher than in cases where no accumulation is observed, indicating a strong correlation between the occurrence of information accumulation and changes in the deep layer information flow patterns.

2.2.2 WHAT DO CHANGES IN INFORMATION FLOW PATTERN AFFECT?

The observation of the previous subsection proves the relation between information accumulation and information flow pattern changes. However, the impact of these changes on the model's reasoning ability remains unclear. Therefore, in this subsection, we delve into the influence of the changes on the accuracy of reasoning.

Setting We randomly selected 50 correct-answer and 50 incorrect-answer instances to demonstrate the applicability of the changes across a broader range. By calculating the S_{IFP}, we aim to measure the relation between reasoning accuracy and the changes.

Observation Figure 4b elaborates the distribution differences in saliency values between correct and incorrect examples. As shown in Figure 4c, the latter part of the reasoning process exhibits a lower mean value for the soft prompt in correct-answer examples compared to incorrect-answer ones, which supports the broader context of the above phenomenon. Thus, we can conclude that: ***soft***

prompts lead to reaching the right answer when the latter reasoning steps put more emphasis on former tokens compared to soft tokens. In contrast, when the soft prompt significantly impacts the latter reasoning steps, the model may reach an incorrect answer. These findings are in line with the human cognitive process: before answering a question, humans always recall the background knowledge related to the question and obtain some relevant inspiration to answer the question; As a carrier containing task-related knowledge Xiao et al. (2024) Yu et al. (2024), the soft prompt can provide beneficial hints to help models understand the question and generate the initial reasoning steps, then use the question and generated steps to solve the problem.

3 METHOD

In this section, we retrospect the vanilla Prompt Tuning and propose the Dynamic Prompt Corruption (DPC) method derived from our analysis and findings to enhance reasoning capabilities.

3.1 PROMPT TUNING

Prompt tuning (PT) is a paradigm where a pre-trained language model Θ can be fine-tuned towards a task $\mathcal{T}$ with training data $(X, Y) = \{x_i, y_i\}_{i=1}^{N}$, requiring merely very few learnable vectors (soft prompts) and prepended to the input embeddings while keeping the model parameters Θ frozen Lester et al. (2021a). Specifically, for an input sequence $T = \{t_1, t_2, \ldots, t_n\} \in \mathbb{R}^{n \times d}$, PT adds a learnable prompt matrix $\mathbb{V} = \{v_1, v_2, \ldots, v_l\} \in \mathbb{R}^{l \times d}$, where l is a hyperparameter. The loss function for PT is optimized to P as follows:

$$\mathcal{L}_{PLM} = -\sum_i \log P(y_i | x_i; \Theta, P). \tag{10}$$

where the input can be represented by the concatenated matrix $[\mathbb{V}; T] \in \mathbb{R}^{(l+n) \times d}$.

3.2 INTERFERING FACTORS RECOGNITION

By analyzing the information flow during the reasoning, we believe that the latter reasoning steps should focus on the reasoning tokens that have been generated rather than soft tokens. Therefore, it is essential to identify those reasoning processes in which the flow of erroneous information occurs. We think that incorrect reasoning is characterized by some affected tokens in the latter half of the reasoning sequence, and Affected tokens are those that have high information flow with the soft prompt. If the proportion of affected tokens exceeds a certain ratio, it is considered likely to result in bad reasoning. Consequently, we calculate the proportion **R** of affected tokens within a reasoning as follows:

$$R = \frac{\sum_{r_h}^{r_e} 1(S_{pr(i)} > \beta)}{\sum_{r_h}^{r_e} 1} \tag{11}$$

$$S_{pr(i)} = \frac{\sum_{(i,j) \in C_{pr(i)}} S_{last}(i,j)}{|C_{pr(i)}|} \tag{12}$$

$$C_{pr(i)} = \{(i,j) | p_s \leq j \leq p_e\}. \tag{13}$$

where β is the average intensity of information flow from the soft prompt to the former part of the reasoning tokens by default, $S_{pr(i)}$ is the intensity of information flow from the soft prompt to the i-th token, $S_{last}(i,j)$ represents the intensity of information flow from the i-th to the j-th token in the model's final layer, $|C_{pr(i)}|$ is the number of interactions among prompt and token i, p_s denotes the start token of the soft prompt, while r_h corresponds to the intermediate token. Similarly, p_e and r_e denote the end tokens. After engaging in a comparative analysis of numerous instances from various datasets with distinct LLMs, we summarize different thresholds to delimit the incorrect reasoning.

Figure 5: The overview of our method, Dynamic Prompt Corruption (DPC). DPC dynamically identifies erroneous information flow patterns and corrupts soft prompt tokens based on the location of information accumulation, alleviating the negative effects caused by the soft prompt in certain situations.

3.3 DYNAMIC CORRUPTION

With the aforementioned dynamic trigger strategy, we can identify the reasoning that produced incorrect answers, and we also need to push them to correct. Inspired by the analysis of section 2.2.1, we propose the Dynamic Corruption strategy to pinpoint the soft prompt locations that cause erroneous information flow at the instance level and then mitigate these errors through targeted corruption operations. Firstly, we locate the position j within the soft prompt where information accumulation is most intense by employing the calculation outlined in Equation 6; Secondly, we mask the value of the j-th prompt vector to obtain the corrupted soft prompts $t_c = \{v_1, v_2, \text{mask} \times v_j, \ldots, v_n\}$, and eliminate the smallest Γ percent of the embedding values, excluding the j-th element. By default, Γ is set to 10.Through the two steps, we can mitigate the potential negative effects of the harmful accumulation.

Combining the thorough analysis in the last section, we propose a novel two-stage strategy called Dynamic Prompt Corruption (DPC): Stage 1, identifying the negative impacts of soft tokens on the reasoning at the instance level; Stage 2: dynamically applying Corruption to the soft prompt. ultimately improving reasoning performance.

4 EXPERIMENT

4.1 SETTINGS

Models   We test DPC and comparison methods on LLaMA3-8B Dubey et al. (2024), LLaMA2-13B Touvron et al. (2023), and Mistral-0.2-7B Jiang et al. (2023) since they are popular Transformer decoder-only LLMs, which are convenient for exploiting and analyzing inside architectures. We set the generation mode to greedy decoding to minimize irrelevant confounders during the model inference to ensure the answers to fixed questions under the same model and prompt, and all the experiments are run on a NVIDIA A100 GPU server.

Datasets   GSM8K Cobbe et al. (2021) is a challenging dataset for assessing the capability of language models in multi-step math reasoning. MATH Hendrycks et al. (2021) is a comprehensive collection of high school-level mathematics problems. It covers a wide range of topics, including algebra, geometry, calculus, and more advanced subjects like number theory and combinatorics. AQuA Ling et al. (2017) is designed for algebraic question-answering tasks and includes a variety of multiple-choice math word problems. The questions in AQuA are derived from standardized tests and other educational resources, focusing on algebra and related topics.

Baselines To validate the effectiveness of the proposed method, we conduct experiments with several baseline models of superior performance in general NLP tasks.

Prompt tuning: Tune the trainable prompt with pretrained model frozen. As the model is fixed, prompt tuning will not change the pretrained model's performance on in-context learning tasks comparing when the prompt is removed.

ACT: Attention Calibration Technique(ACT) (Yu et al., 2024) is a training-free approach aimed at optimizing the attention distributions within llms without requiring weight fine-tuning. It is designed to address the phenomenon of attention sinks that receive disproportionately high attention despite their limited semantic relevance. By visualizing and analyzing the attention patterns across LLMs during inference, ACT identifies and calibrates attention sinks in an input-adaptive manner.

4.2 RESULTS AND DISCUSIONS

Table 2 shows the reasoning results with LLaMA3-8B, Llama2-13B, and Mistral-0.2-7B and various prompts on 3 complex reasoning tasks.

GSM8K Compared with vanilla prompt tuning, our Dynamic Prompt Correction (DPC) method enhanced the accuracy on the GSM8K dataset for Llama2, Llama3, and Mistral-0.2, improving from 38.1%, 65.5%, and 49.5% to 41.9%, 36.3%, and 51.1%, respectively. Notably, vanilla prompt tuning performed suboptimally with Llama3, showing a mere 0.6% increase in accuracy over the pretrained model. In contrast, our DPC method mitigated the challenges of vanilla prompt tuning, achieving a 2.7% improvement in accuracy. Notably, although the ACT method has shown impressive performance in classification tasks, its generalization capability in complex multi-step reasoning tasks is limited, and it fails to alleviate the challenges associated with prompt tuning.

MATH For the MATH dataset, which contains challenging competition-level mathematics problems, models typically perform poorly due to the task's difficulty. However, our DPC method improved the accuracy of Llama2, Llama3, and Mistral-0.2 on the MATH dataset, increasing from 7.6%, 33.7%, and 15.0% to 9.2%, 36.3%, and 16.4%, respectively. This demonstrates the superior performance of our method on difficult tasks.

AQuA DPC improves the accuracy of the AQuA dataset for Llama2, Llama3, and Mistral-0.2 from 22.4%, 33.7%, and 28.7% to 31.1%, 42.5%, and 31.9%, respectively. Notably, we observe an average improvement of 6.9%, and a maximum improvement of 8.8%, showing its outstanding performance in multi-step reasoning multiple-choice tasks.

Table 1: Accuracy % of various baselines and DPC on 3 tasks with LLaMA3-8B, Llama2-13B and Mistral-0.2-7B.

	Llama2-13B			Llama3-8B			Mistral-7B		
	GSM8K	MATH	AQuA	GSM8K	MATH	AQuA	GSM8K	MATH	AQuA
Pretrained model	29.5	2.0	21.0	64.9	30.0	34.0	37.9	5.1	26.0
Prompt tuning	38.1	7.6	22.4	65.5	33.7	38.5	49.5	15.0	28.7
ACT	39.2	7.1	20.1	52.6	33.8	38.6	49.5	15.0	28.7
DPC	**41.9**	**9.2**	**31.1**	**67.6**	**36.3**	**42.5**	**51.1**	**16.4**	**31.9**

4.3 ABLATION STUDIES

To evaluate the effectiveness of various components in our proposed Dynamic Prompt Correction (DPC) method, we conducted a series of ablation experiments. Specifically, we investigated the impact of corruption without Dynamic Trigger and random corruption. By systematically removing or altering some elements, we aim to analyze their contributions to the overall performance and identify key factors that lead to improved reasoning and reduced error rates. The following experiments explore the role of Dynamic corruption and Dynamic Trigger in addressing information accumulation and erroneous information flow patterns.

Setting 1:All corruption   We applied the corruption operation to all instances without the need for confirmation from the dynamic trigger. This allows us to evaluate the effectiveness of the dynamic trigger in isolation, providing insights into its overall impact on model performance.

Setting 2:Random corruption   For each instance of the corruption operation, we randomly selected the position to be corrupted. This random selection enables us to assess the overall robustness of dynamic corruption, and provides a more comprehensive understanding of its effects on model performance.

Table 2: Accuracy % of various baselines and DPC on 3 tasks with LLaMA3-8B.

	LLaMA3-8B		
Model	GSM8K	MATH	AQuA
Prompt tuning	65.5	33.7	38.5
Random corruption	51.3	32.3	39.3
All corrution	65.8	34.2	39.9
DPC	**67.6**	**36.3**	**42.5**

The results of the ablation studies, presented in Table 2, provide crucial insights into the combined effectiveness of dynamic trigger and dynamic corruption in our Dynamic Prompt Correction (DPC) method. The performance of DPC is compared against several baselines, including prompt tuning, random corruption, and corruption without dynamic trigger.

Effectiveness of Random Corruption: Random corruption, where the position of the corruption is selected randomly for each instance, shows a drop in accuracy across all tasks compared to prompt tuning. Specifically, the accuracy on GSM8K, MATH, and AQuA decreases to 51.3%, 32.3%, and 39.3%, respectively. This demonstrates that while corruption can introduce changes, applying it without specific guidance (such as from a dynamic trigger) can disrupt critical information flow, leading to worse performance.

Effectiveness of Corruption Without Dynamic Trigger: Applying corruption to all instances without the dynamic trigger results in marginal improvements over prompt tuning, particularly on the MATH and AQuA datasets, with accuracy increasing to 34.2% and 39.9%, respectively. However, the improvement is modest, and the GSM8K task shows only a minor gain (65.8% vs. 65.5%). These results suggest that although corruption can mitigate some negative effects, the absence of a dynamic trigger to guide when and where to apply it limits its full potential.

Dynamic Prompt Corruption - Combined Effect of Dynamic Trigger and Dynamic Corruption: The full DPC method, which integrates both dynamic trigger and dynamic corruption, demonstrates significant performance gains across all tasks. For GSM8K, MATH, and AQuA, DPC achieves 67.6%, 36.3%, and 42.5% accuracy, respectively. These results highlight that the dynamic trigger plays a vital role in identifying when and where to apply corruption effectively, while dynamic corruption corrects erroneous information flows precisely. The combination of these two components is essential to achieving optimal performance, as neither component alone is sufficient to address the complexities of the task.

Conclusion: The ablation study clearly shows that dynamic corruption alone, or applied indiscriminately, is not sufficient to significantly improve model performance. It is the interaction between dynamic trigger and dynamic corruption that yields the best results. The dynamic trigger ensures that corruptions are applied only when necessary, while dynamic corruption addresses specific errors, leading to a more robust reasoning process and higher overall accuracy. The synergy between these two components is key to the success of the DPC method.

5 RELATED WORK

Parameter-efficient fine-tuning (PEFT) (Han et al., 2024; Ding et al., 2023b) seeks to tune only a few parameters while achieving comparable performance with tuning a full large foundation model.

There are approximately two main branches of methods in the PEFT realm. The first branch considers approximating the change of model parameters or output on lower dimensional space. For instance, LoRA (Hu et al., 2022) that constructs $W \approx W_0 + AB$, where $W_0 \in \mathbb{R}^{d_1 \times d_2}$ is the original weight matrix and $A \in \mathbb{R}^{d_1 \times r}, B \in \mathbb{R}^{r \times d_2}$ are two low-rank matrices that approximates the change of W with fine-tuning. There is also Bitfit (Ben Zaken et al., 2022) that tunes only the bias term of PLMs, and Diff Pruning (Guo et al., 2021) that learns a task-specific "diff" vector that extends the original pre-trained parameters. The Adapter proposed by Houlsby et al. (2019) is also one of the earliest attempts of this branch. The second branch exploits the structure of Transformer (Vaswani et al., 2017), and regards input tokens or prefixes as trainable parameters. Lester et al. (2021b) proposed Prompt Tuning (PT) that prepends a series of learnable prompt tokens to the input. Prefix-tuning (Li & Liang, 2021) further makes a part of the hidden states in the intermediate layers tunable. P-tuning (Liu et al., 2023) and P-tuning v2 (Liu et al., 2022) share similar ideas to PT and Prefix-tuning but with different designs.

As a representative PEFT approach of the second branch, Prompt Tuning (PT) (Lester et al., 2021b) is known for its significant lightweight and simplicity of implementation. Since its proposal, it has been applied to various datasets and models for vision and language. It has also attracted further research to explain and improve it. Oymak et al. (2023) analyzed the role of attention in PT. Petrov et al. (2024) found that soft prompting has more capacity than hard prompting, but is limited to only bias the output of an attention head. Therefore, it can only elicit skills from the pre-trained model, but cannot learn a new task requiring a different attention pattern. Wang et al. (2023b) discussed the universality and limitation of PT. They came up with a corresponding conclusion that PT is a universal approximator for sequence-to-sequence functions, but its expressive power is limited even with infinite trainable parameters, in contrast to MLP which is not limited. Qin et al. (2021; 2024) explores PT on low-dimensional intrinsic subspaces. Wang et al. (2024) tried to decompose format specialization and task learning via a two-stage PT and fine-tuning pipeline. Nemesis (Fu et al., 2024) analyzed a Low-norm Effect that generally exists in soft PT, which reveals decreasing the norm of certain trained soft prompt vectors can benefit the final performance. DePT (Shi & Lipani, 2024) proposed to decompose the trainable soft prompt into a shorter one and a pair of low-rank matrices to reduce time and memory usage, which is also our concern in this paper. Dynamic Prompting (Yang et al., 2023) proposed a unified framework for dynamically choosing position, length, and vector for PT. Our approach shares a similar idea: choose different soft prompts for different queries, but with different designs.

6 CONCLUSION

In this work, we explored the limitations of vanilla Prompt Tuning in complex reasoning tasks and uncovered key factors that contribute to its underperformance. Through neuron saliency score analysis, we demonstrated how soft prompts could positively or negatively affect reasoning processes, depending on how they influence subsequent reasoning steps. Inspired by these insights, we introduced Dynamic Prompt Corruption, a novel approach designed to mitigate the negative impacts of soft prompts on complex reasoning tasks. By employing a two-step process involving dynamic trigger and dynamic corruption, our method successfully adjusts the influence of soft prompts in a way that guides the model towards correct reasoning. Comprehensive experiments across various models and datasets validated the effectiveness of our approach. These findings and results contribute to a deeper understanding of soft prompting mechanisms and provide a practical solution for enhancing reasoning tasks in large language models.

LIMITATIONS

In this work, DPC has demonstrated strong performance; however, the process of identifying erroneous information flow patterns and pinpointing the critical soft prompt tokens requires a complete reasoning pass, which increases the inference cost in practical applications. While our research provides valuable insights into the underlying mechanisms of soft prompts, it should not be viewed as the sole interpretation. We believe that more effective methods may exist to further explain these phenomena.

REFERENCES

Elad Ben Zaken, Yoav Goldberg, and Shauli Ravfogel. BitFit: Simple parameter-efficient fine-tuning for transformer-based masked language-models. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 1–9, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-short.1. URL `https://aclanthology.org/2022.acl-short.1`.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Damai Dai, Li Dong, Yaru Hao, Zhifang Sui, Baobao Chang, and Furu Wei. Knowledge neurons in pretrained transformers. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 8493–8502, 2022.

Ning Ding, Yujia Qin, Guang Yang, Fuchao Wei, Zonghan Yang, Yusheng Su, Shengding Hu, Yulin Chen, Chi-Min Chan, Weize Chen, et al. Parameter-efficient fine-tuning of large-scale pre-trained language models. *Nature Machine Intelligence*, 5(3):220–235, 2023a.

Ning Ding, Yujia Qin, Guang Yang, Fuchao Wei, Zonghan Yang, Yusheng Su, Shengding Hu, Yulin Chen, Chi-Min Chan, Weize Chen, et al. Parameter-efficient fine-tuning of large-scale pre-trained language models. *Nature Machine Intelligence*, 5(3):220–235, 2023b.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Shuai Fu, Xiequn Wang, Qiushi Huang, and Yu Zhang. Nemesis: Normalizing the soft-prompt vectors of vision-language models. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=zmJDzPh1Dm`.

Demi Guo, Alexander Rush, and Yoon Kim. Parameter-efficient transfer learning with diff pruning. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 4884–4896, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.378. URL `https://aclanthology.org/2021.acl-long.378`.

Zeyu Han, Chao Gao, Jinyang Liu, Sai Qian Zhang, et al. Parameter-efficient fine-tuning for large models: A comprehensive survey. *arXiv preprint arXiv:2403.14608*, 2024.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*, 2021.

Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin De Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. Parameter-efficient transfer learning for NLP. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2790–2799. PMLR, 09–15 Jun 2019. URL `https://proceedings.mlr.press/v97/houlsby19a.html`.

Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=nZeVKeeFYf9`.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.

Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning. *arXiv preprint arXiv:2104.08691*, 2021a.

Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning. In Marie-Francine Moens, Xuanjing Huang, Lucia Specia, and Scott Wen-tau Yih (eds.), *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 3045–3059, Online and Punta Cana, Dominican Republic, November 2021b. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.243. URL `https://aclanthology.org/2021.emnlp-main.243`.

Xiang Lisa Li and Percy Liang. Prefix-tuning: Optimizing continuous prompts for generation. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 4582–4597, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.353. URL `https://aclanthology.org/2021.acl-long.353`.

Wang Ling, Dani Yogatama, Chris Dyer, and Phil Blunsom. Program induction by rationale generation: Learning to solve and explain algebraic word problems. *ACL*, 2017.

Xiao Liu, Kaixuan Ji, Yicheng Fu, Weng Tam, Zhengxiao Du, Zhilin Yang, and Jie Tang. P-tuning: Prompt tuning can be comparable to fine-tuning across scales and tasks. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 61–68, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-short.8. URL `https://aclanthology.org/2022.acl-short.8`.

Xiao Liu, Yanan Zheng, Zhengxiao Du, Ming Ding, Yujie Qian, Zhilin Yang, and Jie Tang. Gpt understands, too, 2023. URL `https://arxiv.org/abs/2103.10385`.

Samet Oymak, Ankit Singh Rawat, Mahdi Soltanolkotabi, and Christos Thrampoulidis. On the role of attention in prompt-tuning. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett (eds.), *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pp. 26724–26768. PMLR, 23–29 Jul 2023. URL `https://proceedings.mlr.press/v202/oymak23a.html`.

Aleksandar Petrov, Philip Torr, and Adel Bibi. When do prompting and prefix-tuning work? a theory of capabilities and limitations. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=JewzobRhay`.

Yujia Qin, Xiaozhi Wang, Yusheng Su, Yankai Lin, Ning Ding, Jing Yi, Weize Chen, Zhiyuan Liu, Juanzi Li, Lei Hou, et al. Exploring universal intrinsic task subspace via prompt tuning. *arXiv preprint arXiv:2110.07867*, 2021.

Yujia Qin, Xiaozhi Wang, Yusheng Su, Yankai Lin, Ning Ding, Jing Yi, Weize Chen, Zhiyuan Liu, Juanzi Li, Lei Hou, et al. Exploring universal intrinsic task subspace for few-shot learning via prompt tuning. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 2024.

Zhengxiang Shi and Aldo Lipani. DePT: Decomposed prompt tuning for parameter-efficient fine-tuning. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=KjegfPGRde`.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL `https://proceedings.neurips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf`.

Lean Wang, Lei Li, Damai Dai, Deli Chen, Hao Zhou, Fandong Meng, Jie Zhou, and Xu Sun. Label words are anchors: An information flow perspective for understanding in-context learning. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 9840–9855, 2023a.

Yihan Wang, Jatin Chauhan, Wei Wang, and Cho-Jui Hsieh. Universality and limitations of prompt tuning. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 75623–75643. Curran Associates, Inc., 2023b. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/eef6aecfe050b556c6a48d9c16b15558-Paper-Conference.pdf.

Yihan Wang, Si Si, Daliang Li, Michal Lukasik, Felix Yu, Cho-Jui Hsieh, Inderjit S Dhillon, and Sanjiv Kumar. Two-stage LLM fine-tuning with less specialization and more generalization. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=pCEgna6Qco.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks, 2024.

Xianjun Yang, Wei Cheng, Xujiang Zhao, Wenchao Yu, Linda Petzold, and Haifeng Chen. Dynamic prompting: A unified framework for prompt tuning, 2023. URL https://arxiv.org/abs/2303.02909.

Zhongzhi Yu, Zheng Wang, Yonggan Fu, Huihong Shi, Khalid Shaikh, and Yingyan Celine Lin. Unveiling and harnessing hidden attention sinks: Enhancing large language models without training through attention calibration. *arXiv preprint arXiv:2406.15765*, 2024.

A   IMPLEMENT DETAILS

A.1   PROMPT TUNING TRAINING SETUP

For all prompt tuning experiments, we use learning rate 0.001 and prompt length 100. For LLama3-8b model,we initialized the soft prompt randomly. For LLama2-13b and Mistral-0.2-7b,we initialized the soft prompt with text. The text used for initialization was selected from a single example in the training set of each dataset: GSM8K, MATH, and AQuA. For each dataset, one representative sample, including both the problem and its rationale, was chosen to initialize the soft prompts. This ensures that the prompts are aligned with the specific characteristics of each dataset, enabling more effective prompt tuning during training.

For GSM8K :

```
Question:  Natalia sold clips to 48 of her friends in April,
and then she sold half as many clips in May.  How many clips did
Natalia sell altogether in April and May?
```

Answer: Natalia sold $\frac{48}{2} = 24$ clips in May. Natalia sold $48 + 24 = 72$ clips altogether in April and May. #### 72

For MATH :

```
Problem:
```
What is the degree of the polynomial $(4 + 5x^3 + 100 + 2\pi x^4 + \sqrt{10}x^4 + 9)$?

```
Solution:
```
This polynomial is not written in standard form. However, we don't need to write it in standard form, nor do we need to pay attention to the coefficients. We just look for the exponents on x. We have an x^4 term and no other term of higher degree, so $\boxed{4}$ is the degree of the polynomial.

For AQuA:

```
Question:  A person is traveling at 20 km/hr and reached his
destination in 2.5 hr.  Find the distance?

A) 53 km
B) 55 km
C) 52 km
D) 60 km
E) 50 km T = 2.5 hrs = 5/2  hrs
D = T * S = 20 × 5/2 = 50  km

Answer is E
```

B   COMPARISON OF METHODS

Figure 6: Schematic illustration of methods related to information accumulation: (a) illustrates the distinction between saliency and attention; (b) demonstrates the attention sink phenomenon on initial tokens as described in StreamingLLM; (c) highlights the attention sink phenomenon observed in ACT for special tokens other than initial tokens; (d) and (e) present the accumulation phenomenon related to hallucinations discovered by DOPERA and OPERA in the visual domain; (f) showcases the information accumulation phenomenon we identified in soft prompts.

C   VISUALIZATION OF THE ATTENTION MATRIX

Figure 7: Visualization of the attention matrix in Llama3-8b.