Efficient Dataset Distillation
using Random Feature Approximation

Abstract

Dataset distillation compresses large datasets into smaller synthetic coresets which retain performance with the aim of reducing the storage and computational burden of processing the entire dataset. Today's best performing algorithm, *Kernel Inducing Points* (KIP), which makes use of the correspondence between infinite-width neural networks and kernel-ridge regression, is prohibitively slow due to the exact computation of the neural tangent kernel matrix, scaling $O(|S|^2)$, with $|S|$ being the coreset size. To improve this, we propose a novel algorithm that uses a random feature approximation (RFA) of the Neural Network Gaussian Process (NNGP) kernel which reduces the kernel matrix computation to $O(|S|)$. Our algorithm provides at least a 100-fold speedup over KIP and can run on a single GPU. Our new method, termed an RFA Distillation (RFAD), performs competitively with KIP and other dataset condensation algorithms in accuracy over a range of large-scale datasets, both in kernel regression and finite-width network training. We demonstrate the effectiveness of our approach on tasks involving model interpretability and privacy preservation.

1 Introduction

Coreset algorithms aim to summarize large datasets into significantly smaller datasets that still accurately represent the full dataset on downstream tasks [22]. There are myriad applications of these smaller datasets including speeding up model training [35], reducing catastrophic forgetting [2, 47, 8], and enhancing interpretability [25, 6]. While most coreset selection techniques aim to select representative data points from the dataset, recent work has looked at generating synthetic data points instead, a process known as dataset distillation [57, 7, 53, 65, 63, 39]. These synthetic datasets have the benefit of using continuous gradient-based optimization techniques rather than combinatorial methods and are not limited to the set of images and labels given by the dataset, providing added flexibility and performance.

Figure 1: RFAD provides over 100-fold speedup over the state-of-the-art algorithm Kernel-Inducing Points (KIP) [38], while exceeding its performance on CIFAR-10. (right) Example distilled synthetic sets one image per class

A large variety of applications benefit from obtaining an efficient dataset distillation algorithm. For instance, Kernel methods [56, 24, 51, 15, 48] usually demand a large support set in order to generate good prediction performance at inference. This can be facilitated by an efficient dataset distillation pipeline. Moreover, distilling a synthetic version of sensitive data helps preserve privacy; a support set can be provided to an end-user for the downstream applications without disclosure of data. Lastly, for resource-hungry applications such as continual learning [8], neural architecture search [50] and automated machine learning [20], generation of a support-set on which we can fit models efficiently is very helpful.

Recently, a dataset distillation method called Kernel-Inducing Points (KIP) [38, 39] showed great performance in neural network classification tasks. KIP uses Neural Tangent Kernel (NTK) ridge-regression to *exactly* compute the output states of an infinite-width neural network trained on the support set. Although the method established the state-of-the-art for dataset distillation in terms of accuracy, the computational complexity of KIP is very high due to the exact calculation of the NTK. The algorithm, therefore, has limited applicability.

In this paper, we build on the prior work on KIP and develop a new algorithm for dataset distillation called RFAD which has similar accuracy and significantly better performance than KIP. The key insight is to introduce a new kernel inducing point method which improves complexity from $O(|S|^2)$, (where $|S|$ is the support-set size) to $O(|S|)$. To this end, we make three **major contributions**:

I. We develop RFAD, a fast, accurate and scalable algorithm for dataset distillation in neural network classification tasks.

II. We improve the time performance of KIP [38, 39] by over two orders-of-magnitude while retaining or improving its accuracy. This speedup comes from leveraging a random-feature approximation of the Neural Network Gaussian Process (NNGP) kernel by instantiating random neural networks.

III. We show the effectiveness of RFAD in efficient dataset distillation tasks, enhancing model interpretability and privacy-preservation.

2 Background and Related Work

Coresets and Dataset Distillation. Coresets are a subset of data that ensure models trained on them show competitive performance compared to models trained directly on data. Standard coreset selection algorithms use importance sampling to find coresets [17, 32, 11]. Besides random selection methods, inspired by catastrophic forgetting [55] and mean-matching (adding samples to the coreset to match the mean of the original dataset) [10, 47, 9, 5], new algorithms have been introduced. An overview of how coresets work on point approximation is provided in [43]

More recently, aligned with coreset selection methods, new algorithms have been developed to distill a synthetic dataset from a given dataset, such that fitting to this synthetic set provides performance on par with training on the original dataset [57]. To this end, these dataset condensation (or distillation) algorithms use gradient matching [65, 33, 31], utilize differentiable siamese augmentation [63], and matching distributions [64]. Dataset distillation has also been applied to the labels rather than images [7]. Recently, a novel algorithm called Kernel Inducing Points (KIP) [38, 39] has been introduced that performs very well on distilling synthetic sets by using neural tangent kernel ridge-regression (KRR). KIP, similar to other algorithms, is computationally expensive. Here, we propose a new method to significantly improve its complexity.

Infinite Width Neural Networks. Single-layer infinite-width randomly initialized neural networks correspond to Gaussian Processes [36], allowing for closed-form exact training of Bayesian neural networks for regression. Recently, this has been extended to deep fully-connected networks [30, 13], convolutional networks [40, 14], attention-based networks [18], and even to arbitrary neural architectures [61], with the corresponding GP kernel being the NNGP Kernel. Likewise, for infinite-width neural networks trained with gradient descent, the training process simplifies dramatically, corresponding to kernel ridge regression when trained with MSE loss with the corresponding kernel

being the Neural Tangent Kernel (NTK) [21, 4]. These two kernels are closely related, as the NNGP kernel forms the leading term of the NTK kernel, representing the effect of the final layer weights. Calculation of kernel entries typically scales with $O(HWD)$ for conv nets, with H, W being the image height and width, D the network depth, and $O(H^2W^2D)$ for architectures with global average pooling [4]. This, combined with the necessity of computing and inverting the $N \times N$ kernel matrix for kernel ridge regression, typically make these methods intractable for large datasets [52, 54].

Random Feature methods. Every kernel corresponds to a dot product for some feature map: $k(x, x') = \phi(x)^T\phi(x')$. Random feature methods aim to approximate the feature vector with a finite-dimensional random feature vector, the most notable example being Random Fourier Features [45]. Typically, this limits the rank of the kernel matrix, enabling faster matrix inversion allowing for scaling kernel methods to large datasets. Recently, these random feature methods have been used to speed up NTKs and NNGPs [62, 3, 40] at inference or for neural architecture search [42].

3 Algorithm Setup and Design

In this section, we first provide a high-level background on the KIP algorithm. We then sequentially outline our modifications leading to the RFAD algorithm.

3.1 KIP Revisit. The Kernel-Inducing Point algorithm [38, 39], or KIP, is a dataset distillation technique that uses the NTK kernel ridge-regression correspondence to compute exactly the outputs of an infinite-width neural network trained on the support set, bypassing the need to ever compute gradients or back-propagate on any finite network. Let X_T, y_T correspond to the images and one-hot vector labels on the training dataset and let X_S, y_S be the corresponding images and labels for the support set, which we aim to optimize. We have the outputs of a trained neural network as $f(X_T) = K_{TS}(K_{SS} + \lambda I)^{-1}y_S$, with K being the kernel matrices calculated using the NTK kernel, with $T \times S$ or $S \times S$ entries, for K_{TS} and K_{SS}, respectively. λ is a small regularization parameter. KIP then optimizes $L_{MSE} = ||y_T - f(X_T)||_2^2$ directly. The key bottleneck is the computation of these kernel matrices, requiring $O(TS \cdot HWD)$ time and memory, necessitating the use of hundreds of GPUs working in parallel. Additionally, the use of the MSE loss is suboptimal.

3.2 Replacing the NTK Kernel with an NNGP Kernel. We first replace the NTK used in kernel regression of KIP with an NNGP kernel. While this change alone would yield a speed up, as the NNGP kernel is less computationally intensive to compute [41], we primarily do this because the NNGP kernel admits a simple random feature approximation, with advantages described later in this section. We first justify the appropriateness of this modification.

Firstly, we denote that in the computation of NTK (Θ) and NNGP (K) forms the leading term, as shown in Table 1 in Appendix D of [41] which outlines the NTK and NNGP kernel computation rules for various layers of a neural network. For fully connected (FC) layers, which is the typical final layer in a neural network architecture, the remaining terms are suppressed by a matrix of expected derivatives with respect to activations, $\dot{K}$, as observed by the recursion yielded from the computation of the NTK for an FC network [41]: $\Theta^l = K^l + \dot{K}^l \odot \Theta^{l-1}$. For ReLU activations, the entries in this derivative matrix are upper bounded by 1, so the remaining terms must have a decaying contribution. We verify that our algorithms still provide good performance under the NTK and for finite-networks trained with gradient descent, justifying this approximation.

3.3 Replacing NNGP with an Empirical NNGP. When we sample from a Gaussian process $f \sim \mathcal{GP}(0, K)$, it suggests a natural finite feature map corresponding to scaled draws from the GP: $\hat{\phi}(x) = \frac{1}{\sqrt{N}}[f_1(x), ..., f_N(x)]^T$. For most GPs, this insight is not relevant, as sampling from a GP typically requires a Cholesky decomposition of the kernel matrix, requiring its computation in the first place [46]. However, for NNGP we can generate approximate samples of f by instantiating random neural networks, $f_i(x) = f_{\theta_i}(x), \theta_i \sim p(\theta)$, for some initialization distribution $p(\theta)$. Moreover, with a given neural network, we can define f_i to be a vector of dimension M by having a network with multiple output heads, meaning that with N networks, we have NM features. For our purposes, we typically have N = 8, M = 4096, giving 32768 total features. For the convolutional architectures we

---

Algorithm 1 Dataset distillation by NNGP random features

Require: Training set and labels X_T, y_T, Randomly initialized coreset and labels X_S, y_S, Random network count N, Random network output dimension M, Batch size $|B|$, Random network initialization distribution, $p(\theta)$, Regularization coefficient, λ, Learning rate η,

    while loss not converged **do**

        Sample batch from training set $X_B, y_B \sim p(X_T, y_T)$

        Sample N random networks each with output dimension M from $p(\theta)$: $\theta_1, ...\theta_N \sim p(\theta)$

        Compute random features for batch with random nets:

            $\hat{\Phi}(X_B) \leftarrow \frac{1}{\sqrt{NM}}[f_{\theta_1}(X_B),...,f_{\theta_N}(X_B)]^T \in \mathbb{R}^{|NM| \times |B|}$

        Compute rand features for support set with rand nets:

            $\hat{\Phi}(X_S) \leftarrow \frac{1}{\sqrt{NM}}[f_{\theta_1}(X_S),...,f_{\theta_N}(X_S)]^T \in \mathbb{R}^{|NM| \times |S|}$

        Compute kernel matrices: $\hat{K}_{BS} \leftarrow \hat{\Phi}(X_B)^T \hat{\Phi}(X_S)$

        $\hat{K}_{SS} \leftarrow \hat{\Phi}(X_S)^T \hat{\Phi}(X_S)$

        Calculate trained network output on batch: $\hat{y}_B \leftarrow \hat{K}_{BS}(\hat{K}_{SS} + \lambda I_{|S|})^{-1} y_S$

        Calculate loss: $\mathcal{L} = \mathcal{L}(y_B, \hat{y}_B)$

        Update coreset: $X_S \leftarrow X_S - \eta \frac{\partial \mathcal{L}}{\partial X_S}, y_S \leftarrow y_S - \eta \frac{\partial \mathcal{L}}{\partial y_S}$

    end while

---

consider, this corresponds to $C = 256$ convolutional channels per layer. Even with this relatively large number of features, we still see a significant computation speedup over exact calculation.

To sample $f \sim \mathcal{GP}(0, K)$, we would have to instantiate random *infinite* width neural nets, whereas, in practice, we can only sample finite ones. This discrepancy incurs an $O(1/C)$ bias to our kernel matrix entries, with C being the width relevant parameter (i.e., convolutional channels) [60]. However, we have a $O(1/(NC))$ variance of the mean of the random features [12], meaning that in practice, the variance dominates the computation over bias. This has been noted empirically in [40], and we verify that the finite-width bias does not significantly affect performance in Appendix, showing that we can achieve reasonable performance with as little as *one* convolution channel.

3.4 Loss Function in dataset distillation. We denoted earlier that L_{MSE} is not well suited for dataset distillation settings. In particular, there are two key problems: *Over-influence of already correctly classified datapoints*. Consider two-way classification, with the label 1 corresponding to the positive class and -1 corresponding to the negative class. Let x_1 and x_2 be items in the training set whose labels are both 1. Let $f_{\mathbf{KRR}}(x) = K_{x,S}(K_{SS} + \lambda I)^{-1} y_S$ be the KRR output on x given our support set X_S. If $f_{\mathbf{KRR}}(x_1) = 5$ and $f_{\mathbf{KRR}}(x_2) = -1$, then the resulting MSE error on x_1 and x_2 would be 16 and 4, respectively. Notably, x_1 incurs a larger loss, and results in a larger gradient on X_S than x_2, despite being correctly classified and x_2 being incorrectly classified. In the heavily constrained dataset distillation setting, fitting both datapoints simultaneously is not possible, leading to underfitting of the data in terms of classification, in order to better fit already-correctly labeled datapoints in terms of regression. *Probabilistic interpretation of MSE for classification?* This prevents regression from being used directly in calibration-sensitive environment, necessitating the use of transformation functions in tasks such as GP classification [58, 34].

Based on these two issues, we adopt platt scaling [44], by applying a cross entropy loss to the labels instead of an MSE one: $\mathcal{L}_{platt} = $ x-entropy$(y_T, f(X_T)/\tau)$, where τ is a positive learned temperature scaling parameter. Unlike typical Platt scaling, we learn τ jointly with our support set instead of post-hoc tuning on a separate validation set. $f(X_T)$ is still calculated using the same KRR formula. Accordingly, this corresponds to training a network using MSE loss, but at inference, scaling the outputs by τ^{-1} and applying a softmax to get a categorical distribution. Unlike typical GP classification, we ignore the variance of our predictions, taking only the mean instead.

The combination of these three changes, namely, using the NNGP kernel instead of NTK, applying a random-feature approximation of NNGP, and Platt-scaling result in our RFAD algorithm, which is given in algorithm 1.

Table 1: Kernel distillation results on five datasets with varying support set sizes. **Bolded** numbers indicate the best performance with fixed labels, and underlined numbers indicate the best performance with learned labels. Note that DC and DSA use fixed labels. (n = 4)

	Img/Cls	Fixed Labels				Learned Labels	
		DC	DSA	KIP	RFAD (ours)	KIP	RFAD (ours)
MNIST	1	91.7 ± 0.5	88.7 ± 0.6	95.2 ± 0.2	$\mathbf{96.7 \pm 0.2}$	$\underline{97.3 \pm 0.1}$	97.2 ± 0.2
	10	97.4 ± 0.2	97.8 ± 0.1	98.4 ± 0.0	$\mathbf{99.0 \pm 0.1}$	$\underline{99.1 \pm 0.1}$	$\underline{99.1 \pm 0.0}$
	50	98.8 ± 0.1	$\mathbf{99.2 \pm 0.1}$	99.1 ± 0.0	99.1 ± 0.0	$\underline{99.4 \pm 0.1}$	99.1 ± 0.0
Fashion-MNIST	1	70.5 ± 0.6	70.6 ± 0.6	78.9 ± 0.2	$\mathbf{81.6 \pm 0.6}$	82.9 ± 0.2	$\underline{84.6 \pm 0.2}$
	10	82.3 ± 0.4	84.6 ± 0.3	87.6 ± 0.1	$\mathbf{90.0 \pm 0.1}$	$\underline{91.0 \pm 0.1}$	90.3 ± 0.2
	50	83.6 ± 0.4	88.7 ± 0.2	90.0 ± 0.1	$\mathbf{91.3 \pm 0.1}$	$\underline{92.4 \pm 0.1}$	91.4 ± 0.1
SVHN	1	31.2 ± 1.4	27.5 ± 1.4	48.1 ± 0.7	$\mathbf{51.4 \pm 1.3}$	$\underline{64.3 \pm 0.4}$	$57.4 \pm .8$
	10	76.1 ± 0.6	$\mathbf{79.2 \pm 0.5}$	75.8 ± 0.1	77.2 ± 0.3	$\underline{81.1 \pm 0.5}$	78.2 ± 0.5
	50	82.3 ± 0.3	$\mathbf{84.4 \pm 0.4}$	81.3 ± 0.2	81.8 ± 0.2	$\underline{84.3 \pm 0.1}$	82.4 ± 0.1
CIFAR-10	1	28.3 ± 0.5	28.8 ± 0.7	59.1 ± 0.4	$\mathbf{61.1 \pm 0.7}$	$\underline{64.7 \pm 0.2}$	61.4 ± 0.8
	10	44.9 ± 0.5	52.1 ± 0.5	67.0 ± 0.4	$\mathbf{73.1 \pm 0.1}$	$\underline{75.6 \pm 0.2}$	73.7 ± 0.2
	50	53.9 ± 0.5	60.6 ± 0.5	71.7 ± 0.2	$\mathbf{76.1 \pm 0.3}$	$\underline{80.6 \pm 0.1}$	76.6 ± 0.3
CIFAR-100	1	12.8 ± 0.3	13.9 ± 0.3	31.8 ± 0.3	$\mathbf{36.0 \pm 0.4}$	34.9 ± 0.1	$\underline{44.1 \pm 0.1}$
	10	25.2 ± 0.3	32.3 ± 0.3	$\mathbf{46.0 \pm 0.2}$	44.9 ± 0.2	$\underline{49.5 \pm 0.3}$	46.8 ± 0.2

4 Experiments with RFAD

Here, we perform experiments to evaluate the performance of RFAD in dataset distillation tasks.

Benchmarks. We applied our algorithm to five datasets: MNIST, FashionMNIST, SVHN, CIFAR-10 and CIFAR-100 [28, 59, 37, 27], distilling the datasets to coresets with 1, 10 or 50 images per class.

Network Structure and Training Setup. Similar to previous work on dataset distillation, we used standard ConvNet architectures with three convolutional layers with average pooling and ReLU activations [65, 66, 39]. Similar to KIP [39], we do not use instancenorm layers because of the lack of an infinite-width analog. During training, we used $N = 8$ random models, each with $C = 256$ convolutional channels per layer, and during test-time, we evaluated the datasets using the exact NNGP kernel using the neural-tangents library [41]. We consider both the fixed and learned labels configurations, with Platt scaling

Table 2: Performance of finite networks trained with gradient descent on DC/DSA, KIP, and RFAD distilled images. * denotes the result was obtained using learned labels. (n = 12)

	Img/Cls	DC/DSA	KIP to NN	RFAD to NN
MNIST	1	91.7 ± 0.5	90.1 ± 0.1	$\mathbf{94.4 \pm 1.5}^*$
	10	97.8 ± 0.1	97.5 ± 0.0	$\mathbf{98.5 \pm 0.1}^*$
	50	$\mathbf{99.2 \pm 0.1}$	98.3 ± 0.1	98.8 ± 0.1
Fashion-MNIST	1	70.6 ± 0.6	$73.5 \pm 0.5^*$	$\mathbf{78.6 \pm 1.3}^*$
	10	84.6 ± 0.3	86.8 ± 0.1	$\mathbf{87.0 \pm 0.5}$
	50	88.7 ± 0.2	$88.0 \pm 0.1^*$	$\mathbf{88.8 \pm 0.4}$
SVHN	1	31.2 ± 1.4	$\mathbf{57.3 \pm 0.1}^*$	$52.2 \pm 2.2^*$
	10	$\mathbf{79.2 \pm 0.5}$	75.0 ± 0.1	74.9 ± 0.4
	50	$\mathbf{84.4 \pm 0.4}$	80.5 ± 0.1	$80.9 \pm 0.3^*$
CIFAR-10	1	28.8 ± 0.7	49.9 ± 0.2	$\mathbf{53.6 \pm 1.2}^*$
	10	52.1 ± 0.5	62.7 ± 0.3	$\mathbf{66.3 \pm 0.5}^*$
	50	60.6 ± 0.5	68.6 ± 0.2	$\mathbf{71.1 \pm 0.4}$
CIFAR-100	1	13.9 ± 0.3	15.7 ± 0.2	$\mathbf{26.3 \pm 1.1}^*$
	10	32.3 ± 0.3	28.3 ± 0.1	$\mathbf{33.0 \pm 0.3}^*$

applied and no data augmentation. We used the regularized Zero Component Analysis (ZCA) pre-processing for SVHN, CIFAR-10, and CIFAR-100, to improve KRR performance for color image datasets [49, 39]. More details are available in Appendix.

Baselines. We compare RFAD to recently developed advanced dataset distillation algorithms such as: KIP [38, 39], Dataset Condensation with gradient matching (DC) [65], and differentiable Siamese augmentation (DSA) [63].

Table 1 summarizes the results. We observe that in the fixed label configuration, our method outperforms other models in almost every dataset. In particular, it outperforms KIP by up to 6.1% in the CIFAR-10 10 img/cls setting. We attribute this gain primarily to the use of Platt scaling. RFAD falls slightly behind KIP with learned labels. While this could partially be explained because we did not apply data-augmentation, which marginally elevated performance for KIP on some datasets [39], we hypothesize that the performance difference is caused by the increased gradient variance

Figure 3: NNGP to NTK transfer performance on RFAD distilled images. The blue line indicates the performance of RFAD distilled images evaluated on NNGP. The orange line shows the same images evaluated using NTK. Despite being trained using the empirical NNGP kernel, these images still perform well on the NTK kernel, losing at most a few percentage points. (n = 4)

associated with the random feature method. Nevertheless, in all experiments, RFAD is at least two orders of magnitude faster than KIP (Figure 2).

4.1 Time Savings during training. Next, we evaluated the time efficiency of RFAD. fig. 2 shows the time taken per training iteration on CIFAR-10 over coreset sizes and the number of models, N used to evaluate the empirical NNGP kernel during training. Each training iteration contains 5120 examples from the training set. fig. 2 depicts that the time taken by RFAD is linear in both the number of models used during training and in the coreset size, validating the time complexity described above. We expect that for larger coreset sizes, the matrix inversion will begin to dominate due to its cubic complexity, but for small coreset sizes, computation of the kernel matrix dominates the computation time.

In the right-hand side plot in fig. 2 we show the same plot in log-scale, compared to KIP. For KIP, we used a batch size of 5000, and rather than measuring the time taken, we use the calculation provided in appendix B of [39], which describes the running time of the algorithm. We observe evidently that even for the modest coreset sizes, the quadratic time complexity of computing the exact kernel matrix in KIP results in it being multiple orders of magnitude slower than our RFAD. Both KIP and RFAD converge in between 3000-15000 training iterations, resulting in times between 1-14hrs for RFAD and several hundred GPU hours for KIP, depending on the coreset size dataset, and when the early stopping condition is triggered.

Figure 2: Time per training iteration for RFAD and KIP with varying number of models, N. Left: Linear plot of time. Right: Logarithmic time for training iteration. RFAD achieves over two-orders-of-magnitude speedup compared KIP per training iteration, while converging with a similar number of iterations.

4.2 NTK Kernel and Finite Network Transfer

One of the key elements of the RFAD algorithm is the replacement of NTK with the empirical NNGP kernel. While we argued earlier that the two should exhibit a similar performance given their similar formalism, in this section, we verify this claim experimentally. We evaluated our distilled coresets obtained from our RFAD algorithm in two different transfer scenarios. In the first setting, at test time, we used an NTK kernel instead of the NNGP kernel. In the second setting, we trained a finite-width network with gradient descent on the distilled datasets obtained via RFAD. Similar to [39], we used a 1024-width finite network for our finite-transfer results since it better mimics the infinite width setting that corresponds to the NTK.

Remarkably, as shown in fig. 3, in most datasets, these coresets suffer little to no performance drop when evaluated using NTK compared to the exact NNGP kernel, despite being trained using the empirical NNGP kernel. The largest performance gap is 8% on SVHN with 10 images per class, and in some datasets, notably CIFAR-100, 10 img/cls evaluating using the NTK kernel outperforms NNGP. This suggests that either the exact NNGP kernel or the random feature NNGP kernel could potentially be used as a cheaper approximation for the exact NTK kernel.

Incorrect prediction — Deer ✖ Bird

Correct Prediction — Dog ✔ Dog

Test Image   Most Relevant in Coreset   Most Relevant in Training Set

Figure 4: The most relevant images for an incorrect (top row) and correct (bottom row) predictioin on CIFAR-10. The most relevant coreset images are picked based on the coreset influence score I, and for their training set, the training influence score J. These metrics are fast to compute and result in semantically meaningful explanations for these two predictions.

table 2 shows the resulting finite network transfer when training with gradient descent on our coresets. Our images appear to have the best performance in finite-network transfer, outperforming KIP in almost all benchmarks and the DC/DSA algorithms in many, despite DC/DCA being designed specifically for finite-width networks. We attribute this performance gain over KIP primarily to two tricks we used during training. Firstly, we applied centering, which, rather than training a typical network $f_\theta(x)$, we instead train a network with its output at initialization subtracted: $f_\theta(x) - f_{\theta_0}(x)$.

This has been shown empirically to speed up the convergence of finite-width networks by reducing the bias caused by the finite-width initialization while still preserving the NTK [29, 19]. We find that for these small datasets, this modification significantly improves performance. The second trick is label scaling; we scale the target labels by a factor $\alpha > 1$: $\mathcal{L}_\alpha = ||f_\theta(x) - \alpha y||_2^2/\alpha^2$, and at inference divide the model's outputs by α. Note that this does not affect the infinite-width setting, as in

Figure 5: Empirical NNGP kernel performance at test-time with varying number of models used to compute the empirical NNGP kernel and number of convolutional channels per model. (n = 5)

KRR, the output is linear w.r.t. the support set labels. Ablations of these changes are in Appendix.

4.3 Empirical NNGP Performance at Inference To validate the efficacy of our method, we evaluated our distilled coresets using the features from random networks as opposed to the exact kernel. We varied the width of individual networks between 128 and 1024 channels and the number of models between 1 and 32. fig. 5 shows the resulting classification accuracy on the CIFAR-10 dataset with 10 images/class. The black dot represents the configuration we used during training: 8 models, each with width 256 (More ablations are provided in Appendix). We conclude that the random feature method, for all network widths, is able to reach close to the exact NNGP kernel performance (dotted line) if a sufficient number of models are used. Interestingly, the performance is almost entirely dependent on the total number of features (proportional to $C \times N$, with C being the number of convolutional channels) and not the width of individual networks, suggesting that the finite-width bias associated with random finite networks is minimal.

In Appendix, we show that this can be taken to the extreme, with 70% accuracy achieved with a network with a *single* Conv channel. These results corroborate the findings of [40], which first proposed this random feature method, where they found, like us, that performance was almost entirely determined by the total feature count.

Figure 6: Objective function sensitivity. (n = 4)

Platt scaling. We performed ablations on the use of the cross-entropy loss and the number of models used during training. We reran our algorithm on CIFAR-10 and Fashion-MNIST, using either 1, 2, 4, or 8 models during training, using MSE loss or cross-entropy loss. fig. 6 shows the resulting performance of these configurations. Evidently,

using a cross-entropy loss results in substantial performance gains, even as much as 8% as with Fashion-MNIST with 1 img/cls.

5 RFAD Application I: Interpretability

Large datasets contribute to the difficulty of understanding deep learning models. In this paper we consider interpretability in the sense of the influence of individual training examples on network predictions. One method of understanding this effect is the use of influence functions, which seek to answer the following counterfactual question: which item in the training set, if left out, would change the model's prediction the most [16, 26, 23]? For deep networks, this can only be answered approximately. This is because retraining a network on copies of the training set with individual items left out is computationally intractable. One solution is to use kernel ridge regression on a small support set. We can recompute the KRR on the kernel matrices with the ith individual coreset element removed, with $K_{x,S\setminus i}\,K_{S\setminus i,S\setminus i}$ being the resulting kernel matrices with the ith row/column corresponding to the ith coreset entry removed.

In particular, let $p(y_{\text{test}} = c|S)$ be the probability prediction (computed by applying platt scaling) of an example belonging to class c computed on the entire coreset, S. Let $p(y_{\text{test}} = c|S \setminus i)$ be the same prediction calculated with the ith coreset element removed. We define the influence score, I_i of coreset element i on x_{test} as $\sum_{c \leq C} |p(y_{\text{test}} = c|S) - p(y_{\text{test}} = c|S \setminus i)|$. Taking the top values of I_i yields the most relevant examples.

While this method provides a simple way of gaining insights into how a prediction depends on the coreset, it does not provide insight into how this prediction comes from the original training set which produced the coreset. The method can be extended to accommodate this. Heuristically, we conjecture that two elements are similar if their predictions depend on the same elements in the coreset. We compute $p(y_j = c|S)$ and $p(y_j = c|S \setminus i)$ for every element j in the training set and i in the coreset. Then, we define its influence embedding as $z_{i,c}^j = p(y_j = c|S) - p(y_j = c|S \setminus i), z^j \in R^{|S| \times |C|}$. This way, z^j defines the sensitivity of a training datapoint prediction on the coreset. We compute the same embedding for a test datapoint z^{test}, and to compare data points we simply compute the cosine similarity, $J_{\text{test},j} = \cos(z^{\text{test}}, z^j)$. Values of z^j can be precomputed for the training set, typically in a few minutes for CIFAR-10, allowing for relatively fast queries, in contrast to the more expensive Hessian-inverse vector product required in [26], which is costly to compute and difficult to store.

fig. 4 shows the results of this algorithm applied to CIFAR-10 with 50 img/cls for an incorrectly and correctly predicted image. In both cases, the resulting queries are visually similar to the test data point. One could use this information to not only explain a single incorrect prediction but to understand harmful items in their test set, or where more data needs to be collected.

Figure 7: CelebA distilled datasets for male/female classification with 1 image per class at varying corruption ratios. At $\rho = 0$, the distilled images are very interpretable, but at $\rho = 0.95$, the images look like white noise, despite achieving 86.9% accuracy on the classification task.

6 RFAD Application II: Privacy

As a second application of RFAD, we create coresets that contain no human-understandable information from the source dataset yet still retain high test performance. [38] proposed the concept of a ρ-corrupted coreset: A fraction ρ of the coresets elements are completely independent of the source dataset. Practically, for our algorithm, this means initializing the coreset with random noise and keeping a random ρ fraction of the pixels kept at their initialization. We term this algorithm RFAD$_\rho$. Adding noise to gradient updates of the inputs of a network can be shown to give differentially private guarantees [1]. While our scheme does not provide the same guarantees, we note the following two privacy-preserving properties of RFAD$_\rho$:

firstly, the distillation process is irreversible: there are many datasets for which a distilled dataset provides zero loss. Secondly, if the true data distribution assigns a low probability to images of white noise, then for high values of ρ, this guarantees that the distilled dataset stays far away in L_2 norm from real data points, since ρ fraction of the pixels are stuck at their initialization. This means that a distilled RFAD$_\rho$ dataset will not recreate any real points in the training set.

We applied RFAD$_\rho$ on CIFAR-10, and CelebA faces datasets. For CIFAR-10 we distilled the standard 10-class classification task, with corruption ratios taking values of $[0, 0.2, 0.4, 0.8, 0.9]$, with 1, 10 or 50 images per class. For CelebA, we performed male/female binary classification with corruption ratios between 0 and 0.95 with 1, 10, or 50 samples per class. fig. 8 show the resulting performance.

For CIFAR-10, even at corruption ratios of 0.9, we are able to achieve 40.6% accuracy with one sample per class, far above the natural baseline of 16.1% ([39] table A1). For CelebA, we can achieve 81% accuracy with a total of two images, one male and one female, in the dataset, with 95% of the pixels in the image being random noise. We additionally visualize the distilled images for the male and female classes in the CelebA distillation task with one image per class in fig. 7 at varying corruption ratios. While the image initially contains visually interpretable features with $\rho = 0$, they quickly devolve into pure noise at $\rho = 0.95$.

Figure 8: Performance of RFAD on CIFAR-10 and CelebA classification with varying support set sizes and corruption ratios. Performance degrades very gradually as noise is increased, still achieving high performance with 90% corruption. (n = 3)

7 Limitations

Use of instancenorm. In practice, we found that our datasets distilled without instancenorm do not transfer well to finite networks with it. Conversely, if we use random networks with instancenorm in RFAD, these transfer to finite networks with instancenorm, but not to ones without or the NNGP kernel. This suggests that the features used by networks with/without instancenorm differ, making it difficult to distill datasets that perform well on both. We discuss this further in Appendix.

Overfitting in dataset distillation. On Platt scaling, we argued that the heavily constrained nature of dataset distillation leads to underfitting of the training set when using an MSE-style loss in KIP, and we verified the efficacy of using a Platt loss instead. However, we observed that in simple datasets, such as MNIST, or with large coresets relative to the data, such as CIFAR-100 with 10 images per class, we could overfit to the dataset. We found that these distilled datasets were able to achieve near 100% classification accuracy on the training set, meaning that it was distilled perfectly in terms of the Platt-loss. This implies that adding more images would not improve performance. Thus we hypothesize that using a Platt loss would be detrimental if the compression ratio is low.

8 Conclusions

We proposed RFAD, a dataset distillation algorithm that provides a 100-fold speedup over the current state of the art, KIP, while retaining accuracy. The speedup is primarily due to the use of the approximate NNGP kernel as opposed to the exact NTK one, reducing the time complexity from $O(|S|^2)$ to $O(|S|)$. The success of the approximation here, combined with the similarity between the NTK and NNGP kernels, suggests the random network NNGP approximation as an efficient method for algorithms where the exact computation of the NNGP or NTK kernel is infeasible. We analyzed our method comprehensively and showed its effectiveness, and proposed two applications in model interpretability and privacy-preservation. With this new tool, we hope that future work could begin to use Neural Tangent Kernel as an algorithmic design tool in addition to its current theoretical use for neural network analysis.

References

[1] Martin Abadi, Andy Chu, Ian Goodfellow, H. Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security*, CCS '16, page 308–318, New York, NY, USA, 2016. Association for Computing Machinery.

[2] Rahaf Aljundi, Min Lin, Baptiste Goujaud, and Yoshua Bengio. Gradient based sample selection for online continual learning. In *NeurIPS*, 2019.

[3] Anonymous. Fast finite width neural tangent kernel. In *Submitted to The Tenth International Conference on Learning Representations*, 2022. under review.

[4] Sanjeev Arora, Simon Shaolei Du, Wei Hu, Zhiyuan Li, Ruslan Salakhutdinov, and Ruosong Wang. On exact computation with an infinitely wide neural net. In *NeurIPS*, 2019.

[5] Eden Belouadah and Adrian Popescu. Scail: Classifier weights scaling for class incremental learning. In *The IEEE Winter Conference on Applications of Computer Vision*, 2020.

[6] Jacob Bien and Robert Tibshirani. Prototype selection for interpretable classification. *The Annals of Applied Statistics*, 5(4):2403–2424, 2011.

[7] Ondrej Bohdal, Yongxin Yang, and Timothy Hospedales. Flexible dataset distillation: Learn labels instead of images. *Neural Information Processing Systems Workshop*, 2020.

[8] Zalán Borsos, Mojmír Mutný, and Andreas Krause. Coresets via bilevel optimization for continual learning and streaming. *NeurIPS*, 2020.

[9] Francisco M Castro, Manuel J Marín-Jiménez, Nicolás Guil, Cordelia Schmid, and Karteek Alahari. End-to-end incremental learning. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 233–248, 2018.

[10] Yutian Chen, Max Welling, and Alex Smola. Super-samples from kernel herding. *The Twenty-Sixth Conference Annual Conference on Uncertainty in Artificial Intelligence*, 2010.

[11] Michael B Cohen, Cameron Musco, and Christopher Musco. Input sparsity time low-rank approximation via ridge leverage score sampling. In *Proceedings of the Twenty-Eighth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 1758–1777. SIAM, 2017.

[12] Amit Daniely, Roy Frostig, and Yoram Singer. Toward deeper understanding of neural networks: The power of initialization and a dual view on expressivity. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016.

[13] Alexander G. de G. Matthews, Jiri Hron, Mark Rowland, Richard E. Turner, and Zoubin Ghahramani. Gaussian process behaviour in wide deep neural networks. In *International Conference on Learning Representations*, 2018.

[14] Adrià Garriga-Alonso, Carl Edward Rasmussen, and Laurence Aitchison. Deep convolutional networks as shallow gaussian processes. In *International Conference on Learning Representations*, 2019.

[15] Behrooz Ghorbani, Song Mei, Theodor Misiakiewicz, and Andrea Montanari. When do neural networks outperform kernel methods? *arXiv preprint arXiv:2006.13409*, 2020.

[16] Frank R. Hampel. The influence curve and its role in robust estimation. *Journal of the American Statistical Association*, 69(346):383–393, 1974.

[17] Sariel Har-Peled and Soham Mazumdar. On coresets for k-means and k-median clustering. In *Proceedings of the thirty-sixth annual ACM symposium on Theory of computing*, pages 291–300, 2004.

[18] Jiri Hron, Yasaman Bahri, Jascha Sohl-Dickstein, and Roman Novak. Infinite attention: Nngp and ntk for deep attention networks. In *ICML*, 2020.

[19] Wei Hu, Zhiyuan Li, and Dingli Yu. Simple and effective regularization methods for training on noisily labeled data with generalization guarantee. In *International Conference on Learning Representations*, 2020.

[20] Frank Hutter, Lars Kotthoff, and Joaquin Vanschoren. *Automated machine learning: methods, systems, challenges*. Springer Nature, 2019.

[21] Arthur Jacot, Franck Gabriel, and Clement Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In *Advances in Neural Information Processing Systems*, 2018.

[22] Ibrahim Jubran, Alaa Maalouf, and Dan Feldman. Introduction to coresets: Accurate coresets. *CoRR*, abs/1910.08707, 2019.

[23] Mayank Kabra, Alice Robie, and Kristin Branson. Understanding classifier errors by examining influential neighbors. *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3917–3925, 2015.

[24] Mahmut Kaya and H.s Bilge. Deep metric learning: A survey. *Symmetry*, 11:1066, 08 2019.

[25] Been Kim, Rajiv Khanna, and Oluwasanmi Koyejo. Examples are not enough, learn to criticize! criticism for interpretability. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, NIPS'16, page 2288–2296, Red Hook, NY, USA, 2016. Curran Associates Inc.

[26] Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, page 1885–1894. JMLR.org, 2017.

[27] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009.

[28] Yann LeCun, Corinna Cortes, and CJ Burges. Mnist handwritten digit database. *ATT Labs [Online]. Available: http://yann.lecun.com/exdb/mnist*, 2, 2010.

[29] Jaehoon Lee, Samuel Schoenholz, Jeffrey Pennington, Ben Adlam, Lechao Xiao, Roman Novak, and Jascha Sohl-Dickstein. Finite versus infinite neural networks: an empirical study. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 15156–15172. Curran Associates, Inc., 2020.

[30] Jaehoon Lee, Jascha Sohl-dickstein, Jeffrey Pennington, Roman Novak, Sam Schoenholz, and Yasaman Bahri. Deep neural networks as gaussian processes. In *International Conference on Learning Representations*, 2018.

[31] Jonathan Lorraine, Paul Vicol, and David Duvenaud. Optimizing millions of hyperparameters by implicit differentiation. In *International Conference on Artificial Intelligence and Statistics*, pages 1540–1552. PMLR, 2020.

[32] Mario Lucic, Matthew Faulkner, Andreas Krause, and Dan Feldman. Training gaussian mixture models at scale via coresets. *The Journal of Machine Learning Research*, 18(1):5885–5909, 2017.

[33] Dougal Maclaurin, David Duvenaud, and Ryan Adams. Gradient-based hyperparameter optimization through reversible learning. In *International Conference on Machine Learning*, pages 2113–2122, 2015.

[34] Dimitrios Milios, Raffaello Camoriano, Pietro Michiardi, Lorenzo Rosasco, and Maurizio Filippone. Dirichlet-based gaussian processes for large-scale calibrated classification. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pages 6008–6018, 2018.

[35] Baharan Mirzasoleiman, Jeff A. Bilmes, and Jure Leskovec. Coresets for data-efficient training of machine learning models. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 6950–6960. PMLR, 2020.

[36] Radford M. Neal. *Bayesian Learning for Neural Networks*. Springer-Verlag, Berlin, Heidelberg, 1996.

[37] Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. *Google Research*, 2011.

[38] Timothy Nguyen, Zhourong Chen, and Jaehoon Lee. Dataset meta-learning from kernel ridge-regression. In *International Conference on Learning Representations*, 2021.

[39] Timothy Nguyen, Roman Novak, Lechao Xiao, and Jaehoon Lee. Dataset distillation with infinitely wide convolutional networks. In *Thirty-Fifth Conference on Neural Information Processing Systems*, 2021.

[40] Roman Novak, Lechao Xiao, Yasaman Bahri, Jaehoon Lee, Greg Yang, Daniel A. Abolafia, Jeffrey Pennington, and Jascha Sohl-dickstein. Bayesian deep convolutional networks with many channels are gaussian processes. In *International Conference on Learning Representations*, 2019.

[41] Roman Novak, Lechao Xiao, Jiri Hron, Jaehoon Lee, Alexander A. Alemi, Jascha Sohl-Dickstein, and Samuel S. Schoenholz. Neural tangents: Fast and easy infinite neural networks in python. In *International Conference on Learning Representations*, 2020.

[42] Daiyi Peng, Daniel S. Park, Jaehoon Lee, Jascha Sohl-dickstein, and Yuan Cao. Towards nngp-guided neural architecture search. In *ArXiv*, 2020.

[43] Jeff M Phillips. Coresets and sketches. *arXiv preprint arXiv:1601.00617*, 2016.

[44] John Platt. Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. *Adv. Large Margin Classif.*, 10, 06 2000.

[45] Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. In *Proceedings of the 20th International Conference on Neural Information Processing Systems*, pages 1177–1184, 2007.

[46] Carl Edward Rasmussen and Christopher K. I. Williams. *Gaussian processes for machine learning*. Adaptive computation and machine learning. MIT Press, 2006.

[47] Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, G. Sperl, and Christoph H. Lampert. icarl: Incremental classifier and representation learning. *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5533–5542, 2017.

[48] Maria Refinetti, Sebastian Goldt, Florent Krzakala, and Lenka Zdeborová. Classifying high-dimensional gaussian mixtures: Where kernel methods fail and neural networks succeed. *arXiv preprint arXiv:2102.11742*, 2021.

[49] Vaishaal Shankar, Alex Fang, Wenshuo Guo, Sara Fridovich-Keil, Jonathan Ragan-Kelley, Ludwig Schmidt, and Benjamin Recht. Neural kernels without tangents. In *ICML*, pages 8614–8623, 2020.

[50] Sam Shleifer and Eric Prokop. Using small proxy datasets to accelerate hyperparameter search. *arXiv preprint arXiv:1906.04887*, 2019.

[51] Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Advances in neural information processing systems*, pages 4077–4087, 2017.

[52] Edward Snelson and Zoubin Ghahramani. Sparse gaussian processes using pseudo-inputs. In *Advances in neural information processing systems*, pages 1257–1264, 2006.

[53] Ilia Sucholutsky and Matthias Schonlau. Soft-label dataset distillation and text dataset distillation. *arXiv preprint arXiv:1910.02551*, 2019.

[54] Michalis Titsias. Variational learning of inducing variables in sparse gaussian processes. In *Artificial Intelligence and Statistics*, pages 567–574, 2009.

[55] Mariya Toneva, Alessandro Sordoni, Remi Tachet des Combes, Adam Trischler, Yoshua Bengio, and Geoffrey J Gordon. An empirical study of example forgetting during deep neural network learning. *ICLR*, 2019.

[56] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. In *Advances in neural information processing systems*, 2016.

[57] Tongzhou Wang, Jun-Yan Zhu, Antonio Torralba, and Alexei A Efros. Dataset distillation. *arXiv preprint arXiv:1811.10959*, 2018.

[58] Christopher K. I. Williams and David Barber. Bayesian classification with gaussian processes. *IEEE Trans. Pattern Anal. Mach. Intell.*, 20(12):1342–1351, dec 1998.

[59] Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747*, 2017.

[60] Sho Yaida. Non-Gaussian processes and neural networks at finite widths. In Jianfeng Lu and Rachel Ward, editors, *Proceedings of The First Mathematical and Scientific Machine Learning Conference*, volume 107 of *Proceedings of Machine Learning Research*, pages 165–192. PMLR, 20–24 Jul 2020.

[61] Greg Yang. Tensor programs i: Wide feedforward or recurrent neural networks of any architecture are gaussian processes. In *NeurIPS 2019*, December 2019.

[62] Amir Zandieh, Insu Han, Haim Avron, Neta Shoham, Chaewon Kim, and Jinwoo Shin. Scaling neural tangent kernels via sketching and random features. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

[63] Bo Zhao and Hakan Bilen. Dataset condensation with differentiable siamese augmentation. *arXiv preprint arXiv:2102.08259*, 2021.

[64] Bo Zhao and Hakan Bilen. Dataset condensation with distribution matching. *arXiv preprint arXiv:2110.04181*, 2021.

[65] Bo Zhao, Konda Reddy Mopuri, and Hakan Bilen. Dataset condensation with gradient matching. In *International Conference on Learning Representations*, 2021.

[66] Shengyu Zhao, Zhijian Liu, Ji Lin, Jun-Yan Zhu, and Song Han. Differentiable augmentation for data-efficient gan training. *Neural Information Processing Systems*, 2020.