GREEDY INFORMATION MAXIMIZATION FOR ONLINE FEATURE SELECTION

ABSTRACT

Feature selection is commonly used to reduce feature acquisition costs, but the standard approach is to train models with static feature subsets. Here, we consider the *online feature selection* problem, where the model can adaptively query features based on the presently available information. Online feature selection has mainly been viewed as a reinforcement learning problem, but we propose a simpler approach of greedily selecting features that maximize mutual information with the response variable. This intuitive idea is difficult to implement without perfect knowledge of the joint data distribution, so we propose a deep learning approach that recovers the greedy procedure when perfectly optimized. We apply our approach to numerous datasets and observe better performance than both RL-based and offline feature selection methods.

1 INTRODUCTION

Machine learning models require informative inputs to make accurate predictions, but a model's input features can be costly to acquire. In settings where information is gathered sequentially, and particularly when acquiring features requires time or money, it is reasonable to query features adaptively based on the presently available information. We refer to this problem as *online feature selection*, and it has been considered by several works in the last decade (Dulac-Arnold et al., 2011; Early et al., 2016a; He et al., 2016a; Kachuee et al., 2018; Janisch et al., 2019).

Feature selection with static feature sets (which we refer to as *offline* selection) has received more attention (Guyon & Elisseeff, 2003; Balın et al., 2019), but online selection offers the potential for better performance given a fixed budget. This is easy to see, because selecting the same features for all instances (e.g., all patients visiting a doctor's office) is one possible adaptive policy, but it is likely suboptimal in many applications. However, online selection is also more challenging because it requires both learning a selection policy and making predictions with multiple feature sets.

Prior work has approached online feature selection in several ways (Early et al., 2016b; He et al., 2016a), but most often using reinforcement learning (RL) (Dulac-Arnold et al., 2011; Shim et al., 2017; Kachuee et al., 2018; Janisch et al., 2019). RL is a natural approach for sequential decision-making problems, but current approaches are difficult to train, slow to converge, and do not reliably outperform offline methods (Erion et al., 2021). Our work therefore explores a simpler approach.

Instead of using RL, we propose a greedy policy: sequentially selecting features that have maximum conditional mutual information with the response variable. We refer to this approach as *greedy information maximization*, and it is simple to interpret and relatively easy to learn from standard labeled datasets. Similar to greedy forward selection for offline feature selection (Das & Kempe, 2011), our greedy approach is designed to serve as a simple but powerful baseline for online feature selection. Our contributions in this work are the following:

1. We define greedy online feature selection as identifying the locally optimal selection given an optimal predictor. We then show that for classification tasks, this corresponds to selecting features according to their conditional mutual information with the response variable.

2. We describe an iterative procedure to implement the greedy approach *given perfect knowledge of the data distribution*. While impractical, this procedure is instructive and can be understood as a special case of the framework proposed by Early et al. (2016a).

3. We develop a deep learning approach to approximate the greedy selection procedure. Our policy is learned by gradient descent using a standard labeled dataset, and we prove that our objective function recovers the greedy approach when it is perfectly optimized.

We demonstrate the effectiveness of our approach on numerous datasets, and the results show that our method outperforms both RL-based and offline feature selection methods. Overall, our work shows that the greedy approach is a simple and powerful method for online feature selection.

2 PROBLEM FORMULATION

In this section, we introduce notation used throughout the paper and describe the online feature selection problem.

2.1 NOTATION

Let $\mathbf{x} \in \mathcal{X}$ denote a vector of input features and $\mathbf{y} \in \mathcal{Y}$ a response variable for a supervised learning task. The input consists of d distinct features, or $\mathbf{x} = (\mathbf{x}_1, \ldots, \mathbf{x}_d)$ where $\mathbf{x}_i \in \mathcal{X}_i$. We use $s \subseteq [d] \equiv \{1, \ldots, d\}$ to denote a subset of indices and $\mathbf{x}_s = \{\mathbf{x}_i : i \in s\}$ a subset of features. Bold symbols $\mathbf{x}, \mathbf{y}, \mathbf{s}$ represent random variables, the symbols x, y, s are possible values, and the data distribution is denoted by $p(\mathbf{x}, \mathbf{y})$.

Our goal is to design an online feature selection policy, and the policy can be viewed as a function $\pi(x_s) \in [d]$. That is, the policy receives a subset of features as its input and selects the next feature index to query. The policy is accompanied by a predictor $f(x_s)$ that can make predictions given the set of available features; for example, if $\mathbf{y}$ is discrete then predictions lie in the probability simplex, or $f(x_s) \in \Delta^{|\mathcal{Y}|-1}$. The notation $f(x_s \cup x_i)$ represents the prediction given the combined features $x_{s \cup \{i\}}$, and $\mathbf{x}_{\bar{s}}$ is the set complement $\mathbf{x}_{[d] \setminus s}$. The initial part of the paper considers policy and predictor functions that operate on feature subsets, and Section 4 proposes a practical implementation using a mask variable $m \in [0, 1]^d$ where the functions operate on $x \odot m$.

2.2 ONLINE FEATURE SELECTION

The goal of online feature selection is to select features with a minimal budget that achieve maximum predictive accuracy. Access to more features generally makes prediction problems easier, so the challenge is selecting a small number of informative features. There are multiple formulations for this problem, including non-uniform feature costs and different budgets for each sample, but we focus on the setting with a fixed feature budget and uniform feature costs: our goal is to arrive at a feature set x_s that enables accurate predictions for the unobserved response y, where $|s| = k$.

Given a loss function that measures the discrepancy between predictions and labels $\ell(\hat{y}, y)$, a natural scoring criterion is the expected loss after selecting k features. The scoring is applied to a policy-predictor pair (π, f), and we define the score for a fixed budget k as follows,

$$v_k(\pi, f) = \mathbb{E}_{p(\mathbf{x}, \mathbf{y})} \big[\ell\big(f\big(\{\mathbf{x}_{i_t}\}_{t=1}^k\big), \mathbf{y}\big) \big], \tag{1}$$

where feature indices are chosen sequentially for each $(\mathbf{x}, \mathbf{y})$ according to $i_n = \pi(\{\mathbf{x}_{i_t}\}_{t=1}^{n-1})$. Our goal in designing a policy is to minimize $v_k(\pi, f)$, or to maximize our final predictive accuracy.

One approach is to frame this as a Markov decision process (MDP) and solve it using standard RL techniques, where π and f are trained to optimize a reward function derived from eq. (1). Indeed, several works have designed such formulations (Dulac-Arnold et al., 2011; Kachuee et al., 2018; Janisch et al., 2019). Our work instead focuses on a simpler greedy approach, which has the benefits of being simple to interpret and easier to learn in practice.

3 GREEDY INFORMATION MAXIMIZATION

In this section, we introduce a greedy approach to online feature selection and describe an iterative procedure to implement it given perfect knowledge of the joint data distribution. Later, Section 4 proposes a practical implementation that can be learned by gradient descent.

3.1 THE GREEDY POLICY

Greedy algorithms are characterized by making locally optimal choices, and the greedy approach here is to sequentially select features that maximize the one-step performance improvement. At any point in the selection process, the greedy approach selects the next feature $\mathbf{x}_i$ that is most helpful in combination with the current features x_s, regardless of the feature count $|s|$ and budget k.[1]

More precisely, we define the current greedy selection as the feature index that minimizes the expected prediction loss, similar eq. (1) but with a single additional feature. The expected loss depends on the predictor f, but we are interested primarily in the best-case scenario where the policy π uses an optimal predictor. Fortunately, the optimal predictor can be defined independently of the policy, assuming that features are selected without knowledge of the remaining features or response variable. We formalize this in the following proposition (see proofs in Appendix A).

Proposition 1. *When* $\mathbf{y}$ *is discrete and* ℓ *is cross-entropy loss, the optimal predictor* f^* *for any policy* π *is the Bayes classifier, or* $f^*(x_s) = p(\mathbf{y} \mid x_s)$.

Note that the above property does not hold in problems where the selections are based on the entire feature set (Chen et al., 2018; Yoon et al., 2018). Now, assuming that the policy uses the Bayes classifier f^* as a predictor, we define greedy online feature selection via a policy π^* that minimizes the expected prediction loss, where the expectation is with respect to the unknown variables $(\mathbf{x}_{\bar{s}}, \mathbf{y})$ and conditions on the observed features x_s.

Definition 1 (Greedy online feature selection). *The greedy approach to online feature selection is represented by a policy* π^* *that has the following output given features* x_s:

$$\pi^*(x_s) = \arg\min_i \ \mathbb{E}_{\mathbf{y}, \mathbf{x}_i \mid x_s} \big[\ell(f^*(x_s \cup \mathbf{x}_i), \mathbf{y}) \big]. \tag{2}$$

Following Definition 1, we find that greedy selection policy has an intuitive probabilistic interpretation. We focus on the case where $\mathbf{y}$ is discrete and ℓ is cross-entropy loss, but our results can be generalized to regression problems (see Appendix A). In the classification case, we can show the following result.

Proposition 2. *Given the features* x_s, *the greedy policy* π^* *selects the feature* $\mathbf{x}_i$ *having maximum conditional mutual information with the response variable, or*

$$\pi^*(x_s) = \arg\max_i \ I(\mathbf{y}; \mathbf{x}_i \mid x_s). \tag{3}$$

According to this results, we can understand the greedy policy as sequentially selecting features that provide maximum information about the response variable. We can alternatively understand it as performing greedy uncertainty minimization, because maximizing conditional mutual information with $\mathbf{y}$ is equivalent to minimizing $\mathbf{y}$'s expected conditional entropy (Cover & Thomas, 2012):

$$\arg\max_i \ I(\mathbf{y}; \mathbf{x}_i \mid x_s) = \arg\min_i \ \mathbb{E}_{\mathbf{x}_i \mid x_s} \big[H(\mathbf{y} \mid x_s, \mathbf{x}_i) \big]. \tag{4}$$

Because of these results, we refer to the policy π^* as performing *greedy information maximization*. Maximizing the additional information about $\mathbf{y}$ at each step is intuitive, and this should be an effective approach in many problems. A non-greedy baseline that optimizes for a specific budget k could potentially achieve better performance according to $v_k(\pi, f)$ (see Section 3.3), but even in such cases the greedy approach should serve as a strong baseline.

3.2 AN ITERATIVE IMPLEMENTATION

The greedy policy is trivial to implement if we can directly calculate the conditional mutual information $I(\mathbf{y}; \mathbf{x}_i \mid x_s)$, but this is rarely the case in practice. To motivate our main approach (Section 4), we first describe a procedure to identify the optimal selection given perfect knowledge of the joint data distribution. By perfect knowledge, we mean that we can evaluate the response distributions $p(\mathbf{y} \mid x_s)$ for all $s \subseteq [d]$ and the conditional distributions $p(\mathbf{x}_i \mid x_s)$ for all $s \subseteq [d]$ and $i \in [d]$.

---

[1]Note that this differs from greedily following the Q-network in RL, because the estimated Q-values reflect the reward after multiple selection steps.

At any point in the selection procedure, given the current features x_s, we can iteratively score the features $\mathbf{x}_i$ where $i \notin s$ as follows. First, we can sample multiple values for $\mathbf{x}_i$ from its conditional distribution, or $x_i^j \sim p(\mathbf{x}_i \mid x_s)$ for $j \in [n]$. Next, we can generate Bayes optimal predictions for each sampled value, or $p(\mathbf{y} \mid x_s, x_i^j)$. Finally, we can calculate 1) the mean prediction and 2) the mean KL divergence relative to the mean prediction. This yields a selection criterion defined as

$$I_i^n = \frac{1}{n} \sum_{j=1}^n D_{\mathrm{KL}}\Big(p(\mathbf{y} \mid x_s, x_i^j) \;\|\; \frac{1}{n} \sum_{l=1}^n p(\mathbf{y} \mid x_s, x_i^l)\Big). \tag{5}$$

This criterion measures the variability among predictions and captures whether different $\mathbf{x}_i$ values significantly affect $\mathbf{y}$'s conditional distribution. Selecting the next feature according to $\arg\max_i I_i^n$ coincides with the greedy policy, at least asymptotically. Following the definition of mutual information (Cover & Thomas, 2012), we have the following limiting result (see Appendix A):

$$\lim_{n \to \infty} I_i^n = I(\mathbf{y}; \mathbf{x}_i \mid x_s). \tag{6}$$

Similar ideas for examining prediction variability given sampled $\mathbf{x}_i$ values were explored in prior work (Chen et al., 2015; Early et al., 2016a;b), but the implementation choices in these works prevented them from performing greedy information maximization. Our procedure can be viewed as a special case of the expected utility approach from Early et al. (2016a), but with a carefully chosen prediction function, utility measure, and sampling distribution for missing features.[2]

Our iterative procedure is theoretically justified, but it is unrealistic in practice because we typically lack access to $p(\mathbf{y} \mid \mathbf{x}_s)$ and $p(\mathbf{x}_i \mid \mathbf{x}_s)$. Instead, we can use learned substitutes for each distribution: for example, a classifier learned using a strictly proper scoring function such as cross-entropy loss approximates $f(x_s) \approx p(\mathbf{y} \mid x_s)$ (Gneiting & Raftery, 2007), and we can use a conditional generative model to approximate samples from $p(\mathbf{x}_i \mid \mathbf{x}_s)$ (Yu et al., 2018; Ivanov et al., 2018). Even so, this approach may be unappealing in practice: iteratively scoring each candidate feature can be time-consuming, and conditional generative models are difficult to train compared to predictive models. Section 4 therefore explores a different implementation that bypasses these issues by amortizing the scoring and selection process into a learned selector model.

3.3 GREEDY SUBOPTIMALITY

Before introducing our main approach, we briefly consider the performance gap between the greedy policy and the optimal selection procedure. By definition, the greedy approach cannot achieve a better score than the optimal policy-predictor pair, or

$$\min_{\pi, f} v_k(\pi, f) \leq v_k(\pi^*, f^*). \tag{7}$$

We refer to the difference between the optimal and greedy scores as the *greedy suboptimality gap*, or $G(p, k) = v_k(\pi^*, f^*) - \min_{\pi, f} v_k(\pi, f)$, where the gap depends the data distribution $p(\mathbf{x}, \mathbf{y})$ and feature budget k. The greedy suboptimality gap is difficult to assess in practice, but we design several simple scenarios to illustrate that the gap can be large or small.

Example 1. *When $k = 1$, the greedy and optimal policies are identical and $G(p, k) = 0$ for all data distributions $p(\mathbf{x}, \mathbf{y})$. The gap becomes non-zero only when selecting $k > 1$ features.*

Example 2. *Consider a data distribution $p(\mathbf{x}, \mathbf{y})$ where $\mathbf{x}$ consists of d independent Gaussian variables $\mathbf{x}_i \sim \mathcal{N}(0, \sigma_i^2)$, the variances are ordered as $\sigma_1^2 > \ldots > \sigma_d^2$, and the response is defined as $\mathbf{y} = \sum_{i=1}^d \mathbf{x}_i$. If we let ℓ be squared error loss, then the greedy policy selects the features in order, or $\mathbf{x}_1, \ldots, \mathbf{x}_k$, and the optimal policy selects the same features in arbitrary order. The gap is therefore $G(p, k) = 0$ for all $1 \leq k \leq d$.*

Example 3. *Consider a data distribution $p(\mathbf{x}, \mathbf{y})$ where $\mathbf{x}$ consists of 10 independent Bernoulli variables $\mathbf{x}_i \sim \mathrm{Bern}(0.5)$ and the response is defined as $\mathbf{y} = \mathrm{xor}(\mathbf{x}_1, \mathbf{x}_2)$. Given a budget $k = 2$, the optimal policy selects both $\mathbf{x}_1$ and $\mathbf{x}_2$ and the optimal score is $\min_{f, \pi} v_2(\pi, f) = 0$. In contrast,*

---

[2]Following terminology from Early et al. (2016a), we set the utility to the KL divergence with the mean prediction, we assume the Bayes classifier, and we sample features from $p(\mathbf{x}_i \mid x_s)$ rather than $p(\mathbf{x}_i)$.

the greedy policy will fail to discover this because neither $\mathbf{x}_1$ nor $\mathbf{x}_2$ provide any information on their own. The greedy policy is indifferent among the features, and if it fails to select both $\mathbf{x}_1$ and $\mathbf{x}_2$ then it has no information about $\mathbf{y}$ and we have $G(p, 2) = \log 2$ (the entropy of a coin flip).

The third example illustrates the perils of following a greedy approach: it fails to account for each selection's impact later in the selection procedure. In contrast, a non-greedy policy can make suboptimal selections that yield large improvements in later steps. We find that the greedy approach provides strong performance in practice, but understanding the assumptions that allow us to bound the greedy suboptimality gap is an interesting theoretical topic for future work.

4 PROPOSED METHOD

We now introduce our main approach, a practical implementation of the greedy selection procedure trained using deep learning.

4.1 AN AMORTIZED OPTIMIZATION APPROACH

Instead of iteratively scoring candidate features (Section 3.2), we propose to learn a model that directly outputs the next greedy selection given the current features. Our approach can be learned using a dataset of labeled examples, and it does not require annotations indicating the correct greedy selections. Rather, we cast the optimization-based characterization of the greedy selection policy (Section 3.1) as an objective function to be optimized by a learnable network, leveraging an approach known as *amortized optimization* (Amos, 2022).

First, because it facilitates gradient-based optimization, we now consider that the policy outputs a distribution over feature indices. With slight abuse of notation, this section refers to the policy as a function $\pi(x_s) \in \Delta^{d-1}$, which generalizes the previous definition $\pi(x_s) \in [d]$. Using this stochastic policy, we now formulate our objective function as follows.

Let the selection policy be parameterized by a neural network $\pi(\mathbf{x}_s; \phi)$ and the predictor by a neural network $f(\mathbf{x}_s; \theta)$. Let $p(\mathbf{s})$ represent a distribution over subsets with $p(s) > 0$ for all $|s| < d$. Then, our objective function $\mathcal{L}(\theta, \phi)$ is defined as

$$\mathcal{L}(\theta, \phi) = \mathbb{E}_{p(\mathbf{x}, \mathbf{y})} \mathbb{E}_{p(\mathbf{s})} \Big[\mathbb{E}_{i \sim \pi(\mathbf{x}_s; \phi)} \big[\ell \big(f(\mathbf{x_s} \cup \mathbf{x}_i; \theta), \mathbf{y} \big) \big] \Big]. \tag{8}$$

Intuitively, eq. (8) represents generating a random feature set $\mathbf{x}_s$, sampling a feature index according to $i \sim \pi(\mathbf{x}_s; \phi)$, and then measuring the loss of the prediction $f(\mathbf{x}_s \cup \mathbf{x}_i; \theta)$. We describe this as an implementation of the greedy selection approach because it recovers the greedy behavior if it is perfectly optimized. In the classification case, we can show the following result under a mild assumption that there is a unique optimal greedy selection.

Theorem 1. *When $\mathbf{y}$ is discrete and ℓ is cross-entropy loss, the global optimum of eq. (8) is a predictor that satisfies $f(x_s; \theta^*) = p(\mathbf{y} \mid x_s)$ and a policy $\pi(x_s; \phi^*)$ that puts all probability mass on $i^* = \arg\max_i I(\mathbf{y}; \mathbf{x}_i \mid x_s)$.*

A similar result holds in the regression case, where we can interpret the greedy policy as performing conditional variance minimization.

Theorem 2. *When $\mathbf{y}$ is continuous and ℓ is squared error loss, the global optimum of eq. (8) is a predictor that satisfies $f(x_s; \theta^*) = \mathbb{E}[\mathbf{y} \mid x_s]$ and a policy $\pi(x_s; \phi^*)$ that puts all probability mass on $i^* = \arg\min_i \mathbb{E}_{\mathbf{x}_i \mid x_s}[\text{Var}(\mathbf{y} \mid x_s, \mathbf{x}_i)]$.*

Proofs for these results are in Appendix A. This approach has two key advantages over the iterative procedure from Section 3.2. First, we avoid modeling the conditional distributions $p(\mathbf{x}_i \mid \mathbf{x}_s)$ for all (s, i). Modeling these distributions is a difficult intermediate step, and our approach instead aims to directly estimate the optimal index. Second, our approach is faster because each index is generated in a single forward pass: selecting k features using the iterative procedure requires $\mathcal{O}(dk)$ scoring steps, but our approach requires only k forward passes through the selector $\pi(\mathbf{x}_s; \phi)$.

Figure 1: Diagram of our training approach. Left: features are selected by making repeated calls to the policy network using masked inputs. Right: predictions are made after each selection using the predictor network. Solid lines are backpropagated through when performing gradient descent.

Furthermore, compared to a policy learned by RL, the greedy approach is easier to learn. Our training procedure can be understood as a form of reward shaping (Sutton et al., 1998; Randløv & Alstrøm, 1998), where the reward accounts for the loss after each step and provides a strong signal about whether each selection is helpful. In comparison, observing a reward only after selecting all features provides a comparably weak signal to the policy network. RL methods generally face a challenging exploration-exploitation trade-off, but learning the greedy policy is simpler because it only requires finding the locally optimal choice among $\mathcal{O}(d)$ options at each step.

4.2 CONTINUOUS RELAXATION

Our objective yields the greedy selection policy when it is perfectly optimized, but $\mathcal{L}(\theta, \phi)$ is difficult to optimize by gradient descent. In particular, gradients are difficult to propagate through the policy network given a sampled index $i \sim \pi(x_s; \phi)$. The REINFORCE trick (Williams, 1992) is one way to get stochastic gradients, but high gradient variance can make it ineffective in many problems. There is a robust literature on reducing gradient variance in this setting (Mnih & Gregor, 2014; Tucker et al., 2017; Grathwohl et al., 2018), but we opt for a simple continuous relaxation: the Concrete distribution (Maddison et al., 2016).

An index sampled according to $i \sim \pi(x_s; \phi)$ can be represented by a one-hot vector $m \in \{0,1\}^d$ indicating the chosen index, and with the Concrete distribution we instead sample an *approximately* one-hot vector in the probability simplex, or $m \in \Delta^{d-1}$. The continuous relaxation lets us calculate gradients via the reparameterization trick (Kingma et al., 2015), because the vector can be generated using the parameters $\pi(x_s; \phi)$ using the Gumbel-softmax operation. We refer readers to Maddison et al. (2016) and Jang et al. (2016) for more details on this trick.

Relaxing the subset $s \subseteq [d]$ to a probability vector $m \in \Delta^{d-1}$ also requires relaxing the policy and predictor functions. When optimizing using the Concrete distribution, we let the policy and predictor operate on a masked version of the input x, or the element-wise product $x \odot m$. To avoid ambiguity about whether features are zero or masked, we can also pass the mask as an input. Samples from the Concrete distribution allow information to pass from only one feature, so we make the subsequent prediction after calculating the element-wise maximum with a mask representing the previously available features. Our training procedure is summarized in Figure 1 and Algorithm 1.

Training with the Concrete distribution also requires specifying a temperature parameter $\tau > 0$ to control how discrete its samples are. While previous works have trained with a fixed temperature or annealed it over a pre-determined number of epochs (Chang et al., 2017; Chen et al., 2018; Balın et al., 2019), we train with a sequence of τ values and perform early stopping at each step. This effectively removes the temperature and number of epochs as important hyperparameters.

There are also several optional steps that we found can improve optimization:

- Parameters can be shared between the predictor and policy networks $f(\mathbf{x}; \theta), \pi(\mathbf{x}, \phi)$. This does not complicate their joint optimization, and learning a shared representation in the early network layers can in some cases help the networks optimize faster.

- Rather than training with a random subset distribution $p(\mathbf{s})$, we generate subsets using features selected by the policy network $\pi(\mathbf{x}; \phi)$. This allows the models to focus on subsets likely to be encountered at inference time, and it does not affect eq. (8)'s global optimum due to two key

properties: 1) the subset s communicates nothing about the remaining features $\mathbf{x}_{\bar{s}}$ or response $\mathbf{y}$, and 2) we update the mask variable so that the policy only optimizes for the next prediction.

- We pre-train the predictor $f(\mathbf{x}; \theta)$ using random subsets before jointly training the policy-predictor pair. This works better than optimizing $\mathcal{L}(\theta, \phi)$ from a random initialization, because a random predictor $f(\mathbf{x}; \theta)$ provides no signal to $\pi(\mathbf{x}; \phi)$ about which features are useful.

5 RELATED WORK

Online feature selection has typically been framed as a sequential decision-making problem and addressed using RL. Among these approaches, Dulac-Arnold et al. (2011); Shim et al. (2017); Janisch et al. (2019) optimize a reward based on the final prediction accuracy and total feature cost, and Kachuee et al. (2018) use a reward that accounts for prediction uncertainty based on MC dropout (Gal & Ghahramani, 2016). RL is a natural approach in this setting, but the policies are difficult to learn in practice: they require complex architectures and training routines (Kachuee et al., 2018; Janisch et al., 2019), are slow to converge, and are sensitive to their initialization (Henderson et al., 2018). As a result, they do not reliably outperform offline selection methods (Erion et al., 2021).

Several other approaches include imitation learning (He et al., 2012; 2016a) and iterative feature scoring methods (Chen et al., 2015; Early et al., 2016b;a). Previous iterative techniques are greedy methods, like ours, but they use scoring heuristics unrelated to maximizing mutual information (see Section 3.2). He et al. (2012; 2016a) effectively cast online selection as supervised classification by using imitation learning, but our training objective bypasses the need for an oracle policy.

Feature selection is a long-standing problem (Guyon & Elisseeff, 2003), and offline feature selection has received the most attention. There are no default approaches for non-linear models like neural networks, but several options include ranking features by local or global importance scores (Breiman, 2001; Shrikumar et al., 2017; Sundararajan et al., 2017; Covert et al., 2020), and *differentiable feature selection* (Balın et al., 2019). For linear models, greedy forward selection and lasso regression are popular choices (Tibshirani, 1996), and both are well-understood from a theoretical perspective (Das & Kempe, 2011). Our method can be viewed as an analogous greedy approach for online feature selection, but unlike the offline version, it is easy to apply with non-linear predictors.

Several prior works have leveraged the Concrete relaxation (Maddison et al., 2016) to learn feature selection strategies by gradient descent. For example, Chang et al. (2017); Balın et al. (2019); Yamada et al. (2020) perform offline feature selection, and Chen et al. (2018); Jethani et al. (2021) perform instance-wise feature selection given access to all the features. To our knowledge, our work is the first to apply this optimization approach to online feature selection.

6 EXPERIMENTS

We now demonstrate the use of our greedy approach on several datasets.[3] We first explore tabular datasets of various sizes, including four medical diagnosis tasks, and we then consider two image classification datasets. Several of the tasks are natural candidates for online feature selection, and the remaining ones serve as useful tasks to test the effectiveness of our approach.

As comparisons for our method, we use several online and offline feature selection baselines. To ensure consistent comparisons, we only use methods applicable to neural networks. As offline baselines, we use two methods that rank feature importance based on model accuracy, permutation tests (Breiman, 2001) and SAGE (Covert et al., 2020). We also use two methods that quantify importance on a per-prediction level, DeepLift (Shrikumar et al., 2017) and Integrated Gradients (Sundararajan et al., 2017). We then use a supervised version of Concrete Autoencoders (Balın et al., 2019), a differentiable feature selection method. As online baselines, we use the RL-based Opportunistic Learning (OL) approach (Kachuee et al., 2018), and we follow the authors' implementation with minor modifications (Appendix C). Finally, we use a version of our iterative procedure from Section 3.2: for simplicity, we train a predictor with random feature subsets (similar to our predictor pre-training), and when scoring features we sample values from their marginal rather than conditional distributions, and we calculate the scoring criterion in eq. (5) using $n = 128$ samples.

---

[3]Link to code removed for anonymity.

Figure 2: Evaluating the greedy online selection approach on three medical diagnosis tasks.

6.1 TABULAR DATASETS

We first applied our method to three medical diagnosis tasks derived from an emergency medicine setting. The tasks involve predicting a patient's blood clotting risk, whether the patient requires respiratory support, and whether the patient will be responsive to fluid resuscitation. Appendix B provides more dataset details. In each of these problems, gathering all possible inputs is impractical due to time and resource constraints, thus making online feature selection a natural solution.

Figure 2 shows the results of applying each method with various feature budgets. We use fully connected architectures for all methods, and we use dropout to reduce overfitting (Srivastava et al., 2014). The classification accuracy is measured via AUROC, and our method achieves the best results at nearly all feature budgets for all three tasks. Among the baselines, several offline methods are sometimes close, but OL provides unstable results and the iterative online method is only competitive on the fluid task. The greedy method's advantage is largest when selecting a small number of features, but it is sometimes narrow once the accuracy saturates.

Next, we conducted experiments using three publicly available tabular datasets: spam classification (Dua & Graff, 2017), particle identification (MiniBooNE) (Roe et al., 2005) and diabetes diagnosis (Miller, 1973). The diabetes task is a natural application for online feature selection and was used in prior work (Kachuee et al., 2018). We again applied each method with various feature numbers, and Appendix E shows plots of the AUROC for each budget; on these tasks, our method is most accurate for all numbers of features. Table 1 summarizes the results via the mean AUROC across $k = 1, \dots, 10$ features, emphasizing the benefits the greedy online method across all six datasets.

The results on these datasets reveal that online methods can often be outperformed by offline methods, including even a simple permutation test (Breiman, 2001). Interestingly, this point was not highlighted in prior work because strong offline comparisons were not used (Kachuee et al., 2018; Janisch et al., 2019). Online methods are in principle capable of performing better, so the sub-par results from OL and the iterative online method underscore the difficulty of simultaneously learning a selection policy and an accurate prediction function for multiple feature sets. According to these results, the greedy method is the online approach to do both successfully. Our networks train more easily for the reasons described in Section 4, and we suspect that OL has difficulty optimizing for larger feature budgets due to its delayed rewards.

Table 1: AUROC comparison, averaged across budgets of 1-10 features.

		Spam	MiniBooNE	Diabetes	Clotting	Fluid	Respiratory
Offline	IntGrad	88.97	87.03	89.15	70.08	80.48	79.28
	DeepLift	88.46	85.85	94.92	68.02	77.09	77.56
	SAGE	92.67	91.63	95.47	70.11	82.99	80.17
	Perm Test	90.28	92.01	95.53	71.15	80.96	78.63
	Differentiable	91.63	92.98	95.70	70.33	77.02	77.02
Online	Iterative	85.01	92.17	95.61	70.63	78.85	84.33
	Opportunistic (OL)	85.84	68.46	83.27	61.50	74.77	77.82
	Greedy Online (Ours)	**94.04**	**94.41**	**96.07**	**72.41**	**84.33**	**85.72**

Figure 3: Greedy online feature selection for image classification. Top left: accuracy comparison on MNIST. Top right: accuracy comparison on CIFAR-10. Bottom: example selections and predictions for our greedy online approach given 10 out of 64 patches for CIFAR-10 images.

6.2 IMAGE CLASSIFICATION DATASETS

Next, we considered two standard image classification datasets: MNIST (LeCun et al., 1998) and CIFAR-10 (Krizhevsky et al., 2009). Our goal is to begin with a blank image, sequentially reveal multiple pixels or patches, and eventually make a classification using a small portion of the image. This is not an obvious use case for online feature selection, but it represents a challenging problem for our method, and similar tasks have been considered in several earlier works (Karayev et al., 2012; Mnih et al., 2014; Early et al., 2016a; Janisch et al., 2019).

For MNIST, we use a fully connected architecture for both the policy and predictor because it reaches sufficient accuracy, and we treat pixels as individual features (where $d = 784$). For CIFAR-10, we use a shared ResNet backbone (He et al., 2016b) for the policy and predictor networks, and each network uses its own output head. The 32×32 images are coarsened into $d = 64$ patches of size 4×4, so the selector head generates a grid of logits corresponding to each patch, and the predictor head generates probabilities for each class.

Figure 3 shows our method's accuracy for different feature budgets. For MNIST, we use the previous baselines but exclude the iterative online method due to its computational cost. We observe a large performance gap, particularly when making a small number of selections: our greedy online method reaches nearly 90% accuracy with just 10 pixels, which is nearly 10% higher than the best baseline and considerably higher than prior work (Balın et al., 2019; Yamada et al., 2020; Covert et al., 2020). OL yields the worst results, and it trains slowly due to the large number of states. For CIFAR-10, we use two simple baselines: center crops and random masks of various sizes. For the random baseline, we plot the mean and standard deviation calculated across ten random masks. Our greedy online approach is slightly less accurate with 1-2 patches, but it reaches significantly higher accuracy when using 5-20 patches. Figure 3 also shows qualitative examples of our method's predictions after selecting 10/64 patches, and Appendix E shows similar plots with different numbers of patches.

7 CONCLUSION

In this work, we introduced a greedy approach to online feature selection that selects features according to their conditional mutual information with the response variable. We then proposed a deep learning approach to learn the greedy policy, and experiments on numerous datasets show that our method outperforms a variety of existing feature selection methods. Future work on this topic may include incorporating non-uniform features costs, automatically determining the feature budget on a per-sample basis, and theoretically characterizing the greedy suboptimality gap. Significant progress has been made in analyzing greedy forward selection in the offline setting (Das & Kempe, 2011), and it is possible that similar theoretical tools will prove useful here.

REFERENCES

National health and nutrition examination survey, 2018. URL `https://www.cdc.gov/nchs/nhanes`.

Brandon Amos. Tutorial on amortized optimization for learning to optimize over continuous domains. *arXiv preprint arXiv:2202.00665*, 2022.

Muhammed Fatih Balın, Abubakar Abid, and James Zou. Concrete autoencoders: Differentiable feature selection and reconstruction. In *International Conference on Machine Learning*, pp. 444–453. PMLR, 2019.

Leo Breiman. Random forests. *Machine Learning*, 45(1):5–32, 2001.

Chun-Hao Chang, Ladislav Rampasek, and Anna Goldenberg. Dropout feature ranking for deep learning models. *arXiv preprint arXiv:1712.08645*, 2017.

Jianbo Chen, Le Song, Martin Wainwright, and Michael Jordan. Learning to explain: An information-theoretic perspective on model interpretation. In *International Conference on Machine Learning*, pp. 883–892. PMLR, 2018.

Suming Chen, Arthur Choi, and Adnan Darwiche. Value of information based on decision robustness. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 29, 2015.

T.M. Cover and J.A. Thomas. *Elements of Information Theory*. Wiley, 2012. ISBN 9781118585771.

Ian Covert, Scott M Lundberg, and Su-In Lee. Understanding global feature contributions with additive importance measures. *Advances in Neural Information Processing Systems*, 33:17212–17223, 2020.

Ian Covert, Scott M Lundberg, and Su-In Lee. Explaining by removing: A unified framework for model explanation. *Journal of Machine Learning Research*, 22:209–1, 2021.

Abhimanyu Das and David Kempe. Submodular meets spectral: Greedy algorithms for subset selection, sparse approximation and dictionary selection. *arXiv preprint arXiv:1102.3975*, 2011.

Dheeru Dua and Casey Graff. UCI machine learning repository, 2017. URL `http://archive.ics.uci.edu/ml`.

Gabriel Dulac-Arnold, Ludovic Denoyer, Philippe Preux, and Patrick Gallinari. Datum-wise classification: a sequential approach to sparsity. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 375–390. Springer, 2011.

Kirstin Early, Stephen E Fienberg, and Jennifer Mankoff. Test time feature ordering with FOCUS: Interactive predictions with minimal user burden. In *Proceedings of the 2016 ACM International Joint Conference on Pervasive and Ubiquitous Computing*, pp. 992–1003, 2016a.

Kirstin Early, Jennifer Mankoff, and Stephen E Fienberg. Dynamic question ordering in online surveys. *arXiv preprint arXiv:1607.04209*, 2016b.

Gabriel Erion, Joseph D Janizek, Carly Hudelson, Richard B Utarnachitt, Andrew M McCoy, Michael R Sayre, Nathan J White, and Su-In Lee. CoAI: Cost-aware artificial intelligence for health care. *medRxiv*, 2021.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning*, pp. 1050–1059. PMLR, 2016.

Tilmann Gneiting and Adrian E Raftery. Strictly proper scoring rules, prediction, and estimation. *Journal of the American Statistical Association*, 102(477):359–378, 2007.

Will Grathwohl, Dami Choi, Yuhuai Wu, Geoff Roeder, and David Duvenaud. Backpropagation through the void: Optimizing control variates for black-box gradient estimation. In *International Conference on Learning Representations*, 2018.

Isabelle Guyon and André Elisseeff. An introduction to variable and feature selection. *Journal of Machine Learning Research*, 3(Mar):1157–1182, 2003.

He He, Hal Daumé III, and Jason Eisner. Cost-sensitive dynamic feature selection. In *ICML Inferning Workshop*, 2012.

He He, Paul Mineiro, and Nikos Karampatziakis. Active information acquisition. *arXiv preprint arXiv:1602.02181*, 2016a.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016b.

Peter Henderson, Riashat Islam, Philip Bachman, Joelle Pineau, Doina Precup, and David Meger. Deep reinforcement learning that matters. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32, 2018.

Oleg Ivanov, Michael Figurnov, and Dmitry Vetrov. Variational autoencoder with arbitrary conditioning. In *International Conference on Learning Representations*, 2018.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with Gumbel-softmax. *arXiv preprint arXiv:1611.01144*, 2016.

Jaromír Janisch, Tomáš Pevný, and Viliam Lisý. Classification with costly features using deep reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 3959–3966, 2019.

Neil Jethani, Mukund Sudarshan, Yindalon Aphinyanaphongs, and Rajesh Ranganath. Have we learned to explain?: How interpretability methods can learn to encode predictions in their interpretations. In *International Conference on Artificial Intelligence and Statistics*, pp. 1459–1467. PMLR, 2021.

Mohammad Kachuee, Orpaz Goldstein, Kimmo Kärkkäinen, Sajad Darabi, and Majid Sarrafzadeh. Opportunistic learning: Budgeted cost-sensitive learning from data streams. In *International Conference on Learning Representations*, 2018.

Mohammad Kachuee, Kimmo Karkkainen, Orpaz Goldstein, Davina Zamanzadeh, and Majid Sarrafzadeh. Cost-sensitive diagnosis and learning leveraging public health data. *arXiv preprint arXiv:1902.07102*, 2019.

Sergey Karayev, Tobias Baumgartner, Mario Fritz, and Trevor Darrell. Timely object recognition. *Advances in Neural Information Processing Systems*, 25, 2012.

Durk P Kingma, Tim Salimans, and Max Welling. Variational dropout and the local reparameterization trick. *Advances in Neural Information Processing Systems*, 28, 2015.

Narine Kokhlikyan, Vivek Miglani, Miguel Martin, Edward Wang, Bilal Alsallakh, Jonathan Reynolds, Alexander Melnikov, Natalia Kliushkina, Carlos Araya, Siqi Yan, et al. Captum: A unified and generic model interpretability library for PyTorch. *arXiv preprint arXiv:2009.07896*, 2020.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Chris J Maddison, Andriy Mnih, and Yee Whye Teh. The Concrete distribution: A continuous relaxation of discrete random variables. *arXiv preprint arXiv:1611.00712*, 2016.

Henry W Miller. Plan and operation of the health and nutrition examination survey, United States, 1971-1973. *DHEW publication no. (PHS)-Dept. of Health, Education, and Welfare (USA)*, 1973.

Andriy Mnih and Karol Gregor. Neural variational inference and learning in belief networks. In *International Conference on Machine Learning*, pp. 1791–1799. PMLR, 2014.

Volodymyr Mnih, Nicolas Heess, Alex Graves, et al. Recurrent models of visual attention. *Advances in Neural Information Processing Systems*, 27, 2014.

Michael W Mosesson. Fibrinogen and fibrin structure and functions. *Journal of Thrombosis and Haemostasis*, 3(8):1894–1904, 2005.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

Jette Randløv and Preben Alstrøm. Learning to drive a bicycle using reinforcement learning and shaping. In *ICML*, volume 98, pp. 463–471. Citeseer, 1998.

BP Roe, HJ Yand, J Zhu, Y Lui, I Stancu, et al. Boosted decision trees, an alternative to artificial neural networks. *Nucl. Instrm. Meth. A*, 543:577–584, 2005.

Hajin Shim, Sung Ju Hwang, and Eunho Yang. Why pay more when you can pay less: A joint learning framework for active feature acquisition and classification. *arXiv preprint arXiv:1709.05964*, 2017.

Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning important features through propagating activation differences. In *International Conference on Machine Learning*, pp. 3145–3153. PMLR, 2017.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The Journal of Machine Learning Research*, 15(1):1929–1958, 2014.

ATLS Subcommittee, International ATLS Working Group, et al. Advanced trauma life support (atls®): the ninth edition. *The Journal of Trauma and Acute Care Surgery*, 74(5):1363–1366, 2013.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*, pp. 3319–3328. PMLR, 2017.

Richard S Sutton, Andrew G Barto, et al. Introduction to reinforcement learning. 1998.

Robert Tibshirani. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society: Series B (Methodological)*, 58(1):267–288, 1996.

George Tucker, Andriy Mnih, Chris J Maddison, John Lawson, and Jascha Sohl-Dickstein. Rebar: Low-variance, unbiased gradient estimates for discrete latent variable models. *Advances in Neural Information Processing Systems*, 30, 2017.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine Learning*, 8(3):229–256, 1992.

Yutaro Yamada, Ofir Lindenbaum, Sahand Negahban, and Yuval Kluger. Feature selection using stochastic gates. In *International Conference on Machine Learning*, pp. 10648–10659. PMLR, 2020.

Jinsung Yoon, James Jordon, and Mihaela van der Schaar. INVASE: Instance-wise variable selection using neural networks. In *International Conference on Learning Representations*, 2018.

Jiahui Yu, Zhe Lin, Jimei Yang, Xiaohui Shen, Xin Lu, and Thomas S Huang. Generative image inpainting with contextual attention. In *Proceedings of the IEEE Conference on Computer vision and Pattern Recognition*, pp. 5505–5514, 2018.

A PROOFS

In this section, we re-state and provide proofs for our main theoretical results. We begin with our proposition regarding the optimal predictor f^* for an arbitrary policy π.

Proposition 1. *When $\mathbf{y}$ is discrete and ℓ is cross-entropy loss, the optimal predictor f^* for any policy π is the Bayes classifier, or $f^*(x_s) = p(\mathbf{y} \mid x_s)$.*

Proof. The optimal prediction given x_s is defined as minimizing the expected loss, where the expectation is with respect to $\mathbf{y}$ and we must condition on the observed values x_s. Because features are selected sequentially by π with no knowledge of the non-selected values, there is no other information to condition on. We can therefore derive the optimal prediction as follows:

$$
\begin{aligned}
f^*(x_s) &= \arg\min_{\hat{y}} \ \mathbb{E}_{\mathbf{y}|x_s}\big[\ell(\hat{y}, \mathbf{y})\big] \\
&= \arg\min_{\hat{y}} \ \sum_{i \in \mathcal{Y}} p(\mathbf{y} = i \mid x_s) \log \hat{y}_i \\
&= \arg\min_{\hat{y}} \ D_{\mathrm{KL}}\big(p(\mathbf{y} \mid x_s) \,\|\, \hat{y}\big) + H(\mathbf{y} \mid x_s) \\
&= p(\mathbf{y} \mid x_s).
\end{aligned}
$$

In the case of a continuous response $\mathbf{y} \in \mathbb{R}$ with squared error loss, we have a similar result involving the response's conditional expectation:

$$
\begin{aligned}
f^*(x_s) &= \arg\min_{\hat{y}} \ \mathbb{E}_{\mathbf{y}|x_s}\big[(\hat{y} - \mathbf{y})^2\big] \\
&= \arg\min_{\hat{y}} \ \mathbb{E}_{\mathbf{y}|x_s}\big[(\hat{y} - \mathbb{E}[\mathbf{y} \mid x_s])^2\big] + \mathrm{Var}(\mathbf{y} \mid x_s) \\
&= \mathbb{E}[\mathbf{y} \mid x_s].
\end{aligned}
$$

$\square$

Proposition 2. *Given the features x_s, the greedy policy π^* selects the feature $\mathbf{x}_i$ having maximum conditional mutual information with the response variable, or*

$$
\pi^*(x_s) = \arg\max_i \ I(\mathbf{y}; \mathbf{x}_i \mid x_s). \tag{9}
$$

Proof. Consider the expected loss after observing an additional feature $\mathbf{x}_i$ given the values x_s. The only available information is x_s, so our expected loss is with respect to the conditional distribution $\mathbf{y}, \mathbf{x}_i \mid x_s$. We thus have the following expected loss:

$$
\begin{aligned}
\mathbb{E}_{\mathbf{y},\mathbf{x}_i|x_s}\big[\ell(f^*(x_s \cup \mathbf{x}_i), \mathbf{y})\big] &= \mathbb{E}_{\mathbf{y},\mathbf{x}_i|x_s}\big[\ell(p(\mathbf{y} \mid x_s, \mathbf{x}_i), \mathbf{y})\big] \\
&= \mathbb{E}_{\mathbf{x}_i|x_s}\Big[\mathbb{E}_{\mathbf{y}|x_s,\mathbf{x}_i}[\ell(p(\mathbf{y} \mid x_s, \mathbf{x}_i), \mathbf{y})]\Big] \\
&= \mathbb{E}_{\mathbf{x}_i|x_s}\big[H(\mathbf{y} \mid x_s, \mathbf{x}_i)\big] \\
&= H(\mathbf{y} \mid x_s) - I(\mathbf{y}; \mathbf{x}_i \mid x_s).
\end{aligned}
$$

Note that $H(\mathbf{y} \mid x_s)$ is a constant that does not depend on i. When identifying the index that yields the minimum expected loss, we thus have the following result:

$$
\arg\min_i \ \mathbb{E}_{\mathbf{y},\mathbf{x}_i|x_s}\big[\ell(f^*(x_s \cup \mathbf{x}_i), \mathbf{y})\big] = \arg\max_i \ I(\mathbf{y}; \mathbf{x}_i \mid x_s).
$$

In the case of a continuous response with squared error loss where the predictor is $f^*(x_s) = \mathbb{E}[\mathbf{y} \mid x_s]$, we have a similar result:

$$
\begin{aligned}
\mathbb{E}_{\mathbf{y}, \mathbf{x}_i \mid x_s}\big[(f^*(x_s \cup \mathbf{x}_i) - \mathbf{y})^2\big] &= \mathbb{E}_{\mathbf{y}, \mathbf{x}_i \mid x_s}\big[(\mathbb{E}[\mathbf{y} \mid x_s, \mathbf{x}_i] - \mathbf{y})^2\big] \\
&= \mathbb{E}_{\mathbf{x}_i \mid x_s}\Big[\mathbb{E}_{\mathbf{y} \mid x_s, \mathbf{x}_i}[(\mathbb{E}[\mathbf{y} \mid x_s, \mathbf{x}_i] - \mathbf{y})^2]\Big] \\
&= \mathbb{E}_{\mathbf{x}_i \mid x_s}[\mathrm{Var}(\mathbf{y} \mid x_s, \mathbf{x}_i)].
\end{aligned}
$$

When selecting the index with minimum expected loss, our selection is thus the following:

$$
\arg\min_i \ \mathbb{E}_{\mathbf{x}_i \mid x_s}[\mathrm{Var}(\mathbf{y} \mid x_s, \mathbf{x}_i)].
$$

$\square$

We also prove the limiting result presented in eq. (6), which states that $I_i^n \to I(\mathbf{y}; \mathbf{x}_i \mid x_s)$.

Proof. Conditional mutual information $I(\mathbf{y}; \mathbf{x}_i \mid x_s)$ is defined as follows (Cover & Thomas, 2012):

$$
I(\mathbf{y}; \mathbf{x}_i \mid x_s) = \mathbb{E}_{\mathbf{y}, \mathbf{x}_i \mid x_s}\left[\log \frac{p(\mathbf{y}, \mathbf{x}_i \mid x_s)}{p(\mathbf{x}_i \mid x_s)p(\mathbf{y} \mid x_s)}\right].
$$

Rearranging terms, we can also write it as an expected KL divergence:

$$
\begin{aligned}
I(\mathbf{y}; \mathbf{x}_i \mid x_s) &= \mathbb{E}_{\mathbf{x}_i \mid x_s}\mathbb{E}_{\mathbf{y} \mid x_s, \mathbf{x}_i}\left[\log \frac{p(\mathbf{y}, \mathbf{x}_i \mid x_s)}{p(\mathbf{x}_i \mid x_s)p(\mathbf{y} \mid x_s)}\right] \\
&= \mathbb{E}_{\mathbf{x}_i \mid x_s}\mathbb{E}_{\mathbf{y} \mid x_s, \mathbf{x}_i}\left[\log \frac{p(\mathbf{y} \mid x_s, \mathbf{x}_i)}{p(\mathbf{y} \mid x_s)}\right] \\
&= \mathbb{E}_{\mathbf{x}_i \mid x_s}\Big[D_{\mathrm{KL}}\big(p(\mathbf{y} \mid x_s, \mathbf{x}_i) \,\|\, p(\mathbf{y} \mid x_s)\big)\Big]
\end{aligned}
$$

Now, when we sample multiple values $x_i^1, \ldots, x_i^n \sim p(\mathbf{x}_i \mid x_s)$ and make predictions using the Bayes classifier, we have the following mean prediction as n becomes large:

$$
\lim_{n \to \infty} \frac{1}{n} \sum_{j=1}^{n} p(\mathbf{y} \mid x_s, x_i^j) = \mathbb{E}_{\mathbf{x}_i \mid x_s}\big[p(\mathbf{y} \mid x_s, \mathbf{x}_i)\big] = p(\mathbf{y} \mid x_s).
$$

Calculating the mean KL divergence across each of the predictions, we arrive at the following result:

$$
\lim_{n \to \infty} I_i^n = \mathbb{E}_{\mathbf{x}_i \mid x_s}\Big[D_{\mathrm{KL}}\big(p(\mathbf{y} \mid x_s, \mathbf{x}_i) \,\|\, p(\mathbf{y} \mid x_s)\big)\Big] = I(\mathbf{y}; \mathbf{x}_i \mid x_s).
$$

$\square$

Theorem 1. *When $\mathbf{y}$ is discrete and ℓ is cross-entropy loss, the global optimum of eq. (8) is a predictor that satisfies $f(x_s; \theta^*) = p(\mathbf{y} \mid x_s)$ and a policy $\pi(x_s; \phi^*)$ that puts all probability mass on $i^* = \arg\max_i I(\mathbf{y}; \mathbf{x}_i \mid x_s)$.*

Proof. We first consider the predictor network $f(\mathbf{x}_s; \theta)$. When the predictor is given the feature values x_s, it means that one index $i \in s$ was chosen by the policy according to $\pi(x_{s \setminus i}; \phi)$ and the remaining indices $s \setminus i$ were sampled from $p(\mathbf{s})$. Because $\mathbf{s}$ is sampled independently from $(\mathbf{x}, \mathbf{y})$, and because $\pi(x_{s \setminus i}; \phi)$ is not given access to $(\mathbf{x}_{\bar{s} \cup i}, \mathbf{y})$, the predictor's expected loss must be

considered with respect to the distribution $\mathbf{y} \mid x_s$. The globally optimal predictor $f(x_s; \theta^*)$ is thus defined as follows, regardless of the selection policy $\pi(x_s; \phi)$ and which index i was selected last:

$$f(x_s; \theta^*) = \arg \min_{\hat{y}} \ \mathbb{E}_{\mathbf{y}|x_s}\big[\ell(\hat{y}, \mathbf{y})\big] = p(\mathbf{y} \mid x_s).$$

The above result follows from our proof for Proposition 1. Now, given the optimal predictor $f(x_s; \theta^*)$, we can define the globally optimal policy by minimizing the expected loss for a fixed input x_s. Denoting the probability mass placed on each index $i \in [d]$ as $\pi_i(x_s; \phi)$, where $\pi(x_s; \phi) \in \Delta^{d-1}$, the expected loss is the following:

$$\mathbb{E}_{i \sim \pi(x_s;\phi)}\mathbb{E}_{\mathbf{y},\mathbf{x}_i|x_s}\big[\ell(f(x_s \cup \mathbf{x}_i; \theta^*), \mathbf{y})\big] = \sum_{i \in [d]} \pi_i(x_s; \phi)\mathbb{E}_{\mathbf{y},\mathbf{x}_i|x_s}\big[\ell\big(f(x_s \cup \mathbf{x}_i; \theta^*), \mathbf{y}\big)\big]$$

$$= \sum_{i \in [d]} \pi_i(x_s; \phi)\mathbb{E}_{\mathbf{x}_i|x_s}[H(\mathbf{y} \mid x_s, \mathbf{x}_i)].$$

The above result follows from our proof for Proposition 2. If there exists a single index $i^* \in [d]$ that yields the lowest expected conditional entropy, or

$$\mathbb{E}_{\mathbf{x}_{i^*}|x_s}[H(\mathbf{y} \mid x_s, \mathbf{x}_{i^*})] < \mathbb{E}_{\mathbf{x}_i|x_s}[H(\mathbf{y} \mid x_s, \mathbf{x}_i)] \quad \forall i \neq i^*,$$

then the optimal predictor must put all its probability mass on i^*, or $\pi_{i^*}(x_s; \phi^*) = 1$. Note that the corresponding feature $\mathbf{x}_{i^*}$ has maximum conditional mutual information with $\mathbf{y}$, because we have

$$I(\mathbf{y}; \mathbf{x}_{i^*} \mid x_s) = \underbrace{H(\mathbf{y} \mid x_s)}_{\text{Constant}} - \mathbb{E}_{\mathbf{x}_{i^*}|x_s}[H(\mathbf{y} \mid x_s, \mathbf{x}_{i^*})].$$

To summarize, we derived the global optimum to our objective $\mathcal{L}(\theta, \phi)$ by first considering the optimal predictor $f(\mathbf{x}_s; \theta^*)$, and then the optimal policy $\pi(\mathbf{x}_s; \phi^*)$ assuming the optimal predictor. $\square$

Theorem 2. *When $\mathbf{y}$ is continuous and ℓ is squared error loss, the global optimum of eq. (8) is a predictor that satisfies $f(x_s; \theta^*) = \mathbb{E}[\mathbf{y} \mid x_s]$ and a policy $\pi(x_s; \phi^*)$ that puts all probability mass on $i^* = \arg \min_i \mathbb{E}_{\mathbf{x}_i|x_s}[\text{Var}(\mathbf{y} \mid x_s, \mathbf{x}_i)]$.*

Proof. Our proof follows the same logic as our proof for Theorem 1. For the optimal predictor given an arbitrary policy, we have:

$$f(x_s; \theta^*) = \arg \min_{\hat{y}} \ \mathbb{E}_{\mathbf{y}|x_s}\big[(\hat{y} - \mathbf{y})^2\big] = \mathbb{E}[\mathbf{y} \mid x_s].$$

Then, for the policy's expected loss, we have:

$$\mathbb{E}_{i \sim \pi(x_s;\phi)}\mathbb{E}_{\mathbf{y},\mathbf{x}_i|x_s}\big[\big(f(x_s \cup \mathbf{x}_i; \theta^*) - \mathbf{y}\big)^2\big] = \sum_{i \in [d]} \pi_i(x_s; \phi)\mathbb{E}_{\mathbf{x}_i|x_s}[\text{Var}(\mathbf{y} \mid x_s, \mathbf{x}_i)].$$

If there exists an index $i^* \in [d]$ that yields the lowest expected conditional variance, then the optimal policy must put all its probability mass on i^*, or $\pi_{i^*}(x_s; \phi^*) = 1$. $\square$

B DATASETS

The datasets used in our experiments are summarized in Table 2. Three of the tabular datasets and the two image classification datasets are publicly available, and the three emergency medicine tasks were privately curated from a university hospital system.

Table 2: Summary of datasets used in our experiments.

Dataset	# Features	# Feature Groups	# Classes	# Samples
Fluid	224	162	2	2,850
Respiratory	112	37	2	65,515
Clotting	121	46	2	6,496
Spam	58	–	2	4,601
MiniBooNE	51	–	2	130,064
Diabetes	45	–	3	92,062
MNIST	784	–	10	60,000
CIFAR-10	1,024	64	10	60,000

B.1 MINIBOONE AND SPAM CLASSIFICATION

The spam dataset includes features extracted from e-mail messages to predict whether or not a message is spam. Three features describes the shortest, average, and total length of letters in the message, and the remaining 54 features describe the frequency with which certain key words are used. The MiniBooNE particle identification dataset involves distinguishing electron neutrinos from muon neutrinos based on various continuous features (Roe et al., 2005). Both datasets were obtained from the UCI repository (Dua & Graff, 2017).

B.2 DIABETES CLASSIFICATION

This dataset is obtained from from the National Health and Nutrition Examination Survey (NHANES) (NHA, 2018), an ongoing survey designed to assess the well-being of adults and children in the United States. We used a version of the data pre-processed by Kachuee et al. (2018; 2019) that includes data collected from 1999 through 2016. The input features include demographic information (age, gender, ethnicity, etc.), lab results (total cholesterol, triglyceride, etc.), examination data (weight, height, etc.), and questionnaire answers (smoking, alcohol, sleep habits, etc.). An expert was also asked to suggest costs for each feature based on the financial burden, patient privacy, and patient inconvenience, but we assume uniform feature costs in our experiments for simplicity. Finally, the fasting glucose values were used to define three classes based on standard threshold values: normal, pre-diabetes, and diabetes.

B.3 IMAGE CLASSIFICATION DATASETS

The MNIST and CIFAR-10 datasets were downloaded using PyTorch (Paszke et al., 2017). We used the standard train-test splits, and we split the train set to get a validation set with the same size as the test set.

B.4 EMERGENCY MEDICINE DATASETS

The emergency medicine data used in this study was gathered over a 13-year period (2007-2020) and encompasses 14,463 emergency department admissions. We excluded patients under the age of 18, and we curated 3 clinical cohorts commonly seen in pre-hospitalization settings. These include 1) pre-hospital fluid resuscitation, 2) emergency department respiratory support, and 3) blood clotting. These datasets are not publicly available due to patient privacy concerns.

Pre-hospital fluid resuscitation We selected 224 variables that were available in the pre-hospital setting, including dispatch information (injury date, time, cause, and location), demographic information (age, sex), and pre-hospital vital signs (blood pressure, heart rate, respiratory rate). The outcome was each patient's response to fluid resuscitation, following the Advanced Trauma Life Support (ATLS) definition (Subcommittee et al., 2013).

Emergency department respiratory support In this cohort, our goal is to predict which patients require respiratory support upon arrival in the emergency department. Similar to the previous dataset, we selected 112 pre-hospital clinical features including dispatch information (injury date, time, cause, and location), demographic information (age, sex), and pre-hospital vital signs (blood pressure, heart rate, respiratory rate). The outcome is defined based on whether a patient received respiratory support, including both invasive (intubation) and non-invasive (BiPap) approaches.

Blood clotting In this cohort, we only included patients whose fibrinogen levels were measured, as this provides an indicator for blood clotting or fibrinolysis (Mosesson, 2005). Like the previous datasets, demographic information, dispatch information, and pre-hospital observations were used as input features. The outcome, based on experts' opinion, was defined by whether an individual's fibrinogen level is above 200 mg/dL, which represents higher risk of blood clotting.

C BASELINES

This section provides more details on the baseline methods used in our experiments (Section 6).

C.1 GLOBAL FEATURE IMPORTANCE METHODS

Two of our offline feature selection baselines, permutation tests and SAGE, are known as *global feature importance methods* because they rank features based on their role in improving model accuracy (Covert et al., 2021). In our experiments, we run each method using a single classifier trained on the entire dataset, and we then select the top k features depending on the budget.

When running the permutation test, we evaluate the validation AUROC while replacing values in the corresponding feature column with random draws from the training set. When running SAGE, we use the authors' implementation with automatic convergence detection Covert et al. (2020). For the six tabular datasets, we average across 128 sampled values for the held-out features, and for MNIST we use a zeros baseline to achieve faster convergence.

C.2 LOCAL FEATURE IMPORTANCE METHODS

Two of our offline feature selection baselines, DeepLift and Integrated Gradients, are known as *local feature importance methods* because they rank features based on their importance to a single prediction. In our experiments, we generate feature importance scores for the true class using all examples in the validation set. We then select the top k features based on their mean absolute importance. We use a mean baseline for Integrated Gradients (Sundararajan et al., 2017), and both methods were run using the Captum package (Kokhlikyan et al., 2020).

C.3 OPPORTUNISTIC LEARNING

Kachuee et al. (2018) proposed Opportunistic Learning (OL), an approach to solve online feature selection using RL. The approach consists of two networks analogous to our policy and predictor: a Q-network that estimates the value associated with each action, where actions correspond to features, and a P-network responsible for making predictions. When using OL, we use the same network architectures as our approach, and OL shares network parameters between the P- and Q-networks.

Kachuee et al. (2018) introduce a utility function for their reward, shown in eq. (10), which calculates the difference in prediction uncertainty as approximated by MC dropout (Gal & Ghahramani, 2016). The reward also accounts for feature costs, but we set all feature costs to $c_i = 1$.

$$r_i = \frac{||Cert(x_s) - Cert(x_s \cup x_i)||}{c_i} \tag{10}$$

To provide a fair comparison with the remaining methods, we made several modifications to the authors' implementation. These include 1) preventing the prediction action until the pre-specified budget is met, 2) setting all feature costs to be identical, and 3) supporting pre-defined feature groups as described in Appendix D.3. When training, we update the P-, Q-, and target Q-networks every $1 + \frac{d}{100}$ experiences, where d is the number of features in a dataset. In addition, the replay buffer is set to store the $1000d$ most recent experiences, and the random exploration probability is decayed so that it eventually reaches a value of 0.1.

D TRAINING APPROACH AND HYPERPARAMETERS

This section provides more details on our training approach and selected hyperparameters.

D.1 TRAINING PSEUDOCODE

Algorithm 1 summarizes our training approach. Briefly, we select features by drawing a Concrete sample using policy network's logits, we calculate the loss based on the subsequent prediction, and we then update the mask for the next step using a discrete sample from the policy's distribution. We implemented this approach using PyTorch (Paszke et al., 2017) and PyTorch Lightning[4].

Algorithm 1: Training pseudocode

Input: Data distribution $p(\mathbf{x}, \mathbf{y})$, budget $k > 0$, learning rate $\gamma > 0$, temperature $\tau > 0$
Output: Predictor model $f(\mathbf{x}; \theta)$, selector model $\pi(\mathbf{x}; \phi)$
initialize $f(\mathbf{x}; \theta), \pi(\mathbf{x}; \phi)$
while *not converged* **do**
    sample $x, y \sim p(\mathbf{x}, \mathbf{y})$
    initialize $\mathcal{L} = 0, m = [0, \ldots, 0]$
    for $j = 1$ **to** k **do**
        calculate logits $\alpha = \pi(x \odot m; \phi)$, sample $G_i \sim$ Gumbel for $i \in [d]$
        set $\tilde{m} = \max\big(m, \text{softmax}(G + \alpha, \tau)\big)$ // update with Concrete
        set $m = \max\big(m, \text{softmax}(G + \alpha, 0)\big)$ // update with one-hot
        update $\mathcal{L} \leftarrow \mathcal{L} + \ell\big(f(x \odot \tilde{m}; \theta), y\big)$
    end
    update $\theta \leftarrow \theta - \gamma \nabla_\theta \mathcal{L}, \ \ \phi \leftarrow \phi - \gamma \nabla_\phi \mathcal{L}$
end
return $f(\mathbf{x}; \theta), \pi(\mathbf{x}; \phi)$

D.2 HYPERPARAMETERS

Our experiments with the six tabular datasets all used fully connected architectures with dropout in all layers (Srivastava et al., 2014). The dropout probability is set to 0.3, the networks have two hidden layers of width 128, and we performed early stopping using the validation loss. For our method, the predictor and selector were separate networks with identical architectures. When training models with the features selected by offline methods, we reported results using the best model from multiple training runs based on the validation loss. We did not perform any additional hyperparameter tuning due to the large number of models being trained.

For MNIST, we used fully connected architectures with two layers of width 512 and the dropout probability set to 0.3. Again, our method used separate networks with identical architectures. For CIFAR-10, we used a shared ResNet backbone (He et al., 2016b) consisting of several residually connected convolutional layers. The classification head consists of global average pooling and a linear layer, and the selection head consisted of a transposed convolution layer followed by a 1×1

---

[4]https://www.pytorchlightning.ai

convolution, which output a grid of logits with size 8×8. Our CIFAR-10 networks are trained using random crops and random horizontal flips as augmentations.

D.3 FEATURE GROUPING

All of the methods used in our experiments were designed to select individual features, but this is undesirable when using categorical features with one-hot encodings. Each of our three emergency medicine tasks involve such features, so we extended each method to support feature grouping.

SAGE and permutation tests are trivial to extend to feature groups: we simply removed groups of features rather than individual ones. For DeepLift and Integrated Gradients, we used the summed importance within each group, which preserves each method's additivity property. For the differentiable method based on Concrete Autoencoders (Balın et al., 2019), we implemented a generalized version of the selection layer that operates on feature groups. We also extended OL to operate on feature groups by having the actions map to groups rather than individual features.

Finally, for our method, we parameterized the policy network $\pi(\mathbf{x}; \phi)$ so that the number of outputs is the number of groups g rather than the total number of features d (where $g \leq d$). When applying masking, we first generate a binary mask $m \in [0, 1]^g$, and we then project the mask into $[0, 1]^d$ using a binary groups matrix $M \in \{0, 1\}^{d \times g}$, where $M_{ij} = 1$ if feature i is in group j and $M_{ij} = 0$ otherwise. Thus, our masked input vector is given by $x \odot (Mm)$.

E   ADDITIONAL RESULTS

This section provides several additional experimental results. First, Figure 4 shows the same results as Figure 2 but larger. Next, Figure 5 shows the AUROC for each method under different feature budgets on the three publicly available tabular datasets. Here, our greedy online approach achieves the best results for all feature budgets on all three tasks. Notably, our two online selection baselines are often outperformed by offline methods, particularly the unstable OL method trained using RL.

Finally, Figure 6 displays examples of CIFAR-10 predictions given different numbers of revealed patches. The predictions generally become accurate after revealing only a small number of patches, reflecting a similar result as Figure 3. Qualitatively, we can see that the policy network learns to select vertical stripes, but the order in which it fills out each stripe depends on where it guesses important information may be located.

Figure 4: AUROC comparison on three medical diagnosis tasks.

Figure 5: AUROC comparison on three tabular datasets.

Figure 6: CIFAR-10 predictions with different numbers of patches revealed by our greedy online method.