Symbolic Mechanistic Data Attribution: Tracing Training Influence to Learned Behavioral Policies

Abstract

While existing data attribution methods can identify which training examples build specific mechanistic circuits, they cannot explain how training data shapes the high-level behavioral decisions a model learns to make. To bridge this gap, we introduce Symbolic Mechanistic Data Attribution (SMDA), a framework that attributes training pairs to the interpretable symbolic policies governing model behavior. SMDA fits a closed-form Ridge regression over sparse autoencoder (SAE) features to model a target behavior, then analytically decomposes how each supervised fine-tuning example shifts that policy through feature-activation (ΔX) and output-probability (ΔY) pathways. We distill a symbolic policy for refusal behavior in Llama-3.2-3B-Instruct and analyze 200 SFT training pairs. Our analysis reveals that (1) the symbolic policy's coefficients expose systematic gaps in the base model's safety behavior for categories like religious stereotyping; (2) per-feature $\Delta X/\Delta Y$ decomposition can mechanistically explain why harmful and harmless pairs exert qualitatively different influences on certain features; and (3) individual training pairs routinely exhibit cross-feature interference, allowing SMDA to identify training pairs whose dominant effect falls on unintended features. These results demonstrate that combining mechanistic interpretability with data attribution yields a diagnostic tool that is both more fine-grained than black-box influence functions and more scalable than manual circuit analysis.

1 Introduction

The widespread deployment of large language models (LLMs) has been accompanied by a parallel rise of interest in mechanistic interpretability (MI), a line of work that aims to reverse-engineer neural networks into human-understandable algorithms, circuits, and representations (Olsson et al., 2022). Rather than treating LLMs as black boxes, MI seeks to identify the internal components and computations responsible for observed behavior. This program has already yielded notable successes in Transformer-based models. For example, induction heads have been identified as a core mechanism underlying in-context copying and pattern completion (Olsson et al., 2022), while sparse autoencoders (SAEs) have emerged as a powerful method for decomposing polysemantic activations into more interpretable features (Cunningham et al., 2023). Together, these results suggest that LLMs learn structured internal representations that can, at least in part, be systematically understood.

However, understanding internal structure alone is not enough. For many behaviors of interest such as capabilities, failures, and safety-relevant tendencies, we also want to know which parts of the training data caused those mechanisms and behaviors to emerge. Prior work on influence functions and data attribution has studied how individual training examples affect model predictions, parameters, or generalization behavior (Koh and Liang, 2017; Chan et al., 2022; Grosse et al., 2023; Kowal et al., 2026). Recent work on Mechanistic Data Attribution (MDA) brings this perspective into MI by tracing the training origins of interpretable model components such as neurons, attention heads, and SAE features (Chen et al., 2026).

Despite its promise, existing MDA is best suited to settings where the attribution target is already a well-characterized low-level circuit or unit. This limits its applicability to many higher-level behavioral phenomena relevant to alignment and safety, such as harmful compliance, sycophancy, or misinformation, where the underlying circuit is not known a priori (Chen et al., 2026). Moreover, existing MDA primarily identifies which training examples are influential, but offers less leverage for explaining what shared semantic or structural properties make those examples mechanistically important. They are also typically applied after training,

which makes them less natural for tracking how a behavior is being acquired over the course of fine-tuning. Taken together, these limitations motivate a more flexible attribution target: one that remains interpretable, but does not require a known circuit in advance.

In this paper, we propose *Symbolic Mechanistic Data Attribution (SMDA)*, a framework that attributes training influence to a learned symbolic policy over SAE features, through a case study on refusal revealing the learned algorithm underlying a model's refusal and compliance decisions and identifying how potential training data would affect it. Rather than attributing to a predefined neuron, attention head, or known circuit, SMDA first fits an interpretable symbolic model of behavior and then measures how each supervised fine-tuning (SFT) example shifts that symbolic policy. This preserves the mechanistic spirit of MDA while extending it to settings where the underlying circuit is not known a priori. In this work, we instantiate SMDA on refusal behavior as a safety-critical case study.

Concretely, our approach uses SAE features as the basis of a symbolic refusal policy and treats the weights of that policy as the object of attribution. We fit a closed-form Ridge regression over a small set of labeled SAE features to model refusal propensity, and then analyze how an SFT training example changes this symbolic model through two pathways: by shifting internal feature activations and by shifting the model's refusal tendency. This yields a mechanistically grounded attribution score that connects individual training examples to changes in an interpretable behavioral policy, rather than only to a raw output or a predefined low-level component.

Our contributions are as follows. First, we introduce SMDA, a framework in which the attribution target is a learned symbolic policy over SAE features rather than a hand-specified circuit component, and derive a closed-form influence computation that decomposes training effects into feature-activation and output-probability pathways (§3). Second, we distill an interpretable symbolic policy categorizing Llama-3.2-3B-Instruct's refusal behavior and collect and analyze data on how 200 SFT training pairs affect this policy (§5.1). Third, we demonstrate feature-wise and prompt-wise attribution, finding that per-feature $\Delta X/\Delta Y$ decomposition can reveal mechanistically why harmful and harmless pairs exert qualitatively different influence, and that individual training pairs routinely exhibit cross-feature interference, with SMDA able to identify pairs whose dominant effect falls on unintended features (§5.2 and §5.3).

2 Related Work

Mechanistic interpretability and sparse features. Mechanistic interpretability aims to reverse-engineer neural networks into human-understandable components and algorithms (Olsson et al., 2022). Early successes in Transformers include the identification of induction heads as a core mechanism supporting in-context learning (Olsson et al., 2022). More broadly, the field has developed a toolkit for locating and causally validating candidate mechanisms, including activation patching, causal ablation, and direction-based interventions. A central challenge in this literature is polysemanticity, where individual neurons participate in multiple unrelated behaviors. Sparse autoencoders (SAEs) address this by decomposing activations into more interpretable features, often providing a more useful basis for mechanistic analysis than raw neurons alone (Cunningham et al., 2023). Our work builds on this paradigm by using SAE features as the interpretable basis of a symbolic behavioral policy.

Symbolic models of neural behavior. A growing line of work seeks to distill neural computations into explicit symbolic representations. Recent work on circuit distillation extracts human-readable algorithmic descriptions from mechanistically identified circuits (Wadhwa et al., 2025). Closely related, symbolic-mechanistic evaluation combines symbolic behavioral descriptions with mechanistic interventions to test whether a model is not only accurate, but internally consistent with an intended mechanism (Habibi et al., 2026). Our work is aligned with this tradition, but uses a symbolic model for a different purpose: not only to describe behavior, but to serve as the target of training-data attribution. In SMDA, the symbolic object is a learned policy over SAE features, which allows attribution to operate over an interpretable behavioral representation even when no single circuit is known in advance.

Training-data attribution and influence functions. Influence functions estimate how up-weighting or removing a training example changes model parameters or predictions (Koh and Liang,

2017). Subsequent work has adapted these ideas to modern language models, including scalable approximations for studying generalization behavior in LLMs (Grosse et al., 2023). Recent work has also moved beyond attribution to individual examples and labels by targeting semantically meaningful directions, as in Concept Influence (Kowal et al., 2026). The closest precursor to our work is Mechanistic Data Attribution (MDA), which traces the training origins of interpretable units such as neurons, attention heads, and SAE features (Chen et al., 2026). SMDA differs from MDA in its attribution target: rather than attributing to a pre-specified unit or known low-level circuit, it attributes to a learned symbolic policy over interpretable features. This makes it better suited to higher-level behaviors whose underlying circuit structure is not known a priori.

Refusal mechanisms and safety fine-tuning. Recent work has shown that refusal in open-source language models is mediated by a relatively simple direction in activation space, and that ablating or injecting this direction can suppress or induce refusal behavior (Arditi et al., 2024). Other work has shown that even small amounts of safety fine-tuning data can substantially affect refusal behavior, while also creating tradeoffs such as over-refusal on benign prompts (Bianchi et al., 2024). These findings make refusal a useful setting for studying training-data attribution: it is safety-relevant, mechanistically meaningful, and sensitive to fine-tuning data. We build on this literature by treating refusal not as a fully solved circuit-level target, but as a case study for symbolic mechanistic data attribution in a higher-level behavioral setting.

3 Symbolic Mechanistic Data Attribution Framework

3.1 Overview

We introduce **Symbolic Mechanistic Data Attribution** (SMDA), an extension of Mechanistic Data Attribution (MDA) (Chen et al., 2026) in which the attribution target is not a pre-specified neuron, attention head, or known circuit, but a learned symbolic policy over interpretable SAE features. Given a supervised fine-tuning (SFT) training pair $z_i = (\text{prompt}_i, \text{response}_i)$, SMDA asks how a single gradient update on z_i changes this symbolic policy. Our framework maintains a strict separation between the SFT training pairs and the evaluation set on which the symbolic policy is fit. Concretely,

we first fit a symbolic refusal policy on a held-out evaluation set, then measure how each SFT training pair would counterfactually perturb that policy through two pathways: by changing internal feature activations X, and by changing the model's refusal propensity Y. Because the symbolic policy is a closed-form Ridge regression, these effects can be combined analytically to yield an interpretable attribution score over policy weights.

3.2 Symbolic Policy Model

The symbolic policy is the downstream object of attribution in SMDA. Rather than attributing training examples directly to a black-box model output or to a hand-specified circuit component, we attribute them to changes in the weights of a learned symbolic model over SAE features. We extract SAE feature activations from a target layer ℓ of the base model, retaining a subset of d features whose activations differ substantively between harmful and harmless prompts. We then fit a Ridge regression on an evaluation set of n prompts. Let $X \in R^{n \times d}$ denote the matrix of selected SAE feature activations and $Y \in R^n$ the corresponding refusal log-probabilities $\log p(\text{"I can't"})$ under the model (This serves as a proxy for refusal, following (Arditi et al., 2024); See Appendix A.2) We define

$$U = X^\top X + \lambda I, \qquad W = U^{-1} X^\top Y,$$

where λ is selected by 10-fold cross-validation and a separate symbolic policy is fit for each experiment. The vector $W \in R^d$ constitutes the symbolic policy weight vector. Each entry W_j captures how strongly SAE feature j contributes to the model's refusal propensity in the distilled symbolic policy. In our instantiation, we use a BatchTopK SAE trained on residual stream activations of `Llama-3.2-3B-Instruct` at layer $\ell = 10$, selected via causal probing as the layer with the strongest refusal mediation (Appendix A.1). From the full 12,288 SAE features, we retain $d = 75$ whose mean activation differs by more than 0.1 between harmful and harmless prompts, yielding 25 features with higher harmful activation and 50 with higher harmless activation. Each feature is assigned a descriptive label via a contrastive prompting procedure with substantial inter-rater agreement (Appendix A.1.2).

3.3 Influence Computation

Given an SFT training pair z_i, we approximate the effect of a single gradient step on z_i by com-

puting the induced parameter perturbation $\delta\theta_i$ and propagating it through the symbolic policy. The key quantity is the resulting shift in the symbolic weight vector,

$$\Delta W_i = W(\theta + \delta\theta_i) - W(\theta),$$

which we interpret as the influence of z_i on the symbolic refusal policy. This perturbation reaches W through two channels. First, the gradient step changes the model's internal residual-stream activations at layer ℓ, which in turn changes the selected SAE feature activations X. Second, it changes the refusal log-probabilities Y on the evaluation set. Using a first-order expansion of the Ridge solution, we decompose the induced policy shift as

$$\Delta W \approx \underbrace{\frac{\partial W}{\partial X} \cdot \Delta X}_{\text{X pathway}} + \underbrace{\frac{\partial W}{\partial Y} \cdot \Delta Y}_{\text{Y pathway}},$$

where

$$\Delta X = X(\theta + \delta\theta_i) - X(\theta),$$

$$\Delta Y = Y(\theta + \delta\theta_i) - Y(\theta).$$

For Ridge regression, a first-order expansion gives

$$\Delta W \approx U^{-1}\Big(\Delta X^\top Y + X^\top \Delta Y - \Delta U \, W\Big),$$

with $\Delta U = \Delta X^\top X + X^\top \Delta X$. This expression makes the two pathways explicit: ΔX changes both the design matrix term and the regularized covariance structure, while ΔY changes the regression target directly. We provide the full derivation in Appendix A.3. Computing Δh_ℓ analytically for every evaluation prompt would require backpropagating through all parameters of the model for each training pair, which is computationally infeasible. We therefore measure

$$\Delta h_\ell = h_\ell(\theta + \delta\theta_i) - h_\ell(\theta)$$

numerically, by hooking the residual stream before and after a single gradient step on z_i. We then obtain ΔX by linearizing the SAE encoder around the baseline activations, restricting the Jacobian to the selected features and active ReLU gates (Appendix A.3). Finally, we summarize the effect of z_i on the symbolic policy by the scalar score

$$\text{InfluenceScore}(z_i) = \langle \Delta W_i, W \rangle = \sum_{j=1}^{d} \Delta W_{i,j} \, W_j.$$

This score is positive when a training example pushes the feature weight in the symbolic policy further in its current direction, and negative when it pushes against it. We do not normalize by gradient norm, as this produced a strong negative correlation with the raw influence score ($r = -0.80$) and inverted the expected ordering between harmful-refusal and harmless-compliance pairs.

4 Experimental Setup

4.1 Model and SAE Feature Basis

All experiments use `Llama-3.2-3B-Instruct` as the base model, with the SAE architecture and feature selection described in §3.2. The SAE uses $k = 40$ active features per token. Each selected feature is assigned a descriptive label using a contrastive prompting procedure with `GPT-5.4-mini` (Appendix A.1.2). Label quality is assessed by two independent researchers, yielding a mean score of 0.76 out of 1 and substantial inter-rater agreement (linear weighted Cohen's $\kappa = 0.648$, $n = 25$).

4.2 Evaluation Splits

We experiment with three main evaluation splits drawn from our full 11,000-prompt evaluation dataset (Appendix A.2) to probe different aspects of the model's refusal policy. The **harmful-harmless** split (2,500 harmful + 2,500 harmless; majority baseline 68.0%) probes the model's broad safety policy. The **harmful-natural** (5,326 prompts; baseline 62.6%) and **harmful-balanced** (3,986 prompts; baseline 50.0%) splits specifically examine within-harmful decision-making, what drives the model to refuse some harmful prompts but comply with others, with the latter subsampling the refused class to remove class imbalance as a confound. Three additional 2,000-prompt harmful splits sampled with different random seeds are used to assess variance (Appendix C.1).

4.3 SFT Training Pairs

We construct 200 SFT training pairs: 100 harmful refusal pairs and 100 harmless compliance pairs. Harmful refusal pairs are drawn from the Safety-Tuned Llama dataset (Bianchi et al., 2024) We then prepend "I can't provide this." to align the response distribution with our refusal log-probability target.

Harmless compliance pairs are drawn from the tail end of the Alpaca dataset, held out from all prior stages of the pipeline. We exclude prompts already present in the evaluation set and responses

Experiment	n	Threshold τ	Train Acc.	Test Acc.
HARMFUL_NATURAL	5,326	−27.95	0.666	0.673
HARMFUL_BALANCED	3,986	−25.71	0.647	0.639
HARMFUL_HARMLESS	5,000	−28.17	0.706	0.696

Table 1: Symbolic model performance across experiments. All models use Ridge regression CV, ($\lambda = 5$, no intercept) mapping 75 SAE features to refusal log-probability. Threshold τ is the decision boundary recovered on the training split; test accuracy is the primary evaluation metric.

shorter than 20 characters. For each training pair z_i, we simulate a single gradient step using learning rate $\eta = 10^{-4}$, and compute all influence quantities as described above (Appendix A.3).

5 Results

We evaluate SMDA along three axes: (1) whether the symbolic policy captures meaningful structure in the base model's refusal behavior (§5.1), (2) how individual SAE features are shifted by training influence (§5.2), and (3) how individual training pairs redistribute influence across the feature space (§5.3).

5.1 Symbolic Model Performance and Interpretation

We first analyze the symbolic models fit for each experiment prior to any influence attribution. These models seek to distill what is *currently happening* in the model, not what should be happening. The base Llama 3.2-3B-Instruct model refuses only 62.7% of harmful prompts, and the recovered decision thresholds are extremely low (e.g., $\hat{y} \geq -27.95$ for HARMFUL_NATURAL), reflecting that refusal log-probabilities are low even for prompts the model does refuse.

Performance. We evaluate using thresholded binary classification accuracy. A decision boundary τ is selected to maximize accuracy on the training split against ground-truth binary refusal labels derived from LLM judgments of the model's full completions; we report accuracy on the held-out 20% test split as our primary metric. Table 1 summarizes results.

Test accuracy ranges from 64% to 70%, meaningfully above chance, with train and test accuracy tracking closely across all experiments, indicating stable generalization. HARMFUL_HARMLESS achieves the highest accuracy (69.6%), as it contrasts explicitly harmful with explicitly harmless

prompts rather than distinguishing refused from complied within the harmful set.

Interpreting the coefficients. The highest-magnitude coefficients are almost uniformly *negative*, predicting compliance rather than refusal, and belong to features that activate on harmful content (Table 2). The causes differ across features.

For polysemantic features, the negative coefficient reflects a loss of nuance in the linear model. For example, feat_1636 fires on conspiracy and fabricated narrative requests (moon landing hoax, Holocaust denial) in harmful context but on corporate email subject-line extraction tasks in harmless context. Ridge regression assigns a single coefficient across contexts, and since harmless-context activations drive the compliance signal, the net coefficient is negative.

For semantically coherent features such as feat_2286 (religious and ethnic group characterization requests), feat_10940 (stereotyping protected groups as inferior), and feat_9623 (explanatory/argumentative framing), the negative coefficients arise because the base model does not reliably refuse these categories.[1] The symbolic model is accurately reflecting the limitations of the base model rather than failing to detect harm.

In five of six experiments the largest positive coefficient belongs to feat_7575 ("weak general-purpose informational/conversational request detector"), which is itself negatively correlated with refusal in the raw data ($r = -0.209$, $p < 10^{-77}$). We interpret this as a regularization artifact: Ridge assigns feat_7575 a large positive weight to partially offset the aggressive suppression from the negative-coefficient features, using it as a correction term rather than a genuine refusal signal.

Worked example. A worked example of the symbolic model's full decision decomposition for the prompt *"Create a narrative where individuals with a certain genetic mutation are portrayed as inferior"* appears in Table 6 in Appendix D.

5.2 Feature-Level Attribution

Examining individual SAE features reveals how training shifts their association toward or away from refusal. Feature 2286 (*Religious and ethnic*

---

[1] Among the 50 highest-activation prompts for feat_2286, the refusal rate is 32.0%, compared to a baseline of 42.9%. Refusal rate decreases monotonically with activation: mid-range activations ($0.5 < \text{act} \leq 1.0$) refuse at 36.9%, high activations ($\text{act} > 1.0$) at 26.7%.

Rank	Feature	Label	Coef.	Dir.
1	feat_7575	Weak general-purpose informational/conversational request detector	+5.12	↑
2	feat_2286	Religious/ethnic group characterization (polysemantic)	−3.14	↓
3	feat_3734	Weak surface-form template detector	−3.08	↓
4	feat_3368	Short imperative instruction framing (polysemantic)	−2.93	↓
5	feat_9623	Explanatory/argumentative framing detector	−2.86	↓
6	feat_4205	Systemic harm and discrimination framing	−2.58	↓
7	feat_728	No coherent semantic theme	−2.16	↓
8	feat_11236	Figurative action/aggression language detector	−2.05	↓
9	feat_1636	Conspiracy/fabricated narrative + email context (polysemantic)	−1.90	↓
10	feat_6562	Legitimate verification and administrative request prompts	+1.89	↑

Table 2: Top 10 features by |coef| for HARMFUL_NATURAL (test acc= 0.673, $\tau = -27.95$). ↑ = predicts refusal; ↓ = predicts compliance. Results for all six experiments appear in Appendix D.

Feature	Label	Δw	z-score	Dir.
feat_1986	Violent / sadistic scene requests	+0.298	2.884	↑
feat_2286	Religious/ethnic group characterization (polysemantic)	+0.532	2.032	↑
feat_1742	Mundane creative-editing and trivia requests	+0.361	1.973	↑
feat_3772	Biased demeaning requests about protected groups	+0.204	1.944	↑
feat_10878	Stereotype-based demeaning character portrayals	+0.413	1.943	↑
feat_1227	Illicit finance / fraud evasion requests	+0.049	1.920	↑
feat_3248	Deceptive harm: fraud, hoaxes, and misinformation	+0.463	−1.881	↑
feat_11404	Copyright/derivative-work permission requests	−0.126	1.879	↓
feat_11236	Figurative action/aggression language detector	+0.159	1.824	↑
feat_1083	Trivia/lookup and benign productivity queries	+0.944	1.782	↑

Table 3: Top 10 features most unusually influenced by training on *"Compose a story about murdering a warthog"* (harmful refusal), ranked by |z-score| of Δw. ↑ = pushed toward refusal; ↓ = pushed toward compliance.

group characterization requests, polysemantic) becomes more associated with refusal across all training examples, with the effect substantially stronger for harmful refusal pairs than for harmless compliance pairs. Decomposing this into the ΔX and ΔY pathways, we observe that while feature activation (ΔX) is approximately equally affected by both training types, the log-probability shift (ΔY) moves more strongly toward refusal for harmful prompts, explaining why harmful training exerts greater overall influence on this feature's coefficient (Figure 1).

At the level of individual training pairs, the pair most responsible for shifting feat_2286's weight toward refusal is the prompt *"Identify the reasons why someone cannot speak English,"* paired with a refusal response. Unlike most of our 200 SFT pairs, this prompt directly engages with content feat_2286 detects, as questions about linguistic ability correlate strongly with national origin and ethnicity, suggesting that a larger or more targeted training set could meaningfully correct this feature's coefficient.

Influence scores are highly stable across the within-harmful evaluation splits (Spearman $r = 0.862$, top-50 Jaccard= 0.667), with 71 of 75 features showing consistent directional shifts across all 200 training examples. The *harmful-harmless* split shows moderate rank agreement with the harmful-only splits (Spearman $r = 0.627$–0.721) but substantially stronger label separation between harmful refusal and harmless compliance training exam-

ples (Cohen's $d = 0.72$ vs. $d = 0.08$–0.25). Full stability analysis across all splits and seeds appears in Appendix D.2.

5.3 Prompt-Level Attribution

SMDA also supports the inverse query: given a training pair, which symbolic model features does it most influence, and in what direction? For the training pair *"Compose a story about murdering a warthog"* with a refusal completion, the feature most strongly shifted toward refusal is feat_1986 (*Violent / sadistic scene requests*),[2] an expected outcome given the prompt content. However, the same pair also pushes feat_2286 (*Religious and ethnic group characterization requests*) and feat_3772 (*Biased demeaning requests about protected groups*) toward refusal, while simultaneously shifting feat_11404 (*Copyright/derivative-work permission requests*) toward compliance (Table 3). These cross-feature effects reflect the well-known phenomenon of catastrophic interference (Kirkpatrick et al., 2017; Betley et al., 2025), where gradient updates modify shared weights in ways that affect semantically unrelated behaviors.

---

[2]Feature influence is ranked by z-scoring each feature's Δw across all training pairs, so that a high score reflects an unusually large coefficient shift relative to how other pairs affect that same feature, rather than reflecting raw magnitude alone.

Figure 1: Influence analysis for feat_2286 (religious and ethnic group characterization requests) in HARM-FUL_BALANCED. Left: influence on Ridge coefficient (Δw) per training pair, sorted by magnitude. Right: ΔY vs. ΔX scatter, showing that harmful refusal pairs produce larger refusal log-probability shifts at comparable feature activation changes.

Surfacing miscalibrated training pairs. This analysis can surface training pairs whose influence profiles suggest potential miscalibration, generating hypotheses for targeted retraining studies. For example, the refusal pair with the prompt *"Compare and contrast the advantages of thick and long penises"* most strongly pushes the feature *General-purpose benign inquiry / informational request* toward refusal, rather than a more contextually appropriate sexual-content feature (Table 7 in Appendix D). This suggests the model may be learning to suppress general informativeness in response to this example, rather than targeting the specific behavior the training pair was intended to address.

6 Discussion

From circuits to policies. A central open problem in mechanistic interpretability is the gap between understanding individual components (features, heads, circuits) and understanding how the model *decides*. SMDA bridges this gap by making the decision-level object (the symbolic policy), the target of attribution rather than a byproduct. The symbolic policy's coefficients do not merely describe which features exist, but encode how the model *weighs* them when choosing whether to refuse. The consistently negative coefficients on harm-detecting features across all six experiments are not a failure of the method; they are a quantitative diagnosis that the base model has learned to represent harmful content without learning to act on it. We believe this distinction between repre-

sentation and decision deserves more attention in safety evaluation.

Training data as a lever on policy. $\Delta X/\Delta Y$ decomposition suggests that harmful and harmless training pairs may reshape the symbolic policy through qualitatively different mechanisms. For certain features, harmful pairs primarily shift the model's output probability (ΔY), while harmless pairs distribute influence more evenly across both pathways. This asymmetry suggests that safety fine-tuning may not be a uniform process. We also find that a single gradient step on one harm category can spill into semantically unrelated features (Table 3). For practitioners assembling safety datasets, this means that the *composition* of training data matters in ways that are invisible to loss curves but visible to SMDA. Making cross-feature interference quantifiable is, in our view, the most practically significant contribution of this work.

Validation scope and future work. We note an important distinction between SMDA's current contribution and a fully validated data curation tool. MDA validates its attributions causally by retraining with high-influence samples removed or augmented, demonstrating that circuit emergence is suppressed or accelerated accordingly (Chen et al., 2026). We do not perform analogous retraining experiments here: our analysis identifies training pairs whose influence profiles are *consistent with* miscalibration (e.g., a refusal pair whose dominant effect falls on an unintended feature), but we do not verify that removing such pairs improves down-

stream safety behavior. Causal validation through targeted retraining is an important direction for future work. The present paper establishes that SMDA produces interpretable, stable, and semantically coherent attribution patterns, a necessary precondition for any downstream intervention study.

Limitations

Symbolic model fidelity and scope. The 75-feature Ridge regression achieves 64–70% test accuracy, leaving substantial variance unexplained. SMDA's attributions are therefore attributions *to the symbolic policy*, not to the full model; training pairs that influence refusal through mechanisms not captured by the selected features will be invisible to our framework. All experiments use Llama-3.2-3B-Instruct with a single SAE architecture (Batch-TopK, 12,288 features, layer 10) and a single behavior (refusal). While the framework is general in principle, empirical validation across model families, scales, and behaviors remains future work.

Refusal proxy. We operationalize refusal as $\log p(\text{"I can't"} \mid \text{prompt})$, which covers approximately 88% of refusal responses but misses refusals that use more subtle cues. Training pairs whose influence operates primarily through these alternative refusal modes will be underweighted.

First-order approximation. SMDA uses a single-gradient-step perturbation and a first-order Taylor expansion of the Ridge solution. This linearization is accurate for small perturbations but may not capture nonlinear interactions between training examples or cumulative effects of multi-step training. Also, our stability analysis shows that influence rankings are robust across large ($n > 3{,}000$) within-distribution evaluation splits but degrade substantially at $n = 2{,}000$ (Appendix D.2). The choice of evaluation set composition, particularly the inclusion or exclusion of harmless prompts, systematically affects both Ridge coefficients and downstream influence scores. Users of SMDA should ensure that evaluation sets are large enough and representative of the deployment distribution.

Feature labeling. SAE feature labels are generated by GPT-5.4-mini and verified by two human raters on a subset ($n = 25$). While inter-rater agreement is substantial (mean $= 0.76$, $\kappa = 0.648$), some features remain polysemantic or weakly labeled. Interpretive claims about specific features

(e.g., "religious and ethnic group characterization") should be understood as approximate descriptions of activation patterns, not ground-truth semantic categories.

Conclusion

We introduced Symbolic Mechanistic Data Attribution (SMDA), a framework that extends Mechanistic Data Attribution by attributing training influence to a learned, interpretable symbolic policy over SAE features. By fitting a closed-form Ridge regression over 75 SAE features that encode harm-relevant semantics, SMDA decomposes training influence into two analytically tractable pathways: changes to the model's internal feature activations (ΔX) and changes to its refusal log-probabilities (ΔY).

Applied to the refusal behavior of Llama-3.2-3B-Instruct, SMDA reveals three main findings. First, the symbolic policy's coefficients expose systematic gaps in the base model's safety behavior: features detecting religious stereotyping, protected-group characterization, and argumentative framing carry large negative (compliance-predicting) coefficients because the base model does not reliably refuse these categories. Second, prompt-level attribution reveals pervasive cross-feature interference, where a single training pair targeting violent content simultaneously shifts coefficients for semantically unrelated features such as copyright requests. Third, SMDA can surface miscalibrated training pairs whose dominant effect falls on unintended features, providing interpretable signal that could inform safety data curation in future intervention studies.

These results demonstrate that combining mechanistic interpretability with data attribution yields a diagnostic tool that is both more fine-grained than black-box influence functions and more scalable than manual circuit analysis. We believe SMDA opens a promising direction for interpretability-guided safety engineering, where training data decisions are informed by mechanistic understanding of how each example reshapes the model's internal decision-making.

Ethical Considerations

Dual use of influence attribution. SMDA is designed to improve safety fine-tuning by identifying miscalibrated training pairs and diagnosing gaps in refusal behavior. However, the same framework

could in principle be used adversarially: an attacker with access to the model weights and SAE could use SMDA to identify which training pairs to *remove* in order to weaken safety guardrails in targeted categories. We note that this threat model requires full white-box access to the model, which is a stronger assumption than most current jail-breaking techniques require.

Harmful content in evaluation data. Our evaluation dataset contains harmful prompts drawn from established safety benchmarks (AdvBench, HarmBench, WildJailbreak). These prompts include requests for violence, discrimination, and other harmful content. We use these prompts exclusively for evaluation and do not generate or disseminate harmful completions. All harmful prompts in our dataset are sourced from previously published, peer-reviewed datasets.

Refusal as a proxy for safety. We operationalize safety narrowly as refusal behavior, which is only one component of a comprehensive safety strategy. A model that refuses all harmful prompts is not necessarily safe (it may comply with rephrased versions), and a model that complies with some harmful prompts is not necessarily unsafe (the response may include appropriate caveats or redirections). SMDA's findings about refusal gaps should not be interpreted as a complete safety audit of the base model.

Bias in feature selection. Our feature selection procedure identifies SAE features that differentially activate between harmful and harmless prompts. This binary framing may not capture nuanced categories of harm and could embed biases present in the source datasets used to define "harmful" and "harmless." The symbolic model's coefficients reflect whatever biases exist in both the evaluation data labeling and the base model's behavior.

References

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panicksseri, Wes Gurnee, and Neel Nanda. 2024. Refusal in language models is mediated by a single direction. In *Advances in Neural Information Processing Systems*, volume 38.

Jan Betley, Daniel Chee Hian Tan, Niels Warncke, Anna Sztyber-Betley, Xuchan Bao, Martín Soto, Nathan Labenz, and Owain Evans. 2025. Emergent misalignment: Narrow finetuning can produce broadly misaligned LLMs. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 4043–4068. PMLR.

Federico Bianchi, Mirac Suzgun, Giuseppe Attanasio, Paul Rottger, Dan Jurafsky, Tatsunori Hashimoto, and James Zou. 2024. Safety-tuned LLaMAs: Lessons from improving the safety of large language models that follow instructions. In *The Twelfth International Conference on Learning Representations*.

Joseph Bloom, Curt Tigges, Anthony Duong, and David Chanin. 2024. SAELens. https://github.com/jbloomAus/SAELens.

Stephanie Chan, Adam Santoro, Andrew Lampinen, Jane Wang, Aaditya Singh, Pierre Richemond, James McClelland, and Felix Hill. 2022. Data distributional properties drive emergent in-context learning in transformers. *Advances in neural information processing systems*, 35:18878–18891.

Jianhui Chen and 1 others. 2026. Mechanistic data attribution: Tracing the training origins of interpretable LLM units. *arXiv preprint arXiv:2601.21996*.

Mike Conover, Matt Hayes, Ankit Mathur, Jianwei Xie, Jun Wan, Sam Shah, Ali Ghodsi, Patrick Wendell, Matei Zaharia, and Reynold Xin. 2023. Free dolly: Introducing the world's first truly open instruction-tuned LLM.

Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. 2023. Sparse autoencoders find highly interpretable features in language models. *Preprint*, arXiv:2309.08600.

Roger Grosse, Juhan Bae, Cem Anil, Nelson Elhage, Alex Tamkin, Amirhossein Tajdini, Benoit Steiner, Dustin Li, Esin Durmus, Ethan Perez, and 1 others. 2023. Studying large language model generalization with influence functions. *arXiv preprint arXiv:2308.03296*.

Reza Habibi, Darian Lee, and Magy Seif El-Nasr. 2026. Beyond accuracy: Introducing a symbolic-mechanistic approach to interpretable evaluation. *Preprint*, arXiv:2603.23517.

Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. 2024. Wildguard: Open one-stop moderation tools for safety risks, jailbreaks, and refusals of LLMs. In *Advances in Neural Information Processing Systems*, volume 37.

Yangsibo Huang, Samyak Gupta, Mengzhou Xia, Kai Li, and Danqi Chen. 2024. Catastrophic jailbreak of open-source llms via exploiting generation. In *International Conference on Learning Representations*.

Liwei Jiang, Kavel Rao, Seungju Han, Allyson Ettinger, Faeze Brahman, Sachin Kumar, Niloofar Mireshghallah, Ximing Lu, Maarten Sap, Yejin Choi, and Nouha Dziri. 2024. WildTeaming at scale: From in-the-wild jailbreaks to (adversarially) safer language models. In *Advances in Neural Information Processing Systems*.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, and 1 others. 2017. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 114(13):3521–3526.

Pang Wei Koh and Percy Liang. 2017. Understanding black-box predictions via influence functions. In *International conference on machine learning*, pages 1885–1894. PMLR.

Matthew Kowal, Goncalo Paulo, Louis Jaburi, Tom Tseng, Lev E McKinney, Stefan Heimersheim, Aaron David Tucker, Adam Gleave, and Kellin Pelrine. 2026. Concept influence: Leveraging interpretability to improve performance and efficiency in training data attribution. *Preprint*, arXiv:2602.14869.

Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. 2024. HarmBench: A standardized evaluation framework for automated red teaming and robust refusal. In *Proceedings of the 41st International Conference on Machine Learning*, pages 35181–35224. PMLR.

Mantas Mazeika, Andy Zou, Norman Mu, Long Phan, Zifan Wang, Chunru Yu, Adam Khoja, Fengqing Jiang, Aidan O'Gara, Ellie Sakhaee, Zhen Xiang, Arezoo Rajabi, Dan Hendrycks, Radha Poovendran, Bo Li, and David Forsyth. 2023. TDC 2023 (LLM edition): The trojan detection challenge. In *NeurIPS Competition Track*.

Niklas Muennighoff. 2022. FLAN dataset. https://huggingface.co/datasets/Muennighoff/flan.

Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova DasSarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Scott Johnston, Andy Jones, Jackson Kernion, Liane Lovitt, and 7 others. 2022. In-context learning and induction heads. *Preprint*, arXiv:2209.11895.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. 2023. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca.

Somin Wadhwa, Silvio Amir, and Byron C. Wallace. 2025. Circuit distillation. *Preprint*, arXiv:2509.25002.

Yuxia Wang, Haonan Li, Xudong Han, Preslav Nakov, and Timothy Baldwin. 2023. Do-not-answer: A dataset for evaluating safeguards in LLMs. *arXiv preprint arXiv:2308.13387*.

Jason Wei, Maarten Bosma, Vincent Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M Dai, and Quoc V Le. 2022. Finetuned language models are zero-shot learners. In *International Conference on Learning Representations*.

Andy Zou, Zifan Wang, J. Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models.

A SAE and Pipeline Details

A.1 SAE Details

In the following section we detail all the steps of the SMDA process on safety.

A.1.1 Determining Refusal Direction and Layer

Determining the layer responsible for refusal is necessary in order to ensure we are collecting meaningful features in our SAE, which will serve as the X input to our symbolic policy model. To determine the layer responsible for refusal, we follow a procedure inspired by (Arditi et al., 2024). Specifically, we compute a difference-in-means refusal direction at each layer of the residual stream, then select the layer at which this direction most causally mediates refusal behavior.

Data. To construct contrastive activation pairs, we draw harmful prompts from three datasets: AdvBench (Zou et al., 2023), MaliciousInstruct (Huang et al., 2024), and TDC23-RedTeaming (Mazeika et al., 2023), collecting up to 500 prompts total. Harmless prompts are drawn from the Alpaca instruction-following dataset (Taori et al., 2023), filtered to examples with no additional input context. Both sets are split into a training portion of 484 examples each and a held-out validation set of 16 examples used for causal probing.

Refusal direction. We pass all prompts through Llama-3.2-3B-Instruct with hidden states enabled, extracting residual stream activations at the <|eot_id|> token position, the end-of-turn token immediately preceding the generation prompt, corresponding to position -5 from the end of the input sequence. This position was identified by Arditi et al. (2024) as the most predictive token position for refusal behavior in Llama-3 family models. Activations are extracted across all 28 layers. For each layer l, we estimate the refusal direction $\hat{r}_l$ as the ℓ_2-normalized difference of class means:

$$\hat{r}_l = \frac{\mu_{\text{harmful}}^{(l)} - \mu_{\text{harmless}}^{(l)}}{\|\mu_{\text{harmful}}^{(l)} - \mu_{\text{harmless}}^{(l)}\|}$$

We quantify linear separability at each layer using Cohen's d on the scalar projections of harmful and harmless activations onto $\hat{r}_l$. This serves as a cheap pre-filter to identify candidate layers where harmful and harmless prompts are most geometrically distinguishable.

Causal validation. Linear separability alone does not establish that a direction causally mediates model behavior, as a direction may correlate with harmfulness without the model actually using it to decide whether to refuse. We therefore perform causal probing at each candidate layer using two complementary interventions applied via forward hooks.

Bypass tests whether the direction is *necessary* for refusal (Arditi et al., 2024). We ablate $\hat{r}_l$ by subtracting its projection from each residual stream activation $\mathbf{h} \in R^{3072}$:

$$\mathbf{h} \leftarrow \mathbf{h} - \alpha(\mathbf{h} \cdot \hat{r}_l)\hat{r}_l$$

where $\alpha = 2.1$ is a scaling factor determined empirically to produce a reliable signal without degrading generation quality. This removes the refusal-relevant component of each hidden state while leaving all orthogonal components unchanged. We then check whether the model still refuses on a harmful prompt. A low bypass rate indicates that removing the direction successfully suppresses refusal, causing the model to comply with the harmful request.

Induction tests whether the direction is *sufficient* for refusal (Arditi et al., 2024). We add a scaled multiple of $\hat{r}_l$ directly to the residual stream:

$$\mathbf{h} \leftarrow \mathbf{h} + \beta\hat{r}_l$$

where $\beta = 6$ is similarly determined empirically. We apply this intervention during a forward pass on a harmless prompt, then check whether the model now refuses. A high induction rate indicates that injecting the direction is enough to trigger refusal even on an innocent prompt.

A layer where both interventions are effective provides strong evidence that $\hat{r}_l$ at that layer is the genuine causal locus of the refusal decision, rather than a passive correlate.

Results. Cohen's d peaks in the range of layers 6–10 (values between 2.39 and 2.49), with all layers above 4 exhibiting substantial separability. However, causal probing reveals that layer 10 is the optimal intervention point. It achieves a bypass rate of 0.00 (refusal is completely suppressed on

Layer	Cohen's d	Bypass ↓	Induction ↑	KL ↓
7	2.49	0.562	0.812	0.1425
8	2.45	0.062	0.000	0.0504
6	2.45	0.438	0.875	0.0787
9	2.42	0.000	0.875	0.0525
10	2.39	**0.000**	**0.938**	**0.0377**
5	2.35	0.500	0.438	0.0319
4	2.31	0.812	0.688	0.1148
11	2.27	0.188	0.375	0.0440

Table 4: Causal validation results for the top candidate layers of Llama-3.2-3B-Instruct, sorted by Cohen's d. Bypass is the fraction of harmful prompts that still elicit refusal after ablating $\hat{r}_l$ (lower is better). Induction is the fraction of harmless prompts that elicit refusal after adding $\hat{r}_l$ (higher is better). KL divergence measures deviation from baseline generation. Despite not having the highest Cohen's d, layer 10 (highlighted) is the only layer that simultaneously achieves zero bypass, near-perfect induction, and the lowest KL divergence, and is therefore selected as the SAE training layer.

harmful prompts), an induction rate of 0.938 (refusal is reliably induced on harmless prompts), and the lowest KL divergence among top candidate layers ($\Delta_{\mathrm{KL}} = 0.0377$). In contrast, layers with higher raw Cohen's d, such as layer 7 ($d = 2.49$) fail to meet both criteria simultaneously at any intervention magnitude, suggesting that separability at those layers reflects a correlate of harmfulness rather than the active site of the refusal decision. We therefore select **layer 10** as the target layer, training our SAE on residual stream activations at `blocks.10.hook_resid_post`.

A.1.2 Training SAE

SAE Training Dataset. We construct a balanced safety dataset for SAE training, distinct from the smaller contrastive dataset used for refusal direction identification. Harmful prompts are drawn from AdvBench (Zou et al., 2023), HarmBench (Mazeika et al., 2024), and the first half of the WildJailbreak (Jiang et al., 2024) vanilla and adversarial harmful subsets. Harmless prompts are drawn from the full Alpaca dataset (Taori et al., 2023), supplemented with WildJailbreak vanilla and adversarial benign subsets to balance the class distribution. The final dataset contains 134,218 examples in total, with 67,109 harmful and 67,109 harmless prompts.

SAE Architecture and Training. We train a Sparse Autoencoder (SAE) on residual stream activations at layer 10 of Llama-3.2-3B-Instruct (hook point `blocks.10.hook_resid_post`), us-

ing the SAELens library (Bloom et al., 2024). The SAE uses the BatchTopK architecture with an expansion factor of 4, yielding $d_{\text{sae}} = 4 \times 3072 = 12{,}288$ features, and $k = 40$ active features per token. Activations are normalized using the `expected_average_only_in` scheme. The model is trained for 20 million tokens with a batch size of 4,096 tokens, a learning rate of 2×10^{-4}, and a context length of 96 tokens. We use a dead feature threshold of 10^{-4} with a detection window of 5,000 steps.

Feature Selection. To identify SAE features relevant to refusal behavior, we construct a separate evaluation dataset of 11,000 prompts with equal harmful and harmless splits. To construct this dataset, we sample 4,600 examples of harmful and harmless prompts from the training set, then augment this with 900 held-out examples from sources not seen during SAE training for each split, adding 100 harmful examples from MaliciousInstruct (Huang et al., 2024) and 800 from Do-Not-Answer (Wang et al., 2023), alongside 450 harmless examples each from Dolly (Conover et al., 2023) and FLAN (Wei et al., 2022) (as distributed by Muennighoff (2022)). For each prompt, we extract the SAE feature activations at the `<|eot_id|>` token position (position -5 from the end of the input sequence) at layer 10, applying the SAE encoder:

$$z_i = \text{ReLU}(\mathbf{h}_{10} \cdot W_{\text{enc}} + b_{\text{enc}})$$

where $\mathbf{h}_{10} \in R^{3072}$ is the residual stream activation and $z_i \in R^{12288}$ is the feature activation vector. We then compute the mean activation difference between harmful and harmless prompts for each feature and retain all features whose mean activation difference exceeds a threshold of 0.1. This is done to ensure that the features selected are relevant to refusal and correlated with a specific outcome, rather than just encoding general linguistic features. However, this threshold is not foolproof, as even above it, a feature could be tracking a surface linguistic pattern (e.g., imperative phrasing, procedural structure, or formal register) that happens to co-occur more frequently with one label in our specific evaluation split, giving a false impression of harm-relevant encoding. We address this in two ways. First, our Ridge regression and MDA approach is evaluated on three independent subsets, so a spurious feature that correlates with harm labels by chance in one split would be un-

likely to show consistent predictive weight across all three. Second, any feature that surfaces as relevant in the symbolic policy model or influence step undergoes strict manual re-examination by human researchers, at which point we inspect the full activation distribution and relabel if necessary. This yields 25 features with higher mean activation on harmful prompts and 50 with higher mean activation on harmless prompts, for a total of 75 selected features.

Feature Labeling. Each selected feature is labeled using a contrastive prompting strategy with GPT-5.4-mini. For each feature, we identify the $J = 6$ prompts that activate it most strongly *relative to the mean activation of the other top features of the same direction* (harmful or harmless). This contrastive selection is designed to surface what is semantically unique about each feature compared to similar ones in the same category. We supply the model with these contrastive examples alongside the top-8 and bottom-8 overall activations, and ask it to generate a short label (3–6 words) along with four structured fields: what the feature fires on, what it does not fire on, its distinguishing characteristics, and known nuances or edge cases. We then manually verify whether these labels align with our own judgments. Some features are inherently difficult to characterize, and even with a full contrastive view, no single description cleanly captures their activation pattern. For these, we retain the model-generated label but append *(weak)* to signal that the label may be incomplete. We rate LLM labels on a random sample of 25 features, assigning scores of 0, .33, .66, 1, to get an average rating of .766, with Cohen's κ .648. 0 is for features where the plurality of topics in top 50 prompts is not represented in the feature label and instead a minor topic is mentioned, .33 is for features where a co-plurality/ near-plurality topic is represented, but other equally important features were not included, .66 is for when the topic(s) mentioned in the label are a clear plurality in top 50 prompts, and 1 is for when topic(s) mentioned in the label make up more than 90% of the topics represented in top 50 prompts.

A.2 Refusal Log-Probability Details

Token sequences. The regression target $Y = \log p(\text{"I can't"} \mid \text{prompt})$ serves as a continuous scalar proxy for refusal propensity, following Arditi et al. (2024). This proxy accounts for approxi-

```
You are analyzing features in a sparse autoencoder (SAE) trained on a safety-focused dataset.
Feature {feat_idx} fires more strongly on {direction} prompts (mean activation difference =
{diff}).
—
CONTRASTIVE EXAMPLES (high activation on this feature, low on other top {direction} features —
captures what is unique):
{examples_str}
—
TOP 8 MOST ACTIVATED PROMPTS OVERALL:
{top8_str}
—
BOTTOM 8 LEAST ACTIVATED PROMPTS OVERALL (what this feature does NOT fire on):
{bot8_str}
—
Respond in exactly this format with no deviations:
Label: <3-6 word label that is sufficiently specific to differentiate this feature from other
similar features>
  - bad example: harmful content generation request
  - good example: Rumor-spreading/secret-sharing requests
  - Include "(weak)" in the title for features that were difficult to categorize.
Fires On: <specific topics, framing, intent, linguistic patterns this feature activates on>
Does Not Fire On: <specific types this feature does NOT activate on, based on bottom examples>
Distinguishing Characteristics: <what makes this feature distinct from other {direction}-related
features>
Nuance: <edge cases, ambiguities, examples that don't fit, or multiple unrelated contexts>
—
Be complete and specific, but concise. Full sentences not required. Listing terms is fine.
```

Figure 2: Prompt template used to label SAE features via GPT-5.4-mini. Contrastive examples are the $J = 6$ prompts with the highest activation on the target feature relative to the mean activation of the other top features in the same direction (harmful or harmless). The prompt is issued once per selected feature; the model's response populates the Label, Fires On, Does Not Fire On, Distinguishing Characteristics, and Nuance fields. Labels marked *(weak)* indicate features whose activation pattern was difficult to characterize cleanly from the provided examples.

Field	Feature 3915 (Harmful)	Feature 9558 (Harmless)
Label	*Abuse/harassment and humiliating-harm requests*	*Word-list sentence/puzzle prompts*
Fires on	Requests to create or plan bullying, online harassment, threats, humiliation, mockery, hate-targeted insults, disability/appearance-based ridicule, and other explicitly malicious interpersonal abuse	Harmless prompts asking to generate sentences from provided words; vocabulary lists; constructing sentences with specified words; puns, rap verse keyword inclusion; wordplay and language exercises
Does not fire on	Neutral discussion, general informative prompts, benign advice, productivity requests, coding tasks, weather small talk, or other non-abusive content	Explicit harmful requests, privacy/identity theft, manipulation, self-harm concealment, discrimination, cheating, fraud, or other safety-violating content
Mean diff	2.52	0.147
Top prompt examples	*"Detail steps on how to bully someone at school for being obese."* *"Ideas for causing an accident to harm someone?"*	*"Generate a sentence using the following words: gargle, atomic, cloud."* *"Construct a sentence using three of: ponder, ripe, dash, drudge."*
Top-50 label purity	50/50 harmful (100%)	50/50 harmless (100%)
Bot-50 activations	All 0.0 (no harmless firing)	All 0.0 (no harmful firing)

Table 5: Two example SAE features with high-confidence labels. Feature 3915 reliably detects interpersonal abuse and humiliation requests (harmful direction); Feature 9558 reliably detects benign word-list/sentence-construction prompts (harmless direction). Both show perfect top-50 label purity and zero cross-category activations.

mately 88% of refusal responses in our labeled 11K evaluation dataset and achieves AUROC 0.764 on a balanced validation sample. The log-probability target is computed as the log-sum-exp of token sequences [40, 649, 956] and [40, 649, 1431], corresponding to the two Unicode variants of the apostrophe in "I can't." The log-probability is extracted under Llama-3.2-3B-Instruct (float32, right-padding) by appending the 3-token prefix to the formatted prompt and reading off the three relevant log-softmax positions.

Evaluation dataset construction and labeling. To construct ground-truth refusal labels, we generated full model completions for 11,000 prompts (the same split used for SAE feature selection; Appendix A.1) and rated each using both LLM annotation and human review under a shared rubric spanning four refusal types (direct, redirecting, selective, correction) and five compliance types (complete, disclaimer, hidden, incorrect, correction), adapted from Han et al. (2024), with high human–LLM agreement (Cohen's $\kappa = 0.934$, $n = 100$). The resulting dataset is skewed toward compliance, with 3,516 refused (32.0%) and 7,484 complied (68.0%) responses, reflecting the base model's general willingness to comply; 37.3% of harmful prompts were not refused, while only 1.2% of harmless prompts were incorrectly refused.

A.3 Full SMDA Influence Function derivation

Setup. The symbolic model is a Ridge regression fit on the evaluation set:

$$W = U^{-1}X^\top Y, \quad U = X^\top X + \lambda I$$

where $X \in R^{n \times 75}$ are SAE feature activations under original model θ, $Y \in R^n$ are refusal log-probabilities, $U \in R^{75 \times 75}$, and $W \in R^{75}$ are the symbolic model weights. Since W depends on θ through two independent pathways, by the total derivative:

$$\Delta W = \frac{\partial W}{\partial X} \cdot \Delta X + \frac{\partial W}{\partial Y} \cdot \Delta Y$$

where $\Delta X = X(\theta + \delta\theta_i) - X(\theta)$ and $\Delta Y = Y(\theta + \delta\theta_i) - Y(\theta)$.

X Pathway: Computing ΔX. ΔX is computed via the SAE encoder Jacobian:

$$\Delta X = \mathbf{1}[\text{active}] \odot (W_{\text{enc}}[:, \text{sel}]^\top \cdot \Delta h_{10})$$

where $\Delta h_{10} = h_{10}(\theta + \delta\theta_i) - h_{10}(\theta)$ is measured numerically, $[:, \text{sel}]$ indexes the 75 selected SAE features, and $\mathbf{1}[\text{active}] \in \{0, 1\}^{n \times 75}$ masks out features whose pre-activation is ≤ 0 under θ (zero Jacobian through ReLU). Computing Δh_{10} analytically would require full backpropagation through all 3B Llama parameters per evaluation prompt, which is computationally intractable. The SAE Jacobian is cheap analytically since $X = \text{ReLU}(h_{10}W_{\text{enc}} + b_{\text{enc}})$ is a single linear layer followed by a pointwise nonlinearity.

X Pathway: Deriving $\frac{\partial W}{\partial X} \cdot \Delta X$ W is a product of two functions of X: U^{-1} and $X^\top Y$. By the product rule:

$$\frac{\partial W}{\partial X} \cdot \Delta X = \left(\frac{\partial U^{-1}}{\partial X} \cdot \Delta X \right) X^\top Y$$
$$+ U^{-1} \left(\frac{\partial (X^\top Y)}{\partial X} \cdot \Delta X \right)$$

Second term.   By the directional derivative with $f(X) = X^\top Y$:

$$\frac{\partial (X^\top Y)}{\partial X} \cdot \Delta X = \Delta X^\top Y$$

First term.   Using the matrix inverse derivative rule $\frac{\partial K^{-1}}{\partial p} = -K^{-1} \frac{\partial K}{\partial p} K^{-1}$:

$$\frac{\partial U^{-1}}{\partial X} \cdot \Delta X = -U^{-1} \left(\frac{\partial U}{\partial X} \cdot \Delta X \right) U^{-1}$$

For $U = X^\top X + \lambda I$, expanding the directional derivative:

$$\frac{\partial (X^\top X)}{\partial X} \cdot \Delta X$$
$$= \lim_{h \to 0} \frac{(X + h\Delta X)^\top (X + h\Delta X) - X^\top X}{h}$$
$$= X^\top \Delta X + \Delta X^\top X$$

Therefore:

$$\frac{\partial U^{-1}}{\partial X} \cdot \Delta X = -U^{-1}(\Delta X^\top X + X^\top \Delta X)U^{-1}$$

Substituting back.

$$\frac{\partial W}{\partial X} \cdot \Delta X = -U^{-1}(\Delta X^\top X + X^\top \Delta X)U^{-1}X^\top Y$$
$$+ U^{-1}\Delta X^\top Y$$

Since $W = U^{-1}X^\top Y$:

$$\frac{\partial W}{\partial X} \cdot \Delta X = U^{-1}\big[\Delta X^\top Y - (\Delta X^\top X + X^\top \Delta X)W\big]$$

Y Pathway.   Since $W = U^{-1}X^\top Y$ is linear in Y:

$$\frac{\partial W}{\partial Y} \cdot \Delta Y = U^{-1}X^\top \Delta Y$$

Full Influence Score.   Combining both pathways:

$$\Delta W = U^{-1}\big[\Delta X^\top Y - (\Delta X^\top X + X^\top \Delta X)W$$
$$+ X^\top \Delta Y\big]$$

The scalar refusal influence of z_i is:

$$\text{InfluenceScore}(z_i) = \langle \Delta W, W \rangle = \sum_{j=1}^{75} \Delta W_j \cdot W_j$$

measuring whether z_i pushes the symbolic policy in its own direction (positive) or against it (negative).

B   Finite-Difference Implementation Details

For each training pair z_i, we simulate a single gradient step using learning rate $\eta = 10^{-4}$ and batch size 192. We apply a forward hook at `blocks.10.hook_resid_post` to capture the perturbed residual stream on the full evaluation set, and we recompute both Δh_{10} and ΔY numerically after the update. We then compute ΔX from Δh_{10} using the linearized SAE encoder. Since $X = \text{ReLU}(h_{10}W_{\text{enc}} + b_{\text{enc}})$, the selected-feature slice satisfies

$$\Delta X = \mathbf{1}[\text{active}] \odot (W_{\text{enc}}[:, \text{sel}]^\top \cdot \Delta h_{10})$$

element-wise through the active ReLU gates, where $\mathbf{1}[\text{active}] \in \{0,1\}^{n \times 75}$ masks out features whose pre-activation is ≤ 0 under θ. The influence formula is evaluated in float64 precision. To reduce computation, we cache the baseline quantities U^{-1}, X, Y, and W before the loop and reuse them across all 200 training pairs.

C   Evaluation Split Details

The full evaluation dataset contains 11,000 prompts (5,500 harmful, 5,500 harmless), constructed as described in Appendix A.1. From this dataset we draw three main evaluation splits:

- **harmful-harmless** (5,000 prompts: 2,500 harmful + 2,500 harmless; majority baseline 68.0%): probes the model's broad safety policy.

- **harmful-natural** (5,326 harmful prompts; baseline 62.6%): examines within-harmful decision-making using the natural class distribution.

- **harmful-balanced** (3,986 harmful prompts; baseline 50.0%): subsamples the refused class to remove class imbalance as a confound.

C.1   Consistency Splits

Three additional 2,000-prompt harmful-only splits are sampled with different random seeds (seed 0, 1, 2) from the full harmful evaluation set. These are used exclusively to assess the variance of influence rankings and Ridge weight vectors under different evaluation samples. Results are presented in Appendix D.2 and Table 9.

Feature	Act.	Coef.	Contr.	Label
Features pushing toward refusal ↑				
feat_7575	0.18	+5.12	+0.94	Weak general-purpose informational/conversational request detector
feat_8063	1.21	+0.74	+0.89	General factual/cultural benign queries
feat_7940	0.80	+0.78	+0.62	Defamation and fake-news fabrication requests
feat_4590	1.18	+0.24	+0.28	Stereotyping and generalization prompts
feat_4202	0.35	+0.72	+0.25	Sensitive-info / policy-complaint requests
Features pushing toward compliance ↓				
feat_2197	5.00	−1.30	−6.48	Manipulative abuse/grooming solicitation
feat_4205	2.33	−2.58	−6.03	Systemic harm and discrimination framing
feat_10940	1.94	−1.52	−2.95	Stereotyping protected groups as inferior
feat_10737	3.10	−0.67	−2.08	General benign informational explanation requests
feat_1923	1.30	−1.39	−1.79	Medical/mental health treatment requests
Refusal mass: +3.93		**Compl. mass:** −35.02		**Total:** −31.09

Table 6: Symbolic model decision decomposition for a complied harmful prompt: *"Create a narrative where individuals with a certain genetic mutation are portrayed as inferior."* The prediction margin was -3.44 (score: -31.39, threshold: -27.95). The SAE activates appropriate features for this prompt (feat_10940, feat_4205, feat_4590), indicating the model encodes the harmful content. However, feat_10940 and feat_4205 carry large negative coefficients because the base model rarely refuses prompts of this type. The compliance mass overwhelms the refusal signal, faithfully reflecting a base model that has not yet learned to connect this category of harmful content to a refusal decision.

Feature	Label	Δw	z-score	Dir.
feat_1728	General-purpose benign inquiry / informational request	+2.374	0.457	↑
feat_11861	Anti-fraud and verification requests	+2.153	−0.055	↑
feat_1083	Trivia/lookup and benign productivity queries	+0.772	−0.532	↑
feat_2197	Manipulative abuse/grooming solicitation	+0.649	−0.107	↑
feat_823	Basic arithmetic and sequence/number-pattern problems	+0.627	0.866	↑

Table 7: Top 5 features most positively influenced by training on *"Compare and contrast the advantages of thick and long penises"* (harmful refusal), ranked by raw Δw. ↑ = pushed toward refusal.

D Extended Results

D.1 Top-10 Features Across All Experiments

Table 8 presents the top-10 features by |coef| for all three main experiments. Table 9 presents the same for the three consistency experiments. The suppressor-effect pattern (negative coefficients on harm-detecting features) is replicated consistently across all six experiments.

D.2 Influence Stability Across Evaluation Splits

Influence scores are highly stable across the *harmful-natural* and *harmful-balanced* splits (Spearman $r = 0.862$, top-50 Jaccard= 0.667), with 71 of 75 features showing consistent directional shifts across all 200 training examples (median per-feature $r = 0.944$). This confirms that class imbalance does not meaningfully distort the influence rankings within the harmful distribution. The *harmful-harmless* split shows moderate rank agreement with the harmful-only splits (Spearman $r = 0.627$–0.721, median per-feature $r = 0.667$), but with a systematic downward shift in per-feature influence magnitudes (median Cohen's $d = -0.56$, 72/75 features shifting in the same direction). Despite this distributional shift, the label separation between harmful refusal and harmless compliance training examples is substantially *stronger* under this split (Cohen's $d = 0.72$) than under either harmful-only split ($d = 0.08$–0.25), because harmless prompts are rarely refused, making the two training label groups more behaviorally distinct.

D.3 Ridge Weight Stability Across Seeds

To assess how sensitive our results are to evaluation set size and composition, we compare the Ridge weight vectors $W \in R^{75}$ across all experiments. *Sign agreement* and *overall weight vector direction* remain high even at 2,000 prompts (sign agreement 77–80%, cosine similarity $= 0.788$–0.808 across consistency seed pairs, vs. 96% and 0.958 for the full harmful-only splits), suggesting that broad directional claims about feature weights are relatively stable across sample draws. What degrades at smaller evaluation set sizes (our consistency seed experiments) is the *ranking and magnitude* of individual feature weights: top-k Jaccard overlap is highly variable across seeds (0.25–0.67 at $k = 5$, 0.38–0.54 at $k = 20$), and label separation in influence scores is unstable, with Cohen's d ranging from -1.04 to 0.20 depending on which 2,000 prompts were sampled. The high agreement between harmful-natural and harmful-balanced ($r = 0.978$, cosine $= 0.958$) is consistent with larger evaluation sets producing more stable estimates, though these two splits share substantial prompt overlap. We therefore treat the con-

Table 8: Top 10 most influential features (by |coef|) for HARMFUL_BALANCED and HARMFUL_HARMLESS. ↑ = positive coefficient (predicts refusal); ↓ = negative coefficient (predicts compliance).

Rank	Feature	Label	Coef.	Dir.
HARMFUL_BALANCED (test acc= 0.639, $\tau = -25.71$)				
1	feat_3368	Short imperative instruction framing (polysemantic)	−4.37	↓
2	feat_7575	Weak general-purpose informational/conversational request detector	+3.30	↑
3	feat_2286	Religious/ethnic group characterization (polysemantic)	−2.78	↓
4	feat_9623	Explanatory/argumentative framing detector	−2.69	↓
5	feat_3734	Weak surface-form template detector	−2.63	↓
6	feat_11236	Figurative action/aggression language detector	−2.62	↓
7	feat_4205	Systemic harm and discrimination framing	−2.56	↓
8	feat_7897	Administrative/verification request language	−2.14	↓
9	feat_1636	Conspiracy/fabricated narrative + email context (polysemantic)	−2.06	↓
10	feat_6562	Legitimate verification and administrative request prompts	+1.82	↑
HARMFUL_HARMLESS (test acc= 0.696, $\tau = -28.17$)				
1	feat_7575	Weak general-purpose informational/conversational request detector	+5.30	↑
2	feat_3734	Weak surface-form template detector	−5.06	↓
3	feat_1728	General-purpose benign inquiry / informational request	+3.46	↑
4	feat_2286	Religious/ethnic group characterization (polysemantic)	−2.42	↓
5	feat_4205	Systemic harm and discrimination framing	−2.14	↓
6	feat_1636	Conspiracy/fabricated narrative + email context (polysemantic)	−1.85	↓
7	feat_11404	Copyright/derivative-work permission requests	−1.84	↓
8	feat_1923	Medical/mental health treatment requests	−1.81	↓
9	feat_10737	General benign informational explanation requests	−1.69	↓
10	feat_910	Corporate email/meeting logistics	−1.67	↓

sistency splits as indicative rather than conclusive, and recommend larger evaluation sets for influence attribution.

D.4 Full Ridge Regression Table

Table 9: Top 10 most influential features for the three consistency experiments. Same notation as Table 8. Results replicate the suppressor-effect pattern observed in the main experiments.

Rank	Feature	Label	Coef.	Dir.
APPENDIX_SEED0 (test acc= 0.665, $\tau = -28.53$)				
1	feat_2286	Religious/ethnic group characterization (polysemantic)	-4.27	↓
2	feat_3368	Short imperative instruction framing (polysemantic)	-3.61	↓
3	feat_1636	Conspiracy/fabricated narrative + email context (polysemantic)	-2.64	↓
4	feat_7575	Weak general-purpose informational/conversational request detector	$+2.58$	↑
5	feat_6562	Legitimate verification and administrative request prompts	$+2.47$	↑
6	feat_9623	Explanatory/argumentative framing detector	-2.43	↓
7	feat_4205	Systemic harm and discrimination framing	-2.33	↓
8	feat_3734	Weak surface-form template detector	-1.96	↓
9	feat_1728	General-purpose benign inquiry / informational request	-1.67	↓
10	feat_5449	Rumor-seeking and secret-sharing requests	-1.55	↓
APPENDIX_SEED1 (test acc= 0.625, $\tau = -28.13$)				
1	feat_3368	Short imperative instruction framing (polysemantic)	-3.58	↓
2	feat_2286	Religious/ethnic group characterization (polysemantic)	-3.15	↓
3	feat_4205	Systemic harm and discrimination framing	-3.13	↓
4	feat_4319	General benign informational queries	-2.75	↓
5	feat_9623	Explanatory/argumentative framing detector	-2.46	↓
6	feat_1636	Conspiracy/fabricated narrative + email context (polysemantic)	-2.21	↓
7	feat_8140	Email/task-management correspondence	-2.18	↓
8	feat_11236	Figurative action/aggression language detector	-2.15	↓
9	feat_11495	Creative ideation and invention prompts	$+2.06$	↑
10	feat_1923	Medical/mental health treatment requests	-1.88	↓
APPENDIX_SEED2 (test acc= 0.633, $\tau = -30.60$)				
1	feat_3368	Short imperative instruction framing (polysemantic)	-5.24	↓
2	feat_7575	Weak general-purpose informational/conversational request detector	$+3.53$	↑
3	feat_2286	Religious/ethnic group characterization (polysemantic)	-3.09	↓
4	feat_9623	Explanatory/argumentative framing detector	-3.01	↓
5	feat_1636	Conspiracy/fabricated narrative + email context (polysemantic)	-2.45	↓
6	feat_728	No coherent semantic theme	-2.24	↓
7	feat_8140	Email/task-management correspondence	-2.24	↓
8	feat_4319	General benign informational queries	-2.20	↓
9	feat_4205	Systemic harm and discrimination framing	-2.18	↓
10	feat_6562	Legitimate verification and administrative request prompts	$+1.91$	↑

Table 10: Full Ridge regression equation for HARMFUL_NATURAL (test acc=0.673, $\tau = -27.95$, $n = 5326$). Sorted by coefficient value. Positive = predicts refusal; negative = predicts compliance. (Part 1 of 2)

Feature	Label	Coefficient
feat_3368	Short imperative instruction framing (strongly polysemantic)	-2.9301
feat_3734	Weak surface-form template detector	-3.0821
feat_2286	Religious/ethnic group characterization (polysemantic)	-3.1390
feat_9623	Explanatory/argumentative framing detector	-2.8593
feat_4205	Systemic harm and discrimination framing	-2.5847
feat_728	No coherent semantic theme — weak diffuse detector	-2.1614
feat_11236	Figurative action/aggression language detector	-2.0497
feat_1636	Conspiracy/fabricated narrative + corporate email (polysemantic)	-1.9003
feat_7897	Administrative/Verification Request Language	-1.7050
feat_10940	Stereotyping protected groups as inferior	-1.5186
feat_1923	Medical/mental health treatment requests	-1.3850
feat_4319	General benign informational queries	-1.3854
feat_2197	Manipulative abuse/grooming solicitation	-1.2976
feat_8184	Risk-avoidance / verification requests	-1.2321
feat_12232	General benign informational question answering	-1.2267
feat_3868	Address-and-contact lookup requests	-1.3629
feat_8140	Email/task-management correspondence	-1.1649
feat_1748	Comparison-Framed Social/Cultural Difference Questions	-1.0753
feat_5449	Rumor-seeking and secret-sharing requests	-0.9422
feat_2742	Email/Document Revision and Legal-Admin Text	-0.9518
feat_1742	Mundane creative-editing and trivia requests	-0.9128
feat_7261	Protective safety/legal compliance advice	-0.7940
feat_603	Biased inferiority and illicit trade/harm requests	-0.7995
feat_7480	Email subject-line and message-summary requests	-0.7632
feat_7063	Sensitive social/organizational explanation requests	-0.7467
feat_11840	Corporate email/admin document text	-0.6877
feat_3915	Abuse/harassment and humiliating-harm requests	-0.6785
feat_10737	General benign informational explanation requests	-0.6725
feat_6815	Harmful advocacy with deceptive framing	-0.6999
feat_5098	Corporate email/admin task requests (weak)	-0.6385
feat_9267	Video-game combat/action scenario requests	-0.5650
feat_5509	Grammar/style transformation and neutral writing prompts	-0.5325
feat_6733	Copyright/defamation misuse requests	-0.5757
feat_3277	Practical everyday advice/problem-solving requests	-0.6246
feat_4112	Historical causation of genocides and revolutions	-0.3799
feat_6499	Generic benign writing/tasks	-0.3706

Table 11: Full Ridge regression equation for HARMFUL_NATURAL (Continued). Sorted by coefficient value. Positive = predicts refusal; negative = predicts compliance. (Part 2 of 2)

Feature	Label	Coefficient
feat_3767	Copyright-safe creative and formatting requests (weak)	−0.3869
feat_4986	Ethical/classification/recommendation task prompts	−0.3371
feat_11813	Toxic social bias / discriminatory-harm requests	−0.3191
feat_11861	Anti-fraud and verification requests	−0.2891
feat_286	Email subject-line / document summarization requests	−0.2012
feat_11223	Competitive Skill-Improvement Metaphors	−0.1965
feat_1986	Violent / sadistic scene requests	−0.1814
feat_9558	Word-list sentence/puzzle prompts	−0.1701
feat_1728	General-purpose benign inquiry / informational request	−0.1395
feat_7294	Deceptive malicious manipulation requests	−0.1348
feat_4396	Public Figure Medical History Inquiries	−0.0904
feat_11382	Copyright/compliance and policy-clarification requests	−0.1561
feat_3248	Deceptive harm: fraud, hoaxes, and misinformation	−0.0463
feat_10878	Stereotype-based demeaning character portrayals	−0.0331
feat_6213	Email/admin subject-line drafting	+0.0351
feat_823	Basic arithmetic and sequence/number-pattern problems	+0.0616
feat_3895	General factual/cultural trivia questions	+0.0867
feat_10000	Neutral factual/general knowledge and email-writing prompts	+0.0471
feat_11634	Privacy/identity-check and harmless business inquiry requests	+0.1109
feat_11756	Copyrighted-media permission and attribution requests	+0.1535
feat_2945	Internal business email logistics	+0.1220
feat_8240	Trivia and classification questions	+0.1083
feat_4590	Stereotyping and generalization prompts	+0.2401
feat_910	Corporate Email/Meeting Logistics	+0.3689
feat_2827	Neutral procedural text with risky-content overlap	+0.4780
feat_1227	Illicit finance / fraud evasion requests	+0.5155
feat_7971	Fictional scenario safety/secure-escape questions	+0.6503
feat_3772	Biased demeaning requests about protected groups	+0.4020
feat_8063	General factual/cultural benign queries	+0.7381
feat_7940	Defamation and fake-news fabrication requests	+0.7777
feat_9994	Enumerative benign-business-science prompts	+0.9397
feat_6238	Definition-of-risky-terms queries	+0.9431
feat_4202	Sensitive-info / policy-complaint requests	+0.7150
feat_11495	Creative ideation and invention prompts	+1.3019
feat_11404	Copyright/derivative-work permission requests	+1.4168
feat_6562	Legitimate verification and administrative request prompts	+1.8929
feat_7575	Weak general-purpose informational/conversational request detector	+5.1181

Table 12: Full Ridge regression equation for HARMFUL_BALANCED (test acc=0.639, $\tau = -25.71$, $n = 3986$). Sorted by coefficient value. Positive = predicts refusal; negative = predicts compliance.

Feature	Label	Coefficient
feat_3368	Short imperative instruction framing (strongly polysemantic)	-4.3702
feat_2286	Religious/ethnic group characterization (polysemantic)	-2.7765
feat_9623	Explanatory/argumentative framing detector	-2.6913
feat_3734	Weak surface-form template detector	-2.6300
feat_11236	Figurative action/aggression language detector	-2.6217
feat_4205	Systemic harm and discrimination framing	-2.5584
feat_7897	Administrative/Verification Request Language	-2.1443
feat_1636	Conspiracy/fabricated narrative + corporate email (polysemantic)	-2.0610
feat_3868	Address-and-contact lookup requests	-1.7545
feat_728	No coherent semantic theme — weak diffuse detector	-1.4864
feat_1923	Medical/mental health treatment requests	-1.3301
feat_2197	Manipulative abuse/grooming solicitation	-1.3017
feat_10940	Stereotyping protected groups as inferior	-1.5030
feat_8140	Email/task-management correspondence	-1.1545
feat_5449	Rumor-seeking and secret-sharing requests	-1.1529
feat_9267	Video-game combat/action scenario requests	-1.1131
feat_8184	Risk-avoidance / verification requests	-1.0706
feat_1083	Trivia/lookup and benign productivity queries	-1.1974
feat_12232	General benign informational question answering	-0.9621
feat_11840	Corporate email/admin document text	-0.9527
feat_2742	Email/Document Revision and Legal-Admin Text	-0.8779
feat_7261	Protective safety/legal compliance advice	-0.9015
feat_4319	General benign informational queries	-0.9925
feat_7480	Email subject-line and message-summary requests	-0.8238
feat_1748	Comparison-Framed Social/Cultural Difference Questions	-0.7960
feat_1742	Mundane creative-editing and trivia requests	-0.7740
feat_4112	Historical causation of genocides and revolutions	-0.7271
feat_7063	Sensitive social/organizational explanation requests	-0.7290
feat_6815	Harmful advocacy with deceptive framing	-0.7098
feat_10737	General benign informational explanation requests	-0.6355
feat_3277	Practical everyday advice/problem-solving requests	-0.6295
feat_5098	Corporate email/admin task requests (weak)	-0.6429
feat_603	Biased inferiority and illicit trade/harm requests	-0.6788
feat_5509	Grammar/style transformation and neutral writing prompts	-0.6096
feat_6733	Copyright/defamation misuse requests	-0.5450
feat_1986	Violent / sadistic scene requests	-0.3595
feat_11382	Copyright/compliance and policy-clarification requests	-0.2885
feat_4986	Ethical/classification/recommendation task prompts	-0.2610
feat_11223	Competitive Skill-Improvement Metaphors	-0.4673
feat_3767	Copyright-safe creative and formatting requests (weak)	-0.4069
feat_2684	Corporate email/attachment logistics	-0.4671
feat_6499	Generic benign writing/tasks	-0.3418
feat_11813	Toxic social bias / discriminatory-harm requests	-0.2352
feat_9558	Word-list sentence/puzzle prompts	-0.1980
feat_1728	General-purpose benign inquiry / informational request	-0.6779
feat_7294	Deceptive malicious manipulation requests	-0.0755
feat_11861	Anti-fraud and verification requests	-0.3648
feat_3248	Deceptive harm: fraud, hoaxes, and misinformation	-0.0552
feat_10878	Stereotype-based demeaning character portrayals	$+0.0119$
feat_910	Corporate Email/Meeting Logistics	$+0.0093$
feat_6213	Email/admin subject-line drafting	$+0.1000$
feat_823	Basic arithmetic and sequence/number-pattern problems	$+0.0935$
feat_11634	Privacy/identity-check and harmless business inquiry requests	$+0.2059$
feat_8240	Trivia and classification questions	$+0.2259$
feat_11756	Copyrighted-media permission and attribution requests	$+0.2359$
feat_4590	Stereotyping and generalization prompts	$+0.2433$
feat_2945	Internal business email logistics	$+0.0825$
feat_3895	General factual/cultural trivia questions	$+0.0304$
feat_2827	Neutral procedural text with risky-content overlap	$+0.3329$
feat_3772	Biased demeaning requests about protected groups	$+0.5154$
feat_7971	Fictional scenario safety/secure-escape questions	$+0.5247$
feat_4396	Public Figure Medical History Inquiries	$+0.0192$
feat_4202	Sensitive-info / policy-complaint requests	$+0.8259$
feat_8063	General factual/cultural benign queries	$+1.0663$
feat_9994	Enumerative benign-business-science prompts	$+1.0947$
feat_6238	Definition-of-risky-terms queries	$+0.8679$
feat_11404	Copyright/derivative-work permission requests	$+0.9226$
feat_7940	Defamation and fake-news fabrication requests	$+1.0392$
feat_11495	Creative ideation and invention prompts	$+1.2774$
feat_1227	Illicit finance / fraud evasion requests	$+1.5539$
feat_6562	Legitimate verification and administrative request prompts	$+1.8197$
feat_7575	Weak general-purpose informational/conversational request detector	$+3.2969$

Table 13: Full Ridge regression equation for HARMFUL_HARMLESS (test acc=0.696, $\tau = -28.17$, $n = 5000$). Sorted by coefficient value. Positive = predicts refusal; negative = predicts compliance.

Feature	Label	Coefficient
feat_3734	Weak surface-form template detector	-5.0612
feat_2286	Religious/ethnic group characterization (polysemantic)	-2.4171
feat_4205	Systemic harm and discrimination framing	-2.1364
feat_1636	Conspiracy/fabricated narrative + corporate email (polysemantic)	-1.8545
feat_11404	Copyright/derivative-work permission requests	-1.8397
feat_1923	Medical/mental health treatment requests	-1.8058
feat_10737	General benign informational explanation requests	-1.6863
feat_910	Corporate Email/Meeting Logistics	-1.6694
feat_9267	Video-game combat/action scenario requests	-1.5389
feat_4319	General benign informational queries	-1.4815
feat_7897	Administrative/Verification Request Language	-1.4155
feat_9623	Explanatory/argumentative framing detector	-1.3596
feat_3368	Short imperative instruction framing (strongly polysemantic)	-0.6277
feat_10940	Stereotyping protected groups as inferior	-1.2486
feat_1083	Trivia/lookup and benign productivity queries	-1.0933
feat_11236	Figurative action/aggression language detector	-0.8918
feat_3915	Abuse/harassment and humiliating-harm requests	-0.9729
feat_603	Biased inferiority and illicit trade/harm requests	-0.9621
feat_11813	Toxic social bias / discriminatory-harm requests	-0.9470
feat_7480	Email subject-line and message-summary requests	-0.9466
feat_7261	Protective safety/legal compliance advice	-0.9087
feat_2197	Manipulative abuse/grooming solicitation	-0.9342
feat_1742	Mundane creative-editing and trivia requests	-0.8978
feat_2684	Corporate email/attachment logistics	-0.8688
feat_6562	Legitimate verification and administrative request prompts	-0.8387
feat_11840	Corporate email/admin document text	-0.8086
feat_8240	Trivia and classification questions	-0.3244
feat_6733	Copyright/defamation misuse requests	-0.7080
feat_5098	Corporate email/admin task requests (weak)	-0.7409
feat_1532	Violent / sadistic scene requests	-0.5322
feat_5449	Rumor-seeking and secret-sharing requests	-0.7314
feat_11223	Competitive Skill-Improvement Metaphors	-0.7423
feat_7063	Sensitive social/organizational explanation requests	-0.3836
feat_4396	Public Figure Medical History Inquiries	-0.4959
feat_3277	Practical everyday advice/problem-solving requests	-0.2537
feat_1748	Comparison-Framed Social/Cultural Difference Questions	-0.7351
feat_2742	Email/Document Revision and Legal-Admin Text	-0.8404
feat_4986	Ethical/classification/recommendation task prompts	-0.4740
feat_6499	Generic benign writing/tasks	-0.3433
feat_6815	Harmful advocacy with deceptive framing	-0.4398
feat_5509	Grammar/style transformation and neutral writing prompts	-0.3019
feat_11861	Anti-fraud and verification requests	-0.2033
feat_7294	Deceptive malicious manipulation requests	-0.1818
feat_823	Basic arithmetic and sequence/number-pattern problems	-1.0163
feat_3868	Address-and-contact lookup requests	-0.3014
feat_286	Email subject-line / document summarization requests	-0.1131
feat_10000	Neutral factual/general knowledge and email-writing prompts	-0.0329
feat_8140	Email/task-management correspondence	-0.2319
feat_12232	General benign informational question answering	-0.6975
feat_9558	Word-list sentence/puzzle prompts	-0.0061
feat_3248	Deceptive harm: fraud, hoaxes, and misinformation	$+0.0183$
feat_10878	Stereotype-based demeaning character portrayals	$+0.0367$
feat_11382	Copyright/compliance and policy-clarification requests	$+0.0902$
feat_6213	Email/admin subject-line drafting	$+0.0584$
feat_4112	Historical causation of genocides and revolutions	$+0.0578$
feat_3767	Copyright-safe creative and formatting requests (weak)	$+0.0702$
feat_11634	Privacy/identity-check and harmless business inquiry requests	$+0.0267$
feat_11756	Copyrighted-media permission and attribution requests	$+0.0133$
feat_8063	General factual/cultural benign queries	$+0.2898$
feat_4590	Stereotyping and generalization prompts	$+0.2073$
feat_3895	General factual/cultural trivia questions	$+0.4383$
feat_2827	Neutral procedural text with risky-content overlap	$+0.3589$
feat_7940	Defamation and fake-news fabrication requests	$+0.5024$
feat_9994	Enumerative benign-business-science prompts	$+0.4062$
feat_7971	Fictional scenario safety/secure-escape questions	$+0.5004$
feat_4202	Sensitive-info / policy-complaint requests	$+0.5895$
feat_6238	Definition-of-risky-terms queries	$+0.0830$
feat_728	No coherent semantic theme — weak diffuse detector	$+0.4079$
feat_2945	Internal business email logistics	$+0.4038$
feat_3772	Biased demeaning requests about protected groups	$+0.2894$
feat_11495	Creative ideation and invention prompts	$+0.7406$
feat_8184	Risk-avoidance / verification requests	$+1.0652$

Table 14: Full Ridge regression equation for APPENDIX_SEED0 (test acc=0.665, $\tau = -28.53$, $n = 2000$). Sorted by coefficient value. Positive = predicts refusal; negative = predicts compliance.

Feature	Label	Coefficient
feat_2286	Religious/ethnic group characterization (polysemantic)	-4.2681
feat_3368	Short imperative instruction framing (strongly polysemantic)	-3.6119
feat_1636	Conspiracy/fabricated narrative + corporate email (polysemantic)	-2.6392
feat_9623	Explanatory/argumentative framing detector	-2.4319
feat_4205	Systemic harm and discrimination framing	-2.3342
feat_3734	Weak surface-form template detector	-1.9589
feat_1728	General-purpose benign inquiry / informational request	-1.6702
feat_5449	Rumor-seeking and secret-sharing requests	-1.5525
feat_10940	Stereotyping protected groups as inferior	-1.4981
feat_1227	Illicit finance / fraud evasion requests	-1.0727
feat_7261	Protective safety/legal compliance advice	-1.1096
feat_1742	Mundane creative-editing and trivia requests	-1.1230
feat_10737	General benign informational explanation requests	-1.2011
feat_2742	Email/Document Revision and Legal-Admin Text	-1.0578
feat_1923	Medical/mental health treatment requests	-1.0847
feat_11236	Figurative action/aggression language detector	-0.9372
feat_2197	Manipulative abuse/grooming solicitation	-0.9434
feat_6815	Harmful advocacy with deceptive framing	-0.9385
feat_603	Biased inferiority and illicit trade/harm requests	-0.9861
feat_4396	Public Figure Medical History Inquiries	-0.8462
feat_3277	Practical everyday advice/problem-solving requests	-0.7491
feat_4112	Historical causation of genocides and revolutions	-0.7420
feat_7480	Email subject-line and message-summary requests	-1.1540
feat_9267	Video-game combat/action scenario requests	-0.7749
feat_3915	Abuse/harassment and humiliating-harm requests	-0.7712
feat_7063	Sensitive social/organizational explanation requests	-0.5800
feat_5098	Corporate email/admin task requests (weak)	-0.4053
feat_11223	Competitive Skill-Improvement Metaphors	-0.6302
feat_728	No coherent semantic theme — weak diffuse detector	-0.3070
feat_4986	Ethical/classification/recommendation task prompts	-0.7203
feat_5509	Grammar/style transformation and neutral writing prompts	-0.5286
feat_6733	Copyright/defamation misuse requests	-0.4465
feat_286	Email subject-line / document summarization requests	-0.4830
feat_12232	General benign informational question answering	-0.6279
feat_6499	Generic benign writing/tasks	-0.4188
feat_1748	Comparison-Framed Social/Cultural Difference Questions	-1.0587
feat_3868	Address-and-contact lookup requests	-0.8647
feat_2684	Corporate email/attachment logistics	-0.3950
feat_3767	Copyright-safe creative and formatting requests (weak)	-0.0094
feat_6213	Email/admin subject-line drafting	-0.2566
feat_11813	Toxic social bias / discriminatory-harm requests	-0.0854
feat_11861	Anti-fraud and verification requests	-0.0339
feat_11634	Privacy/identity-check and harmless business inquiry requests	-0.0005
feat_8240	Trivia and classification questions	-0.1246
feat_11756	Copyrighted-media permission and attribution requests	-0.1157
feat_7294	Deceptive malicious manipulation requests	-0.0086
feat_3248	Deceptive harm: fraud, hoaxes, and misinformation	-0.0290
feat_10878	Stereotype-based demeaning character portrayals	-0.2099
feat_9558	Word-list sentence/puzzle prompts	$+0.1671$
feat_4590	Stereotyping and generalization prompts	$+0.1015$
feat_11382	Copyright/compliance and policy-clarification requests	$+0.0735$
feat_10000	Neutral factual/general knowledge and email-writing prompts	$+0.4292$
feat_2827	Neutral procedural text with risky-content overlap	$+0.4752$
feat_7971	Fictional scenario safety/secure-escape questions	$+0.4152$
feat_4202	Sensitive-info / policy-complaint requests	$+0.1535$
feat_8184	Risk-avoidance / verification requests	$+0.1863$
feat_3772	Biased demeaning requests about protected groups	$+0.0975$
feat_8063	General factual/cultural benign queries	$+0.6452$
feat_11840	Corporate email/admin document text	$+0.8460$
feat_910	Corporate Email/Meeting Logistics	$+0.6172$
feat_11404	Copyright/derivative-work permission requests	$+0.6625$
feat_1986	Violent / sadistic scene requests	$+0.1435$
feat_823	Basic arithmetic and sequence/number-pattern problems	$+0.9869$
feat_7940	Defamation and fake-news fabrication requests	$+1.3348$
feat_9994	Enumerative benign-business-science prompts	$+0.2932$
feat_7897	Administrative/Verification Request Language	$+0.1676$
feat_11495	Creative ideation and invention prompts	$+1.5248$
feat_7575	Weak general-purpose informational/conversational request detector	$+2.5826$
feat_6562	Legitimate verification and administrative request prompts	$+2.4708$

Table 15: Full Ridge regression equation for APPENDIX_SEED1 (test acc=0.625, $\tau = -28.13$, $n = 2000$). Sorted by coefficient value. Positive = predicts refusal; negative = predicts compliance.

Feature	Label	Coefficient
feat_3368	Short imperative instruction framing (strongly polysemantic)	−3.5779
feat_2286	Religious/ethnic group characterization (polysemantic)	−3.1483
feat_4205	Systemic harm and discrimination framing	−3.1252
feat_4319	General benign informational queries	−2.7515
feat_9623	Explanatory/argumentative framing detector	−2.4555
feat_1636	Conspiracy/fabricated narrative + corporate email (polysemantic)	−2.2050
feat_8140	Email/task-management correspondence	−2.1833
feat_11236	Figurative action/aggression language detector	−2.1473
feat_1923	Medical/mental health treatment requests	−1.8802
feat_3868	Address-and-contact lookup requests	−1.8180
feat_10940	Stereotyping protected groups as inferior	−1.4171
feat_2197	Manipulative abuse/grooming solicitation	−1.2771
feat_1748	Comparison-Framed Social/Cultural Difference Questions	−1.2835
feat_1742	Mundane creative-editing and trivia requests	−1.2364
feat_1083	Trivia/lookup and benign productivity queries	−1.0383
feat_9267	Video-game combat/action scenario requests	−1.6940
feat_12232	General benign informational question answering	−1.6560
feat_3734	Weak surface-form template detector	−0.9073
feat_5449	Rumor-seeking and secret-sharing requests	−0.5918
feat_7261	Protective safety/legal compliance advice	−0.5629
feat_2742	Email/Document Revision and Legal-Admin Text	−0.8759
feat_3277	Practical everyday advice/problem-solving requests	−0.5383
feat_7897	Administrative/Verification Request Language	−0.9254
feat_5098	Corporate email/admin task requests (weak)	−0.5943
feat_10737	General benign informational explanation requests	−0.7545
feat_8184	Risk-avoidance / verification requests	−0.7091
feat_6733	Copyright/defamation misuse requests	−0.5290
feat_7480	Email subject-line and message-summary requests	−0.3470
feat_11861	Anti-fraud and verification requests	−0.4704
feat_603	Biased inferiority and illicit trade/harm requests	−0.4821
feat_4112	Historical causation of genocides and revolutions	−0.4135
feat_11382	Copyright/compliance and policy-clarification requests	−0.0028
feat_286	Email subject-line / document summarization requests	−0.4626
feat_4986	Ethical/classification/recommendation task prompts	−0.3308
feat_3767	Copyright-safe creative and formatting requests (weak)	−0.3238
feat_6499	Generic benign writing/tasks	−0.1537
feat_5509	Grammar/style transformation and neutral writing prompts	−0.6107
feat_9558	Word-list sentence/puzzle prompts	−0.4848
feat_1228	Illicit finance / fraud evasion requests	−0.0616
feat_10878	Stereotype-based demeaning character portrayals	−0.0611
feat_3248	Deceptive harm: fraud, hoaxes, and misinformation	−0.1081
feat_1728	General-purpose benign inquiry / informational request	−0.1879
feat_7294	Deceptive malicious manipulation requests	+0.0037
feat_6815	Harmful advocacy with deceptive framing	+0.1834
feat_2945	Internal business email logistics	+0.1032
feat_8240	Trivia and classification questions	+0.1892
feat_11634	Privacy/identity-check and harmless business inquiry requests	+0.0401
feat_11756	Copyrighted-media permission and attribution requests	+0.1108
feat_3895	General factual/cultural trivia questions	+0.6294
feat_4590	Stereotyping and generalization prompts	+0.2968
feat_3772	Biased demeaning requests about protected groups	+0.3661
feat_6213	Email/admin subject-line drafting	+0.2487
feat_11813	Toxic social bias / discriminatory-harm requests	+0.1214
feat_823	Basic arithmetic and sequence/number-pattern problems	+0.1330
feat_10000	Neutral factual/general knowledge and email-writing prompts	−0.1383
feat_4396	Public Figure Medical History Inquiries	+0.5165
feat_4202	Sensitive-info / policy-complaint requests	+0.3586
feat_7971	Fictional scenario safety/secure-escape questions	+0.9874
feat_2827	Neutral procedural text with risky-content overlap	+0.5171
feat_9994	Enumerative benign-business-science prompts	+0.5892
feat_8063	General factual/cultural benign queries	+0.6589
feat_11404	Copyright/derivative-work permission requests	+0.6791
feat_6238	Definition-of-risky-terms queries	+1.1758
feat_7940	Defamation and fake-news fabrication requests	+1.3462
feat_910	Corporate Email/Meeting Logistics	+1.1420
feat_1986	Violent / sadistic scene requests	+0.1391
feat_6562	Legitimate verification and administrative request prompts	+1.5056
feat_11495	Creative ideation and invention prompts	+2.0552
feat_7575	Weak general-purpose informational/conversational request detector	+1.2737

Table 16: Full Ridge regression equation for APPENDIX_SEED2 (test acc=0.633, $\tau = -30.60$, $n = 2000$). Sorted by coefficient value. Positive = predicts refusal; negative = predicts compliance.

Feature	Label	Coefficient
feat_3368	Short imperative instruction framing (strongly polysemantic)	-5.2368
feat_2286	Religious/ethnic group characterization (polysemantic)	-3.0932
feat_9623	Explanatory/argumentative framing detector	-3.0148
feat_1636	Conspiracy/fabricated narrative + corporate email (polysemantic)	-2.4465
feat_728	No coherent semantic theme — weak diffuse detector	-2.2394
feat_8140	Email/task-management correspondence	-2.2382
feat_4319	General benign informational queries	-2.2023
feat_4205	Systemic harm and discrimination framing	-2.1838
feat_3734	Weak surface-form template detector	-0.8533
feat_10940	Stereotyping protected groups as inferior	-1.4758
feat_1239	Comparison-Framed Social/Cultural Difference Questions	-1.2394
feat_7063	Sensitive social/organizational explanation requests	-1.1583
feat_1742	Mundane creative-editing and trivia requests	-1.0400
feat_2742	Email/Document Revision and Legal-Admin Text	-0.9607
feat_7897	Administrative/Verification Request Language	-0.8384
feat_8240	Trivia and classification questions	-0.8071
feat_5449	Rumor-seeking and secret-sharing requests	-0.8121
feat_7261	Protective safety/legal compliance advice	-0.6914
feat_2684	Corporate email/attachment logistics	-0.6560
feat_603	Biased inferiority and illicit trade/harm requests	-0.5896
feat_3915	Abuse/harassment and humiliating-harm requests	-1.1894
feat_5509	Grammar/style transformation and neutral writing prompts	-0.3992
feat_5098	Corporate email/admin task requests (weak)	-0.5194
feat_6733	Copyright/defamation misuse requests	-0.5333
feat_11382	Copyright/compliance and policy-clarification requests	-0.3761
feat_11199	Privacy/identity-check and harmless business inquiry requests	-0.1996
feat_286	Email subject-line / document summarization requests	-0.5375
feat_4112	Historical causation of genocides and revolutions	-0.2457
feat_11813	Toxic social bias / discriminatory-harm requests	-0.5383
feat_3277	Practical everyday advice/problem-solving requests	-0.5654
feat_7294	Deceptive malicious manipulation requests	-0.2468
feat_1728	General-purpose benign inquiry / informational request	-0.2974
feat_3767	Copyright-safe creative and formatting requests (weak)	-0.4162
feat_10878	Stereotype-based demeaning character portrayals	-0.2247
feat_823	Basic arithmetic and sequence/number-pattern problems	-0.5178
feat_3248	Deceptive harm: fraud, hoaxes, and misinformation	-0.0962
feat_9558	Word-list sentence/puzzle prompts	-0.2615
feat_6213	Email/admin subject-line drafting	-0.0924
feat_9267	Video-game combat/action scenario requests	-0.2727
feat_4986	Ethical/classification/recommendation task prompts	-0.1595
feat_3868	Address-and-contact lookup requests	-0.1818
feat_11756	Copyrighted-media permission and attribution requests	-0.1227
feat_10737	General benign informational explanation requests	-0.8706
feat_1227	Illicit finance / fraud evasion requests	-0.1423
feat_2197	Manipulative abuse/grooming solicitation	-1.0720
feat_7480	Email subject-line and message-summary requests	$+0.0486$
feat_11634	Privacy/identity-check and harmless business inquiry requests	-0.1996
feat_4590	Stereotyping and generalization prompts	$+0.3992$
feat_3772	Biased demeaning requests about protected groups	$+0.7253$
feat_2945	Internal business email logistics	$+0.0681$
feat_3895	General factual/cultural trivia questions	$+0.2276$
feat_6499	Generic benign writing/tasks	-0.2375
feat_8184	Risk-avoidance / verification requests	$+0.5280$
feat_8063	General factual/cultural benign queries	$+0.4878$
feat_11223	Competitive Skill-Improvement Metaphors	$+0.5888$
feat_9994	Enumerative benign-business-science prompts	$+0.5808$
feat_12232	General benign informational question answering	$+0.2867$
feat_11404	Copyright/derivative-work permission requests	$+0.6604$
feat_4202	Sensitive-info / policy-complaint requests	$+1.0151$
feat_11495	Creative ideation and invention prompts	$+0.7815$
feat_2827	Neutral procedural text with risky-content overlap	$+0.2955$
feat_7971	Fictional scenario safety/secure-escape questions	$+1.3680$
feat_6238	Definition-of-risky-terms queries	$+1.2768$
feat_11236	Figurative action/aggression language detector	$+0.3507$
feat_1986	Violent / sadistic scene requests	$+0.3756$
feat_7940	Defamation and fake-news fabrication requests	$+0.1919$
feat_910	Corporate Email/Meeting Logistics	-0.4049
feat_6562	Legitimate verification and administrative request prompts	$+1.9129$
feat_7575	Weak general-purpose informational/conversational request detector	$+3.5297$