Cortico-cerebellar networks as decoupled neural interfaces

Abstract

The brain solves the credit assignment problem remarkably well. For credit to be correctly assigned across multiple cortical areas a given area should, in principle, wait for others to finish their computation. How the brain deals with this locking problem has remained unclear. Deep learning methods suffer from similar locking constraints both on the forward and backward phase. Recently, decoupled neural interfaces (DNI) were introduced as a solution to the forward and backward locking problems. Here we propose that a specialised brain region, the cerebellum, helps the cerebral cortex solve the locking problem closely matching the computations and architecture of DNI. In particular, we propose that classical cerebellar forward and inverse models are equivalent to solving the backward and forward locking problems, respectively. We tested the cortico-cerebellar-DNI (CC-DNI) model in a range of sensorimotor and cognitive tasks that have been shown to be cerebellar-dependent. First, we show that the CC-DNI unlocking mechanisms can facilitate learning in a simple target reaching task. Next, by building on the sequential MNIST task we demonstrate that these results generalise to more complex sensorimotor tasks. Our cortico-cerebellar model readily applies to a wider range of modalities, to demonstrate this we tested the model in a cognitive task, caption generation. Models without the cerebellar-DNI component exhibit deficits similar to what has been observed in cerebellar patients in both motor and cognitive tasks. Finally, we introduce a CC-DNI model with highly sparse connectivity as observed in the cerebellum, which substantially reduces the number of parameters while improving learning through decorrelation. Overall, our work offers a novel perspective on the cerebellum as a brain-wide decoupling machine for efficient credit assignment and opens a new avenue of research between deep learning and neuroscience.

1 Introduction

Efficient credit assignment in the brain is a critical part of learning. However, how the brain solves the credit assignment problem remains a mystery. One of the central issues of credit assignment across multiple stages of processing is the need to wait for previous stages to finish their computation before others can proceed (Rumelhart et al., 1986; Schmidhuber, 1990; Lee et al., 2015; Marblestone et al., 2016; Jaderberg et al., 2017). In deep artificial neural networks these constraints are explicit. During the forward phase a given layer has to wait for all its previous layers to finish before it can proceed, a constraint known as the *forward lock*. Similarly, during the backward phase a given layer has to wait for all the layers above to finish computing its gradients – *backward lock*. Recently, a framework was introduced to decouple artificial neural networks – decoupled neural interfaces (DNI; (Jaderberg et al., 2017))[1], effectively breaking forward and/or backward locks.

Here, we propose that a specialised brain area, the cerebellum, performs a similar role in the brain. In the classical view the cerebellum is key for fine motor control and learning by constructing internal models of behaviour. (Marr, 1969; Albus, 1971; Raymond and Medina, 2018; Wolpert et al., 1998; Miall et al., 1993). More recently, however, the idea that the cerebellum is also involved in cognition has gained significant traction (Schmahmann et al., 2019; Wagner and Luo, 2020; Brissenden and Somers, 2019). An increasing body of behavioural, anatomical and imaging studies points to a role of the cerebellum in cognition in humans and non-human primates (Schmahmann et al., 2019;

---

[1]DNIs are related to earlier work on using network critics to train neural networks (Schmidhuber, 1990).

Brissenden and Somers, 2019; Guell et al., 2015; 2018). Impairments in cerebellar patients occur across a range of tasks including language (Guell et al., 2015), working memory (Deverett et al., 2019), planning (Baker et al., 1996), and others (Fiez et al., 1992). These observations suggest that the cerebellum implements a *universal function* across the brain (Diedrichsen et al., 2019). Moreover, experimental studies looking at cortico-cerebellar interactions have demonstrated that cerebellar output is crucial for maintaining neocortical representations in order to drive behaviour (Chabrol et al., 2019; Gao et al., 2018). However, to the best of our knowledge, no theoretical framework has considered what might be the function of such interactions between the cerebellum and cortical areas.

In an attempt to reduce the existing gap between experimental observations and existing computational approaches we introduce DNI as a cortico-cerebellar model – *cortico-cerebellar DNI* (CC-DNI). Consistent with the cerebellar universal role we theorise that the cerebellum serves to break the locks inherent to both feedforward and feedback information processing in the brain, akin to DNI. In particular, we posit that the two classical internal models of the cerebellum, forward and inverse models, are equivalent to DNI-mediated unlocking of feedback (gradients) and feedforward communication, respectively. Following this view the cerebellum not only provides motor or sensory estimates, but also any other modality encoded by a particular brain region. Inspired by neuroscientific studies, we test our model on sensorimotor tasks: (i) a target reaching task (Sanes et al., 1990; Butcher et al., 2017; Nashef et al., 2019) and (ii) a set of more complex temporal tasks based on the MNIST dataset, but also (iii) on a cognitive task – caption generation (Guell et al., 2015). Our results support the cortico-cerebellar DNI models we study and show that they generally speed up learning by unlocking the main network, qualitatively consistent with a wide range of behavioural observations (Guell et al., 2015; Sanes et al., 1990; Butcher et al., 2017; Nashef et al., 2019).

Two defining features of the cerebellum are the large expansion at the granule cell input layer with 50 billion neurons (the most numerous cell in the brain) and the highly sparse connectivity (each granule cell receives ~ 4 synapses) (Sanger et al., 2020). These observations have been long suggested to help speed-up learning in the cerebellum through decorrelation (Albus, 1971; Sanger et al., 2020; Cayco-Gajic et al., 2017). Building on these studies we introduce a new DNI model, *sparse CC-DNI*. Consistent with classical cerebellar models (Albus, 1971; Cayco-Gajic et al., 2017) we show that input sparsity can improve learning in the presence of high correlations. We finish with a discussion on the implications and predictions of this new brain-wide model of the cerebellum.

Figure 1: Cortico-cerebellar networks as decoupled neural interfaces (CC-DNI). Here we highlight the mapping between cerebellar forward models and backward DNI (back-CC-DNI). (**a**) In the classical forward model the cerebellum predicts the consequences ($\hat{g}_M$) of a given motor command (h_M). We propose that this predictive model enables the cerebellum to decouple the brain by breaking the backward (or feedback; dashed blue arrows) lock as done by DNI Jaderberg et al. (2017). By relying on the cerebellum for predictions $\hat{g}_M$ of motor commands h_M, the motor cortex can quickly receive a prediction to inform future behaviour. The cerebellum receives efferent motor copies, which project (sparsely) through mossy fibers (cyan) onto granule cells (PC; orange) and Purkinje cells (PC; orange). Learning is mediated by the inferior olive, which compares estimated predictions $\hat{g}_M$ with real predictions g_M, computing $\mathcal{L} = ||g_M - \hat{g}_M||$ (see main text). Sparse connectivity onto GCs (connections and pruned connections denoted by solid and dashed cyan lines, respectively) represents the sparseDNI model. (**b**) Example of backward CC-DNI model in a non-motor domain. Here the cerebellum computes a cognitive prediction g_I given an associative input h_A. Note that this model can be applied both in feedforward or recurrent networks.

2 CEREBELLUM AS A DECOUPLING MACHINE

We first describe DNIs following Jaderberg et al. (2017) and then establish the link to cortico-cerebellar networks. Assume that a feedforward neural network consists of N layers, with the ith layer ($1 \leq i \leq N$) performing a "computational step" f_i with parameters θ_i. Given input x at layer 1, the output of the network at its final layer is therefore given by $f_N(f_{N-1}(\ldots f_2(f_1(x))\ldots))$. We use $\mathcal{F}_i^j$ to denote the composition of steps from layer i to layer j (inclusively). Finally, let h_i denote the (hidden) activity at layer i, so that $h_i = f_i(h_{i-1})$ with $h_0 = x$.

To illustrate the locking constraints of standard artificial neural networks used in deep learning suppose that a network is in the process of learning via backpropagation, with current input-target pair (x, y_{targ}). To update the layer parameters θ_i the gradient $\frac{\partial L}{\partial \theta_i}$ is required, where $L = \mathcal{L}(y, y_{\text{targ}})$ is the loss which compares the target value against the model output $y = \mathcal{F}_1^N(x)$ under some loss function $\mathcal{L}$; we then apply gradient descent on the parameters, $\theta_i \leftarrow \theta_i - \alpha \frac{\partial L}{\partial \theta_i}$, with learning rate $\alpha > 0$. Suppose however that the network has only recently received the input x and is currently only at module i of the forward computation. In order to update the corresponding parameters of that layer, θ_i, the layer must first wait for all remaining layers to finish f_j ($j > i$) for the loss to be computed. Only then the various gradients of the loss are backpropogated and $\frac{\partial L}{\partial \theta_i}$ is finally available. These two characteristics of backpropagation make layer i "backward locked" to $\mathcal{F}_{i+1}^j$, enforcing a strong dependence of the layer's learning to the speed of forward and backward propagation through the rest of the network.

The key idea behind *backward DNI* is to break the backward lock by feeding the hidden layer i activity h_i to a separate neural network, a backward synthesiser $\mathcal{C}_i^B$, that learns to produce a *synthetic gradient* – an estimate of the real gradient expected by layer i, $\mathcal{C}_i(h_i) = \frac{\hat{\partial} L}{\partial h_i} \approx \frac{\partial L}{\partial h_i}$. This synthetic gradient can then be used to update the weights of layer i as soon as h_i is available, following

$$\theta_i \leftarrow \theta_i - \alpha \frac{\hat{\partial} L}{\partial h_i} \frac{\partial h_i}{\partial \theta_i}; \qquad \frac{\hat{\partial} L}{\partial h_i} = \mathcal{C}_i(h_i) \tag{1}$$

More specifically, the parameters of $\mathcal{C}_i^B(h_i)$ are learned by comparing the estimated gradient with the true gradient, $\mathcal{L} = ||\frac{\partial L}{\partial h_i} - \frac{\hat{\partial} L}{\partial h_i}||$. Interestingly, using a simple one or two hidden layer feedforward network to model $\mathcal{C}_i(h_i)$ has been shown to converge to the true gradient for linear deep networks Czarnecki et al. (2017), and to work well in practice for non-linear networks Jaderberg et al. (2017).

In contrast to backward DNI, *forward DNI* is used to break the "forward lock" within the network. In order to compute $\frac{\partial L}{\partial h_i}$ the activity h_i must be calculated via the forward propagation of all preceding layers; until then any update of f_i (and indeed, all subsequent layers) is locked to the forward pass of $\mathcal{F}_1^{i-1}$. Forward DNI removes this restriction by providing a direct connection between the input x (or any other layer $i - 1$) and module i. This is achieved again with the use of a distinct network, a forward synthesiser $\mathcal{C}_i^F$, which attempts to replicate the composition of steps between x and f_i, so that $\mathcal{C}^F(x) \approx \mathcal{F}_1^{i-1}(x)$.

2.1 CORTICO-CEREBELLAR DNI MODELS

Building directly on DNI we introduce a model of cortico-cerebellar computation (CC-DNI). These models use a simple feedforward neural network, consistent with the mostly feedforward architecture of the cerebellum (Marr, 1969; Albus, 1971; Raymond and Medina, 2018). The input layer of the cerebellum module $\mathcal{C}$ models the mossy fiber input onto granule cells (GCs; Fig. 1), which are the most numerous neurons in the brain (> 50 billion in humans (Herculano-Houzel, 2009)). Consistent with this cerebellar dimensionality expansion, in our models we use $M \gg N$, where M is the number of GCs and N the number of neurons in the main (cortical) network. (Fig. 1). In particular, we use ratios $\frac{M}{N} \sim 4$, consistent with experimental observations (Herculano-Houzel, 2009). In addition, the hidden layers and the output of $\mathcal{C}$ approximate the role of GCs and Purkinje cells, and the cerebellar output nuclei, respectively.

Cerebellar granule cells receive sparse input connections (K) with only around 3-7 synapses per GC (Herculano-Houzel, 2009; Eccles et al., 2013). These architectural constraints have led to sparse encoding and decorrelation theories of cerebellar function (Albus, 1971; Cayco-Gajic et al., 2017;

Schweighofer et al., 2001; Broomhead and Lowe, 1988; Billings et al., 2014; Litwin-Kumar et al., 2017; Sanger et al., 2019). Inspired on these features, we introduce a new model – *sparse CC-DNI* (sCC-DNI), for which we set a small number of incoming input connections $K = 4$ (Fig. 1).

To measure decorrelation achieved by sCC-DNI we use the Pearson correlation and a population correlation metric r_{pop} that has been shown to better capture cerebellar effects (Cayco-Gajic et al., 2017) $r_{\mathrm{pop}} = \frac{Z}{Z-1} \left(\frac{\max\{\sqrt{\lambda_i}\}_i}{\sum_i \sqrt{\lambda_i}} - \frac{1}{Z} \right)$ where Z are the number of neurons being considered and λ_i are the eigenvalues of the covariance matrix of the neuronal activity (e.g. h_M). To manipulate the hidden correlations of the model, we adjust the variance of its input and recurrent weights by scaling each by a factor b with $b \neq 1$ (see SM).

There is a strong similarity between CC-DNI models and the flow of information in standard internal models of the cortico-cerebellar networks (Fig. 1, Table S1). Below we draw a parallel between classical cerebellar internal models and our CC-DNI models. For simplicity, below and in our results we focus on the link between forward internal models and backward DNI (but see S1 for our interpretation of inverse internal model as forward DNI).

2.1.1 FORWARD CEREBELLAR MODELS AS BACKWARD DNI

We propose that classical forward cerebellar models are equivalent to backward DNI. In the forward model of sensorimotor control, the cerebellum receives an efferent copy of the motor command from the motor cortex (Miall et al., 1993; Ito, 1970), and sensory feedback from motor centres. With these two inputs the forward model learns to predict the sensory consequences of motor commands (Fig. 1a). Recently it has been argued that a similar predictive model can be applied to predict cerebral activity in brain regions such as the prefrontal cortex and the temporo-parietal cortex which are involved in planning of cognitive behaviour and decision making (Schmahmann et al., 2019; Wagner and Luo, 2020; Brissenden and Somers, 2019; Ito, 2008) (Fig. 1b). Similarly to the forward model backward-DNI also receives an efferent copy, which is represented by the hidden activity from a given layer (or brain area) h_i. From this input the synthesiser learns to predict the gradient with respect to the activity of layer h_{i+1} (Fig. 1a,c). In addition, we suggest that the cost function is computed by the *inferior olive* (e.g. $\mathcal{L} = ||g_M - \hat{g}_M||$; Fig. 1a), which mediates learning in the cerebellum via climbing fibres, consistent with existing cerebellar theoretical frameworks (Marr, 1969; Albus, 1971; Raymond and Medina, 2018). Finally, the prediction $\hat{g}_M$ is sent back to the brain (e.g. as sensory prediction). In the brain such gradient signals are believed to be encoded through feedback activity between brain areas (Sacramento et al., 2018; Richards and Lillicrap, 2019). However, in our experiments we use gradients directly as that allows us to use existing deep learning libraries.

Backward DNIs are of particular importance when using recurrent neural networks (RNNs), which learn to estimate future gradients from timestep $t + 1$ given current state at time t (Jaderberg et al., 2017) (see SM for more details). Our tasks use RNNs with backpropagation through time (BPTT) as it allow us to use current deep learning libraries and to more clearly demonstrate the potential of the CC-DNI models. In the brain temporal gradient signals are likely computed forward in time, in which CC-DNI would play a similar role in predicting future gradients given the current state (Fig. S2; (Bellec et al., 2019)). Here we use LSTMs (Hochreiter and Schmidhuber, 1997) as a model of cortical networks, which have recently been mapped onto cortical microcircuit (Costa et al., 2017).

2.1.2 ENCODING GRADIENTS IN THE BRAIN

Recent developments have introduced biologically plausible solutions to how the brain encodes gradients (Sacramento et al., 2018; Richards and Lillicrap, 2019; Lillicrap and Santoro, 2019; Guerguiev et al., 2017; Payeur et al., 2020; Ahmad et al., 2020). Regarding spatial backpropagation of gradients (i.e. across layers), Sacramento et al. (2018) demonstrated that biological networks do not need to explicitly send gradient information, but rather that this can be reconstructed locally in dendritic microcircuits. On the other hand Bellec et al. (2019) showed that temporal gradients as used in BPTT are equivalent to using eligibility traces that transmit gradient information forward in time. Both of these solutions can be incorporated into our framework, in which CC-DNI would predict feedback activity originating from upstream brain areas (as in Sacramento et al. (2018)) and/or eligibility traces in RNNs (see S2 for a schematic; Bellec et al. (2019)). However, this is outside of the scope of the current paper and we leave this to future work (see more detailed discussion in SM).

2.2 COMPARISON WITH EXISTING CEREBELLAR COMPUTATIONAL MODELS

Over the past decades the regular circuitry of the cerebellum has driven theorists to model the cerebellar cortex in order to understand its function (Kaiser et al., 2018). The Marr-Albus models are particular popular models which view the local cerebellar circuitry as multi-layer perceptrons (Albus, 1971). Another modelling framework that has been used is based on Kalman filters, which are also used to model the local circuitry to generate sensorimotor predictions (Porrill et al., 2013). These models have enabled significant theoretical and experimental advances. However, they do not consider potential interactions with the wider brain, in particular the neocortex, which are known to exist and appear to be critical for cerebellar function (Gao et al., 2018). Moreover, these models have so far only captured relatively simplistic (sensorimotor) tasks (e.g. eye-blink conditioning). In contrast, our framework provides a solution to both of these issues, while being consistent with existing local models of the cerebellum.

3 RESULTS

In this paper we focus our experiments on backward-CC-DNI models (cerebellar forward model; Fig. 1a,b) which we test on a range of task domains that have been shown to be cerebellar-dependent. Below we provide a summary of these different tasks and the respective results (see details in SM).

3.1 SIMPLE SENSORIMOTOR TASK: TARGET REACHING

Figure 2: Target reaching task. (**a**) Trajectory produced by LSTM (grey), CC-DNI (orange) and sCC-DNI (cyan) models towards 7 targets when using BPTT $T = 2$. (**b**) Models MSE. (**c**) Distance between model output and the targets. (**d**) MSE for multiple truncations T over the last 5 epochs. (**e**) MSE and correlation of hidden activity (r_h) at epoch 1. (**f**) Correlation of CC-DNI estimated gradients ($r_{\hat{g}}$) over the first 100 epochs of learning.

Inspired by classical sensorimotor studies in the cerebellum we first test a simple target reaching task (Sanes et al., 1990; Butcher et al., 2017; Nashef et al., 2019), in which given an input at time t_1 the network needs to reach a target (Fig. 2a and S8; see SM for more details). In this task error signals are only available at the end of task, which must be associated with the initial input. In line with cerebellar experiments (Sanes et al., 1990; Butcher et al., 2017; Nashef et al., 2019), only the CC-DNI models learn to reach the target with good accuracy, while LSTM still learns but much more slowly (Fig. 2a,b). Interestingly, sparse CC-DNI not only learns more quickly than CC-DNI (Fig. 2b,d, and S3), but also reaches the target more quickly (i.e. in fewer time steps) than the two other models (Fig. 2c). Consistent with cerebellar theories (Sanger et al., 2020; Cayco-Gajic et al., 2017; Billings et al., 2014) sCC-DNI helps when high correlations are present in the main network activity h (Fig. 2e), due to decorrelation of its estimated gradients $\hat{g}$ (Figs. 2f; see S6 for pop. corr.). CC-DNI properties are particularly important when learning with low BPTT truncations (Fig. 2d), predicting that the cerebellum is particularly important for more temporally challenging tasks and consistent with DNI theory (Jaderberg et al., 2017).

3.2 ADVANCED SENSORIMOTOR TASK: SEQUENTIAL MNIST

Figure 3: Sequential MNIST tasks. (**a**) Illustration of the four variants of sequential MNIST (seqMNIST). Top left: Standard classification sequential MNIST (row-by-row). Top right: given seqMNIST input the model is asked to reach a target coordinates (c-seqMNIST); Bottom left: given seqMNIST input the model is asked to draw the digit following a template (dd-seqMNIST); Bottom right: as in dd-seqMNIST, but the model is asked to draw a straight line (ld-seqMNIST). Target drawings in dotted grey and model output coloured by digit. (**b**) Validation learning curves for the four tasks with gradient truncation $T = 5$. For ld-seqMNIST, different degrees of loss sparsity γ are shown (see main text). (**c**) Model performance across T for seqMNIST (top) and respective differences between DNI and LSTM (bottom). (**d**) Model performance after 5 epochs as a function of the Pearson correlation r_h of the hidden activity at epoch 1 in the main network (dots; top). Correlation of synthetic gradients $r_{\hat{g}}$ produced by CC-DNIs (bottom).

Next, to test whether the target reaching results generalise to more realistic tasks we explored a range of more advanced sensorimotor tasks building on the classical MNIST dataset.

3.2.1 SEQUENTIAL MNIST

We first test the standard sequential MNIST (seqMNIST), in which the model gradually receives an MNIST image row by row before classifying the image as a number $0 - 9$ (Fig. 3a) (Le et al., 2015). As in the target reaching task, the loss function is only defined at the end of the sequence, making this a challenging temporal task.

With truncated BPTT with modest truncation sizes $T \leq 6$, CC-DNI models learn more quickly and achieve better overall performance compared to a standard LSTM (Fig. 3b,c), in line with the previous task. Interestingly, for this task we observe that the cerebellar architecture (i.e. high $\frac{M}{N}$ ratio, and sparse input connections K) to be the best solution (Figs. S4, S5). As in the target reaching task, sparse CC-DNI helps in the case of high correlations in the main network activity h, likely achieved by the decorrelation effect sCC-DNI has on the estimated gradients $\hat{g}$ (Figs. 3d, S7).

3.2.2 COORDINATE SEQUENTIAL MNIST

To see how well the above results generalise to a regression task in which the model has to reach a particular point (as in the target reaching task), we develop a coordinate seqMNIST (c-seqMNIST)

task. As before, the model receives the image sequentially, but must now output one out of ten different equally spaced 2D coordinates (Fig. 3a). Note that this is a harder task as models have to learn to transform a complex input pattern towards a specific 2D point (Fig. 3b). Both DNI models outperformed the LSTM model. There is however notably less difference between sCC-DNI and CC-DNI between compared to the standard version of seqMNIST (see also the following tasks), which may suggests that the cerebellum is better suited for pattern separation tasks, in line with existing cerebellar pattern separation theories (Albus, 1971; Sanger et al., 2020; Cayco-Gajic et al., 2017; Litwin-Kumar et al., 2017).

3.2.3 DRAWING SEQUENTIAL MNIST

Next, we test an explicit drawing task in which we trained the models to draw either a template digit (dd-seqMNIST) or a straight line (ld-seqMNIST) given an image of a digit (Fig. 3a). For these tasks, the loss function is computed at every point in time as $\mathcal{L} = (y_i - \hat{y}_i)^2$, where y_i and $\hat{y}_i$ denote the desired and predicted coordinate at timestep i, respectively. Due to the loss being computed at every timestep in both tasks, CC-DNI models are not as important and show a minimal improvement in performance (Figs. 3b, S4). To demonstrate that the temporal resolution of the loss is important for CC-DNI, we varied the loss sparsity, giving the model a loss every γ timesteps for ld-seqMNIST. This setup resembles sensorimotor feedback which is typically periodic rather than continuous (Sanes et al., 1990; Synofzik et al., 2008). As expected, for sparser losses (i.e. higher γ) both DNI models improves learning (Fig. 3b).

3.3 COGNITIVE TASK: CAPTION GENERATION

Our framework does not only apply to sensorimotor tasks, but should generalise to virtually any task within the grasp of deep learning systems, or indeed the brain. To demonstrate this and inspired by cognitive tasks in which cerebellar patients have shown deficits (Gebhart et al., 2002) we test our models in a caption generation task. In this task the network needs to generate a textual description for a given image. All models have two components: a pretrained convolutional neural network (CNN) to extract a lower dimensional representation of the image, and an LSTM on top to generate text (Fig. 4a). For simplicity and to draw comparison with previous tasks the DNI models contain one synthesiser at the RNN-level, but more could be added to help learning of the CNN.

We use a standard dataset (ILSVRC-2012-CLS (Russakovsky et al., 2015)) and the networks are trained to maximise the likelihood of each target word given an image (SM for more details). We find that CC-DNI models exhibit faster learning (Fig. 4b) for truncation sizes $T \leq 10$ (Fig. 4d) and better generalisation[2] (Fig. S13). All models produce reasonable captions for images unseen during training, but CC-DNI models tend to produce captions more semantically accurate than LSTMs (Figs. 4c, S12), consistent with cerebellar deficits (Guell et al., 2015). In addition, we observe that sCC-DNI are more robust to initial conditions (Fig. 4d), consistent with the decorrelation property. Moreover, consistent with bridging of gradient truncations provided by DNIs, we observe that CC-DNI helps learning in the presence of long captions, whereas sCC-DNI helps mostly for the most common caption lengths (Fig. 4d), suggesting that sCC-DNI better captures the data distribution.

4 CONCLUSIONS

Our work introduces a deep learning model of cortico-cerebellar function, which suggests that the cerebellum functions as a decoupling machine. We demonstrate that this idea is directly related to classical cerebellar forward and inverse models (Marr, 1969; Albus, 1971; Raymond and Medina, 2018), but with the key prediction that the cerebellum decouples activity propagation across the brain, speeding up credit assignment across multiple brain areas. Temporal credit assignment is directly related to the ability of networks to maintain input information (Bellec et al., 2019). Therefore, our results on truncated BPTT suggest that the cerebellum becomes increasingly important as task difficulty increases due to the inability of cortical networks to maintain a information for longer than hundreds of milliseconds until an error signal arrives, consistent with recent observations (Deverett et al., 2019).

---

[2]See Czarnecki et al. (2017) for discussion on the regularisation effect of synthetic gradients.

Figure 4: Caption generation task. (**a**) A graphical description of the model. The image is first processed by a pretrained convolutional neural network (CNN). The resulting feature vector is then provided to a connected but distinct RNN which is trained to predict the next word given the previous words of a provided "gold standard" caption to the image. The cerebellum module $\mathcal{C}$ is only applied to the RNN. (**b**) Top: Learning curves in bits per word (BPW) on validation set for gradient truncation $T = 4$. Full learning curve shown as inset. Bottom: standard language metrics (BLEU, Rouge-L, METEOR, CIDEr, SPICE). (**c**) Two example images from the validation set with corresponding model captions and gold standard captions (black). (**d**) Top: Change in loss with respect to LSTM as a function of T. Middle: Standard deviation σ_{loss} over the average loss across *all* epochs as a function of T. Bottom: Change in loss (i.e. CC-DNIs - LSTM) as a function of caption length, where the cross designates the mean (gold standard) caption length.

Our results are largely consistent with observed cognitive deficits in cerebellar patients, such as in language (Guell et al., 2015), which cannot be attributed directly to deficits in motor control (Stoodley and Schmahmann, 2009) and can in principle be used to develop behavioural strategies optimised to reduce deficits of cerebellar patients (Donchin and Timmann, 2019). Because of the explicit use of labels (or desired targets) here we have relied on supervised learning settings[3], but the same framework can be easily applied in reinforcement and other unsupervised learning settings (Jaderberg et al., 2017), which do not require an explicit teacher. Indeed the cerebellar model we propose here is of particular relevance for reinforcement learning due to the prevalence of sparse and delayed rewards, consistent with recent observations of reward-related signals in the cerebellum (Sendhilnathan et al., 2020).

Finally, our work makes numerous predictions and opens the exciting door to explicit comparison between the representations learned in the proposed cortico-cerebellar model and those recently observed across a range of motor and cognitive tasks (King et al., 2019; Ashida et al., 2019). On the deep learning side, with sparse CC-DNI we have only just scratched the surface of new DNI models that could be developed inspired by cortico-cerebellar networks. Overall, we put forward a novel cerebellar theory that is consistent with experimental observations while generating several experimental predictions and a window of interactions with deep learning research.

---

[3]Note, however, that learning of language models (as in caption generation) is often done in an unsupervised (self-supervised) setting.

REFERENCES

David E Rumelhart, Geoffrey E Hinton, and Ronald J Williams. Learning representations by back-propagating errors. *Nature*, 323(6088):533–536, 1986.

Jürgen Schmidhuber. Networks adjusting networks. In *Proceedings of" Distributed Adaptive Neural Information Processing"*, pages 197–208, 1990.

Dong-Hyun Lee, Saizheng Zhang, Asja Fischer, and Yoshua Bengio. Difference target propagation. In *Joint european conference on machine learning and knowledge discovery in databases*, pages 498–515. Springer, 2015.

Adam H Marblestone, Greg Wayne, and Konrad P Kording. Toward an integration of deep learning and neuroscience. *Frontiers in computational neuroscience*, 10:94, 2016.

Max Jaderberg, Wojciech Marian Czarnecki, Simon Osindero, Oriol Vinyals, Alex Graves, David Silver, and Koray Kavukcuoglu. Decoupled neural interfaces using synthetic gradients. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 1627–1635. JMLR. org, 2017.

David Marr. A theory of cerebellar cortex. *The Journal of Physiology*, 202(2):437–470, jun 1969. ISSN 00223751. doi: 10.1113/jphysiol.1969.sp008820. URL http://doi.wiley.com/10.1113/jphysiol.1969.sp008820.

James S Albus. A theory of cerebellar function. *Mathematical Biosciences*, 10(1):25–61, 1971. ISSN 0025-5564. doi: https://doi.org/10.1016/0025-5564(71)90051-4. URL http://www.sciencedirect.com/science/article/pii/0025556471900514.

Jennifer L Raymond and Javier F Medina. Computational principles of supervised learning in the cerebellum. *Annual review of neuroscience*, 41:233–253, 2018.

Daniel M Wolpert, R Chris Miall, and Mitsuo Kawato. Internal models in the cerebellum. *Trends in cognitive sciences*, 2(9):338–347, 1998.

R. C. Miall, D. J. Weir, D. M. Wolpert, and J. F. Stein. Is the cerebellum a smith predictor? *Journal of Motor Behavior*, 25(3):203–216, 1993. ISSN 19401027. doi: 10.1080/00222895.1993.9942050.

Jeremy D. Schmahmann, Xavier Guell, Catherine J. Stoodley, and Mark A. Halko. The Theory and Neuroscience of Cerebellar Cognition. *Annual Review of Neuroscience*, 42(1):337–364, jul 2019. ISSN 0147-006X. doi: 10.1146/annurev-neuro-070918-050258. URL https://www.annualreviews.org/doi/10.1146/annurev-neuro-070918-050258.

Mark J. Wagner and Liqun Luo. Neocortex–Cerebellum Circuits for Cognitive Processing. *Trends in Neurosciences*, 43(1):42–54, 2020. ISSN 1878108X. doi: 10.1016/j.tins.2019.11.002. URL https://doi.org/10.1016/j.tins.2019.11.002.

James A. Brissenden and David C. Somers. Cortico–cerebellar networks for visual attention and working memory. *Current Opinion in Psychology*, 29:239–247, 2019. ISSN 2352250X. doi: 10.1016/j.copsyc.2019.05.003. URL https://doi.org/10.1016/j.copsyc.2019.05.003.

Xavier Guell, Franziska Hoche, and Jeremy D. Schmahmann. Metalinguistic Deficits in Patients with Cerebellar Dysfunction: Empirical Support for the Dysmetria of Thought Theory. *Cerebellum*, 14(1):50–58, 2015. ISSN 14734230. doi: 10.1007/s12311-014-0630-z.

Xavier Guell, John D.E. Gabrieli, and Jeremy D. Schmahmann. Triple representation of language, working memory, social and emotion processing in the cerebellum: convergent evidence from task and seed-based resting-state fMRI analyses in a single large cohort. *NeuroImage*, 172:437–449, may 2018. ISSN 10959572. doi: 10.1016/j.neuroimage.2018.01.082.

Ben Deverett, Mikhail Kislin, David W Tank, S Samuel, and H Wang. Cerebellar disruption impairs working memory during evidence accumulation. *bioRxiv*, page 521849, 2019.

S C Baker, R D Rogers, Adrian M Owen, C D Frith, Raymond J Dolan, R S J Frackowiak, and Trevor W Robbins. Neural systems engaged by planning: a PET study of the Tower of London task. *Neuropsychologia*, 34(6):515–526, 1996.

Julie A Fiez, Steven E Petersen, Marshall K Cheney, and Marcus E Raichle. Impaired non-motor learning and error detection associated with cerebellar damage: A single case study. *Brain*, 115(1):155–178, 1992.

Jörn Diedrichsen, Maedbh King, Carlos Hernandez-Castillo, Marty Sereno, and Richard B. Ivry. Universal Transform or Multiple Functionality? Understanding the Contribution of the Human Cerebellum across Task Domains. *Neuron*, 102(5):918–928, 2019. ISSN 10974199. doi: 10.1016/j.neuron.2019.04.021.

Francois P Chabrol, Antonin Blot, and Thomas D Mrsic-Flogel. Cerebellar contribution to preparatory activity in motor neocortex. *Neuron*, 103(3):506–519, 2019.

Zhenyu Gao, Courtney Davis, Alyse M Thomas, Michael N Economo, Amada M Abrego, Karel Svoboda, Chris I De Zeeuw, and Nuo Li. A cortico-cerebellar loop for motor planning. *Nature*, 563(7729):113–116, 2018.

Jerome N Sanes, Bozhidar Dimitrov, and Mark Hallett. Motor learning in patients with cerebellar dysfunction. *Brain*, 113(1):103–120, 1990.

Peter A. Butcher, Richard B. Ivry, Sheng Han Kuo, David Rydz, John W. Krakauer, and Jordan A. Taylor. The cerebellum does more than sensory prediction error-based learning in sensorimotor adaptation tasks. *Journal of Neurophysiology*, 118(3):1622–1636, 2017. ISSN 15221598. doi: 10.1152/jn.00451.2017.

Abdulraheem Nashef, Oren Cohen, Ran Harel, Zvi Israel, and Yifat Prut. Reversible Block of Cerebellar Outflow Reveals Cortical Circuitry for Motor Coordination. *Cell Reports*, 27(9):2608–2619.e4, 2019. ISSN 22111247. doi: 10.1016/j.celrep.2019.04.100. URL https://doi.org/10.1016/j.celrep.2019.04.100.

Terence D. Sanger, Okito Yamashita, and Mitsuo Kawato. Expansion coding and computation in the cerebellum: 50 years after the Marr–Albus codon theory. *Journal of Physiology*, 598(5):913–928, mar 2020. ISSN 14697793. doi: 10.1113/JP278745.

N Alex Cayco-Gajic, Claudia Clopath, and R Angus Silver. Sparse synaptic connectivity is required for decorrelation and pattern separation in feedforward networks. *Nature communications*, 8(1):1–11, 2017.

Wojciech Marian Czarnecki, Grzegorz Swirszcz, Max Jaderberg, Simon Osindero, Oriol Vinyals, and Koray Kavukcuoglu. Understanding synthetic gradients and decoupled neural interfaces. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 904–912. JMLR. org, 2017.

Suzana Herculano-Houzel. The human brain in numbers: a linearly scaled-up primate brain. *Frontiers in Human Neuroscience*, 3:31, 2009. ISSN 1662-5161. doi: 10.3389/neuro.09.031.2009. URL https://www.frontiersin.org/article/10.3389/neuro.09.031.2009.

J C Eccles, M Ito, and J Szentagothai. *The Cerebellum as a Neuronal Machine*. Springer Berlin Heidelberg, 2013. ISBN 9783662131473. URL https://books.google.co.uk/books?id=omLoCAAAQBAJ.

N Schweighofer, K Doya, and F Lay. Unsupervised learning of granule cell sparse codes enhances cerebellar adaptive control. *Neuroscience*, 103(1):35–50, 2001. ISSN 0306-4522. doi: https://doi.org/10.1016/S0306-4522(00)00548-0. URL http://www.sciencedirect.com/science/article/pii/S0306452200005480.

David S Broomhead and David Lowe. Radial basis functions, multi-variable functional interpolation and adaptive networks. Technical report, Royal Signals and Radar Establishment Malvern (United Kingdom), 1988.

Guy Billings, Eugenio Piasini, Andrea L\Horincz, Zoltan Nusser, and R Angus Silver. Network structure within the cerebellar input layer enables lossless sparse encoding. *Neuron*, 83(4):960–974, 2014.

Ashok Litwin-Kumar, Kameron Decker Harris, Richard Axel, Haim Sompolinsky, and LF Abbott. Optimal degrees of synaptic connectivity. *Neuron*, 93(5):1153–1164, 2017.

Terence D Sanger, Okito Yamashita, and Mitsuo Kawato. Expansion coding and computation in the cerebellum: 50 years after the Marr-Albus codon theory. *The Journal of Physiology*, 2019.

M Ito. Neurophysiological aspects of the cerebellar motor control system. *International journal of neurology*, 7 (2):162–176, 1970. ISSN 0020-7446. URL http://europepmc.org/abstract/MED/5499516.

Masao Ito. Control of mental activities by internal models in the cerebellum. *Nature Reviews Neuroscience*, 9 (4):304–313, apr 2008. ISSN 1471-003X. doi: 10.1038/nrn2332. URL www.nature.com/reviews/neurohttp://www.nature.com/articles/nrn2332.

João Sacramento, Rui Ponte Costa, Yoshua Bengio, and Walter Senn. Dendritic cortical microcircuits approximate the backpropagation algorithm. In *Advances in Neural Information Processing Systems*, pages 8721–8732, 2018.

Blake A Richards and Timothy P Lillicrap. Dendritic solutions to the credit assignment problem. *Current opinion in neurobiology*, 54:28–36, 2019.

Guillaume Bellec, Franz Scherr, Elias Hajek, Darjan Salaj, Robert Legenstein, and Wolfgang Maass. Biologically inspired alternatives to backpropagation through time for learning in recurrent neural nets. *arXiv preprint arXiv:1901.09049*, 2019.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.

Rui Ponte Costa, Ioannis Alexandros Assael, Brendan Shillingford, Nando de Freitas, and Tim Vogels. Cortical microcircuits as gated-recurrent neural networks. In *Advances in neural information processing systems*, pages 272–283, 2017.

Timothy P Lillicrap and Adam Santoro. Backpropagation through time and the brain. *Current opinion in neurobiology*, 55:82–89, 2019.

Jordan Guerguiev, Timothy P Lillicrap, and Blake A Richards. Towards deep learning with segregated dendrites. *ELife*, 6:e22901, 2017.

Alexandre Payeur, Jordan Guerguiev, Friedemann Zenke, Blake Richards, and Richard Naud. Burst-dependent synaptic plasticity can coordinate learning in hierarchical circuits. *bioRxiv*, 2020. doi: 10.1101/2020.03. 30.015511. URL https://www.biorxiv.org/content/early/2020/03/31/2020.03.30. 015511.

Nasir Ahmad, Marcel A J van Gerven, and Luca Ambrogioni. GAIT-prop: A biologically plausible learning rule derived from backpropagation of error. *arXiv preprint arXiv:2006.06438*, 2020.

Jacques Kaiser, Hesham Mostafa, and Emre Neftci. Synaptic plasticity dynamics for deep continuous local learning. *arXiv preprint arXiv:1811.10766*, 2018.

John Porrill, Paul Dean, and Sean R Anderson. Adaptive filters and internal models: Multilevel description of cerebellar function. *Neural Networks*, 47:134–149, 2013. ISSN 0893-6080. doi: https://doi.org/10. 1016/j.neunet.2012.12.005. URL http://www.sciencedirect.com/science/article/pii/ S0893608012003206.

Quoc V Le, Navdeep Jaitly, and Geoffrey E Hinton. A simple way to initialize recurrent networks of rectified linear units. *arXiv preprint arXiv:1504.00941*, 2015.

Matthis Synofzik, Axel Lindner, and Peter Thier. The Cerebellum Updates Predictions about the Visual Consequences of One's Behavior. *Current Biology*, 18(11):814–818, 2008. ISSN 09609822. doi: 10.1016/j. cub.2008.04.071.

Andrea L Gebhart, Steven E Petersen, and W Thomas Thach. Role of the posterolateral cerebellum in language. *Annals of the New York Academy of Sciences*, 978(1):318–333, 2002.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 115(3):211–252, 2015. doi: 10.1007/s11263-015-0816-y.

Catherine J. Stoodley and Jeremy D. Schmahmann. Functional topography in the human cerebellum: A meta-analysis of neuroimaging studies. *NeuroImage*, 44(2):489–501, 2009. ISSN 10538119. doi: 10.1016/j. neuroimage.2008.08.039. URL http://dx.doi.org/10.1016/j.neuroimage.2008.08.039.

Opher Donchin and Dagmar Timmann. How to help cerebellar patients make the most of their remaining learning capacities. *Brain*, 142(3):492–495, 2019.

Naveen Sendhilnathan, Anna E Ipata, and Michael E Goldberg. Neural correlates of reinforcement learning in mid-lateral cerebellum. *Neuron*, 2020.

Maedbh King, Carlos R Hernandez-Castillo, Russell A Poldrack, Richard B Ivry, and Jörn Diedrichsen. Functional boundaries in the human cerebellum revealed by a multi-domain task battery. *Nature Neuroscience*, 22(8):1371–1378, August 2019.

Reiko Ashida, Nadia L Cerminara, Richard J Edwards, Richard Apps, and Jonathan C W Brooks. Sensorimotor, language, and working memory representation within the human cerebellum. *Human Brain Mapping*, 40(16): 4732–4747, July 2019.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pages 1026–1034, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. BLEU: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting on association for computational linguistics*, pages 311–318. Association for Computational Linguistics, 2002.

Chin-Yew Lin. {ROUGE}: A Package for Automatic Evaluation of Summaries. In *Text Summarization Branches Out*, pages 74–81, Barcelona, Spain, jul 2004. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/W04-1013.

Michael Denkowski and Alon Lavie. Meteor universal: Language specific translation evaluation for any target language. In *Proceedings of the ninth workshop on statistical machine translation*, pages 376–380, 2014.

Ramakrishna Vedantam, C Lawrence Zitnick, and Devi Parikh. Cider: Consensus-based image description evaluation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4566–4575, 2015.

Peter Anderson, Basura Fernando, Mark Johnson, and Stephen Gould. Spice: Semantic propositional image caption evaluation. In *European Conference on Computer Vision*, pages 382–398. Springer, 2016.

Richard Apps, Richard Hawkes, Sho Aoki, Fredrik Bengtsson, Amanda M. Brown, Gang Chen, Timothy J. Ebner, Philippe Isope, Henrik Jörntell, Elizabeth P. Lackey, Charlotte Lawrenson, Bridget Lumb, Martijn Schonewille, Roy V. Sillitoe, Ludovic Spaeth, Izumi Sugihara, Antoine Valera, Jan Voogd, Douglas R. Wylie, and Tom J. H. Ruigrok. Cerebellar Modules and Their Role as Operational Cerebellar Processing Units: A Consensus paper. *The Cerebellum*, 17(5):683–684, 2018. ISSN 1473-4222. doi: 10.1007/s12311-018-0959-9.

Nadia L. Cerminara and Richard Apps. Behavioural significance of cerebellar modules. *Cerebellum*, 10(3): 484–494, 2011. ISSN 14734222. doi: 10.1007/s12311-010-0209-2.

Tom J.H. Ruigrok. Ins and outs of cerebellar modules. *Cerebellum*, 10(3):464–474, 2011. ISSN 14734222. doi: 10.1007/s12311-010-0164-y.

Robert A Barton and Chris Venditti. Rapid evolution of the cerebellum in humans and other great apes. *Current Biology*, 24(20):2440–2444, 2014.

Suzana Herculano-Houzel. Coordinated scaling of cortical and cerebellar numbers of neurons. *Frontiers in Neuroanatomy*, 4(MARCH):1–8, 2010. ISSN 16625129. doi: 10.3389/fnana.2010.00012.

A   EXPERIMENTAL DETAILS

In each of our tasks we use a long-short term memory network (LSTM; (Hochreiter and Schmidhuber, 1997)) as the main "cortical" network (Costa et al., 2017), and a simple feedforward network of one (sensorimotor tasks) or two hidden layers (caption generation) as the synthesiser "cerebellar" network. As in (Jaderberg et al., 2017) the cerebellar network first predicts gradients for both the memory cell and output state of the LSTM (i.e. for each neuron in the main network the cerebellar network receives two inputs), so that the 'cerebellar' input and output size is two times the number of LSTM units, and this synthetic gradient $\hat{g}$ is then scaled by a factor of 0.1 before being used by the main model for stability purposes. The final 'readout' of the model is a (trained) linear sum of the LSTM output states. All networks are optimised using ADAM (Kingma and Ba, 2014) (see learning rates below).

In each experiment all initial LSTM parameters are drawn from the uniform distribution $\mathcal{U}(\frac{1}{\sqrt{n_{\text{LSTM}}}}, \frac{1}{\sqrt{n_{\text{LSTM}}}})$, where n_{LSTM} is the number of LSTM units. Other than the final layer, as in (Jaderberg et al., 2017), the feedforward weights of the cerebellar network are initialised according to $\mathcal{U}(-b_k, b_k)$ where b_k denotes the "kaiming bound" as computed in (He et al., 2015) (slope $a = \sqrt{5}$), and the biases are draw from $\mathcal{U}(\frac{1}{\sqrt{n_{\text{inp}}}}, \frac{1}{\sqrt{n_{\text{inp}}}})$, where n_{inp} denotes the input size of the layer. As in (Jaderberg et al., 2017), the last layer (both weights and bias) of the cerebellar network is zero-initialised, so that the produced synthetic gradients at the start are zero.

A range of correlations (here quantified as Pearson or population correlation coefficient) for the LSTM activity h can be achieved naturally through different random initialisations (accessed through different random seeds), but can be also controlled by the scaling of initial parameters of the LSTM with a bias factor b, where $b > 1$ and $b < 1$ induces greater and smaller variability in parameter values respectively. The results demonstrating the effect of correlation (Figs 2f,g, 3d) are obtained across 10 random seeds, for multiple bias factor values $b \in [0.01, 0.1, 0.5, 1, 2]$.

During learning, backpropogation through time (BPTT) takes place strictly within distinct truncations, and computed gradients are not propagated between them: *truncated* BPTT. As soon as the forward computation of a given truncation is completed, assuming a corresponding (synthetic) loss gradient is available, the model parameters are updated; that is, at a resolution of the preset truncation size, there is *online learning*. We split the original input into truncations as follows. Given an input sequence of N timesteps $x_1, x_2, \ldots, x_N$ and a truncation size T, we divide the sequence into T sized truncations with any remainder going to the last truncation. In other words, the sequence is now made up of truncations of $(x_1, \ldots, x_T), (x_{T+1}, \ldots, x_{2T}), \ldots, (x_{(m-1)T+1}, \ldots, x_{mT}), (x_{N-r}, \ldots, x_N)$, where $N = mT + r$ for positive integers m, r with $0 \leq r < T$. Note that, along with the value T, how well the sequence is divided into truncations (i.e. values m, r) is an important factor for learning.

Unless stated otherwise, reported error/loss values are on a held-out validation set at the end of learning. All experiments were conducted using PyTorch.

A.1   TARGET REACHING TASK

In the target reaching task, an LSTM network receives a discrete input cue which signals the network to move to a particular target location in 2D space. In the results presented in the main text (Fig. 2) we set 6 distinct non-zero input-target pairs $\{(x_i, y_i)\}_{i=1}^6$, where each input x_i is a (one dimensional) integer $\in \{\pm 1, \pm 2, \pm 3\}$, and the targets $\{y_i\}_{i=1}^6$ lie equidistantly on a circle centred on the origin with radius 10. Once an input cue is received at timestep t_0, the model receives no new information (i.e. all future input is zero) and has 10 timesteps to move to the corresponding target location. The model is trained to minimise the mean squared error (MSE) between its final output and the cue-based target. In addition, if no input cue is provided ($x = 0$), the network is trained to not move at all ($y = 0$). Note therefore that only the final model output 'matters' in the sense that it defines model performance.

The cortical network has one hidden layer of 10 LSTM units (i.e. 20 when including the memory cells; unless stated otherwise, the cerebellar network contains one hidden layer of 80 hidden neurons. The initial learning rate is set to 0.001. Each epoch comprises one batch of 50 randomised examples. Model performance is averaged over 10 random seeds (with error bars), where each seed determines the initial weights of the network. Truncation values $T \in [2, 3, 4, 5, 7]$ are considered.

Furthermore, to see how the above conditions generalise we consider variants of the task with 1. different numbers of cue/target pairs (see Fig. S8a and b) and 2. higher dimensional input (see Fig. S8c and d). More specifically, we consider two cases where the model receives two-dimensional (Fig. S8c) and 28-dimensional (Fig. S8d) input. For the former the model architecture remains the same except now the model receives at time t_0 the (two-dimensional) target values scaled by a factor 0.1 as input. For the latter we have an LSTM with 30 hidden units and the input x is now a binary vector of size 28. In order to increase the task difficulty for these variants of higher dimensional input, we add to the input Gaussian noise with variance 0.1 at each timestep.

A.2   SEQUENTIAL MNIST TASKS

For each seqMNIST based task the model receives the same temporal MNIST input, and the tasks are only differentiated by the model output. Given a 28×28 MNIST image, at timestep i the model receives the pixels from row i of the image, so that there are 28 total timesteps and an input size of 28. Only the final model output matters for the seqMNIST and c-seqMNIST tasks - that is, the loss is solely defined at the end of the sequence - whereas the model output is assessed at every timestep for dd-seqMNIST and ld-seqMNIST.

In each case we have one hidden layer of 30 LSTM units in the main model and one hidden layer of 300 (unless stated otherwise) hidden units in the feedforward cerebellar network. Data was presented in batches of 50 with an initial learning rate of 0.0001.

Training and validation data was assigned a $4 : 1$ split, containing 48000 and 12000 distinct image/number pairs respectively. The truncation values $T \in [2, 3, 4, 5, 7, 10]$ are considered. Model performance averaged (with error bars) over 3 random seeds for weight initialisation.

A.2.1   SEQMNIST

This is the standard form of seqMNIST, where at the end of the presentation of the image the model must classify in the image as a number between 0 and 9. The output of the model is a vector probabilities of size 10 (one entry for each number), and the model was trained to maximise the likelihood of the correct number.

A.2.2   C-SEQMNIST

In this variant each number 0-9 MNIST image is allocated an xy position on the edge of a circle centred at 0, with the position uniquely determined by the digit represented by the image (Fig. 3a). With the model output then a vector of size 2, the training loss is defined at the end by the mean squared error (MSE) between the final output of the model and the target coordinate; since the radius of the circle is length 10 (arbitrary unit), a static model, where the model output remains at 0, would have a constant MSE of 100.

A.2.3   DD-SEQMNIST

Like c-seqMNIST, in this variant the model outputs 2D coordinates, but now the model must learn to predict an entire sequence of coordinates $\{\hat{y}_i\}_{i=1}^{28}$. The target sequence $\{y_i\}_{i=1}^{28}$ can be considered a drawing, and in this case resembles the shape of the number itself (Fig. 3c; number 0 not shown). The model is then trained at each timestep to minimise the MSE between the model output at that time and corresponding target point, so that the loss at timestep t defined as $\mathrm{MSE}(y_t, \hat{y}_t)$.

For each number, the corresponding target drawing lies in $[0, 1]^2$, with the gap between each successive point roughly the same. To prevent the model being too harshly judged at timestep 1, all drawings begin in the top left corner $(0, 1)$ (apart from the drawing of 1 which begins slightly beneath/to the right). MSE scores are reported as 100 times their raw values to ease comparison with c-SEQMNIST/dd-SEQMNIST.

A.2.4   LD-SEQMNIST

This variant can be thought of as a mixture between c-seqMNIST and dd-seqMNIST. Like dd-seqMNIST the model is constantly assessed and must produce a desired shape, but now the desired set of points form an equally spaced line where the start point is the origin and the end point is

determined by the number-to-coordinate mapping of c-seqMNIST. As with dd-seqMNIST, the loss is defined at each timestep by the difference between the model output and appropriate point on the line.

A.3 CAPTION GENERATION

The architecture for the caption generation task consists of a pretrained CNN coupled with an RNN (LSTM in this case). The synthesiser (cerebellar network) only communicates to the LSTM. The LSTM network has one layer of 256 LSTM units and the cerebellar network has two hidden layers of 1024 neurons.

The dynamics from image to caption is as follows. As part of image preprocessing and data augmentation, a given image is randomly cropped to size 224×224, flipped horizontally with even chance, and appropriately normalised to be given to a pretrained resnet model (He et al., 2016). A feature vector X of size 256 is thus obtained and is passed to the LSTM at timestep 0. The LSTM is subsequently presented the "gold standard" caption $\{w_i\}_{i=1}^{n}$ one word per timestep, each time learning to predict the next word; i.e., at timestep t the model learns $P(w_t|X, \{w_i\}_{i=1}^{t-1})$. The network simultaneously learns a word embedding so that each word w_i is first transformed to a feature vector of size 256 before being served as input. With a preset vocabulary of 9956 distinct words, the final output of the model ($P(w_i)$) is a probability vector of size 9956.

We find that though DNI could help without any explicit method for regularisation (not shown), all models are prone to overfitting. For this reason, we apply dropout (during training) on the input to the LSTM, where a given input element is set to zero with $p = 0.5$ probability.

Once training is complete the models can generate their own unique captions to previously unseen images (Figs. 4, S12). Given an image at timestep 0,, the model applies a 'greedy search' where the output of the model at timestep i is the word with the highest probability, and the same word is then provided as input to the model at timestep $i + 1$. In this way the model eventually outputs an entire sequence of words which forms a caption. In the (highly) rare case where the model generates a sequence of > 20 words, we consider only the first 20 words as its caption.

The coco training set ILSVRC-2012-CLS (Russakovsky et al., 2015) holds 414113 total image-caption pairs with 82783 unique images while the held-out validation set holds 202654 with 40504 unique images; note that each image therefore has ~ 5 distinct gold standard captions. Training takes place in batches of 100 image/caption pairs, with learning rate of 0.001. Model performance averaged (with error bars) over 5 random seeds for weight initialisation.

In order to judge the models beyond their learning curves in BPW, we quantify their ability to generate captions using a variety of language modelling metrics popular in the realm of language evaluation (image captioning, machine translation, etc). In particular, we compare model-generated captions against the gold standard captions using the metrics BLEU, Rouge-L, METEOR, CIDEr, SPICE (Papineni et al., 2002; Lin, 2004; Denkowski and Lavie, 2014; Vedantam et al., 2015; Anderson et al., 2016). We use BLEU_4 (i.e. consider only n-grams for $n \leq 4$) as the default BLEU score (see Fig4), though we also look at BLEU_1, BLEU_2, BLEU_3 (Fig S15.

B COMPARISON WITH OTHER MODELS OF THE CEREBELLUM

In section 2 of the main text we argue that there is a strong similarity between the flow of information in DNI and classical internal models of the cerebellum. In Table S1 we compare explicitly the input and output components of both types of models.

B.0.1 INVERSE AND FORWARD DNI CEREBELLAR MODELS

The inverse model of the cerebellum in motor control computes the motor predictions given a target (or desired) response (Ito, 1970). Feedback errors are derived by comparing a motor command from the motor cortex with the predicted motor command in the cerebellum. We propose that the inverse model is equivalent to forward DNI, as it aims to predict the incoming activity at a given layer (e.g. motor command, h_M, or associative input, h_A) given the input activity observed at a lower layer (e.g. sensory target response, h_S; Fig. 1). Consistent with the modular anatomy of the cerebellum (Apps

	Forward Model	Backward DNI	Inverse Model	Forward DNI
Controller	Neocortex	Main model	Cerebellum	Synthesiser
Input	$\mathbf{h}_m$	$\mathbf{h}_m$	$\mathbf{h}_s, \mathbf{d}_s$	$\mathbf{h}_s$
Output	$f_{\text{unk}}(\mathbf{h}_m)$	$\mathcal{C}^B(\mathbf{h}_m) = \frac{\partial \hat{L}}{\partial \mathbf{h}_m}$	$f_{\text{unk}}(\mathbf{h}_s, \mathbf{d}_s)$	$\mathcal{C}^F(\mathbf{h}_s)$
Ouput destination	Neocortex	Main model	Controlled object	Main model

Table S1: Internal models versus DNI. The properties of the forward model of the cerebellum can be set against those of backward DNI (blue); similarly, the properties of the inverse model of the cerebellum can be set against those of forward DNI (red). Notation is largely consistent with section 2 of the main text: $\mathbf{h}_m, \mathbf{h}_s$ denotes the hidden activity of a motor area and sensory area, respectively; $\mathcal{C}^B, \mathcal{C}^F$ denotes the computation of backward DNI and forward DNI, respectively; L denotes the loss function. In addition, the inverse model of the cerebellum traditionally also has access to a *desired* state $\mathbf{d}_s$ (in particular, one can consider this a special case of "context" provided to the synthesiser; cf (Jaderberg et al., 2017)). There are no explicit equations for the computational processes of the forward and inverse models, and both are thus represented by the unknown function f_{unk}.

Figure S1: Equivalent to Fig. 1 for how cerebellar inverse models map onto forward DNI (forward-CC-DNI). (**a**) In the inverse model the cerebellum generates motor predictions ($\hat{h}_M$) given desired target responses (h_S). This allows the brain to break forward locks (dashed black arrows), for example to go directly from sensory areas to higher areas. The inferior olive plays a similar role to (a,b) but here it allows the cerebellum to learn estimations of forward activities (e.g. $\mathcal{L} = ||h_S - \hat{h}_M||$). (**b**) Example of forward CC-DNI model in a non-motor domain. The cerebellum computes an associative prediction h_A given a sensory input h_S. Multiple backward and forward DNI-cerebellum modules can co-exist working in parallel. h and g variables represent forward and gradient information as in DNI (see main text).

et al., 2018; Cerminara and Apps, 2011; Ruigrok, 2011) multiple CC-DNI (backward and/or forward) modules can co-exist estimating different pathways components.

C RECURRENT DNI

In section 2 of the main text we formally describe the dynamics of DNI in a feedforward setting. Here we show how these dynamics easily generalise to the time dependent, recurrent setting. We now take the main model as a recurrent neural network (RNN), where the (recurrent) hidden layer is again connected to a distinct, feedforward synthesiser. By unrolling the network over several timesteps we can keep much of the notation as introduced in section 2, but now h_i denotes the hidden (cortical) activity at *timestep i* (as opposed to layer i) with a unique recurrent weight $\theta (= \theta_i \forall i)$; furthermore, the loss L is now a sum of individual losses over the timesteps: $L = \sum_i L_i$.

DNI is strictly applied to RNNs which learn via truncated BPTT, where BPTT takes place in equally-spaced truncations of time so that any hidden activity will only be attributed to future losses within the truncation window T (i.e. $\frac{\partial L_{i+t}}{\partial h_i} = 0 \; \forall t > T$), effectively ignoring future losses and potentially disregarding important temporal correlations. The key idea behind recurrent DNI is to bridge these truncations using synthetic gradients (Fig. S2a). For simplicity assume that timestep i is the start of a given truncation. By enabling DNI, a (backward) synthesiser $\mathcal{C}$ is used to provide an estimated

gradient $\hat{\delta}_{i+T}$ for all future losses, *outside of the truncation*, with respect to the last hidden activity of the truncation h_{i+T}; i.e. $\hat{\delta}_{i+T} \approx \delta_{i+T} = \sum_{j=i+T+1}^{\infty} \frac{\partial L_j}{\partial h_{i+T}}$. The weight update is then analogous to the feedforward case in equation 1

$$\theta \leftarrow \theta - \alpha \Big[\sum_{j=i}^{i+T} \frac{\partial L_j}{\partial \theta} + \hat{\delta}_{i+T} \frac{\partial h_{i+T}}{\partial \theta} \Big]; \quad \hat{\delta}_{i+T} = \mathcal{C}(h_{i+T}) \tag{2}$$

It is not difficult to see that if the synthesiser perfectly predicts the future gradient, $\hat{\delta}_{i+T} = \delta_{i+T}$, then the weight will be perfectly updated according to the gradient of all future losses, $\theta \leftarrow \theta - \alpha \sum_{j=i}^{\infty} \frac{\partial L_i}{\partial \theta}$. Allowing the synthesiser access to this gold standard, δ_{i+T}, however, requires waiting an arbitrary amount of time and is therefore not practical for training. Instead, $\hat{\delta}_{i+T}$ is trained to replicate an itself approximate, bootstrapped version of the future gradient, $\bar{\delta}_{i+T}$, where $\bar{\delta}_{i+T} = \sum_{j=i+T+1}^{i+2T} \frac{\partial L_j}{\partial h_{i+T}} + \hat{\delta}_{i+2T} \frac{\partial h_{i+2T}}{\partial h_{i+T}}$. Note that $\bar{\delta}_{i+T}$ is available in one truncation's timespan.

In the brain an approximation of BPTT can be implemented forward in time using a mixture of eligibility traces and sparse learning signals (e.g. reward) ((Bellec et al., 2019); Fig. S2b). The dynamics of this more "biologically plausible" learning regime are subtle and are not described here; we simply mention that the cerebellum might be the source of such (future) learning signals and predict that many of the results observed with BPTT will hold for the forward propagation of gradients.

Figure S2: Synthetic gradients in RNNs with eligibility traces. (**a**) An example of backpropagation through time with truncation every T=3 timesteps (dashed black arrows). A DNI can be used to bridge the gap between truncations allowing gradients to be sent further back in time ($\hat{\delta}_t$ and $\hat{\delta}_{t+3}$). Adapted from Jaderberg et al. (2017). (**b**) Schematic of a biologically plausible RNN with eligibility traces that encode information needed to compute the gradients at a later point in time (green traces; cf. (Bellec et al., 2019)). The cerebellar-DNI model $\mathcal{C}$ can be used to estimate gradients $\hat{\delta}$ derived from general losses L or reward signals R to update synaptic weights at a given point in time. Note that teaching signals/rewards are often sparse. (**c**) Schematic of information used by synthesiser to learn in a BPTT setting (δ_{t+3} represents the future gradients). (**d**) Schematic of information used by synthesiser to learn to predict future losses δ from the current activity h. For biological simplicity we assume that the synthesiser has access to the learning signal directly, but in practice its likely to be a function of L.

D   INPUT EXPANSION AND SPARSE CONNECTIVITY IN CEREBELLUM-DNI

We also study the effects of input expansion and sparse connectivity from the main model to the synthesiser in our (s)CC-DNI model. Input expansion and sparse connectivity are two defining features of the cerebellum. Often human intelligence is linked to its expanded neocortex. However, the cerebellar/neocortical cell ratio in humans 4/1 and the cerebellum has significantly expanded throughout evolution (Barton and Venditti (2014); Herculano-Houzel (2010)). Here we aim to study the effect of this input expansion into the cerebellum by systematically varying the number of hidden units in the synthesiser relative to the number of units in the main network. We show this for both sensorimotor task: target reaching task (Fig. S3) and seq-MNIST tasks (Fig. S4 and S5) . In addition, it is known that one granule cell receives input from four mossy fibres on average. Mossy fibres form the main inputs to the cerebellum. The largest source of mossy fibres is the neocortex which projects inputs to the cerebellum via the pons. To quantify the effect of the sparse input connectivity we quantify next to the Pearson correlation also the population correlation coefficient for the target reaching task (Fig. S6) and the standard seq-MNIST task (Fig. S7).

E   TARGET REACHING SUPPLEMENTARY DATA

Here we show that the target reaching task results extrapolate to variants of the task with varied input-output combinations (Fig. S8). Furthermore, in line with Fig. 2b we include the learning curves across different truncation values for the three models (Fig. S9).

F   SEQMNIST SUPPLEMENTARY DATA

In line with Fig.3c, we include the learning curves across different truncation values T for the standard seqMNIST task as well as its variants (Figs. S10, S11).

G   IMAGE CAPTIONING SUPPLEMENTARY DATA

In line with Fig. 4, we include more examples of image-caption pairs (Fig. S12) as well as the learning curves and metric scores across different truncation values (Figs. S14, S15). Moreover, we demonstrate that DNI models for this task often generalise to unseen data better than regular LSTM models (Fig. S13).

Figure S3: (**a**) Learning curves for target reaching as in Fig. 2 over different divergence ratios M/N, where M is the number of hidden 'granular' units in cerebellar model, N the number of input units, and number of non-zero input connections K. LSTM performance (grey) shown along with fully (orange) and sparsely (cyan) connected CC-DNI models. Note that N is fixed here as $2 \times 10 = 20$ (10 LSTM units with gradients calculated for both cell and output states), hence * denotes full connectivity. The smaller x-axis in each subplot represents the epoch number and the smaller y-axis represents mean squared error. (**b**) Average performance over last five epochs (295-300) against divergence ratio M/N and input connection sparsity K for target reaching as in Fig. 2. (**c**) Same as (**a**) but for complex input (input dimension =28) and seven 2-D target coordinates (30 LSTM units with gradients calculated for both cell and output states). (**d**) Same as (**b**) for target reaching with complex input (input dimension = 28) and seven 2-D target coordinates over last 5 epochs (95-100).

Figure S4: Learning curves for all seqMNIST based tasks over different cerebellum divergence ratios M/N, where M is the number of hidden 'granular' units in cerebellar model, N the number of input units, and number of non-zero input connections K. LSTM performance (grey) shown as a reference along with fully (orange) and sparsely (cyan) connected cc-DNI models. Note that N is fixed here as $2 \times 30 = 60$ (30 LSTM units with gradients calculated for both cell and output states), hence * denotes full connectivity. The smaller x-axis in each subplot represents the epoch number and the y-axis represents performance over validation data (error for seqMNIST, MSE for the others).

Figure S5: Related to Fig. S4. Average performance over last five epochs (21-25) against divergence ratio M/N and input connection sparsity K for each seqMNIST based task. * denotes full connectivity. The divergence ratio and connectivity of the default LSTM, CC-DNI and sCC-DNI models used for the seqMNIST tasks (see Fig. 3) are illustrated by the grey, orange and cyan squares respectively.

Figure S6: Equivalent to Fig. 2f for population correlation r_{pop} (see equation **??**). (top) Effect of correlation of hidden (cortical) activity h on performance for cc-DNI (orange) and sCC-DNI (cyan) on the target reaching task, where population correlation and performance are recorded during the first and last (300) epoch respectively. (bottom) Evolution of the population correlation of the synthetic gradient $\hat{g}$ over the first hundred epochs.

Figure S7: Equivalent to Fig. 3d for population correlation r_{pop} (see equation **??**). (top) Effect of correlation of hidden (cortical) activity h on performance for cc-DNI (orange) and sCC-DNI (cyan) on the (standard) seqMNIST task, where population correlation and performance are recorded during the first and fifth epoch respectively. (bottom) Evolution of the population correlation of the synthetic gradient $\hat{g}$ over the first five epochs.

Figure S8: (**a, b**) Target reaching task as in Fig. 2 with varying number of targets. (**a**) Given a one-dimensional input the network has to learn to drive its output towards one of the 3 targets over 10 timesteps. For this variant divergence ratio for CC-DNI is $M/N = 4$ and $K = 4$ for sCC-DNI. (**b**) Given a one-dimensional input the network has to learn to drive its output towards one of the 9 targets over 10 timesteps. For this variant divergence ratio for CC-DNI is $M/N = 2$ and $K = 4$ for sCC-DNI. (**c, d**) Two variants on the target reaching task with varying input dimension, two-dimensional (i.e. $X = \{x_1, x_2\}$) and and 28-dimensional (Fig. S8d) (i.e. $X = \{x_1, ..., x_28\}$) input respectively. (**c**) Given a two-dimensional input the network has to learn to drive its output towards one of the 7 targets over 10 timesteps. For this variant divergence ratio for CC-DNI is $M/N = 4$ and $K = 4$ for sCC-DNI. (**d**) Given a 28-dimensional input the network has to learn to drive its output towards one of the 7 targets over 10 timesteps. For this variant divergence ratio for CC-DNI is $M/N = 4$ and $K = 4$ for sCC-DNI.

Figure S9: Learning curves for the target reaching task as in Fig. 2b across different truncation values T shown for the three models LSTM (grey), CC-DNI (orange) and sCC-DNI (cyan). Pararameters are the same as in Fig. 2b with divergence ratio $M/N = 4$ and sparse input connectivity $K = 4$ for sCC-DNI.

Figure S10: Learning curves for all seqMNIST based tasks across different truncation values. Model colours as in the main text (LSTM grey; CC-DNI orange; sCC-DNI cyan), with the default parameters of a $5/1$ divergence (300 GCs) in the DNI models and $K = 4$ for sCC-DNI.

Figure S11: Related to Fig. S10. Average performance over last five epochs (21-25) for c-seqMNIST, dd-seqMNIST, ld-seqMNIST tasks across truncation sizes for LSTM (grey), cc-DNI (orange), sCC-DNI (cyan). See Fig. 3c for (standard) seqMNIST.

Figure S12: Example images from the validation set with corresponding model captions (LSTM (grey); CC-DNI (orange); sCC-DNI (cyan)) and gold standard captions (black). Here we show a combination of examples of how the models describe the presented image. In some case all or some models fail to give an accurate description of the image. In other cases all models are able to an accurate caption describing the image, with each model displaying subtle differences in the generated captions.

Figure S13: Generalisation of CC-DNI (orange) and sCC-DNI (cyan) for truncation values T from 3 to 7. The change in loss is computed with reference to the LSTM (i.e. (s)CC-DNI - LSTM). Training loss is calculated *after* training (with dropout disabled) to enable fair comparison with final validation performance.

Figure S14: Validation learning curves in bits per word (BPW) for LSTM (grey), CC-DNI (orange) and sCC-DNI (cyan) across different truncation sizes T (see Fig. 4). BPW range restricted to enable comparison between truncation values; full curves are shown in inset. The surprising performance for $T = 10$ is likely due to how the sequence is divided into truncations. With a strong majority of (gold standard) caption lengths between 11-15 (mean ~ 13, the sequence will often be divided into two uneven truncations, perhaps making BPTT difficult for the LSTM. However, in the case of two truncations a synthetic gradient will only be required once (in between the two truncations) and is analogous to the "easier" job of a synthesiser predicting gradients for a feedforward network, explaining the particular relative improvement seen for the CC-DNI models in this case.

Figure S15: Evaluation of model-generated captions across truncation sizes for metrics (in order as shown) BLEU_1, BLEU_2, BLEU_3, BLEU_4, Rouge-L, METEOR, CIDEr, SPICE. The caption length *ratio* C_m/C_{gs}, where C_m is the length of the model-generated caption and C_{gs} is the length of the corresponding gold standard caption of closest length, is also shown.