LLM-grounded Diffusion: Enhancing Prompt Understanding of Text-to-Image Diffusion Models with Large Language Models

Abstract

Recent advancements in text-to-image diffusion models have yielded impressive results in generating realistic and diverse images. However, these models still struggle with complex prompts, such as those that involve numeracy and spatial reasoning. This work proposes to enhance prompt understanding capabilities in diffusion models. Our method leverages a pretrained large language model (LLM) for grounded generation in a novel two-stage process. In the first stage, the LLM generates a scene layout that comprises captioned bounding boxes from a given prompt describing the desired image. In the second stage, a novel controller guides an off-the-shelf diffusion model for layout-grounded image generation. Both stages utilize existing pretrained models without additional model parameter optimization. Our method significantly outperforms the base diffusion model and several strong baselines in accurately generating images according to prompts that require various capabilities, *doubling* the generation accuracy across four tasks on average. Furthermore, our method enables instruction-based multi-round scene specification and can handle prompts in languages not supported by the underlying diffusion model. We anticipate our method to unleash users' creativity by accurately following more complex prompts.[1]

Figure 1: **(a)** Stable Diffusion, even the latest SDXL (Podell et al., 2023), often struggles to accurately follow prompts that involve negation, numeracy, attribute binding, or spatial relationships. **(b)** Our method LMD achieves enhanced prompt understanding capabilities and accurately follows these types of prompts.

1 Introduction

The field of text-to-image generation has witnessed significant advancements, particularly with the emergence of diffusion models. These models have showcased remarkable capabilities in generating realistic and diverse images in response to textual prompts. However, despite the impressive results, diffusion models often struggle

---

[1]A video introducing this work is presented in the supplementary materials.

Figure 2: **Our proposed LMD enhances prompt understanding in text-to-image diffusion models through a novel two-stage generation process**: **1)** An LLM layout generator takes a prompt from the user and outputs an image layout in the form of captioned bounding boxes. **2)** A stable diffusion model guided by our layout-grounded controller generates the final image. Both stages utilize frozen pretrained models, which makes our method applicable to off-the-shelf LLMs and other diffusion models without grounding in their training objective.

Figure 3: **LMD is naturally able to perform instruction-based multi-round scene specification** and adapt subsequent rounds of generation according to users' followup instructions and clarifications.

to accurately follow complex prompts that require specific capabilities to understand. Fig. 1 shows that Stable Diffusion (Rombach et al., 2022), even the latest SDXL (Podell et al., 2023), often could not generate a certain number of objects or understand negation in the prompt. It also struggles with spatial reasoning or associating attributes correctly with objects.

One potential solution to address this issue is of course to gather a comprehensive multi-modal dataset comprising intricate captions and train a text-to-image diffusion model for enhanced prompt understanding. Nonetheless, this approach presents notable drawbacks. It requires considerable time and resources to curate a diverse and high-quality multi-modal dataset, not to mention the challenges associated with training or fine-tuning a diffusion model on such extensive data.

In contrast, we propose a novel *training-free* method that equips the diffusion model with an LLM that provides grounding for enhanced prompt understanding. Our method **LLM**-grounded **D**iffusion (LMD) consists of a two-stage generation process as shown in Fig. 2.

In the first stage of our method, we adapt an LLM to be a text-grounded layout generator through in-context learning. Given a prompt describing the desired image, the LLM generates scene layouts in the form of captioned bounding boxes, with a background caption and a negative prompt for what to avoid in generation.

In the second stage, we introduce a novel controller that guides an existing diffusion model without grounding in its training objective (e.g., Stable Diffusion) to follow the layout grounding generated in the first stage. In contrast to previous and concurrent works on region control (e.g., Bar-Tal et al. (2023); Chen et al. (2023); Xie et al. (2023)) that apply *semantic* control to certain spatial regions, our approach allows precise control over object *instances* in designated regions.

Notably, both stages utilize frozen pretrained models *off-the-shelf*, making our method applicable to LLMs and diffusion models trained independently *without any LLM or diffusion model parameter optimization.*

In addition to enhanced prompt understanding, our method also naturally enables instruction-based scene specification with multiple rounds of user requests (Fig. 3) and image generation from prompts in languages not supported by the base diffusion model (Fig. 13) without additional training.

Shown in Fig. 1, LMD provides a unified solution to several caveats in prompt understanding *at once* and enables accurate and high-quality image generation from complex prompts. We demonstrate that a diffusion model grounded with LLM-generated layouts outperforms its base diffusion model and several strong baselines, *doubling* the average generation accuracy across four tasks. **Our primary contributions include:**

1. We improve prompt understanding in text-to-image diffusion models by leveraging LLMs in a training-free two-stage generation process.

2. We introduce a novel controller that steers a diffusion model to generate images grounded on bounding box layouts from the LLM.

3. LMD enables instruction-based scene specification and allows broader language support for the input.

4. We propose a benchmark to assess the prompt-following ability of a text-to-image model and demonstrate the superior performance of LMD over several strong baselines.

We expect LMD to empower users with more precise control of text-to-image diffusion models. We will release our code and benchmark to facilitate future research and applications.

2 Related Work

Text-to-image diffusion models. High-quality image generation from textual descriptions with diffusion models has been popular recently (Ramesh et al., 2022; Saharia et al., 2022; Rombach et al., 2022; Podell et al., 2023). Despite the impressive visual quality, these models still tend to exhibit unsatisfactory performance when it comes to complex prompts that involve skills such as binding attributes to objects and spatial reasoning (Ramesh et al., 2022). We refer readers to Appendix A for a brief introduction to diffusion models.

LLMs for visual grounding. Many multi-modal models benefit from integrating LLMs for grounding vision models. BLIP-2 (Li et al., 2023a) bootstraps vision-language pre-training from a frozen image encoder and an LLM. Flamingo (Alayrac et al., 2022) tackles tasks such as few-shot visual question-answering and captioning tasks. Gupta et al. (2021) uses Transformer (Vaswani et al., 2017) for layout prediction but focuses on generating layouts for a limited closed set of object classes in the annotated training set. Wu et al. (2023) and Koh et al. (2023) also involve LLMs in conditional image generation. However, these methods still rely on CLIP text embeddings to convey the information to the diffusion model. Therefore, they often exhibit insufficient control compared to our method, which explicitly asks the LLM to reason about the spatial composition of different objects and poses direct spatial control. Concurrent to our work, LayoutGPT (Feng et al., 2023) proposes prompting an LLM for layout generation in a CSS structure. While LayoutGPT depends on a dataset annotated with boxes and captions to retrieve relevant in-context examples for the LLM, our method demonstrates that the ability for generating high-quality layouts is already present in pretrained LLM weights and can be prompted with a fixed set of in-context examples without external annotations.

Spatially-conditioned image generation creates images based on given priors such as poses, segmentation maps, strokes, and layouts. Prior to the popularity of diffusion models, SPADE (Park et al., 2019), BlobGAN (Epstein et al., 2022), and Layout2Im (Zhao et al., 2019) synthesize photorealistic images from a given layout. Xu et al. (2017); Johnson et al. (2018); Herzig et al. (2020) generate images with scene graphs. ControlNet (Zhang & Agrawala, 2023), SpaText (Avrahami et al., 2023), LayoutDiffuse (Cheng et al., 2023), LayoutDiffusion, (Zheng et al., 2023), GLIGEN (Li et al., 2023b) and ReCo (Yang et al., 2023) propose training-based adaptation on the diffusion models for spatially-conditioned image generation, with Li et al. (2023b) and Yang et al. (2023) supporting open-vocabulary labels for layout boxes. However, these methods *rely on annotated external datasets* such as COCO (Lin et al., 2014) to supply images with annotations such

Figure 4: **In stage 1, LMD generates an image layout from a user prompt.** LMD embeds the user prompt into a template with instructions and in-context examples. An LLM is then queried for completion. Finally, the LLM completion is parsed to obtain a set of captioned bounding boxes, a background caption, and an optional negative prompt.

as boxes and captions. Furthermore, training-based adaptation makes the model incompatible to add-ons such as LoRA weights (Hu et al., 2021) and renders it difficult to train a new LoRA model from a training set without box annotations. In contrast, we propose a training-free generation controller that steers *existing* text-to-image diffusion models that are *not specifically trained* for layout-grounded image generation and does *not* require external datasets. Furthermore, our method can also integrate with training-based methods for further improvements.

Very recently, Bar-Tal et al. (2023); Chen et al. (2023); Xie et al. (2023) allow training-free region control in image generation and share a similar task formulation to our layout-to-image stage. However, these works ground the image generation on the region *semantics* and pose little control over the number of object instances inside each semantic region, whereas our method focuses on grounding generation on *instances.*

Similar to our instruction-based scene specification, Brooks et al. (2023) recently proposed instruction-based image editing. Wu et al. (2023) and Gupta & Kembhavi (2023) also allow using external image editing models in an LLM-driven dialog. Different from these methods, we aim to edit the *scene layout* rather than the *image pixels*, which easily allows support for a greater set of instructions such as swapping/moving objects.

3 LLM-grounded Diffusion

In this section, we introduce our method **LLM**-grounded **D**iffusion (LMD). LMD focuses on the text-to-image generation setting: generate image x_0 given text prompt y, potentially by denoising from an initial latent noise z_T to z_0 and decoding to the pixel space. Our method generates an image in two stages: text-grounded layout generation (Section 3.1) and layout-grounded image generation (Section 3.2).

3.1 LLM-based Layout Generation

To generate the layout of an image, our method embeds the input text prompt y into a template and queries an LLM for completion (Fig. 4).

Layout representation of LMD comprises two components: **1)** a captioned bounding box for each foreground object, with coordinates specified in the *(x, y, width, height)* format, and **2)** a simple and concise caption describing the image background along with an optional negative prompt indicating what should not appear in a generated image. The negative prompt is empty when the layout does not impose restrictions on what should not appear.

Instructions. Our text instructions to the LLM consist of two parts:
1. Task specification:

> *Your task is to generate the bounding boxes for the objects mentioned in the caption, along with a background prompt describing the scene.*

2. Supporting details:

> *The images are of size 512x512... Each bounding box should be in the format of ... If needed, you can make reasonable guesses.*

(a) Step 1: per-box masked latent generation

(b) Step 2: overall image generation with masked latents as priors

Figure 5: **In stage 2, we introduce a novel layout-grounded controller that guides stable diffusion to generate images based on the layout obtained from the previous stage.** Our layout-grounded image generation process consists of two steps: **(a)** generating masked latents for each box specified in the layout, with attention control ensuring that the object is placed in the designated box; and **(b)** composing the masked latents as priors to guide the image generation to adhere to the specified layout.

In-context learning. Similar to Brooks et al. (2023), we provide the LLM with manually curated examples after the task description. Through these examples, we clarify the layout representation and provide preferences to disperse ambiguity. An example is shown as follows:

> *Caption: A watercolor painting of a wooden table in the living room with an apple on it*
> *Objects: [('a wooden table', [65, 243, 344, 206]), ('an apple', [206, 306, 81, 69])]*
> *Background prompt: A watercolor painting of a living room*
> *Negative prompt:*

To ensure precise layout control, we adhere to two key principles in our example design: **1)** Each object instance is represented by a single bounding box. For instance, if the prompt mentions four apples, we include four boxes with "an apple" in each caption. **2)** We leave no foreground objects specified in the boxes to the background caption to ensure all foreground objects are controlled by our layout-grounded image generator (Section 3.2). These principles allow for accurate and instance-controlled layout generation.

LLM completion. After providing the in-context examples, we query the LLM for completion:

> *Caption: [input prompt from the user]*
> *Objects: [start of LLM completion]*

The resulting layout from the LLM completion is then parsed and used for the subsequent image generation process. We refer readers to the Appendix H for our complete prompt.

3.2 Layout-grounded Stable Diffusion

In this stage, we introduce a controller to ground the image generation on the LLM-generated layout. While previous training-free region control methods (Bar-Tal et al., 2023; Chen et al., 2023; Xie et al., 2023) apply *semantic* guidance through regional latent denoising or attention manipulation, these methods lack the ability to control the number of objects within a semantic region. This limitation arises as the different instances are often indistinguishable in either the latent space or the attention map, hindering instance-level control.

In contrast, LMD enables *instance*-level grounding by first generating masked latents for each individual bounding box and then composing the masked latents as priors to guide the overall image generation. This allows for precise placement and attribute binding for each object instance.

Per-box masked latents. While diffusion models lack inherent instance-level distinction in their latent space or attention maps for fine-grained control, we observe that they are often able to generate images with one specified instance. Hence, we process one foreground box at a time for instance-level grounding.

As depicted in Fig. 5(a), for each foreground object i, we first generate an image with a single instance by denoising from $\mathbf{z}_T^{(i)}$ to $\mathbf{z}_0^{(i)}$, where we use *"[background prompt] with [box caption]"* (e.g., *"a realistic image of an indoor scene with a gray cat"*) as the denoising prompt. The initial noise latent is shared for all boxes to ensure globally coherent viewpoint, style, and lighting (i.e., $\mathbf{z}_T^{(i)} = \mathbf{z}_T, \forall\, i$).

To ensure the object aligns with the bounding box, we manipulate the cross-attention maps $\mathbf{A}^{(i)}$ of the noise-prediction network.[2] Each map describes the affinity from pixels to text tokens:
$$\mathbf{A}_{uv}^{(i)} = \mathsf{Softmax}(\mathbf{q}_u^T \mathbf{k}_v) \tag{1}$$
where $\mathbf{q}_u$ and $\mathbf{k}_v$ are linearly transformed image feature at spatial location u and text feature at token index v in the prompt, respectively.

Following Chen et al. (2023); Xie et al. (2023), we strengthen the cross-attention from pixels inside the box to tokens associated with the box caption while attenuating the cross-attention from pixels outside the box. To achieve this, we define a simple energy function:
$$E(\mathbf{A}^{(i)}, i, v) = -\mathsf{Topk}_u(\mathbf{A}_{uv} \cdot \mathbf{m}_i) + \tag{2}$$
$$\omega \mathsf{Topk}_u(\mathbf{A}_{uv} \cdot (1 - \mathbf{m}_i)) \tag{3}$$
where $\cdot$ is element-wise multiplication, $\mathbf{m}_i$ is a binary mask of the box i with the region in the box set to 1, Topk_u takes the average of top-k values across the spatial dimension u, and $\omega = 4.0$. The energy function is minimized by updating the latent before each denoising step:
$$\mathbf{z}_t^{(i)} \leftarrow \mathbf{z}_t^{(i)} - \eta \nabla_{\mathbf{z}_t^{(i)}} \sum_{v \in V_i} E(\mathbf{A}^{(i)}, i, v) \tag{4}$$
$$\mathbf{z}_{t-1}^{(i)} \leftarrow \mathsf{Denoise}(\mathbf{z}_t^{(i)}) \tag{5}$$
where η is the guidance strength hyperparam, and the set V_i contains the token indices for the box caption in the prompt for box i.

After generation, we obtain the cross-attention map that corresponds to the box caption, which serves as a saliency mask for the object. We optionally use SAM (Kirillov et al., 2023) to refine the quality of the mask. This can be done by querying either with the pixel location that has the highest saliency or with the layout box. With mask $m^{(i)}$ for exactly one foreground instance, we perform element-wise multiplication between the mask and the latent at each denoising step to create a sequence of *masked* instance latents $(\hat{\mathbf{z}}_t^{(i)})_{t=0}^T$:
$$\hat{\mathbf{z}}_t^{(i)} = \mathbf{z}_t^{(i)} \otimes m^{(i)} \tag{6}$$

Masked latents as priors for instance-level control. The masked instance latents $(\hat{\mathbf{z}}_t^{(i)})_{t=0}^T$ are then leveraged to provide instance-level hints to the diffusion model for the overall image generation. As illustrated in Fig. 5(b), during each denoising time step $rT \leq t \leq T$ in the early denoising process[3], we place each masked foreground latents $\hat{\mathbf{z}}_t^{(i)}$ onto the composed latents $\mathbf{z}_t^{(\mathrm{comp})}$:
$$\mathbf{z}_t^{(\mathrm{comp})} \leftarrow \mathsf{Compose}(\mathbf{z}_t^{(\mathrm{comp})}, \hat{\mathbf{z}}_t^{(i)}) \quad \forall i \tag{7}$$

---

[2]The cross-attention layer index is omitted for simplicity. We sum the energy values for all selected layers during optimization.
[3]In the notation of this work, the denoising process starts from time step T to step 0.

Figure 6: **LMD and LMD+ support instruction-based scene specification, empowering the users to add/move/remove objects, modify object attributes, and clarify the prompt in multiple rounds of dialog. (a)**: the initial prompt for the scene; **(b)-(i)**: eight subsequent instructions that *sequentially* modify the scene. By separating the generation of each foreground object as well as the background, LMD ensures consistent image generation when the same seed is used for image generation throughout the dialog.

Figure 7: LMD outperforms its base text-to-image diffusion model Podell et al. (2023) in accurately following the prompts that require spatial and language reasoning. Best viewed when zoomed in.

where $\mathbf{z}_T^{(\text{comp})}$ is initialized from $\mathbf{z}_T$ for foreground generation for consistency.

Since diffusion models tend to generate the object placement in the initial denoising steps and then object details in later steps (Bar-Tal et al., 2023), we only compose the latents from timestep T to rT, where $r \in [0, 1]$ balances instance control and image coherency. By primarily intervening during the steps for object placement, our method merely provides instance-level layout hints rather than forcing each masked region of the resulting generation to look the same as the per-box generation.

To make our guidance more robust, we further transfer the cross-attention maps from per-box generation to the corresponding regions in the composed generation by adapting the energy function:

$$E^{(\text{comp})}(\mathbf{A}^{(\text{comp})}, \mathbf{A}^{(i)}, i, v) = E(\mathbf{A}^{(\text{comp})}, i, v) + \lambda \sum_{u \in V_i} \left| \mathbf{A}_{uv}^{(\text{comp})} - \mathbf{A}_{uv}^{(i)} \right| \tag{8}$$

where $\lambda = 2.0$ and the energy value of each box i is summed up for optimization.

In this way, our controller conditions the diffusion model to generate one instance at each masked location, with the final generation natural and coherent in terms of foreground-background composition.

Finally, we decode latents $\mathbf{z}_0^{(\text{comp})}$ to pixels $\mathbf{x}_0$ via the diffusion image decoder. We refer readers to Appendix B for the overall pseudo-code for layout grounding.

Integration with training-based methods. Our training-free controller can also be applied on top of training-based methods such as GLIGEN (Li et al., 2023b) to leverage instance-annotated external datasets when available. Since GLIGEN trains adapter layers taking box inputs, the integration with GLIGEN, denoted as LMD+, involves adopting its adapter weights and passing the layout guidance to the adapter layers. Note that LMD+ uses adapters along with the instance-level guidance introduced above, which greatly surpasses only using GLIGEN adapters, as shown in Table 2. We achieve further enhanced instance and attribute control without additional training through this integration.

3.3 Additional Capabilities of LMD

Our LLM-grounded generation pipeline allows for two additional capabilities without additional training.

Instruction-based scene specification. Leveraging an LLM that supports multi-round dialog (e.g., GPT-3.5/4), LMD empowers the users to specify the desired image with multiple instructions following an initial prompt (Fig. 3). Specifically, after the initial image generation, a user can simply give clarifications or additional requests to the LLM. With the updated layout from the LLM, we can leverage LMD again to generate images with the updated layout. Since we edit the layout rather than the raw image, our generation remains consistent after multiple rounds of requests and can handle requests such as swapping objects that were unachievable through previous instruction-based image editing method Brooks et al. (2023), as demonstrated in Fig. 6. This capability applies to both LMD and LMD+.

Supporting more languages. By giving an in-content example of a non-English user prompt and an English layout output[4], the LLM layout generator accepts non-English user prompts and outputs layouts with English captions. This allows generation from prompts in languages not supported by the underlying diffusion model *without additional training* (Fig. 13). We refer readers to Appendix G for additional details.

4 Evaluation

4.1 Qualitative Comparison

Setup. We qualitatively compare our approach with Stable Diffusion (SD, Rombach et al. (2022); Podell et al. (2023)). SD family is also chosen as our underlying base model for layout-grounded image generation given its strong capabilities and widespread adoption in text-to-image generation research. Thanks to the training-free nature of our work, our method is applicable to various diffusion models without additional training. Therefore, for Fig. 1, 7, and 9, we use the largest Stable Diffusion model SDXL as the base model of LMD and compare against SDXL as a strong baseline (see Appendix E for details). For all other settings, we use Stable Diffusion v1.5 as the base model unless stated otherwise. We use `gpt-4` (OpenAI, 2023) for layout generation for all qualitative comparisons. **Results.** In Fig. 1 and 7, we observe that our two-stage text-to-image generation approach greatly enhances prompt following ability compared to our base model by generating images that align with the layouts from the LLM.

Comparing with other LLM-based image generators. VisualChatGPT (Wu et al., 2023) and GILL (Koh et al., 2023) also leverage LLMs as a part of the image generation pipelines. Both works leverage SD as the underlying image generation model. VisualChatGPT treats SD as a module that can be used by the LLM and passes text caption to it, and GILL outputs a embedding in place of the text embedding for SD. Since both methods utilize LLMs to only provide conditions to SD in the form of text embeddings, these methods still inherit the problems of insufficient control of text embeddings from the base SD model. In contrast, our method asks the LLM to explicitly reason about the spatial relationships and applies direct spatial control on our underlying diffusion model, thereby bypassing the bottleneck of the text embedding representation that does not accurately convey spatial information. As shown in Fig. 8, both methods cannot accurately follow text prompts of several categories that our method is able to correctly generate in Fig. 1 and Fig. 10. Furthermore, although the involvement of LLM in VisualChatGPT and GILL also potentially allows multi-round instruction-based scene specification (Section 3.3), we empirically observe that the generated images quickly deviate from the scene of "a wooden table" starting from the second iteration in Fig. 11, with the final generation being incomprehensible.

4.2 Quantitative evaluation

4.2.1 Proposed benchmark

We propose a text-to-image evaluation benchmark that includes four tasks: negation, generative numeracy, attribute binding, and spatial reasoning. Negation and generative numeracy involve generating a specific

---

[4]We simply translate the example prompt input in our last example to the desired language, while keeping its layout in English.

Figure 8: We qualitatively compare with VisualChatGPT (Wu et al., 2023) and GILL (Koh et al., 2023) that also leverage LLMs in the image generation pipelines. **Both baselines lack the ability to accurately follow the prompts for three out of four tasks that our method can solve in Fig. 1 and 10.**

Tasks	Accuracy		
	SD	**LMD**	**LMD+**
Negation	28%	**100% (3.6×)**	**100% (3.6×)**
Generative Numeracy	39%	**62% (1.6×)**	**86% (2.2×)**
Attribute Binding	52%	**65% (1.3×)**	**69% (1.3×)**
Spatial Relationships	28%	**79% (2.8×)**	**67% (2.4×)**
Average	37%	**77% (2.1×)**	**81% (2.2×)**

Table 1: With guidance from the LLM-based layout generator and our novel layout-grounded controller, **our LMD significantly outperforms the Stable Diffusion model (SD) that we use under the hood in four tasks benchmarking prompt-following abilities.** LMD denotes our method directly applied on SD. LMD+ denotes additionally integrating pretrained GLIGEN (Li et al., 2023b) adapters into our controller.

number of objects or not generating specific objects. Attribute binding involves assigning the right attribute to the right object with multiple objects in the prompt. Spatial reasoning involves understanding words that describe the relative locations of objects. For each task, we programmatically compose 100 prompts and query each model for text-to-image generation, with 400 prompts in total. `gpt-3.5-turbo` (Brown et al., 2020) is used in LMD for the benchmarks. We also implemented LMD+, a LMD variant that integrate pretrained GLIGEN (Li et al., 2023b) adapters into our controller without further training. We refer readers to appendix for details.

Detection-based evaluation. We use an open-vocabulary object detector, OWL-ViT (Minderer et al., 2022), to obtain bounding boxes for the objects of interest. We then check whether each generated image satisfies the requirements in the prompt. The accuracy of each task is computed by calculating the proportion of the image generations that match the prompt over all generations.

Results. As presented in Table 1, our model shows significant improvements in generation accuracy, ranging from 1.3× to 3.6× compared to SD across four tasks and *doubling* the accuracy on average. Notably, LMD achieves image generation accuracy that is *more than twice* of the SD accuracy for the spatial relationships and the negation task. This highlights the utility of the grounding image generation on the LLM layout generator. Furthermore, when additionally integrating GLIGEN to our pipeline to leverage in-domain instance-annotated data, our method, denoted as LMD+, achieves additional improvements.

4.2.2 T2I-CompBench

In addition to our proposed benchmark with detection-based evaluation, we evaluate our method on T2I-CompBench (Huang et al., 2023) that additionally uses visual question answering (VQA) models for generation

Stage 1/Stage 2	Accuracy				
	Negation	Numeracy	Attribute	Spatial	Average
Training-free methods:					
LMD/MultiDiffusion (Bar-Tal et al., 2023)	**100%**	30%	42%	36%	52.0%
LMD/Backward Guidance (Chen et al., 2023)	**100%**	42%	36%	61%	59.8%
LMD/BoxDiff (Xie et al., 2023)	**100%**	32%	55%	62%	62.3%
LMD/LMD (Ours)	**100%**	**62%**	**65%**	**79%**	**76.5%** (+ 14.2)
Training-based methods:					
LMD/GLIGEN (Li et al., 2023b)	**100%**	57%	57%	45%	64.8%
LMD/LMD+ (Ours)	**100%**	**86%**	**69%**	**67%**	**80.5%** (+ 15.7)
LMD/LMD+ (Ours, GPT-4)	**100%**	**84%**	**79%**	**82%**	**86.3%** (+ 21.5)
Evaluating generated layouts only (upper bound for image generation):					
LMD/-	100%	97%	100%	99%	99.0%

Table 2: **Our LLM layout generator (stage 1) is compatible with other layout-to-image methods as stage 2, although our proposed layout-grounded controller performs the best among them.** Our controller could also be applied on top of training-based GLIGEN (Li et al., 2023b), denoted as LMD+, for additional improvements. Finally, the LLM-generated layouts almost always align with the prompt, highlighting that the bottleneck is the layout-grounded image generation. The scores for negation task are high because we pass the negative prompts generated by the LLM to the underlying diffusion model, which does not depend on the stage 2 implementation.

Method	Image Accuracy
	Average of 4 tasks
SD v1.5 (Default)	37%
LMD (on SDv1.5) (**Ours**, default)	**77%** (2.1×)
SD v2.1	38%
LMD (on SDv2.1) (**Ours**)	**77%** (2.0×)

Table 3: **LMD achieves comparable gains when adapted to Stable Diffusion v2.1 without any hyperparam tuning or model training.** This shows a promising signal that the gains from our method could carry along with the enhancement of diffusion models. The performance of our method could potentially be improved further with additional hyperparam tuning.

Method	Image Accuracy
	Average of 4 tasks
LMD (w/o SAM)	72.8%
LMD (with SAM)	**76.5%**
LMD+ (w/o SAM)	**82.8%**
LMD+ (with SAM)	80.5%

Table 4: **Ablations on using SAM vs using simple attention thresholding in stage 2.** While removing SAM leads to a slight degradation in LMD, removing SAM leads to even better performance in LMD+.

Stage 1 Model	Layout (Image) Accuracy
	Average of 4 tasks
StableBeluga2	96.5% (67.0%)
gpt-3.5-turbo	99.0% (80.5%)
gpt-4	**100.0%** **(86.3%)**

Table 5: **Ablations on different LLMs in stage 1.** Although proprietary models such as GPT-3.5 and GPT-4 perform the best, the ability to generate high-quality layouts is also present in open-source models Mahan et al. (2023); Touvron et al. (2023). The image accuracy is benchmarked using LMD+ as stage 2.

Stage 1 Model	Layout Accuracy
	Average of 4 tasks
StableBeluga-7B	59.3%
StableBeluga-13B	84.0%
StableBeluga2 (70B)	**96.5%**

Table 6: **Ablations on the LLM model size on StableBeluga Models (Mahan et al., 2023) based on Llama-2 (Touvron et al., 2023) for layout generation (stage 1 only).** Larger LLMs offer more accurate layout generation compared to smaller LLMs.

	Layout Accuracy (4 tasks)	
# shots	gpt-3.5-turbo	gpt-4
1 Shot	89.8%	**100.0%**
4 Shots	96.3%	**100.0%**
7 Shots	**99.0%**	**100.0%**

	Color	Shape	Texture	Spatial
SDv1	0.3765	0.3576	0.4156	0.1246
LMD (on SDv1)	**0.5495**	**0.5462**	**0.5241**	**0.2570**
SDv2	0.5065	0.4221	0.4922	0.1342
LMD (on SDv2)	**0.5736**	**0.5334**	**0.5227**	**0.2704**

Table 7: **Ablations on the number of in-context examples ("shots") given to the LLM.** While GPT-3.5 benefits from more in-context examples, GPT-4 already excels in layout generation even with only one example.

Table 8: **Our method surpasses the base diffusion models SDv1 and SDv2 on T2I-CompBench (Huang et al., 2023) on all four tasks without additional training.**

evaluation. The color, shape, and texture tasks employ BLIP (Li et al., 2022) in a VQA setting, while the spatial task uses UniDet (Zhou et al., 2022) for evaluation. As shown in Table 8, our method LMD, when applied on either SDv1 or SDv2, improves the performance on all four tasks.

4.2.3 Evaluator-based Assessment

Setting. We also evaluate the prompt following ability and the naturalness of the generated images with our base image generation method. We randomly selected 10 text prompts from our proposed benchmark and generated a pair of images per text prompt, one with our LMD+ and one with the base model SD. We then invited 11 evaluators to compare each image pair and answer two questions:

1. Question 1: Which image aligns better with the text prompt?
2. Question 2: Which image has a more natural and coherent foreground-background composition?

In addition to an option for preferring each image, a "similar" option is also provided for each pair.

Results. We average the scores across the image pairs and evaluators. The results show that our method got **88.18%** (vs 10.90% for SD) for the first question and **35.45%** (vs 31.81% for SD) for the second question. This indicates that our method generates images that accurately align with the prompt compared to the baseline SD without degradation of naturalness or coherency.

4.3 Ablation Study

Layout-to-image stage. *Comparing with other layout-to-image methods.* As shown in Table 2, compared with training-free *semantic* control methods, our proposed layout-grounded controller provides much better *instance*-level grounding, justified by the fact that our training-free controller even *surpasses training-based method* GLIGEN (Li et al., 2023b) in the generative numeracy task, despite not trained with any instance-level annotation. Furthermore, our controller also sigficantly surpasses training-based method GLIGEN (Li et al., 2023b) in attribute binding and spatial reasoning task. When integrated with GLIGEN to leverage instance-annotated datasets, our integration, denoted as LMD+, allows for further improvements without the need for additional training. *Switching the base diffusion model without hyperparam tuning.* As shown in Table 3, thanks to our training-free nature, LMD maintains the gains to the base model (around $2\times$ performance boost) when we switch the base diffusion model from SDv1.5 to SDv2.1 *without hyperparam tuning.* This showcases the potential of integrating LMD with future diffusion models. *Using SAM vs a simple attention threshold to obtain the per-box mask.* Instead of using SAM to obtain the mask for each box, we also explored an approach that does not require an additional segmentation module. Alternatively, we sort the pixels in each box according to their attention value with respect to the box caption and pick the top 75% pixels in each box with the highest attention as the mask for the box. As shown in Table 4, the impact of SAM is different for LMD/LMD+. In LMD, since the attention-based guidance is less spatially accurate with respect to the layout boxes, SAM helps to obtain the right mask that covers the object. Therefore, removing SAM leads to a slight degradation in LMD. In LMD+, since the guidance is more spatially accurate, SAM is no longer necessary most of the time. Instead, SAM sometimes picks a region that includes the background, causing confusion and reduced performance. Therefore, removing

(a) Stable Diffusion XL (b) Our Layout (c) Our Generation (d) Round 2 Layout (e) Round 2 Generation

Figure 9: **A failure case** occurs when our method, shown in **(c)**, generates objects in unintentional viewpoints and sizes due to the ambiguity in the generated layout. The LLM-generated layout **(b)** is suitable for close-up top-down view of a small table, but the layout-to-image model assumes a side view and thus fails to generate a feasible image that fits the layout. Nevertheless, our method still provides more interpretability through the intermediate layout **(b)** compared to baseline SDXL **(a)**. With an additional request for the side view and correct object sizes, the LLM adjusted the scene accordingly in **(d)** and the final generation in the second round **(e)** is aligned with the input text prompt.

SAM leads to comparable or even slightly better results in LMD+. We make SAM an optional choice (as described in Fig. 2) but still recommend it for LMD and enable it by default.

Text-to-layout stage. *Varying the LLM types.* All LLMs in Table 5 generate layouts that almost perfectly follow the requirements in the prompts, indicating the bottleneck to be the layout-to-image stage. `gpt-4` shows improved results in layout and the subsequent image generation, compared to `gpt-3.5-turbo`. The capability to generate high-quality layouts are *not limited to proprietary LLMs*, with Llama2-based `StableBeluga2` (Mahan et al., 2023; Touvron et al., 2023; Mukherjee et al., 2023) also able to perform text-to-layout generation in the stage 1. *Varying the LLM sizes.* We also tested the ability of layout generation on LLMs of different model sizes. As shown in Table 6, larger LLMs offer much better layout generation capabilities. *Varying the number of in-context examples.* In addition to using the seven fixed in-context examples provided in Table 10 by default, we also vary the number of in-context examples given to the LLM (i.e., "shots"). We show in Table 7 that while GPT-3.5 benefits from more in-context examples, GPT-4 is able to successfully generate all the layouts even when given only one in-context example. Note that we also observe GPT-4 to still be able to generate layouts *without any in-context examples* (i.e., given only the text instructions). However, since no examples are offered as references in this zero-shot setting, the format of LLM outputs are observed to different in different runs, making it hard to parse with a program. Since it is much easier to convey the format through an example than through language instructions, we recommend having at least one example. Our observation shows that LLMs *already learn the ability to generate object boxes during pretraining* and do not need us to convey through many in-context examples.

5 Limitations

Since we use models off-the-shelf, the LLM may generate a layout that is ambiguous to the diffusion model. For example, the generated layout in Fig. 9(b) is feasible for a top-down close-up image, but the diffusion model generates an image viewing from the side. This makes the apples not on the table in Fig. 9(c). Prompting or fine-tuning the LLM to be more explicit about its assumptions in the layouts, such as the viewpoints, may alleviate this problem. Thanks to the two-stage generation process, the intermediate layout allows for more interpretability compared to our base model stable diffusion. After diagnosing the point of failure, we give an additional request for the side view and correct object sizes to the LLM. The LLM adjusted the subsequent layout generation, which allows generating images that align with the input prompt in round 2, as shown in Fig. 9(d,e). Our method also inherits biases from the base diffusion model (Luccioni et al., 2023).

6 Summary

In this paper, we enhance the prompt understanding capabilities of text-to-image diffusion models. We present a novel training-free two-stage generation process that incorporates LLM-based text-grounded layout generation and layout-grounded image generation. Our method also enables instruction-based scene specification and generation from prompts in languages unsupported by the base diffusion model. Our method outperforms strong baselines in accurately following the prompts in text-to-image generation.

References

Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *Advances in Neural Information Processing Systems*, 35:23716–23736, 2022.

Omri Avrahami, Thomas Hayes, Oran Gafni, Sonal Gupta, Yaniv Taigman, Devi Parikh, Dani Lischinski, Ohad Fried, and Xi Yin. Spatext: Spatio-textual representation for controllable image generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 18370–18380, 2023.

Omer Bar-Tal, Lior Yariv, Yaron Lipman, and Tali Dekel. Multidiffusion: Fusing diffusion paths for controlled image generation. *arXiv preprint arXiv:2302.08113*, 2, 2023.

Tim Brooks, Aleksander Holynski, and Alexei A Efros. Instructpix2pix: Learning to follow image editing instructions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 18392–18402, 2023.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Minghao Chen, Iro Laina, and Andrea Vedaldi. Training-free layout control with cross-attention guidance. *arXiv preprint arXiv:2304.03373*, 2023.

Jiaxin Cheng, Xiao Liang, Xingjian Shi, Tong He, Tianjun Xiao, and Mu Li. Layoutdiffuse: Adapting foundational diffusion models for layout-to-image generation. *arXiv preprint arXiv:2302.08908*, 2023.

Prafulla Dhariwal and Alexander Nichol. Diffusion models beat gans on image synthesis. *Advances in Neural Information Processing Systems*, 34:8780–8794, 2021.

Dave Epstein, Taesung Park, Richard Zhang, Eli Shechtman, and Alexei A Efros. Blobgan: Spatially disentangled scene representations. In *Computer Vision–ECCV 2022: 17th European Conference, Tel Aviv, Israel, October 23–27, 2022, Proceedings, Part XV*, pp. 616–635. Springer, 2022.

Weixi Feng, Wanrong Zhu, Tsu-jui Fu, Varun Jampani, Arjun Akula, Xuehai He, Sugato Basu, Xin Eric Wang, and William Yang Wang. Layoutgpt: Compositional visual planning and generation with large language models. *arXiv preprint arXiv:2305.15393*, 2023.

Kamal Gupta, Justin Lazarow, Alessandro Achille, Larry S Davis, Vijay Mahadevan, and Abhinav Shrivastava. Layouttransformer: Layout generation and completion with self-attention. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1004–1014, 2021.

Tanmay Gupta and Aniruddha Kembhavi. Visual programming: Compositional visual reasoning without training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14953–14962, 2023.

Roei Herzig, Amir Bar, Huijuan Xu, Gal Chechik, Trevor Darrell, and Amir Globerson. Learning canonical representations for scene graph to image generation. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XXVI 16*, pp. 210–227. Springer, 2020.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

Kaiyi Huang, Kaiyue Sun, Enze Xie, Zhenguo Li, and Xihui Liu. T2i-compbench: A comprehensive benchmark for open-world compositional text-to-image generation. *arXiv preprint arXiv:2307.06350*, 2023.

Justin Johnson, Agrim Gupta, and Li Fei-Fei. Image generation from scene graphs. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1219–1228, 2018.

Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C. Berg, Wan-Yen Lo, Piotr Dollár, and Ross Girshick. Segment anything. *arXiv:2304.02643*, 2023.

Jing Yu Koh, Daniel Fried, and Ruslan Salakhutdinov. Generating images with multimodal language models. *arXiv preprint arXiv:2305.17216*, 2023.

Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. Blip: Bootstrapping language-image pre-training for unified vision-language understanding and generation. In *International Conference on Machine Learning*, pp. 12888–12900. PMLR, 2022.

Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. *arXiv preprint arXiv:2301.12597*, 2023a.

Yuheng Li, Haotian Liu, Qingyang Wu, Fangzhou Mu, Jianwei Yang, Jianfeng Gao, Chunyuan Li, and Yong Jae Lee. Gligen: Open-set grounded text-to-image generation. *arXiv preprint arXiv:2301.07093*, 2023b.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *Computer Vision–ECCV 2014: 13th European Conference, Zurich, Switzerland, September 6-12, 2014, Proceedings, Part V 13*, pp. 740–755. Springer, 2014.

Alexandra Sasha Luccioni, Christopher Akiki, Margaret Mitchell, and Yacine Jernite. Stable bias: Analyzing societal representations in diffusion models. *arXiv preprint arXiv:2303.11408*, 2023.

Calvin Luo. Understanding diffusion models: A unified perspective. *arXiv preprint arXiv:2208.11970*, 2022.

Dakota Mahan, Ryan Carlow, Louis Castricato, Nathan Cooper, and Christian Laforte. Stable beluga models, 2023. URL https://huggingface.co/stabilityai/StableBeluga2.

Matthias Minderer, Alexey Gritsenko, Austin Stone, Maxim Neumann, Dirk Weissenborn, Alexey Dosovitskiy, Aravindh Mahendran, Anurag Arnab, Mostafa Dehghani, Zhuoran Shen, et al. Simple open-vocabulary object detection with vision transformers. *arXiv preprint arXiv:2205.06230*, 2022.

Ron Mokady, Amir Hertz, Kfir Aberman, Yael Pritch, and Daniel Cohen-Or. Null-text inversion for editing real images using guided diffusion models. *arXiv preprint arXiv:2211.09794*, 2022.

Subhabrata Mukherjee, Arindam Mitra, Ganesh Jawahar, Sahaj Agarwal, Hamid Palangi, and Ahmed Awadallah. Orca: Progressive learning from complex explanation traces of gpt-4, 2023.

OpenAI. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

Taesung Park, Ming-Yu Liu, Ting-Chun Wang, and Jun-Yan Zhu. Semantic image synthesis with spatially-adaptive normalization. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 2337–2346, 2019.

Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. Sdxl: improving latent diffusion models for high-resolution image synthesis. *arXiv preprint arXiv:2307.01952*, 2023.

Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10684–10695, 2022.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *Medical Image Computing and Computer-Assisted Intervention–MICCAI 2015: 18th International Conference, Munich, Germany, October 5-9, 2015, Proceedings, Part III 18*, pp. 234–241. Springer, 2015.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L Denton, Kamyar Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, et al. Photorealistic text-to-image diffusion models with deep language understanding. *Advances in Neural Information Processing Systems*, 35: 36479–36494, 2022.

Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. *arXiv preprint arXiv:2010.02502*, 2020.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Chenfei Wu, Shengming Yin, Weizhen Qi, Xiaodong Wang, Zecheng Tang, and Nan Duan. Visual chatgpt: Talking, drawing and editing with visual foundation models. *arXiv preprint arXiv:2303.04671*, 2023.

Jinheng Xie, Yuexiang Li, Yawen Huang, Haozhe Liu, Wentian Zhang, Yefeng Zheng, and Mike Zheng Shou. Boxdiff: Text-to-image synthesis with training-free box-constrained diffusion. *arXiv preprint arXiv:2307.10816*, 2023.

Danfei Xu, Yuke Zhu, Christopher B Choy, and Li Fei-Fei. Scene graph generation by iterative message passing. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5410–5419, 2017.

Zhengyuan Yang, Jianfeng Wang, Zhe Gan, Linjie Li, Kevin Lin, Chenfei Wu, Nan Duan, Zicheng Liu, Ce Liu, Michael Zeng, et al. Reco: Region-controlled text-to-image generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14246–14255, 2023.

Lvmin Zhang and Maneesh Agrawala. Adding conditional control to text-to-image diffusion models. *arXiv preprint arXiv:2302.05543*, 2023.

Bo Zhao, Lili Meng, Weidong Yin, and Leonid Sigal. Image generation from layout. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8584–8593, 2019.

Guangcong Zheng, Xianpan Zhou, Xuewei Li, Zhongang Qi, Ying Shan, and Xi Li. Layoutdiffusion: Controllable diffusion model for layout-to-image generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 22490–22499, 2023.

Xingyi Zhou, Vladlen Koltun, and Philipp Krähenbühl. Simple multi-dataset detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7571–7580, 2022.

A   Preliminary introduction on diffusion models

Diffusion models are a class of powerful generative models that learn the data distribution of complex datasets. During the forward process, noise is added to an image to the input data $\mathbf{x}_0$ for T steps, until the resulting vector $\mathbf{x}_T$ is almost distributed according to a standard Gaussian distribution. In the reverse process, a diffusion model iteratively subtracts a predicted noise vector from $\mathbf{x}_T$ to transform it into a sample that resembles the real data in the training dataset. The reverse process is often referred to as "denoising". We refer readers to Luo (2022) for a more in-depth introduction to diffusion models.

DDPM. Ho et al. (2020). The denoising process of denoising diffusion probabilistic models starts with the initial noise vector sampled from a standard Gaussian noise vector $\mathbf{x}_T \sim \mathcal{N}(0, \mathbf{I})$. During training, a neural network with parameter θ learns to predict the added noise for the forward process by minimizing the training objective:

$$\mathcal{L} = ||\boldsymbol{\epsilon} - \boldsymbol{\epsilon}_{\theta(\mathbf{x}_t, t)}||^2 \tag{9}$$

At inference time, for each of the T denoising steps, DDPM predicts the noise $\boldsymbol{\epsilon}$ and then obtains $\mathbf{x}_{t-1}$ from $\mathbf{x}_t$:

$$\mathbf{x}_{t-1} = \frac{1}{\sqrt{\alpha_t}}\Big(\mathbf{x}_t - \frac{1-\alpha_t}{\sqrt{1-\prod_{i=1}^t \alpha_i}}\boldsymbol{\epsilon}_\theta(\mathbf{x}_t, t)\Big) + \sigma_t \mathbf{z} \tag{10}$$

where $\mathbf{z} \sim \mathcal{N}(0, \mathbf{I})$, α_t and σ_t are parameterized by a variance schedule $\{\beta_t \in (0, 1)\}_{t=1}^T$ that controls the size of the denoising step.

DDIM Song et al. (2020). Denoising diffusion implicit models are a generalization to DDPM which allows sampling with fewer iterations. DDIM applies the following update rule:

$$\mathbf{x}_{t-1} = \sqrt{\alpha_{t-1}}\Big(\frac{\mathbf{x}_t - \sqrt{1-\alpha_t}\boldsymbol{\epsilon}_\theta(\mathbf{x}_t, t)}{\sqrt{\alpha_t}}\Big) + \sigma_t \boldsymbol{\epsilon}_t \tag{11}$$

Note that DDIM shares the same training procedure with DDIM, which means we can take a model trained with DDPM objective and perform faster sampling using DDIM. When σ_t is set to 0, which is the case for our setting, the denoising becomes deterministic given $\mathbf{x}_T$. Assuming each step only performs small changes to $\mathbf{x}_t$, DDIM sampling can also be conducted in the reverse order, as proposed in Song et al. (2020); Dhariwal & Nichol (2021) to obtain a vector $\mathbf{x}'_T$ from $\mathbf{x}_0$ so that $\mathbf{x}'_T$, when de-noised, gives back $\mathbf{x}'_0$ that is close to $\mathbf{x}_0$. The process of inverting the $\mathbf{x}_0$ to get $\mathbf{x}'_T$ is called DDIM inversion Mokady et al. (2022).

Latent Diffusion and Stable Diffusion Rombach et al. (2022). While DDIM and DDPM are denoising images from raw pixel space, latent diffusion proposes to denoise from initial latent noise $\mathbf{z}_T$ to $\mathbf{z}_0$. Then an image decoder decodes the generated $\mathbf{z}_0$ in the latent space to an output image $\mathbf{x}_0$. Latent/Stable Diffusion lowers the cost of training high resolution diffusion models and is widely used in text-to-image generation. Our method improves the prompt understanding of Stable Diffusion without adapting the weights.

Latent diffusion also proposes a conditioning scheme that allows generating samples with other modalities (e.g., text) as the condition. The condition is realized through cross-attention layers Vaswani et al. (2017) that attend from latent locations in U-Net Ronneberger et al. (2015) feature maps to the encoded condition (e.g., text features from a CLIP text encoder).

Stable diffusion models are large text-to-image generation models trained on large multi-modal datasets using the techniques proposed for latent diffusion.

B   Pseudo-code for layout-grounded image generation

We present the pseudo-code for our layout-grounding stage (stage 2) in Algorithm 1. We explain the functionality of the functions used in the pseudo-code:

1. `SampleGaussian` samples i.i.d standard Gaussian as the initial noise for the latent tensor.

2. `PromptForBox` simply sets *"[background prompt] with [box caption]"* (e.g., *"a realistic image of an indoor scene with a gray cat"*) as the denoising prompt.

Algorithm 1 Layout-grounded image generation.

Input: A set of captioned bounding boxes $\{(\mathbf{b}^{(i)}, \mathbf{y}^{(i)})\}_{i=1}^{N}$. Background caption $\mathbf{y}^{(\mathrm{bg})}$.
Output: Image $\mathbf{z}^{(\mathrm{comp})}$.
1: $\mathbf{z}_T \leftarrow \mathtt{SampleGaussian}(\mathbf{0}, \mathbf{I})$
2: *Per-box masked latent generation:*
3: **for** each captioned box $(\mathbf{b}^{(i)}, \mathbf{y}^{(i)})$ **do**
4:     $\mathbf{z}_T^{(i)} \leftarrow \mathbf{z}_T$
5:     $\mathbf{y}^{(i)} \leftarrow \mathtt{PromptForBox}(\mathbf{y}^{(i)}, \mathbf{y}^{(\mathrm{bg})})$
6:     **for** $t \leftarrow T$ to 1 **do**
7:         $\mathbf{z}_t^{(i)} \leftarrow \mathtt{AttnControl}(\mathbf{z}_t^{(i)}, \mathbf{y}^{(i)}, \mathbf{b}^{(i)})$
8:         $\mathbf{z}_{t-1}^{(i)} \leftarrow \mathtt{Denoise}(\mathbf{z}_t^{(i)}, \mathbf{y}^{(i)})$ with cross-attention map extracted to $A_t^{\prime(i)}$
9:     **end for**
10:     $A^{\prime(i)} \leftarrow \mathtt{TemporalAverage}(A_t^{\prime(i)})$
11:     $A^{(i)} \leftarrow \mathtt{SAMRefine}(A^{\prime(i)}, \mathbf{z}_0^{(i)})$ (Optional: This could be replaced with an attention thresholding instead.)
12: **end for**
13: *Composed image generation:*
14: $\mathbf{z}_T^{(\mathrm{comp})} \leftarrow \mathbf{z}_T$
15: $\mathbf{y} \leftarrow \mathtt{ComposedPrompt}((\mathbf{y}^{(i)})_{i=1}^{N}, \mathbf{y}^{(\mathrm{bg})})$
16: **for** $t \leftarrow T$ to 1 **do**
17:     **if** $t \geq rT$ **then**
18:         $\mathbf{z}_t^{(\mathrm{comp})} \leftarrow \mathtt{LatentCompose}(\mathbf{z}_t^{(\mathrm{comp})},$
19: $(\mathbf{z}^{(i)})_{i=1}^{N}, A^{(i)})$
20:         $\mathbf{z}_t^{(\mathrm{comp})} \leftarrow \mathtt{AttnTransfer}(\mathbf{z}_t^{(\mathrm{comp})},$
21: $\mathbf{y}^{(\mathrm{comp})}, A_t^{\prime(i)})$
22:     **end if**
23:     $\mathbf{z}_{t-1}^{(\mathrm{comp})} \leftarrow \mathtt{Denoise}(\mathbf{z}_t^{(\mathrm{comp})}, \mathbf{y}^{(\mathrm{comp})})$
24: **end for**
25: $\mathbf{x}_0 \leftarrow \mathtt{Decode}(\mathbf{z}_0^{(\mathrm{comp})})$

---

3. `AttnControl` performs backward guidance to minimize the energy function described in Section 3 to encourage the attention to the area within the box and discourage the attention on area outside the box.

4. `Denoise` denotes one denoising step by the diffusion model.

5. `TemporalAverage` averages the cross-attention map across the timestep dimension

6. `SAMRefine` refines the attention map by internally decoding the latent and refining with SAM. If SAM is not enabled, we perform an attention thresholding instead.

7. `ComposedPrompt` composes the prompt for overall generation. We offer two options for the overall prompt: using the original input prompt or composing the prompt as *"[background prompt] with [box caption 1], [box caption 2], ..."*. The former one allows capturing the object as well as forground-background interactions that are not captured in the layout. The latter allows captions in languages unsupported by the diffusion model and stays robust when the caption is misleading (e.g., "neither of the apples is red"). We use the latter by default but also allow the former for fine-grained adjustments.

8. `LatentCompose` spatially composes the latent with respect to the mask, replacing the content of the destination latent on the masked locations.

9. `AttnTransfer` performs backward guidance to minimize the energy function in Section 3 to encourage the attention in overall generation within the box to be similar to the attention in per-box generation in addition to attention control.

Figure 10: **We also generate images with the same text prompts as Fig. 1 with SDv1.5 and LMD on SDv1.5.** We observe similar results which show that while Stable Diffusion Rombach et al. (2022) **(a)** often struggles to accurately follow several types of complex prompts, our method LMD **(b)** achieves enhanced prompt understanding capabilities and accurately follows these types of prompts.

C   Additional visualizations

We also present Fig. 10, which includes a qualitative comparison with Stable Diffusion v1.5 (abbreviated as SDv1) and shares the prompts with Fig. 1.

D   Benchmarking VisualChatGPT and GILL for multi-round instruction-based scene specification

VisualChatGPT (Wu et al., 2023) and GILL (Koh et al., 2023) involve LLM in their image generation pipelines and thus could potentially take instructions from multiple rounds of dialog for image generation. Therefore, in addition to the qualitative benchmark in Fig. 8, we also benchmark both methods for multi-round scene specification. As shown in Fig. 11, the generated images quickly degrade starting from the second iteration, showing that neither method is able to take instructions from multiple rounds of dialog for image generation. In contrast, our method is able to handle several rounds of sequential requests on image generation without generation degradation, shown in Fig. 6.

E   Details for SDXL integration

Thanks to the training-free nature of our work, our method is applicable to various diffusion models without additional training. Therefore, we also apply our method on SDXL 1.0 (Podell et al., 2023), the latest stable diffusion model which has a 3× larger U-Net module compared to previous stable diffusion models (Rombach et al., 2022).

It is straightforward to apply the LMD pipeline directly to SDXL UNet, which has a very similar procedure to applying the LMD pipeline to SD v1/v2. This approach only requires marginal modifications of the LMD pipeline: different from SD v1/v2 that use only one text encoder for encoding the prompts, SDXL involves two text encoders for text feature generation, and the attention control proposed in LMD needs to be applied to the cross-attention with both text encoders taken into account. The rest follows from the standard LMD pipeline.

Inspired by methods such as Ramesh et al. (2022) that generate low resolution images and then upsample the generation to the target resolution, an alternative approach is to perform denoising with the standard LMD with a standard SDv1/v2 resolution (i.e., 512×512) and then perform upsampling with SDXL refiner for a few steps to the intended resolution (e.g., 1024×1024). Since most of the generation still happens in the standard resolution latent space, with the SDXL only involved a limited number of steps for high-resolution latents, this approach is more efficient compared to the former approach. We compare the generation for the same scene with SDXL baseline and both approaches in Fig. 12. Both approaches present much better prompt

Figure 11: VisualChatGPT Wu et al. (2023) and GILL Koh et al. (2023) generally cannot handle more than one round of image generation requests, with the generated image degraded starting from the second request. In contrast, our method is able to handle several rounds of sequential requests on image generation without generation degradation, shown in Fig. 6.

following ability compared to SDXL baseline. We observe similar generation quality on both approaches. Therefore, we use the latter approach by default.

For Fig. 1 and Fig. 7, we use SDXL 1.0 as the base model of LMD and compare against SDXL as a strong baseline. For all other settings, including the qualitative evaluation setting, we use Stable Diffusion v1.5 (denoted as SDv1) unless stated otherwise. For fair comparison with Wu et al. (2023) and Koh et al. (2023) that only use Stable Diffusion v1.5, we also generate images for the same set of prompts of Fig. 1 with Stable Diffusion v1.5 in Fig. 10.

(a) SDXL Baseline

(b) Applying LMD directly on SDXL

(c) Applying LMD on SD in low-res and refine with SDXL in high-res

Figure 12: **LMD can be easily applied on the latest stable diffusion model SDXL (Podell et al., 2023).** We compare generated images from text prompt "A realistic photo of a **gray cat** and an **orange dog** on the grass". **(a)** directly generates the image from the text prompt. SDXL does not accurately generate the image from the prompt, showing that *simply scaling the diffusion model does not necessarily lead to improved prompt following ability.* **(b)** Thanks to our method being training-free, our method can be directly applied on SDXL without additional training. **(c)** An alternative way to integrate our method with SDXL is to use our method to generate low-resolution images with SD and then refine the image in high-resolution in SDXL. Since most denoising is completed in low-resolution latents, this approach is more efficient.

Figure 13: By asking the LLM to always output layouts in English, **LMD is naturally able to generate images from prompts in languages not supported by the underlying diffusion model.**

F Details for text-to-image benchmarks

We pick 10 common object types from the COCO dataset Lin et al. (2014) for generation[5].

For negation and generative numeracy task, each prompt requires the model to generate a layout of a scene with some number of a certain object or without a certain object. Then we count the number of objects and consider the layout to be correct if the number of the object of that particular type matches the one in the prompt, with the number ranging from 1 to 5.

The objective for each prompt in the attribute binding task is to generate an object of a color and another object of another color, for which the evaluation is similar to other tasks.

---

[5]Backpack, book, bottle, bowl, car, cat, chair, cup, dog, and laptop.

For the spatial relationship task, we generate an object at a certain location and another object at an opposite location (left/right and top/bottom). We then check the spatial coordinates of the boxes to ensure the layout exactly matches the prompt. In each task, we generate 100 text prompts, with 400 text prompts in total.

Prompts. For the negation benchmark, we use the prompt *A realistic photo of a scene without [object name]*.

For generative numeracy, we use the prompt *A realistic photo of a scene with [number] [object name]*.

For attribute assignment, we use the prompt *A realistic photo of a scene with [modifier 1] [object name 1] and [modifier 2] [object name2]*, where the two modifiers are randomly chosen from colors (red, orange, yellow, green, blue, purple, pink, brown, black, white, and gray).

For the spatial relationship benchmark, we use the prompt *A realistic photo of a scene with [object name 1] on the [location] and [modifier 2] [object name2] on the [opposite location]*, where the location is chosen from left, right, top, and bottom.

Implementation details. For LMD, we use Stable Diffusion v1.5 by default. For LMD+, we use GLIGEN (Li et al., 2023b) model without additional training or adaptation. We selected the GLIGEN (Li et al., 2023b) model trained based on Stable Diffusion v1.4, which is the latest at the time of writing. We use $\eta = 5$, $\lambda = 2.0$, $r = 0.4$, guidance scale 7.5. The energy minimization is repeated 5 times for each denoising timestep and linearly decrease for every five denoising steps until the repetition is reduced to 1, and we do not perform guidance after 30 steps. k in the $\mathsf{Topk}(\cdot)$ in Eq. (3) is set to 20% of the area of the mask for each mask. The the background part (second term) of Eq. (3) is weighted by $\omega = 4.0$. We run the denoising process with 50 steps by default. We only perform latent compose in the first half of the denoising process (first 25 steps). The qualitative visualizations/quantitative comparisons are generated by LMD+/LMD, respectively, by default unless stated otherwise.

G Generating images from languages not supported by the underlying diffusion model

As shown in Fig. 13, by asking the LLM to always output layouts in English even if the prompt is non-English (e.g., Korean or Chinese as in Fig. 13) and providing an in-context example of non-English input and English layout, LMD is able to generate images from prompts in languages not supported by the underlying diffusion model. We simply translate the prompt input of the last in-context example to non-English, while keeping the output in this example in English. No adaptation is needed on the diffusion model since the underlying diffusion model still takes in English layout as input.

H Our LLM prompt

Our LLM prompt is listed in Table 9. Our in-context examples are listed in Table 10.

```
1 You are an intelligent bounding box generator. I will provide you with a caption for a photo,
     image, or painting. Your task is to generate the bounding boxes for the objects mentioned in
     the caption, along with a background prompt describing the scene. The images are of size
     512x512. The top-left corner has coordinate [0, 0]. The bottom-right corner has coordinnate
     [512, 512]. The bounding boxes should not overlap or go beyond the image boundaries. Each
     bounding box should be in the format of (object name, [top-left x coordinate, top-left y
     coordinate, box width, box height]) and should not include more than one object. Do not put
     objects that are already provided in the bounding boxes into the background prompt. Do not
     include non-existing or excluded objects in the background prompt. Use "A realistic scene"
     as the background prompt if no background is given in the prompt. If needed, you can make
     reasonable guesses. Please refer to the example below for the desired format.
2
3 [In-context Examples]
4
5 Caption: [User Prompt]
6 Objects:
```

Table 9: Our full prompt to the LLM for layout generation. LLM starts completion from "`Objects:`".

```
1 Caption: A realistic image of landscape scene depicting a green car parking on the left of a
     blue truck, with a red air balloon and a bird in the sky
2 Objects: [('a green car', [21, 281, 211, 159]), ('a blue truck', [269, 283, 209, 160]), ('a red
     air balloon', [66, 8, 145, 135]), ('a bird', [296, 42, 143, 100])]
3 Background prompt: A realistic landscape scene
4 Negative prompt:
5
6 Caption: A realistic top-down view of a wooden table with two apples on it
7 Objects: [('a wooden table', [20, 148, 472, 216]), ('an apple', [150, 226, 100, 100]), ('an
     apple', [280, 226, 100, 100])]
8 Background prompt: A realistic top-down view
9 Negative prompt:
10
11 Caption: A realistic scene of three skiers standing in a line on the snow near a palm tree
12 Objects: [('a skier', [5, 152, 139, 168]), ('a skier', [278, 192, 121, 158]), ('a skier', [148,
     173, 124, 155]), ('a palm tree', [404, 105, 103, 251])]
13 Background prompt: A realistic outdoor scene with snow
14 Negative prompt:
15
16 Caption: An oil painting of a pink dolphin jumping on the left of a steam boat on the sea
17 Objects: [('a steam boat', [232, 225, 257, 149]), ('a jumping pink dolphin', [21, 249, 189,
     123])]
18 Background prompt: An oil painting of the sea
19 Negative prompt:
20
21 Caption: A cute cat and an angry dog without birds
22 Objects: [('a cute cat', [51, 67, 271, 324]), ('an angry dog', [302, 119, 211, 228])]
23 Background prompt: A realistic scene
24 Negative prompt: birds
25
26 Caption: Two pandas in a forest without flowers
27 Objects: [('a panda', [30, 171, 212, 226]), ('a panda', [264, 173, 222, 221])]
28 Background prompt: A forest
29 Negative prompt: flowers
30
31 Caption: An oil painting of a living room scene without chairs with a painting mounted on the
     wall, a cabinet below the painting, and two flower vases on the cabinet
32 Objects: [('a painting', [88, 85, 335, 203]), ('a cabinet', [57, 308, 404, 201]), ('a flower
     vase', [166, 222, 92, 108]), ('a flower vase', [328, 222, 92, 108])]
33 Background prompt: An oil painting of a living room scene
34 Negative prompt: chairs
```

Table 10: Our in-context examples. We use fixed in-context examples for layout generation.