Language Models as Recommender Systems: Evaluations and Limitations

Abstract

Pre-trained language models (PLMs) such as BERT and GPT learn general text representations and encode extensive world knowledge; thus, they can be efficiently and accurately adapted to various downstream tasks. In this work, we propose to leverage these powerful PLMs as recommender systems and use prompts to reformulate the session-based recommendation task to a multi-token cloze task. We evaluate the proposed method on a movie recommendation dataset in zero-shot and fine-tuned settings where no or limited training data are available. In the zero-shot setting: we find that PLMs outperform the random recommendation baseline by a large margin; in the meantime, we observe strong linguistic bias when using PLMs as recommenders. In the fine-tuned setting: such bias is reduced with available training data; however, PLMs tend to under-perform traditional recommender system baselines such as GRU4Rec. Our observations demonstrate the current challenges of multi-token inference and shed light on future works in this novel direction.

1 Introduction

Language models (LMs) learn probability distributions over sequences of words [1]. Pre-training LMs over large corpora of texts and adapting these PLMs such as BERT [4] or GPT-2 [12] to different downstream tasks have been a default paradigm for natural language processing in recent years.

In this work, we explore using powerful PLMs as recommender systems by reformulating recommendation as a language modeling task. More specifically, we convert a user's interaction sequence to a text inquiry (e.g., item sequence: $\langle \underline{1193}, \underline{661}, \underline{914} \rangle$ to text sequence: *A user watched One Flew Over the Cuckoo's Nest, James and the Giant Peach, My Fair Lady. Now the user wants to watch _ _ _.*, where _ is a special mask token.) and use PLMs to fill in masks as recommendations.

By converting the traditional item-based recommendation to this text-based cloze task [14], we hope to leverage PLMs to tackle two challenging problems for recommendation:

- **Zero-shot Recommendations:** Generating personalized recommendations when no interaction data is available for training is an important business scenario, especially for startup companies. We refer to recommendation tasks in this setting as zero-shot recommendation [5]. Many recent works have demonstrated that PLMs acquire and store extensive knowledge into their parameters during the pre-training stage [2, 11]. They find that PLMs even correctly answer more factoid questions than the models that explicitly use external knowledge bases [13]. We believe such knowledge could also be beneficial to the zero-shot recommendation problem.

- **Data Efficiency:** The general representations learned during the pre-training stage enable language models to easily adapt to a variety of downstream tasks. Moreover, recently-proposed prompt-based tuning approaches further improve the data efficiency [15] — PLMs

can be 100x more data efficient when converting various natural language processing tasks such as text classification, question answering, natural language inference to cloze task with a prompt (in our example, *A user watched... Now the user wants to watch...* is a prompt) [10]. Similarly, we believe PLMs could also be used as data-efficient recommender systems.

We evaluate our method on both zero-shot and supervised movie recommendation tasks. In the zero-shot setting, we find that the language model recommender system outperforms random recommendations but has strong linguistic biases for its recommendations. We further fine-tune the language models with prompt-tuning techniques, and we find that such bias is reduced but fine-tuned models under-perform traditional recommender system baseline GRU4Rec [8]. Our observations shed light on the potential opportunities as well as current challenges in this novel direction.

2 Method

In recommendation, given a user with viewed item sequence $[x_1, x_2, ..., x_{t-1}]$, we want to predict the probability distribution of the next item $p(x_t | x_1, ..., x_{t-1})$. For traditional methods, each x_i is embedded into a vector (item embedding), and sequence modeling techniques such as recurrent neural networks or self-attention is applied to model the item sequence (user embedding).

For our method, we first map each item to its word description (e.g., movie name) $d(x_i) = [w_{i_1}, w_{i_2}, ..., w_{i_L}]$ and use a prompt $f(\cdot)$ to convert the item sequence into the word sequence $c = f([d(x_1), d(x_2), ..., d(x_{t-1})])$ as the context. We then use the language model to estimate the probability distribution of the next item by aggregating the probability of each word in the item description $p(d(x_t)|c) = p(w_{t_1}, w_{t_2}, ..., w_{t_L}|c)$. Note that with this model, we assume a one-to-one correspondence between x and $d(x)$ in the candidate set.

The key challenge of our proposed method is multi-word inference. As language models are designed to predict a single word distribution at each time step, how to estimate the probability distribution of the next item that is always corresponding to multiple words (e.g., "Star Wars" in movie recommendations) remains an open problem in natural language processing research.

First, different items have different lengths of word descriptions. We can pad each item description to the same fixed length (e.g., the maximum length of all the item names) and compute the average probability of each word. Moreover, another critical choice is whether to estimate the probability distribution of each word in the item description independently or dependently. That is, whether we want to model $p(w_{t_1}, w_{t_2}, ..., w_{t_L}|c) = \prod_j p(w_{t_j}|c)or\prod_j p(w_{t_j}|w_{t_{<j}}, c)$. Technically, it is achieved by whether to use the language model to fill in all the masks at a time or in an auto-regressive fashion. We refer to the independent estimation as O(1) inference as we only need a single forward pass for the language model[1] and the dependent estimation as O(LN) inference as we need L forward passes for each item and LN passes for N items. While the second estimation is intuitively more accurate, it is computationally inefficient when we have a large collection of items.

For training, we maximize the probability of the ground-truth item $p(d(x_t)|c)$ via the cross-entropy loss. For evaluation, we use MRR@K and Recall@K (R@K) metrics based on top K predicted items.

3 Experiments

Research Questions: We are hereby to answer the following questions:

Q1 Can we use pre-trained language models for zero-shot recommendation? (Section 3.1)
Q2 Can we fine-tune pre-trained language models to improve recommendations? (Section 3.2)

Dataset: We train and evaluate the model on the widely-used movie recommendation dataset MovieLens-1M (ML1M) [7], which consists of 6040 users, N=3883 movies, and 1M interactions.

3.1 Zero-shot Recommendations

We start with zero-shot (i.e., no interaction data is available for training) language model recommender systems (LMRecSys). For each user, we provide the model with their first 5 watched movies and use

---

[1]Since the context c is the same for all the N candidate items, we only need 1 forward pass instead of N.

the model to predict their 6^{th} watched movie. We use the movie title as the item description and pad or truncate all the titles to L=10 words. We use the prompt *A user watched A, B, C, D, E. Now the user may want to watch [F].*, where each letter represents a full movie title. We compare different inference methods, model sizes, and prompts.

We compare our LMRecSys with two zero-shot baselines **Random** and **BERT-Base ItemKNN** (Using BERT to generate item embeddings and computing nearest neighbors) and two supervised baselines **POP** (Popularity-based model) and **GRU4Rec** [8] (GRU over item embeddings generated based on item ID). Table 1 shows zero-shot model performances on the MovieLens-1M dataset, while Table 2 shows the case study of different inference methods (full results see Supplementary Table 4).

3.1.1 Results & Analysis

Multi-token inference methods significantly influence the results. For O(1) inference, we pad or truncate all the titles to L=10 words, leave 10 masks, and use the language model to fill all the masks by one pass. BERT O(1) shows even worse performance than the random recommendation. We find that this is because not all the movie names are exactly 10 tokens, always adding a period after 10 masks makes the text ungrammatical, and language models can hardly fill these ungrammatical texts that are never-before-seen during pre-training. We use a simple solution by leaving 1-10 masks, feeding them into the model for 10 times, and select the output for each movie based on its length [9]. We name this method as O(10) inference, which achieves ~2x more R@20 than O(1) inference and ~1x more R@20 than random. Inputs are guaranteed to be grammatically correct for O(LN) inference as we only add a period after the exact name. GPT2 O(LN) shows much better performances than other inferences because of the more accurate probability estimation but much more computational cost.

Model size and prompt have small influences on the results. Model size and prompt have a significant impact on performances for many NLP tasks [3]. However, for our task, the R@20 only improves by 0.72% from GPT2-Small (117M parameters) to GPT-XL (1542M parameters). We also design a weaker and a stronger prompt for comparison[2]. However, for our task, using different prompts achieves very close performances.

3.1.2 Case Study

Language models show clear linguistic biases for recommendations. Despite higher performances achieved by LMRecSys compared to random predictions, we observe that models have strong linguistic biases for their top predictions and bottom predictions. Different biases are associated with different inference methods because of different probabilities modeled. O(1) inference favors generic and grammatical sequences, O(LN) inference favors uniquely long and grammatical sequences, and O(KN, sum) inference favors short and grammatical sequences. All the inference methods penalize ungrammatical sequences. In other words, language models are more "language modeling" (predicting fluent and grammatically correct text) than "collaborate filtering"

Method	# Params	R@20
Zero-shot		
Random	0	0.0052
BERT-Base ItemKNN	110M	0.0599
BERT-Base O(1)	110M	0.0030
BERT-Base O(10)	110M	0.0094
BERT-Base (DAPT) O(10)	110M	0.0137
GPT2-Small O(LN)	117M	0.0667
GPT2-Medium O(LN)	345M	0.0617
GPT2-Large O(LN)	762M	0.0587
GPT2-XL O(LN)	1542M	0.0739
GPT2-Small O(LN) Weak Prompt	117M	0.0627
GPT2-Small O(LN) Strong Prompt	117M	0.0653
GPT2-Small O(LN, sum)	117M	0.0320
GPT2-Small O(LN) Calibrated	117M	0.0733
Supervised		
POP	0	0.1507
GRU4Rec	-	0.1664

Table 1: Zero-shot model performances on ML-1M.

(recommending similar items based on user preferences). Please refer Table 2 for more details.

Calibration slightly reduces linguistic biases. As language models show clear linguistic biases for recommendations, here we use a simple calibration method by subtracting the base probability predicted by the language model from the original probability $p'(d(x_t)|c) = p(d(x_t)|c) - \alpha p(d(x_t))$ [16].

---

[2]Weaker prompt: *A, B, C, D, E, [F].*; Stronger prompt: *A user watched movies A, B, C, D, E. Now the user may want to watch the movie [F]..*

Technically, the base probability is computed by feeding the model with a null context instead of the user-viewed context. By only considering the changing amount in predicted scores, movies with rare words in titles will be less penalized. The coefficient α is tuned on a small set of 50 examples. We find that the calibration improves the R@20 by 0.66% when choosing $\alpha = 0.40$. However, linguistic bias is only slightly mitigated as shown in the Supplementary Table 4.

Method	Probability	Top 3 Predictions	Top Prediction Bias
BERT-Base O(1)	$\prod_i \sqrt[k]{p(w_i\|c)}$	(1) If....
(2) Them!
(3) The Show	Generic and grammatical word sequences
GPT2-Small O(LN)	$\prod_i \sqrt[k]{p(w_i\|c, w_{<i})}$	(1) Dr. Strangelove or: How I Learned to Stop Worrying and Love the Bomb
(2) Star Wars: Episode VI - Return of the Jedi
(3) Star Wars: Episode V - The Empire Strikes Back	Uniquely long and grammatical word sequences
GPT2-Small O(KN, sum)	$\prod_i p(w_i\|c, w_{<i})$	(1) Raiders of the Lost Ark
(2) Jurassic Park
(3) Ghostbusters I	Short and grammatical word sequences

Table 2: Case study of different inference methods. *Input: A user watched Raiders of the Lost Ark, Star Wars: Ep VI-Return of the Jedi, Ran, Ghostbusters II, Gandhi. Now the user may want to watch _. Answer: Indochine*

3.2 Fine-tuned Recommendations

We explore fine-tuning LMRecSys to improve recommendations. We experiment with different inference methods, different models, and different amount of training data (by controlling the session length K). Due to computational limits, here we only use inference methods that have constant complexity. Table 3 shows fine-tuned model performances (full results see Supplementary Table 5)[3].

3.2.1 Results & Analysis

LMRecSys under-performs GRU4Rec. LMRecSys with different PLMs and inference methods achieve slightly worse performances than baseline GRU4Rec after fine-tuning. This is probably because learning to predict the next item as multiple tokens is intrinsically more challenging than predicting the next item as a whole. RoBERTa achieves slightly better performances than BERT probably because of 10x more pre-training data.

Domain-adaptive pre-training (DAPT) [6] shows small improvements. To inject domain-specific knowledge, we continue pre-training the BERT on 520K movie synopses crawled from the web. We concatenate each synopsis with its title (i.e., *[synopsis]. This is the movie [Title].*), mask 30% random words or only the entire title for 1:1 ratio, and train the model to predict the masked words. We find that this hybrid masking strategy is better than a purely random masking strategy and leads to small improvements for both zero-shot and fine-tuned recommendations. The limited improvements may be due to the small data size compared to the general pre-training data.

Fine-tuned LMRecSys learn how to recommend but linguistic biases still exist for bottom predictions. From Supplementary Table 4, no clear bias is observed for the top predictions, but models still penalize movies with ungrammatical names (e.g., non-English words).

Method	MRR@20	R@20
Random	-	0.0052
POP	0.0202	0.0817
GRU4Rec	0.0302	0.0986
BERT O(1)	0.0177	0.0843
RoBERTa O(1)	0.0204	0.0843
BERT O(10)	0.0181	0.0852
BERT (DAPT) O(10)	0.0187	0.0872

Table 3: Fine-tuned model performances on ML-1M-5Star.

4 Conclusion

In this work, we propose to leverage pre-trained language models as recommender systems and transform the recommendation task to the cloze task. However, as multi-token inference is still an open problem in natural language processing research, we find existing inference methods have strong linguistic biases for predictions and fail to achieve expected gains after fine-tuning.

---

[3]Here we use a different data processing method by only keeping the last K movies that a user watched and rated as 5 stars to reduce the popularity bias in the dataset. We name this dataset as ML-1M-5Star.

References

[1] Yoshua Bengio, Réjean Ducharme, Pascal Vincent, and Christian Janvin. A neural probabilistic language model. *JMLR*, 2003.

[2] Antoine Bosselut, Hannah Rashkin, Maarten Sap, Chaitanya Malaviya, Asli Celikyilmaz, and Yejin Choi. Comet: Commonsense transformers for automatic knowledge graph construction. In *ACL*, 2019.

[3] Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *OpenAI*, 2020.

[4] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *NAACL*, 2019.

[5] Hao Ding, Yifei Ma, Anoop Deoras, Yuyang Wang, and Hao Wang. Zero-shot recommender systems. *arXiv:2105.08318*, 2021.

[6] Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A Smith. Don't stop pretraining: Adapt language models to domains and tasks. In *ACL*, 2020.

[7] F Maxwell Harper and Joseph A Konstan. The movielens datasets: History and context. *TIIS*, 2015.

[8] Balázs Hidasi, Alexandros Karatzoglou, Linas Baltrunas, and Domonkos Tikk. Session-based recommendations with recurrent neural networks. In *ICLR*, 2016.

[9] Zhengbao Jiang, Antonios Anastasopoulos, Jun Araki, Haibo Ding, and Graham Neubig. X-factr: Multilingual factual knowledge retrieval from pretrained language models. In *EMNLP*, 2020.

[10] Teven Le Scao and Alexander M Rush. How many data points is a prompt worth? In *NAACL*, 2021.

[11] Fabio Petroni, Tim Rocktäschel, Sebastian Riedel, Patrick Lewis, Anton Bakhtin, Yuxiang Wu, and Alexander Miller. Language models as knowledge bases? In *EMNLP*, 2019.

[12] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI*, 2019.

[13] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *JMLR*, 2020.

[14] Timo Schick and Hinrich Schütze. Exploiting cloze-questions for few-shot text classification and natural language inference. In *EACL*, 2021.

[15] Timo Schick and Hinrich Schütze. It's not just size that matters: Small language models are also few-shot learners. In *NAACL*, 2021.

[16] Tony Z Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. Calibrate before use: Improving few-shot performance of language models. In *ICML*, 2021.

A Appendix

Method	Probability	Top 3 Predictions	Top Prediction Bias	Bottom 3 Predictions	Bottom Prediction Bias
BERT-Base O(1)	$\prod_i \sqrt[k]{p(w_i\|c)}$	1. If.... 2. Them! 3. The Show	Generic and grammatical word sequences	3. Shaft 2. Trois 1. Nowhere	Ungrammatical sequences
GPT2-Small O(LN)	$\prod_i \sqrt[k]{p(w_i\|c, w_{<i})}$	1. Dr. Strangelove or: How I Learned to Stop Worrying and Love the Bomb 2. Star Wars: Episode VI - Return of the Jedi 3. Star Wars: Episode V - The Empire Strikes Back	Uniquely long and grammatical word sequences	3. Children Are Watching us, The (Bambini ci guardano, I) 2. Under the Domin Tree (Etz Hadomim Tafus) 1. Goodbye, 20th Century (Zbogum na dvadesetiot vek)	Ungrammatical sequences
GPT2-Small O(KN, sum)	$\prod_i p(w_i\|c, w_{<i})$	1. Raiders of the Lost Ark 2. Jurassic Park 3. Ghostbusters II	Short and grammatical word sequences	3. Garden of Finzi-Contini, The (Giardio dei Finzi-Contini, Il) 2. Old Lady Who Walked in the Sea, The (Vieille qui marchait dans la mer, La) 1. Goodbye, 20th Century (Zbogum na dvadesetiot vek)	Ungrammatical sequences
GPT2-Small O(LN) Calibrated	$\prod_i \sqrt[k]{p(w_i\|c, w_{<i})} - \alpha \prod_i \sqrt[k]{p(w_i\|w_{<i})}$	1. Star Wars: Episode VI - Return of the Jedi 2. Star Wars: Episode V - The Empire Strikes Back 3. Close Encounters of the Third Kind	Uniquely long and grammatical word sequences	3. Children Are Watching us, The (Bambini ci guardano, I) 2. Under the Domin Tree (Etz Hadomim Tafus) 1. Goodbye, 20th Century (Zbogum na dvadesetiot vek)	Ungrammatical sequences
BERT-Base O(1) Fine-tuned	$\prod_i \sqrt[k]{p(w_i\|c)}$	1. The Insider 2. Saving Private Ryan 3. Boys Don't Cry	No clear bias observed	3. Black Tights (Les Collants Noirs) 2. Half-moon (Paul Bowles - Halbmond) 1. Beloved/Friend (Amigo/Amado)	Ungrammatical sequences

Table 4: Case study of different inference methods. *Input: A user watched Raiders of the Lost Ark, Star Wars: Episode VI - Return of the Jedi, Ran, Ghostbusters II, Gandhi. Now the user may want to watch ___. Answer: Indochine*

Method	K=4		K=5		K=6		K=7	
	MRR@20	R@20	MRR@20	R@20	MRR@20	R@20	MRR@20	R@20
Random	-	0.0052	-	0.0052	-	0.0052	-	0.0052
POP	0.0202	0.0817	0.0196	0.0828	0.0199	0.0793	0.0198	0.0763
GRU4Rec	0.0302	0.0986	0.0325	0.1210	0.0370	0.1505	0.0410	0.1542
BERT-Base O(1)	0.0177	0.0843	0.0223	0.0959	0.0257	0.1051	0.0319	0.1210
BERT-Base O(10)	0.0181	0.0852	-	-	-	-	-	-
RoBERTa-Base O(1)	0.0204	0.0843	0.0209	0.1012	0.0265	0.1087	0.0289	0.1250
RoBERTa-Base (DAPT) O(10)	0.0187	0.0872	-	-	-	-	-	-

Table 5: Fine-tuned model performances on ML-1M-5Star with different session lengths K.