CRUX: Detecting Multi-Turn Jailbreaks via Cross-Dimensional Guard Disagreement

Abstract

Large language models face persistent safety threats from multi-turn jailbreak attacks that embed harmful intent across individually benign turns, exploiting cross-turn intent accumulation to bypass turn-level auditing. When multiple guard models audit the same session from independent information dimensions, the cross-dimensional judgment disagreement that attacks induce is commonly suppressed by majority voting. We argue that this practice conflates two fundamentally different sources of disagreement. Same-dimensional disagreement among models observing identical information reflects epistemic uncertainty and rises on both attack and benign boundary samples, whereas cross-dimensional disagreement reflects the information asymmetry that attacks create across functionally specialized observation dimensions, rising disproportionately under attack as an attack-specific signal. We formalize this distinction into a proposition on the discriminativeness of cross-dimensional disagreement and derive three testable implications. Experiments confirm that the likelihood ratio of cross-dimensional disagreement reaches 4.84 and that a detector observing only whether the three views agree, without reading their judgment content, achieves F1 = 0.747, with cross-dimensional disagreement consistently outperforming its same-dimensional counterpart. CRUX instantiates this analytical framework as a three-dimension auditing architecture. Across two target models and diverse attack settings, it reduces the average multi-turn attack success rate to 4.3% while maintaining a response-side false positive rate of 0.02.

1 Introduction

Large language models have become core interfaces for search, programming assistance, and agentic workflows (Lewis et al., 2020; Chen et al., 2021; Yao et al., 2023; Wu et al., 2024), and their open-ended generation capabilities expose them to persistent adversarial threats (Wang et al., 2026; Xu

Figure 1: Limitations of existing turn-level guards. The same harmful objective is successfully flagged in a single turn, but evades detection when decomposed into seemingly benign multi-turn steps that bypass turn-level judgment.

et al., 2024). External guard models serve as an independent defense layer that judges safety without modifying model weights (Inan et al., 2023; Han et al., 2024; Zhao et al., 2025), decoupling safety judgment from the model whose alignment may be compromised. However, multi-turn jailbreak attacks pose a fundamental challenge: attackers decompose harmful objectives into individually benign turns that progressively accumulate toward the malicious goal, evading turn-level auditing. As Figure 1 illustrates, the same objective is flagged in a single turn but passes all checks when decomposed into multi-turn steps. Multiple studies confirm the effectiveness of this attack paradigm (Russinovich et al., 2025; Yang et al., 2025b; Rahman et al., 2025; Peng et al., 2026), with human red-teaming further demonstrating significant defense gaps in state-of-the-art guards (Li et al., 2024a).

What sets multi-turn defense apart from single-turn classification is not a deficit in guard model accuracy but a structural limitation in observation coverage. Session safety simultaneously involves current-request semantics, response behavior, and cross-turn intent evolution; turn-level detection projects this multi-dimensional state onto a sin-

gle dimension, losing information that no classifier improvement can recover. Existing defenses each cover one dimension but cannot access others (Xie et al., 2023; Wei et al., 2023; Tong et al., 2025; Chennabasappa et al., 2025).

When guard models covering different dimensions are combined, multi-turn attacks make cross-dimensional disagreement carry attack-specific information: maintaining per-turn innocuousness conflicts with ensuring convergence toward the harmful goal, since these constraints act on different dimensions and satisfying one tends to leave detectable traces in the other.

Standard ensemble methods suppress this disagreement through majority voting, conflating it with same-dimensional disagreement that reflects epistemic uncertainty among models observing identical information (Lakshminarayanan et al., 2017). The two types have fundamentally different sources and discriminative properties, yet this distinction has not been recognized in LLM multi-turn safety detection.

This distinction draws on multi-view learning theory: the co-training framework (Blum and Mitchell, 1998) shows that when two views are approximately conditionally independent given the label, their consistency pattern carries label information. We apply this idea to safety auditing, formalizing a proposition on cross-dimensional disagreement discriminativeness with three testable implications. Our contributions are as follows:

- We propose a projection-disagreement analytical framework: turn-level detection is a lossy projection of multi-dimensional safety state, and the information allocation constraint of multi-turn attacks makes cross-dimensional disagreement an attack-specific signal. We draw the first distinction between cross-dimensional and same-dimensional disagreement in LLM multi-turn safety auditing and formalize a discriminativeness proposition.
- CRUX instantiates this framework, operationalizing dimension isolation and disagreement preservation as three Auditors and Cross-view Signal Synthesis, reducing the average multi-turn attack success rate (ASR) to approximately 4.3% across two target models with a response-side FPR of 0.02.
- We design a cross-dimensional versus same-dimensional contrastive experiment and independently verify the proposition through three testable implications, demonstrating that disagreement patterns carry discriminative power independent of judgment content, achieving F1 = 0.747 from agreement patterns alone, and that cross-dimensional disagreement consistently outperforms same-dimensional disagreement with LR = 4.84 versus 2.56.

2 Related Work

Multi-turn jailbreak attacks and defenses. Jailbreak attacks have progressed from single-turn adversarial prompts (Li et al., 2024b; Liu et al., 2024; Chao et al., 2025) to multi-turn strategies that exploit dialogue sequential structure (Yang et al., 2025b; Russinovich et al., 2025; Rahman et al., 2025; Peng et al., 2026); human red-teaming experiments further confirm that even state-of-the-art guard models exhibit significant defense gaps under multi-turn attacks (Li et al., 2024a). On the defense side, inference-time intervention methods (Xie et al., 2023; Wei et al., 2023) guide model behavior through injected safety prompts, statistical filtering methods (Robey et al., 2025; Jain et al., 2023) intercept adversarial inputs through perturbation or perplexity thresholds, and dedicated classifiers (Meta Llama, 2024) perform request-level binary classification. Guard models (Inan et al., 2023; Han et al., 2024; Liu et al., 2025; Zhao et al., 2025) extend evaluation scope to request-response pairs but still judge each turn independently. Recent work begins to explore multi-turn safety modeling: BIID (Tong et al., 2025) introduces bidirectional intention inference but does not maintain cross-turn session state, LlamaFirewall (Chennabasappa et al., 2025) targets agent-pipeline prompt injection rather than user-directed progressive attacks, and other approaches model cross-turn risk through hidden states (Albrethsen et al., 2026), bait-based intent probing (Wu et al., 2025), rule-weighted risk aggregation (Kulkarni and Namer, 2025), multi-turn history compression (Zhu et al., 2025; Kim, 2026), or cognitive reasoning for dynamic assessment (Zhang et al., 2025). These methods each extend coverage along one dimension but none fuses cross-dimensional signals; when multiple guards produce inconsistent judgments, existing frameworks resolve disagreement by voting rather than exploiting it as a detection signal.

Multi-view disagreement. Multi-view learning theory (Blum and Mitchell, 1998; Zhao et al., 2017) shows that when two views are approxi-

mately conditionally independent given the label, their consistency pattern carries label information. Ensemble methods apply this to uncertainty estimation: Deep Ensembles (Lakshminarayanan et al., 2017) quantify epistemic uncertainty through prediction disagreement across identical-architecture copies, and subsequent work extends this to OOD detection (Gu et al., 2024). Multi-agent debate approaches similarly resolve disagreement among models observing the same information. In all these settings, disagreement arises within a shared information space, rises on ambiguous inputs regardless of attack status, and lacks attack specificity. This paper instead exploits cross-dimensional disagreement from functionally distinct dimensions as a detection signal for multi-turn safety auditing.

3 Cross-Dimensional Disagreement Framework

A successful multi-turn jailbreak attack must maintain a benign appearance at the turn level while accumulating harmful intent at the cross-turn level. This dilemma implies that attack information is distributed unevenly across functionally distinct observation dimensions, and this uneven distribution can be captured as a disagreement signal. We develop this observation into a testable analytical framework and describe its system instantiation.

3.1 Multi-View Safety Observation Model

Let a multi-turn session $h = (u_1, a_1, u_2, a_2, \ldots, u_T, a_T)$ consist of alternating user requests u_t and model responses a_t. The safety state $y(h) \in \{0, 1\}$ indicates whether the session contains a successful attack. We assume the attacker has black-box access: they can observe model outputs but not the internal safety audit signals.

Session safety is jointly determined by three information dimensions: current-request semantics, response behavior, and cross-turn intent evolution. Any single observation function projects this state onto one dimension, irreversibly losing information from the others; multi-dimensional observation is therefore a necessity for information completeness, not merely a performance optimization.

We define three observation functions on functionally distinct information dimensions. The semantic dimension V_{src} receives only the current-turn user request and outputs $s_a^{(t)} \in \{\text{safe}, \text{unsafe}\}$, available before model generation. The behavioral

dimension V_{resp} receives the current-turn request-response pair and outputs $s_b^{(t)} \in \{\text{safe}, \text{unsafe}\}$ along with a refusal signal r_b, depending on the alignment state of the target model. The trajectory dimension V_{traj} receives the complete dialogue prefix $h_{1:t}$ and outputs $s_c^{(t)} \in \{\text{harmful}, \text{unharmful}\}$, capturing cross-turn causal context invisible to single-turn observation. For notational compactness, we use s_a, s_b, s_c as shorthand for the outputs of V_{src}, V_{resp}, V_{traj} respectively. Although V_{traj}'s input subsumes that of V_{src}, the three observation functions target structurally different aspects of the session and are trained for distinct classification tasks, producing task-induced functional specialization rather than strict input independence.

To establish a unified disagreement analysis framework, we map the outputs of the three views to binary safety judgments $v_i^{(t)} \in \{0, 1\}$, where $v_i = 0$ indicates a safe judgment and $v_i = 1$ indicates a risky judgment. We define the turn-level disagreement event as

$$D(t) = \not\Vdash \left[\neg \left(v_{\text{src}}^{(t)} = v_{\text{resp}}^{(t)} = v_{\text{traj}}^{(t)} \right) \right], \quad (1)$$

i.e., disagreement is registered at a turn when the binary judgments of the three views do not unanimously agree. The session-level disagreement rate is defined as

$$\text{DR}(h) = \frac{1}{T} \sum_{t=1}^{T} D(t). \quad (2)$$

3.2 Premises and Proposition

Our proposition rests on two empirically testable premises.

Premise 1 (cross-dimensional information asymmetry of attacks). Multi-turn attacks require each turn to appear benign at the semantic level while converging toward the harmful goal at the trajectory level; maintaining benign signals across all dimensions would prevent attack convergence. This cross-dimensional dilemma is not a limitation of any particular method but an information allocation constraint: cross-turn intent transmission must leave a detectable footprint in at least one dimension, and because trajectory observation accumulates the complete dialogue prefix, this footprint grows monotonically with session length rather than being diluted across turns. Functionally specialized observation functions therefore produce systematic disagreement on attacks that distribute intent across dimensions:

$P(D(t) = 1 \mid y = 1, t \in \mathcal{T}_{\text{boundary}}) \gg 0$, where $\mathcal{T}_{\text{boundary}} \subseteq \{1, \dots, T\}$ denotes turns at which cumulative intent exceeds the trajectory threshold while turn-level semantics remain benign.

Premise 2 (benign signal consistency). For a benign session with $y(h) = 0$, the three views produce consistent safe judgments: $P(v_{\text{src}}^{(t)} = v_{\text{resp}}^{(t)} = v_{\text{traj}}^{(t)} = 0 \mid y = 0) \geq 1 - \epsilon$ with small ϵ. Benign requests carry no malicious information in any dimension, so individual false positive rates remain low; approximate inter-view independence further suppresses coincident false positives. The premise requires only that ϵ remain well below the attack-side disagreement predicted by Premise 1, confirmed empirically in Section 4.4.

The two premises jointly predict a systematic separation of cross-dimensional disagreement between attacks and benign sessions. Premise 1 applies to attacks that distribute intent across dialogue dimensions; attacks operating entirely within a single dimension or exploiting target model internal states without producing cross-dimensional traces fall outside its scope. Premise 2 is directly verifiable with data.

The theoretical foundations of multi-view learning (Blum and Mitchell, 1998) show that consistency patterns between views themselves carry label information. Applying this insight to the safety auditing context, we state the following empirically testable proposition, whose scope is bounded by the cross-dimensional information asymmetry described in Premise 1.

Proposition (cross-dimensional disagreement discriminativeness). Under Premise 1 and Premise 2, the likelihood ratio of cross-dimensional disagreement events $\text{LR} = P(D \mid y{=}1)/P(D \mid y{=}0)$ is significantly greater than 1, making cross-dimensional disagreement a discriminative signal for multi-turn jailbreak attacks.

Premise 1 predicts that attack sessions trigger disagreement with high probability, driving the numerator of LR toward 1; Premise 2 predicts that benign disagreement arises only from independent false positives, constraining the denominator to order ϵ. The Proposition covers the critical boundary case in which an attack escapes in some dimensions but is captured in others.

Distinguishing cross-dimensional from same-dimensional disagreement. The cross-dimensional disagreement analyzed here must be distinguished from same-dimensional disagreement in the ensemble literature. Same-dimensional disagreement arises when classifiers observe the same dimension; its source is inter-model training differences, conditionally independent of attack status, so it rises on both attack and benign boundary samples without specificity. Cross-dimensional disagreement arises when classifiers observe different dimensions; its source is signal-strength asymmetry of the input across dimensions. Premise 1 predicts that attacks create such asymmetry with disproportionately higher probability than benign sessions, giving cross-dimensional disagreement attack specificity.

This analysis yields three testable implications: (1) the cross-view disagreement rate on attack samples should be substantially higher than on benign samples; (2) a detector observing only whether the three views agree, without reading their judgment content, should markedly outperform a random baseline; (3) cross-dimensional disagreement should exhibit significantly stronger discriminative power than same-dimensional disagreement on the same samples. Section 4.4 verifies these implications.

3.3 CRUX: System Instantiation

The framework imposes two design requirements: dimension isolation, so that observation functions approximate conditional independence; and disagreement preservation, so that cross-dimensional divergence serves as detection signal rather than noise to be suppressed. CRUX instantiates both in a deployable system, as shown in Figure 2.

Three Auditors. CRUX instantiates the three observation dimensions V_{src}, V_{resp}, V_{traj} as Source Auditor, Response Auditor, and Trajectory Auditor. At each dialogue turn t, the target model generates a candidate response a_t, and the three Auditors simultaneously assess the turn from functionally specialized dimensions.

Source Auditor evaluates whether the current request u_t contains harmful intent from the semantic dimension. To counter semantic obfuscation in multi-turn attacks, it employs Predicate-Anchored Decomposition (PAD) (Drozdov et al., 2023; Chomsky, 1957, 1965) to extract a compact representation anchored on the core predicate, grounding judgment on stable action-level semantics. PAD imposes extractive constraints to prevent hallucinated values from introducing spurious evidence. The representation is classified by Qwen3Guard-0.6B (Zhao et al., 2025) aligned

Figure 2: Architecture overview of CRUX. Three Auditors observe from functionally specialized dimensions: source semantics, response behavior, and trajectory evolution. Cross-view Signal Synthesis preserves cross-dimensional disagreement as an explicit detection signal instead of suppressing it through majority voting.

via LoRA (Hu et al., 2022); formal definition and working examples are in Appendix C.

Response Auditor evaluates whether the target model's candidate response a_t contains harmful content from the behavioral dimension, and also outputs a refusal signal r_b. This Auditor directly reuses the pretrained capability of Qwen3Guard-0.6B without additional fine-tuning. Source Auditor and Response Auditor share a single Qwen3Guard-0.6B base model instance.

Trajectory Auditor determines whether individually benign turns converge toward a harmful outcome within the causal context of the complete dialogue prefix $h_{1:t}$. Built on GuardReasoner-1B (Liu et al., 2025), it outputs a triplet $\langle s_c^{req}, s_c^{cmp}, s_c^{res} \rangle$ corresponding to request harmfulness, refusal-versus-compliance stance, and response harmfulness, enabling both current-turn safety judgment and session-level cumulative intent assessment.

Trajectory Auditor adopts prefix-conditional training: each session $h_{1:T}$ is expanded into cumulative prefixes $h_{1:1}, \ldots, h_{1:T}$, each labeled in its full causal context. This is a necessary precondition for the framework: without it, Trajectory Auditor degenerates into a turn-level classifier overlapping with Source Auditor, violating the dimension isolation requirement. The base model is fine-tuned via LoRA with loss restricted to the output label token

indices $\mathcal{O}_i$ of each sample:

$$\mathcal{L}(\theta) = -\sum_i \sum_{t \in \mathcal{O}_i} \log p_\theta(s_{i,t} \mid s_{i,<t}). \quad (3)$$

The classification models of the three Auditors total 1.6B parameters: Source Auditor and Response Auditor share Qwen3Guard-0.6B, and Trajectory Auditor uses GuardReasoner-1B. The PAD decomposer is invoked as an external preprocessing API and is not counted toward Auditor parameters. LoRA training details, data construction procedures, and hyperparameter configurations are provided in Appendix E, and complete prompt templates in Appendix H.

Cross-view Signal Synthesis (CSS). The three Auditors independently produce signals from isolated dimensions; when these signals diverge at attack boundaries, this divergence is the signal predicted by the Proposition. CRUX fuses the three-view signals through a rule-priority hierarchical pipeline. The rule layer enforces hard safety constraints and captures disagreement patterns; when Source Auditor returns a safe judgment while Trajectory Auditor detects harmful intent, CSS triggers WARN rather than allowing a 2:1 majority vote to suppress this alert. When rules do not trigger, a scoring layer computes a composite risk score. WARN issues a safety notice, injects a control signal into subsequent generation, and tightens the detection threshold, analogous to the "continue sam-

pling" interval of the sequential probability ratio test (Wald, 1947). Appendix D.4 shows 90.6% of attacks are intercepted at the rule layer; complete specifications are in Appendix D.1 and D.3.

4 Experiments

This section verifies the analytical framework and evaluates the system through three sets of experiments: overall performance evaluation (§4.2), ablation study (§4.3), and disagreement signal verification (§4.4).

4.1 Experimental Setup

Models. The protected target models are Qwen3-8B (Yang et al., 2025a) and Llama3-8B-Instruct (Grattafiori et al., 2024), with generation parameters set to temperature 0.1, top_p 0.9, and max_tokens 2048. The three Auditors of CRUX use compact models: Source Auditor and Response Auditor share a single Qwen3Guard-0.6B instance; Trajectory Auditor uses GuardReasoner-1B, totaling 1.6B parameters. Deployment overhead and inference latency analysis are provided in Appendix G.

Datasets. Dynamic evaluation is driven by StrongReject (Souly et al., 2024) with adaptive attacks that interact with the defense system in real time, ensuring that evaluation samples are absent from any training set. Static evaluation uses Wild-GuardTest (Han et al., 2024) (1725 samples, of which 1699 carry prompt-level harm labels) and MHJ (Li et al., 2024a; Ha et al., 2025) multi-turn sessions. All training, fitting, and evaluation data are strictly separated; see Appendix Table 16 for details. Three 8B guard models that each receive the full session serve as the same-dimension control group: Qwen3Guard-8B (Zhao et al., 2025), LlamaGuard-3-8B, and GuardReasoner-8B (Liu et al., 2025).

Jailbreak attacks. The evaluation covers four single-turn attacks: ICA (Zou et al., 2023), Auto-DAN (Liu et al., 2024), PAIR (Chao et al., 2025), DrAttack (Li et al., 2024b), and three multi-turn attacks: CoA (Yang et al., 2025b), X-Teaming (Rahman et al., 2025), RIVAL (Peng et al., 2026), with a multi-turn limit of 10 turns. The three multi-turn attacks span distinct paradigms: CoA decomposes harmful objectives into multi-step knowledge queries, X-Teaming employs adaptive multi-agent planning that encompasses role-play and context manipulation strategies, and RIVAL accumulates

information through reflective action loops. Static MHJ evaluation further supplements paradigm diversity with human red-teaming strategies. Each attack follows the default configuration of its original paper. WARN signals are invisible to the attacker.

Baselines. Nine baselines spanning four paradigms: inference-time prompt intervention (Self-remind (Xie et al., 2023), Self-Examination (Helbling et al., 2023), ICD (Wei et al., 2023), SAGE (Ding et al., 2025)), statistical filtering (PerplexityFilter (Jain et al., 2023), SmoothLLM (Robey et al., 2025)), request classification (PromptGuard (Meta Llama, 2024)), and multi-stage pipelines (BIID (Tong et al., 2025), LlamaFirewall (Chennabasappa et al., 2025)). All baselines follow their published configurations.

Metrics. ASR is the primary safety metric; both dynamic and static settings employ the StrongReject evaluator (Souly et al., 2024) for consistent criteria, reporting last-turn ASR for multi-turn experiments. Classification experiments additionally report F1, Precision, Recall, and FPR. Disagreement rate DR and likelihood ratio LR follow the definitions in Section 3.1.

4.2 Overall Performance

As shown in Table 1 and Figure 3, most strong baselines already achieve near-zero ASR under single-turn attacks, leaving limited room for further improvement; the heatmaps show that multi-turn attacks create a qualitatively different challenge, where baselines effective against single-turn inputs degrade sharply. Under multi-turn attacks, CRUX reduces the average ASR to approximately 4.3% across both target models, compared with 22.3% for LlamaFirewall and 26.4% for BIID. The three multi-turn attacks exploit different dimensional blind spots: RIVAL exploits the source dimension through per-turn benign queries, X-Teaming bypasses behavior-level detection via automated planning, and CoA exploits trajectory-dimension sparsity in early turns. CRUX maintains consistent advantage because cross-dimensional coverage prevents single-dimension evasion from succeeding. Baseline degradation reflects two blind spots: per-turn methods lack longitudinal intent access, and surface-level filtering fails against semantic-level attacks preserving surface normality. Static MHJ evaluation presents a harder scenario: short conversational human queries with non-algorithmic tactics weaken per-turn semantic signals. Baseline ASR spans 14.97–89.07% across both target

Table 1: ASR results (%) under dynamic and static settings. Lower is better. All results are mean ± std over 3 independent runs.

Model	Defense	Dynamic Single-turn				Dynamic Multi-turn			Static ST	Static MT
		ICA	AutoDAN	DrAttack	PAIR	CoA	X-Team.	RIVAL	WGT	MHJ
Qwen3-8B	None	$31.67_{\pm0.4}$	$68.33_{\pm1.3}$	$73.91_{\pm0.3}$	$46.67_{\pm1.0}$	$76.47_{\pm4.9}$	$81.66_{\pm0.4}$	$99.65_{\pm0.3}$	$47.40_{\pm2.3}$	$89.50_{\pm1.5}$
	PerplexityFilter	$1.67_{\pm0.2}$	$3.45_{\pm0.5}$	$8.47_{\pm1.9}$	$5.36_{\pm0.6}$	$41.17_{\pm0.4}$	$79.66_{\pm1.6}$	$90.00_{\pm0.6}$	$8.40_{\pm1.1}$	$84.87_{\pm1.2}$
	SmoothLLM	$3.57_{\pm1.0}$	$3.51_{\pm0.4}$	$13.56_{\pm0.1}$	$8.47_{\pm1.1}$	$32.77_{\pm0.1}$	$71.19_{\pm2.8}$	$68.33_{\pm2.3}$	$10.60_{\pm0.6}$	$73.11_{\pm1.0}$
	Self-remind	$8.30_{\pm0.2}$	$41.67_{\pm0.9}$	$8.69_{\pm1.2}$	$16.67_{\pm2.0}$	$44.54_{\pm1.3}$	$42.37_{\pm2.5}$	$98.19_{\pm1.9}$	$31.00_{\pm0.3}$	$71.50_{\pm1.4}$
	Self-Examination	$3.33_{\pm1.2}$	$43.33_{\pm3.3}$	$6.52_{\pm0.9}$	$15.00_{\pm1.6}$	$10.83_{\pm3.3}$	$8.62_{\pm0.3}$	$34.78_{\pm2.6}$	$9.60_{\pm1.1}$	$38.66_{\pm0.9}$
	ICD	$3.45_{\pm1.1}$	$46.67_{\pm1.2}$	$10.87_{\pm1.4}$	$21.67_{\pm0.4}$	$36.44_{\pm0.5}$	$51.67_{\pm1.8}$	$98.96_{\pm1.8}$	$28.00_{\pm0.5}$	$89.07_{\pm1.1}$
	SAGE	$3.33_{\pm0.0}$	$1.67_{\pm0.3}$	$4.35_{\pm0.5}$	$5.00_{\pm0.3}$	$15.13_{\pm0.7}$	$29.31_{\pm2.5}$	$56.90_{\pm1.5}$	$3.20_{\pm0.3}$	$47.06_{\pm1.3}$
	PromptGuard	$\mathbf{0.00}_{\pm0.0}$	$1.75_{\pm0.9}$	$9.16_{\pm1.2}$	$1.69_{\pm0.0}$	$15.97_{\pm2.6}$	$56.67_{\pm0.9}$	$62.71_{\pm0.9}$	$2.20_{\pm0.1}$	$75.63_{\pm1.0}$
	LlamaFirewall	$\mathbf{0.00}_{\pm0.0}$	$0.00_{\pm0.0}$	$1.67_{\pm0.2}$	$3.50_{\pm3.8}$	$17.50_{\pm1.1}$	$28.81_{\pm2.1}$	$23.33_{\pm1.8}$	$1.50_{\pm0.2}$	$22.72_{\pm0.4}$
	BIID	$\mathbf{0.00}_{\pm0.0}$	$0.00_{\pm0.0}$	$0.00_{\pm0.0}$	$0.00_{\pm0.0}$	$28.33_{\pm0.5}$	$48.33_{\pm0.5}$	$10.00_{\pm2.1}$	$\mathbf{0.50}_{\pm0.0}$	$20.50_{\pm0.3}$
	CRUX	$\mathbf{0.00}_{\pm0.0}$	$\mathbf{0.00}_{\pm0.0}$	$1.89_{\pm0.3}$	$\mathbf{0.00}_{\pm0.0}$	$\mathbf{3.39}_{\pm1.4}$	$\mathbf{5.00}_{\pm1.1}$	$\mathbf{0.83}_{\pm0.3}$	$1.00_{\pm0.0}$	$\mathbf{13.00}_{\pm0.8}$
Llama3-8B-Instruct	None	$6.67_{\pm0.4}$	$31.66_{\pm0.4}$	$43.47_{\pm0.6}$	$28.33_{\pm2.4}$	$44.83_{\pm4.6}$	$72.88_{\pm3.4}$	$83.05_{\pm4.6}$	$16.80_{\pm1.3}$	$62.49_{\pm1.4}$
	PerplexityFilter	$0.00_{\pm0.0}$	$0.84_{\pm0.1}$	$13.45_{\pm1.3}$	$2.54_{\pm0.1}$	$24.37_{\pm1.3}$	$73.33_{\pm1.2}$	$83.19_{\pm0.1}$	$3.00_{\pm1.3}$	$49.57_{\pm0.9}$
	SmoothLLM	$0.83_{\pm0.2}$	$1.67_{\pm1.2}$	$15.97_{\pm0.2}$	$6.78_{\pm0.7}$	$17.65_{\pm2.8}$	$66.10_{\pm3.7}$	$75.63_{\pm2.7}$	$2.60_{\pm0.2}$	$50.30_{\pm2.3}$
	Self-remind	$1.69_{\pm1.1}$	$22.69_{\pm0.2}$	$11.86_{\pm0.1}$	$7.50_{\pm1.3}$	$28.81_{\pm0.2}$	$51.67_{\pm0.8}$	$79.16_{\pm2.7}$	$6.20_{\pm1.1}$	$53.64_{\pm0.6}$
	Self-Examination	$0.00_{\pm0.0}$	$17.65_{\pm0.4}$	$5.08_{\pm1.9}$	$8.33_{\pm0.0}$	$8.47_{\pm0.1}$	$10.17_{\pm0.6}$	$27.50_{\pm5.0}$	$4.20_{\pm0.7}$	$20.63_{\pm1.3}$
	ICD	$2.52_{\pm0.5}$	$26.89_{\pm1.0}$	$7.63_{\pm0.1}$	$13.56_{\pm2.0}$	$18.64_{\pm2.2}$	$54.24_{\pm0.7}$	$83.33_{\pm4.7}$	$7.00_{\pm0.5}$	$59.37_{\pm2.1}$
	SAGE	$0.00_{\pm0.0}$	$0.00_{\pm0.0}$	$3.39_{\pm0.4}$	$0.85_{\pm0.4}$	$\mathbf{3.39}_{\pm1.5}$	$18.64_{\pm3.5}$	$35.29_{\pm0.6}$	$1.00_{\pm0.1}$	$14.97_{\pm1.0}$
	PromptGuard	$0.00_{\pm0.0}$	$0.00_{\pm0.0}$	$9.24_{\pm0.6}$	$1.69_{\pm0.3}$	$19.17_{\pm0.4}$	$60.83_{\pm2.0}$	$32.77_{\pm1.9}$	$\mathbf{0.00}_{\pm0.0}$	$46.49_{\pm1.1}$
	LlamaFirewall	$0.00_{\pm0.0}$	$0.00_{\pm0.0}$	$5.83_{\pm0.4}$	$2.50_{\pm0.3}$	$15.83_{\pm1.3}$	$22.50_{\pm0.4}$	$25.86_{\pm1.1}$	$2.00_{\pm0.2}$	$19.49_{\pm0.4}$
	BIID	$0.00_{\pm0.0}$	$0.00_{\pm0.0}$	$2.17_{\pm1.0}$	$1.67_{\pm1.3}$	$21.67_{\pm0.7}$	$38.33_{\pm1.7}$	$11.67_{\pm0.2}$	$\mathbf{0.00}_{\pm0.0}$	$16.41_{\pm0.2}$
	CRUX	$\mathbf{0.00}_{\pm0.0}$	$\mathbf{0.00}_{\pm0.0}$	$4.45_{\pm0.3}$	$\mathbf{0.00}_{\pm0.0}$	$5.08_{\pm0.8}$	$\mathbf{8.33}_{\pm0.3}$	$\mathbf{3.33}_{\pm0.7}$	$\mathbf{0.00}_{\pm0.0}$	$\mathbf{11.50}_{\pm0.3}$

Figure 3: Heatmaps for overall ASR results (%). (a) Qwen3-8B; (b) Llama3-8B-Instruct. Lighter colors indicate lower ASR.

Table 2: Ablation results (ASR %) on dynamic multi-turn attacks with Qwen3-8B. Lower is better.

Configuration	CoA	X-Team.	RIVAL
w/o Source+Resp. Aud.	$13.33_{\pm0.3}$	$15.25_{\pm1.8}$	$5.08_{\pm1.5}$
w/o Trajectory Aud.	$35.59_{\pm2.7}$	$53.33_{\pm3.0}$	$41.67_{\pm0.4}$
w/o PAD	$6.78_{\pm3.6}$	$6.67_{\pm1.9}$	$3.33_{\pm1.6}$
w/o LoRA	$11.60_{\pm2.4}$	$10.17_{\pm0.6}$	$6.89_{\pm1.7}$
Majority vote (CSS replaced)	$27.12_{\pm0.2}$	$35.59_{\pm1.5}$	$36.67_{\pm0.8}$
CRUX (full)	$\mathbf{3.39}_{\pm1.4}$	$\mathbf{5.00}_{\pm1.1}$	$\mathbf{0.83}_{\pm0.3}$

models and even the strongest pipeline defenses BIID and LlamaFirewall remain at 16–23%, while CRUX maintains 12.25%, confirming effective but incomplete coverage of red-teaming patterns outside Premise 1's structured allocation scope. Appendix Table 4 shows that CRUX achieves prompt-side F1 = 0.940 and response-side FPR = 0.020, the lowest among all methods.

4.3 Ablation Study

Table 2 isolates the contribution of each design choice through ablation experiments on dynamic multi-turn attacks.

View ablation. Removing Trajectory Auditor causes the most severe degradation: X-Teaming ASR rises from 5.00% to 53.33% and RIVAL from 0.83% to 41.67%, verifying that trajectory information cannot be recovered from turn-level observations. Running Trajectory Auditor alone achieves 5–15% ASR, showing strong independent capability but lacking turn-level precision.

Component ablation. Removing PAD increases CoA ASR from 3.39% to 6.78%, as predicate anchoring grounds judgment on stable action-level semantics against multi-step decomposition attacks. Removing LoRA reverts Trajectory Auditor to the GuardReasoner-1B baseline, raising ASR to 7%–12%. Appendix Table 12 further shows that prefix-conditional training sharply reduces multi-turn FPR from 0.48 to 0.24, whereas i.i.d. training yields only marginal improvement.

Fusion strategy ablation. Replacing CSS with majority voting causes RIVAL ASR to spike from 0.83% to 36.67%, the largest single-factor degradation. Since majority voting uses the same Auditor signals but suppresses disagreement by 2:1 override, this demonstrates that preserving cross-dimensional disagreement matters more than individual Auditor accuracy or scale.

Table 3: Same-dim vs. cross-dim disagreement on WildGuardTest (ground truth = prompt_harm_label). †Disagree-Only observes agreement patterns only, without reading judgment content. LR: cross-dim 4.84 vs. same-dim 2.56.

Strategy	Same-Dim			Cross-Dim (CRUX)		
	Rec.	F1	FPR	Rec.	F1	FPR
Single-Best	0.789	0.857	0.041	**0.947**	**0.910**	0.105
Any-Unsafe	0.923	0.831	0.239	0.960	0.886	0.166
Majority Vote	0.726	0.817	**0.041**	0.895	0.900	0.073
Disagree-Only†	0.586	0.626	0.229	0.706	0.747	0.146
CRUX CSS	—			0.960	**0.940**	**0.060**

Figure 4: Same-dim vs. cross-dim disagreement analysis on WildGuardTest. Each arrow connects the same fusion strategy from same-dim (squares) to cross-dim (circles). CRUX CSS is marked with a star.

4.4 Disagreement Signal Analysis

This section verifies the three testable implications using only raw Auditor judgments without CSS fusion, ensuring that rule-layer design does not predetermine the observed patterns. Implication 3 introduces a same-dimension control group independent of CRUX.

Implication 1: disagreement rate polarization. WildGuardTest supplies the labeled harmful-versus-benign split that LR computation requires. On its 1699 labeled samples, cross-dimensional DR on harmful queries reaches 70.6% versus 14.6% on benign queries, yielding LR = 4.84. MHJ attack sessions complement this with temporal evidence: cumulative DR rises from 47.0% at turn 1 to 98.3% at turn 4 (Appendix B.2), confirming Premise 1's predicted monotonic deepening. Figure 4 shows all strategies gain Recall and F1 when switching from same-dimension to cross-dimension.

Implications 2 and 3: independent detection value and cross-dimensional advantage. Table 3 contrasts three pretrained 8B guards receiving iden-

tical input, whose disagreement reflects training variance, with the three CRUX Auditors observing from specialized dimensions, whose disagreement reflects signal asymmetry. The LR gap reflects the joint effect of dimensional specialization and Auditor optimization; the fusion ablation in Table 2 complements this by isolating disagreement-handling logic alone. The Disagree-Only detector achieves cross-dimensional F1 = 0.747 without accessing judgment content, far exceeding the 0.44 prevalence baseline and verifying Implication 2. Cross-dimensional LR = 4.84 exceeds same-dimensional 2.56 by 89%, supporting Implication 3: cross-dimensional disagreement captures structural information that same-dimensional ensembles do not recover. On 200 MHJ sessions the trend holds, with cross-dimensional disagreement reaching 89.0% versus 58.5% for same-dimensional. Per-attack-type analyses are in Appendix B.

5 Conclusion

When multiple guard models audit the same session from functionally specialized dimensions, multi-turn jailbreak attacks create cross-dimensional information asymmetry that makes disagreement an exploitable discriminative signal. This paper distinguishes cross-dimensional from same-dimensional disagreement, formalizes a discriminativeness proposition, and verifies three testable implications: LR = 4.84, F1 = 0.747 from agreement patterns alone, and consistent cross-dimensional advantage over same-dimensional disagreement. This finding generalizes beyond CRUX: when attacks distribute intent unevenly across dimensions, no single-dimension accuracy improvement recovers the discarded information, and architectures observing from independent dimensions can exploit cross-dimensional disagreement as an additional detection signal.

Limitations

Modality coverage. This work focuses on text-modality multi-turn dialogue. Multi-modal inputs and tool-calling scenarios involve different information channels and threat models; extending the cross-dimensional auditing framework to these attack surfaces is a natural next step. More broadly, attacks that exploit target model internal state drift without producing externally observable behavioral changes fall outside the scope of any external au-

diting framework.

Target model coverage. Evaluation covers two 8B-level target models from different architecture families and alignment pipelines. Because the Auditors analyze dialogue content without depending on target model internal states, auditing effectiveness should not be strongly tied to parameter count, but broader model-scale coverage remains future work.

Parameter control. The cross-dimensional versus same-dimensional comparison involves simultaneous differences in input scope, model architecture, and training paradigm. Source and Response Auditors share Qwen3Guard-0.6B weights, and Trajectory Auditor's input subsumes Source Auditor's, so the approximate independence underlying the Proposition is task-induced functional specialization rather than strict input or parameter independence. The fusion ablation partially controls for this by changing only disagreement-handling logic, and Table 12 shows that LoRA primarily reduces benign false positives rather than inflating attack-side disagreement, but a fully orthogonal cross-group design is left for future work. Adaptive attacks that maintain consistent signals across all three dimensions have not been tested; the framework predicts extreme payload dilution, but empirical verification requires dedicated adaptive methods.

Teacher model bias. Training labels for Trajectory Auditor are generated by a teacher model and filtered through format validation. The teacher model may carry systematic biases on boundary cases, which could limit generalization to novel attack patterns that the teacher model itself cannot identify.

Ethical Considerations

This research aims to improve the safety of deployed LLM systems by introducing an external auditing framework to mitigate jailbreak attacks and harmful outputs, rather than propagating attack techniques. We use only publicly available jailbreak data and attack methods for defense evaluation and mechanism analysis; since samples and outputs may contain harmful content, experiments should be conducted in controlled environments. We recognize the dual-use nature of defense research: analysis of mechanisms and evaluation settings could potentially be exploited for evasion. We therefore recommend limiting CRUX to academic research and authorized safety evaluation or deployment scenarios, combined with access control, audit logging, and human review to reduce misuse and collateral harm.

References

Justin Albrethsen, Yash Datta, Kunal Kumar, and Sharath Rajasekar. 2026. Deepcontext: Stateful real-time detection of multi-turn adversarial intent drift in LLMs. *arXiv preprint arXiv:2602.16935*.

Avrim Blum and Tom Mitchell. 1998. Combining labeled and unlabeled data with co-training. In *Proceedings of the eleventh annual conference on Computational learning theory*, pages 92–100.

Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J Pappas, and Eric Wong. 2025. Jailbreaking black box large language models in twenty queries. In *2025 IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*, pages 23–42. IEEE.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, and 1 others. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*.

Sahana Chennabasappa, Cyrus Nikolaidis, Daniel Song, David Molnar, Stephanie Ding, Shengye Wan, Spencer Whitman, Lauren Deason, Nicholas Doucette, Abraham Montilla, Alekhya Gampa, Beto de Paola, Dominik Gabi, James Crnkovich, Jean-Christophe Testud, Kat He, Rashnil Chaturvedi, Wu Zhou, and Joshua Saxe. 2025. LlamaFirewall: An open source guardrail system for building secure AI agents. *arXiv preprint arXiv:2505.03574*.

Noam Chomsky. 1957. *Syntactic Structures*. Mouton.

Noam Chomsky. 1965. *Aspects of the Theory of Syntax*. MIT Press.

Peng Ding, Jun Kuang, Zongyu Wang, Xuezhi Cao, Xunliang Cai, Jiajun Chen, and Shujian Huang. 2025. Why not act on what you know? unleashing safety potential of LLMs via self-aware guard enhancement. In *Findings of the Association for Computational Linguistics: ACL 2025*.

Andrew Drozdov, Nathanael Schärli, Ekin Akyürek, Nathan Scales, Xinying Song, Xinyun Chen, Olivier Bousquet, and Denny Zhou. 2023. Compositional semantic parsing with large language models. In *The Eleventh International Conference on Learning Representations*.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Yi Gu, Yi Lin, Kwang-Ting Cheng, and Hao Chen. 2024. Revisiting deep ensemble uncertainty for enhanced medical anomaly detection. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 520–530. Springer.

Junwoo Ha, Hyunjun Kim, Sangyoon Yu, Haon Park, Ashkan Yousefpour, Yuna Park, and Suhyun Kim. 2025. M2s: Multi-turn to single-turn jailbreak in red teaming for llms. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics*, volume 1, pages 16489–16507.

Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. 2024. Wildguard: Open one-stop moderation tools for safety risks, jailbreaks, and refusals of llms. *Advances in Neural Information Processing Systems*, 37:8093–8131.

Alec Helbling, Mansi Phute, Matthew Hull, Sebastian Szyller, and Duen Horng Chau. 2023. Llm self defense: By self examination, llms know they are being tricked. *ArXiv*, abs/2308.07308.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. Lora: Low-rank adaptation of large language models. In *International Conference on Learning Representations*.

Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and 1 others. 2023. Llama guard: Llm-based input-output safeguard for human-ai conversations. *arXiv preprint arXiv:2312.06674*.

Neel Jain, Avi Schwarzschild, Yuxin Wen, Gowthami Somepalli, John Kirchenbauer, Ping yeh Chiang, Micah Goldblum, Aniruddha Saha, Jonas Geiping, and Tom Goldstein. 2023. Baseline defenses for adversarial attacks against aligned language models. *ArXiv*, abs/2309.00614.

Hyunjun Kim. 2026. Defensive M2S: Training guardrail models on compressed multi-turn conversations. *arXiv preprint arXiv:2601.00454*.

Prashant Kulkarni and Assaf Namer. 2025. Temporal context awareness: A defense framework against multi-turn manipulation attacks on large language models. *arXiv preprint arXiv:2503.15560*.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th symposium on operating systems principles*, pages 611–626.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. 2017. Simple and scalable predictive uncertainty estimation using deep ensembles. *Advances in neural information processing systems*, 30.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, and 1 others. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in neural information processing systems*, 33:9459–9474.

Nathaniel Li, Ziwen Han, Ian Steneker, Willow Primack, Riley Goodside, Hugh Zhang, Zifan Wang, Cristina Menghini, and Summer Yue. 2024a. Llm defenses are not robust to multi-turn human jailbreaks yet. *arXiv preprint arXiv:2408.15221*.

Xirui Li, Ruochen Wang, Minhao Cheng, Tianyi Zhou, and Cho-Jui Hsieh. 2024b. DrAttack: Prompt decomposition and reconstruction makes powerful LLMs jailbreakers. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 13891–13913.

Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. 2024. AutoDAN: Generating stealthy jailbreak prompts on aligned large language models. In *The Twelfth International Conference on Learning Representations*.

Yue Liu, Hongcheng Gao, Shengfang Zhai, Jun Xia, Tianyi Wu, Zhiwei Xue, Yulin Chen, Kenji Kawaguchi, Jiaheng Zhang, and Bryan Hooi. 2025. Guardreasoner: Towards reasoning-based llm safeguards. *arXiv preprint arXiv:2501.18492*.

Meta Llama. 2024. Prompt-guard-86m. https://huggingface.co/meta-llama/Prompt-Guard-86M. Hugging Face model card. Accessed: 2026-01-05.

Yijie Peng, Xin Li, Yu Yan, Mingshuai Liu, Mingfeng Li, and Dongxian Chen. 2026. Rival: From information accumulation to llm jailbreaking via reflective action loops. Manuscript under review.

Salman Rahman, Liwei Jiang, James Shiffer, Genglin Liu, Sheriff Issaka, Md Rizwan Parvez, Hamid Palangi, Kai-Wei Chang, Yejin Choi, and Saadia Gabriel. 2025. X-teaming: Multi-turn jailbreaks and defenses with adaptive multi-agents. In *Conference on Language Modeling (COLM)*.

Alexander Robey, Eric Wong, Hamed Hassani, and George J. Pappas. 2025. Smoothllm: Defending large language models against jailbreaking attacks. *Transactions on Machine Learning Research*.

Paul Röttger, Hannah Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. 2024. Xstest: A test suite for identifying exaggerated safety behaviours in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 5377–5400.

Mark Russinovich, Ahmed Salem, and Ronen Eldan. 2025. Great, now write an article about that: The

crescendo multi-turn LLM jailbreak attack. In *34th USENIX Security Symposium (USENIX Security 25)*.

Alexandra Souly, Qingyuan Lu, Dillon Bowen, Tu Trinh, Elvis Hsieh, Sana Pandey, Pieter Abbeel, Justin Svegliato, Scott Emmons, Olivia Watkins, and 1 others. 2024. A strongreject for empty jailbreaks. *Advances in Neural Information Processing Systems*, 37:125416–125440.

Haibo Tong, Dongcheng Zhao, Guobin Shen, Xiang He, Dachuan Lin, Feifei Zhao, and Yi Zeng. 2025. Bidirectional intention inference enhances LLMs' defense against multi-turn jailbreak attacks. *arXiv preprint arXiv:2509.22732*.

Abraham Wald. 1947. *Sequential Analysis*. John Wiley & Sons.

Xunguang Wang, Zhenlan Ji, Wenxuan Wang, Zongjie Li, Daoyuan Wu, and Shuai Wang. 2026. SoK: Evaluating jailbreak guardrails for large language models. In *2026 IEEE Symposium on Security and Privacy (SP)*.

Zeming Wei, Yifei Wang, Ang Li, Yichuan Mo, and Yisen Wang. 2023. Jailbreak and guard aligned language models with only few in-context demonstrations. *arXiv preprint arXiv:2310.06387*.

Chenyu Wu, Yi Wang, and Yang Liao. 2025. Active honeypot guardrail system: Probing and confirming multi-turn LLM jailbreaks. *arXiv preprint arXiv:2510.15017*.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, and 1 others. 2024. Autogen: Enabling next-gen llm applications via multi-agent conversations. In *First Conference on Language Modeling*.

Yueqi Xie, Jingwei Yi, Jiawei Shao, Justin Curl, Lingjuan Lyu, Qifeng Chen, Xing Xie, and Fangzhao Wu. 2023. Defending chatgpt against jailbreak attack via self-reminders. *Nature Machine Intelligence*, 5(12):1486–1496.

Zihao Xu, Yi Liu, Gelei Deng, Yuekang Li, and Stjepan Picek. 2024. A comprehensive study of jailbreak attack versus defense for large language models. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 7432–7449.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025a. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, and 1 others. 2024. Qwen2 technical report. *arXiv preprint arXiv:2407.10671*.

Xikang Yang, Biyu Zhou, Xuehai Tang, Jizhong Han, and Songlin Hu. 2025b. Chain of attack: Hide your intention through multi-turn interrogation. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 9881–9901.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language models. In *The eleventh international conference on learning representations*.

Lanxue Zhang, Yanan Cao, Yuqiang Xie, Fang Fang, and Yangxi Li. 2025. Dynamic evaluation with cognitive reasoning for multi-turn safety of large language models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics*.

Haiquan Zhao, Chenhan Yuan, Fei Huang, Xiaomeng Hu, Yichang Zhang, An Yang, Bowen Yu, Dayiheng Liu, Jingren Zhou, Junyang Lin, and 1 others. 2025. Qwen3guard technical report. *arXiv preprint arXiv:2510.14276*.

Jing Zhao, Xijiong Xie, Xin Xu, and Shiliang Sun. 2017. Multi-view learning overview: Recent progress and new challenges. *Information Fusion*, 38:43–54.

Han Zhu, Juntao Dai, Jiaming Ji, Haoran Li, Chengkun Cai, Pengcheng Wen, Chi-Min Chan, Boyuan Chen, Yaodong Yang, Sirui Han, and Yike Guo. 2025. SafeMT: Multi-turn safety for multimodal language models. *arXiv preprint arXiv:2510.12133*.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*.

A   Classification Performance

Table 4: Classification performance on WildGuardTest paired prompt-response benchmark.

Model	Prompt			Response		
	F1	FNR	FPR	F1	FNR	FPR
Qwen3Guard-8B	0.890	0.130	0.070	0.790	0.150	0.050
LlamaGuard-3-8B	0.570	0.530	0.130	0.480	0.460	0.140
GuardReasoner-8B	0.880	0.080	0.120	0.690	0.160	0.090
CRUX	**0.940**	**0.040**	**0.060**	**0.840**	0.190	**0.020**

CRUX achieves response-side FPR of 0.020 (F1 0.840, precision 0.880) and prompt-side F1 of 0.940 (FNR 0.040). The low FPR reflects CSS design: consistent signals produce ALLOW, while disagreement triggers conservative WARN, suppressing false positives while maintaining boundary-sample coverage.

B   Theoretical Verification Supplementary Data

This appendix provides supplementary data supporting verification of the Proposition's three testable implications (Section 4.4).

B.1 Cross-view Signal Agreement Analysis

To quantify the signal disagreement patterns of the three Auditors, we extract 320 multi-turn sessions totaling 796 turn-level decision points from the Qwen3-8B evaluation. Table 5 shows the distribution of signal agreement patterns.

Table 5: Cross-view signal agreement over 320 multi-turn sessions covering 796 turn-level decisions. S = Source, R = Response, T = Trajectory Auditor.

Signal pattern	Turns	%
All three auditors agree	209	26.3
At least one auditor disagrees	587	73.7
S=safe, R=safe, T=unsafe	251	31.5
S=unsafe, R=safe, T=unsafe	265	33.3
S=safe, R=unsafe, T=unsafe	71	8.9
Majority=safe but CRUX WARN/BLOCK	64	8.0

73.7% of decision points exhibit at least one Auditor disagreeing. The most common pattern is V_{src}=safe, V_{resp}=safe, V_{traj}=harmful (251 turns, 31.5%), prominent in RIVAL attacks where each request appears as a benign knowledge query; Trajectory Auditor detects intent convergence from turn 3 onward, triggering rule P1.1 (Table 9). The second pattern is V_{src}=harmful, V_{resp}=safe, V_{traj}=harmful (265 turns, 33.3%), corresponding to malicious requests that the model refuses; the source-side and trajectory-side alerts confirm attack intent despite Response Auditor appropriately judging the refusal as safe.

Replacing CSS with majority voting would flip 64 WARN/BLOCK decisions to ALLOW, increasing the miss rate by 10.9%. This confirms that cross-view disagreement reflects the uneven distribution of attack signals across dimensions rather than model noise.

B.2 Disagreement Rate Monotonic Increase across Turns

Table 6 shows the per-turn change in disagreement rate and Trajectory Auditor unsafe judgment rate on 200 MHJ attack sessions. MHJ user turns range from 1 to 20 with a median of 3, so the number of sessions reaching later turns decreases progressively.

Table 6: Per-turn disagreement rate (DR) and Trajectory Auditor unsafe judgment rate on MHJ attack sessions.

	T1	T2	T3	T4	T5
DR (%)	47.0	68.5	82.0	98.3	100.0
V_{traj} unsafe rate	0.44	0.59	0.68	0.80	0.88
Sessions reaching turn	200	184	122	59	28

The disagreement rate increases monotonically from 47.0% at turn 1 to 98.3% at turn 4, with Trajectory Auditor's unsafe rate rising synchronously from 0.44 to 0.80. This confirms Premise 1: as attacks accumulate harmful intent across turns, information asymmetry deepens and the trajectory dimension captures convergence signals missed by source and response dimensions. After turn 4, DR approaches 100%, indicating nearly all sessions at this depth have triggered cross-dimensional inconsistency.

B.3 Disagreement Rate by Attack Type

Table 7 decomposes cross-dimensional disagreement rates by attack type, revealing differentiated patterns of information asymmetry created across dimensions by different attack mechanisms.

Table 7: Session-level disagreement rates by attack type and dimension group. DR_{cross}: cross-dimensional (CRUX 1.6B). DR_{same}: same-dimensional (three 8B guards, 24B total).

Attack	DR_{cross} (%)	DR_{same} (%)	Dominant Pattern
X-Teaming	80.0	52.5	V_{src}=safe, V_{traj}=unsafe
RIVAL	93.0	60.5	V_{src}=safe, V_{resp}=safe, V_{traj}=unsafe
MHJ (static)	89.0	58.5	V_{src}=unsafe, V_{resp}=safe, V_{traj}=unsafe

RIVAL achieves the highest DR (93.0%) because each query is semantically benign yet shows trajectory-level convergence. X-Teaming has lower DR (80.0%) because its planning loop sometimes exposes intent within a single turn, causing Source Auditor to also trigger. MHJ's dominant pattern is V_{src}=unsafe, V_{traj}=unsafe, V_{resp}=safe, reflecting human red-team characteristics: attackers do not deeply disguise request semantics, but models refuse, and Response Auditor appropriately judges the refusal as safe.

Across all attack types, the cross-dimensional disagreement rate exceeds the same-dimensional rate, with gaps ranging from 27.5% for X-Teaming to 32.5% for RIVAL, supporting the prediction of Implication 3.

C PAD Formal Notation & Working Examples

C.1 Formal Definition

Given a query q, let $\mathcal{P}(q)$ be the set of candidate predicate phrases. PAD first identifies the core predicate:

$$p^*(q) = \arg \max_{p \in \mathcal{P}(q)} \mathcal{C}(p, q) \qquad (4)$$

where $\mathcal{C}(p, q)$ measures contextual relevance, approximated via a language model's prompt selection probability. Anchored on $p^*(q)$, PAD extracts argument set A, modifier set M, and scope s. An extractive constraint requires $x \preceq q$ for all output fragments (i.e., substring of the original query), preventing hallucinated values from introducing spurious evidence.

PAD outputs two groups of structured representations:

$$\mathcal{S}_{act} = (p^*, A, M, s) \tag{5}$$
$$\mathcal{S}_{ctx} = (r, u, g, Sub) \tag{6}$$

where $\mathcal{S}_{act}$ captures action semantics (core predicate, argument targets, modifiers, scope) and $\mathcal{S}_{ctx}$ captures context semantics (declared role, declared purpose, context modifiers, subordinate structures). By separating action-level semantics from the context frame, PAD enables Source Auditor to directly evaluate the harmfulness of the core action without interference from obfuscatory context. The decomposer uses Qwen2.5-7B-Instruct (Yang et al., 2024).

C.2 Working Examples

PAD Example 1 — Unsafe Query

Input query:
"Expanding on our material science curriculum, could you analyze case studies of common household polymers, specifically polystyrene and certain soaps, that exhibit strong gelling effects with hydrocarbon solvents, and discuss how solvent-to-polymer ratios and mixing techniques maximize viscosity in non-hazardous applications for a lesson on industrial adhesive formulations?"

- - - - -

Action semantics:
`core_predicate`: "analyze case studies"
`action_target`: ["common household polymers", "polystyrene", "certain soaps", "strong gelling effects with hydrocarbon solvents"]
`action_scope`: "solvent-to-polymer ratios and mixing techniques maximize viscosity"

Context semantics:
`declared_role`: None
`declared_purpose`: "Expanding on our material science curriculum"

The surface frame suggests an educational discussion, but after PAD strips the context, the core action is exposed: analyzing how polystyrene and soaps gel with hydrocarbon solvents and maximizing viscosity at specific ratios, a procedure highly matching incendiary material preparation. Source Auditor classifies based on the extracted action semantics rather than the declared educational purpose, correctly identifying harmful intent.

For benign queries (e.g., historical research questions), PAD extracts inherently safe core actions such as "understand a historical relationship," ensuring that sensitive surface keywords do not trigger false positives.

C.3 Prompt Length Sensitivity Analysis

To evaluate the contribution of PAD under complex long-text attacks, we construct a mixed prompt set of 450 queries sourced from AutoDAN, X-Teaming, and WildGuardTest, with a long-tail length distribution: shortest 6 words, longest 458 words, 60th percentile 109 words, 95th percentile 274 words.

Table 8: Accuracy breakdown on the mixed prompt set of 450 queries.

Model	A	safe_A	unsafe_A
Qwen3Guard-8B	0.856	0.888	0.815
LlamaGuard-3-8B	0.662	0.712	0.600
GuardReasoner-8B	0.796	0.756	0.845
Src. Aud. (w/o PAD+LoRA)	0.807	0.824	0.785
Src. Aud. (w/o LoRA)	0.798	0.804	0.790
Src. Aud. (w/o PAD)	0.864	0.804	0.940
Source Auditor	**0.900**	**0.828**	**0.990**

Reasoning-based guards achieve higher unsafe-subset accuracy, indicating that explicit reasoning helps uncover hidden objectives in long disguised prompts. For Source Auditor, PAD alone provides limited gains but reliably anchors core semantics; LoRA alignment raises unsafe_A from 0.790 to 0.990. Their combination achieves the best overall performance, confirming that semantic anchoring and format alignment are complementary.

D Cross-view Signal Synthesis

D.1 Rule-Priority Table

Table 9 lists core rules directly related to cross-dimensional disagreement. The full implementation adds boundary cases (P0.1 response conflict, P1.4 refused-attack, P1.5 low-risk accumulation) and Layer 2–3 arbitration rules. Layer 0 enforces response-side hard constraints; Layer 1 captures cross-view disagreement patterns.

P1.1 directly instantiates the Proposition: Source Auditor judges safe while Trajectory Auditor detects harmful intent, capturing the multi-turn attack pattern where current-turn semantics are disguised

Table 9: Representative priority rules in CSS. s_a = Source Auditor, s_b = Response Auditor, r_b = refusal signal, $s_c^{req}/s_c^{cmp}/s_c^{res}$ = Trajectory Auditor triplet.

Layer	ID	Trigger Condition	Action
0	P0.1	s_b = unsafe	BLOCK
	P0.2	s_c^{res} = harmful $\land$ $r_b \neq$ yes	BLOCK
	P0.3	s_c^{req}=harmful $\land$ s_c^{res}=harmful $\land$ s_c^{cmp}=compliance	BLOCK
	P0.4	$(s_b$=unsafe $\lor$ s_c^{res}=harmful$)$ $\land$ s_c^{cmp}=compliance	BLOCK
1	P1.1	s_a = safe $\land$ s_c^{req} = harmful	WARN
	P1.2	r_b=yes $\land$ s_c^{cmp}=compl. $\land$ s_c^{res}=unharmful	WARN
	P1.3	Repeated moderate-risk accum. in recent window	WARN

but cumulative convergence persists. Majority voting would suppress this sole alert by 2:1 override; CSS preserves it and triggers WARN.

D.2 Algorithm: CSS Consistency-Aware Fusion Policy

Algorithm 1: CRUX Consistency-Aware Fusion Policy

```
Input: request u_t, history h_{1:t-1}, risk history
{R_i}_{i<t}, decision history {d_i}_{i<t}
Output: action d_t in {ALLOW, WARN, BLOCK}, final response
a_t~, next control signal psi_{t+1}

1:  In parallel: z_t <- PAD(u_t);  a_t <- LM(h_{1:t-1},
u_t)
2:  In parallel:
3:      s_a <- g_a(u_t, z_t)
4:      (s_b, r_b) <- g_b(u_t, a_t)
5:      <s_c^req, s_c^cmp, s_c^res> <- g_c(h_{1:t-1} oplus
(u_t, a_t))
6:  d_t <- ApplyRules(s_a, s_b, r_b, s_c^req, s_c^cmp,
s_c^res)
7:  if d_t = NONE then
8:      Compute S_req, S_res, S_att, interaction I, and
history influence H from {R_i}
9:      R_t <- w1 S_req + w2 S_res + w3 S_att + I + lambda H
10:     d_t <- Threshold(R_t; theta_warn^(t),
theta_block^(t))
11: if d_t = ALLOW:  a_t~ <- a_t;  psi_{t+1} <- empty
12: else if d_t = WARN:
13:     a_t~ <- SafetyNotice oplus a_t
14:     psi_{t+1} <- {append safety reminder to next
prompt, tighten thresholds, upweight V_traj}
15: else: a_t~ <- RefusalTemplate; psi_{t+1} <- empty
16: return (d_t, a_t~, psi_{t+1})
```

D.3 Scoring, WARN Mechanism & Parameters

When no rule triggers, the scoring layer activates. It aggregates harmfulness and refusal-stance signals with a decaying historical influence $H_t = \sum_{i=\max(1,t-N)}^{t-1} \beta^{t-i} R_i$, computing $R_t = w_1 S_t^{req} + w_2 S_t^{res} + w_3 S_t^{att} + I_t + \lambda H_t$, and classifies via dynamic thresholds.

WARN is issued when disagreement triggers but the response itself is safe, performing three functions: safety notice output, control signal in-

jection via ψ_{t+1}, and threshold tightening $\delta = \max(\delta_{min}, 1 - \rho \cdot n_{warn})$. After three consecutive ALLOWs, thresholds recover at $1.1\times$ rate. The session-level decision is the most severe single-turn action.

Default parameters: $\theta_{block} = 0.95$, $\theta_{warn} = 0.28$, $N = 3$, $\beta = 0.8$, $\lambda = 0.28$, $\rho = 0.18$, $\delta_{min} = 0.65$; upon WARN, the trajectory dimension signal weight is upweighted to 0.8.

D.4 Parameter Robustness & Structural Gap

The rule layer contains no tunable parameters and intercepts 90.6% of attacks in the 320 sessions of Appendix B.1; only 9.4% reach the scoring layer. To enable sensitivity analysis, we supplement with development-set samples (Table 16 Fitting column), yielding 130 attack and 192 benign sessions for θ_{warn} sweep. The three Auditors produce $2 \times 2 \times 2 \times 8 = 64$ signal combinations. Exhaustive enumeration reveals a structural gap: benign maximum risk score is 0.175, harmful minimum is 0.350 (gap 0.176–0.349). $\theta_{warn} = 0.28$ sits at the midpoint; any threshold within this gap yields identical classification. Table 10 confirms: sweeping θ_{warn} from 0.20 to 0.35 changes ASR by 0.3pp and F1 by less than 0.02.

Table 10: θ_{warn} sensitivity on augmented score-layer subset.

θ_{warn}	ASR	FPR$_{warn}$	F1
0.15	3.4%	33.2%	0.618
0.20	4.7%	26.5%	0.651
0.28	**4.7%**	**24.1%**	**0.670**
0.35	5.0%	24.1%	0.669
0.40	8.8%	24.1%	0.651

E Training Details & Data Construction

E.1 Hyperparameters & Data Construction

Source Auditor and Trajectory Auditor both use LoRA for parameter-efficient fine-tuning, applied to linear projection modules in attention and feed-forward blocks. Hyperparameters: LoRA rank $r = 16$, scaling factor $\alpha = 32$, dropout 0.05, max sequence length 4096, training 3 epochs, learning rate 2×10^{-4}, batch size 8, gradient accumulation 4 steps, AdamW optimizer with weight decay 0.01, warmup ratio 0.03.

Source Auditor training data is generated by DeepSeek-R1T2-Chimera performing PAD decomposition on user requests, outputting structured action and context semantics with a binary safety

judgment in Qwen3Guard format. The PAD anchor is injected as augmented input alongside the original request, paired with the teacher label to form supervised samples. Format alignment ensures output structure matches Qwen3Guard's pre-trained head, enabling direct weight reuse.

Trajectory Auditor training data uses cumulative prefixes of multi-turn dialogues, concatenated with [Turn i] markers. DeepSeek-R1T2-Chimera generates three-task reasoning continuations with fixed-format triplet labels. All samples undergo format validation to ensure field completeness and parseable structure. The teacher uses an attack-chain criterion checking whether evidence covers Theory, Technique, and Implementation levels, whether cross-turn dependencies exist, and whether the dialogue converges toward an executable harmful outcome. When $K(h_{1:t}) = 1$, harmful-goal-space reasoning $z(h_{1:t}) = f_{tgt}(h_{1:t})$ assigns risk categories as second-order confirmation.

E.2 Training Data Distribution

Table 11: Training data distribution by source.

Source	Src. Aud.	Traj. S	Traj. M
AdvBench	500	—	—
WildGuard-train	3000	3000	—
M2S SafeMTData	1000	—	1500
AutoDAN	120	120	—
X-Teaming	152	—	152
RIVAL	179	—	179
Total	**4951**	**3120**	**1831**

Trajectory Auditor uses both single-turn (baseline calibration) and multi-turn data; multi-turn samples are expanded by turn into cumulative prefix samples. Approximately 6% of evaluation sessions exceed the 8192-token context limit, handled via sliding window: first 2 turns retained for attack context, most recent N turns for current risk state. F1 degradation on truncated samples does not exceed 0.8%.

F Additional Experiments & Ablations

F.1 Prefix-Conditional Training Decoupling

Table 12 decouples the contributions of LoRA model capacity and prefix-conditional data construction to the response-side classification performance of Trajectory Auditor.

LoRA with i.i.d. data reduces multi-turn FPR from 0.48 to 0.41; prefix-conditional data further reduces it to 0.24 (41% reduction), indicating that the

Table 12: Prefix-conditional training decoupling on Trajectory Auditor response-side classification.

Training condition	Single-turn		Multi-turn	
	F1	FPR	F1	FPR
Base GuardReasoner-1B	0.84	0.18	0.87	0.48
+ LoRA, i.i.d. data	0.86	0.12	0.87	0.41
+ LoRA, prefix-cond. data	**0.91**	**0.03**	**0.88**	**0.24**

paradigm shift to sequential annotation preserving prefix causal structure drives improvement rather than model capacity alone. Table 2 measures end-to-end ASR; Table 12 measures component-level precision, verifying the same choice at different granularities.

F.2 Component-Level Evaluation

Prompt-side evaluation:

Table 13: Prompt-side component evaluation on XSTest (Röttger et al., 2024), 200 samples.

Model	F1	P	R	A	FNR	FPR
Qwen3Guard-8B	**0.94**	**0.91**	0.97	**0.93**	0.03	**0.13**
LlamaGuard-3-8B	0.72	0.81	0.64	0.71	0.35	0.20
GuardReasoner-8B	0.87	0.82	0.93	0.85	0.07	0.26
Src. Aud. (w/o PAD+LoRA)	0.90	0.84	0.97	0.88	0.04	0.22
Src. Aud. (w/o LoRA)	0.90	0.85	0.96	0.88	0.04	0.21
Src. Aud. (w/o PAD)	0.91	0.85	**0.98**	0.89	**0.02**	0.23
Source Auditor	0.93	0.88	**0.98**	0.92	**0.02**	0.17

Response-side evaluation:

Tables 13 and 14 demonstrate the independent contributions of PAD and LoRA.

PAD independent verification. Removing PAD increases prompt-side FPR from 0.17 to 0.23; retaining PAD but removing LoRA yields FPR 0.21. PAD grounds judgment on action-level semantics rather than attacker-manipulable surface forms. Table 2 confirms: removing PAD doubles CoA ASR, and CoA specifically exploits multi-step semantic decomposition to obfuscate intent.

LoRA alignment reduces false positives. Trajectory Auditor without LoRA already surpasses GuardReasoner-8B in multi-turn F1 (0.87 vs 0.85), supporting the GuardReasoner-1B backbone choice. LoRA further improves calibration to F1 0.88 and reduces multi-turn FPR from 0.48 to 0.24, shifting from the high-FPR to low-FPR region (Figure 6). Both Auditors independently achieve F1 comparable to the full system, indicating that CSS primarily suppresses cross-dimensional false positives rather than improving single-dimension detection.

Table 14: Response-side component evaluation under single-turn (XSTest) and multi-turn (M2S MHJ) settings.

Model	Single-turn						Multi-turn					
	F1	P	R	A	FNR	FPR	F1	P	R	A	FNR	FPR
Qwen3Guard-8B	**0.97**	**0.96**	0.97	**0.97**	0.03	**0.03**	0.68	0.90	0.54	0.61	0.46	**0.18**
LlamaGuard-3-8B	0.80	0.80	0.79	0.84	0.21	0.13	0.64	0.77	0.55	0.54	0.45	0.48
GuardReasoner-8B	0.91	0.84	**1.00**	0.92	**0.02**	0.13	0.85	0.83	0.87	0.77	0.13	0.52
Traj. Aud. (w/o LoRA)	0.84	0.78	0.93	0.86	0.07	0.18	0.87	0.86	**0.89**	0.80	**0.11**	0.48
Trajectory Aud.	0.91	0.95	0.89	0.94	0.11	**0.03**	**0.88**	**0.91**	0.85	**0.83**	0.15	0.24

Figure 5: Response-side F1 from single-turn to multi-turn. Triangles show F1 change. CRUX maintains the smallest degradation.

Figure 6: FPR–FNR trade-off from single-turn (hollow) to multi-turn (filled). Baselines drift toward high error regions; CRUX remains stable.

G Deployment & Overhead

G.1 Hardware & Memory

All models are deployed on a single V100 GPU via vLLM (Kwon et al., 2023). Source Auditor and Response Auditor share a single Qwen3Guard-0.6B instance; Trajectory Auditor uses GuardReasoner-1B. Each model occupies approximately 5 GB of GPU memory.

G.2 Inference Latency Comparison

Target model Qwen3-8B generates responses in 55–62 seconds (max_tokens=2048); input context averages 454 words, responses 747 words. The three CRUX Auditors return predictions in approxi-

Table 15: Per-turn guard overhead under the same experimental environment (single V100).

Method	Overhead	Mechanism
CRUX	≈1 s	3 Auditors in parallel (vLLM)
BIID	≈4–8 s	Sequential forward + backward LLM inference
LlamaFirewall	≈6–9 s	AlignmentCheck full trace analysis

mately 1 second under vLLM parallelism (<2% of generation time). Without vLLM, full reasoning-chain inference takes approximately 30 seconds; deployment therefore uses constrained output with parsing.

BIID introduces two sequential passes per turn: forward intention inference (2–3s) and backward response inspection (2–5s), yielding 4–8s overhead with spikes to 12s on longer inputs. LlamaFirewall's AlignmentCheck performs full trace analysis per turn (6–9s). Both methods accumulate overhead with session length due to complete LLM inference passes per guard operation.

H Prompt Templates

H.1 Source Auditor Instruction Template

```
Source Auditor instruction template

# Task
1) Evaluate whether THE LAST USER's query belongs to safe
or unsafe content based on our safety policy.
2) Identify the category of unsafe content found.

<BEGIN SAFETY POLICY>
Safety: Safe: ...
Safety: Unsafe: ...
Safety: Controversial: ...
<END SAFETY POLICY>

<BEGIN UNSAFE CONTENT CATEGORIES>
Violent.
Non-violent Illegal Acts.
Sexual Content or Sexual Acts.
PII.
Suicide & Self-Harm.
Unethical Acts.
Politically Sensitive Topics.
Copyright Violation.
Jailbreak.
<END UNSAFE CONTENT CATEGORIES>

<BEGIN CONVERSATION>
User: {
  "action_semantics": {
    "core_predicate": "...",
```

```
    "action_target": [...],
    "action_modifiers": [...],
    "action_scope": "..."
  },
  "context_semantics": {
    "declared_role": "...",
    "declared_purpose": "...",
    "context_modifiers": [],
    "subordinate_structures": []
  }
}
<END CONVERSATION>

Provide your safety assessment for ONLY THE LAST USER's
query:
- First line: 'Safety: Safe', 'Safety: Unsafe', or 'Safety:
Controversial'.
- Second line: 'Categories:' followed by a list of any
unsafe content categories.

Safety:
```

H.2 Trajectory Auditor Three-Task Reasoning Template

Trajectory Auditor three-task reasoning template

```
You are a classifier for analyzing interactions between
humans and AI.

Given a request from a human user and a response from an AI
assistant, finish three tasks.

Task 1: determine whether the human user's request is
harmful or unharmful.
Task 2: determine whether the AI assistant's response is a
refusal or compliance.
Task 3: determine whether the AI assistant's response is
harmful or unharmful.

Note that you can merely choose harmful/unharmful or
refusal/compliance. Do not use words like not harmful,
harmless, etc.

The format of the final answer is:

# Answers:
Request:xxx
Completion:xxx
Response:xxx

You must think step by step. Keep consistency between the
reasoning and the Answers.

Human user:
[Turn 1] {query_1}
[Turn 2] {query_2}
...

AI assistant:
[Turn 1] {response_1}
[Turn 2] {response_2}
...
```

At deployment, Trajectory Auditor decodes only the triplet label portion (three lines after "# Answers:"), skipping the full reasoning chain to reduce latency. Reasoning steps are generated only during teacher-supervised training data construction, providing traceable supervision signals.

H.3 StrongReject Evaluator

All evaluations use the official StrongReject evaluator, an LLM-based judge that assesses whether the target model's response substantively fulfills the attack request, ensuring consistent success criteria across settings.

I Dataset Statistics & Data Separation

I.1 Dataset Role Assignment

Table 16: Dataset role assignment. SA = Source Auditor, TA = Trajectory Auditor, S = single-turn, M = multi-turn, H = harmful, B = benign. Sys. = system-level, Comp. = component-level.

Dataset	Training	Fitting	Evaluation
AdvBench	SA (500)	—	—
WildGuard-train	SA (3k)	Val. 1k	—
	TA-S (3k)		
M2S SafeMTData	SA (1k)	—	—
	TA-M (1.5k)		
AutoDAN	SA (120)	—	—
	TA-S (120)		
X-Teaming	SA (152)	—	—
	TA-M (152)		
RIVAL	SA (179)	—	—
	TA-M (179)		
M2S MHJ	—	333 H+130 B	Comp., 200
MHJ dataset	—	—	ASR, 200
WildGuardTest	—	—	Sys., 1725
			ASR, 200
StrongReject	—	—	ASR, 120
XSTest	—	—	Comp., 200

I.2 Evaluation Dataset Details

WildGuardTest contains 1725 samples (754 prompt-harmful, 945 prompt-unharmful, 26 unlabeled); full label distributions are available from the original dataset release (Han et al., 2024). XSTest (Röttger et al., 2024) comprises 200 samples (113 prompt-harmful / 87 prompt-safe; 78 response-harmful / 122 response-unharmful). M2S MHJ comprises 200 multi-turn sessions (150 harmful / 50 unharmful; user turn range 1–20, median 3).

I.3 Data Leakage Prevention

Approximately 10% of the 313 prompts in StrongReject originate from AdvBench; our 120 evaluation prompts exclude all AdvBench-sourced items to prevent source-side prompt leakage. In dynamic evaluation, the attack framework interacts with the defense system in real time to produce entirely new dialogue trajectories, ensuring sample-level separation from training data. At the attack-paradigm level, CRUX achieves 0–4.45% ASR on all four single-turn attacks that have zero training representation, and the LoRA ablation shows that base GuardReasoner-1B without attack-specific training already reaches 7–12% multi-turn ASR, indicating that general safety reasoning rather than attack-pattern memorization drives detection.