Effectively Clarify Confusion via Visualized Aggregation and Separation of Deep Representation

Abstract

Clarifying confusion is the most critical issue for improving classification performance. Confusion occurs with almost all classification models but tends to be ignored in excellent-performing models. The current mainstream research mainly focuses on solving the confusion in a specific case, such as data insufficiency and class imbalance. We believe that effectively clarifying confusion will improve model performance in various special cases. In this paper, we propose a novel, simple and intuitive Aggregation Separation Loss (ASLoss), as an adjunct for classification loss to clarify the confusion in some common cases. The ASLoss aggregates the representations of the same class samples as near as possible and separates the representations of different classes as far as possible. We use two image classification tasks with three simultaneous confounding characteristics i.e. data insufficiency, class imbalance, and unclear class evidence to demonstrate the performance of ASLoss. Extensive comparative experiments and representation visualization are conducted. The experimental results show that representations in deep spaces extracted by ASLoss are sufficiently clear and distinguishable, the confusion among different classes is significantly clarified and the best-performing network using ASLoss reaches the state-of-the-art level.

1 Introduction

Clarifying confusion is the most critical issue for improving classification performance. In fact, all prediction mistakes in classification are confusion, i.e., the model incorrectly considers samples of class "A" as class "B". Confusion occurs with almost all classification models but tends to be ignored in excellent-performing models because the mainstream datasets are artificially constructed to be nearly perfect Torralba et al. (2008); Russakovsky et al. (2015); Lin et al. (2014). However, the sample distribution in practical problems is often not as perfect as artificial datasets. First, collecting enough samples is difficult in some situations, such as the medical field due to privacy invasion Lin et al. (2021). High-performing models are extremely hard to obtain with insufficient data. Second, samples of different categories generally do not follow a uniform distribution but class imbalance Liu et al. (2019); Buda et al. (2018). The vast majority of samples belong to a small number of categories. Samples from unimpressive categories will be confused by the model into fat categories Cui et al. (2019). In addition, the classification boundaries of some problems are not clear Lin et al. (2022). Models will always confuse samples into similar classes. More seriously, many real-world problems simultaneously have more than one case confusing the models. We believe that effectively clarifying the confusion will improve model performance in these common cases.

Many methods have been proposed to clarify confusion, but almost focus on insufficient data or class imbalance. For insufficient data, few-shot learning is a mainstream, including meta-learning and metric-based methods. The meta-learning methods frequently switch among different classification tasks during learning process to obtain the ability of quickly distinguishing by observing only a few data Antoniou et al. (2019); Jamal et al. (2019); Lifchitz et al. (2019); Metz et al. (2019); Rajeswaran et al. (2019). The metric-based methods aim to learn better representations for different classes, then use distance to determine categories Zhang et al. (2020); Li et al. (2019); Sung et al. (2018). These methods have made great progress but the lack of data in few-shot learning is too extreme while its true generalization performance is still unclear. For class imbalance, resampling and reweighting are

two mainstreams. Resampling methods directly repeat the samples of minority classes or remove some samples of majority classes to balance training data Chawla et al. (2002); Wang et al. (2019); Zhou et al. (2020). The re-weighting methods allocate larger weight to the loss of unimpressive classes and less to the fat classes Cao et al. (2019); Cui et al. (2019). All these methods balance input sample frequency or loss of different classes but ignore the characteristic difference among categories.

In view of previous research, we believe that focusing on the class-level representation of samples to mine the commonalities of the same class and the gaps among different classes can clarify the confusion in these common fusion cases. As long as deep learning models can construct **sufficiently clear representations** during extracting features, the confusion under common conditions will be clarified. We think that all linear layers in front of the final classification layer are looking for suitable deep representations when optimizing a deep network. Stacked linear layers continuously map feature representations from one deep space to another. The representations in different spaces move little by little motivated by derivation from classification loss until finding good enough locations that support the final classification. In this process, we propose an assistant to optimize the **representations into distinguishable** in the geometric space of deep features to efficiently clarify the confusion.

Figure 1: Schematic of Aggregation Separation Loss.

In this paper, we propose a novel, simple and intuitive method called Aggregation Separation Loss (ASLoss), as an adjunct for classification loss. This loss can be adopted on any linear feature extraction layers, constructing distinguishable representations in geometric spaces of deep features to clarify the confusion in common cases. The schematic diagram of our ASLoss is shown in Figure 1 and Figure 2. **It aggregates the representations of the same class samples as near as possible and separates the representations of different classes as far as possible. To interpret the effect of our ASLoss, the distinguishable representations can be visualized by condensing the final feature extraction layers into two dimensions.**

Figure 2: Schematic of Using Aggregation Separation Loss.

We validate our method using two image classification tasks that simultaneously have three easily confusion-caused common conditions: data insufficiency, class imbalance, and unclear evidence. The experimental results show that the representations in deep geometric spaces are sufficiently clearer, the performances of various deep networks are efficiently improved and the optimal network achieves state-of-the-art. The code for this work is available on GitHub[1].

2 AGGREGATION SEPARATION LOSS

The proposed ASLoss is a simple and intuitive method as an adjunct for classification loss to clarify confusion. The motivation of ASLoss is to construct sufficiently clear and distinguishable representations in deep spaces. It can be adopted on linear extraction layers as shown in Figure 2.

---

[1]The link will be open if our work can be accepted.

The ASLoss contains three parts: inner aggregation, outer separation and boundary constraint. The inner aggregation narrows deep representations of the same class as near as possible. The outer separation pushes the representations of different classes away as far as possible. However, the farthest distance in a space can be infinite. The optimization of outer separation will not converge. So the boundary constraint limits the representation locations to ensure training convergence.

2.1 INNER AGGREGATION

The inner aggregation narrowing deep representations of the same class as near as possible is computed as:

$$dis_{inner} = \frac{1}{N_{c_i=c_j}} \sum_{i=1}^{N} \sum_{j=i}^{N} \mathbb{I}(c_i = c_j) D(r_i, r_j) \tag{1}$$

where N is the total number of samples, c_i denotes the class of sample i, $N_{c_i=c_j}$ is the total number of $c_i = c_j$ and r_i refers to the representation in a deep geometric space output from a certain linear layer of sample i. $\mathbb{I}(c_i = c_j)$ is an indicator function whose value is 1 when $c_i = c_j$, otherwise the value is 0. $D(r_i, r_j)$ is a distance metric of r_i and r_j such as Euclidean distance etc. dis_{inner} represents the average intra-class distance of all samples. Minimizing dis_{inner} will aggregate the representations of the same class together during optimizing networks.

2.2 OUTER SEPARATION

The outer separation pushing the representations of different classes away as far as possible is calculated as:

$$dis_{outer} = \frac{1}{N_{c_i \neq c_j}} \sum_{i=1}^{N} \sum_{j=i}^{N} \mathbb{I}(c_i \neq c_j) D(r_i, r_j) \tag{2}$$

where N is the total number of samples, c_i denotes the class of sample i, $N_{c_i \neq c_j}$ is the total number of $c_i \neq c_j$ and r_i refers to the representation in a deep geometric space output from a certain linear layer of sample i. $\mathbb{I}(c_i \neq c_j)$ is an indicator function whose value is 1 when $c_i \neq c_j$, otherwise the value is 0. $D(r_i, r_j)$ is a distance metric of r_i and r_j. dis_{outer} represents the average inter-class distance of all samples. Maximizing dis_{outer} will separate the representations of different classes farther during optimizing networks.

2.3 BOUNDARY CONSTRAINT

Because the farthest distance in a space can be infinity, The optimization of equation 2 will not converge. So we use the boundary constraint to limit the representation locations to ensure training convergence as:

$$dis_{boundary} = \frac{1}{N} \sum_{i=1}^{N} ||D(r_i, \mathbf{0}) - constraint||_2 \tag{3}$$

where N is the total number of samples and r_i refers to the representation in a deep geometric space output from a certain linear layer of sample i. $D(r_i, \mathbf{0})$ is a distance metric of r_i and origin of the space. $|| \cdot ||$ is $L2$ norm. $constraint$ is a parameter used to limit the distance of representations to the origin. $dis_{boundary}$ represents the average Euclidean distance of all samples to the boundary. When the number of categories is large, $dis_{boundary}$ can be set larger, so that different categories can find suitable spatial positions. However, if $dis_{boundary}$ is too large, the convergence will be slow. Minimizing $dis_{boundary}$ ensures that the representations will not infinitely far from the origin, then the training process can converge.

2.4 OVERALL OPTIMIZATION

The optimization of ASLoss is calculated as follows:

$$ASLoss = \lambda_{inner} dis_{inner} - \lambda_{outer} dis_{outer} + \lambda_{boundary} dis_{boundary} \tag{4}$$

where λ_{inner}, λ_{outer} and $\lambda_{boundary}$ are three parameters. To ensure overall convergence, $\lambda_{boundary}$ should be slightly larger than λ_{outer}.

Figure 3: The total, trainset and testset sample numbers for each category of the ACNE04 and CelebA subset. (NO: mouth not open, NS: not smile, O: mouth open and S: smile)

The final overall optimization of the whole network is computed as:

$$Loss_{overall} = \lambda_{asl}ASLoss + \lambda_{cls}Loss_{cls} \qquad (5)$$

where λ_{asl} and λ_{cls} are two parameters and $Loss_{cls}$ refers to the classification loss such as cross entropy loss.

3 EXPERIMENT SETTINGS

3.1 TASK DESIGN, DATASETS AND EVALUATION METRICS

Task Design and datasets: We conduct experiments on two classification tasks that are extremely prone to confusion, i.e. *acne severity grading* and *facial expression recognition* to verify the effectiveness of the proposed method. Both tasks simultaneously have three confounding characteristics: data insufficiency, class imbalance, and vague evidence.

Acne Severity Grading: We use the ACNE04 dataset Wu et al. (2019) for acne severity grading. It is an open image dataset for facial acne severity grading. This dataset was collected from outpatients, so its number of class samples can reflect the true distribution of the severity of acne patients. The dataset totally contains 1457 images. According to the annotations of the ACNE04 dataset, there are four levels (four categories): mild, moderate, severe and very severe. For each category, 80% of the samples are randomly divided into the training set and the rest are the test set. The class sample distribution is shown in Figure 3. First, the data is insufficient for deep learning where only 633 samples in the fattest class. Second, the class imbalance is also serious. The sample size of the largest class is almost five times than that of the smallest class. Next, the evidence for dis-

Figure 4: Examples for each category of the ACNE04 and CelebA subset.

tinguishing among the four categories is unclear. The severity depends on the number of very fine-grained lesions on the whole face where 1 to 5 is mild, 6 to 20 is moderate, 21 to 50 is severe, and more than 50 is very severe. For models, inputs are large faces but the classification evidence is the number of extremely small objects which is very difficult to mine. This blurs the lines among the different categories. Some examples can be seen in Figure 4.

Facial Expression Recognition: We use a subset of the CelebA dataset Liu et al. (2015) for this task. CelebA is an open dataset containing 202,599 face images of 10,177 celebrity identities. Its

annotations contain 40 attributes, such as eyebrows, eyes, nose shape, and more. We selected two attributes to form four categories: NO&NS (no mouth open and no smile), NO&S (no mouth open and smile), O&NS (mouth open and no smile), and O&S (mouth open and smile). Then, we randomly selected 1000 samples according to the class distribution of the ACNE04 dataset and divided 80% as the trainset and the rest as the test set as shown in Figure 3. Similarly, this subset is also insufficient, imbalanced and the evidence for distinguishing the four classes is also unclear because differences among categories are not significant. The inputs are similar faces but the identification should be focused only on the mouth.

Evaluation Metrics: We use the accuracy, precision, recall and f1-score commonly used in classification tasks as the evaluation metrics.

3.2 Implementation Details

All models in the experiment use the same implementation settings. For the parameters of the ASLoss, the λ_{inner} and λ_{outer} are both set as 0.001 and the $\lambda_{boundary}$ is set as 0.01. For the parameters of the overall optimization, the λ_{asl} and the λ_{cls} are both set as 0.5. For training different networks, the learning rate is set as 1e-3, the batch size is set as 16 and the maximum training epoch is 400. Adam is chosen as the optimizer employed for training all models. In the whole iteration of training, we choose the model with the best accuracy as the optimal parameter for all models. All programs are coded using Python with PyTorch. All the experiments are conducted on a Linux Ubuntu with 32G RAM and an NVIDIA Geforce RTX 3090 GPU of 24G VRAM.

4 Experiment Results, Analysis and Discussion

4.1 Effective of Aggregation Separation Loss

To verify the effectiveness of ASLoss, we use ASLoss with different distance metrics on several mainstream deep vision networks. The mainstream vision networks include convolution-based VG-GNet Simonyan & Zisserman (2015), ResNet He et al. (2016), EfficientNet Tan & Le (2019) and transformer-based ViT Dosovitskiy et al. (2021), Swin-Transformer Liu et al. (2021), PVT Wang et al. (2021) and T2T-Vit Yuan et al. (2021). For each network, we add linear mapping layers to the output backend of the original network to gradually reduce the number of features into two dimensions and then add a classification layer. The schematic diagram is shown in Figure 2. Next, we use ASLoss of three distance measures, L1 distance, L2 distance and cosine similarity, respectively, on the last two-dimensional feature layer. The comparison results on the two tasks of acne severity grading and facial expression recognition are shown in Table 1.

The performances of all the networks have been improved after using ASLoss, no matter the convolution-based or transformer-based network. For the severity grading task, the ASLoss with L1 distance metric improves the VGG16 network the most. The ASLoss with L2 distance brings the most improvement to the RES50, EFFICIENT_B3, Swin-Transformer and PVT networks. The ASLoss with cosine similarity improves the ViT and T2T-ViT the most significantly. Among all the networks, ASLoss brings the most obvious improvement to ViT with almost all evaluation metrics improved by about 15%. Meanwhile, the best performing model is EFFICIENT_B3 using ASLoss of L2 distance, with all evaluation results over 87%, surpassing the performances of all the other networks. For the facial expression recognition task, the ASLoss with L1 distance improves the VGG16 and EFFICIENT_B3 mostly. The ASLoss with L2 distance improves the Res50, Swin-Transformer and T2T-ViT most significantly. The ASLoss with cosine similarity brings the most obvious improvement to ViT and PVT. Among them, ASLoss brings the most obvious improvement to ViT, some evaluation metrics are even improved by about 20%. The best performing model is RES50 using ASLoss with L2 distance, with all evaluation results around 83%, surpassing most of the other network performances. Overall, ASLoss with L2 distance brings significant improvements on most networks.

First, the performance of these networks on the acne severity grading is slightly better than that on the facial expression recognition. On the one hand, the data volume for the acne severity grading is slightly larger than that of the facial expression recognition. On the other hand, mouth opening and smiling are more easily confused, compared to the number of small lesions. So the networks are more easily to obtain effective generalization on the acne severity grading task. Next, the

Table 1: Comparison results of mainstream deep vision methods not using and using ASLoss of different distance metrics on acne severity grading (left) and facial expression recognition (right). ACC: Accuracy, PRE: Precision, REC: Recall and F1: F1-score. L1: L1 distance, L2: L2 distance and COS: Cosine Similarity. ASL: ASLoss.

Tasks	Acne Severity Grading				Facial Expression Recognition			
Methods	ACC↑	PRE↑	REC↑	F1↑	ACC↑	PRE↑	REC↑	F1↑
VGG16	85.62	85.98	84.00	84.69	80.81	79.64	80.10	79.86
VGG16+ASL(L1)	85.96	**86.73**	**85.27**	**85.59**	**82.83**	**82.59**	**82.97**	**82.46**
VGG16+ASL(L2)	**86.64**	86.56	84.49	85.04	82.83	80.03	79.66	79.65
VGG16+ASL(COS)	85.96	84.54	82.71	83.30	82.83	81.82	79.29	80.05
RES50	83.22	82.88	81.26	81.76	82.32	78.80	78.44	78.55
RES50+ASL(L1)	84.25	84.98	81.19	82.86	83.84	82.85	**85.38**	**83.93**
RES50+ASL(L2)	**86.64**	**86.56**	**84.49**	**85.04**	**85.35**	**85.00**	82.40	83.59
RES50+ASL(COS)	83.90	83.56	82.64	82.27	83.84	81.33	81.16	81.05
EFFICIENT_B3	82.53	83.60	80.74	81.80	79.80	78.81	78.74	78.77
EFFICIENT_B3+ASL(L1)	86.30	86.19	83.90	84.88	**83.84**	**83.50**	**84.13**	**83.73**
EFFICIENT_B3+ASL(L2)	**87.33**	**89.17**	**88.46**	**88.78**	83.33	82.78	83.78	83.10
EFFICIENT_B3+ASL(COS)	85.62	86.40	85.08	85.44	83.33	80.88	81.81	81.30
ViT	65.75	66.93	64.94	65.44	66.67	57.30	47.30	47.57
ViT+ASL(L1)	**82.88**	83.04	81.19	81.09	82.32	**81.59**	80.32	80.90
ViT+ASL(L2)	82.53	82.63	79.42	80.12	**83.84**	81.37	79.51	80.31
ViT+ASL(COS)	82.53	**83.75**	**82.99**	**83.29**	81.82	81.17	**82.74**	**81.01**
Swin-Transformer	84.93	85.20	82.61	83.04	77.78	76.54	74.77	74.95
Swin-Transformer+ASL(L1)	85.96	**85.92**	82.84	83.83	80.30	75.95	79.43	77.20
Swin-Transformer+ASL(L2)	**86.99**	85.08	**85.06**	**84.90**	**84.34**	**81.49**	**82.25**	**81.57**
Swin-Transformer+ASL(COS)	83.22	82.81	78.11	80.14	81.31	80.62	76.10	78.08
PVT	80.48	80.71	78.83	79.71	75.25	72.20	68.80	70.10
PVT+ASL(L1)	83.90	82.04	81.34	81.46	76.26	78.67	70.57	73.65
PVT+ASL(L2)	**83.90**	**82.35**	**81.34**	**81.66**	77.78	79.06	**73.73**	**75.99**
PVT+ASL(COS)	83.56	82.38	79.84	80.80	**79.29**	**79.39**	71.63	74.48
T2T-ViT	82.53	82.14	79.64	79.75	79.80	78.97	76.10	76.83
T2T-ViT+ASL(L1)	83.22	81.67	82.26	81.83	78.79	81.10	**76.74**	78.68
T2T-ViT+ASL(L2)	83.90	**84.74**	83.19	83.67	**81.82**	**85.25**	76.62	**79.86**
T2T-ViT+ASL(COS)	**84.25**	83.42	**84.79**	**84.08**	80.30	79.13	76.32	77.25

transformer-based ViT-series networks do not perform significantly better than convolution-based networks. We believe that it is difficult for the ViT series of methods to converge at a good enough performance when the data is not sufficient for both tasks. In addition, the distance metrics that improve significantly on most networks are the L1 and L2 distances, although the ASLoss of all three distance metrics can improve the performance of different networks. In fact, when using L1 and L2 distances, ASLoss aggregates and diverges the representation locations of different classes in a deep space. While using cosine similarity, it gathers and diverges the angles of representation vectors. We believe that angular differences are still difficult to distinguish near the origin, compared to their positional differences in space. Therefore, ASLoss using L1 and L2 distance metrics performs slightly better than cosine similarity.

Such experimental results show that ASLoss can improve the performance of various mainstream visual networks, including convolution-based networks and transformer-based series. And the two best performing models, EFFICIENTNET_B3 and Res50, using the ASLoss of the L2 distance metric on the two tasks are selected to conduct the following experiments.

4.2 AGGREGATION SEPARATION LOSS ON MULTIPLE SPACES

As mentioned above, the proposed ASLoss method can be used on arbitrary linear feature extraction layers. Therefore, we apply ASLoss to the last layer, the last two layers, the last three layers and the last four layers before the output layer, respectively, and compare their performances for both the

Table 2: Comparison results of using ASLoss on multiple linear layers in front of the classification layer on acne severity grading (left) and facial expression recognition (right). ACC: Accuracy, PRE: Precision, REC: Recall and F1: F1-score. L2: L2 distance. ASL: ASLoss.

| Tasks | Acne Severity Grading | | | | Facial Expression Recognition | | | |
| Base Models | EFFICIENT_B3 + ASL(L2) | | | | Res50 + ASL(L2) | | | |
Layers	ACC↑	PRE↑	REC↑	F1↑	ACC↑	PRE↑	REC↑	F1↑
Base model	82.53	83.60	80.74	81.80	82.32	78.80	78.44	78.55
ASLoss on the last one layer	**87.33**	**89.17**	**88.46**	**88.78**	85.35	**85.00**	**82.40**	**83.59**
ASLoss on the last two layers	85.96	85.57	86.37	85.95	84.34	81.78	81.71	81.46
ASLoss on the last three layers	85.27	85.74	85.74	85.54	**86.36**	84.32	81.05	82.41
ASLoss on the last four layers	85.62	86.01	84.86	85.39	84.34	81.78	80.20	80.88

acne severity grading task and facial expression recognition task. The schematic is shown in Figure 2. Since the best performing models on acne severity grading and facial expression recognition tasks are EFFICIENT_B3 and Res50 optimized by ASLoss of L2 distance metric, we continue to use these two networks as base models. The comparison results are displayed in Table 2. The first row in the table shows the results of the base model without ASLoss. Rows two to five show the experimental results of gradually increasing the number of representation spaces using ASLoss.

From the experimental results, the performance of the base model can be improved by using ASLoss on representations of all four multi-spatial strategies. For the acne severity grading task, the employment of ASLoss on four multi-space representations improves the accuracy of the base model by about 3%, the precision by about 2%, the recall by more than 4%, and the f1-score by more than 4%. Among them, the model optimized by ASLoss only on the one previous layer of the output layer achieves the best performance. Compared with the base model, the accuracy is increased by nearly 5%, the precision is increased by more than 5%, the recall rate is increased by nearly 8%, and the f1-score is increased by nearly 7%. For the facial expression recognition task, the results are similar to the acne severity grading. The employment of ASLoss on four multi-space representations improves the accuracy of the base model by over 3%, the precision by about 3%, the recall by around 3%, and the f1-score by about 4%. Among them, the model optimized by ASLoss only on the one previous layer of the output layer achieves the best performance. Compared with the base model, the accuracy is increased by over 3%, the precision is increased by more than 6%, the recall rate is increased by nearly 4%, and the f1-score is increased by over 5%.

For the performance on the two tasks, increasing the feature space employed by the ASLoss does not gradually improve the model performance. We believe that excellent performance is based on extracting enough representations. Premature aggregation and separation of feature representations may lead to insufficient feature extraction. At the same time, too many layers to perform feature aggregation and separation at the same time may lead to contradictions in gradient update, resulting in inconsistent update directions of network weights. Weight changes in the previous layers will cause the subsequent layers to change. Convergence will become difficult. Therefore, only the aggregation and separation of representations in the one layer before the classification layer achieves the best results.

4.3 Representation Visualization

To explain the plausibility of ASLoss, we visualize the representations extracted by the ASLoss method. We connect the representation extraction layer after the original network output and set the feature extraction layer finally to be two-dimensional. The two-dimensional output representations are visualized and compared as shown in Figure 5. The left and right halves are for the acne severity grading and the facial expression recognition tasks. The EFFICIENT_B3 and Res50 are selected for the two tasks to conduct this experiment due to their excellent performances. For each task, the left and right two subfigures are the representations extracted without and with ASLoss of L2 distance metric. The upper and lower subfigures are representations for train data and test data.

For the acne severity grading task, the training sample representations extracted by the model without ASLoss have no obvious boundary and the distribution is scattered. For the training repre-

Figure 5: Visualization of representations. The left and right halves are for the acne severity grading (EF-FICIENT_B3 with ASLoss of L2 distance) and the facial expression recognition (Res50 with ASLoss of L2 distance). For each task, the left and right two subfigures are the representations extracted without and with ASLoss. The upper and lower subfigures are representations of train data and test data.

sentations using ASLoss, the representations of the same category are more concentrated, and the samples of different categories can be clearly separated. For test data, the representation overlap is serious when not using ASLoss. After using ASLoss, the overlap of representations in space is alleviated. For the facial expression recognition task, three categories concentrated in the coordinate origin and coordinate axes in the training samples without ASLoss, leading to heavy overlap. After using ASLoss, the representations of different classes are spread out. For the test data representations, heavy overlap happens without ASLoss. After using ASLoss, the overlap is alleviated. All representations using ASLoss are constrained to the ideal range without disorderly dilation.

This result shows that ASLoss can effectively aggregate in-class samples to separate out-of-class samples. For the test samples of the two tasks, the effect of widening the distance of different classes is significant. This increases the distinguishability of these samples that are located among different class distributions. So the confusion among different classes can be clarified.

4.4 COMPARISON OF CONFUSION

The confusion matrixes for the two tasks are shown in Figure 6. The left and right halves are for the acne severity grading and the facial expression recognition tasks. The EFFICIENT_B3 and Res50 are also selected as the comparison models for the two tasks respectively. For each task, the left and right two confusion matrixes are from the models without and with ASLoss of L2 distance. The upper and lower confusion matrixes are for train and test data.

For both tasks, the use of ASLoss can improve performance of the models on not only the training data but also the test data. On the training data, both base models perform a little confusion on different categories. With the help of ASLoss, the confusion on the training dataset almost completely disappeared. On the test data, the predictions of the models without ASLoss perform confusion seriously. After using ASLoss on the models, the performance of the two classes 2 and 3 with insufficient data is improved sufficiently, while the performance of the two classes 0 and 1 with more samples decreases slightly. The overall accuracy is significantly improved.

This result demonstrates that the ASLoss effectively clarifies the confusion. Such results can be explained from visualization. The representation distances of the categories are pulled apart. The distribution of the same class is concentrated. So the confusion can be clarified.

4.5 COMPARISON WITH STATE-OF-THE-ARTS

To demonstrate the effectiveness, we compare the proposed ASLoss with some state-of-the-art methods including Focal Loss Lin et al. (2020), Weighted Cross Entropy Wang et al. (2017), CBLoss Cui

Figure 6: Comparison of confusion matrixes. The left and right halves are for the acne severity grading (EFFICIENT_B3 with ASLoss of L2 distance) and the facial expression recognition (Res50 with ASLoss of L2 distance). For each task, the left and right two confusion matrixes are from the models without and with ASLoss. The upper and lower confusion matrixes are for train data and test data.

Table 3: Comparative experimental results with state-of-the-art methods on acne severity grading (left) and facial expression recognition (right). ACC: Accuracy, PRE: Precision, REC: Recall and F1: F1-score.

Tasks	Acne Severity Grading				Facial Expression Recognition			
Methods	ACC↑	PRE↑	REC↑	F1↑	ACC↑	PRE↑	REC↑	F1↑
BaseModel + Focal Loss	82.19	81.75	79.26	79.25	84.85	83.32	**82.62**	82.94
BaseModel + Weighted CE	83.90	83.87	81.70	82.38	83.84	81.38	82.31	81.69
BaseModel + CBLoss	82.88	81.94	79.32	80.46	82.83	80.57	79.77	80.13
BaseModel + TDE	85.27	85.32	83.22	83.78	84.85	82.91	81.74	82.15
BaseModel + ASLoss(ours)	**87.33**	**89.17**	**88.46**	**88.78**	**85.35**	**85.00**	82.40	**83.59**

et al. (2019) and TDE Tang et al. (2020) as shown in Table 3. The left and right halves are for the acne severity level and facial expression recognition tasks.

From the experiment results, the proposed ASLoss outperforms other methods on all metrics for the acne severity grading task. For the facial expression recognition, the overall performance of ASLoss outperforms all other methods, although the recall of Focal Loss is slightly higher than the ASLoss. The experimental results show that the performance of ASLoss reaches the state-of-the-art level.

5 CONCLUSION

In this paper, we propose a novel, simple and intuitive ASLoss, as an adjunct for classification loss to clarify the confusion in some common cases. The ASLoss aggregates the representations of the same class samples as near as possible and separates the representations of different classes as far as possible. It is adopted on linear feature extraction layers to construct distinguishable representations in geometric spaces of deep features. We use two classification tasks with three simultaneous common confounding characteristics i.e. data insufficiency, class imbalance, and unclear class evidence to demonstrate the performance of ASLoss. We conduct representation visualization, confusion comparison, and detailed comparison experiments. The experimental results show that the model using ASLoss can extract sufficiently clear and distinguishable representations in deep spaces, the confusion among different classes is significantly clarified and the best-performing network reaches the state-of-the-art level.

REFERENCES

Antreas Antoniou, Harrison Edwards, and Amos J. Storkey. How to train your maml. *In ICLR*, 2019.

Mateusz Buda, Atsuto Maki, and Maciej A. Mazurowski. A systematic study of the class imbalance problem in convolutional neural networks. *Neural networks : the official journal of the International Neural Network Society*, 106:249–259, 2018.

Kaidi Cao, Colin Wei, Adrien Gaidon, Nikos Aréchiga, and Tengyu Ma. Learning imbalanced datasets with label-distribution-aware margin loss. In *NeurIPS*, 2019.

N. Chawla, K. Bowyer, Lawrence O. Hall, and W. Philip Kegelmeyer. Smote: Synthetic minority over-sampling technique. *J. Artif. Intell. Res.*, 16:321–357, 2002.

Yin Cui, Menglin Jia, Tsung-Yi Lin, Yang Song, and Serge J. Belongie. Class-balanced loss based on effective number of samples. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9260–9269, 2019.

A. Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, M. Dehghani, Matthias Minderer, G. Heigold, S. Gelly, Jakob Uszkoreit, and N. Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *ArXiv*, abs/2010.11929, 2021.

Kaiming He, X. Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016.

Muhammad Abdullah Jamal, Guo-Jun Qi, and Mubarak Shah. Task agnostic meta-learning for few-shot learning. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 11711–11719, 2019.

Wenbin Li, Lei Wang, J. Xu, Jing Huo, Yang Gao, and Jiebo Luo. Revisiting local descriptor based image-to-class measure for few-shot learning. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 7253–7260, 2019.

Yann Lifchitz, Yannis Avrithis, Sylvaine Picard, and Andrei Bursuc. Dense classification and implanting for few-shot learning. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9250–9259, 2019.

Tsung-Yi Lin, Michael Maire, Serge J. Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. Microsoft coco: Common objects in context. In *ECCV*, 2014.

Tsung-Yi Lin, Priya Goyal, Ross B. Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 42:318–327, 2020.

Yi Lin, Yi Guan, Zhaoyang Ma, Haiyan You, Xue Cheng, and Jingchi Jiang. An acne grading framework on face images via skin attention and sfnet. *2021 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*, pp. 2407–2414, 2021.

Yi Lin, Jingchi Jiang, Zhaoyang Ma, Dongxin Chen, Yi Guan, Haiyan You, Xue Cheng, Bingmei Liu, and Gongning Luo. Kieglfn: A unified acne grading framework on face images. *Computer methods and programs in biomedicine*, 221:106911, 2022.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and B. Guo. Swin transformer: Hierarchical vision transformer using shifted windows. *ArXiv*, abs/2103.14030, 2021.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

Ziwei Liu, Zhongqi Miao, Xiaohang Zhan, Jiayun Wang, Boqing Gong, and Stella X. Yu. Large-scale long-tailed recognition in an open world. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 2532–2541, 2019.

Luke Metz, Niru Maheswaranathan, Brian Cheung, and Jascha Narain Sohl-Dickstein. Meta-learning update rules for unsupervised representation learning. *In ICLR*, 2019.

Aravind Rajeswaran, Chelsea Finn, Sham M. Kakade, and Sergey Levine. Meta-learning with implicit gradients. In *NeurIPS*, 2019.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael S. Bernstein, Alexander C. Berg, and Li Fei-Fei. Imagenet large scale visual recognition challenge. *International Journal of Computer Vision*, 115:211–252, 2015.

K. Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *CoRR*, abs/1409.1556, 2015.

Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip H. S. Torr, and Timothy M. Hospedales. Learning to compare: Relation network for few-shot learning. *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1199–1208, 2018.

Mingxing Tan and Quoc V. Le. Efficientnet: Rethinking model scaling for convolutional neural networks. *ArXiv*, abs/1905.11946, 2019.

Kaihua Tang, Jianqiang Huang, and Hanwang Zhang. Long-tailed classification by keeping the good and removing the bad momentum causal effect. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Antonio Torralba, Rob Fergus, and William T. Freeman. 80 million tiny images: A large data set for nonparametric object and scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 30:1958–1970, 2008.

Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pyramid vision transformer: A versatile backbone for dense prediction without convolutions. *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 548–558, 2021.

Yiru Wang, Weihao Gan, Wei Wu, and Junjie Yan. Dynamic curriculum learning for imbalanced data classification. *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 5016–5025, 2019.

Yu-Xiong Wang, Deva Ramanan, and Martial Hebert. Learning to model the tail. In *NIPS*, 2017.

Xiaoping Wu, Wen Ni, Liang Jie, Yu-Kun Lai, She Cheng, Dongyu, Ming-Ming, and Jufeng Yang. Joint acne image grading and counting via label distribution learning. In *IEEE International Conference on Computer Vision(ICCV)*, 2019.

Li Yuan, Yunpeng Chen, Tao Wang, Weihao Yu, Yujun Shi, Francis E. H. Tay, Jiashi Feng, and Shuicheng Yan. Tokens-to-token vit: Training vision transformers from scratch on imagenet. *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 538–547, 2021.

Chi Zhang, Yujun Cai, Guosheng Lin, and Chunhua Shen. Deepemd: Few-shot image classification with differentiable earth mover's distance and structured classifiers. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 12200–12210, 2020.

Boyan Zhou, Quan Cui, Xiu-Shen Wei, and Zhao-Min Chen. Bbn: Bilateral-branch network with cumulative learning for long-tailed visual recognition. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9716–9725, 2020.